



TESTING LABORATORY
CERTIFICATE #4820.01



FCC PART 15.247

TEST REPORT

For

Yibai Science & Technology (Shenzhen) Co., Ltd.

No. 1112, Building 5A, Tusincere Technology Park. Huanggkeng Community Longcheng
Street, Longgang, Shenzhen, China

FCC ID: 2AVYG-ZIP20


Report Type: Original Report	Product Name: True Wireless Earphone
Report Number: <u>RDG201014153-00B</u>	
Report Date: <u>2020-11-13</u>	
Reviewed By: Ivan Cao Assistant Manager	
Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn	

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
DECLARATIONS.....	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	6
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS.....	7
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE.....	8
APPLICABLE STANDARD	8
FCC §15.203 - ANTENNA REQUIREMENT.....	9
APPLICABLE STANDARD	9
ANTENNA CONNECTOR CONSTRUCTION	9
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	10
APPLICABLE STANDARD	10
EUT SETUP	10
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	11
TEST PROCEDURE	11
TEST EQUIPMENT LIST AND DETAILS.....	11
CORRECTED AMPLITUDE & MARGIN CALCULATION	12
TEST DATA	12
FCC §15.247(a) (1) - CHANNEL SEPARATION TEST	18
APPLICABLE STANDARD	18
TEST EQUIPMENT LIST AND DETAILS.....	18
TEST PROCEDURE	18
TEST DATA	18
FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING.....	24
APPLICABLE STANDARD	24
TEST PROCEDURE	24
TEST EQUIPMENT LIST AND DETAILS.....	24
TEST DATA	24
FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST.....	30
APPLICABLE STANDARD	30
TEST PROCEDURE	30
TEST EQUIPMENT LIST AND DETAILS.....	30
TEST DATA	30
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	33

APPLICABLE STANDARD	33
TEST PROCEDURE	33
TEST EQUIPMENT LIST AND DETAILS.....	33
TEST DATA	33
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	39
APPLICABLE STANDARD	39
TEST PROCEDURE	39
TEST EQUIPMENT LIST AND DETAILS.....	39
TEST DATA	39
FCC §15.247(d) - BAND EDGES TESTING	41
APPLICABLE STANDARD	41
TEST PROCEDURE	41
TEST EQUIPMENT LIST AND DETAILS.....	41
TEST DATA	42

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

EUT Name:	True Wireless Earphone
EUT Model:	ZIP 20
Multiple Models:	ZIP06, ZIP08, ZIP10, ZIP18, ZIP26, ZIP28
Operation Frequency:	2402-2480MHz
Maximum Peak Output Power (Conducted):	4.63 dBm
Modulation Type:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Antenna GainΔ:	-0.3 dBi
Rated Input Voltage:	DC 3.6V from Battery
Serial Number:	RDG201012153-RF-S2
EUT Received Date:	2020.10.15
EUT Received Status:	Good

Note: The series product, models ZIP 20, ZIP06, ZIP08, ZIP10, ZIP18, ZIP26, ZIP28 are electrically identical, the model ZIP 20 was fully tested. The difference between them please refer to the declaration letter for details.

Objective

This report is prepared on behalf of **Yibai Science & Technology (Shenzhen) Co., Ltd.** in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Rules Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15C DTS submissions with FCC ID: 2AVYG-ZIP20.

Test Methodology

All measurements detailed in this Test Report were performed in accordance with ANSI C63.10-2013 "American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices".

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.55 dB, 200M~1GHz: 5.92 dB, 1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1°C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “ Δ ”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in engineering mode, which was provided by manufacturer.

EUT Exercise Software


The 'Blue Test 3' was used during test, which was provided by manufacturer. The maximum power level was configured by the software as below table△:

Mode	Channel	Frequency (MHz)	Power Level Setting
GFSK	Low	2402	50
	Middle	2441	50
	High	2480	50
$\pi/4$ -DQPSK	Low	2402	50
	Middle	2441	50
	High	2480	50
8DPSK	Low	2402	50
	Middle	2441	50
	High	2480	50

Equipment Modifications

No modification was made to the EUT.

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC§15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
FCC §15.203	Antenna requirement	Compliance
FCC §15.207(a)	AC line conducted emissions	Not Applicable
FCC §15.205, §15.209, §15.247(d)	Spurious emissions	Compliance
FCC §15.247(a)(1)	Channel separation	Compliance
FCC §15.247(a)(1)	20 dB bandwidth	Compliance
FCC §15.247(a)(1)(iii)	Quantity of hopping channel test	Compliance
FCC §15.247(a)(1)(iii)	Time of occupancy (dwell time)	Compliance
FCC §15.247(b)(1)	Peak output power measurement	Compliance
FCC §15.247(d)	Band edges	Compliance

Not Applicable: the device was powered by battery when operating.

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

The max conducted power including tune-up tolerance is 5.0 dBm (3.16 mW).

$[(\text{max. power of channel, mW}) / (\text{min. test separation distance, mm})] [\sqrt{f(\text{GHz})}] = 3.16 / 5 * (\sqrt{2.480}) = 1.0 < 3.0$

So the stand-alone SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna arrangement, fulfill the requirement of this section. Please refer to below information and the EUT photos:

Antenna Type	input impedance (Ohm)	Antenna Gain /Frequency Range
Chip	50	-0.3 dBi/2.4~2.5GHz

Result: Compliance.


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission below 1GHz tests were performed in the 10 meters chamber, above 1GHz tests were performed in the 3 meters chamber A, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

According to FCC public notice: DA-00-705, during the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	AV

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and average detection modes for frequencies above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiation Below 1GHz					
Sunol Sciences	Antenna	JB3	A060611-2	2020-08-25	2023-08-25
R&S	EMI Test Receiver	ESCI	100224	2020-09-12	2021-09-12
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2020-09-05	2021-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-02	2020-09-05	2021-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0530-01	2020-09-24	2021-09-24
Sonoma	Amplifier	310N	185914	2020-10-13	2021-10-13
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Radiation Above 1GHz					
TDK RF	Horn Antenna	HRN-0118	130 084	2018-10-12	2021-10-12
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2017-12-06	2020-12-05
R&S	Spectrum Analyzer	FSP 38	100478	2020-07-07	2021-07-07
HUBER+SUHNE R	Coaxial Cable	SUCOFLEX 126EA	MY369/26/26E A	2020-09-25	2021-09-25
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2020-09-05	2021-09-05
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2020-06-27	2021-06-27
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
E-Microwave	Band-stop Filters	OBSF-2400-2483.5-S	OE01601525	2020-06-16	2021-06-16
Micro-tronics	High Pass Filter	HPM50111	S/N-G217	2020-06-16	2021-06-16

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$


Test Data

Environmental Conditions


Test Items	Radiation Below 1GHz	Radiation Above 1GHz
Temperature:	27.8°C	27.8°C
Relative Humidity:	46%	43%
ATM Pressure:	100.5kPa	100.7kPa
Tester:	Michael Zhang	Felix Wang
Test Date:	2020-10-22	2020-10-31

Test Mode: Transmitting

1) 30MHz-1GHz (BDR High channel was the worst)

Horizontal:80.0 dB μ V/m

Frequency (MHz)	Receiver Reading (dB μ V)	Remark	Correction Factor (dB/m)	Cord. Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
30.0000	27.47	peak	-4.10	23.37	40.00	16.63
156.1000	30.55	peak	-9.38	21.17	43.50	22.33
296.7500	28.32	peak	-7.60	20.72	46.00	25.28
436.4300	27.00	peak	-4.48	22.52	46.00	23.48
572.2300	27.44	peak	-1.50	25.94	46.00	20.06
703.1800	27.18	peak	0.04	27.22	46.00	18.78

Vertical:




Frequency (MHz)	Receiver Reading (dB μ V)	Remark	Correction Factor (dB/m)	Cord. Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
30.0000	27.40	peak	-4.10	23.30	40.00	16.70
142.5200	27.84	peak	-9.11	18.73	43.50	24.77
380.1700	28.37	peak	-5.85	22.52	46.00	23.48
543.1300	26.54	peak	-2.02	24.52	46.00	21.48
668.2600	27.51	peak	0.00	27.51	46.00	18.49
725.4900	26.94	peak	0.67	27.61	46.00	18.39

2)1GHz-25GHz:*BDR Mode(GFSK was the worst):*

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Remark	Polar (H/V)	Factor (dB/m)					
Low Channel: 2402 MHz									
2402.00	66.94	PK	H	24.82	2.50	0.00	94.26	N/A	N/A
2402.00	57.63	AV	H	24.82	2.50	0.00	84.95	N/A	N/A
2402.00	66.46	PK	V	24.82	2.50	0.00	93.78	N/A	N/A
2402.00	57.06	AV	V	24.82	2.50	0.00	84.38	N/A	N/A
2390.00	29.31	PK	H	24.80	2.50	0.00	56.61	74.00	17.39
2390.00	17.00	AV	H	24.80	2.50	0.00	44.30	54.00	9.70
4804.00	46.42	PK	H	29.71	3.59	27.36	52.36	74.00	21.64
4804.00	34.91	AV	H	29.71	3.59	27.36	40.85	54.00	13.15
7206.00	37.24	PK	H	33.93	4.68	27.19	48.66	74.00	25.34
7206.00	24.31	AV	H	33.93	4.68	27.19	35.73	54.00	18.27
Middle Channel: 2441 MHz									
2441.00	66.50	PK	H	24.89	2.51	0.00	93.90	N/A	N/A
2441.00	57.21	AV	H	24.89	2.51	0.00	84.61	N/A	N/A
2441.00	66.02	PK	V	24.89	2.51	0.00	93.42	N/A	N/A
2441.00	56.73	AV	V	24.89	2.51	0.00	84.13	N/A	N/A
4882.00	45.49	PK	H	29.86	3.58	27.56	51.37	74.00	22.63
4882.00	34.05	AV	H	29.86	3.58	27.56	39.93	54.00	14.07
7323.00	37.17	PK	H	34.12	4.64	27.26	48.67	74.00	25.33
7323.00	24.22	AV	H	34.12	4.64	27.26	35.72	54.00	18.28
High Channel: 2480 MHz									
2480.00	66.24	PK	H	24.96	2.52	0.00	93.72	N/A	N/A
2480.00	56.78	AV	H	24.96	2.52	0.00	84.26	N/A	N/A
2480.00	65.76	PK	V	24.96	2.52	0.00	93.24	N/A	N/A
2480.00	56.31	AV	V	24.96	2.52	0.00	83.79	N/A	N/A
2483.50	36.94	PK	H	24.97	2.53	0.00	64.44	74.00	9.56
2483.50	19.25	AV	H	24.97	2.53	0.00	46.75	54.00	7.25
4960.00	43.96	PK	H	30.02	3.59	27.37	50.20	74.00	23.80
4960.00	33.12	AV	H	30.02	3.59	27.37	39.36	54.00	14.64
7440.00	36.87	PK	H	34.30	4.61	27.22	48.56	74.00	25.44
7440.00	23.91	AV	H	34.30	4.61	27.22	35.60	54.00	18.40




Worst plots (GFSK low channel was the worst)**Horizontal**

Fundamental
Test with Band
Rejection Filter



Vertical

Fundamental
Test with Band
Rejection Filter



FCC §15.247(a) (1) - CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2020-07-07	2021-07-07
yzjingcheng	Coaxial Cable	KTRFBU-141-50	41005012	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another trace.
3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	27.1 °C
Relative Humidity:	36 %
ATM Pressure:	101.2kPa
Test by:	Rennes Guo
Test Date:	2020-11-04

Test Result: Compliance. Please refer to following tables and plots

Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)
BDR (GFSK)	Low	2402	1.000	0.59
	Middle	2441	0.994	0.62
	High	2480	1.000	0.62
EDR ($\pi/4$ -DQPSK)	Low	2402	1.000	0.83
	Middle	2441	1.000	0.83
	High	2480	1.000	0.84
EDR (8DPSK)	Low	2402	0.994	0.84
	Middle	2441	1.000	0.84
	High	2480	1.006	0.84

Note: Limit = (2/3) × 20dB bandwidth

BDR Mode (GFSK):

Low Channel

Date: 4.NOV.2020 11:37:16

Middle Channel

Date: 4.NOV.2020 11:38:35

High Channel

Date: 4.NOV.2020 11:39:33


EDR Mode ($\pi/4$ -DQPSK):

Low Channel




Date: 4.NOV.2020 11:44:00

Middle Channel



Date: 4.NOV.2020 11:42:32

High Channel

Date: 4.NOV.2020 11:40:55

*EDR Mode (8DPSK):***Low Channel**

Date: 4.NOV.2020 11:46:28

Middle Channel

Date: 4.NOV.2020 11:47:38

High Channel

Date: 4.NOV.2020 11:48:41

FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2020-07-07	2021-07-07
yzjingcheng	Coaxial Cable	KTRFBU-141-50	41005012	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	27.1 °C
Relative Humidity:	36 %
ATM Pressure:	101.2kPa
Test by:	Rennes Guo
Test Date:	2020-11-04


Test Result: Compliance. Please refer to following tables and plots

Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
BDR Mode (GFSK)	Low	2402	0.888
	Middle	2441	0.928
	High	2480	0.928
EDR Mode ($\pi/4$ -DQPSK)	Low	2402	1.244
	Middle	2441	1.252
	High	2480	1.256
EDR Mode (8DPSK)	Low	2402	1.264
	Middle	2441	1.264
	High	2480	1.264

BDR Mode (GFSK):

Low Channel



Middle Channel



Date: 4.NOV.2020 10:37:19

High Channel



Date: 4.NOV.2020 10:38:06

EDR Mode ($\pi/4$ -DQPSK):

Low Channel



Date: 4.NOV.2020 10:42:29


Middle Channel



Date: 4.NOV.2020 10:41:37


High Channel

Date: 4.NOV.2020 10:40:51

*EDR Mode (8DPSK):***Low Channel**


Date: 4.NOV.2020 10:43:23

Middle Channel



Date: 4.NOV.2020 10:44:18

High Channel



Date: 4.NOV.2020 10:45:12

FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2020-07-07	2021-07-07
yzjingcheng	Coaxial Cable	KTRFBU-141-50	41005012	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data


Environmental Conditions

Temperature:	27.1 °C
Relative Humidity:	36 %
ATM Pressure:	101.2kPa
Test by:	Rennes Guo
Test Date:	2020-11-04


Test Result: Compliance. Please refer to following tables and plots

Test Mode: Transmitting

Test mode	Frequency Range (MHz)	Number of Hopping Channel	Limit
GFSK	2400-2483.5	79	≥15
π/4-DQPSK	2400-2483.5	79	≥15
8DPSK	2400-2483.5	79	≥15


BDR Mode (GFSK)

Date: 4.NOV.2020 11:58:22

EDR Mode ($\pi/4$ -DQPSK)

Date: 4.NOV.2020 11:51:58

EDR Mode (8DPSK)



Date: 4.NOV.2020 11:55:38

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; the time of single pulses was tested.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2020-07-07	2021-07-07
yzjingcheng	Coaxial Cable	KTRFBU-141-50	41005012	Each time	N/A

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**


Temperature:	27.1 °C
Relative Humidity:	36 %
ATM Pressure:	101.2kPa
Test by:	Rennes Guo
Test Date:	2020-11-04

Test Result: Compliance. Please refer to following tables and plots

Test Mode: Transmitting


Mode	Packet type	Channel	Frequency (MHz)	Pulse width (ms)	Result (s)	Limit (s)
GFSK	DH1	Middle	2441	0.392	0.125	0.4
	DH3	Middle	2441	1.653	0.264	
	DH5	Middle	2441	2.907	0.31	
$\pi/4$ -DQPSK	2DH1	Middle	2441	0.397	0.127	0.4
	2DH3	Middle	2441	1.657	0.265	
	2DH5	Middle	2441	2.914	0.311	
8DPSK	3DH1	Middle	2441	0.397	0.127	0.4
	3DH3	Middle	2441	1.663	0.266	
	3DH5	Middle	2441	2.925	0.312	

Note:
DH1:Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s
DH3:Dwell time=Pulse time (ms) \times (1600/4/79) \times 31.6 s
DH5:Dwell time=Pulse time (ms) \times (1600/6/79) \times 31.6 s

*BDR Mode (GFSK):***DH1: Middle Channel**


Date: 4.NOV.2020 12:18:31

DH3: Middle Channel



Date: 4.NOV.2020 12:20:14


DH5: Middle Channel



Date: 4.NOV.2020 12:21:28


EDR Mode ($\pi/4$ -DQPSK):

2DH1: Middle Channel




Date: 4.NOV.2020 12:16:51

2DH3: Middle Channel



Date: 4.NOV.2020 12:15:52


2DH5: Middle Channel



Date: 4.NOV.2020 12:14:20


EDR Mode (8DPSK):

3DH1: Middle Channel




Date: 4.NOV.2020 12:07:24

3DH3: Middle Channel



Date: 4.NOV.2020 12:10:54

3DH5: Middle Channel



Date: 4.NOV.2020 12:12:51

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	USB Wideband Power Sensor	U2021XA	MY54080014	2020-09-12	2021-09-12
E-Microwave	Blocking Control	EMDCB-00036	0E01201048	Each time	N/A
yzjingcheng	Coaxial Cable	KTRFBU-141-50	41005012	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	27.1 °C
Relative Humidity:	36 %
ATM Pressure:	101.2kPa
Test by:	Rennes Guo
Test Date:	2020-11-04

Test Result: Compliance.

Test Mode: Transmitting

Mode	Frequency (MHz)	Peak Conducted Output power (dBm)	Limit (dBm)
BDR Mode (GFSK)	2402	4.63	21
	2441	3.49	21
	2480	1.73	21
EDR Mode ($\pi/4$ -DQPSK)	2402	3.26	21
	2441	2.84	21
	2480	1.06	21
EDR Mode (8DPSK)	2402	3.49	21
	2441	3.06	21
	2480	1.24	21

Note: The data above was tested in conducted mode.

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW/ VBW of spectrum analyzer to 100/300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2020-07-07	2021-07-07
yzjingcheng	Coaxial Cable	KTRFBU-141-50	41005012	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data


Environmental Conditions

Temperature:	27.1 °C
Relative Humidity:	36 %
ATM Pressure:	101.2kPa
Test by:	Rennes Guo
Test Date:	2020-11-04

Test Result: Compliance


*Single Channel Mode,
BDR Mode (GFSK):*

Band Edge, Left Side



Date: 4.NOV.2020 11:36:56


Band Edge, Right Side




Date: 4.NOV.2020 11:39:08

EDR Mode ($\pi/4$ -DQPSK):


Band Edge, Left Side




Date: 4.NOV.2020 11:43:04

Band Edge, Right Side

Date: 4.NOV.2020 11:40:24


*EDR Mode (8DPSK):***Band Edge, Left Side**

Date: 4.NOV.2020 11:46:01

Band Edge, Right Side


Date: 4.NOV.2020 11:48:11

*Hopping Mode,
BDR Mode (GFSK):*

Band Edge, Left Side

Date: 4.NOV.2020 11:57:29

Band Edge, Right Side




Date: 4.NOV.2020 12:01:15

EDR Mode ($\pi/4$ -DQPSK):


Band Edge, Left Side




Date: 4.NOV.2020 11:54:42

Band Edge, Right Side

Date: 4.NOV.2020 12:03:47

*EDR Mode (8DPSK):***Band Edge, Left Side**

Date: 4.NOV.2020 12:05:32

Band Edge, Right Side

Date: 4.NOV.2020 11:50:46

******* END OF REPORT *******