



## Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V05

Report Template Revision Date: 2021-11-03

# TEST REPORT

**Report No.:** CQASZ20230300321E-02  
**Applicant:** TOPDON TECHNOLOGY Co., Ltd.  
**Address of Applicant:** Unit 2005 20/F, Qianhai Shima Tower, Qianhai Shenzhen-Hong Kong Cooperation Zone Shenzhen China  
**Equipment Under Test (EUT):**  
**Product:** Thermal Imaging Camera  
**Model No.:** TC003  
**Test Model No.:** TC003  
**Brand Name:** **TOPDON**<sup>TM</sup>  
**FCC ID:** 2AVYW-TC003  
**Standards:** 47 CFR Part 15, Subpart C  
**Date of Receipt:** 2023-03-10  
**Date of Test:** 2023-03-10 to 2023-03-17  
**Date of Issue:** 2023-03-23  
**Test Result :** **PASS\***

\*In the configuration tested, the EUT complied with the standards specified above

**Tested By:**

*Lewis Zhou*

( Lewis Zhou )

**Reviewed By:**

*Timo Lei*

( Timo Lei )

**Approved By:**

*Jack Ai*

( Jack Ai )



The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

---

## 1 Version

### Revision History Of Report

| Report No.           | Version | Description    | Issue Date |
|----------------------|---------|----------------|------------|
| CQASZ20230300321E-02 | Rev.01  | Initial report | 2023-03-23 |

## 2 Test Summary

| Test Item                                                         | Test Requirement                                    | Test method      | Result |
|-------------------------------------------------------------------|-----------------------------------------------------|------------------|--------|
| Antenna Requirement                                               | 47 CFR Part 15, Subpart C Section 15.203/15.247 (c) | ANSI C63.10 2013 | PASS   |
| AC Power Line Conducted Emission                                  | 47 CFR Part 15, Subpart C Section 15.207            | ANSI C63.10 2013 | PASS   |
| Conducted Peak & Average Output Power                             | 47 CFR Part 15, Subpart C Section 15.247 (b)(3)     | ANSI C63.10 2013 | PASS   |
| 6dB Occupied Bandwidth                                            | 47 CFR Part 15, Subpart C Section 15.247 (a)(2)     | ANSI C63.10 2013 | PASS   |
| Power Spectral Density                                            | 47 CFR Part 15, Subpart C Section 15.247 (e)        | ANSI C63.10 2013 | PASS   |
| Band-edge for RF Conducted Emissions                              | 47 CFR Part 15, Subpart C Section 15.247(d)         | ANSI C63.10 2013 | PASS   |
| RF Conducted Spurious Emissions                                   | 47 CFR Part 15, Subpart C Section 15.247(d)         | ANSI C63.10 2013 | PASS   |
| Radiated Spurious Emissions                                       | 47 CFR Part 15, Subpart C Section 15.205/15.209     | ANSI C63.10 2013 | PASS   |
| Restricted bands around fundamental frequency (Radiated Emission) | 47 CFR Part 15, Subpart C Section 15.205/15.209     | ANSI C63.10 2013 | PASS   |

### 3 Contents

|                                                             | Page      |
|-------------------------------------------------------------|-----------|
| <b>1 VERSION .....</b>                                      | <b>2</b>  |
| <b>2 TEST SUMMARY .....</b>                                 | <b>3</b>  |
| <b>3 CONTENTS .....</b>                                     | <b>4</b>  |
| <b>4 GENERAL INFORMATION .....</b>                          | <b>5</b>  |
| 4.1 CLIENT INFORMATION .....                                | 5         |
| 4.2 GENERAL DESCRIPTION OF EUT .....                        | 5         |
| 4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD ..... | 5         |
| 4.4 TEST ENVIRONMENT AND MODE .....                         | 7         |
| 4.5 DESCRIPTION OF SUPPORT UNITS .....                      | 8         |
| 4.6 TEST LOCATION .....                                     | 8         |
| 4.7 TEST FACILITY .....                                     | 8         |
| 4.8 STATEMENT OF THE MEASUREMENT UNCERTAINTY .....          | 9         |
| 4.9 DEVIATION FROM STANDARDS .....                          | 9         |
| 4.10 ABNORMALITIES FROM STANDARD CONDITIONS .....           | 9         |
| 4.11 OTHER INFORMATION REQUESTED BY THE CUSTOMER .....      | 9         |
| 4.12 EQUIPMENT LIST .....                                   | 10        |
| <b>5 TEST RESULTS AND MEASUREMENT DATA .....</b>            | <b>11</b> |
| 5.1 ANTENNA REQUIREMENT .....                               | 11        |
| 5.2 CONDUCTED EMISSIONS .....                               | 12        |
| 5.3 CONDUCTED PEAK & AVERAGE OUTPUT POWER .....             | 16        |
| <i>Test Result</i> .....                                    | 17        |
| <i>Test Graphs</i> .....                                    | 18        |
| 5.4 6dB OCCUPY BANDWIDTH .....                              | 23        |
| <i>Test Result</i> .....                                    | 24        |
| <i>Test Graphs</i> .....                                    | 25        |
| 5.5 POWER SPECTRAL DENSITY .....                            | 30        |
| <i>Test Result</i> .....                                    | 31        |
| <i>Test Graphs</i> .....                                    | 32        |
| 5.6 BAND-EDGE FOR RF CONDUCTED EMISSIONS .....              | 37        |
| <i>Test Result</i> .....                                    | 38        |
| 5.6.1 <i>Test Graphs</i> .....                              | 39        |
| 5.7 RF CONDUCTED SPURIOUS EMISSIONS .....                   | 42        |
| <i>Test Result</i> .....                                    | 43        |
| <i>Test Graphs</i> .....                                    | 44        |
| 5.8 RADIATED SPURIOUS EMISSIONS .....                       | 58        |
| 5.8.1 <i>Radiated emission below 1GHz</i> .....             | 61        |
| 5.8.2 <i>Transmitter emission above 1GHz</i> .....          | 63        |
| 5.9 RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY .....     | 65        |
| <b>6 PHOTOGRAPHS - EUT TEST SETUP .....</b>                 | <b>71</b> |
| 6.1 RADIATED EMISSION .....                                 | 71        |
| 6.2 CONDUCTED EMISSION .....                                | 72        |
| <b>7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS .....</b>     | <b>73</b> |

## 4 General Information

### 4.1 Client Information

|                          |                                                                                                 |
|--------------------------|-------------------------------------------------------------------------------------------------|
| Applicant:               | TOPDON TECHNOLOGY Co., Ltd.                                                                     |
| Address of Applicant:    | Unit 2005 20/F, Qianhai Shima Tower, Qianhai Shenzhen-Hong kong Cooperation Zone Shenzhen China |
| Manufacturer:            | TOPDON TECHNOLOGY Co., Ltd.                                                                     |
| Address of Manufacturer: | Unit 2005 20/F, Qianhai Shima Tower, Qianhai Shenzhen-Hong kong Cooperation Zone Shenzhen China |
| Factory:                 | TOPDON TECHNOLOGY Co., Ltd.                                                                     |
| Address of Factory:      | Unit 2005 20/F, Qianhai Shima Tower, Qianhai Shenzhen-Hong kong Cooperation Zone Shenzhen China |

### 4.2 General Description of EUT

|                                  |                                                                        |
|----------------------------------|------------------------------------------------------------------------|
| Product Name:                    | Thermal Imaging Camera                                                 |
| Model No.:                       | TC003                                                                  |
| Test Model No.:                  | TC003                                                                  |
| Trade Mark:                      | <b>TOPDON</b>                                                          |
| Software Version:                | TOPDON UI V1.12                                                        |
| Hardware Version:                | TC003_V0_3                                                             |
| Power Supply:                    | Li-ion battery DC 3.7V 5050mAh, Charge by DC 5V for adapter            |
| EUT Supports Radios application: | BT: 2402-2480MHz<br>2.4GHz: Wi-Fi: 802.11b/g/n(HT20): 2412MHz~2462MHz; |

### 4.3 Product Specification subjective to this standard

|                       |                                                                                                                                                                                                                            |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operation Frequency:  | IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz                                                                                                                                                                                 |
| Channel Numbers:      | IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels                                                                                                                                                                             |
| Channel Separation:   | 5MHz                                                                                                                                                                                                                       |
| Type of Modulation:   | IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK)<br>IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK)<br>IEEE for 802.11n(HT20) : OFDM (64QAM, 16QAM, QPSK, BPSK)                                                                   |
| Transfer Rate:        | IEEE for 802.11b:<br>1Mbps/2Mbps/5.5Mbps/11Mbps<br>IEEE for 802.11g :<br>6Mbps/9Mbps/12Mbps/18Mbps/24Mbps/36Mbps/48Mbps/54Mbps<br>IEEE for 802.11n(HT20) :<br>6.5Mbps/13Mbps/19.5Mbps/26Mbps/39Mbps/52Mbps/58.5Mbps/65Mbps |
| Product Type:         | <input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable                                                                                                                                               |
| Test Software of EUT: | ADB                                                                                                                                                                                                                        |
| Antenna Type:         | FPC antenna                                                                                                                                                                                                                |
| Antenna Gain:         | 1.65dBi                                                                                                                                                                                                                    |

| Operation Frequency each of channel(802.11b/g/n HT20) |           |         |           |         |           |         |           |
|-------------------------------------------------------|-----------|---------|-----------|---------|-----------|---------|-----------|
| Channel                                               | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
| 1                                                     | 2412MHz   | 4       | 2427MHz   | 7       | 2442MHz   | 10      | 2457MHz   |
| 2                                                     | 2417MHz   | 5       | 2432MHz   | 8       | 2447MHz   | 11      | 2462MHz   |
| 3                                                     | 2422MHz   | 6       | 2437MHz   | 9       | 2452MHz   |         |           |

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:


For 802.11b/g/n (HT20):

| Channel             | Frequency |
|---------------------|-----------|
| The Lowest channel  | 2412MHz   |
| The Middle channel  | 2437MHz   |
| The Highest channel | 2462MHz   |

Note:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

## 4.4 Test Environment and Mode

|                                                                                      |                                                                                          |
|--------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
| <b>Operating Environment:</b>                                                        |                                                                                          |
| <b>Radiated Emissions:</b>                                                           |                                                                                          |
| Temperature:                                                                         | 25.3 °C                                                                                  |
| Humidity:                                                                            | 55 % RH                                                                                  |
| Atmospheric Pressure:                                                                | 1009 mbar                                                                                |
| <b>Conducted Emissions:</b>                                                          |                                                                                          |
| Temperature:                                                                         | 25.6 °C                                                                                  |
| Humidity:                                                                            | 60 % RH                                                                                  |
| Atmospheric Pressure:                                                                | 1009 mbar                                                                                |
| <b>Radio conducted item test (RF Conducted test room):</b>                           |                                                                                          |
| Temperature:                                                                         | 25.5 °C                                                                                  |
| Humidity:                                                                            | 52 % RH                                                                                  |
| Atmospheric Pressure:                                                                | 1009 mbar                                                                                |
| <b>Test mode:</b>                                                                    |                                                                                          |
| Transmitting mode:                                                                   | Keep the EUT in transmitting mode with all kind of modulation and all kind of data rate. |
| <b>Run Software:</b>                                                                 |                                                                                          |
|  |                                                                                          |

## 4.5 Description of Support Units

The EUT has been tested with associated equipment below.

### 1) Support equipment

| Description | Manufacturer | Model No. | Certification | Supplied by |
|-------------|--------------|-----------|---------------|-------------|
| /           | /            | /         | /             | /           |

### 2) Cable

| Cable No. | Description | Manufacturer | Cable Type/Length | Supplied by |
|-----------|-------------|--------------|-------------------|-------------|
| /         | /           | /            | /                 | /           |

## 4.6 Test Location

All tests were performed at:

Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua New District, Shenzhen, Guangdong, China

## 4.7 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

### • A2LA (Certificate No. 4742.01)

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

### • FCC Registration No.: 522263

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263



## 4.8 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

| No. | Item                               | Uncertainty        | Notes |
|-----|------------------------------------|--------------------|-------|
| 1   | Radiated Emission (Below 1GHz)     | 5.12dB             | (1)   |
| 2   | Radiated Emission (Above 1GHz)     | 4.60dB             | (1)   |
| 3   | Conducted Disturbance (0.15~30MHz) | 3.34dB             | (1)   |
| 4   | Radio Frequency                    | $3 \times 10^{-8}$ | (1)   |
| 5   | Duty cycle                         | 0.6 %.             | (1)   |
| 6   | Occupied Bandwidth                 | 1.1%               | (1)   |
| 7   | RF conducted power                 | 0.86dB             | (1)   |
| 8   | RF power density                   | 0.74               | (1)   |
| 9   | Conducted Spurious emissions       | 0.86dB             | (1)   |
| 10  | Temperature test                   | 0.8℃               | (1)   |
| 11  | Humidity test                      | 2.0%               | (1)   |
| 12  | Supply voltages                    | 0.5 %.             | (1)   |
| 13  | Frequency Error                    | 5.5 Hz             | (1)   |

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

## 4.9 Deviation from Standards

None.

## 4.10 Abnormalities from Standard Conditions

None.

## 4.11 Other Information Requested by the Customer

None.

## 4.12 Equipment List

| Test Equipment                            | Manufacturer | Model No.              | Instrument No. | Calibration Date | Calibration Due Date |
|-------------------------------------------|--------------|------------------------|----------------|------------------|----------------------|
| EMI Test Receiver                         | R&S          | ESR7                   | CQA-005        | 2022/09/09       | 2023/09/08           |
| Spectrum analyzer                         | R&S          | FSU26                  | CQA-038        | 2022/09/09       | 2023/09/08           |
| Spectrum analyzer                         | R&S          | FSU40                  | CQA-075        | 2022/09/09       | 2023/09/08           |
| Preamplifier                              | MITEQ        | AFS4-00010300-18-10P-4 | CQA-035        | 2022/09/09       | 2023/09/08           |
| Preamplifier                              | MITEQ        | AMF-6D-02001800-29-20P | CQA-036        | 2022/09/09       | 2023/09/08           |
| Preamplifier                              | EMCI         | EMC184055SE            | CQA-089        | 2022/09/09       | 2023/09/08           |
| Loop antenna                              | Schwarzbeck  | FMZB1516               | CQA-060        | 2021/09/16       | 2024/09/15           |
| Bilog Antenna                             | R&S          | HL562                  | CQA-011        | 2021/09/16       | 2024/09/15           |
| Horn Antenna                              | R&S          | HF906                  | CQA-012        | 2021/09/16       | 2024/09/15           |
| Horn Antenna                              | Schwarzbeck  | BBHA 9170              | CQA-088        | 2021/09/16       | 2024/09/15           |
| Coaxial Cable (Above 1GHz)                | CQA          | N/A                    | C007           | 2022/09/09       | 2023/09/08           |
| Coaxial Cable (Below 1GHz)                | CQA          | N/A                    | C013           | 2022/09/09       | 2023/09/08           |
| RF cable(9KHz~40GHz)                      | CQA          | RF-01                  | CQA-079        | 2022/09/09       | 2023/09/08           |
| Antenna Connector                         | CQA          | RFC-01                 | CQA-080        | 2022/09/09       | 2023/09/08           |
| Power Sensor                              | KEYSIGHT     | U2021XA                | CQA-30         | 2022/09/09       | 2023/09/08           |
| N1918A Power Analysis Manager Power Panel | Agilent      | N1918A                 | CQA-074        | 2022/09/09       | 2023/09/08           |
| Power meter                               | R&S          | NRVD                   | CQA-029        | 2022/09/09       | 2023/09/08           |
| Power divider                             | MIDWEST      | PWD-2533-02-SMA-79     | CQA-067        | 2022/09/09       | 2023/09/08           |
| EMI Test Receiver                         | R&S          | ESR7                   | CQA-005        | 2022/09/09       | 2023/09/08           |
| LISN                                      | R&S          | ENV216                 | CQA-003        | 2022/09/09       | 2023/09/08           |
| Coaxial cable                             | CQA          | N/A                    | CQA-C009       | 2022/09/09       | 2023/09/08           |
| DC power                                  | KEYSIGHT     | E3631A                 | CQA-028        | 2022/09/09       | 2023/09/08           |

Test software:


|                                   | Manufacturer | Software brand |
|-----------------------------------|--------------|----------------|
| Radiated Emissions test software  | Tonscend     | JS1120-3       |
| Conducted Emissions test software | Audix        | e3             |
| RF Conducted test software        | Audix        | e3             |

## 5 Test results and Measurement Data

### 5.1 Antenna Requirement

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                     |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <b>Standard requirement:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 47 CFR Part 15C Section 15.203 /247(c)                                              |
| <p>15.203 requirement:<br/>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(b) (4) requirement:<br/>The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p> |                                                                                     |
| <b>EUT Antenna:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |  |
| The antenna is FPC antenna. The best case gain of the antenna is 1.65 dBi.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                     |


## 5.2 Conducted Emissions

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |              |           |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-----------|
| Test Requirement:     | 47 CFR Part 15C Section 15.207                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |              |           |
| Test Method:          | ANSI C63.10: 2013                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |              |           |
| Test Frequency Range: | 150kHz to 30MHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |              |           |
| Limit:                | Frequency range (MHz)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Limit (dBuV) |           |
|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Quasi-peak   | Average   |
|                       | 0.15-0.5                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 66 to 56*    | 56 to 46* |
|                       | 0.5-5                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 56           | 46        |
|                       | 5-30                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 60           | 50        |
|                       | * Decreases with the logarithm of the frequency.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |              |           |
| Test Procedure:       | <ol style="list-style-type: none"> <li>1) The mains terminal disturbance voltage test was conducted in a shielded room.</li> <li>2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a <math>50\Omega/50\mu\text{H} + 5\Omega</math> linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.</li> <li>3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,</li> <li>4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.</li> <li>5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.</li> </ol> |              |           |
| Test Setup:           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |              |           |

|                        |                                                                                                                                            |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Exploratory Test Mode: | Transmitting with all kind of modulations, data rates at lowest, middle and highest channel.                                               |
| Final Test Mode:       | Through Pre-scan, find the 1Mbps of rate of 802.11b at middle channel is the worst case.<br>Only the worst case is recorded in the report. |
| Test Voltage:          | AC120V/60Hz                                                                                                                                |
| Test Results:          | Pass                                                                                                                                       |

## Measurement Data

Live Line:




|      | Freq   | Read Level | Factor | Level | Limit Line | Over Limit | Remark  | Pol/Phase |
|------|--------|------------|--------|-------|------------|------------|---------|-----------|
|      | MHz    | dBuV       | dB     | dBuV  | dBuV       | dB         |         |           |
| 1    | 0.150  | 24.44      | 9.70   | 34.14 | 56.00      | -21.86     | Average | Line      |
| 2    | 0.150  | 34.36      | 9.70   | 44.06 | 66.00      | -21.94     | QP      | Line      |
| 3    | 0.225  | 23.90      | 9.58   | 33.48 | 52.63      | -19.15     | Average | Line      |
| 4    | 0.225  | 32.61      | 9.58   | 42.19 | 62.63      | -20.44     | QP      | Line      |
| 5    | 0.665  | 21.51      | 9.87   | 31.38 | 46.00      | -14.62     | Average | Line      |
| 6    | 0.665  | 30.09      | 9.87   | 39.96 | 56.00      | -16.04     | QP      | Line      |
| 7 PP | 1.630  | 20.89      | 11.07  | 31.96 | 46.00      | -14.04     | Average | Line      |
| 8 QP | 1.630  | 29.00      | 11.07  | 40.07 | 56.00      | -15.93     | QP      | Line      |
| 9    | 2.965  | 14.31      | 10.81  | 25.12 | 46.00      | -20.88     | Average | Line      |
| 10   | 2.965  | 25.32      | 10.81  | 36.13 | 56.00      | -19.87     | QP      | Line      |
| 11   | 19.125 | 11.86      | 9.82   | 21.68 | 50.00      | -28.32     | Average | Line      |
| 12   | 19.125 | 21.67      | 9.82   | 31.49 | 60.00      | -28.51     | QP      | Line      |

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.



Neutral Line:




|      | Freq   | Read  |        | Limit | Over  |        |         |           |
|------|--------|-------|--------|-------|-------|--------|---------|-----------|
|      | MHz    | Level | Factor | Level | Line  | Limit  | Remark  | Pol/Phase |
|      | MHz    | dBuV  | dB     | dBuV  | dBuV  | dB     |         |           |
| 1    | 0.155  | 23.71 | 9.69   | 33.40 | 55.73 | -22.33 | Average | Neutral   |
| 2    | 0.155  | 32.24 | 9.69   | 41.93 | 65.73 | -23.80 | QP      | Neutral   |
| 3    | 0.225  | 24.35 | 9.57   | 33.92 | 52.63 | -18.71 | Average | Neutral   |
| 4    | 0.225  | 30.85 | 9.57   | 40.42 | 62.63 | -22.21 | QP      | Neutral   |
| 5 PP | 0.575  | 26.19 | 9.78   | 35.97 | 46.00 | -10.03 | Average | Neutral   |
| 6 QP | 0.575  | 31.29 | 9.78   | 41.07 | 56.00 | -14.93 | QP      | Neutral   |
| 7    | 0.905  | 19.43 | 9.76   | 29.19 | 46.00 | -16.81 | Average | Neutral   |
| 8    | 0.905  | 24.78 | 9.76   | 34.54 | 56.00 | -21.46 | QP      | Neutral   |
| 9    | 2.140  | 21.54 | 9.75   | 31.29 | 46.00 | -14.71 | Average | Neutral   |
| 10   | 2.140  | 27.52 | 9.75   | 37.27 | 56.00 | -18.73 | QP      | Neutral   |
| 11   | 13.850 | 10.84 | 9.77   | 20.61 | 50.00 | -29.39 | Average | Neutral   |
| 12   | 13.850 | 18.32 | 9.77   | 28.09 | 60.00 | -31.91 | QP      | Neutral   |

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

### 5.3 Conducted Peak & Average Output Power


|                        |                                                                                                                                                                                                                                                                                                                                                                                                  |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement:      | 47 CFR Part 15C Section 15.247 (b)(3)                                                                                                                                                                                                                                                                                                                                                            |
| Test Method:           | ANSI C63.10: 2013                                                                                                                                                                                                                                                                                                                                                                                |
| Test Setup:            |  <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by two vertical legs. Below the table is a Ground Reference Plane.</p> |
| Exploratory Test Mode: | Transmitting with all kind of modulations, data rates                                                                                                                                                                                                                                                                                                                                            |
| Final Test Mode:       | Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20).<br>Only the worst case is recorded in the report.                                                                                                                                                                         |
| Limit:                 | 30dBm                                                                                                                                                                                                                                                                                                                                                                                            |
| Test Results:          | Pass                                                                                                                                                                                                                                                                                                                                                                                             |





**Test Result**

| TestMode  | Antenna | Channel | Result[dBm] | Limit[dBm] | Verdict |
|-----------|---------|---------|-------------|------------|---------|
| 11B       | Ant1    | 2412    | 1.79        | ≤30        | PASS    |
|           |         | 2437    | 2.65        | ≤30        | PASS    |
|           |         | 2462    | 1.49        | ≤30        | PASS    |
| 11G       | Ant1    | 2412    | 1.65        | ≤30        | PASS    |
|           |         | 2437    | 2.58        | ≤30        | PASS    |
|           |         | 2462    | 3.00        | ≤30        | PASS    |
| 11N20SISO | Ant1    | 2412    | 1.36        | ≤30        | PASS    |
|           |         | 2437    | 2.54        | ≤30        | PASS    |
|           |         | 2462    | 2.95        | ≤30        | PASS    |


## Test Graphs








11N20SISO\_Ant1\_2412




Date: 17.MAR.2023 03:53:22


11N20SISO\_Ant1\_2437



Date: 17.MAR.2023 03:55:15



## 5.4 6dB Occupy Bandwidth


|                        |                                                                                                                                                                                                                          |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement:      | 47 CFR Part 15C Section 15.247 (a)(2)                                                                                                                                                                                    |
| Test Method:           | ANSI C63.10: 2013                                                                                                                                                                                                        |
| Test Setup:            |  <p>Offset=cable loss+ attenuation factor</p>                                                                                          |
| Exploratory Test Mode: | Transmitting with all kind of modulations, data rates                                                                                                                                                                    |
| Final Test Mode:       | Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20).<br>Only the worst case is recorded in the report. |
| Limit:                 | $\geq 500$ kHz                                                                                                                                                                                                           |
| Test Results:          | Pass                                                                                                                                                                                                                     |

### Test Result


| TestMode  | Antenna | Frequency[MHz] | DTS BW<br>[MHz] | FL[MHz] | FH[MHz] | Limit[MHz] | Verdict |
|-----------|---------|----------------|-----------------|---------|---------|------------|---------|
| 11B       | Ant1    | 2412           | 9.04            | 2407.48 | 2416.52 | 0.5        | PASS    |
|           |         | 2437           | 9.04            | 2432.48 | 2441.52 | 0.5        | PASS    |
|           |         | 2462           | 9.04            | 2457.48 | 2466.52 | 0.5        | PASS    |
| 11G       | Ant1    | 2412           | 13.80           | 2405.72 | 2419.52 | 0.5        | PASS    |
|           |         | 2437           | 10.08           | 2431.96 | 2442.04 | 0.5        | PASS    |
|           |         | 2462           | 11.32           | 2455.72 | 2467.04 | 0.5        | PASS    |
| 11N20SISO | Ant1    | 2412           | 10.08           | 2406.96 | 2417.04 | 0.5        | PASS    |
|           |         | 2437           | 10.08           | 2431.96 | 2442.04 | 0.5        | PASS    |
|           |         | 2462           | 11.32           | 2455.72 | 2467.04 | 0.5        | PASS    |



## Test Graphs




11B Ant1\_2462




Date: 17.MAR.2023 04:21:33

11G Ant1\_2412




Date: 17.MAR.2023 03:48:14

11G\_Ant1\_2437




Date: 17.MAR.2023 03:49:59

11G\_Ant1\_2462




Date: 17.MAR.2023 03:51:28

11N20SISO\_Ant1\_2412




Date: 17.MAR.2023 03:53:08


11N20SISO\_Ant1\_2437



Date: 17.MAR.2023 03:55:02




## 5.5 Power Spectral Density

|                        |                                                                                                                                                                                                                          |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement:      | 47 CFR Part 15C Section 15.247 (e)                                                                                                                                                                                       |
| Test Method:           | ANSI C63.10: 2013                                                                                                                                                                                                        |
| Test Setup:            |  <p>Offset=cable loss+ attenuation factor</p>                                                                                          |
| Exploratory Test Mode: | Transmitting with all kind of modulations, data rates                                                                                                                                                                    |
| Final Test Mode:       | Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20).<br>Only the worst case is recorded in the report. |
| Limit:                 | $\leq 8.00\text{dBm}/3\text{kHz}$                                                                                                                                                                                        |
| Test Results:          | Pass                                                                                                                                                                                                                     |

## Test Result


| TestMode  | Antenna | Channel | Result[dBm/3-100kHz] | Limit[dBm/3kHz] | Verdict |
|-----------|---------|---------|----------------------|-----------------|---------|
| 11B       | Ant1    | 2412    | -25.11               | ≤8              | PASS    |
|           |         | 2437    | -24.87               | ≤8              | PASS    |
|           |         | 2462    | -26.1                | ≤8              | PASS    |
| 11G       | Ant1    | 2412    | -23.35               | ≤8              | PASS    |
|           |         | 2437    | -22.77               | ≤8              | PASS    |
|           |         | 2462    | -21.76               | ≤8              | PASS    |
| 11N20SISO | Ant1    | 2412    | -24.14               | ≤8              | PASS    |
|           |         | 2437    | -21.69               | ≤8              | PASS    |
|           |         | 2462    | -23.93               | ≤8              | PASS    |

## Test Graphs






11B\_Ant1\_2462




Date: 17.MAR.2023 04:21:55

11G\_Ant1\_2412




Date: 17.MAR.2023 03:48:36


11G\_Ant1\_2437



11G\_Ant1\_2462




11N20SISO\_Ant1\_2412




Date: 17.MAR.2023 03:53:30


11N20SISO\_Ant1\_2437



Date: 17.MAR.2023 03:55:24




## 5.6 Band-edge for RF Conducted Emissions

|                        |                                                                                                                                                                                                                                                                                                                                                                                         |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement:      | 47 CFR Part 15C Section 15.247 (d)                                                                                                                                                                                                                                                                                                                                                      |
| Test Method:           | ANSI C63.10: 2013                                                                                                                                                                                                                                                                                                                                                                       |
| Test Setup:            |  <p>Offset=cable loss+ attenuation factor</p>                                                                                                                                                                                                                                                         |
| Exploratory Test Mode: | Transmitting with all kind of modulations, data rates                                                                                                                                                                                                                                                                                                                                   |
| Final Test Mode:       | Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20).<br>Only the worst case is recorded in the report.                                                                                                                                                                |
| Limit:                 | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. |
| Test Results:          | Pass                                                                                                                                                                                                                                                                                                                                                                                    |


**Test Result**

| TestMode  | Antenna | ChName | Frequency[MHz] | RefLevel[dBm] | Result[dBm] | Limit[dBm]    | Verdict |
|-----------|---------|--------|----------------|---------------|-------------|---------------|---------|
| 11B       | Ant1    | Low    | 2412           | -7.97         | -50.15      | $\leq -37.97$ | PASS    |
|           |         | High   | 2462           | -8.38         | -48.64      | $\leq -38.38$ | PASS    |
| 11G       | Ant1    | Low    | 2412           | -7.90         | -49.31      | $\leq -37.9$  | PASS    |
|           |         | High   | 2462           | -9.06         | -49.48      | $\leq -39.06$ | PASS    |
| 11N20SISO | Ant1    | Low    | 2412           | -9.27         | -49.91      | $\leq -39.27$ | PASS    |
|           |         | High   | 2462           | -6.36         | -48.83      | $\leq -36.36$ | PASS    |

## 5.6.1 Test Graphs




11G\_Ant1\_Low\_2412



Date: 17.MAR.2023 03:48:46


11G\_Ant1\_High\_2462



Date: 17.MAR.2023 03:52:00



11N20SISO\_Ant1\_Low\_2412




Date: 17.MAR.2023 03:53:40

11N20SISO\_Ant1\_High\_2462



Date: 17.MAR.2023 03:57:03


## 5.7 RF Conducted Spurious Emissions

|                        |                                                                                                                                                                                                                                                                                                                                                                                         |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement:      | 47 CFR Part 15C Section 15.247 (d)                                                                                                                                                                                                                                                                                                                                                      |
| Test Method:           | ANSI C63.10: 2013                                                                                                                                                                                                                                                                                                                                                                       |
| Test Setup:            |  <p>Offset=cable loss+ attenuation factor</p>                                                                                                                                                                                                                                                         |
| Exploratory Test Mode: | Transmitting with all kind of modulations, data rates                                                                                                                                                                                                                                                                                                                                   |
| Final Test Mode:       | Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20).<br>Only the worst case is recorded in the report.                                                                                                                                                                |
| Limit:                 | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. |
| Test Results:          | Pass                                                                                                                                                                                                                                                                                                                                                                                    |


## Test Result

| TestMode  | Antenna | Frequency[MHz] | FreqRange [Mhz] | RefLevel [dBm] | Result [dBm] | Limit [dBm]   | Verdict |
|-----------|---------|----------------|-----------------|----------------|--------------|---------------|---------|
| 11B       | Ant1    | 2412           | Reference       | -8.39          | -8.39        | ---           | PASS    |
|           |         |                | 30~1000         | -8.39          | -58.16       | $\leq -38.39$ | PASS    |
|           |         |                | 1000~26500      | -8.39          | -53.81       | $\leq -38.39$ | PASS    |
|           |         | 2437           | Reference       | -7.16          | -7.16        | ---           | PASS    |
|           |         |                | 30~1000         | -7.16          | -58.06       | $\leq -37.16$ | PASS    |
|           |         |                | 1000~26500      | -7.16          | -54.85       | $\leq -37.16$ | PASS    |
|           |         | 2462           | Reference       | -8.52          | -8.52        | ---           | PASS    |
|           |         |                | 30~1000         | -8.52          | -58.02       | $\leq -38.52$ | PASS    |
|           |         |                | 1000~26500      | -8.52          | -54.14       | $\leq -38.52$ | PASS    |
| 11G       | Ant1    | 2412           | Reference       | -7.72          | -7.72        | ---           | PASS    |
|           |         |                | 30~1000         | -7.72          | -57.87       | $\leq -37.72$ | PASS    |
|           |         |                | 1000~26500      | -7.72          | -55.04       | $\leq -37.72$ | PASS    |
|           |         | 2437           | Reference       | -6.64          | -6.64        | ---           | PASS    |
|           |         |                | 30~1000         | -6.64          | -57.88       | $\leq -36.64$ | PASS    |
|           |         |                | 1000~26500      | -6.64          | -55.56       | $\leq -36.64$ | PASS    |
|           |         | 2462           | Reference       | -6.42          | -6.42        | ---           | PASS    |
|           |         |                | 30~1000         | -6.42          | -58.27       | $\leq -36.42$ | PASS    |
|           |         |                | 1000~26500      | -6.42          | -54.63       | $\leq -36.42$ | PASS    |
| 11N20SISO | Ant1    | 2412           | Reference       | -7.62          | -7.62        | ---           | PASS    |
|           |         |                | 30~1000         | -7.62          | -57.66       | $\leq -37.62$ | PASS    |
|           |         |                | 1000~26500      | -7.62          | -55.21       | $\leq -37.62$ | PASS    |
|           |         | 2437           | Reference       | -6.72          | -6.72        | ---           | PASS    |
|           |         |                | 30~1000         | -6.72          | -57.94       | $\leq -36.72$ | PASS    |
|           |         |                | 1000~26500      | -6.72          | -54.77       | $\leq -36.72$ | PASS    |
|           |         | 2462           | Reference       | -6.42          | -6.42        | ---           | PASS    |
|           |         |                | 30~1000         | -6.42          | -58.01       | $\leq -36.42$ | PASS    |
|           |         |                | 1000~26500      | -6.42          | -54.65       | $\leq -36.42$ | PASS    |

## Test Graphs




11B\_Ant1\_2412\_1000~26500




Date: 17.MAR.2023 04:19:34

11B\_Ant1\_2437\_0~Reference




Date: 17.MAR.2023 04:20:32

11B\_Ant1\_2437\_30~1000



Date: 17.MAR.2023 04:20:39

11B\_Ant1\_2437\_1000~26500




Date: 17.MAR.2023 04:21:01

11B\_Ant1\_2462\_0~Reference




Date: 17.MAR.2023 04:22:14

11B\_Ant1\_2462\_30~1000




Date: 17.MAR.2023 04:22:20

11B\_Ant1\_2462\_1000~26500



Date: 17.MAR.2023 04:22:43


11G\_Ant1\_2412\_0~Reference



Date: 17.MAR.2023 03:48:55




11G\_Ant1\_2412\_30~1000




Date: 17.MAR.2023 03:49:01


11G\_Ant1\_2412\_1000~26500



Date: 17.MAR.2023 03:49:24




11G\_Ant1\_2437\_1000~26500




Date: 17.MAR.2023 03:50:58

11G\_Ant1\_2462\_0~Reference




Date: 17.MAR.2023 03:52:09

11G\_Ant1\_2462\_30~1000




Date: 17.MAR.2023 03:52:15

11G\_Ant1\_2462\_1000~26500




Date: 17.MAR.2023 03:52:37

11N20SISO\_Ant1\_2412\_0~Reference




Date: 17.MAR.2023 03:53:49

11N20SISO\_Ant1\_2412\_30~1000




Date: 17.MAR.2023 03:53:56

11N20SISO\_Ant1\_2412\_1000~26500




Date: 17.MAR.2023 03:54:18

11N20SISO\_Ant1\_2437\_0~Reference




Date: 17.MAR.2023 03:55:33

11N20SISO\_Ant1\_2437\_30~1000




Date: 17.MAR.2023 03:55:39

11N20SISO\_Ant1\_2437\_1000~26500




Date: 17.MAR.2023 03:56:01

11N20SISO\_Ant1\_2462\_0~Reference




Date: 17.MAR.2023 03:57:12

11N20SISO\_Ant1\_2462\_30~1000



Date: 17.MAR.2023 03:57:18





**Remark:**

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

## 5.8 Radiated Spurious Emissions

|                   |                                                                                                                                                                                                                                                                             |                                     |                   |            |                             |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|-------------------|------------|-----------------------------|
| Test Requirement: | 47 CFR Part 15C Section 15.209 and 15.205                                                                                                                                                                                                                                   |                                     |                   |            |                             |
| Test Method:      | ANSI C63.10 2013                                                                                                                                                                                                                                                            |                                     |                   |            |                             |
| Test Site:        | Measurement Distance: 3m (Semi-Anechoic Chamber)                                                                                                                                                                                                                            |                                     |                   |            |                             |
| Receiver Setup:   | Frequency                                                                                                                                                                                                                                                                   | Detector                            | RBW               | VBW        | Remark                      |
|                   | 0.009MHz-0.090MHz                                                                                                                                                                                                                                                           | Peak                                | 10kHz             | 30kHz      | Peak                        |
|                   | 0.009MHz-0.090MHz                                                                                                                                                                                                                                                           | Average                             | 10kHz             | 30kHz      | Average                     |
|                   | 0.090MHz-0.110MHz                                                                                                                                                                                                                                                           | Quasi-peak                          | 10kHz             | 30kHz      | Quasi-peak                  |
|                   | 0.110MHz-0.490MHz                                                                                                                                                                                                                                                           | Peak                                | 10kHz             | 30kHz      | Peak                        |
|                   | 0.110MHz-0.490MHz                                                                                                                                                                                                                                                           | Average                             | 10kHz             | 30kHz      | Average                     |
|                   | 0.490MHz -30MHz                                                                                                                                                                                                                                                             | Quasi-peak                          | 10kHz             | 30kHz      | Quasi-peak                  |
|                   | 30MHz-1GHz                                                                                                                                                                                                                                                                  | Quasi-peak                          | 100 kHz           | 300kHz     | Quasi-peak                  |
|                   | Above 1GHz                                                                                                                                                                                                                                                                  | Peak                                | 1MHz              | 3MHz       | Peak                        |
|                   |                                                                                                                                                                                                                                                                             | Peak                                | 1MHz              | 10Hz       | Average                     |
| Limit:            | Frequency                                                                                                                                                                                                                                                                   | Field strength<br>(microvolt/meter) | Limit<br>(dBuV/m) | Remark     | Measurement<br>distance (m) |
|                   | 0.009MHz-0.490MHz                                                                                                                                                                                                                                                           | 2400/F(kHz)                         | -                 | -          | 300                         |
|                   | 0.490MHz-1.705MHz                                                                                                                                                                                                                                                           | 24000/F(kHz)                        | -                 | -          | 30                          |
|                   | 1.705MHz-30MHz                                                                                                                                                                                                                                                              | 30                                  | -                 | -          | 30                          |
|                   | 30MHz-88MHz                                                                                                                                                                                                                                                                 | 100                                 | 40.0              | Quasi-peak | 3                           |
|                   | 88MHz-216MHz                                                                                                                                                                                                                                                                | 150                                 | 43.5              | Quasi-peak | 3                           |
|                   | 216MHz-960MHz                                                                                                                                                                                                                                                               | 200                                 | 46.0              | Quasi-peak | 3                           |
|                   | 960MHz-1GHz                                                                                                                                                                                                                                                                 | 500                                 | 54.0              | Quasi-peak | 3                           |
|                   | Above 1GHz                                                                                                                                                                                                                                                                  | 500                                 | 54.0              | Average    | 3                           |
|                   | Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device. |                                     |                   |            |                             |

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:

- a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.  
2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.  
Note: For the radiated emission test above 1GHz: Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                        | <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p> <p>g. Test the EUT in the lowest channel, the middle channel, the Highest channel.</p> <p>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case.</p> <p>i. Repeat above procedures until all frequencies measured was complete.</p> |
| Exploratory Test Mode: | Transmitting with all kind of modulations, data rates at lowest, middle and highest channel.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Final Test Mode:       | <p>Pretest the EUT at Transmitting mode and Charge +Transmitting mode, found the Charge +Transmitting mode which it is worse case.</p> <p>Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20).</p> <p>For below 1GHz, through Pre-scan, find the 1Mbps of rate of 802.11b at middle channel is the worst case.</p> <p>Only the worst case is recorded in the report.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Test Results:          | Pass                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |