

# FCC Test Report

Report No.: AGC09566191201FE03

**FCC ID** : 2AVZYRC-101PLUS  
**APPLICATION PURPOSE** : Original Equipment  
**PRODUCT DESIGNATION** : Remote Control  
**BRAND NAME** : Maxkin  
**MODEL NAME** : RC-101 PLUS, RC-101  
**APPLICANT** : Maxkin Mobile Technology Co., Ltd.  
**DATE OF ISSUE** : Mar. 30, 2020  
**STANDARD(S)**  
**TEST PROCEDURE(S)** : FCC Part 15 Subpart C Section 15.231  
**REPORT VERSION** : V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

**CAUTION:**

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,  
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

### Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Mar. 30, 2020	Valid	Initial release



## TABLE OF CONTENTS

<b>1. VERIFICATION OF CONFORMITY .....</b>	<b>4</b>
<b>2. GENERAL INFORMATION .....</b>	<b>5</b>
2.1. PRODUCT DESCRIPTION .....	5
2.2. TEST METHODOLOGY .....	5
<b>3. MEASUREMENT UNCERTAINTY .....</b>	<b>6</b>
<b>4. DESCRIPTION OF TEST MODES .....</b>	<b>7</b>
<b>5. SYSTEM TEST CONFIGURATION .....</b>	<b>7</b>
5.1. CONFIGURATION OF EUT SYSTEM .....	7
5.2. EQUIPMENT USED IN EUT SYSTEM .....	7
5.3. SUMMARY OF TEST RESULTS .....	7
<b>6. TEST FACILITY .....</b>	<b>8</b>
<b>7. TEST EQUIPMENT LIST .....</b>	<b>8</b>
<b>8. PROVISION FOR MOMENTARY OPERATION .....</b>	<b>9</b>
8.1 MEASUREMENT PROCEDURE .....	9
8.2 TEST SETUP .....	9
8.3 TEST RESULT .....	10
<b>9. DUTY CYCLE CORRECTION FACTOR .....</b>	<b>13</b>
9.1 MEASUREMENT PROCEDURE .....	13
9.2 TEST SETUP .....	13
9.3 TEST RESULT .....	13
<b>10. RADIATED EMISSION .....</b>	<b>14</b>
10.1. MEASUREMENT PROCEDURE .....	14
10.2. TEST SETUP .....	16
10.3. TEST RESULT .....	17
<b>11. BANDWIDTH .....</b>	<b>23</b>
11.1. MEASUREMENT PROCEDURE .....	23
11.2. TEST SETUP .....	23
11.3. TEST RESULT .....	24
<b>APPENDIX B: PHOTOGRAPHS OF EUT .....</b>	<b>28</b>


## 1. VERIFICATION OF CONFORMITY

<b>Applicant</b>	Maxkin Mobile Technology Co., Ltd.
<b>Address</b>	Room 301, 3rd floor, NO.26 Laowei 1st Zone, Shuidoulaowei, Yousong Community, Longhua District, Shenzhen, China
<b>Manufacturer</b>	Maxkin Mobile Technology Co., Ltd.
<b>Address</b>	Room 301, 3rd floor, NO.26 Laowei 1st Zone, Shuidoulaowei, Yousong Community, Longhua District, Shenzhen, China
<b>Factory</b>	Maxkin Mobile Technology Co., Ltd.
<b>Address</b>	Room 301, 3rd floor, NO.26 Laowei 1st Zone, Shuidoulaowei, Yousong Community, Longhua District, Shenzhen, China
<b>Product Designation</b>	Remote Control
<b>Brand Name</b>	Maxkin
<b>Test Model</b>	RC-101 PLUS
<b>Series Model</b>	RC-101
<b>Difference Description</b>	All the same except for the model name
<b>Date of test</b>	Dec. 27, 2019 to Mar. 30, 2020
<b>Deviation</b>	No any deviation from the test method
<b>Condition of Test Sample</b>	Normal
<b>Test Result</b>	Pass
<b>Report Template</b>	AGCRT-US-BR/RF

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, the energy emitted by the sample tested as described in this report is in compliance with the requirements of FCC Rules Part 15.231. The test results of this report relate only to the tested sample identified in this report.


Prepared By



Sky Dong  
(Project Engineer)

Mar. 30, 2020

Reviewed By



Max Zhang  
(Reviewer)

Mar. 30, 2020

Approved By



Forrest Lei  
(Authorized Officer)

Mar. 30, 2020



## 2. GENERAL INFORMATION

### 2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

Operation Frequency	433.2MHz, 434.0MHz, 434.4MHz
Field Strength(3m)	79.77dBuV/m(Peak)@3m
Modulation	ASK
Number of channels	3
Hardware Version	V2.3
Software Version	V1.1
Antenna Designation	Integral antenna
Antenna Gain	3dBi
Power Supply	DC 3V

### 2.2. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013).

Radiated testing was performed at an antenna to EUT distance 3 meters.



### 3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95%.

- Uncertainty of Conducted Emission,  $U_c = \pm 3.2$  dB
- Uncertainty of Radiated Emission below 1GHz,  $U_c = \pm 3.9$  dB
- Uncertainty of Radiated Emission above 1GHz,  $U_c = \pm 4.8$  dB
- Uncertainty of Occupied Channel Bandwidth:  $U_c = \pm 2$  %



#### 4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Transmitting mode(Manual operated)

Note:  
1. All the test modes can be supply by new battery, and only the data of the worst case recorded in the test report.  
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.

#### 5. SYSTEM TEST CONFIGURATION

##### 5.1. CONFIGURATION OF EUT SYSTEM

Configure 1:



##### 5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Mfr/Brand	Model/Type No.	Remark
1	Remote Control	Maxkin	RC-101 PLUS	EUT

##### 5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.203	Antenna Requirement	Compliant
§15.231(a)(1)	Activated manually	Compliant
ANSI C63.10 Clause 7.5	Average Factor	N/A
§15.231(b) & §15.209	Field Strength of Fundamental and Spurious Emission	Compliant
§15.231(c)	Bandwidth	Compliant

## 6. TEST FACILITY

<b>Test Site</b>	Attestation of Global Compliance (Shenzhen) Co., Ltd
<b>Location</b>	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
<b>Designation Number</b>	CN1259
<b>FCC Test Firm Registration Number</b>	975832
<b>A2LA Cert. No.</b>	5054.02
<b>Description</b>	Attestation of Global Compliance(Shenzhen) Co., Ltd is accredited by A2LA

## 7. TEST EQUIPMENT LIST

### TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Jun. 12, 2019	Jun. 26, 2020
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Dec. 12, 2019	Dec. 11, 2020
Attenuator	ZHINAN	E-002	N/A	Aug. 26, 2019	Aug. 25, 2020
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	Jun. 14, 2018	Jun. 13, 2020
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	May. 26, 2018	May. 25, 2020
Broadband Preamplifier	ETS LINDGREN	3117PA	00225134	Oct. 15, 2019	Oct. 14, 2020
ANTENNA	SCHWARZBECK	VULB9168	494	Jan. 09, 2019	Jan. 08, 2021






## 8. PROVISION FOR MOMENTARY OPERATION

### 8.1 MEASUREMENT PROCEDURE

1. Set the parameters of SPA as below:  
Centre frequency = Operation Frequency  
RBW=1MHz, VBW=3MHz  
Span: 0Hz  
Sweep time: 10S
2. Set the EUT to transmit activated automatically. Use the “View” function of SPA to find the transmission time of being released.
3. Record the data and Reported.

### 8.2 TEST SETUP




### 8.3 TEST RESULT

Mode2(Manual operated):

Test Mode: EUT @ 433.2MHz for RF Transmitter

The time of stopping transmission	Limit (s)
1.478	5.00



RESULT: PASS



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,  
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China


Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

Test Mode: EUT @ 434.0MHz for RF Transmitter

The time of stopping transmission	Limit (s)
1.479	5.00



RESULT: PASS



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,  
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China


Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

Test Mode: EUT @ 433.4MHz for RF Transmitter

The time of stopping transmission	Limit (s)
1.478	5.00



RESULT: PASS



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,  
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118




## 9. DUTY CYCLE CORRECTION FACTOR

### 9.1 MEASUREMENT PROCEDURE

1. Set the parameters of SPA as below:  
Centre frequency = Operation Frequency  
RBW=1MHz; VBW=3MHz  
Span: 0Hz  
Sweep time: more than two pulse trains or more than each type of pulse occupancy time
2. Set the EUT to transmit by manually operated. Use the “Delta mark” function of SPA to find the period time between two pulse trains and each type of pulse occupancy time.
3. Record the plots and Reported.

### 9.2 TEST SETUP



### 9.3 TEST RESULT

Note: The level of the peak emission are less than the average limit, so the average factor need not to be tested.



## 10. RADIATED EMISSION

### 10.1. MEASUREMENT PROCEDURE

1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.



The following table is the setting of spectrum analyzer and receiver.


Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RBW 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RBW 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RBW 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/1MHz for Peak, 1MHz/10Hz for Average

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RBW 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RBW 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RBW 120KHz for QP




## 10.2. TEST SETUP


### Radiated Emission Test-Setup Frequency Below 30MHz



### RADIATED EMISSION TEST SETUP 30MHz-1000MHz



### RADIATED EMISSION TEST SETUP ABOVE 1000MHz






### 10.3. TEST RESULT

Test Mode: EUT @ 433.2MHz for RF Transmitter

#### RADIATED EMISSION BELOW 30MHz


No emission found between lowest internal used/generated frequencies to 30MHz.

#### RADIATED EMISSION BELOW 1GHZ-Horizontal



NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	40.6700	26.99	14.91	40.00	13.01	100	6	Horizontal
2	52.3100	30.87	14.49	40.00	9.13	100	358	Horizontal
3	66.8600	24.85	12.76	40.00	15.15	100	63	Horizontal
4	141.5500	21.58	14.88	43.50	21.92	100	273	Horizontal
5	271.5300	21.13	15.55	46.00	24.87	100	60	Horizontal
6	433.2000	79.77	20.61	80.80	1.03	100	193	Horizontal

### RADIATED EMISSION BELOW 1GHZ-Vertical



NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	36.7900	29.18	14.16	40.00	10.82	100	320	Vertical
2	44.5500	30.26	14.82	40.00	9.74	100	141	Vertical
3	52.3100	31.36	14.49	40.00	8.64	100	100	Vertical
4	78.5000	24.33	10.46	40.00	15.67	100	284	Vertical
5	139.6100	20.81	14.85	43.50	22.69	100	177	Vertical
6	433.2000	74.90	20.61	80.80	5.90	100	117	Vertical

### RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

3. Emissions of frequency range from 1GHz to 5GHz have 20dB margin. No recording in the test report.

4. Peak detector is used for radiation dispersion test.




**Test Mode: EUT @ 434.0MHz for RF Transmitter**

**RADIATED EMISSION BELOW 30MHz**


No emission found between lowest internal used/generated frequencies to 30MHz.

**RADIATED EMISSION BELOW 1GHZ-Horizontal**



NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	40.6700	25.27	14.91	40.00	14.73	100	17	Horizontal
2	52.3100	29.08	14.49	40.00	10.92	100	196	Horizontal
3	62.9800	26.31	13.42	40.00	13.69	100	136	Horizontal
4	141.5500	21.51	14.88	43.50	21.99	100	263	Horizontal
5	434.0000	78.97	20.63	80.83	1.86	100	200	Horizontal
6	768.1700	34.18	27.65	46.00	11.82	100	263	Horizontal

### RADIATED EMISSION BELOW 1GHZ-Vertical



NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	36.7900	26.99	14.16	40.00	13.01	100	67	Vertical
2	48.4300	33.96	14.71	40.00	6.04	100	1	Vertical
3	78.5000	24.42	10.46	40.00	15.58	100	280	Vertical
4	149.3100	21.06	14.88	43.50	22.44	100	17	Vertical
5	434.0000	72.17	20.63	80.83	8.66	100	117	Vertical
6	776.9000	33.84	27.86	46.00	12.16	100	180	Vertical

### RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

3. Emissions of frequency range from 1GHz to 5GHz have 20dB margin. No recording in the test report.

4. Peak detector is used for radiation dispersion test.




**Test Mode: EUT @ 434.4MHz for RF Transmitter**

**RADIATED EMISSION BELOW 30MHz**

No emission found between lowest internal used/generated frequencies to 30MHz.

**RADIATED EMISSION BELOW 1GHZ-Horizontal**



NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	40.6700	25.98	14.91	40.00	14.02	100	260	Horizontal
2	52.3100	30.67	14.49	40.00	9.33	100	163	Horizontal
3	66.8600	25.25	12.76	40.00	14.75	100	243	Horizontal
4	141.5500	21.40	14.88	43.50	22.10	100	250	Horizontal
5	434.4000	78.70	20.63	80.84	2.14	100	190	Horizontal
6	814.7300	35.07	28.74	46.00	10.93	100	316	Horizontal



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.


Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,  
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

# RADIATED EMISSION BELOW 1GHZ-Vertical



NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	36.7900	28.78	14.16	40.00	11.22	100	357	Vertical
2	48.4300	33.80	14.71	40.00	6.20	100	359	Vertical
3	82.3800	24.40	10.17	40.00	15.60	100	168	Vertical
4	131.8500	19.48	14.28	43.50	24.02	100	360	Vertical
5	434.4000	74.25	20.63	80.84	6.59	100	114	Vertical
6	696.3900	32.63	25.91	46.00	13.37	100	7	Vertical

## RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

3. Emissions of frequency range from 1GHz to 5GHz have 20dB margin. No recording in the test report.


4. Peak detector is used for radiation dispersion test.

## 11. BANDWIDTH

### 11.1. MEASUREMENT PROCEDURE

1. Set the parameters of SPA as below:  
Centre frequency = Operation Frequency  
RBW=10kHz  
VBW=30KHz  
Span: 500kHz  
Sweep time: Auto
2. Set the EUT to continue transmitting mode. Allow the trace to stabilize. Use the “N dB down” function of SPA to define the bandwidth.
3. Record the plots and Reported.


### 11.2. TEST SETUP



### 11.3. TEST RESULT

Test Mode: EUT @ 433.2MHz for RF Transmitter

-20dB bandwidth	LIMIT	RESULT
50.91kHz	1083.0KHz	Pass
Note: Limit= Operation Frequency x0.25%		



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,  
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088


E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118



Test Mode: EUT @ 434.0MHz for RF Transmitter

-20dB bandwidth	LIMIT	RESULT
50.66kHz	1085.0KHz	Pass
Note: Limit= Operation Frequency $\times$ 0.25%		



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,  
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China


Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

Test Mode: EUT @ 434.4MHz for RF Transmitter

-20dB bandwidth	LIMIT	RESULT
45.26kHz	1086.0KHz	Pass
Note: Limit= Operation Frequency $\times$ 0.25%		



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,  
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

**APPENDIX A: PHOTOGRAPHS OF TEST SETUP**  
**FCC RADIATED EMISSION TEST SETUP**



## APPENDIX B: PHOTOGRAPHS OF EUT

TOP VIEW OF EUT



BOTTOM VIEW OF EUT





FRONT VIEW OF EUT



BACK VIEW OF EUT





LEFT VIEW OF EUT



RIGHT VIEW OF EUT



**Attestation of Global Compliance**

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,  
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118



OPEN VIEW OF EUT-1




OPEN VIEW OF EUT-2






INTERNAL VIEW OF EUT-1




INTERNAL VIEW OF EUT-2






INTERNAL VIEW OF EUT-3




INTERNAL VIEW OF EUT-4






INTERNAL VIEW OF EUT-5



VIEW OF BATTERY



----END OF REPORT----