

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	Remote Control
Model Name	RC-101 PLUS, RC-101
FCC ID	2AVZYRC-101PLUS

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR.}$

Where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

433.2MHz:

$$P_t = -15.43 \text{ dBm} = 0.029 \text{ mW}$$

The value of the Maximum output power P_t is referred to the test report of the CFR47 §15.231.

The result for RF exposure evaluation $\text{SAR} = (0.029 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{0.4332(\text{GHz})}] = 0.0038 < 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR.}$

4. CONCLUSION

The SAR evaluation is not required.