



$\pi/4$ -DQPSK mode


Test channel:	2441MHz
---------------	---------



2DH1




2DH3



2DH5

8-DPSK

Test channel:	2441MHz
---------------	---------



3DH1




3DH3



3DH5

4.8 Band Edge

4.8.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)	
Test Method:	ANSI C63.10:2013	
Receiver setup:	RBW=100kHz, VBW=300kHz, Detector=Peak	
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.	
Test setup:	 The diagram illustrates the test setup for conducted emission measurement. A Spectrum Analyzer is connected via a red cable to an E.U.T (Equipment Under Test). Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.	
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 23.4°C	Humid.: 54%RH
Test voltage:	DC 3.7V	
Test results:	Pass	

Test plot as follows:

AC6976D Module

GFSK Mode:



$\pi/4$ -DQPSK Mode:



8-DPSK Mode:




AC6956C Module


GFSK Mode:

Test channel:

Lowest channel




No-hopping mode




Hopping mode

Test channel:

Highest channel



No-hopping mode



Hopping mode


$\pi/4$ -DQPSK Mode:



8-DPSK Mode:



4.8.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	Above 1GHz		54.00		Average Value
			74.00		Peak Value
Test setup:					
Test Procedure:	1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.				
Test Instruments:	Refer to section 3.0 for details				
Test mode:	Refer to section 2.2 for details				
Test environment:	Temp.: 23.4°C		Humid.: 54%RH		
Test voltage:	DC 3.7V				
Test results:	Pass				

Remark:

During the test, pre-scan the GFSK, $\pi/4$ -DQPSK, 8-DPSK modulation, and found the 8-DPSK modulation (two module operate simultaneously) which it is worse case.

Measurement Data

Test channel:	Lowest
---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	69.17	27.40	3.41	45.40	54.58	74.00	-19.42	Horizontal
2390.00	69.80	27.10	3.43	45.40	54.93	74.00	-19.07	Horizontal
2400.00	73.14	27.10	3.43	45.40	58.27	74.00	-15.73	Horizontal
2310.00	69.87	27.40	3.41	45.40	55.28	74.00	-18.72	Vertical
2390.00	72.06	27.10	3.43	45.40	57.19	74.00	-16.81	Vertical
2400.00	72.84	27.10	3.43	45.40	57.97	74.00	-16.03	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	49.95	27.40	3.41	45.40	35.36	54.00	-18.64	Horizontal
2390.00	50.95	27.10	3.43	45.40	36.08	54.00	-17.92	Horizontal
2400.00	53.47	27.10	3.43	45.40	38.60	54.00	-15.40	Horizontal
2310.00	49.32	27.40	3.41	45.40	34.73	54.00	-19.27	Vertical
2390.00	51.93	27.10	3.43	45.40	37.06	54.00	-16.94	Vertical
2400.00	55.42	27.10	3.43	45.40	40.55	54.00	-13.45	Vertical

Test channel:	Highest
---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	62.32	27.80	3.56	45.40	48.28	74.00	-25.72	Horizontal
2500.00	61.30	27.80	3.56	45.40	47.26	74.00	-26.74	Horizontal
2483.50	63.84	27.80	3.56	45.40	49.80	74.00	-24.20	Vertical
2500.00	60.22	27.80	3.56	45.40	46.18	74.00	-27.82	Vertical

Average value:


Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	53.71	27.80	3.56	45.40	39.67	54.00	-14.33	Horizontal
2500.00	51.51	27.80	3.56	45.40	37.47	54.00	-16.53	Horizontal
2483.50	53.79	27.80	3.56	45.40	39.75	54.00	-14.25	Vertical
2500.00	50.92	27.80	3.56	45.40	36.88	54.00	-17.12	Vertical

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.

4.9 Spurious Emission

4.9.1 Conducted Emission Method


Test Requirement:	FCC Part15 C Section 15.247 (d)	
Test Method:	ANSI C63.10:2013	
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.	
Test setup:	 The diagram illustrates the test setup for conducted emission measurement. A Spectrum Analyzer is connected via a red cable to an E.U.T (Equipment Under Test). Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.	
Test Instruments:	Refer to section 3.0 for details	
Test mode:	Refer to section 2.2 for details	
Test environment:	Temp.: 23.4°C	Humid.: 54%RH
Test voltage:	DC 3.7V	
Test results:	Pass	

AC6976D Module

GFSK mode:

Test channel:


Lowest channel



30MHz~25GHz

Test channel:


Middle channel



30MHz~25GHz

Test channel:

Highest channel




30MHz~25GHz

$\pi/4$ -DQPSK mode:

Test channel:


Lowest channel



30MHz~25GHz

Test channel:


Middle channel



30MHz~25GHz

Test channel:

Highest channel




30MHz~25GHz

8-DPSK mode:

Test channel:


Lowest channel



30MHz~25GHz

Test channel:


Middle channel



30MHz~25GHz

Test channel:

Highest channel




30MHz~25GHz

AC6956C Module

GFSK mode:

Test channel:


Lowest channel



30MHz~25GHz

Test channel:


Middle channel



30MHz~25GHz

Test channel:

Highest channel




30MHz~25GHz

$\pi/4$ -DQPSK mode:

Test channel:


Lowest channel



30MHz~25GHz

Test channel:


Middle channel



30MHz~25GHz

Test channel:

Highest channel




30MHz~25GHz

8-DPSK mode:

Test channel:


Lowest channel



30MHz~25GHz

Test channel:


Middle channel



30MHz~25GHz


Test channel:



Highest channel



30MHz~25GHz

4.9.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Limit (uV/m)		Value	Measurement Distance
	0.009MHz-0.490MHz	2400/F(KHz)		QP	300m
	0.490MHz-1.705MHz	24000/F(KHz)		QP	30m
	1.705MHz-30MHz	30		QP	30m
	30MHz-88MHz	100		QP	3m
	88MHz-216MHz	150		QP	
	216MHz-960MHz	200		QP	
	960MHz-1GHz	500		QP	
	Above 1GHz	500		Average	
		5000		Peak	
Test setup:	For radiated emissions from 9kHz to 30MHz				
					

	For radiated emissions from 30MHz to1GHz  For radiated emissions above 1GHz 					
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.					
Test Instruments:	Refer to section 3.0 for details					
Test mode:	Refer to section 2.2 for details					
Test environment:	Temp.:	23.8 °C	Humid.:	51%	Press.:	1012mbar
Test voltage:	DC 3.7V From battery					
Test results:	Pass					

Measurement data:

Remarks:

1. *During the test, pre-scan the GFSK, $\pi/4$ -DQPSK, 8-DPSK modulation, and found the 8-DPSK modulation (two module operate simultaneously) which it is worse case.*
2. *Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.*


■ **9kHz~30MHz**

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

■ Below 1GHz

Pre-scan all test modes, the report only shows the worst mode data, and the worst mode is two module operate simultaneously on 8-DPSK (2480MHz).

Vertical:




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	108.6470	53.01	-24.25	28.76	43.50	-14.74	QP
2	273.2341	59.41	-21.60	37.81	46.00	-8.19	QP
3	293.0842	59.93	-20.63	39.30	46.00	-6.70	QP
4	304.6099	56.60	-20.07	36.53	46.00	-9.47	QP
5	354.1831	53.47	-19.22	34.25	46.00	-11.75	QP
6	982.6200	34.22	-3.51	30.71	54.00	-23.29	QP

Level = Reading + Factor, Margin=level-Limit

Factor= Antenna Factor + Cable Loss – Preamplifier Factor

Horizontal:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	109.7960	53.16	-24.12	29.04	43.50	-14.46	QP
2	266.6089	64.53	-21.83	42.70	46.00	-3.30	QP
3	300.3672	62.64	-20.24	42.40	46.00	-3.60	QP
4	352.9433	61.56	-19.27	42.29	46.00	-3.71	QP
5	473.8346	49.15	-15.53	33.62	46.00	-12.38	QP
6	614.2142	46.72	-11.15	35.57	46.00	-10.43	QP

Level = Reading + Factor, Margin=level-Limit

Factor= Antenna Factor + Cable Loss – Preamplifier Factor

■ Above 1GHz

Test channel:	Lowest
---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	55.04	32.10	5.96	45.70	47.40	74.00	-26.60	Vertical
7206.00	51.07	36.10	6.86	45.50	48.53	74.00	-25.47	Vertical
9608.00	50.44	38.30	8.25	46.20	50.79	74.00	-23.21	Vertical
12010.00	*	--	--	--	--	74.00	--	Vertical
14412.00	*	--	--	--	--	74.00	--	Vertical
4804.00	57.66	32.10	5.96	45.70	50.02	74.00	-23.98	Horizontal
7206.00	52.67	36.10	6.86	45.50	50.13	74.00	-23.87	Horizontal
9608.00	52.10	38.30	8.25	46.20	52.45	74.00	-21.55	Horizontal
12010.00	*	--	--	--	--	74.00	--	Horizontal
14412.00	*	--	--	--	--	74.00	--	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	47.94	32.10	5.96	45.70	40.30	54.00	-13.70	Vertical
7206.00	42.12	36.10	6.86	45.50	39.58	54.00	-14.42	Vertical
9608.00	41.10	38.30	8.25	46.20	41.45	54.00	-12.55	Vertical
12010.00	*	--	--	--	--	54.00	--	Vertical
14412.00	*	--	--	--	--	54.00	--	Vertical
4804.00	48.53	32.10	5.96	45.70	40.89	54.00	-13.11	Horizontal
7206.00	42.23	36.10	6.86	45.50	39.69	54.00	-14.31	Horizontal
9608.00	40.49	38.30	8.25	46.20	40.84	54.00	-13.16	Horizontal
12010.00	*	--	--	--	--	54.00	--	Horizontal
14412.00	*	--	--	--	--	54.00	--	Horizontal

Test channel:	Middle
---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	55.38	32.10	5.96	45.70	47.74	74.00	-26.26	Vertical
7323.00	50.44	36.80	6.86	45.50	48.60	74.00	-25.40	Vertical
9764.00	49.04	38.40	8.25	46.20	49.49	74.00	-24.51	Vertical
12205.00	*	--	--	--	--	74.00	--	Vertical
14646.00	*	--	--	--	--	74.00	--	Vertical
4882.00	56.52	32.10	5.96	45.70	48.88	74.00	-25.12	Horizontal
7323.00	52.72	36.80	6.86	45.50	50.88	74.00	-23.12	Horizontal
9764.00	49.99	38.40	8.25	46.20	50.44	74.00	-23.56	Horizontal
12205.00	*	--	--	--	--	74.00	--	Horizontal
14646.00	*	--	--	--	--	74.00	--	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	43.70	32.10	5.96	45.70	36.06	54.00	-17.94	Vertical
7323.00	42.22	36.80	6.86	45.50	40.38	54.00	-13.62	Vertical
9764.00	40.67	38.40	8.25	46.20	41.12	54.00	-12.88	Vertical
12205.00	*	--	--	--	--	54.00	--	Vertical
14646.00	*	--	--	--	--	54.00	--	Vertical
4882.00	44.12	32.10	5.96	45.70	36.48	54.00	-17.52	Horizontal
7323.00	41.00	36.80	6.86	45.50	39.16	54.00	-14.84	Horizontal
9764.00	40.18	38.40	8.25	46.20	40.63	54.00	-13.37	Horizontal
12205.00	*	--	--	--	--	54.00	--	Horizontal
14646.00	*	--	--	--	--	54.00	--	Horizontal

Test channel:	Highest
---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	55.79	32.70	5.96	45.70	48.75	74.00	-25.25	Vertical
7440.00	49.20	36.40	6.86	45.50	46.96	74.00	-27.04	Vertical
9920.00	48.84	38.00	8.25	46.20	48.89	74.00	-25.11	Vertical
12400.00	*	--	--	--	--	74.00	--	Vertical
14880.00	*	--	--	--	--	74.00	--	Vertical
4960.00	55.80	32.70	5.96	45.70	48.76	74.00	-25.24	Horizontal
7440.00	51.61	36.40	6.86	45.50	49.37	74.00	-24.63	Horizontal
9920.00	50.82	38.00	8.25	46.20	50.87	74.00	-23.13	Horizontal
12400.00	*	--	--	--	--	74.00	--	Horizontal
14880.00	*	--	--	--	--	74.00	--	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	41.96	32.70	5.96	45.70	34.92	54.00	-19.08	Vertical
7440.00	38.09	36.40	6.86	45.50	35.85	54.00	-18.15	Vertical
9920.00	38.97	38.00	8.25	46.20	39.02	54.00	-14.98	Vertical
12400.00	*	--	--	--	--	54.00	--	Vertical
14880.00	*	--	--	--	--	54.00	--	Vertical
4960.00	43.10	32.70	5.96	45.70	36.06	54.00	-17.94	Horizontal
7440.00	38.13	36.40	6.86	45.50	35.89	54.00	-18.11	Horizontal
9920.00	38.29	38.00	8.25	46.20	38.34	54.00	-15.66	Horizontal
12400.00	*	--	--	--	--	54.00		Horizontal
14880.00	*	--	--	--	--	54.00		Horizontal

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

5 Test Setup Photo

Reference to the **appendix I** for details.

6 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----