

Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11n(HT40) Mode 5190MHz (U-NII-1) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11n(HT40) Mode 5190MHz (U-NII-1) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11n(HT40) Mode 5230MHz (U-NII-1) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11n(HT40) Mode 5230MHz (U-NII-1) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ac(VHT40) Mode 5190MHz (U-NII-1) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ac(VHT40) Mode 5190MHz (U-NII-1) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11ac(VHT40) Mode 5230MHz (U-NII-1) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11ac(VHT40) Mode 5230MHz (U-NII-1) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11 ax(HE40) Mode 5190MHz (U-NII-1) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11 ax(HE40) Mode 5190MHz (U-NII-1) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11ax(HE40) Mode 5230MHz (U-NII-1) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11ax(HE40) Mode 5230MHz (U-NII-1) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ac(VHT80) Mode 5210MHz (U-NII-1) -CDD		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	10420.432	40.28	6.25	46.53	54.00	-7.47	AVG	P
2	10420.541	51.21	6.25	57.46	68.30	-10.84	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ac(VHT80) Mode 5210MHz (U-NII-1) -CDD		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	10420.112	40.97	6.25	47.22	54.00	-6.78	AVG	P
2	10420.322	50.73	6.25	56.98	68.30	-11.32	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11ax(HE80) Mode 5210MHz (U-NII-1) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11ax(HE80) Mode 5210MHz (U-NII-1) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



5250MHz-5320MHz(U-NII-2A)

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11a Mode 5260MHz (U-NII-2A) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11a Mode 5260MHz (U-NII-2A) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11a Mode 5280MHz (U-NII-2A) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11a Mode 5280MHz (U-NII-2A) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	26°C		Relative Humidity:	54%										
Test Voltage:	AC 120V/60Hz													
Ant. Pol.	Horizontal													
Test Mode:	TX 802.11a Mode 5320MHz (U-NII-2A) -CDD													
Remark:														
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)														
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)														
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)														
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.														
5. No report for the emission which more than 20dB below the prescribed limit.														

Temperature:	26°C		Relative Humidity:	54%										
Test Voltage:	AC 120V/60Hz													
Ant. Pol.	Vertical													
Test Mode:	TX 802.11a Mode 5320MHz (U-NII-2A) -CDD													
Remark:														
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)														
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)														
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)														
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.														
5. No report for the emission which more than 20dB below the prescribed limit.														



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11n(HT20) Mode 5260MHz (U-NII-2A) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11n(HT20) Mode 5260MHz (U-NII-2A) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C	Relative Humidity:	54%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Horizontal																													
Test Mode:	TX 802.11n(HT20) Mode 5280MHz (U-NII-2A) -CDD																													
<table border="1"> <thead> <tr> <th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr> </thead> <tbody> <tr> <td>1 *</td><td>10560.368</td><td>40.14</td><td>6.39</td><td>46.53</td><td>54.00</td><td>-7.47</td><td>AVG</td><td>P</td></tr> <tr> <td>2</td><td>10560.584</td><td>51.43</td><td>6.39</td><td>57.82</td><td>68.30</td><td>-10.48</td><td>peak</td><td>P</td></tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	10560.368	40.14	6.39	46.53	54.00	-7.47	AVG	P	2	10560.584	51.43	6.39	57.82	68.30	-10.48	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1 *	10560.368	40.14	6.39	46.53	54.00	-7.47	AVG	P																						
2	10560.584	51.43	6.39	57.82	68.30	-10.48	peak	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														

Temperature:	26°C	Relative Humidity:	54%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Vertical																													
Test Mode:	TX 802.11n(HT20) Mode 5280MHz (U-NII-2A) -CDD																													
<table border="1"> <thead> <tr> <th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr> </thead> <tbody> <tr> <td>1</td><td>10560.462</td><td>52.57</td><td>6.39</td><td>58.96</td><td>68.30</td><td>-9.34</td><td>peak</td><td>P</td></tr> <tr> <td>2 *</td><td>10560.742</td><td>42.13</td><td>6.39</td><td>48.52</td><td>54.00</td><td>-5.48</td><td>AVG</td><td>P</td></tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1	10560.462	52.57	6.39	58.96	68.30	-9.34	peak	P	2 *	10560.742	42.13	6.39	48.52	54.00	-5.48	AVG	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1	10560.462	52.57	6.39	58.96	68.30	-9.34	peak	P																						
2 *	10560.742	42.13	6.39	48.52	54.00	-5.48	AVG	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														



Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11n(HT20) Mode 5320MHz (U-NII-2A) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11n(HT20) Mode 5320MHz (U-NII-2A) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	26°C	Relative Humidity:	54%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Horizontal																													
Test Mode:	TX 802.11ac(VHT20) Mode 5260MHz (U-NII-2A) -CDD																													
<table border="1"> <thead> <tr> <th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr> </thead> <tbody> <tr> <td>1</td><td>10520.113</td><td>50.71</td><td>6.40</td><td>57.11</td><td>68.30</td><td>-11.19</td><td>peak</td><td>P</td></tr> <tr> <td>2 *</td><td>10520.237</td><td>40.96</td><td>6.40</td><td>47.36</td><td>54.00</td><td>-6.64</td><td>AVG</td><td>P</td></tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1	10520.113	50.71	6.40	57.11	68.30	-11.19	peak	P	2 *	10520.237	40.96	6.40	47.36	54.00	-6.64	AVG	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1	10520.113	50.71	6.40	57.11	68.30	-11.19	peak	P																						
2 *	10520.237	40.96	6.40	47.36	54.00	-6.64	AVG	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														

Temperature:	26°C	Relative Humidity:	54%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Vertical																													
Test Mode:	TX 802.11ac(VHT20) Mode 5260MHz (U-NII-2A) -CDD																													
<table border="1"> <thead> <tr> <th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr> </thead> <tbody> <tr> <td>1</td><td>10520.566</td><td>50.82</td><td>6.40</td><td>57.22</td><td>68.30</td><td>-11.08</td><td>peak</td><td>P</td></tr> <tr> <td>2 *</td><td>10520.654</td><td>40.18</td><td>6.39</td><td>46.57</td><td>54.00</td><td>-7.43</td><td>AVG</td><td>P</td></tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1	10520.566	50.82	6.40	57.22	68.30	-11.08	peak	P	2 *	10520.654	40.18	6.39	46.57	54.00	-7.43	AVG	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1	10520.566	50.82	6.40	57.22	68.30	-11.08	peak	P																						
2 *	10520.654	40.18	6.39	46.57	54.00	-7.43	AVG	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ac(VHT20) Mode 5280MHz (U-NII-2A) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ac(VHT20) Mode 5280MHz (U-NII-2A) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11 ac(VHT20) Mode 5320MHz (U-NII-2A) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11ac(VHT20) Mode 5320MHz (U-NII-2A) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	26°C	Relative Humidity:	54%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Horizontal																													
Test Mode:	TX 802.11ax(HE20) Mode 5260MHz (U-NII-2A) -CDD																													
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>10520.634</td> <td>40.76</td> <td>6.39</td> <td>47.15</td> <td>54.00</td> <td>-6.85</td> <td>AVG</td> <td>P</td> </tr> <tr> <td>2</td> <td>10520.652</td> <td>50.83</td> <td>6.39</td> <td>57.22</td> <td>68.30</td> <td>-11.08</td> <td>peak</td> <td>P</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	10520.634	40.76	6.39	47.15	54.00	-6.85	AVG	P	2	10520.652	50.83	6.39	57.22	68.30	-11.08	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1 *	10520.634	40.76	6.39	47.15	54.00	-6.85	AVG	P																						
2	10520.652	50.83	6.39	57.22	68.30	-11.08	peak	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m) = Corr. (dB/m) + Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m) - Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														

Temperature:	26°C	Relative Humidity:	54%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Vertical																													
Test Mode:	TX 802.11ax(HE20) Mode 5260MHz (U-NII-2A) -CDD																													
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>10520.127</td> <td>41.13</td> <td>6.40</td> <td>47.53</td> <td>54.00</td> <td>-6.47</td> <td>AVG</td> <td>P</td> </tr> <tr> <td>2</td> <td>10520.257</td> <td>50.08</td> <td>6.40</td> <td>56.48</td> <td>68.30</td> <td>-11.82</td> <td>peak</td> <td>P</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	10520.127	41.13	6.40	47.53	54.00	-6.47	AVG	P	2	10520.257	50.08	6.40	56.48	68.30	-11.82	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1 *	10520.127	41.13	6.40	47.53	54.00	-6.47	AVG	P																						
2	10520.257	50.08	6.40	56.48	68.30	-11.82	peak	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m) = Corr. (dB/m) + Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m) - Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														



Temperature:	26°C		Relative Humidity:	54%																															
Test Voltage:	AC 120V/60Hz																																		
Ant. Pol.	Horizontal																																		
Test Mode:	TX 802.11ax(HE20) Mode 5280MHz (U-NII-2A) -CDD																																		
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>10560.465</td> <td>50.54</td> <td>6.39</td> <td>56.93</td> <td>68.30</td> <td>-11.37</td> <td>peak</td> <td>P</td> </tr> <tr> <td>2 *</td> <td>10560.564</td> <td>41.13</td> <td>6.39</td> <td>47.52</td> <td>54.00</td> <td>-6.48</td> <td>AVG</td> <td>P</td> </tr> </tbody> </table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1	10560.465	50.54	6.39	56.93	68.30	-11.37	peak	P	2 *	10560.564	41.13	6.39	47.52	54.00	-6.48	AVG	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																											
1	10560.465	50.54	6.39	56.93	68.30	-11.37	peak	P																											
2 *	10560.564	41.13	6.39	47.52	54.00	-6.48	AVG	P																											
Remark: <ol style="list-style-type: none"> 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV) 3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit. 																																			

Temperature:	26°C		Relative Humidity:	54%																															
Test Voltage:	AC 120V/60Hz																																		
Ant. Pol.	Vertical																																		
Test Mode:	TX 802.11ax(HE20) Mode 5280MHz (U-NII-2A) -CDD																																		
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>10560.167</td> <td>51.80</td> <td>6.39</td> <td>58.19</td> <td>68.30</td> <td>-10.11</td> <td>peak</td> <td>P</td> </tr> <tr> <td>2 *</td> <td>10560.456</td> <td>40.97</td> <td>6.39</td> <td>47.36</td> <td>54.00</td> <td>-6.64</td> <td>AVG</td> <td>P</td> </tr> </tbody> </table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1	10560.167	51.80	6.39	58.19	68.30	-10.11	peak	P	2 *	10560.456	40.97	6.39	47.36	54.00	-6.64	AVG	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																											
1	10560.167	51.80	6.39	58.19	68.30	-10.11	peak	P																											
2 *	10560.456	40.97	6.39	47.36	54.00	-6.64	AVG	P																											
Remark: <ol style="list-style-type: none"> 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV) 3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit. 																																			



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ax(HE20) Mode 5320MHz (U-NII-2A) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ax(HE20) Mode 5320MHz (U-NII-2A) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11n(HT40) Mode 5270MHz (U-NII-2A) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11n(HT40) Mode 5270MHz (U-NII-2A) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11n(HT40) Mode 5310MHz (U-NII-2A) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11n(HT40) Mode 5310MHz (U-NII-2A) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11ac(VHT40) Mode 5270MHz (U-NII-2A) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11ac(VHT40) Mode 5270MHz (U-NII-2A) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11ac(VHT40) Mode 5310MHz (U-NII-2A) -CDD												
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F					
1 *	10620.124	39.89	6.50	46.39	54.00	-7.61	AVG	P					
2	10620.685	50.87	6.51	57.38	68.30	-10.92	peak	P					
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11ac(VHT40) Mode 5310MHz (U-NII-2A) -CDD												
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F					
1	10620.635	51.12	6.50	57.62	68.30	-10.68	peak	P					
2 *	10620.635	39.87	6.50	46.37	54.00	-7.63	AVG	P					
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	26 °C	Relative Humidity:	54%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Horizontal																													
Test Mode:	TX 802.11ax(HE40) Mode 5270MHz (U-NII-2A) -CDD																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>10540.641</td> <td>40.13</td> <td>6.39</td> <td>46.52</td> <td>54.00</td> <td>-7.48</td> <td>AVG</td> <td>P</td> </tr> <tr> <td>2</td> <td>10540.821</td> <td>49.96</td> <td>6.39</td> <td>56.35</td> <td>68.30</td> <td>-11.95</td> <td>peak</td> <td>P</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	10540.641	40.13	6.39	46.52	54.00	-7.48	AVG	P	2	10540.821	49.96	6.39	56.35	68.30	-11.95	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1 *	10540.641	40.13	6.39	46.52	54.00	-7.48	AVG	P																						
2	10540.821	49.96	6.39	56.35	68.30	-11.95	peak	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m) = Corr. (dB/m) + Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m) - Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														

Temperature:	26 °C	Relative Humidity:	54%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Vertical																													
Test Mode:	TX 802.11ax(HE40) Mode 5270MHz (U-NII-2A) -CDD																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>10540.245</td> <td>49.74</td> <td>6.39</td> <td>56.13</td> <td>68.30</td> <td>-12.17</td> <td>peak</td> <td>P</td> </tr> <tr> <td>2 *</td> <td>10540.782</td> <td>39.37</td> <td>6.39</td> <td>45.76</td> <td>54.00</td> <td>-8.24</td> <td>AVG</td> <td>P</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1	10540.245	49.74	6.39	56.13	68.30	-12.17	peak	P	2 *	10540.782	39.37	6.39	45.76	54.00	-8.24	AVG	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1	10540.245	49.74	6.39	56.13	68.30	-12.17	peak	P																						
2 *	10540.782	39.37	6.39	45.76	54.00	-8.24	AVG	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m) = Corr. (dB/m) + Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m) - Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ax(HE40) Mode 5310MHz (U-NII-2A) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ax(HE40) Mode 5310MHz (U-NII-2A) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ac(VHT80) Mode 5290MHz (U-NII-2A) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ac(VHT80) Mode 5290MHz (U-NII-2A) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ax(HE80) Mode 5290MHz (U-NII-2A) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ax(HE80) Mode 5290MHz (U-NII-2A) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ac(VHT160) Mode 5250MHz (U-NII-2A) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ac(VHT160) Mode 5250MHz (U-NII-2A) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ax(HE160) Mode 5250MHz (U-NII-2A) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ax(HE160) Mode 5250MHz (U-NII-2A) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



5500MHz-5720MHz(U-NII-2C)

Temperature:	26°C	Relative Humidity:	54%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Horizontal																													
Test Mode:	TX 802.11a Mode 5500MHz (U-NII-2C) -CDD																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>11000.124</td> <td>39.36</td> <td>8.17</td> <td>47.53</td> <td>54.00</td> <td>-6.47</td> <td>AVG</td> <td>P</td> </tr> <tr> <td>2</td> <td>11000.351</td> <td>50.45</td> <td>8.17</td> <td>58.62</td> <td>68.30</td> <td>-9.68</td> <td>peak</td> <td>P</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	11000.124	39.36	8.17	47.53	54.00	-6.47	AVG	P	2	11000.351	50.45	8.17	58.62	68.30	-9.68	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1 *	11000.124	39.36	8.17	47.53	54.00	-6.47	AVG	P																						
2	11000.351	50.45	8.17	58.62	68.30	-9.68	peak	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														

Temperature:	26°C	Relative Humidity:	54%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Vertical																													
Test Mode:	TX 802.11a Mode 5500MHz (U-NII-2C) -CDD																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>11000.231</td> <td>39.06</td> <td>8.17</td> <td>47.23</td> <td>54.00</td> <td>-6.77</td> <td>AVG</td> <td>P</td> </tr> <tr> <td>2</td> <td>11000.521</td> <td>48.08</td> <td>8.17</td> <td>56.25</td> <td>68.30</td> <td>-12.05</td> <td>peak</td> <td>P</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	11000.231	39.06	8.17	47.23	54.00	-6.77	AVG	P	2	11000.521	48.08	8.17	56.25	68.30	-12.05	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1 *	11000.231	39.06	8.17	47.23	54.00	-6.77	AVG	P																						
2	11000.521	48.08	8.17	56.25	68.30	-12.05	peak	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														



Temperature:	26 °C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11a Mode 5580MHz (U-NII-2C) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	26 °C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11a Mode 5580MHz (U-NII-2C) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11a Mode 5700MHz (U-NII-2C) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11a Mode 5700MHz (U-NII-2C) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11a Mode 5720MHz (U-NII-2C) -CDD		

No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F
1 *	11440.224	38.54	8.99	47.53	54.00	-6.47	AVG	P
2	11440.311	47.25	8.99	56.24	68.30	-12.06	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11a Mode 5720MHz (U-NII-2C) -CDD		

No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F
1 *	11440.441	37.59	8.99	46.58	54.00	-7.42	AVG	P
2	11440.625	48.13	8.99	57.12	68.30	-11.18	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11n(HT20) Mode 5500MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11 n(HT20) Mode 5500MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11n(HT20) Mode 5580MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m) = Corr. (dB/m) + Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m) - Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11n(HT20) Mode 5580MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m) = Corr. (dB/m) + Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m) - Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C		Relative Humidity:	54%							
Test Voltage:	AC 120V/60Hz										
Ant. Pol.	Horizontal										
Test Mode:	TX 802.11n(HT20) Mode 5700MHz (U-NII-2C) -CDD										
Remark:	<ol style="list-style-type: none">1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.5. No report for the emission which more than 20dB below the prescribed limit.										

Temperature:	26°C		Relative Humidity:	54%							
Test Voltage:	AC 120V/60Hz										
Ant. Pol.	Vertical										
Test Mode:	TX 802.11n(HT20) Mode 5700MHz (U-NII-2C) -CDD										
Remark:	<ol style="list-style-type: none">1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.5. No report for the emission which more than 20dB below the prescribed limit.										



Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11n(HT20) Mode 5720MHz (U-NII-2C) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11n(HT20) Mode 5720MHz (U-NII-2C) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	26°C		Relative Humidity:		54%																														
Test Voltage:	AC 120V/60Hz																																		
Ant. Pol.	Horizontal																																		
Test Mode:	TX 802.11ac(VHT20) Mode 5500MHz (U-NII-2C) -CDD																																		
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dB_uV)</th> <th>Factor (dB/m)</th> <th>Level (dB_uV/m)</th> <th>Limit (dB_uV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>11000.113</td> <td>48.11</td> <td>8.17</td> <td>56.28</td> <td>68.30</td> <td>-12.02</td> <td>peak</td> <td>P</td> </tr> <tr> <td>2 *</td> <td>11000.531</td> <td>39.36</td> <td>8.17</td> <td>47.53</td> <td>54.00</td> <td>-6.47</td> <td>AVG</td> <td>P</td> </tr> </tbody> </table>									No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F	1	11000.113	48.11	8.17	56.28	68.30	-12.02	peak	P	2 *	11000.531	39.36	8.17	47.53	54.00	-6.47	AVG	P
No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F																											
1	11000.113	48.11	8.17	56.28	68.30	-12.02	peak	P																											
2 *	11000.531	39.36	8.17	47.53	54.00	-6.47	AVG	P																											
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB _u V/m)= Corr. (dB/m)+ Read Level (dB _u V) 3. Margin (dB) = Peak/AVG (dB _u V/m)-Limit PK/AVG(dB _u V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																																			

Temperature:	26°C		Relative Humidity:		54%																														
Test Voltage:	AC 120V/60Hz																																		
Ant. Pol.	Vertical																																		
Test Mode:	TX 802.11 ac(VHT20) Mode 5500MHz (U-NII-2C) -CDD																																		
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dB_uV)</th> <th>Factor (dB/m)</th> <th>Level (dB_uV/m)</th> <th>Limit (dB_uV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>11000.567</td> <td>38.41</td> <td>8.17</td> <td>46.58</td> <td>54.00</td> <td>-7.42</td> <td>AVG</td> <td>P</td> </tr> <tr> <td>2</td> <td>11000.771</td> <td>48.65</td> <td>8.17</td> <td>56.82</td> <td>68.30</td> <td>-11.48</td> <td>peak</td> <td>P</td> </tr> </tbody> </table>									No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F	1 *	11000.567	38.41	8.17	46.58	54.00	-7.42	AVG	P	2	11000.771	48.65	8.17	56.82	68.30	-11.48	peak	P
No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F																											
1 *	11000.567	38.41	8.17	46.58	54.00	-7.42	AVG	P																											
2	11000.771	48.65	8.17	56.82	68.30	-11.48	peak	P																											
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB _u V/m)= Corr. (dB/m)+ Read Level (dB _u V) 3. Margin (dB) = Peak/AVG (dB _u V/m)-Limit PK/AVG(dB _u V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																																			



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11 ac(VHT20) Mode 5580MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11 ac(VHT20) Mode 5580MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C	Relative Humidity:	54%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Horizontal																													
Test Mode:	TX 802.11 ac(VHT20) Mode 5700MHz (U-NII-2C) -CDD																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBμV)</th> <th>Factor (dB/m)</th> <th>Level (dBμV/m)</th> <th>Limit (dBμV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>11400.355</td> <td>37.54</td> <td>8.98</td> <td>46.52</td> <td>54.00</td> <td>-7.48</td> <td>AVG</td> <td>P</td> </tr> <tr> <td>2</td> <td>11400.412</td> <td>47.74</td> <td>8.98</td> <td>56.72</td> <td>68.30</td> <td>-11.58</td> <td>peak</td> <td>P</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F	1 *	11400.355	37.54	8.98	46.52	54.00	-7.48	AVG	P	2	11400.412	47.74	8.98	56.72	68.30	-11.58	peak	P
No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F																						
1 *	11400.355	37.54	8.98	46.52	54.00	-7.48	AVG	P																						
2	11400.412	47.74	8.98	56.72	68.30	-11.58	peak	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														

Temperature:	26°C	Relative Humidity:	54%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Vertical																													
Test Mode:	TX 802.11 ac(VHT20) Mode 5700MHz (U-NII-2C) -CDD																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBμV)</th> <th>Factor (dB/m)</th> <th>Level (dBμV/m)</th> <th>Limit (dBμV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>11400.557</td> <td>47.73</td> <td>8.98</td> <td>56.71</td> <td>68.30</td> <td>-11.59</td> <td>peak</td> <td>P</td> </tr> <tr> <td>2 *</td> <td>11400.634</td> <td>38.34</td> <td>8.98</td> <td>47.32</td> <td>54.00</td> <td>-6.68</td> <td>AVG</td> <td>P</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F	1	11400.557	47.73	8.98	56.71	68.30	-11.59	peak	P	2 *	11400.634	38.34	8.98	47.32	54.00	-6.68	AVG	P
No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F																						
1	11400.557	47.73	8.98	56.71	68.30	-11.59	peak	P																						
2 *	11400.634	38.34	8.98	47.32	54.00	-6.68	AVG	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11 ac(VHT20) Mode 5720MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11 ac(VHT20) Mode 5720MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C	Relative Humidity:	54%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Horizontal																													
Test Mode:	TX 802.11 ax(HE20) Mode 5500MHz (U-NII-2C) -CDD																													
<table border="1"> <thead> <tr> <th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr> </thead> <tbody> <tr> <td>1 *</td><td>11000.468</td><td>38.39</td><td>8.17</td><td>46.56</td><td>54.00</td><td>-7.44</td><td>AVG</td><td>P</td></tr> <tr> <td>2</td><td>11000.567</td><td>49.37</td><td>8.17</td><td>57.54</td><td>68.30</td><td>-10.76</td><td>peak</td><td>P</td></tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	11000.468	38.39	8.17	46.56	54.00	-7.44	AVG	P	2	11000.567	49.37	8.17	57.54	68.30	-10.76	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1 *	11000.468	38.39	8.17	46.56	54.00	-7.44	AVG	P																						
2	11000.567	49.37	8.17	57.54	68.30	-10.76	peak	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														

Temperature:	26°C	Relative Humidity:	54%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Vertical																													
Test Mode:	TX 802.11 ax(HE20) Mode 5500MHz (U-NII-2C) -CDD																													
<table border="1"> <thead> <tr> <th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr> </thead> <tbody> <tr> <td>1</td><td>11000.138</td><td>48.61</td><td>8.17</td><td>56.78</td><td>68.30</td><td>-11.52</td><td>peak</td><td>P</td></tr> <tr> <td>2 *</td><td>11000.256</td><td>39.39</td><td>8.17</td><td>47.56</td><td>54.00</td><td>-6.44</td><td>AVG</td><td>P</td></tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1	11000.138	48.61	8.17	56.78	68.30	-11.52	peak	P	2 *	11000.256	39.39	8.17	47.56	54.00	-6.44	AVG	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1	11000.138	48.61	8.17	56.78	68.30	-11.52	peak	P																						
2 *	11000.256	39.39	8.17	47.56	54.00	-6.44	AVG	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														



Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11 ax(HE20) Mode 5580MHz (U-NII-2C) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11 ax(HE20) Mode 5580MHz (U-NII-2C) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	26°C	Relative Humidity:	54%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Horizontal																													
Test Mode:	TX 802.11 ax(HE20) Mode 5700MHz (U-NII-2C) -CDD																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBμV)</th> <th>Factor (dB/m)</th> <th>Level (dBμV/m)</th> <th>Limit (dBμV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>11400.118</td> <td>47.47</td> <td>8.98</td> <td>56.45</td> <td>68.30</td> <td>-11.85</td> <td>peak</td> <td>P</td> </tr> <tr> <td>2 *</td> <td>11400.127</td> <td>38.27</td> <td>8.98</td> <td>47.25</td> <td>54.00</td> <td>-6.75</td> <td>AVG</td> <td>P</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F	1	11400.118	47.47	8.98	56.45	68.30	-11.85	peak	P	2 *	11400.127	38.27	8.98	47.25	54.00	-6.75	AVG	P
No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F																						
1	11400.118	47.47	8.98	56.45	68.30	-11.85	peak	P																						
2 *	11400.127	38.27	8.98	47.25	54.00	-6.75	AVG	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														

Temperature:	26°C	Relative Humidity:	54%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Vertical																													
Test Mode:	TX 802.11 ax(HE20) Mode 5700MHz (U-NII-2C) -CDD																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBμV)</th> <th>Factor (dB/m)</th> <th>Level (dBμV/m)</th> <th>Limit (dBμV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>11400.574</td> <td>38.58</td> <td>8.98</td> <td>47.56</td> <td>54.00</td> <td>-6.44</td> <td>AVG</td> <td>P</td> </tr> <tr> <td>2</td> <td>11400.652</td> <td>48.14</td> <td>8.98</td> <td>57.12</td> <td>68.30</td> <td>-11.18</td> <td>peak</td> <td>P</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F	1 *	11400.574	38.58	8.98	47.56	54.00	-6.44	AVG	P	2	11400.652	48.14	8.98	57.12	68.30	-11.18	peak	P
No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F																						
1 *	11400.574	38.58	8.98	47.56	54.00	-6.44	AVG	P																						
2	11400.652	48.14	8.98	57.12	68.30	-11.18	peak	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														



Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11 ax(HE20) Mode 5720MHz (U-NII-2C) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11 ax(HE20) Mode 5720MHz (U-NII-2C) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11n(HT40) Mode 5510MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11n(HT40) Mode 5510MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C		Relative Humidity:	54%																															
Test Voltage:	AC 120V/60Hz																																		
Ant. Pol.	Horizontal																																		
Test Mode:	TX 802.11n(HT40) Mode 5550MHz (U-NII-2C) -CDD																																		
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBμV)</th> <th>Factor (dB/m)</th> <th>Level (dBμV/m)</th> <th>Limit (dBμV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>11100.247</td> <td>49.59</td> <td>7.76</td> <td>57.35</td> <td>68.30</td> <td>-10.95</td> <td>peak</td> <td>P</td> </tr> <tr> <td>2 *</td> <td>11100.352</td> <td>40.61</td> <td>7.76</td> <td>48.37</td> <td>54.00</td> <td>-5.63</td> <td>AVG</td> <td>P</td> </tr> </tbody> </table>									No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F	1	11100.247	49.59	7.76	57.35	68.30	-10.95	peak	P	2 *	11100.352	40.61	7.76	48.37	54.00	-5.63	AVG	P
No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F																											
1	11100.247	49.59	7.76	57.35	68.30	-10.95	peak	P																											
2 *	11100.352	40.61	7.76	48.37	54.00	-5.63	AVG	P																											

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.

Temperature:	26°C		Relative Humidity:	54%																															
Test Voltage:	AC 120V/60Hz																																		
Ant. Pol.	Vertical																																		
Test Mode:	TX 802.11n(HT40) Mode 5550MHz (U-NII-2C) -CDD																																		
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBμV)</th> <th>Factor (dB/m)</th> <th>Level (dBμV/m)</th> <th>Limit (dBμV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>11100.274</td> <td>49.45</td> <td>7.76</td> <td>57.21</td> <td>68.30</td> <td>-11.09</td> <td>peak</td> <td>P</td> </tr> <tr> <td>2 *</td> <td>11100.635</td> <td>40.59</td> <td>7.76</td> <td>48.35</td> <td>54.00</td> <td>-5.65</td> <td>AVG</td> <td>P</td> </tr> </tbody> </table>									No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F	1	11100.274	49.45	7.76	57.21	68.30	-11.09	peak	P	2 *	11100.635	40.59	7.76	48.35	54.00	-5.65	AVG	P
No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F																											
1	11100.274	49.45	7.76	57.21	68.30	-11.09	peak	P																											
2 *	11100.635	40.59	7.76	48.35	54.00	-5.65	AVG	P																											

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11n(HT40) Mode 5670MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11n(HT40) Mode 5670MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C		Relative Humidity:	54%																															
Test Voltage:	AC 120V/60Hz																																		
Ant. Pol.	Horizontal																																		
Test Mode:	TX 802.11n(HT40) Mode 5710MHz (U-NII-2C) -CDD																																		
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBμV)</th> <th>Factor (dB/m)</th> <th>Level (dBμV/m)</th> <th>Limit (dBμV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>11420.112</td> <td>48.65</td> <td>8.98</td> <td>57.63</td> <td>68.30</td> <td>-10.67</td> <td>peak</td> <td>P</td> </tr> <tr> <td>2 *</td> <td>11420.625</td> <td>37.95</td> <td>8.98</td> <td>46.93</td> <td>54.00</td> <td>-7.07</td> <td>AVG</td> <td>P</td> </tr> </tbody> </table>									No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F	1	11420.112	48.65	8.98	57.63	68.30	-10.67	peak	P	2 *	11420.625	37.95	8.98	46.93	54.00	-7.07	AVG	P
No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F																											
1	11420.112	48.65	8.98	57.63	68.30	-10.67	peak	P																											
2 *	11420.625	37.95	8.98	46.93	54.00	-7.07	AVG	P																											
Remark: <ol style="list-style-type: none"> 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV) 3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit. 																																			

Temperature:	26°C		Relative Humidity:	54%																															
Test Voltage:	AC 120V/60Hz																																		
Ant. Pol.	Vertical																																		
Test Mode:	TX 802.11n(HT40) Mode 5710MHz (U-NII-2C) -CDD																																		
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBμV)</th> <th>Factor (dB/m)</th> <th>Level (dBμV/m)</th> <th>Limit (dBμV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>11420.274</td> <td>48.37</td> <td>8.98</td> <td>57.35</td> <td>68.30</td> <td>-10.95</td> <td>peak</td> <td>P</td> </tr> <tr> <td>2 *</td> <td>11420.652</td> <td>37.60</td> <td>8.98</td> <td>46.58</td> <td>54.00</td> <td>-7.42</td> <td>AVG</td> <td>P</td> </tr> </tbody> </table>									No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F	1	11420.274	48.37	8.98	57.35	68.30	-10.95	peak	P	2 *	11420.652	37.60	8.98	46.58	54.00	-7.42	AVG	P
No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F																											
1	11420.274	48.37	8.98	57.35	68.30	-10.95	peak	P																											
2 *	11420.652	37.60	8.98	46.58	54.00	-7.42	AVG	P																											
Remark: <ol style="list-style-type: none"> 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV) 3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit. 																																			



Temperature:	26°C	Relative Humidity:	54%																																
Test Voltage:	AC 120V/60Hz																																		
Ant. Pol.	Horizontal																																		
Test Mode:	TX 802.11ac(VHT40) Mode 5510MHz (U-NII-2C) -CDD																																		
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr></thead><tbody><tr><td>1 *</td><td>11020.554</td><td>39.44</td><td>8.08</td><td>47.52</td><td>54.00</td><td>-6.48</td><td>AVG</td><td>P</td></tr><tr><td>2</td><td>11020.613</td><td>49.31</td><td>8.08</td><td>57.39</td><td>68.30</td><td>-10.91</td><td>peak</td><td>P</td></tr></tbody></table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	11020.554	39.44	8.08	47.52	54.00	-6.48	AVG	P	2	11020.613	49.31	8.08	57.39	68.30	-10.91	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																											
1 *	11020.554	39.44	8.08	47.52	54.00	-6.48	AVG	P																											
2	11020.613	49.31	8.08	57.39	68.30	-10.91	peak	P																											
Remark:																																			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)																																			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)																																			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)																																			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.																																			
5. No report for the emission which more than 20dB below the prescribed limit.																																			

Temperature:	26°C	Relative Humidity:	54%																																
Test Voltage:	AC 120V/60Hz																																		
Ant. Pol.	Vertical																																		
Test Mode:	TX 802.11ac(VHT40) Mode 5510MHz (U-NII-2C) -CDD																																		
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr></thead><tbody><tr><td>1 *</td><td>11020.439</td><td>39.44</td><td>8.08</td><td>47.52</td><td>54.00</td><td>-6.48</td><td>AVG</td><td>P</td></tr><tr><td>2</td><td>11020.525</td><td>49.30</td><td>8.08</td><td>57.38</td><td>68.30</td><td>-10.92</td><td>peak</td><td>P</td></tr></tbody></table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	11020.439	39.44	8.08	47.52	54.00	-6.48	AVG	P	2	11020.525	49.30	8.08	57.38	68.30	-10.92	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																											
1 *	11020.439	39.44	8.08	47.52	54.00	-6.48	AVG	P																											
2	11020.525	49.30	8.08	57.38	68.30	-10.92	peak	P																											
Remark:																																			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)																																			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)																																			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)																																			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.																																			
5. No report for the emission which more than 20dB below the prescribed limit.																																			



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ac(VHT40) Mode 5550MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ac(VHT40) Mode 5550MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C		Relative Humidity:	54%								
Test Voltage:	AC 120V/60Hz											
Ant. Pol.	Horizontal											
Test Mode:	TX 802.11ac(VHT40) Mode 5670MHz (U-NII-2C) -CDD											
Remark:												
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)												
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)												
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)												
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.												
5. No report for the emission which more than 20dB below the prescribed limit.												

Temperature:	26°C		Relative Humidity:	47%								
Test Voltage:	AC 120V/60Hz											
Ant. Pol.	Vertical											
Test Mode:	TX 802.11ac(VHT40) Mode 5670MHz (U-NII-2C) -CDD											
Remark:												
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)												
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)												
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)												
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.												
5. No report for the emission which more than 20dB below the prescribed limit.												



Temperature:	26°C		Relative Humidity:	54%								
Test Voltage:	AC 120V/60Hz											
Ant. Pol.	Horizontal											
Test Mode:	TX 802.11ac(VHT40) Mode 5710MHz (U-NII-2C) -CDD											
Remark:												
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)												
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)												
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)												
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.												
5. No report for the emission which more than 20dB below the prescribed limit.												

Temperature:	26°C		Relative Humidity:	47%								
Test Voltage:	AC 120V/60Hz											
Ant. Pol.	Vertical											
Test Mode:	TX 802.11ac(VHT40) Mode 5710MHz (U-NII-2C) -CDD											
Remark:												
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)												
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)												
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)												
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.												
5. No report for the emission which more than 20dB below the prescribed limit.												



Temperature:	26°C	Relative Humidity:	54%						
Test Voltage:	AC 120V/60Hz								
Ant. Pol.	Horizontal								
Test Mode:	TX 802.11ax(HE40) Mode 5510MHz (U-NII-2C) -CDD								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	
1	11020.351	48.24	8.08	56.32	68.30	-11.98	peak	P	
2 *	11020.512	39.48	8.08	47.56	54.00	-6.44	AVG	P	
Remark:									
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)									
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)									
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)									
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.									
5. No report for the emission which more than 20dB below the prescribed limit.									

Temperature:	26°C	Relative Humidity:	54%						
Test Voltage:	AC 120V/60Hz								
Ant. Pol.	Vertical								
Test Mode:	TX 802.11ax(HE40) Mode 5510MHz (U-NII-2C) -CDD								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	
1 *	11020.554	38.44	8.08	46.52	54.00	-7.48	AVG	P	
2	11020.625	48.88	8.08	56.96	68.30	-11.34	peak	P	
Remark:									
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)									
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)									
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)									
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.									
5. No report for the emission which more than 20dB below the prescribed limit.									



Temperature:	26°C		Relative Humidity:	54%																															
Test Voltage:	AC 120V/60Hz																																		
Ant. Pol.	Horizontal																																		
Test Mode:	TX 802.11ax(HE40) Mode 5550MHz (U-NII-2C) -CDD																																		
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr></thead><tbody><tr><td>1</td><td>11100.327</td><td>49.47</td><td>7.76</td><td>57.23</td><td>68.30</td><td>-11.07</td><td>peak</td><td>P</td></tr><tr><td>2 *</td><td>11100.635</td><td>39.17</td><td>7.76</td><td>46.93</td><td>54.00</td><td>-7.07</td><td>AVG</td><td>P</td></tr></tbody></table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1	11100.327	49.47	7.76	57.23	68.30	-11.07	peak	P	2 *	11100.635	39.17	7.76	46.93	54.00	-7.07	AVG	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																											
1	11100.327	49.47	7.76	57.23	68.30	-11.07	peak	P																											
2 *	11100.635	39.17	7.76	46.93	54.00	-7.07	AVG	P																											
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																																			

Temperature:	26°C		Relative Humidity:	54%																															
Test Voltage:	AC 120V/60Hz																																		
Ant. Pol.	Vertical																																		
Test Mode:	TX 802.11ax(HE40) Mode 5550MHz (U-NII-2C) -CDD																																		
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr></thead><tbody><tr><td>1</td><td>11100.123</td><td>49.67</td><td>7.76</td><td>57.43</td><td>68.30</td><td>-10.87</td><td>peak</td><td>P</td></tr><tr><td>2 *</td><td>11100.357</td><td>39.46</td><td>7.76</td><td>47.22</td><td>54.00</td><td>-6.78</td><td>AVG</td><td>P</td></tr></tbody></table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1	11100.123	49.67	7.76	57.43	68.30	-10.87	peak	P	2 *	11100.357	39.46	7.76	47.22	54.00	-6.78	AVG	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																											
1	11100.123	49.67	7.76	57.43	68.30	-10.87	peak	P																											
2 *	11100.357	39.46	7.76	47.22	54.00	-6.78	AVG	P																											
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																																			



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ax(HE40) Mode 5670MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	47%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ax(HE40) Mode 5670MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ax(HE40) Mode 5710MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	47%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ax(HE40) Mode 5710MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ac(VHT80) Mode 5530MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ac(VHT80) Mode 5530MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ac(VHT80) Mode 5610MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ac(VHT80) Mode 5610MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ac(VHT80) Mode 5690MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ac(VHT80) Mode 5690MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C	Relative Humidity:	54%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Horizontal																													
Test Mode:	TX 802.11ax(HE80) Mode 5530MHz (U-NII-2C) -CDD																													
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>11060.165</td> <td>49.49</td> <td>7.92</td> <td>57.41</td> <td>68.30</td> <td>-10.89</td> <td>peak</td> <td>P</td> </tr> <tr> <td>2 *</td> <td>11060.574</td> <td>39.61</td> <td>7.92</td> <td>47.53</td> <td>54.00</td> <td>-6.47</td> <td>AVG</td> <td>P</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1	11060.165	49.49	7.92	57.41	68.30	-10.89	peak	P	2 *	11060.574	39.61	7.92	47.53	54.00	-6.47	AVG	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1	11060.165	49.49	7.92	57.41	68.30	-10.89	peak	P																						
2 *	11060.574	39.61	7.92	47.53	54.00	-6.47	AVG	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														

Temperature:	26°C	Relative Humidity:	54%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Vertical																													
Test Mode:	TX 802.11ax(HE80) Mode 5530MHz (U-NII-2C) -CDD																													
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>11060.123</td> <td>39.60</td> <td>7.92</td> <td>47.52</td> <td>54.00</td> <td>-6.48</td> <td>AVG</td> <td>P</td> </tr> <tr> <td>2</td> <td>11060.722</td> <td>49.32</td> <td>7.91</td> <td>57.23</td> <td>68.30</td> <td>-11.07</td> <td>peak</td> <td>P</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	11060.123	39.60	7.92	47.52	54.00	-6.48	AVG	P	2	11060.722	49.32	7.91	57.23	68.30	-11.07	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1 *	11060.123	39.60	7.92	47.52	54.00	-6.48	AVG	P																						
2	11060.722	49.32	7.91	57.23	68.30	-11.07	peak	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														



Temperature:	26°C	Relative Humidity:	54%																																
Test Voltage:	AC 120V/60Hz																																		
Ant. Pol.	Horizontal																																		
Test Mode:	TX 802.11ax(HE80) Mode 5610MHz (U-NII-2C) -CDD																																		
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr></thead><tbody><tr><td>1 *</td><td>11060.311</td><td>38.59</td><td>7.92</td><td>46.51</td><td>54.00</td><td>-7.49</td><td>AVG</td><td>P</td></tr><tr><td>2</td><td>11060.545</td><td>48.40</td><td>7.92</td><td>56.32</td><td>68.30</td><td>-11.98</td><td>peak</td><td>P</td></tr></tbody></table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	11060.311	38.59	7.92	46.51	54.00	-7.49	AVG	P	2	11060.545	48.40	7.92	56.32	68.30	-11.98	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																											
1 *	11060.311	38.59	7.92	46.51	54.00	-7.49	AVG	P																											
2	11060.545	48.40	7.92	56.32	68.30	-11.98	peak	P																											
Remark:																																			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)																																			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)																																			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)																																			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.																																			
5. No report for the emission which more than 20dB below the prescribed limit.																																			

Temperature:	26°C	Relative Humidity:	54%																																
Test Voltage:	AC 120V/60Hz																																		
Ant. Pol.	Vertical																																		
Test Mode:	TX 802.11ax(HE80) Mode 5610MHz (U-NII-2C) -CDD																																		
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr></thead><tbody><tr><td>1</td><td>11220.452</td><td>48.37</td><td>8.10</td><td>56.47</td><td>68.30</td><td>-11.83</td><td>peak</td><td>P</td></tr><tr><td>2 *</td><td>11220.625</td><td>39.42</td><td>8.10</td><td>47.52</td><td>54.00</td><td>-6.48</td><td>AVG</td><td>P</td></tr></tbody></table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1	11220.452	48.37	8.10	56.47	68.30	-11.83	peak	P	2 *	11220.625	39.42	8.10	47.52	54.00	-6.48	AVG	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																											
1	11220.452	48.37	8.10	56.47	68.30	-11.83	peak	P																											
2 *	11220.625	39.42	8.10	47.52	54.00	-6.48	AVG	P																											
Remark:																																			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)																																			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)																																			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)																																			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.																																			
5. No report for the emission which more than 20dB below the prescribed limit.																																			



Temperature:	26°C		Relative Humidity:	54%																															
Test Voltage:	AC 120V/60Hz																																		
Ant. Pol.	Horizontal																																		
Test Mode:	TX 802.11ax(HE80) Mode 5690MHz (U-NII-2C) -CDD																																		
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dB_uV)</th> <th>Factor (dB/m)</th> <th>Level (dB_uV/m)</th> <th>Limit (dB_uV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>11380.124</td> <td>47.51</td> <td>8.96</td> <td>56.47</td> <td>68.30</td> <td>-11.83</td> <td>peak</td> <td>P</td> </tr> <tr> <td>2 *</td> <td>11380.521</td> <td>37.56</td> <td>8.96</td> <td>46.52</td> <td>54.00</td> <td>-7.48</td> <td>AVG</td> <td>P</td> </tr> </tbody> </table>									No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F	1	11380.124	47.51	8.96	56.47	68.30	-11.83	peak	P	2 *	11380.521	37.56	8.96	46.52	54.00	-7.48	AVG	P
No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F																											
1	11380.124	47.51	8.96	56.47	68.30	-11.83	peak	P																											
2 *	11380.521	37.56	8.96	46.52	54.00	-7.48	AVG	P																											
Remark: <ol style="list-style-type: none"> 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB_uV/m)= Corr. (dB/m)+ Read Level (dB_uV) 3. Margin (dB) = Peak/AVG (dB_uV/m)-Limit PK/AVG(dB_uV/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit. 																																			

Temperature:	26°C		Relative Humidity:	54%																															
Test Voltage:	AC 120V/60Hz																																		
Ant. Pol.	Vertical																																		
Test Mode:	TX 802.11ax(HE80) Mode 5690MHz (U-NII-2C) -CDD																																		
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dB_uV)</th> <th>Factor (dB/m)</th> <th>Level (dB_uV/m)</th> <th>Limit (dB_uV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>11380.211</td> <td>38.57</td> <td>8.96</td> <td>47.53</td> <td>54.00</td> <td>-6.47</td> <td>AVG</td> <td>P</td> </tr> <tr> <td>2</td> <td>11380.327</td> <td>48.67</td> <td>8.96</td> <td>57.63</td> <td>68.30</td> <td>-10.67</td> <td>peak</td> <td>P</td> </tr> </tbody> </table>									No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F	1 *	11380.211	38.57	8.96	47.53	54.00	-6.47	AVG	P	2	11380.327	48.67	8.96	57.63	68.30	-10.67	peak	P
No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F																											
1 *	11380.211	38.57	8.96	47.53	54.00	-6.47	AVG	P																											
2	11380.327	48.67	8.96	57.63	68.30	-10.67	peak	P																											
Remark: <ol style="list-style-type: none"> 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB_uV/m)= Corr. (dB/m)+ Read Level (dB_uV) 3. Margin (dB) = Peak/AVG (dB_uV/m)-Limit PK/AVG(dB_uV/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit. 																																			



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ac(VHT160) Mode 5570MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ac(VHT160) Mode 5570MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ax(HE160) Mode 5570MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ax(HE160) Mode 5570MHz (U-NII-2C) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



5745MHz-5825MHz(U-NII-3)

Temperature:	26°C	Relative Humidity:	54%					
Test Voltage:	AC 120V/60Hz							
Ant. Pol.	Horizontal							
Test Mode:	TX 802.11a Mode 5745MHz (U-NII-3) -CDD							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11490.657	47.53	8.99	56.52	68.30	-11.78	peak	P
2 *	11490.711	38.86	8.99	47.85	54.00	-6.15	AVG	P
Remark:								
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)								
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)								
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)								
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.								
5. No report for the emission which more than 20dB below the prescribed limit.								

Temperature:	26°C	Relative Humidity:	54%					
Test Voltage:	AC 120V/60Hz							
Ant. Pol.	Vertical							
Test Mode:	TX 802.11a Mode 5745MHz (U-NII-3) -CDD							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11490.248	48.53	8.99	57.52	68.30	-10.78	peak	P
2 *	11490.511	37.59	8.99	46.58	54.00	-7.42	AVG	P
Remark:								
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)								
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)								
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)								
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.								
5. No report for the emission which more than 20dB below the prescribed limit.								



Temperature:	26°C		Relative Humidity:	54%								
Test Voltage:	AC 120V/60Hz											
Ant. Pol.	Horizontal											
Test Mode:	TX 802.11a Mode 5785MHz (U-NII-3) -CDD											
Remark:												
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)												
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)												
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)												
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.												
5. No report for the emission which more than 20dB below the prescribed limit.												

Temperature:	26°C		Relative Humidity:	54%								
Test Voltage:	AC 120V/60Hz											
Ant. Pol.	Vertical											
Test Mode:	TX 802.11a Mode 5785MHz (U-NII-3) -CDD											
Remark:												
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)												
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)												
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)												
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.												
5. No report for the emission which more than 20dB below the prescribed limit.												



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11a Mode 5825MHz (U-NII-3) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11a Mode 5825MHz (U-NII-3) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11n(HT20) Mode 5745MHz (U-NII-3) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m) = Corr. (dB/m) + Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m) - Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11n(HT20) Mode 5745MHz (U-NII-3) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m) = Corr. (dB/m) + Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m) - Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11n(HT20) Mode 5785MHz (U-NII-3) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11n(HT20) Mode 5785MHz (U-NII-3) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11n(HT20) Mode 5825MHz (U-NII-3) -CDD		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	11650.123	38.85	8.70	47.55	54.00	-6.45	AVG	P
2	11650.545	48.75	8.70	57.45	68.30	-10.85	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11n(HT20) Mode 5825MHz (U-NII-3) -CDD		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11650.341	48.17	8.70	56.87	68.30	-11.43	peak	P
2 *	11650.413	37.86	8.70	46.56	54.00	-7.44	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	26°C		Relative Humidity:		54%									
Test Voltage:	AC 120V/60Hz													
Ant. Pol.	Horizontal													
Test Mode:	TX 802.11ac(VHT20) Mode 5745MHz (U-NII-3) -CDD													
Remark:														
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)														
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)														
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)														
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.														
5. No report for the emission which more than 20dB below the prescribed limit.														

Temperature:	26°C		Relative Humidity:		54%									
Test Voltage:	AC 120V/60Hz													
Ant. Pol.	Vertical													
Test Mode:	TX 802.11ac(VHT20) Mode 5745MHz (U-NII-3) -CDD													
Remark:														
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)														
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)														
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)														
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.														
5. No report for the emission which more than 20dB below the prescribed limit.														



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ac(VHT20) Mode 5785MHz (U-NII-3) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ac(VHT20) Mode 5785MHz (U-NII-3) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C	Relative Humidity:	54%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Horizontal																													
Test Mode:	TX 802.11ac(VHT20) Mode 5825MHz (U-NII-3) -CDD																													
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr></thead><tbody><tr><td>1</td><td>11650.356</td><td>48.73</td><td>8.70</td><td>57.43</td><td>68.30</td><td>-10.87</td><td>peak</td><td>P</td></tr><tr><td>2 *</td><td>11650.640</td><td>37.82</td><td>8.70</td><td>46.52</td><td>54.00</td><td>-7.48</td><td>AVG</td><td>P</td></tr></tbody></table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1	11650.356	48.73	8.70	57.43	68.30	-10.87	peak	P	2 *	11650.640	37.82	8.70	46.52	54.00	-7.48	AVG	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1	11650.356	48.73	8.70	57.43	68.30	-10.87	peak	P																						
2 *	11650.640	37.82	8.70	46.52	54.00	-7.48	AVG	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														

Temperature:	26°C	Relative Humidity:	54%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Vertical																													
Test Mode:	TX 802.11ac(VHT20) Mode 5825MHz (U-NII-3) -CDD																													
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr></thead><tbody><tr><td>1 *</td><td>11650.678</td><td>38.45</td><td>8.70</td><td>47.15</td><td>54.00</td><td>-6.85</td><td>AVG</td><td>P</td></tr><tr><td>2</td><td>11650.684</td><td>49.12</td><td>8.70</td><td>57.82</td><td>68.30</td><td>-10.48</td><td>peak</td><td>P</td></tr></tbody></table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	11650.678	38.45	8.70	47.15	54.00	-6.85	AVG	P	2	11650.684	49.12	8.70	57.82	68.30	-10.48	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1 *	11650.678	38.45	8.70	47.15	54.00	-6.85	AVG	P																						
2	11650.684	49.12	8.70	57.82	68.30	-10.48	peak	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														



Temperature:	26°C	Relative Humidity:	54%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Horizontal																													
Test Mode:	TX 802.11ax(HE20) Mode 5745MHz (U-NII-3) -CDD																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>11490.112</td> <td>47.13</td> <td>8.99</td> <td>56.12</td> <td>68.30</td> <td>-12.18</td> <td>peak</td> <td>P</td> </tr> <tr> <td>2 *</td> <td>11490.332</td> <td>38.54</td> <td>8.99</td> <td>47.53</td> <td>54.00</td> <td>-6.47</td> <td>AVG</td> <td>P</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1	11490.112	47.13	8.99	56.12	68.30	-12.18	peak	P	2 *	11490.332	38.54	8.99	47.53	54.00	-6.47	AVG	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1	11490.112	47.13	8.99	56.12	68.30	-12.18	peak	P																						
2 *	11490.332	38.54	8.99	47.53	54.00	-6.47	AVG	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														

Temperature:	26°C	Relative Humidity:	54%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Vertical																													
Test Mode:	TX 802.11ax(HE20) Mode 5745MHz (U-NII-3) -CDD																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>11490.112</td> <td>37.54</td> <td>8.99</td> <td>46.53</td> <td>54.00</td> <td>-7.47</td> <td>AVG</td> <td>P</td> </tr> <tr> <td>2</td> <td>11490.321</td> <td>48.24</td> <td>8.99</td> <td>57.23</td> <td>68.30</td> <td>-11.07</td> <td>peak</td> <td>P</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	11490.112	37.54	8.99	46.53	54.00	-7.47	AVG	P	2	11490.321	48.24	8.99	57.23	68.30	-11.07	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1 *	11490.112	37.54	8.99	46.53	54.00	-7.47	AVG	P																						
2	11490.321	48.24	8.99	57.23	68.30	-11.07	peak	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ax(HE20) Mode 5785MHz (U-NII-3) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ax(HE20) Mode 5785MHz (U-NII-3) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ax(HE20) Mode 5825MHz (U-NII-3) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ax(HE20) Mode 5825MHz (U-NII-3) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11n(HT40) Mode 5755MHz (U-NII-3) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11n(HT40) Mode 5755MHz (U-NII-3)-CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C	Relative Humidity:	54%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Horizontal																													
Test Mode:	TX 802.11n(HT40) Mode 5795MHz (U-NII-3) -CDD																													
<table border="1"> <thead> <tr> <th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr> </thead> <tbody> <tr> <td>1</td><td>11590.127</td><td>49.17</td><td>8.69</td><td>57.86</td><td>68.30</td><td>-10.44</td><td>peak</td><td>P</td></tr> <tr> <td>2 *</td><td>11590.685</td><td>37.86</td><td>8.69</td><td>46.55</td><td>54.00</td><td>-7.45</td><td>AVG</td><td>P</td></tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1	11590.127	49.17	8.69	57.86	68.30	-10.44	peak	P	2 *	11590.685	37.86	8.69	46.55	54.00	-7.45	AVG	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1	11590.127	49.17	8.69	57.86	68.30	-10.44	peak	P																						
2 *	11590.685	37.86	8.69	46.55	54.00	-7.45	AVG	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m) = Corr. (dB/m) + Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m) - Limit PK/AVG (dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														

Temperature:	26°C	Relative Humidity:	54%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Vertical																													
Test Mode:	TX 802.11n(HT40) Mode 5795MHz (U-NII-3) -CDD																													
<table border="1"> <thead> <tr> <th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr> </thead> <tbody> <tr> <td>1</td><td>11590.751</td><td>49.17</td><td>8.69</td><td>57.86</td><td>68.30</td><td>-10.44</td><td>peak</td><td>P</td></tr> <tr> <td>2 *</td><td>11590.968</td><td>38.84</td><td>8.69</td><td>47.53</td><td>54.00</td><td>-6.47</td><td>AVG</td><td>P</td></tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1	11590.751	49.17	8.69	57.86	68.30	-10.44	peak	P	2 *	11590.968	38.84	8.69	47.53	54.00	-6.47	AVG	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1	11590.751	49.17	8.69	57.86	68.30	-10.44	peak	P																						
2 *	11590.968	38.84	8.69	47.53	54.00	-6.47	AVG	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m) = Corr. (dB/m) + Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m) - Limit PK/AVG (dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ac(VHT40) Mode 5755MHz (U-NII-3) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ac(VHT40) Mode 5755MHz (U-NII-3) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11ac(VHT40) Mode 5795MHz (U-NII-3) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													

Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11ac(VHT40) Mode 5795MHz (U-NII-3) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ax(HE40) Mode 5755MHz (U-NII-3) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ax(HE40) Mode 5755MHz (U-NII-3) -CDD		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11ax(HE40) Mode 5795MHz (U-NII-3) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													

Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11ax(HE40) Mode 5795MHz (U-NII-3) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	26°C		Relative Humidity:	54%																															
Test Voltage:	AC 120V/60Hz																																		
Ant. Pol.	Horizontal																																		
Test Mode:	TX 802.11ac(VHT80) Mode 5775MHz (U-NII-3) -CDD																																		
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dB_uV)</th> <th>Factor (dB/m)</th> <th>Level (dB_uV/m)</th> <th>Limit (dB_uV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>11510.531</td> <td>48.47</td> <td>8.95</td> <td>57.42</td> <td>68.30</td> <td>-10.88</td> <td>peak</td> <td>P</td> </tr> <tr> <td>2 *</td> <td>11510.632</td> <td>39.28</td> <td>8.95</td> <td>48.23</td> <td>54.00</td> <td>-5.77</td> <td>AVG</td> <td>P</td> </tr> </tbody> </table>									No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F	1	11510.531	48.47	8.95	57.42	68.30	-10.88	peak	P	2 *	11510.632	39.28	8.95	48.23	54.00	-5.77	AVG	P
No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F																											
1	11510.531	48.47	8.95	57.42	68.30	-10.88	peak	P																											
2 *	11510.632	39.28	8.95	48.23	54.00	-5.77	AVG	P																											
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB _u V/m) = Corr. (dB/m) + Read Level (dB _u V) 3. Margin (dB) = Peak/AVG (dB _u V/m) - Limit PK/AVG(dB _u V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																																			

Temperature:	26°C		Relative Humidity:	54%																															
Test Voltage:	AC 120V/60Hz																																		
Ant. Pol.	Vertical																																		
Test Mode:	TX 802.11ac(VHT80) Mode 5775MHz (U-NII-3) -CDD																																		
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dB_uV)</th> <th>Factor (dB/m)</th> <th>Level (dB_uV/m)</th> <th>Limit (dB_uV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>11510.612</td> <td>38.58</td> <td>8.95</td> <td>47.53</td> <td>54.00</td> <td>-6.47</td> <td>AVG</td> <td>P</td> </tr> <tr> <td>2</td> <td>11510.867</td> <td>47.91</td> <td>8.95</td> <td>56.86</td> <td>68.30</td> <td>-11.44</td> <td>peak</td> <td>P</td> </tr> </tbody> </table>									No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F	1 *	11510.612	38.58	8.95	47.53	54.00	-6.47	AVG	P	2	11510.867	47.91	8.95	56.86	68.30	-11.44	peak	P
No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F																											
1 *	11510.612	38.58	8.95	47.53	54.00	-6.47	AVG	P																											
2	11510.867	47.91	8.95	56.86	68.30	-11.44	peak	P																											
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB _u V/m) = Corr. (dB/m) + Read Level (dB _u V) 3. Margin (dB) = Peak/AVG (dB _u V/m) - Limit PK/AVG(dB _u V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																																			



Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11ax(HE80) Mode 5775MHz (U-NII-3) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m) = Corr. (dB/m) + Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m) - Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	26°C		Relative Humidity:	54%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11ax(HE80) Mode 5775MHz (U-NII-3) -CDD												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m) = Corr. (dB/m) + Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m) - Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



5180MHz-5240MHz(U-NII-1)

Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11n(HT20) Mode 5180MHz (U-NII-1) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11n(HT20) Mode 5180MHz (U-NII-1) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11n(HT20) Mode 5200MHz (U-NII-1) -BF												
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F					
1	10400.156	51.21	6.21	57.42	68.30	-10.88	peak	P					
2 *	10400.635	40.32	6.21	46.53	54.00	-7.47	AVG	P					

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.

Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11n(HT20) Mode 5200MHz (U-NII-1) -BF												
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F					
1	10400.358	50.02	6.21	56.23	68.30	-12.07	peak	P					
2 *	10400.457	41.32	6.21	47.53	54.00	-6.47	AVG	P					

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11n(HT20) Mode 5240MHz (U-NII-1) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11n(HT20) Mode 5240MHz (U-NII-1) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11ac(VHT20) Mode 5180MHz (U-NII-1) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11ac(VHT20) Mode 5180MHz (U-NII-1) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11ac(VHT20) Mode 5200MHz (U-NII-1) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11ac(VHT20) Mode 5200MHz (U-NII-1) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11 ac(VHT20) Mode 5240MHz (U-NII-1) -BF												
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F					
1	10480.537	50.89	6.36	57.25	68.30	-11.05	peak	P					
2 *	10480.712	41.76	6.36	48.12	54.00	-5.88	AVG	P					

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.

Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11ac(VHT20) Mode 5240MHz (U-NII-1) -BF												
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F					
1	10480.553	50.86	6.36	57.22	68.30	-11.08	peak	P					
2 *	10480.712	41.27	6.36	47.63	54.00	-6.37	AVG	P					

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11 ax(HE20) Mode 5180MHz (U-NII-1) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11 ax(HE20) Mode 5180MHz (U-NII-1) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11 ax(HE20) Mode 5200MHz (U-NII-1) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11 ax(HE20) Mode 5200MHz (U-NII-1) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11 ax(HE20) Mode 5240MHz (U-NII-1) -BF												
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F					
1 *	10480.457	41.20	6.36	47.56	54.00	-6.44	AVG	P					
2	10480.564	51.49	6.36	57.85	68.30	-10.45	peak	P					

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.

Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11ax(HE20) Mode 5240MHz (U-NII-1) -BF												
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F					
1 *	10480.357	41.75	6.36	48.11	54.00	-5.89	AVG	P					
2	10480.693	51.50	6.36	57.86	68.30	-10.44	peak	P					

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11n(HT40) Mode 5190MHz (U-NII-1) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11n(HT40) Mode 5190MHz (U-NII-1) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	24.3°C	Relative Humidity:	52%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Horizontal																													
Test Mode:	TX 802.11n(HT40) Mode 5230MHz (U-NII-1) -BF																													
<table border="1"> <thead> <tr> <th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr> </thead> <tbody> <tr> <td>1 *</td><td>10460.546</td><td>42.19</td><td>6.32</td><td>48.51</td><td>54.00</td><td>-5.49</td><td>AVG</td><td>P</td></tr> <tr> <td>2</td><td>10460.588</td><td>51.24</td><td>6.32</td><td>57.56</td><td>68.30</td><td>-10.74</td><td>peak</td><td>P</td></tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	10460.546	42.19	6.32	48.51	54.00	-5.49	AVG	P	2	10460.588	51.24	6.32	57.56	68.30	-10.74	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1 *	10460.546	42.19	6.32	48.51	54.00	-5.49	AVG	P																						
2	10460.588	51.24	6.32	57.56	68.30	-10.74	peak	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m) = Corr. (dB/m) + Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m) - Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														

Temperature:	24.3°C	Relative Humidity:	52%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Vertical																													
Test Mode:	TX 802.11n(HT40) Mode 5230MHz (U-NII-1) -BF																													
<table border="1"> <thead> <tr> <th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr> </thead> <tbody> <tr> <td>1 *</td><td>10460.564</td><td>42.25</td><td>6.32</td><td>48.57</td><td>54.00</td><td>-5.43</td><td>AVG</td><td>P</td></tr> <tr> <td>2</td><td>10460.625</td><td>51.31</td><td>6.32</td><td>57.63</td><td>68.30</td><td>-10.67</td><td>peak</td><td>P</td></tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	10460.564	42.25	6.32	48.57	54.00	-5.43	AVG	P	2	10460.625	51.31	6.32	57.63	68.30	-10.67	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1 *	10460.564	42.25	6.32	48.57	54.00	-5.43	AVG	P																						
2	10460.625	51.31	6.32	57.63	68.30	-10.67	peak	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m) = Corr. (dB/m) + Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m) - Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														



Temperature:	24.3°C	Relative Humidity:	52%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Horizontal																													
Test Mode:	TX 802.11ac(VHT40) Mode 5190MHz (U-NII-1) -BF																													
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>10380.227</td> <td>41.49</td> <td>6.14</td> <td>47.63</td> <td>54.00</td> <td>-6.37</td> <td>AVG</td> <td>P</td> </tr> <tr> <td>2</td> <td>10380.634</td> <td>52.61</td> <td>6.14</td> <td>58.75</td> <td>68.30</td> <td>-9.55</td> <td>peak</td> <td>P</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	10380.227	41.49	6.14	47.63	54.00	-6.37	AVG	P	2	10380.634	52.61	6.14	58.75	68.30	-9.55	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1 *	10380.227	41.49	6.14	47.63	54.00	-6.37	AVG	P																						
2	10380.634	52.61	6.14	58.75	68.30	-9.55	peak	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m) = Corr. (dB/m) + Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m) - Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														

Temperature:	24.3°C	Relative Humidity:	52%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Vertical																													
Test Mode:	TX 802.11ac(VHT40) Mode 5190MHz (U-NII-1) -BF																													
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>10380.437</td> <td>52.32</td> <td>6.14</td> <td>58.46</td> <td>68.30</td> <td>-9.84</td> <td>peak</td> <td>P</td> </tr> <tr> <td>2 *</td> <td>10380.635</td> <td>42.43</td> <td>6.14</td> <td>48.57</td> <td>54.00</td> <td>-5.43</td> <td>AVG</td> <td>P</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1	10380.437	52.32	6.14	58.46	68.30	-9.84	peak	P	2 *	10380.635	42.43	6.14	48.57	54.00	-5.43	AVG	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1	10380.437	52.32	6.14	58.46	68.30	-9.84	peak	P																						
2 *	10380.635	42.43	6.14	48.57	54.00	-5.43	AVG	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m) = Corr. (dB/m) + Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m) - Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														



Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11ac(VHT40) Mode 5230MHz (U-NII-1) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11ac(VHT40) Mode 5230MHz (U-NII-1) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	24.3°C		Relative Humidity:	52%																															
Test Voltage:	AC 120V/60Hz																																		
Ant. Pol.	Horizontal																																		
Test Mode:	TX 802.11 ax(HE40) Mode 5190MHz (U-NII-1) -BF																																		
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr></thead><tbody><tr><td>1 *</td><td>10380.479</td><td>41.42</td><td>6.14</td><td>47.56</td><td>54.00</td><td>-6.44</td><td>AVG</td><td>P</td></tr><tr><td>2</td><td>10380.655</td><td>52.31</td><td>6.14</td><td>58.45</td><td>68.30</td><td>-9.85</td><td>peak</td><td>P</td></tr></tbody></table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	10380.479	41.42	6.14	47.56	54.00	-6.44	AVG	P	2	10380.655	52.31	6.14	58.45	68.30	-9.85	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																											
1 *	10380.479	41.42	6.14	47.56	54.00	-6.44	AVG	P																											
2	10380.655	52.31	6.14	58.45	68.30	-9.85	peak	P																											
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																																			

Temperature:	24.3°C		Relative Humidity:	52%																															
Test Voltage:	AC 120V/60Hz																																		
Ant. Pol.	Vertical																																		
Test Mode:	TX 802.11 ax(HE40) Mode 5190MHz (U-NII-1) -BF																																		
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr></thead><tbody><tr><td>1 *</td><td>10380.364</td><td>42.43</td><td>6.14</td><td>48.57</td><td>54.00</td><td>-5.43</td><td>AVG</td><td>P</td></tr><tr><td>2</td><td>10380.478</td><td>51.39</td><td>6.14</td><td>57.53</td><td>68.30</td><td>-10.77</td><td>peak</td><td>P</td></tr></tbody></table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	10380.364	42.43	6.14	48.57	54.00	-5.43	AVG	P	2	10380.478	51.39	6.14	57.53	68.30	-10.77	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																											
1 *	10380.364	42.43	6.14	48.57	54.00	-5.43	AVG	P																											
2	10380.478	51.39	6.14	57.53	68.30	-10.77	peak	P																											
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																																			



Temperature:	24.3°C		Relative Humidity:	52%								
Test Voltage:	AC 120V/60Hz											
Ant. Pol.	Horizontal											
Test Mode:	TX 802.11ax(HE40) Mode 5230MHz (U-NII-1) -BF											
Remark:												
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)												
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)												
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)												
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.												
5. No report for the emission which more than 20dB below the prescribed limit.												

Temperature:	24.3°C		Relative Humidity:	52%								
Test Voltage:	AC 120V/60Hz											
Ant. Pol.	Vertical											
Test Mode:	TX 802.11ax(HE40) Mode 5230MHz (U-NII-1) -BF											
Remark:												
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)												
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)												
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)												
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.												
5. No report for the emission which more than 20dB below the prescribed limit.												



Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ac(VHT80) Mode 5210MHz (U-NII-1) -BF		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	10420.479	41.28	6.25	47.53	54.00	-6.47	AVG	P
2	10420.653	52.00	6.25	58.25	68.30	-10.05	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.

Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ac(VHT80) Mode 5210MHz (U-NII-1) -BF		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	10420.367	42.27	6.25	48.52	54.00	-5.48	AVG	P
2	10420.637	51.18	6.25	57.43	68.30	-10.87	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11ax(HE80) Mode 5210MHz (U-NII-1) -BF												
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F					
1	10420.285	52.27	6.25	58.52	68.30	-9.78	peak	P					
2 *	10420.751	41.71	6.25	47.96	54.00	-6.04	AVG	P					

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.

Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11ax(HE80) Mode 5210MHz (U-NII-1) -BF												
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F					
1	10420.638	52.47	6.25	58.72	68.30	-9.58	peak	P					
2 *	10420.741	41.31	6.25	47.56	54.00	-6.44	AVG	P					

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.



5250MHz-5320MHz(U-NII-2A)

Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11n(HT20) Mode 5260MHz (U-NII-2A) -BF		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11n(HT20) Mode 5260MHz (U-NII-2A) -BF		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11n(HT20) Mode 5280MHz (U-NII-2A) -BF		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m) = Corr. (dB/m) + Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m) - Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11n(HT20) Mode 5280MHz (U-NII-2A) -BF		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m) = Corr. (dB/m) + Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m) - Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11n(HT20) Mode 5320MHz (U-NII-2A) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11n(HT20) Mode 5320MHz (U-NII-2A) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	24.3°C	Relative Humidity:	52%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Horizontal																													
Test Mode:	TX 802.11ac(VHT20) Mode 5260MHz (U-NII-2A) -BF																													
<table border="1"> <thead> <tr> <th>No.</th><th>Frequency (MHz)</th><th>Reading (dB_uV)</th><th>Factor (dB/m)</th><th>Level (dB_uV/m)</th><th>Limit (dB_uV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr> </thead> <tbody> <tr> <td>1</td><td>10520.546</td><td>49.88</td><td>6.40</td><td>56.28</td><td>68.30</td><td>-12.02</td><td>peak</td><td>P</td></tr> <tr> <td>2 *</td><td>10520.789</td><td>41.86</td><td>6.39</td><td>48.25</td><td>54.00</td><td>-5.75</td><td>AVG</td><td>P</td></tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F	1	10520.546	49.88	6.40	56.28	68.30	-12.02	peak	P	2 *	10520.789	41.86	6.39	48.25	54.00	-5.75	AVG	P
No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F																						
1	10520.546	49.88	6.40	56.28	68.30	-12.02	peak	P																						
2 *	10520.789	41.86	6.39	48.25	54.00	-5.75	AVG	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB _u V/m) = Corr. (dB/m) + Read Level (dB _u V) 3. Margin (dB) = Peak/AVG (dB _u V/m) - Limit PK/AVG(dB _u V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														

Temperature:	24.3°C	Relative Humidity:	52%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Vertical																													
Test Mode:	TX 802.11ac(VHT20) Mode 5260MHz (U-NII-2A) -BF																													
<table border="1"> <thead> <tr> <th>No.</th><th>Frequency (MHz)</th><th>Reading (dB_uV)</th><th>Factor (dB/m)</th><th>Level (dB_uV/m)</th><th>Limit (dB_uV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr> </thead> <tbody> <tr> <td>1</td><td>10520.127</td><td>50.42</td><td>6.40</td><td>56.82</td><td>68.30</td><td>-11.48</td><td>peak</td><td>P</td></tr> <tr> <td>2 *</td><td>10520.557</td><td>41.13</td><td>6.40</td><td>47.53</td><td>54.00</td><td>-6.47</td><td>AVG</td><td>P</td></tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F	1	10520.127	50.42	6.40	56.82	68.30	-11.48	peak	P	2 *	10520.557	41.13	6.40	47.53	54.00	-6.47	AVG	P
No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F																						
1	10520.127	50.42	6.40	56.82	68.30	-11.48	peak	P																						
2 *	10520.557	41.13	6.40	47.53	54.00	-6.47	AVG	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB _u V/m) = Corr. (dB/m) + Read Level (dB _u V) 3. Margin (dB) = Peak/AVG (dB _u V/m) - Limit PK/AVG(dB _u V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														



Temperature:	24.3°C		Relative Humidity:	52%																															
Test Voltage:	AC 120V/60Hz																																		
Ant. Pol.	Horizontal																																		
Test Mode:	TX 802.11ac(VHT20) Mode 5280MHz (U-NII-2A) -BF																																		
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>10560.244</td> <td>41.84</td> <td>6.39</td> <td>48.23</td> <td>54.00</td> <td>-5.77</td> <td>AVG</td> <td>P</td> </tr> <tr> <td>2</td> <td>10560.876</td> <td>51.78</td> <td>6.39</td> <td>58.17</td> <td>68.30</td> <td>-10.13</td> <td>peak</td> <td>P</td> </tr> </tbody> </table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	10560.244	41.84	6.39	48.23	54.00	-5.77	AVG	P	2	10560.876	51.78	6.39	58.17	68.30	-10.13	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																											
1 *	10560.244	41.84	6.39	48.23	54.00	-5.77	AVG	P																											
2	10560.876	51.78	6.39	58.17	68.30	-10.13	peak	P																											
Remark: <ol style="list-style-type: none"> 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV) 3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit. 																																			

Temperature:	24.3°C		Relative Humidity:	52%																															
Test Voltage:	AC 120V/60Hz																																		
Ant. Pol.	Vertical																																		
Test Mode:	TX 802.11ac(VHT20) Mode 5280MHz (U-NII-2A) -BF																																		
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>10560.356</td> <td>51.03</td> <td>6.39</td> <td>57.42</td> <td>68.30</td> <td>-10.88</td> <td>peak</td> <td>P</td> </tr> <tr> <td>2 *</td> <td>10560.543</td> <td>41.30</td> <td>6.39</td> <td>47.69</td> <td>54.00</td> <td>-6.31</td> <td>AVG</td> <td>P</td> </tr> </tbody> </table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1	10560.356	51.03	6.39	57.42	68.30	-10.88	peak	P	2 *	10560.543	41.30	6.39	47.69	54.00	-6.31	AVG	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																											
1	10560.356	51.03	6.39	57.42	68.30	-10.88	peak	P																											
2 *	10560.543	41.30	6.39	47.69	54.00	-6.31	AVG	P																											
Remark: <ol style="list-style-type: none"> 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV) 3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit. 																																			



Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11 ac(VHT20) Mode 5320MHz (U-NII-2A) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11ac(VHT20) Mode 5320MHz (U-NII-2A) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11ax(HE20) Mode 5260MHz (U-NII-2A) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11ax(HE20) Mode 5260MHz (U-NII-2A) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11ax(HE20) Mode 5280MHz (U-NII-2A) -BF												
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F					
1	10560.546	51.13	6.39	57.52	68.30	-10.78	peak	P					
2 *	10560.667	41.84	6.39	48.23	54.00	-5.77	AVG	P					

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.

Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11ax(HE20) Mode 5280MHz (U-NII-2A) -BF												
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F					
1 *	10560.123	42.13	6.39	48.52	54.00	-5.48	AVG	P					
2	10560.653	51.13	6.39	57.52	68.30	-10.78	peak	P					

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ax(HE20) Mode 5320MHz (U-NII-2A) -BF		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ax(HE20) Mode 5320MHz (U-NII-2A) -BF		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Ant. Pol.	Horizontal							
Test Mode:	TX 802.11n(HT40) Mode 5270MHz (U-NII-2A) -BF							
No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F
1 *	10540.257	41.88	6.39	48.27	54.00	-5.73	AVG	P
2	10540.687	52.17	6.39	58.56	68.30	-9.74	peak	P

Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Ant. Pol.	Vertical							
Test Mode:	TX 802.11n(HT40) Mode 5270MHz (U-NII-2A) -BF							
No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F
1	10540.557	52.24	6.39	58.63	68.30	-9.67	peak	P
2 *	10540.657	42.13	6.39	48.52	54.00	-5.48	AVG	P



Temperature:	24.3°C		Relative Humidity:	52%								
Test Voltage:	AC 120V/60Hz											
Ant. Pol.	Horizontal											
Test Mode:	TX 802.11n(HT40) Mode 5310MHz (U-NII-2A) -BF											
Remark:												
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)												
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)												
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)												
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.												
5. No report for the emission which more than 20dB below the prescribed limit.												

Temperature:	24.3°C		Relative Humidity:	52%								
Test Voltage:	AC 120V/60Hz											
Ant. Pol.	Vertical											
Test Mode:	TX 802.11n(HT40) Mode 5310MHz (U-NII-2A) -BF											
Remark:												
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)												
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)												
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)												
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.												
5. No report for the emission which more than 20dB below the prescribed limit.												



Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11ac(VHT40) Mode 5270MHz (U-NII-2A) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11ac(VHT40) Mode 5270MHz (U-NII-2A) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Ant. Pol.	Horizontal							
Test Mode:	TX 802.11ac(VHT40) Mode 5310MHz (U-NII-2A) -BF							
Emissions Test Report								
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	10620.137	41.03	6.50	47.53	54.00	-6.47	AVG	P
2	10620.567	51.66	6.50	58.16	68.30	-10.14	peak	P

Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Ant. Pol.	Vertical							
Test Mode:	TX 802.11ac(VHT40) Mode 5310MHz (U-NII-2A) -BF							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	10620.215	41.03	6.50	47.53	54.00	-6.47	AVG	P
2	10620.712	51.92	6.51	58.43	68.30	-9.87	peak	P



Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ax(HE40) Mode 5270MHz (U-NII-2A) -BF		

No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F
1 *	10540.567	41.14	6.39	47.53	54.00	-6.47	AVG	P
2	10540.978	51.09	6.39	57.48	68.30	-10.82	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB_uV/m) = Corr. (dB/m) + Read Level (dB_uV)
3. Margin (dB) = Peak/AVG (dB_uV/m) - Limit PK/AVG(dB_uV/m)
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.

Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ax(HE40) Mode 5270MHz (U-NII-2A) -BF		

No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F
1 *	10540.617	41.20	6.39	47.59	54.00	-6.41	AVG	P
2	10540.963	52.33	6.39	58.72	68.30	-9.58	peak	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB_uV/m) = Corr. (dB/m) + Read Level (dB_uV)
3. Margin (dB) = Peak/AVG (dB_uV/m) - Limit PK/AVG(dB_uV/m)
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ax(HE40) Mode 5310MHz (U-NII-2A) -BF		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ax(HE40) Mode 5310MHz (U-NII-2A) -BF		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11ac(VHT80) Mode 5290MHz (U-NII-2A) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11ac(VHT80) Mode 5290MHz (U-NII-2A) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	24.3°C	Relative Humidity:	52%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Horizontal																													
Test Mode:	TX 802.11ax(HE80) Mode 5290MHz (U-NII-2A) -BF																													
<table border="1"> <thead> <tr> <th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr> </thead> <tbody> <tr> <td>1</td><td>10580.345</td><td>51.63</td><td>6.38</td><td>58.01</td><td>68.30</td><td>-10.29</td><td>peak</td><td>P</td></tr> <tr> <td>2 *</td><td>10580.745</td><td>41.14</td><td>6.38</td><td>47.52</td><td>54.00</td><td>-6.48</td><td>AVG</td><td>P</td></tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1	10580.345	51.63	6.38	58.01	68.30	-10.29	peak	P	2 *	10580.745	41.14	6.38	47.52	54.00	-6.48	AVG	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1	10580.345	51.63	6.38	58.01	68.30	-10.29	peak	P																						
2 *	10580.745	41.14	6.38	47.52	54.00	-6.48	AVG	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														

Temperature:	24.3°C	Relative Humidity:	52%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Vertical																													
Test Mode:	TX 802.11ax(HE80) Mode 5290MHz (U-NII-2A) -BF																													
<table border="1"> <thead> <tr> <th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr> </thead> <tbody> <tr> <td>1 *</td><td>10580.674</td><td>41.15</td><td>6.38</td><td>47.53</td><td>54.00</td><td>-6.47</td><td>AVG</td><td>P</td></tr> <tr> <td>2</td><td>10580.771</td><td>51.73</td><td>6.38</td><td>58.11</td><td>68.30</td><td>-10.19</td><td>peak</td><td>P</td></tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	10580.674	41.15	6.38	47.53	54.00	-6.47	AVG	P	2	10580.771	51.73	6.38	58.11	68.30	-10.19	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1 *	10580.674	41.15	6.38	47.53	54.00	-6.47	AVG	P																						
2	10580.771	51.73	6.38	58.11	68.30	-10.19	peak	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														



Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ac(VHT160) Mode 5250MHz (U-NII-2A) -BF		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ac(VHT160) Mode 5250MHz (U-NII-2A) -BF		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ax(HE160) Mode 5250MHz (U-NII-2A) -BF		
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)
1 *	10500.574	42.13	6.40
2	10500.635	50.72	6.40
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ax(HE160) Mode 5250MHz (U-NII-2A) -BF		
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)
1	10500.245	51.84	6.40
2 *	10500.652	41.13	6.40
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



5500MHz-5720MHz(U-NII-2C)

Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11n(HT20) Mode 5500MHz (U-NII-2C) -BF		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11 n(HT20) Mode 5500MHz (U-NII-2C) -BF		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11n(HT20) Mode 5580MHz (U-NII-2C) -BF		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m) = Corr. (dB/m) + Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m) - Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11n(HT20) Mode 5580MHz (U-NII-2C) -BF		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m) = Corr. (dB/m) + Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m) - Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11n(HT20) Mode 5700MHz (U-NII-2C) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11n(HT20) Mode 5700MHz (U-NII-2C) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Ant. Pol.	Horizontal							
Test Mode:	TX 802.11n(HT20) Mode 5720MHz (U-NII-2C) -BF							
No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F
1	11440.576	48.23	8.99	57.22	68.30	-11.08	peak	P
2 *	11440.678	38.97	8.99	47.96	54.00	-6.04	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB_uV/m)= Corr. (dB/m)+ Read Level (dB_uV)
3. Margin (dB) = Peak/AVG (dB_uV/m)-Limit PK/AVG(dB_uV/m)
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.

Temperature:	24.3°C	Relative Humidity:	52%					
Test Voltage:	AC 120V/60Hz							
Ant. Pol.	Vertical							
Test Mode:	TX 802.11n(HT20) Mode 5720MHz (U-NII-2C) -BF							
No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F
1	11440.124	48.20	8.99	57.19	68.30	-11.11	peak	P
2 *	11440.567	38.54	8.99	47.53	54.00	-6.47	AVG	P

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB_uV/m)= Corr. (dB/m)+ Read Level (dB_uV)
3. Margin (dB) = Peak/AVG (dB_uV/m)-Limit PK/AVG(dB_uV/m)
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.



Temperature:	24.3°C		Relative Humidity:		52%																													
Test Voltage:	AC 120V/60Hz																																	
Ant. Pol.	Horizontal																																	
Test Mode:	TX 802.11ac(VHT20) Mode 5500MHz (U-NII-2C) -BF																																	
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dB_uV)</th> <th>Factor (dB/m)</th> <th>Level (dB_uV/m)</th> <th>Limit (dB_uV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>11000.354</td> <td>38.76</td> <td>8.17</td> <td>46.93</td> <td>54.00</td> <td>-7.07</td> <td>AVG</td> <td>P</td> </tr> <tr> <td>2</td> <td>11000.451</td> <td>49.41</td> <td>8.17</td> <td>57.58</td> <td>68.30</td> <td>-10.72</td> <td>peak</td> <td>P</td> </tr> </tbody> </table>								No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F	1 *	11000.354	38.76	8.17	46.93	54.00	-7.07	AVG	P	2	11000.451	49.41	8.17	57.58	68.30	-10.72	peak	P
No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F																										
1 *	11000.354	38.76	8.17	46.93	54.00	-7.07	AVG	P																										
2	11000.451	49.41	8.17	57.58	68.30	-10.72	peak	P																										
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB _u V/m)= Corr. (dB/m)+ Read Level (dB _u V) 3. Margin (dB) = Peak/AVG (dB _u V/m)-Limit PK/AVG(dB _u V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																																		

Temperature:	24.3°C		Relative Humidity:		52%																													
Test Voltage:	AC 120V/60Hz																																	
Ant. Pol.	Vertical																																	
Test Mode:	TX 802.11 ac(VHT20) Mode 5500MHz (U-NII-2C) -BF																																	
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dB_uV)</th> <th>Factor (dB/m)</th> <th>Level (dB_uV/m)</th> <th>Limit (dB_uV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>11000.685</td> <td>39.35</td> <td>8.17</td> <td>47.52</td> <td>54.00</td> <td>-6.48</td> <td>AVG</td> <td>P</td> </tr> <tr> <td>2</td> <td>11000.745</td> <td>49.45</td> <td>8.17</td> <td>57.62</td> <td>68.30</td> <td>-10.68</td> <td>peak</td> <td>P</td> </tr> </tbody> </table>								No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F	1 *	11000.685	39.35	8.17	47.52	54.00	-6.48	AVG	P	2	11000.745	49.45	8.17	57.62	68.30	-10.68	peak	P
No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F																										
1 *	11000.685	39.35	8.17	47.52	54.00	-6.48	AVG	P																										
2	11000.745	49.45	8.17	57.62	68.30	-10.68	peak	P																										
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB _u V/m)= Corr. (dB/m)+ Read Level (dB _u V) 3. Margin (dB) = Peak/AVG (dB _u V/m)-Limit PK/AVG(dB _u V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																																		



Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11 ac(VHT20) Mode 5580MHz (U-NII-2C) -BF		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11 ac(VHT20) Mode 5580MHz (U-NII-2C) -BF		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11 ac(VHT20) Mode 5700MHz (U-NII-2C) -BF		
FCC ID: 2ABCN-A9503			

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11400.187	48.56	8.98	57.54	68.30	-10.76	peak	P
2 *	11400.535	38.54	8.98	47.52	54.00	-6.48	AVG	P

Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11 ac(VHT20) Mode 5700MHz (U-NII-2C) -BF		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11400.521	48.55	8.98	57.53	68.30	-10.77	peak	P
2 *	11400.714	39.31	8.98	48.29	54.00	-5.71	AVG	P



Temperature:	24.3°C	Relative Humidity:	52%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Horizontal																													
Test Mode:	TX 802.11 ac(VHT20) Mode 5720MHz (U-NII-2C) -BF																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dB_uV)</th> <th>Factor (dB/m)</th> <th>Level (dB_uV/m)</th> <th>Limit (dB_uV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>11440.178</td> <td>38.54</td> <td>8.99</td> <td>47.53</td> <td>54.00</td> <td>-6.47</td> <td>AVG</td> <td>P</td> </tr> <tr> <td>2</td> <td>11440.635</td> <td>49.53</td> <td>8.99</td> <td>58.52</td> <td>68.30</td> <td>-9.78</td> <td>peak</td> <td>P</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F	1 *	11440.178	38.54	8.99	47.53	54.00	-6.47	AVG	P	2	11440.635	49.53	8.99	58.52	68.30	-9.78	peak	P
No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F																						
1 *	11440.178	38.54	8.99	47.53	54.00	-6.47	AVG	P																						
2	11440.635	49.53	8.99	58.52	68.30	-9.78	peak	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB _u V/m) = Corr. (dB/m) + Read Level (dB _u V) 3. Margin (dB) = Peak/AVG (dB _u V/m) - Limit PK/AVG(dB _u V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														

Temperature:	24.3°C	Relative Humidity:	52%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Vertical																													
Test Mode:	TX 802.11 ac(VHT20) Mode 5720MHz (U-NII-2C) -BF																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dB_uV)</th> <th>Factor (dB/m)</th> <th>Level (dB_uV/m)</th> <th>Limit (dB_uV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>11440.412</td> <td>39.28</td> <td>8.99</td> <td>48.27</td> <td>54.00</td> <td>-5.73</td> <td>AVG</td> <td>P</td> </tr> <tr> <td>2</td> <td>11440.492</td> <td>48.29</td> <td>8.99</td> <td>57.28</td> <td>68.30</td> <td>-11.02</td> <td>peak</td> <td>P</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F	1 *	11440.412	39.28	8.99	48.27	54.00	-5.73	AVG	P	2	11440.492	48.29	8.99	57.28	68.30	-11.02	peak	P
No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F																						
1 *	11440.412	39.28	8.99	48.27	54.00	-5.73	AVG	P																						
2	11440.492	48.29	8.99	57.28	68.30	-11.02	peak	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB _u V/m) = Corr. (dB/m) + Read Level (dB _u V) 3. Margin (dB) = Peak/AVG (dB _u V/m) - Limit PK/AVG(dB _u V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														



Temperature:	24.3°C	Relative Humidity:	52%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Horizontal																													
Test Mode:	TX 802.11 ax(HE20) Mode 5500MHz (U-NII-2C) -BF																													
<table border="1"> <thead> <tr> <th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr> </thead> <tbody> <tr> <td>1 *</td><td>11000.468</td><td>38.39</td><td>8.17</td><td>46.56</td><td>54.00</td><td>-7.44</td><td>AVG</td><td>P</td></tr> <tr> <td>2</td><td>11000.567</td><td>49.37</td><td>8.17</td><td>57.54</td><td>68.30</td><td>-10.76</td><td>peak</td><td>P</td></tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	11000.468	38.39	8.17	46.56	54.00	-7.44	AVG	P	2	11000.567	49.37	8.17	57.54	68.30	-10.76	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1 *	11000.468	38.39	8.17	46.56	54.00	-7.44	AVG	P																						
2	11000.567	49.37	8.17	57.54	68.30	-10.76	peak	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														

Temperature:	24.3°C	Relative Humidity:	52%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Vertical																													
Test Mode:	TX 802.11 ax(HE20) Mode 5500MHz (U-NII-2C) -BF																													
<table border="1"> <thead> <tr> <th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr> </thead> <tbody> <tr> <td>1 *</td><td>11000.562</td><td>40.19</td><td>8.17</td><td>48.36</td><td>54.00</td><td>-5.64</td><td>AVG</td><td>P</td></tr> <tr> <td>2</td><td>11000.745</td><td>50.28</td><td>8.17</td><td>58.45</td><td>68.30</td><td>-9.85</td><td>peak</td><td>P</td></tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	1 *	11000.562	40.19	8.17	48.36	54.00	-5.64	AVG	P	2	11000.745	50.28	8.17	58.45	68.30	-9.85	peak	P
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F																						
1 *	11000.562	40.19	8.17	48.36	54.00	-5.64	AVG	P																						
2	11000.745	50.28	8.17	58.45	68.30	-9.85	peak	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														



Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11 ax(HE20) Mode 5580MHz (U-NII-2C) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11 ax(HE20) Mode 5580MHz (U-NII-2C) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	24.3°C	Relative Humidity:	52%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Horizontal																													
Test Mode:	TX 802.11 ax(HE20) Mode 5700MHz (U-NII-2C) -BF																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dB_uV)</th> <th>Factor (dB/m)</th> <th>Level (dB_uV/m)</th> <th>Limit (dB_uV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>11400.448</td> <td>38.71</td> <td>8.98</td> <td>47.69</td> <td>54.00</td> <td>-6.31</td> <td>AVG</td> <td>P</td> </tr> <tr> <td>2</td> <td>11400.549</td> <td>48.58</td> <td>8.98</td> <td>57.56</td> <td>68.30</td> <td>-10.74</td> <td>peak</td> <td>P</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F	1 *	11400.448	38.71	8.98	47.69	54.00	-6.31	AVG	P	2	11400.549	48.58	8.98	57.56	68.30	-10.74	peak	P
No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F																						
1 *	11400.448	38.71	8.98	47.69	54.00	-6.31	AVG	P																						
2	11400.549	48.58	8.98	57.56	68.30	-10.74	peak	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB _u V/m)= Corr. (dB/m)+ Read Level (dB _u V) 3. Margin (dB) = Peak/AVG (dB _u V/m)-Limit PK/AVG(dB _u V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														

Temperature:	24.3°C	Relative Humidity:	52%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Vertical																													
Test Mode:	TX 802.11 ax(HE20) Mode 5700MHz (U-NII-2C) -BF																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dB_uV)</th> <th>Factor (dB/m)</th> <th>Level (dB_uV/m)</th> <th>Limit (dB_uV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>11400.456</td> <td>39.54</td> <td>8.98</td> <td>48.52</td> <td>54.00</td> <td>-5.48</td> <td>AVG</td> <td>P</td> </tr> <tr> <td>2</td> <td>11400.775</td> <td>49.36</td> <td>8.98</td> <td>58.34</td> <td>68.30</td> <td>-9.96</td> <td>peak</td> <td>P</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F	1 *	11400.456	39.54	8.98	48.52	54.00	-5.48	AVG	P	2	11400.775	49.36	8.98	58.34	68.30	-9.96	peak	P
No.	Frequency (MHz)	Reading (dB _u V)	Factor (dB/m)	Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Detector	P/F																						
1 *	11400.456	39.54	8.98	48.52	54.00	-5.48	AVG	P																						
2	11400.775	49.36	8.98	58.34	68.30	-9.96	peak	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB _u V/m)= Corr. (dB/m)+ Read Level (dB _u V) 3. Margin (dB) = Peak/AVG (dB _u V/m)-Limit PK/AVG(dB _u V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														



Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11 ax(HE20) Mode 5720MHz (U-NII-2C) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11 ax(HE20) Mode 5720MHz (U-NII-2C) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11n(HT40) Mode 5510MHz (U-NII-2C) -BF		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11n(HT40) Mode 5510MHz (U-NII-2C) -BF		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Horizontal												
Test Mode:	TX 802.11n(HT40) Mode 5550MHz (U-NII-2C) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													

Temperature:	24.3°C		Relative Humidity:	52%									
Test Voltage:	AC 120V/60Hz												
Ant. Pol.	Vertical												
Test Mode:	TX 802.11n(HT40) Mode 5550MHz (U-NII-2C) -BF												
Remark:													
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)													
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)													
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)													
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.													
5. No report for the emission which more than 20dB below the prescribed limit.													



Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11n(HT40) Mode 5670MHz (U-NII-2C) -BF		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			

Temperature:	24.3°C	Relative Humidity:	52%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11n(HT40) Mode 5670MHz (U-NII-2C) -BF		
Remark:			
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)			
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)			
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)			
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.			
5. No report for the emission which more than 20dB below the prescribed limit.			



Temperature:	24.3°C	Relative Humidity:	52%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Horizontal																													
Test Mode:	TX 802.11n(HT40) Mode 5710MHz (U-NII-2C) -BF																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBμV)</th> <th>Factor (dB/m)</th> <th>Level (dBμV/m)</th> <th>Limit (dBμV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>11420.234</td> <td>38.58</td> <td>8.98</td> <td>47.56</td> <td>54.00</td> <td>-6.44</td> <td>AVG</td> <td>P</td> </tr> <tr> <td>2</td> <td>11420.698</td> <td>49.77</td> <td>8.98</td> <td>58.75</td> <td>68.30</td> <td>-9.55</td> <td>peak</td> <td>P</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F	1 *	11420.234	38.58	8.98	47.56	54.00	-6.44	AVG	P	2	11420.698	49.77	8.98	58.75	68.30	-9.55	peak	P
No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F																						
1 *	11420.234	38.58	8.98	47.56	54.00	-6.44	AVG	P																						
2	11420.698	49.77	8.98	58.75	68.30	-9.55	peak	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														

Temperature:	24.3°C	Relative Humidity:	52%																											
Test Voltage:	AC 120V/60Hz																													
Ant. Pol.	Vertical																													
Test Mode:	TX 802.11n(HT40) Mode 5710MHz (U-NII-2C) -BF																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBμV)</th> <th>Factor (dB/m)</th> <th>Level (dBμV/m)</th> <th>Limit (dBμV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>11420.659</td> <td>49.54</td> <td>8.98</td> <td>58.52</td> <td>68.30</td> <td>-9.78</td> <td>peak</td> <td>P</td> </tr> <tr> <td>2 *</td> <td>11420.674</td> <td>38.95</td> <td>8.98</td> <td>47.93</td> <td>54.00</td> <td>-6.07</td> <td>AVG</td> <td>P</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F	1	11420.659	49.54	8.98	58.52	68.30	-9.78	peak	P	2 *	11420.674	38.95	8.98	47.93	54.00	-6.07	AVG	P
No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F																						
1	11420.659	49.54	8.98	58.52	68.30	-9.78	peak	P																						
2 *	11420.674	38.95	8.98	47.93	54.00	-6.07	AVG	P																						
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. 5. No report for the emission which more than 20dB below the prescribed limit.																														

