

RF EXPOSURE REPORT

Applicant	:	Shenzhen SDMC Technology Co.,Ltd
Address of Applicant		Room 1022, Floor 10, Building A, Customs Building, No. 2, Xin'an 3rd Road, Dalang Community, Xin'an Street, Bao'an District, Shenzhen, China
Manufacturer	:	Shenzhen SDMC Technology Co.,Ltd
Address of Manufacturer		Room 1022, Floor 10, Building A, Customs Building, No. 2, Xin'an 3rd Road, Dalang Community, Xin'an Street, Bao'an District, Shenzhen, China
Equipment under Test	ent under Test : Wi-Fi BT Module	
Model No.	••	CDW-N37663U-02
FCC ID	/	2AW68-N37663U
Test Standard(s) : KDB447498 D01 General RF Exposure Guid		KDB447498 D01 General RF Exposure Guidance v06
Report No.	:	DDT-RE24070224-1E02
Issue Date	:	2024/08/29
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808



Table of Contents

1.	General Test Information	5
1.1.	Description of EUT	5
1.2.	Accessories of EUT	5
1.3.	Test laboratory	5
2.	RF Exposure evaluation for FCC	6
2.1.	Assessment procedure	6
2.2.	Assess result	7
3.	Photos of the EUT	8

Test Report Declare

Applicant	:	Shenzhen SDMC Technology Co.,Ltd			
Address of Applicant		Room 1022, Floor 10, Building A, Customs Building, No. 2, Kin'an 3rd Road, Dalang Community, Xin'an Street, Bao'an District, Shenzhen, China			
Equipment under Test		Wi-Fi BT Module			
Model No.		CDW-N37663U-02			
Manufacturer		Shenzhen SDMC Technology Co.,Ltd			
Address of Manufacturer		Room 1022, Floor 10, Building A, Customs Building, No. 2, Xin'an 3rd Road, Dalang Community, Xin'an Street, Bao'an District, Shenzhen, China			

Test Standard Used:

KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE24070224-1E02			
Date of Receipt:	2024/04/22 2024/07/09	II)ate of Lest:	2024/04/23~2024/06/05 2024/07/09~2024/08/26	

Prepared By:

Approved By:

Tiger Mo

Damon Mu

Tiger Mo/Engineer Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
	Initial issue ®	2024/08/29	®
	X X X X	*	

Report No.:DDT-RE24070224-1E02

1. General Test Information

1.1. Description of EUT

EUT Name	:	Wi-Fi BT Module
Model Number	:	CDW-N37663U-02
EUT Function Description	:	Please reference user manual of this device
Power Supply	:	DC 3.3V

Note: This EUT support Bluetooth BR/EDR/LE, 2.4 GHz WLAN, 5 GHz WLAN.

Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

"⊠" means to be chosen or applicable; "□" means don't to be chosen or not applicable; This note applies to entire report.

1.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
/ ®	/	®/	@/

1.3. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, http://www.dgddt.com, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2. RF Exposure evaluation for FCC

2.1. Assessment procedure

Requirement:

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic FieldStrength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time $ E ^2, H ^2 \text{ or S}$ (minutes)	
0.3-1.34	614	1.63	(100)*	30	
1.34-30	824/f	2.19/f	(180/f)*	30	
30-300	27.5	0.073	0.2	30	
300-1500		*Or	F/1500	30	
1500-100000		10/	1.0	30	

Note: f= frequency in MHz; *Plane-wave equivalent power density

Calculation method

$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d}$$
 Power Density: $S(mW/cm^2) = \frac{E^2}{377}$

E = Electric field (V/m)

P = Peak RF output power (mW)

G = EUT Antenna numeric gain (numeric)=

d = Separation distance between radiator and human body (m)

The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \text{ or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2 m, as well as the gain of the used antenna, the RF power density can be obtained.

2.2. Assess result

Mode	Output power (dBm)	Output power (mW)	tune up power (dBm)	tune up power (mW)	Antenna Gain (dBi)	Antenna Gain (linear)	MPE Values (mW/cm ²)	MPE Limit (mW/cm ²)
BT	7.28	5.35	8	6.31	1.90	1.55	0.0016	1
BLE	4.54	2.84	5	3.16	1.90	1.55	0.0009	1
2.4G WIFI	18.18	65.77	19	79.43	3.34	2.16	0.0282	1
5G WIFI	19.53	89.74	20	100	6.72	4.70	0.0839	1

Simultaneous transmit evaluation worst result: BT+5G WIFI:0.0016+0.0839=0.0855<1.

Note1: The estimation distance is 20 cm

Conclusion: MPE evaluation required since transmitter power is below FCC threshold

3. Photos of the EUT

Please refer to DDT-Q24070224-1E appendix I

-----End Report-----