

RF Exposure Evaluation

**Test report
On Behalf of
Seaver
For
CeeFit
Model No.: Y2, SeaverV2**

FCC ID: 2AW7G-SEAVERY2

Prepared for : Seaver
17 rue claude bloch 14000 caen, France Zip code: 14000

Prepared By : Shenzhen HUAK Testing Technology Co., Ltd.
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street,
Bao'an District, Shenzhen City, China

Date of Test: Jul. 10, 2020 -- Jul. 22, 2020

Date of Report: Jul. 22, 2020

1 General Description of EUT

Product Name:	CeeFit
Model/Type reference:	Y2
Serial Model:	SeaverV2
Trade Mark:	Seaver
FCC ID	2AW7G-SEAVERY2
Hardware Version:	V1.0
Software Version:	V1.15.0
Operation frequency:	2402MHz ~ 2480MHz
Channel separation:	2MHz
Channel number:	40
Modulation Technology:	GFSK
Antenna Type:	PCB Antenna
Antenna Gain:	0dBi
Power Supply:	DC3.7V from battery

2 RF Exposure Compliance Requirement

2.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

2.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}$$

Where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The results are rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

3 EUT RF Exposure

For BLE

GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	-0.62	-1±1	0	1.000	0.310	3.0
Middle (2440MHz)	-1.331	-1±1	0	1.000	0.312	
Highest (2480MHz)	-0.946	-1±1	0	1.000	0.315	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: HK2007211846-E