

RF Test Report

For

HANGZHOU LIJIACHENG ELECTRIC CO., LTD

Test Standards:	<u>Part 15C Subpart C §15.247</u>
Product Name:	<u>WiFi Smart Bulb</u>
Tested Model:	<u>HT-US-G10A199W850-RGBCW2E-V#</u>
Brand Name:	<u>HENGTE</u>
FCC ID:	<u>2AW8CG10A199W</u>
Classification	<u>(DTS) Digital Transmission System</u>
Report No.:	<u>EC2008036RF01</u>
Tested Date:	<u>2020-08-25 to 2020-09-22</u>
Issued Date:	<u>2020-09-22</u>
Prepared By:	<u>Jack Liu.</u> Jack Liu / Engineer
Approved By:	<u>Bacon Wu</u> Bacon Wu / RF Manager

Hunan Ecloud Testing Technology Co., Ltd.

Building A1, Changsha E Center, No. 18 Xiangtai Avenue, Liuyang Economic and
Technological Development Zone, Hunan, P.R.C

Tel.: +86-731-89634887 Fax.: +86-731-89634887

www.hn-ecloud.com

Note: The test results in this report apply exclusively to the tested model / sample. Without written approval of Hunan Ecloud Testing Technology Co., Ltd., the test report shall not be reproduced except in full.

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	2020.09.22	Valid	Original Report

TABLE OF CONTENTS

1	TEST LABORATORY	5
1.1	Test facility	5
2	GENERAL DESCRIPTION.....	6
2.1	Applicant	6
2.2	Manufacturer	6
2.3	General Description Of EUT	6
2.4	Modification of EUT	7
2.5	Applicable Standards	7
3	TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	8
3.1	Descriptions of Test Mode	8
3.2	Test Mode	8
3.3	Support Equipment	9
3.4	Test Setup	9
3.5	Measurement Results Explanation Example	12
4	TEST RESULT	13
4.1	DTS and Occupied Channel Bandwidth Measurement	13
4.2	Maximum Conducted Output Power Measurement	14
4.3	Maximum Power Spectral Density Measurement	15
4.4	Band Edges and Spurious Emission Measurement	16
4.5	Radiated Band Edges and Spurious Emission Measurement	17
4.6	AC Conducted Emission Measurement	99
4.7	Antenna Requirements	102
5	LIST OF MEASURING EQUIPMENT	103
6	UNCERTAINTY OF EVALUATION.....	105
	Appendix A: DTS Bandwidth.....	106
	Appendix B: Occupied Channel Bandwidth	112
	Appendix C: Maximum conducted output power	118
	Appendix D: Duty Cycle.....	124
	Appendix E: Maximum power spectral density.....	130
	Appendix F: Band edge measurements	138
	Appendix G: Conducted Spurious Emission	142
	Appendix H: Setup Photographs	157

Summary Of Test Result

FCC Rule	Description	Limit	Result	Remark
15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
-	99% Bandwidth	-	Pass	-
15.247(b)(3)	Peak Output Power	$\leq 30\text{dBm}$	Pass	-
15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
15.247(d)	Conducted Band Edges and Spurious Emission	$\leq 20\text{dBc}$	Pass	-
15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 2.03 dB at 2390 MHz
15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 17.02 dB at 0.576 MHz
15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

1 Test Laboratory

1.1 Test facility

CNAS (accreditation number: L11138)

Hunan Ecloud Testing Technology Co., Ltd. has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS).

FCC (Designation number: CN1244 , Test Firm Registration Number: 793308)

Hunan Ecloud Testing Technology Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

ISED(CAB identifier: CN0012, ISED# :24347)

Hunan Ecloud Testing Technology Co., Ltd. has been listed on the Wireless Device Testing Laboratories list of innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements.

A2LA (Certificate Code : 4895.01)

Hunan Ecloud Testing Technology Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

2 General Description

2.1 Applicant

HANGZHOU LIJIACHENG ELECTRIC CO., LTDD
NO 35 YANGSHAN ROAD,GAOHONG ZONE,HANGZHOU City,China

2.2 Manufacturer

HANGZHOU LIJIACHENG ELECTRIC CO., LTD
NO 35 YANGSHAN ROAD,GAOHONG ZONE,HANGZHOU City,China

2.3 General Description Of EUT

Product	WiFi Smart Bulb
Model No.	HT-US-G10A199W850-RGBCW2E-V#
Brand Name	HENGTE
Additional No.	NA
Difference Description	NA
FCC ID	2AW8CG10A199W
Power Supply	120Vac
Modulation Technology	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
Modulation Type	802.11b : DSSS 802.11g/n : OFDM
Operating Frequency	2412-2462MHz
Number Of Channel	11
Max. Output Power	802.11b : 17.05 dBm (0.0507 W) 802.11g : 13.19 dBm (0.0208 W) 802.11n HT20 : 13.00 dBm (0.020 W)
Max. e.i.r.p.	21.28 (0.134W)
Antenna Type	Monopole Antenna type with 4.23dBi gain
HW Version	V1.3
SW Version	V1.0
I/O Ports	Refer to user's manual

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

2.4 Modification of EUT

No modifications are made to the EUT during all test items.

2.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ ANSI C63.10-2013
- ♦ KDB 558074 D01 15.247 Meas Guidance v05r02

Remark:

1. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B , recorded in a separate test report.

3 Test Configuration of Equipment Under Test

3.1 Descriptions of Test Mode

11 channels are provided for 802.11b, 802.11g and 802.11n(HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

The transmitter has a maximum peak conducted output power as follows:

Frequency Range(MHz)	Mode	Rate	Output Power(dBm)
2412~2462	802.11b	1Mbps	17.05
2412~2462	802.11g	6Mbps	13.19
2412~2462	802.11n HT20	MCS0	13.00

- Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

3.2 Test Mode

3.2.1 Antenna Port Conducted Measurement

Summary table of Test Cases			
Test Item	Modulation		
	802.11 b	802.11 g	802.11n HT20
Conducted Test Cases	Mode 1: CH01	Mode 1: CH01	Mode 1: CH01
	Mode 2: CH06	Mode 2: CH06	Mode 2: CH06
	Mode 3: CH011	Mode 3: CH011	Mode 3: CH011

3.2.2 Radiated Emission Test (Below 1GHz)

Radiated Test Cases	802.11 b
	Mode 1: CH01

Note : 1. Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna

diversity architecture) and packet type. Z orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Z orientation.

2. Following channel(s) was (were) selected for the final test as listed above

3.2.3 Radiated Emission Test (Above 1GHz)

Test Item	Modulation		
	802.11 b	802.11 g	802.11n HT20
Radiated Test Cases	Mode 1: CH01	Mode 1: CH01	Mode 1: CH01
	Mode 2: CH06	Mode 2: CH06	Mode 2: CH06
	Mode 3: CH11	Mode 3: CH11	Mode 3: CH11

Note : 1. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that Z orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Z orientation.

2. Following channel(s) was (were) selected for the final test as listed above

3. For frequency above 18GHz, the measured value is much lower than the limit, therefore, it is not reflected in the report.

3.2.4 Power Line Conducted Emission Test:

AC Conducted Emission	Mode 1 : WLAN Linking + Lighting
-----------------------	----------------------------------

3.3 Support Equipment


Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	NETGEAR	R7800	PY315100319	N/A	shielded, 1.8 m
2.	Notebook	Lenovo	E470C	FCC sDoC	N/A	shielded cable DC O/P 1.8 m unshielded AC I/P cable1.2 m

3.4 Test Setup


The EUT is continuously communicating to the WIFI tester during the tests.

EUT was set in the Hidden menu mode to enable WIFI communications.


The following picture is a screenshot of the test software




Setup diagram for Conducted Test




Setup diagram for Radiation(9KHz~30MHz) Test




Setup diagram for Radiation(Below 1G) Test



Setup diagram for Radiation(Above1G) Test



Setup diagram for AC Conducted Emission Test



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.5 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 5 + 10 = 15 \text{ (dB)} \end{aligned}$$

For all radiated test items:

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

Over Limit (dB μ V/m) = Level(dB μ V/m) - Limit Level (dB μ V/m)

4 Test Result

4.1 DTS and Occupied Channel Bandwidth Measurement

4.1.1 Limit of 6dB Bandwidth

FCC §15.247 (a) (2)

The minimum 6 dB bandwidth shall be at least 500 kHz.

4.1.2 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v05r02.
2. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
3. Turn on the EUT and connect it to measurement instrument.
4. Set to the maximum power setting and enable Transmitting the EUT transmit continuously
5. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
6. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) setting should be 1%-5% of OBW, please revise and set the Video bandwidth (VBW) $\geq 3 \times$ RBW.

4.1.3 Test Result of 6dB Bandwidth

Refer to Appendix A of this test report.

4.1.4 Test Result of 99% Bandwidth

Refer to Appendix B of this test report.

4.2 Maximum Conducted Output Power Measurement

4.2.1 Limit of Output Power

FCC §15.247 (b)(3)

For systems using digital modulation in the 2400-2483.5 MHz bands: 30dBm.

4.2.2 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 section 11.9.2.2.4 Measurement using a spectrum analyzer.
2. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
3. Turn on the EUT and connect it to spectrum analyzer.
4. Set to the maximum power setting and enable Transmitting the EUT transmit continuously
5. Measure the duty cycle, x , of the transmitter output signal as described in below:
 - a. Set the center frequency of the instrument to the center frequency of the transmission.
 - b. Set RBW to the largest available Transmitting value.
 - c. Set detector = peak
6. Set span to at least $1.5 \times \text{OBW}$. Set RBW=510KHz, VBW=2MHz, Number of points in sweep $\geq 2/3 \times$ span, Sweep time = auto. Detector = RMS
7. Allow the sweep to "free run". Trace average 100 traces in RMS mode
8. Compute power by integrating the spectrum across the OBW of the signal using the instrument's Channel power measurement function with band limits set equal to the OBW band edges.
9. Add $10 \log (1/x)$, where x is the duty cycle. The duty cycle factor has been compensated to the "offset" of the spectrum analyser.

4.2.3 Test Result of Peak Output Power

Refer to Appendix C of this test report.

4.2.4 Test Result of Duty Cycle

Refer to Appendix D of this test report.

4.3 Maximum Power Spectral Density Measurement

4.3.1 Limits of Power Spectral Density

FCC§15.247(e)

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

4.3.2 Test Procedure

1. The testing follows Measurement Procedure 8.4 DTS maximum power spectral density level in the fundamental emission of ANSI C63.10-2013 section 11.9.2.2.4
2. Turn on the EUT and connect it to measurement instrument.
3. Measure the duty cycle, x , of the transmitter output signal as described in below:
 - a. Set the center frequency of the instrument to the center frequency of the transmission.
 - b. Set RBW to the largest available Transmitting value.
 - c. Set detector = peak
4. Set span to at least $1.5 \times \text{OBW}$. Set RBW= 30 KHz, VBW=100 KHz, Number of points in sweep $\geq 2/3 \times \text{span}$, Sweep time = auto.
5. Detector = power averaging (rms), Sweep time = auto couple, Trace mode = averaging (rms) mode over a minimum of 100 traces. Use the peak marker function to determine the maximum power level.
6. Add $10 \log(1/x)$, where x is the duty cycle.
7. Measure and record the results in the test report.
8. The Measured power density (dBm)/ 100kHz is a reference level and used as 30dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.
9. Add $10 \log(1/x)$, where x is the duty cycle. The duty cycle factor has been compensated to the ‘offset’ of the spectrum analyser.

4.3.3 Test Result of Power Spectral Density

Refer to Appendix E of this test report.

4.4 Band Edges and Spurious Emission Measurement

4.4.1 Limit of Conducted Band Edges and Spurious Emission

FCC §15.247 (d)

Maximum conducted (average) output power was used to determine compliance, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).

4.4.2 Test Procedures

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument.
3. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
4. Measure and record the results in the test report.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

4.4.3 Test Result of Conducted Band Edges

Refer to Appendix F of this test report.

4.4.4 Test Result of Conducted Spurious Emission

Refer to Appendix G of this test report.

4.5 Radiated Band Edges and Spurious Emission Measurement

4.5.1 Limit of Radiated Band Edges and Spurious Emission

FCC §15.247 (d)

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 30 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.


Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

4.5.2 Test Procedures


1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The measurement distance is 3 meter.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz, RBW=1MHz for $f > 1$ GHz ; VBW RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement:
VBW = 10 Hz, when duty cycle is no less than 98 percent.
VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control

level for the tested mode of operation.


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	99.79	8.38	0.12	10Hz
802.11g	98.92	1.39	0.72	10Hz
802.11n HT20	98.75	1.30	0.77	10Hz



802.11b



802.11g



802.11n HT20

6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level


4.5.3 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

4.5.4 Test Result of Radiated Spurious at Band Edges

Test Mode :	802.11b CH01 (2412 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.425GHz	Polarization :	Horizontal


Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11b CH01(2412MHz)	Power rating:	120VAC



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamplifier factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	44.42	27.38	4.11	35.61	40.30	74.00	-33.70	Peak
2390.000	65.03	27.56	4.18	35.79	60.98	74.00	-13.02	Peak
2411.875	111.90	27.61	4.20	35.84	107.87	74.00	33.87	Peak


Test Mode :	802.11b CH01 (2412 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.425GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11b CH01(2412MHz)	Power rating:	120Vac



Test Mode :	802.11b CH01 (2412 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.425GHz	Polarization :	Vertical


Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11b CH01(2412MHz)	Power rating:	120VAc



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	46.45	27.38	4.11	35.61	42.33	74.00	-31.67	Peak
2390.000	65.77	27.56	4.18	35.79	61.72	74.00	-12.28	Peak
2412.125	112.69	27.61	4.20	35.84	108.66	74.00	34.66	Peak


Test Mode :	802.11b CH01 (2412 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.425GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11b CH01(2412MHz)	Power rating:	120Vac



Test Mode :	802.11b CH11 (2462 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.45GHz~2.51GHz	Polarization :	Horizontal


Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11b CH11(2462MHz)	Power rating:	120VAc



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2461.760	113.63	27.72	4.24	35.95	109.64	74.00	35.64	Peak
2483.500	61.03	27.76	4.26	36.00	57.05	74.00	-16.95	Peak
2500.000	50.16	27.80	4.28	36.04	46.20	74.00	-27.80	Peak

Test Mode :	802.11b CH11 (2462 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.45GHz~2.51GHz	Polarization :	Horizontal


Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11b CH11(2462MHz)	Power rating:	120VAc



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2461.280	105.91	27.71	4.24	35.95	101.91	54.00	47.91	Average
2483.500	49.26	27.76	4.26	36.00	45.28	54.00	-8.72	Average
2500.000	38.25	27.80	4.28	36.04	34.29	54.00	-19.71	Average

Test Mode :	802.11b CH11 (2462 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.45GHz~2.51GHz	Polarization :	Vertical


Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11b CH11(2462MHz)	Power rating:	120VAc



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2462.180	113.06	27.72	4.24	35.95	109.07	74.00	35.07	Peak
2483.500	61.07	27.76	4.26	36.00	57.09	74.00	-16.91	Peak
2500.000	50.52	27.80	4.28	36.04	46.56	74.00	-27.44	Peak

Test Mode :	802.11b CH11 (2462 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.45GHz~2.51GHz	Polarization :	Vertical


Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11b CH11(2462MHz)	Power rating:	120VAc



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2462.780	105.89	27.72	4.24	35.96	101.89	54.00	47.89	Average
2483.500	50.32	27.76	4.26	36.00	46.34	54.00	-7.66	Average
2500.000	39.84	27.80	4.28	36.04	35.88	54.00	-18.12	Average

Test Mode :	802.11g CH01 (2412 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.425GHz	Polarization :	Horizontal


Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11g CH01(2412MHz)	Power rating:	120Wac



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	47.67	27.38	4.11	35.61	43.55	74.00	-30.45	Peak
2390.000	74.10	27.56	4.18	35.79	70.05	74.00	-3.95	Peak
2412.750	107.79	27.61	4.20	35.84	103.76	74.00	29.76	Peak


Test Mode :	802.11g CH01 (2412 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.425GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11g CH01(2412MHz)	Power rating:	120Vac



Test Mode :	802.11g CH01 (2412 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.425GHz	Polarization :	Vertical


Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11g CH01(2412MHz)	Power rating:	120VAc



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	46.38	27.38	4.11	35.61	42.26	74.00	-31.74	Peak
2390.000	73.72	27.56	4.18	35.79	69.67	74.00	-4.33	Peak
2408.125	107.39	27.60	4.20	35.83	103.36	74.00	29.36	Peak


Test Mode :	802.11g CH01 (2412 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.425GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11g CH01(2412MHz)	Power rating:	120VAc



Test Mode :	802.11g CH11 (2462 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.45GHz~2.51GHz	Polarization :	Horizontal


Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11g CH11(2462MHz)	Power rating:	120Vac



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamplifier factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2462.840	110.59	27.72	4.24	35.96	106.59	74.00	32.59	Peak
2483.500	69.02	27.76	4.26	36.00	65.04	74.00	-8.96	Peak
2500.000	51.80	27.80	4.28	36.04	47.84	74.00	-26.16	Peak


Test Mode :	802.11g CH11 (2462 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.45GHz~2.51GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11g CH11(2462MHz)	Power rating:	120VAc



Test Mode :	802.11g CH11 (2462 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.45GHz~2.51GHz	Polarization :	Vertical


Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11g CH11(2462MHz)	Power rating	: 120VAc



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2463.020	105.96	27.72	4.24	35.96	101.96	74.00	27.96	Peak
2483.500	63.27	27.76	4.26	36.00	59.29	74.00	-14.71	Peak
2500.000	47.52	27.80	4.28	36.04	43.56	74.00	-30.44	Peak

Test Mode :	802.11g CH11 (2462 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.45GHz~2.51GHz	Polarization :	Vertical


Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11g CH11(2462MHz)	Power rating:	120VAc



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2460.800	92.51	27.71	4.24	35.95	88.51	54.00	34.51	Average
2483.500	41.27	27.76	4.26	36.00	37.29	54.00	-16.71	Average
2500.000	32.65	27.80	4.28	36.04	28.69	54.00	-25.31	Average

Test Mode :	802.11n HT20 CH01 (2412 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.425GHz	Polarization :	Horizontal


Test Site : 3m Chamber
 Temp/Humi : 22℃/64%
 Tested by : Jack
 Pol/Phase : HORIZONTAL
 Test Mode : 802.11N HT20 CH01(2412MHz)
 Power rating: 120Vac



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	49.30	27.38	4.11	35.61	45.18	74.00	-28.82	Peak
2390.000	75.27	27.56	4.18	35.79	71.22	74.00	-2.78	Peak
2408.250	110.70	27.60	4.20	35.83	106.67	74.00	32.67	Peak


Test Mode :	802.11n HT20 CH01 (2412 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.425GHz	Polarization :	Horizontal

Test Site : 3m Chamber
 Temp/Humi : 22℃/64%
 Tested by : Jack
 Pol/Phase : HORIZONTAL
 Test Mode : 802.11N HT20 CH01(2412MHz)
 Power rating: 120VAc



Test Mode :	802.11n HT20 CH01 (2412 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.425GHz	Polarization :	Vertical


Test Site : 3m Chamber
 Temp/Humi : 22℃/64%
 Tested by : Jack
 Pol/Phase : VERTICAL
 Test Mode : 802.11N HT20 CH01(2412MHz)
 Power rating: 120Vac



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	48.08	27.38	4.11	35.61	43.96	74.00	-30.04	Peak
2390.000	73.74	27.56	4.18	35.79	69.69	74.00	-4.31	Peak
2408.375	108.22	27.60	4.20	35.83	104.19	74.00	30.19	Peak


Test Mode :	802.11n HT20 CH01 (2412 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.3GHz~2.425GHz	Polarization :	Vertical

Test Site : 3m Chamber
 Temp/Humi : 22℃/64%
 Tested by : Jack
 Pol/Phase : VERTICAL
 Test Mode : 802.11N HT20 CH01(2412MHz)
 Power rating: 120Vac



Test Mode :	802.11n HT20 CH11 (2462 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.45GHz~2.51GHz	Polarization :	Horizontal


Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11N HT20 CH11(2462MHz)	Power rating:	120Vac



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2458.100	112.26	27.71	4.24	35.94	108.27	74.00	34.27	Peak
2483.500	73.26	27.76	4.26	36.00	69.28	74.00	-4.72	Peak
2500.000	53.88	27.80	4.28	36.04	49.92	74.00	-24.08	Peak

Test Mode :	802.11n HT20 CH11 (2462 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.45GHz~2.51GHz	Polarization :	Horizontal


Test Site : 3m Chamber
 Temp/Humi : 22℃/64%
 Tested by : Jack
 Pol/Phase : HORIZONTAL
 Test Mode : 802.11N HT20 CH11(2462MHz)
 Power rating: 120Vac



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2460.740	101.76	27.71	4.24	35.95	97.76	54.00	43.76	Average
2483.500	55.56	27.76	4.26	36.00	51.58	54.00	-2.42	Average
2500.000	40.18	27.80	4.28	36.04	36.22	54.00	-17.78	Average

Test Mode :	802.11n HT20 CH11 (2462 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.45GHz~2.51GHz	Polarization :	Vertical


Test Site : 3m Chamber
 Temp/Humi : 22℃/64%
 Tested by : Jack
 Pol/Phase : VERTICAL
 Test Mode : 802.11N HT20 CH11(2462MHz)
 Power rating: 120Vac



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2458.400	106.99	27.71	4.24	35.95	102.99	74.00	28.99	Peak
2483.500	68.17	27.76	4.26	36.00	64.19	74.00	-9.81	Peak
2500.000	50.43	27.80	4.28	36.04	46.47	74.00	-27.53	Peak

Test Mode :	802.11n HT20 CH11 (2462 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	2.45GHz~2.51GHz	Polarization :	Vertical


Test Site : 3m Chamber
 Temp/Humi : 22℃/64%
 Tested by : Jack
 Pol/Phase : VERTICAL
 Test Mode : 802.11N HT20 CH11(2462MHz)
 Power rating: 120VAc



4.5.5 Test Result of Radiated Spurious Emission (1GHz ~ 10th Harmonic)

Test Mode :	802.11b CH01 (2412 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal

Test Site : 3m Chamber	Temp/Humi : 22℃/64%
Tested by : Jack	Pol/Phase : HORIZONTAL
Test Mode : 802.11b CH01(2412MHz)	Power rating: 120VAC



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2412.000	113.09	27.61	4.20	35.84	109.06	74.00	35.06	Peak

Test Mode :	802.11b CH01 (2412 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Test Site : 3m Chamber

Temp/Humi : 22℃/64%


Tested by : Jack

Pol/Phase : HORIZONTAL


Test Mode : 802.11b CH01(2412MHz)

Power rating: 120VAc

Data: 3




Test Site	: 3m Chamber	Temp/Humi	: 22°C/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11b CH01(2412MHz)	Power rating:	: 120VAc



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11b CH01 (2412 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11b CH01(2412MHz)	Power rating:	120VAc



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2412.000	109.39	27.61	4.20	35.84	105.36	74.00	31.36	Peak

Test Mode :	802.11b CH01 (2412 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Test Site : 3m Chamber

Temp/Humi : 22℃/64%


Tested by : Jack

Pol/Phase : VERTICAL


Test Mode : 802.11b CH01(2412MHz)

Power rating: 120VAc

Data: 1




Test Site	: 3m Chamber	Temp/Humi	: 22°C/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11b CH01(2412MHz)	Power rating:	: 120VAC



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11b CH06 (2437MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11b CH06(2437MHz)	Power rating:	120VAc



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2437.000	112.40	27.66	4.22	35.90	108.38	74.00	34.38	Peak

Test Mode :	802.11b CH06 (2437MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Test Site : 3m Chamber

Temp/Humi : 22℃/64%


Tested by : Jack

Pol/Phase : HORIZONTAL


Test Mode : 802.11b CH06(2437MHz)

Power rating: 120VAc

Data: 5




Test Site	: 3m Chamber	Temp/Humi	: 22°C/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11b CH06(2437MHz)	Power rating:	: 120VAC



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11b CH06 (2437MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11b CH06(2437MHz)	Power rating:	120VAc



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2437.000	109.54	27.66	4.22	35.90	105.52	74.00	31.52	Peak

Test Mode :	802.11b CH06 (2437MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Test Site : 3m Chamber

Temp/Humi : 22℃/64%


Tested by : Jack

Pol/Phase : VERTICAL


Test Mode : 802.11b CH06(2437MHz)

Power rating: 120VAc

Data: 7




Test Site	: 3m Chamber	Temp/Humi	: 22°C/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11b CH06(2437MHz)	Power rating:	: 120VAC



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11b CH11 (2462MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11b CH11(2462MHz)	Power rating:	120VAc



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2462.000	108.58	27.72	4.24	35.95	104.59	74.00	30.59	Peak

Test Mode :	802.11b CH11 (2462MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Test Site : 3m Chamber

Temp/Humi : 22℃/64%


Tested by : Jack

Pol/Phase : HORIZONTAL


Test Mode : 802.11b CH11(2462MHz)

Power rating: 120VAC

Data: 11




Test Site	: 3m Chamber	Temp/Humi	: 22°C/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11b CH11(2462MHz)	Power rating:	: 120VAC



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11b CH11 (2462MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11b CH11(2462MHz)	Power rating:	: 120VAc



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2462.000	108.49	27.72	4.24	35.95	104.50	74.00	30.50	Peak

Test Mode :	802.11b CH11 (2462MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Test Site : 3m Chamber

Temp/Humi : 22℃/64%


Tested by : Jack

Pol/Phase : VERTICAL


Test Mode : 802.11b CH11(2462MHz)

Power rating: 120VAc

Data: 9



Test Site	: 3m Chamber	Temp/Humi	: 22°C/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11b CH11(2462MHz)	Power rating:	: 120VAC



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4924.000	64.32	31.09	6.08	58.11	43.38	54.00	-10.62	Average
4924.000	70.51	31.09	6.08	58.11	49.57	74.00	-24.43	Peak
7386.000	51.18	35.83	9.18	58.59	37.60	54.00	-16.40	Average
7386.000	64.06	35.83	9.18	58.59	50.48	74.00	-23.52	Peak
9848.000	49.58	38.58	12.83	57.89	43.10	54.00	-10.90	Average
9848.000	62.68	38.58	12.83	57.89	56.20	74.00	-17.80	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11g CH01 (2412 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal

Test Site : 3m Chamber

Temp/Humi : 22℃/64%


Tested by : Jack

Pol/Phase : HORIZONTAL

Test Mode : 802.11g CH01(2412MHz)

Power rating: 120VAc

Data: 96



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2412.000	107.25	27.61	4.20	35.84	103.22	74.00	29.22	Peak

Test Mode :	802.11g CH01 (2412 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Test Site : 3m Chamber

Temp/Humi : 22℃/64%


Tested by : Jack

Pol/Phase : HORIZONTAL


Test Mode : 802.11g CH01(2412MHz)

Power rating: 120VAc

Data: 13



Test Site	: 3m Chamber	Temp/Humi	: 22°C/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11g CH01(2412MHz)	Power rating:	: 120VAC




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4824.000	59.82	30.95	6.09	58.24	38.62	54.00	-15.38	Average
4824.000	68.09	30.95	6.09	58.24	46.89	74.00	-27.11	Peak
7236.000	52.58	35.47	9.21	58.53	38.73	54.00	-15.27	Average
7236.000	67.51	35.47	9.21	58.53	53.66	74.00	-20.34	Peak
9648.000	50.21	38.42	12.32	58.03	42.92	54.00	-11.08	Average
9648.000	63.08	38.42	12.32	58.03	55.79	74.00	-18.21	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11g CH01 (2412 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11g CH01(2412MHz)	Power rating:	120VAc



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2412.000	103.12	27.61	4.20	35.84	99.09	74.00	25.09	Peak

Test Mode :	802.11g CH01 (2412 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Test Site : 3m Chamber

Temp/Humi : 22℃/64%


Tested by : Jack

Pol/Phase : VERTICAL


Test Mode : 802.11g CH01(2412MHz)

Power rating: 120VAc

Data: 15



Test Site	: 3m Chamber	Temp/Humi	: 22°C/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11g CH01(2412MHz)	Power rating:	: 120VAC




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4824.000	58.16	30.95	6.09	58.24	36.96	54.00	-17.04	Average
4824.000	65.83	30.95	6.09	58.24	44.63	74.00	-29.37	Peak
7236.000	51.18	35.47	9.21	58.53	37.33	54.00	-16.67	Average
7236.000	65.28	35.47	9.21	58.53	51.43	74.00	-22.57	Peak
9648.000	50.27	38.42	12.32	58.03	42.98	54.00	-11.02	Average
9648.000	63.68	38.42	12.32	58.03	56.39	74.00	-17.61	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11g CH06 (2437MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11g CH06(2437MHz)	Power rating:	120VAc



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2437.000	109.58	27.66	4.22	35.90	105.56	74.00	31.56	Peak

Test Mode :	802.11g CH06 (2437MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Test Site : 3m Chamber

Temp/Humi : 22℃/64%


Tested by : Jack

Pol/Phase : HORIZONTAL


Test Mode : 802.11g CH06(2437MHz)

Power rating: 120VAc

Data: 19



Test Site	: 3m Chamber	Temp/Humi	: 22°C/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11g CH06(2437MHz)	Power rating:	: 120VAC




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4874.000	60.72	31.02	6.08	58.17	39.65	54.00	-14.35	Average
4874.000	66.49	31.02	6.08	58.17	45.42	74.00	-28.58	Peak
7311.000	51.31	35.65	9.20	58.56	37.60	54.00	-16.40	Average
7311.000	65.00	35.65	9.20	58.56	51.29	74.00	-22.71	Peak
9748.000	49.62	38.50	12.48	57.96	42.64	54.00	-11.36	Average
9748.000	62.61	38.50	12.48	57.96	55.63	74.00	-18.37	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11g CH06 (2437MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11g CH06(2437MHz)	Power rating:	: 120VAc



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2437.000	106.33	27.66	4.22	35.90	102.31	74.00	28.31	Peak

Test Mode :	802.11g CH06 (2437MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Test Site : 3m Chamber

Temp/Humi : 22℃/64%


Tested by : Jack

Pol/Phase : VERTICAL


Test Mode : 802.11g CH06(2437MHz)

Power rating: 120VAc

Data: 17




Test Site	: 3m Chamber	Temp/Humi	: 22°C/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11g CH06(2437MHz)	Power rating:	: 120VAc



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11g CH11 (2462MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11g CH11(2462MHz)	Power rating:	: 120VAc



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2462.000	108.22	27.72	4.24	35.95	104.23	74.00	30.23	Peak

Test Mode :	802.11g CH11 (2462MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Test Site : 3m Chamber

Temp/Humi : 22℃/64%


Tested by : Jack

Pol/Phase : HORIZONTAL


Test Mode : 802.11g CH11(2462MHz)

Power rating: 120VAc

Data: 21




Test Site	: 3m Chamber	Temp/Humi	: 22°C/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11g CH11(2462MHz)	Power rating:	: 120VAC



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11g CH11 (2462MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11g CH11(2462MHz)	Power rating	: 120VAc



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2462.000	102.55	27.72	4.24	35.95	98.56	74.00	24.56	Peak

Test Mode :	802.11g CH11 (2462MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Test Site : 3m Chamber

Temp/Humi : 22℃/64%


Tested by : Jack

Pol/Phase : VERTICAL


Test Mode : 802.11g CH11(2462MHz)

Power rating: 120VAc

Data: 23




Test Site	: 3m Chamber	Temp/Humi	: 22°C/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11g CH11(2462MHz)	Power rating:	: 120VAC



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11n HT20 CH01 (2412 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal


Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11N HT20 CH01(2412MHz)	Power rating:	120VAc



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2412.000	111.12	27.61	4.20	35.84	107.09	74.00	33.09	Peak


Test Mode :	802.11n HT20 CH01 (2412 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11N HT20 CH01(2412MHz)	Power rating:	120VAc



Test Site	: 3m Chamber	Temp/Humi	: 22°C/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11N HT20 CH01(2412MHz)	Power rating:	: 120VAC

Data: 28




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4824.000	59.72	30.95	6.09	58.24	38.52	54.00	-15.48	Average
4824.000	66.82	30.95	6.09	58.24	45.62	74.00	-28.38	Peak
7236.000	51.21	35.47	9.21	58.53	37.36	54.00	-16.64	Average
7236.000	68.85	35.47	9.21	58.53	55.00	74.00	-19.00	Peak
9648.000	51.85	38.42	12.32	58.03	44.56	54.00	-9.44	Average
9648.000	63.26	38.42	12.32	58.03	55.97	74.00	-18.03	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11n HT20 CH01 (2412 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical


Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11N HT20 CH01(2412MHz)	Power rating:	120VAc




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2412.000	104.60	27.61	4.20	35.84	100.57	74.00	26.57	Peak

Test Mode :	802.11n HT20 CH01 (2412 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11N HT20 CH01(2412MHz)	Power rating:	120VAc




Test Site	: 3m Chamber	Temp/Humi	: 22°C/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11N HT20 CH01(2412MHz)	Power rating:	: 120VAC



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11n HT20 CH06 (2437MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal


Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11N HT20 CH06(2437MHz)	Power rating:	120VAc




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2437.000	111.39	27.66	4.22	35.90	107.37	74.00	33.37	Peak

Test Mode :	802.11n HT20 CH06 (2437MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11N HT20 CH06(2437MHz)	Power rating:	120VAc



Test Site	: 3m Chamber	Temp/Humi	: 22°C/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11N HT20 CH06(2437MHz)	Power rating:	: 120VAC




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4874.000	60.38	31.02	6.08	58.17	39.31	54.00	-14.69	Average
4874.000	67.08	31.02	6.08	58.17	46.01	74.00	-27.99	Peak
7311.000	51.18	35.65	9.20	58.56	37.47	54.00	-16.53	Average
7311.000	64.81	35.65	9.20	58.56	51.10	74.00	-22.90	Peak
9748.000	49.75	38.50	12.48	57.96	42.77	54.00	-11.23	Average
9748.000	62.71	38.50	12.48	57.96	55.73	74.00	-18.27	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11n HT20 CH06 (2437MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical


Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11N HT20 CH06(2437MHz)	Power rating:	120VAc



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2437.000	108.15	27.66	4.22	35.90	104.13	74.00	30.13	Peak


Test Mode :	802.11n HT20 CH06 (2437MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11N HT20 CH06(2437MHz)	Power rating:	120VAC



Test Site	: 3m Chamber	Temp/Humi	: 22°C/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11N HT20 CH06(2437MHz)	Power rating:	: 120VAc

Data: 32




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4874.000	56.80	31.02	6.08	58.17	35.73	54.00	-18.27	Average
4874.000	65.28	31.02	6.08	58.17	44.21	74.00	-29.79	Peak
7311.000	50.71	35.65	9.20	58.56	37.00	54.00	-17.00	Average
7311.000	64.65	35.65	9.20	58.56	50.94	74.00	-23.06	Peak
9748.000	49.65	38.50	12.48	57.96	42.67	54.00	-11.33	Average
9748.000	62.87	38.50	12.48	57.96	55.89	74.00	-18.11	Peak

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11n HT20 CH11 (2462 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Horizontal


Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11N HT20 CH11(2462MHz)	Power rating:	120VAc




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2462.000	110.20	27.72	4.24	35.95	106.21	74.00	32.21	Peak

Test Mode :	802.11n HT20 CH11 (2462 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Horizontal

Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11N HT20 CH11(2462MHz)	Power rating:	120VAc




Test Site	: 3m Chamber	Temp/Humi	: 22°C/64%
Tested by	: Jack	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11N HT20 CH11(2462MHz)	Power rating:	: 120VAC



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Test Mode :	802.11n HT20 CH11 (2462 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	1GHz~3GHz	Polarization :	Vertical


Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11N HT20 CH11(2462MHz)	Power rating:	120VAc




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2462.000	105.90	27.72	4.24	35.95	101.91	74.00	27.91	Peak

Test Mode :	802.11n HT20 CH11 (2462 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	3GHz~18GHz	Polarization :	Vertical

Test Site	: 3m Chamber	Temp/Humi	: 22℃/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11N HT20 CH11(2462MHz)	Power rating	: 120VAc



Test Site	: 3m Chamber	Temp/Humi	: 22°C/64%
Tested by	: Jack	Pol/Phase	: VERTICAL
Test Mode	: 802.11N HT20 CH11(2462MHz)	Power rating:	120VAc




Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

4.5.6 Test Result of Radiated Spurious Emission (30MHz ~ 1GHz)

Test Mode :	802.11b CH01 (2412 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	30MHz~1GHz	Polarization :	Horizontal

Test Site : 3m Chamber
 Temp/Humi : 25℃/64%
 Tested by : Jack
 Pol/Phase : HORIZONTAL
 Test Mode : 802.11b CH01(2412MHz)
 Power rating: 120V



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
189.080	53.82	11.17	2.66	32.47	35.18	43.50	-8.32	QP
263.770	41.52	13.40	3.18	32.48	25.62	46.00	-20.38	QP
455.830	36.85	17.37	4.24	32.59	25.87	46.00	-20.13	QP
504.330	39.84	18.00	4.45	32.63	29.66	46.00	-16.34	QP
644.010	34.12	20.62	5.05	32.67	27.12	46.00	-18.88	QP
800.180	31.58	22.40	5.67	32.31	27.34	46.00	-18.66	QP

Test Mode :	802.11b CH01 (2412 MHz)	Temperature :	21~23℃
Test Engineer :	Jack Liu	Relative Humidity :	63~65%
Frequency Range	30MHz~1GHz	Polarization :	Vertical

Test Site : 3m Chamber

Temp/Humi : 25℃/64%


Tested by : Jack

Pol/Phase : VERTICAL

Test Mode : 802.11b CH01(2412MHz)

Power rating: 120V

Data: 107



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
50.370	40.98	12.65	1.37	32.51	22.49	40.00	-17.51	Peak
191.990	55.64	11.00	2.68	32.47	36.85	43.50	-6.65	Peak
504.330	43.39	18.00	4.45	32.63	33.21	46.00	-12.79	Peak
612.000	41.14	20.17	4.92	32.68	33.55	46.00	-12.45	Peak
647.890	39.76	20.67	5.06	32.67	32.82	46.00	-13.18	Peak
796.300	38.24	22.39	5.66	32.32	33.97	46.00	-12.03	Peak

4.6 AC Conducted Emission Measurement

4.6.1 Limit of AC Conducted Emission

FCC §15.207

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50


*Decreases with the logarithm of the frequency.

4.6.2 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

4.6.3 Test Result of AC Conducted Emission


Test Mode :	Mode 1	Temperature :	20°C
Test Engineer :	Jack Liu	Relative Humidity :	64%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	WLAN Linking + Lighting		



Freq MHz	Reading level dBuV	LISN/ISN factor dB	Cable loss dB	Result level dBuV	Limit level dBuV	Over limit dB	Remark
0.244	30.30	9.55	0.03	39.88	61.95	-22.07	QP
0.244	12.10	9.55	0.03	21.68	51.95	-30.27	Average
0.358	30.20	9.56	0.02	39.78	58.78	-19.00	QP
0.358	9.40	9.56	0.02	18.98	48.78	-29.80	Average
0.398	30.00	9.56	0.02	39.58	57.90	-18.32	QP
0.398	9.10	9.56	0.02	18.68	47.90	-29.22	Average
0.532	28.10	9.56	0.02	37.68	56.00	-18.32	QP
0.532	10.50	9.56	0.02	20.08	46.00	-25.92	Average
0.576	29.40	9.56	0.02	38.98	56.00	-17.02	QP
0.576	11.50	9.56	0.02	21.08	46.00	-24.92	Average
0.708	28.00	9.57	0.01	37.58	56.00	-18.42	QP
0.708	8.30	9.57	0.01	17.88	46.00	-28.12	Average

Result Level= Reading Level + LISN Factor + Cable Loss

Test Mode :	Mode 1	Temperature :	20°C
Test Engineer :	Jack Liu	Relative Humidity :	64%
Test Voltage :	125Vac / 60Hz	Phase :	NEUTRAL
Function Type :	WLAN Linking + Lighting		



Freq MHz	Reading level dBuV	LISN/ISN factor dB	Cable loss dB	Result level dBuV	Limit level dBuV	Over limit dB	Remark
0.200	35.20	9.56	0.03	44.79	63.62	-18.83	QP
0.200	16.70	9.56	0.03	26.29	53.62	-27.33	Average
0.312	30.60	9.58	0.03	40.21	59.93	-19.72	QP
0.312	10.80	9.58	0.03	20.41	49.93	-29.52	Average
0.352	32.00	9.58	0.02	41.60	58.91	-17.31	QP
0.352	10.70	9.58	0.02	20.30	48.91	-28.61	Average
0.398	29.80	9.58	0.02	39.40	57.90	-18.50	QP
0.398	8.90	9.58	0.02	18.50	47.90	-29.40	Average
0.484	28.70	9.59	0.02	38.31	56.27	-17.96	QP
0.484	9.00	9.59	0.02	18.61	46.27	-27.66	Average
0.529	28.50	9.59	0.02	38.11	56.00	-17.89	QP
0.529	8.90	9.59	0.02	18.51	46.00	-27.49	Average

Result Level= Reading Level + LISN Factor + Cable Loss

4.7 Antenna Requirements

4.7.1 Standard Applicable

According to antenna requirement of §15.203.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be re-placed by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded..

And according to §15.247(4)(1), system operating in the 2400-2483.5MHz bands that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 Antenna Connected Construction

An Monopole Antenna type design is used.

4.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Due Date	Remark
Spectrum Analyzer	Keysight	N9010A	MY56070788	2020-01-15	2021-01-14	Conducted
Power Sensor	Keysight	U2021XA	MY56510025	2020-01-16	2021-01-15	Conducted
Power Sensor	Keysight	U2021XA	MY57030005	2020-01-16	2021-01-15	Conducted
Power Sensor	Keysight	U2021XA	MY56510018	2020-01-16	2021-01-15	Conducted
Power Sensor	Keysight	U2021XA	MY56480002	2020-01-16	2021-01-15	Conducted
Thermal Chamber	Sanmtest	SMC-408-CD	2435	2020-05-09	2021-05-08	Conducted
Base Station	R&S	CMW 270	101231	2020-01-16	2021-01-15	Conducted
Signal Generator (Interferer)	Keysight	N5182B	MY56200384	2020-02-21	2021-02-20	Conducted
Signal Generator (Blocker)	Keysight	N5171B	MY56200661	2020-01-15	2021-01-14	Conducted

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV 40	101433	2020-01-16	2021-01-15	Radiation
Amplifier	Sonoma	310	363917	2020-01-15	2021-01-14	Radiation
Amplifier	Schwarzbeck	BBV 9718	327	2020-01-15	2021-01-14	Radiation
Amplifier	Narda	TTA1840-35-HG	2034380	2020-05-14	2021-05-15	Radiation
Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-051	2020-02-14	2023-02-13	Radiation
Broadband Antenna	Schwarzbeck	VULB 9168	9168-757	2018-08-31	2021-08-30	Radiation
Horn Antenna	Schwarzbeck	BBHA 9120 D	1677	2020-02-14	2023-02-13	Radiation
Horn Antenna	COM-POWER	AH-1840	101117	2018-06-20	2021-06-19	Radiation
Test Software	Auidx	E3	6.111221a	N/A	N/A	Radiation
Filter	Micro-Tronics	BRM 50702	G266	N/A	N/A	Radiation

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Due Date	Remark
LISN	R&S	ENV216	102125	2020-01-08	2021-01-07	Conducted
LISN	R&S	ENV432	101327	2020-01-08	2021-01-07	Conducted
EMI Test Receiver	R&S	ESR3	102143	2020-01-16	2021-01-15	Conducted
EMI Test Software	Audix	E3	N/A	N/A	N/A	Conducted

N/A: No Calibration Required

6 Uncertainty of Evaluation

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.42dB
Radiated emission	30MHz ~ 1GMHz	2.50dB
	1GHz ~ 18GHz	3.51dB
	18GHz ~ 40GHz	3.96dB

MEASUREMENT	UNCERTAINTY
Occupied Channel Bandwidth	$\pm 196.4\text{Hz}$
RF output power, conducted	$\pm 2.31\text{dB}$
Power density, conducted	$\pm 2.31\text{dB}$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.


Appendix A: DTS Bandwidth

Test Result


TestMode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	10.160	2406.920	2417.080	≥ 0.5	PASS
		2437	10.160	2431.920	2442.080	≥ 0.5	PASS
		2462	11.160	2455.920	2467.080	≥ 0.5	PASS
11G	Ant1	2412	15.200	2404.400	2419.600	≥ 0.5	PASS
		2437	15.600	2429.200	2444.800	≥ 0.5	PASS
		2462	15.400	2454.200	2469.600	≥ 0.5	PASS
11N20SISO	Ant1	2412	15.480	2404.440	2419.920	≥ 0.5	PASS
		2437	15.440	2429.360	2444.800	≥ 0.5	PASS
		2462	15.160	2454.400	2469.560	≥ 0.5	PASS

Test Graphs

11B_Ant1_2412



11B_Ant1_2437



11B_Ant1_2462



11G_Ant1_2412




11G_Ant1_2437




11G_Ant1_2462



11N20SISO_Ant1_2412



11N20SISO_Ant1_2437



11N20SISO_Ant1_2462




Appendix B: Occupied Channel Bandwidth

Test Result

TestMode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	16.098	2403.982	2420.080	---	PASS
		2437	16.121	2428.959	2445.080	---	PASS
		2462	16.138	2453.924	2470.062	---	PASS
11G	Ant1	2412	16.696	2403.659	2420.355	---	PASS
		2437	16.705	2428.641	2445.346	---	PASS
		2462	16.682	2453.601	2470.283	---	PASS
11N20SISO	Ant1	2412	17.530	2403.239	2420.769	---	PASS
		2437	17.553	2428.193	2445.746	---	PASS
		2462	17.532	2453.181	2470.713	---	PASS

Test Graphs

11B_Ant1_2412




11B_Ant1_2437




11B_Ant1_2462




11G_Ant1_2412




11G_Ant1_2437



11G_Ant1_2462







Appendix C: Maximum conducted output power

Test Result

TestMode	Antenna	Channel	Result [dBm]	EIRP [dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	17.05	21.28	<=30	PASS
		2437	16.96	21.19	<=30	PASS
		2462	16.72	20.95	<=30	PASS
11G	Ant1	2412	13.19	17.42	<=30	PASS
		2437	12.95	17.18	<=30	PASS
		2462	12.30	16.53	<=30	PASS
11N20SISO	Ant1	2412	13.00	17.23	<=30	PASS
		2437	12.86	17.09	<=30	PASS
		2462	12.15	16.38	<=30	PASS

Test Graphs

11B_Ant1_2412



11B_Ant1_2437

