



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V04

Report Template Revision Date: 2018-07-06

RF Exposure Evaluation Report

Report No. : CQASZ20200800820E-03
Applicant: SHENZHEN XINWU TECHNOLOGY LIMITED
Address of Applicant: Floor 5, Building 2, Chungu Science park, Meisheng Huigu Science Park, 83 Dabao Road, Baoan District, Shenzhen
Equipment Under Test (EUT):
EUT Name: Bluetooth module
Model No.: XW32-BLE
Brand Name: N/A
FCC ID: 2AW97-XW32
Standards: 47 CFR Part 1.1307
47 CFR Part 2.1093
KDB447498D01 General RF Exposure Guidance v06
Date of Receipt: 2020-08-10
Date of Test: 2020-08-10 to 2020-09-03
Date of Issue: 2020-09-03
Test Result : PASS*

*In the configuration tested, the EUT complied with the standards specified above

Tested By:

Tiny You

(Tiny You)

Reviewed By:

Sheek, Luo

(Sheek Luo)

Approved By:

Jack Ai

(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20200800820E-03	Rev.01	Initial report	2020-09-03

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 GENERAL DESCRIPTION OF BT	4
3.4 GENERAL DESCRIPTION OF BLE	4
4 SAR EVALUATION.....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 <i>Standard Requirement</i>	5
4.1.2 <i>Limits</i>	5
4.1.3 <i>EUT RF Exposure</i>	6

3 General Information

3.1 Client Information

Applicant:	SHENZHEN XINWU TECHNOLOGY LIMITED
Address of Applicant:	Floor 5, Building 2, Chungu Science park, Meisheng Huigu Science Park, 83 Dabao Road, Baoan District, Shenzhen
Manufacturer:	Shenzhen jingzhuo Electronic Technology Co., Ltd
Address of Manufacturer:	4 / F, building C10, Fuyuan Industrial Town, Jiuwei, Xixiang street, Bao'an District, Shenzhen
Factory:	SHENZHEN YUANKONG TECHNOLOGY LIMITED
Address of Factory:	4 / F, No. 39, Furong Road, Gushu community, Xixiang street, Bao'an District, Shenzhen

3.2 General Description of EUT

Product Name:	Bluetooth module
Model No.:	XW32-BLE
Trade Mark:	N/A
Hardware Version:	XW32-BLE-A0_V1.0.pcb
Software Version:	XW32-BLE_V1.5
Sample Type:	☐ Mobile ☒ Portable ☐ Fix Location
EUT Power Supply:	DC 2.2-3.6V

3.3 General Description of BT

Operation Frequency:	2402MHz~2480MHz
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK
Number of Channel:	79
Transfer Rate:	1Mbps
Hopping Channel Type:	Adaptive Frequency Hopping systems
Test Software of EUT:	BK RF Test (manufacturer declare)
Antenna Type:	PCB Antenna
Antenna Gain:	2.0dBi

3.4 General Description of BLE

Operation Frequency:	2402MHz~2480MHz
Modulation Type:	GFSK
Transfer Rate:	1Mbps
Number of Channel:	40
Test Software of EUT:	BK RF Test (manufacturer declare)
Antenna Type:	PCB Antenna
Antenna Gain:	2.0dBi

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{[\sqrt{f(\text{GHz})}]^3} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where} \right]$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

4.1.3 EUT RF Exposure

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-2.640	-2.5±1	-1.5	0.708
Middle(2441MHz)	-2.900	-2.5±1	-1.5	0.708
Highest(2480MHz)	-2.740	-2.5±1	-1.5	0.708

Worst case: GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune- up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	-2.640	-2.5±1	-1.5	0.708	0.219	3.0
Middle (2441MHz)	-2.900	-2.5±1	-1.5	0.708	0.221	
Highest (2480MHz)	-2.740	-2.5±1	-1.5	0.708	0.223	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20200800820E-02

2) For BLE

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-2.63	-2.5±1	-1.5	0.708
Middle(2440MHz)	-2.85	-2.5±1	-1.5	0.708
Highest(2480MHz)	-2.66	-2.5±1	-1.5	0.708

Worst case: GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune- up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	-2.63	-2.5±1	-1.5	0.708	0.219	3.0
Middle (2440MHz)	-2.85	-2.5±1	-1.5	0.708	0.221	
Highest (2480MHz)	-2.66	-2.5±1	-1.5	0.708	0.223	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20200800820E-01

BDR and BLE can not simultaneous transmitting at same time.