

1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 General Information

Client Information

Applicant:	Pro Charging Systems, LLC
Address of applicant:	1551 Heil Quaker Blvd., LaVergne, TN 37086
Manufacturer:	Pro Charging Systems, LLC
Address of manufacturer:	1551 Heil Quaker Blvd., LaVergne, TN 37086

General Description of EUT:

Product Name:	Eagle Performance Series Battery Charger
Trade Name	/
Model No.:	18100
Adding Model(s):	/
Rated Voltage:	AC 120V
Power Adapter:	/
Software Version:	/
Hardware Version:	PCS 18100 V1.1
FCC ID:	2AWBX-PCSEBTLE
Equipment Type:	Mobile

Technical Characteristics of EUT:

Bluetooth Version:	V5.0 (BLE mode)
Frequency Range:	2402-2480MHz
RF Output Power:	-3.72dBm (Conducted)
Data Rate:	1Mbps, 2Mbps
Modulation:	GFSK
Quantity of Channels:	40
Channel Separation:	2MHz
Type of Antenna:	Chip Antenna
Antenna Gain:	5.46dBi

1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalents power density

1.3 MPE Calculation Method

$$S = (30 * P * G) / (377 * R^2)$$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator,
the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.4 MPE Calculation Result

For Bluetooth

Maximum Tune-Up output power: -3(dBm)

Maximum peak output power at antenna input terminal: 0.50 (mW)

Prediction distance: >20(cm)

Prediction frequency: 2480(MHz)

Antenna gain: 5.46 (dBi)

Directional gain (numeric gain): 3.52

The worst case is power density at prediction frequency at 20cm: 0.0004 (mw/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

Result: Pass