



MPE ESTIMATION

FCC ID: 2AWC8-RS13RBP01

1, Limit for General Population/ Uncontrolled Exposures

Frequency	Power density (mW/ cm ²)	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

Note: F= Frequency in MHz

2, Estimation Result

WIFI

Mode	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (numerical)	MPE (mW/cm ²)
2.4G WIFI	21.66	21±1(22)	158.489	3	1.9953	0.06294
5.8G WIFI	18.57	18±1(19)	79.433	3	1.9953	0.03155

$$Pd = \frac{Pout * G}{4\pi r^2} ;$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report **HK2003030561-1E/2E**, antenna gain=3dBi

simultaneously MPE

2.4G WIFI MPE_(max) = 0.06294 (mW/cm²)

5G WIFI MPE_(max) = 0.03155 (mW/cm²)

simultaneously MPE=0.06294+0.03155=0.09449(mW/cm²)

when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.09449 mW/cm² which is < 1.0mW/cm², RF Exposure testing is not required.

-----The End-----