



MPE ESTIMATION

FCC ID: 2AWC8-RS13SDP03

1, Limit for General Population/ Uncontrolled Exposures

Frequency	Power density (mW/ cm ²)	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

Note: F= Frequency in MHz

2, Estimation Result

WIFI

Mode	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (numerical)	MPE (mW/cm ²)
2.4G WIFI	13.84	13±1(14)	25.119	3	1.9953	0.00998
5.8G WIFI	11.68	11±1(12)	15.849	3	1.9953	0.00629
$Pd = \frac{Pout * G}{4\pi r^2}$;						
Note:						
Note: The estimation distance is 20cm						
Note:						
PK Output power= conducted power.						
Conducted power see the test report HK2004080646-1E/2E , antenna gain=3dBi						

simultaneously MPE

2.4G WIFI MPE _(max)= 0.00998 (mW/cm²)

5G WIFI MPE _(max)= 0.00629 (mW/cm²)

simultaneously MPE=0.00998+0.00629=0.01627(mW/cm²)

when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.01627 mW/cm² which is< 1.0mW/cm², RF Exposure testing is not required.

-----The End-----