



FCC Test Report

For:
Aetheros Inc

Model:
AOS ESR-M Residential

Product Description:
AOS Edge Card for Residential Electricity Meters

FCC ID: 2AWD3ESR5G3

Applied Rules and Standards:
47 CFR Parts 24, 27

REPORT #: EMC_AETHE_001_FCC_24_27

DATE: 9/8/2025



A2LA Accredited

IC recognized #
3462B

CETECOM Inc.

411 Dixon Landing Road ♦ Milpitas, CA 95035 ♦ U.S.A.

Phone: + 1 (408) 586 6200 ♦ Fax: + 1 (408) 586 6299 ♦ E-mail: info@cetecom.com ♦ <http://www.cetecom.com>

CETECOM Inc. is a Delaware Corporation with Corporation number: 2905571

TABLE OF CONTENTS

1	ASSESSMENT	3
2	ADMINISTRATIVE DATA.....	4
2.1	IDENTIFICATION OF THE TESTING LABORATORY ISSUING THE EMC TEST REPORT.....	4
2.2	IDENTIFICATION OF THE CLIENT	4
2.3	IDENTIFICATION OF THE MANUFACTURER.....	4
3	EQUIPMENT UNDER TEST (EUT)	5
3.1	EUT SPECIFICATIONS	5
3.2	EUT SAMPLE DETAILS	6
3.3	ACCESSORY EQUIPMENT (AE) DETAILS	6
3.4	TEST SAMPLE CONFIGURATION.....	6
3.5	MODE OF OPERATION DETAILS.....	7
3.6	JUSTIFICATION FOR WORST CASE MODE OF OPERATION.....	7
4	SUBJECT OF INVESTIGATION	8
5	MEASUREMENT UNCERTAINTY	8
5.1	ENVIRONMENTAL CONDITIONS DURING TESTING:.....	8
5.2	DATES OF TESTING:	8
5.3	DECISION RULE:	8
6	MEASUREMENT PROCEDURES.....	9
6.1	RADIATED MEASUREMENT	9
6.2	SAMPLE CALCULATIONS FOR FIELD STRENGTH MEASUREMENTS	11
7	MEASUREMENT RESULTS SUMMARY	12
7.1	FCC 24.....	12
7.2	FCC 27.....	12
8	TEST RESULT DATA.....	14
8.1	ERP/EIRP	14
8.2	RADIATED SPURIOUS EMISSIONS	15
9	TEST SETUP PHOTOS.....	56
10	TEST EQUIPMENT AND ANCILLARIES USED FOR TESTIN	56
11	REVISION HISTORY	57

1 Assessment

The following device as further described in section 3 of this report was evaluated against the applicable criteria specified in the Code of Federal Regulations Title 47 parts 22, 24, 27, 90 and Industry Canada Standards RSS-GEN issue 5, RSS-130 issue 2, RSS-132 issue 4, RSS-133 issue 7, RSS-139 issue 4 and RSS-199 issue 4.

No deficiencies were ascertained.

Company	Description	Model #
Aetheros Inc	AOS Edge Card for Residential Electricity Meters	AOS ESR-M Residential

Report Reviewer:

Alvin, Ilarina

2025-09-08

Compliance

(Director of EMC Services)

Date	Section	Name	Signature
------	---------	------	-----------

Responsible for the Report:

Art Thammanavarat

2025-09-08

Compliance

(Lead Engineer)

Date	Section	Name	Signature
------	---------	------	-----------

The test results of this test report relate exclusively to the test item specified in Section3.

CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM Inc. USA.

2 Administrative Data

2.1 Identification of the Testing Laboratory Issuing the EMC Test Report

Company Name:	CETECOM Inc.
Department:	Compliance
Street Address:	411 Dixon Landing Road
City/Zip Code	Milpitas, CA 95035
Country	USA
Telephone:	+1 (408) 586 6200
Fax:	+1 (408) 586 6299
EMC Lab Manager:	Alvin, Ilarina
Responsible Project Leader:	Jayalakshmi, Sekar

2.2 Identification of the Client

Client Firm/Name:	Aetheros Inc
Street Address:	80 Liberty Ship Way, Suite 6
City/Zip Code	Sausalito, CA 94965
Country	USA

2.3 Identification of the Manufacturer

Manufacturer's Name:	Same as Client
Manufacturers Address:	
City/Zip Code	
Country	

3 Equipment Under Test (EUT)

3.1 EUT Specifications

Product Description:	AOS Edge Card for Residential Electricity Meters
Model Name:	AOS ESR-M Residential
HW Version:	v3.0
SW Version:	v7.2
FCC-ID:	2AWD3ESR5G3
Bands/Modes Supported	Cellular Modules Company Name: u-blox AG Model Number : SARA-R520M10X FCC: XPYUBX19KM01 ISED: 8595A-UBX19KM01 Wireless Technologies LTE FDD/TDD CAT-M1 Band: 2,4,12,13
Frequency Range	FCC BANDS LTE Band 2: 1850 – 1910 MHz LTE Band 4: 1710 – 1755 MHz LTE Band 12: 699 – 716 MHz LTE Band 13: 777 – 787 MHz
Max. declared antenna gain	Name: INPAQ Type: PIFA 4G Cellular Location: Internal Peak Gain: • LTE Band 12: 3.85 dBi • LTE Band 13: 3.73 dBi • LTE Band 2: 3.25 dBi • LTE Band 4: 3.90 dBi
Other Radios included in the device:	GNSS; Wi-Fi
Power Supply/ Rated Operating Voltage Range	4V DC, 8A
Operating Temperature Range	Low: -40 °C to High +65 °C
Sample Revision	☒ Production ☐ Pre-Production
EUT Dimensions	PCBA = 90mm x 49mm x 11mm
EUT Diameter	☒ < 60 cm ☐ Other _____
Note: The information of the EUT specifications in the table above is provided by the client.	

3.2 EUT Sample details

EUT #	Serial Number	HW Version	SW Version	Notes/Comments
1	AOS ESR-M	V3.0	V7.2	Radiated Emission

3.3 Accessory Equipment (AE) details

AE #	Type	Model	Manufacturer	Serial Number	Comments
1	Laptop	P135G	Dell	12243628947	Support laptop provided by Cetecom to exercise device.
2	Power Converter	SW-S12	SINGWAY	N/A	Power converter from 120Vac to 230Vac

3.4 Test Sample Configuration

Set-up #	EUT / AE used for set-up	Comments
1	EUT#1 + AE#1 + AE#2	Cellular was tested on LTE Low, Mid, High Channel at the maximum power, in simultaneous transmission mode with Wi-Fi. The client provides a USB cable to communicate with the device and send commands for configuring the Cellular and Wi-Fi radios into a specific test mode. This test mode configuration, designed for worst-case scenarios, is not intended for end-user application and is outlined as follows: - Cellular: send AT commands to connect the EUT to the base station simulator (R&S CMW500) - Wi-Fi: continuous modulated transmission at the maximum power settings, highest duty cycle on all channels. - Power converters converts 120 to 230 Vac. - Radiated RF measurements were performed with EUT configured via Android Debug Bridge (adb) and instructions - The EUT connected to support laptop to exercise device.

3.5 Mode of Operation details

Mode of Operation	Description of Operating modes	Additional Information
Op. 1	Cellular and WiFi 802.11b Co-Transmission	Cellular was tested on Low, Mid, High Channels at maximum power in a co-transmission mode WiFi radio was configured to 802.11b Mid channel using special commands through command window provided by the client that will not be available to the end user

3.6 Justification for Worst Case Mode of Operation

During the testing process the EUT was tested with transmitter sets on low, mid and high channels at the maximum power simultaneous transmission with WiFi radio 802.11b Mid channel, which is the worst case of the radios supported, based on the maximum average conducted output power from the reports.

For radiated measurements, all data in this report shows the worst case between horizontal and vertical antenna polarizations and for all orientations of the EUT.

4 Subject of Investigation

The objective of the measurements done by CETECOM Inc. was to evaluate the compliance of the EUT against the relevant requirements specified in the Code of Federal Regulations Title 47 parts 24, 27.

5 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus, with 95% confidence interval (in dB delta to result), based on a coverage factor k=2.

Radiated measurement

Measurement System		EMC Lab 1	EMC Lab 2
Conducted emissions (mains port)	150 kHz – 30 MHz	2.47 dB	N/A
Radiated emissions	9 kHz – 30 MHz	2.68 dB	2.53 dB
	30 – 100 MHz	4.39 dB	3.85 dB
	100 MHz – 1 GHz	5.65 dB	5.24 dB
	1 – 6 GHz	5.0 dB	4.88 dB
	6 – 18 GHz	4.76 dB	4.58 dB
	18 – 40 GHz	4.65 dB	4.61 dB

RF conducted measurement ± 0.5 dB

According to TR 102 273 a multiplicative propagation of error is assumed for RF measurement systems. For this reason the RMS method is applied to dB values and not to linear values as appropriate for additive propagation of error. Also used: <http://physics.nist.gov/cuu/Uncertainty/typeb.html>. The above calculated uncertainties apply to direct application of the Substitution method. The Substitution method is always used when the EUT comes closer than 3dB to the limit.

5.1 Environmental Conditions During Testing:

The following environmental conditions were maintained during the course of testing:

- Ambient Temperature: 20-25°C
- Relative humidity: 40-60%

5.2 Dates of Testing:

8/7/2025 - 8/16/2025


5.3 Decision Rule:

Cetecom Inc follows ILAC G8:09/2019 chapter 4.2.1 (Simple Acceptance Rule).

Only the measured values related to their corresponding limits will be used to decide whether the equipment under test meets the requirements of the test standards listed in chapter 3. The measurement uncertainty is mentioned in this test report, See chapter 9, but is not taken into account – neither to the limits nor to the measurement results. Measurement results with a smaller margin to the corresponding limits than the measurement uncertainty have a potential risk of more than 5% that the decision might be wrong.

6 Measurement Procedures


Testing is performed according to the guidelines provided in FCC publication (KDB) 971168 D01 v03r01 – “Measurement Guidance for Certification of Licensed Digital Transmitters” and according to relevant parts of ANSI/TIA-603-D-2010 as detailed below.




6.1 Radiated Measurement


- The exploratory measurement is accomplished by running a matrix of 16 sweeps over the required frequency range with R&S Test-SW EMC32 for 4 positions of the turntable, two orthogonal positions of the EUT and both antenna polarizations. This procedure exceeds the requirement of the above standards to cover the 3 orthogonal axis of the EUT. A max peak detector is utilized during the exploratory measurement. The Test-SW creates an overall maximum trace for all 12 sweeps and saves the settings for each point of this trace. The maximum trace is part of the test report.
- The 10 highest emissions are selected with an automatic algorithm of EMC32 searching for peaks in the noise floor and ensuring that broadband signals are not selected multiple times.
- The maxima are then put through the final measurement and again maximized in a 90deg range of the turntable, fine search in frequency domain and height scan between 1m and 4m.
- The above procedure is repeated for all possible ways of power supply to EUT and for all supported modulations.
- In case there are no emissions above noise floor level only the maximum trace is reported as described above.
- The results are split up into up to 4 frequency ranges due to antenna bandwidth restrictions. A magnetic loop is used from 9 kHz to 30 MHz, a Biconilog antenna is used from 30 MHz to 1 GHz, and two different horn antennas are used to cover frequencies up to 40 GHz.

Radiated Emissions Test Setup below 30MHz Measurements



Radiated Emissions Test Setup 30MHz-1GHz Measurements





6.2 Sample Calculations for Field Strength Measurements

Field Strength is calculated from the Spectrum Analyzer/ Receiver readings, taking into account the following parameters:

- Measured reading in dB μ V
- Cable Loss between the receiving antenna and SA in dB and
- Antenna Factor in dB/m

All radiated measurement plots in this report are taken from a test SW that calculates the Field Strength based on the following equation:

$$FS \text{ (dB}\mu\text{V/m)} = \text{Measured Value on SA (dB}\mu\text{V)} + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$$

Example:

Frequency (MHz)	Measured SA (dB μ V)	Cable Loss (dB)	Antenna Factor Correction (dB)	Field Strength Result (dB μ V/m)
1000	80.5	3.5	14	98.0

7 Measurement Results Summary

7.1 FCC 24

Test Specification	Test Case	Temperature and Voltage Conditions	Mode	Pass	Fail	NA	NP	Result
§2.1046; §24.232 (a)	RF Output Power	Nominal	-	☐	☐	☐	■	Complies Note 1 Note 2
§2.1047	Modulation Characteristics	Nominal	-	☐	☐	☐	■	Complies Note 1 Note 2
§2.1055; §24.235	Frequency Stability	Extreme Temperature and Voltage	-	☐	☐	☐	■	Complies Note 1 Note 2
§2.1049; §24.238	Occupied Bandwidth	Nominal	-	☐	☐	☐	■	Complies Note 1 Note 2
§2.1051; §24.238	Band Edge Compliance	Nominal	-	☐	☐	☐	■	Complies Note 1 Note 2
§2.1051; §24.238	Conducted Spurious Emissions	Nominal	-	☐	☐	☐	■	Complies Note 1 5Note 2
§2.1053; §24.238	Radiated Spurious Emissions	Nominal	Op. 1	■	☐	☐	☐	Complies

Note 1: NA= Not Applicable; NP= Not Performed.

Note 2: Leveraged from module certification Ublox SARA-R520M10X (FCC ID: XPYUBX19KM01, ISED: 8595A-UBX19KM01)

7.2 FCC 27

Test Specification	Test Case	Temperature and Voltage Conditions	Mode	Pass	Fail	NA	NP	Result
§2.1046; §27.50	RF Output Power	Nominal	-	☐	☐	☐	■	Complies Note 1 Note 2
§2.1047; §27.50,	Modulation Characteristics	Nominal	-	☐	☐	☐	■	Complies Note 1 Note 2
§2.1055; §27.54	Frequency Stability	Extreme Temperature and Voltage	-	☐	☐	☐	■	Complies Note 1 Note 2
§2.1049; §27.53	Occupied Bandwidth	Nominal	-	☐	☐	☐	■	Complies Note 1 Note 2
§2.1051; §27.53	Band Edge Compliance	Nominal	-	☐	☐	☐	■	Complies Note 1 Note 2
§2.1051; §27.53	Conducted Spurious Emissions	Nominal	-	☐	☐	☐	■	Complies Note 1 Note 2

§2.1053; §27.53	Radiated Spurious Emissions	Nominal	Op. 1	■	□	□	□	Complies
-----------------	-----------------------------	---------	-------	---	---	---	---	----------

Note 1: NA= Not Applicable; NP= Not Performed.

Note 2: Leveraged from module certification Ublox SARA-R520M10X (FCC ID: XPYUBX19KM01, ISED: 8595A-UBX19KM01)

8 Test Result Data

8.1 ERP/EIRP

FCC Rule Parts	Band	Frequency Range	Power Conducted Note 1	Power Conducted	Gain	EIRP Note 2	ERP Note 2	Limit EIRP	Limit ERP
		(MHz)	(dBm)	(W)	(dBi)	(W)	(W)	(W)	(W)
24E	LTE 2	1850 – 1910	22.49	0.177	3.25	0.375	0.229	2	-
27	LTE 4	1710 – 1755	22.57	0.181	3.90	0.444	0.270	1	-
27	LTE 12	699 – 716	21.91	0.155	3.85	0.377	0.230	-	3
27	LTE 13	777 – 787	22.51	0.178	3.73	0.421	0.257	-	3

Note 1: Power Conducted (dBm) leveraged from test report "MDE_UBLOX_2219_FCC_01_rev01" prepared by 7layers GmbH of cellular module name: Ublox SARA-R520M10X (FCC ID: XPYUBX19KM01, ISED: 8595A-UBX19KM01)

Note 2: ERP/EIRP are based on calculations from Power Conducted by adding the declared maximum gain of the utilized cellular antenna per operational description.

8.2 Radiated Spurious Emissions

8.2.1 Measurement utilizing KDB 971168 D01 Power Meas License Digital Systems v03r01, and according to ANSI/TIA-603-E-2016

Spectrum Analyzer Settings for FCC 24 and 27

Frequency Range	30MHz – 1 GHz	1 – 2.7 GHz	2.7 – 18 GHz	18 – 19.1 GHz
Resolution Bandwidth	100 kHz	1 MHz	1 MHz	1 MHz
Video Bandwidth	100 kHz	1 MHz	1 MHz	1 MHz
Detector	Peak	Peak	Peak	Peak
Trace Mode	Max Hold	Max Hold	Max Hold	Max Hold
Sweep Time	Auto	Auto	Auto	Auto

8.2.2 Limits:

8.2.2.1 FCC Part 24.238 (a); FCC Part 27.53 (h)

Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Note: The limit calculation result is a constant of -13 dBm.

8.2.3 Test conditions and setup:

Ambient Temperature (°C)	EUT Set-Up #	EUT operating mode	Power Input
22.0	1	Op. 1	120 Vac

8.2.4 Measurement result:

Plot #	Cellular Uplink Operating Channel	EUT Operating Mode	Scan Frequency	Limit (dBm)	Result
1-4	Low	LTE B2 + Wi-Fi B Mode	30 MHz – 22 GHz	-13	Pass
5-8	Mid	LTE B2 + Wi-Fi B Mode	30 MHz – 22 GHz	-13	Pass
9-12	High	LTE B2 + Wi-Fi B Mode	30 MHz – 22 GHz	-13	Pass
13-15	Low	LTE B4 + Wi-Fi B Mode	30 MHz – 18 GHz	-13	Pass
16-18	Mid	LTE B4 + Wi-Fi B Mode	30 MHz – 18 GHz	-13	Pass
19-21	High	LTE B4 + Wi-Fi B Mode	30 MHz – 18 GHz	-13	Pass
22-24	Low	LTE B12 + Wi-Fi B Mode	30 MHz – 8 GHz	-13	Pass
25-27	Mid	LTE B12 + Wi-Fi B Mode	30 MHz – 8 GHz	-13	Pass
28-30	High	LTE B12 + Wi-Fi B Mode	30 MHz – 8 GHz	-13	Pass
31-33	Low	LTE B13 + Wi-Fi B Mode	30 MHz – 8 GHz	-13	Pass
34-36	Mid	LTE B13 + Wi-Fi B Mode	30 MHz – 8 GHz	-13	Pass
37-39	High	LTE B13 + Wi-Fi B Mode	30 MHz – 8 GHz	-13	Pass

8.2.5 Measurement plots:


8.2.5.1 LTE Band 2

Plot # 1 Radiated Emissions: 30 MHz – 1GHz

Channel: Low

Final_Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
585.653	-69.307	-13.00	56.31	500.0	120.0	125.0	V	220.0	-70.3	2.2	0.0	-72.6	1.0




— Preview Result 1-PK+ — FCC Licensed -13dBm ◆ Final_Result RMS

Plot # 2 Radiated Emissions: 1 GHz - 3 GHz

Channel: Low

Final Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
1164.250	-52.185	-13.00	39.18	500.0	1000.0	187.0	H	273.0	-67.2	3.2	0.0	-70.4	15.0
1173.085	-50.263	-13.00	37.26	500.0	1000.0	116.0	H	267.0	-67.1	3.2	0.0	-70.4	16.9
1273.832	-57.425	-13.00	44.43	500.0	1000.0	100.0	V	2.0	-66.6	3.5	0.0	-70.1	9.2
1839.464	-53.106	-13.00	40.11	500.0	1000.0	119.0	H	289.0	-64.1	4.3	0.0	-68.5	11.0




— Preview Result 1-PK+ — FCC Licensed -13dBm ◆ Final_Result RMS

Plot # 3 Radiated Emissions: 3 GHz – 18 GHz

Channel: Low

Final_Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preampl (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
3127.281	-62.122	-13.00	49.12	500.0	1000.0	125.0	H	-39.0	-	5.5	-45.9	-62.5	40.9
3700.532	-60.771	-13.00	47.77	500.0	1000.0	134.0	V	30.0	-	6.3	-45.5	-62.2	40.7
5563.844	-62.082	-13.00	49.08	500.0	1000.0	158.0	H	307.0	-99.1	7.7	-46.5	-60.3	37.0
9252.407	-62.879	-13.00	49.88	500.0	1000.0	186.0	H	292.0	-95.5	10.6	-47.1	-58.9	32.6
11601.473	-38.271	-13.00	25.27	500.0	1000.0	100.0	H	22.0	-92.7	11.1	-46.6	-57.2	54.4




Plot # 4 Radiated Emissions: 18 GHz – 22 GHz

Channel: Low

Final_Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
---	---	---	---	---	---	---	---	---	---	---	---	---	---



— Preview Result 1-PK+
— FCC Licensed -13dBm


* Critical_Freqs PK+
◆ Final_Result RMS

Plot # 5 Radiated Emissions: 30 MHz – 1GHz

Channel: Mid

Final Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preampl (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
557.473	-68.888	-13.00	55.89	500.0	120.0	100.0	H	123.0	-70.6	2.2	0.0	-72.8	1.7




— Preview Result 1-PK+ — FCC Licensed -13dBm ◆ Final_Result RMS

Plot # 6 Radiated Emissions: 1 GHz - 3 GHz

Channel: Mid

Final Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
1117.750	-47.662	-13.00	34.66	500.0	1000.0	224.0	H	54.0	-67.4	3.2	0.0	-70.6	19.7
1318.250	-46.290	-13.00	33.29	500.0	1000.0	134.0	V	8.0	-66.7	3.5	0.0	-70.1	20.4
1871.000	-54.439	-13.00	41.44	500.0	1000.0	201.0	V	20.0	-64.0	4.4	0.0	-68.4	9.5
2637.687	-45.514	-13.00	32.51	500.0	1000.0	297.0	H	342.0	-61.6	5.0	0.0	-66.6	16.1
2654.833	-43.273	-13.00	30.27	500.0	1000.0	283.0	V	315.0	-61.4	5.0	0.0	-66.4	18.1




Plot # 7 Radiated Emissions: 3 GHz – 18 GHz

Channel: Mid

Final Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preampl (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
3755.875	-47.874	-13.00	34.87	500.0	1000.0	218.0	H	9.0	-	6.0	-45.7	-62.2	54.0
5645.999	-61.682	-13.00	48.68	500.0	1000.0	159.0	H	9.0	-98.7	7.6	-46.1	-60.2	37.1
11267.811	-54.597	-13.00	41.60	500.0	1000.0	118.0	H	280.0	-93.1	10.8	-46.3	-57.5	38.5
11766.469	-40.263	-13.00	27.26	500.0	1000.0	100.0	H	9.0	-91.9	11.4	-46.4	-56.9	51.7
13145.375	-56.253	-13.00	43.25	500.0	1000.0	151.0	H	-2.0	-87.4	12.2	-43.2	-56.4	31.1




Plot # 8 Radiated Emissions: 18 GHz – 22 GHz

Channel: Mid

Final_Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preampl (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
---	---	---	---	---	---	---	---	---	---	---	---	---	---



— Preview Result 1-PK+
— FCC Licensed -13dBm


* Critical_Freqs PK+
◆ Final_Result RMS

Plot # 9 Radiated Emissions: 30 MHz – 1GHz

Channel: High

Final Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
---	---	---	---	---	---	---	---	---	---	---	---	---	---




— Preview Result 1-PK+ * Critical_Freqs PK+
— FCC Licensed -13dBm ◆ Final_Result RMS

Plot # 10 Radiated Emissions: 1 GHz - 3 GHz

Channel: High

Final Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
1380.373	-39.992	-13.00	26.99	500.0	1000.0	144.0	V	317.0	-66.6	3.6	0.0	-70.2	26.6
2748.000	-46.882	-13.00	33.88	500.0	1000.0	186.0	H	319.0	-61.3	5.2	0.0	-66.5	14.5
2764.250	-49.301	-13.00	36.30	500.0	1000.0	177.0	H	317.0	-61.3	5.2	0.0	-66.5	12.0
2968.333	-47.386	-13.00	34.39	500.0	1000.0	127.0	H	11.0	-60.1	5.4	0.0	-65.4	12.7



Preview Result 1-PK+

FCC Licensed -13dBm


Final_Result RMS

Plot # 11 Radiated Emissions: 3 GHz – 18 GHz

Channel: High

Final_Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preampl (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
3249.156	-46.472	-13.00	33.47	500.0	1000.0	247.0	H	17.0	-	5.6	-45.9	-62.6	56.4
3819.156	-51.531	-13.00	38.53	500.0	1000.0	151.0	H	268.0	-	6.1	-46.0	-62.1	50.5
9548.399	-55.664	-13.00	42.66	500.0	1000.0	162.0	H	291.0	-94.2	10.7	-46.6	-58.3	38.6
11457.407	-61.247	-13.00	48.25	500.0	1000.0	185.0	V	45.0	-93.4	11.0	-47.0	-57.4	32.2
11931.458	-41.732	-13.00	28.73	500.0	1000.0	100.0	H	304.0	-90.6	11.8	-45.6	-56.8	48.9




Plot # 12 Radiated Emissions: 18 GHz – 22 GHz

Channel: High

Final_Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preampl (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
---	---	---	---	---	---	---	---	---	---	---	---	---	---



— Preview Result 1-PK+
— FCC Licensed -13dBm



* Critical_Freqs PK+
 ◆ Final_Result RMS

8.2.6 Measurement plots:


8.2.6.1 LTE Band 4

Plot # 13 Radiated Emissions: 30 MHz – 1GHz

Channel: Low

Final Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
727.591	-62.584	-13.00	49.58	500.0	100.0	230.0	V	4.0	-68.0	2.5	0.0	-70.4	5.4




— Preview Result 1-PK+ — FCC Licensed -13dBm ◆ Final_Result RMS

Plot # 14 Radiated Emissions: 1 GHz - 3 GHz

Channel: Low

Final_Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
1706.250	-47.475	-13.00	34.47	500.0	1000.0	218.0	H	-21.0	-64.6	4.6	0.0	-69.3	17.1
1720.750	-53.114	-13.00	40.11	500.0	1000.0	107.0	H	336.0	-64.5	4.6	0.0	-69.2	11.4



Preview Result 1-PK+

FCC Licensed -13dBm


Final_Result RMS

Plot # 15 Radiated Emissions: 3 GHz – 18 GHz

Channel: Low

Final_Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preampl (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
3159.156	-65.845	-13.00	52.85	500.0	1000.0	162.0	H	-17.0	-	5.5	-46.0	-62.6	37.2
3249.156	-49.167	-13.00	36.17	500.0	1000.0	169.0	H	-1.0	-	5.6	-45.9	-62.6	53.7
7311.344	-54.488	-13.00	41.49	500.0	1000.0	129.0	H	32.0	-96.9	9.0	-46.6	-59.3	42.4
12002.094	-58.667	-13.00	45.67	500.0	1000.0	107.0	H	301.0	-90.7	11.6	-45.7	-56.7	32.1
13716.796	-59.276	-13.00	46.28	500.0	1000.0	100.0	H	313.0	-87.3	12.4	-43.6	-56.1	28.0




Preview Result 1-PK+ FCC Licensed -13dBm Final_Result RMS

Plot # 16 Radiated Emissions: 30 MHz – 1GHz

Channel: Mid

Final Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
---	---	---	---	---	---	---	---	---	---	---	---	---	---



— Preview Result 1-PK+
— FCC Licensed -13dBm


* Critical_Freqs PK+
◆ Final_Result RMS

Plot # 17 Radiated Emissions: 1 GHz - 3 GHz

Channel: Mid

Final_Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
1691.500	-58.920	-13.00	45.92	500.0	1000.0	107.0	H	322.0	-64.7	4.6	0.0	-69.3	5.8
1720.491	-56.984	-13.00	43.98	500.0	1000.0	169.0	V	333.0	-64.5	4.6	0.0	-69.1	7.5
1745.000	-56.743	-13.00	43.74	500.0	1000.0	167.0	V	332.0	-64.4	4.5	0.0	-69.0	7.7
1754.137	-57.970	-13.00	44.97	500.0	1000.0	151.0	V	333.0	-64.3	4.6	0.0	-68.9	6.4




— Preview Result 1-PK+ — FCC Licensed -13dBm ◆ Final_Result RMS

Plot # 18 Radiated Emissions: 3 GHz – 18 GHz

Channel: Mid

Final_Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preampl (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
3249.156	-48.286	-13.00	35.29	500.0	1000.0	175.0	H	-2.0	-	5.6	-45.9	-62.6	54.6
3460.531	-62.595	-13.00	49.59	500.0	1000.0	180.0	H	350.0	-	5.7	-46.1	-62.5	40.2
11511.782	-68.535	-13.00	55.53	500.0	1000.0	100.0	H	1.0	-93.2	11.0	-46.9	-57.4	24.7
12112.351	-57.994	-13.00	44.99	500.0	1000.0	100.0	H	305.0	-90.9	11.6	-45.9	-56.6	32.9
13843.344	-56.424	-13.00	43.42	500.0	1000.0	100.0	H	311.0	-87.4	12.7	-44.1	-56.0	31.0




Preview Result 1-PK+ FCC Licensed -13dBm Final_Result RMS

Plot # 19 Radiated Emissions: 30 MHz – 1GHz

Channel: High

Final_Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
---	---	---	---	---	---	---	---	---	---	---	---	---	---




— Preview Result 1-PK+ * Critical_Freqs PK+
— FCC Licensed -13dBm ◆ Final_Result RMS

Plot # 20 Radiated Emissions: 1 GHz - 3 GHz

Channel: High

Final Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
2264.355	-55.767	-13.00	42.77	500.0	1000.0	379.0	H	17.0	-62.2	5.4	0.0	-67.6	6.5




Plot # 21 Radiated Emissions: 3 GHz – 18 GHz

Channel: High

Final Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
3249.156	-51.124	-13.00	38.12	500.0	1000.0	168.0	H	355.0	-	5.6	-45.9	-62.6	51.8
4873.844	-52.354	-13.00	39.35	500.0	1000.0	151.0	H	-44.0	-	7.0	-45.9	-61.1	47.6
8772.875	-65.242	-13.00	52.24	500.0	1000.0	173.0	V	355.0	-96.6	10.7	-48.0	-59.3	31.4
12253.844	-61.322	-13.00	48.32	500.0	1000.0	144.0	H	295.0	-90.2	11.8	-45.5	-56.6	28.9
14037.438	-53.634	-13.00	40.63	500.0	1000.0	100.0	H	310.0	-87.6	12.8	-44.5	-55.8	33.9



8.2.7 Measurement plots:


8.2.7.1 LTE Band 12

Plot # 22 Radiated Emissions: 30 MHz – 1GHz

Channel: Low

Final Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
700.926	-46.592	-13.00	33.59	500.0	100.0	231.0	H	13.0	-68.4	2.5	0.0	-70.9	21.8
704.683	-51.397	-13.00	38.40	500.0	100.0	117.0	H	23.0	-68.4	2.5	0.0	-70.9	17.0




Plot # 23 Radiated Emissions: 1 GHz - 3 GHz

Channel: Low

Final_Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
2204.936	-56.087	-13.00	43.09	500.0	1000.0	227.0	H	333.0	-62.5	5.2	0.0	-67.7	6.4




— Preview Result 1-PK+ — FCC Licensed -13dBm ◆ Final_Result RMS

Plot # 24 Radiated Emissions: 3 GHz – 9 GHz

Channel: Low

Final_Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
3249.286	-48.323	-13.00	35.32	500.0	1000.0	171.0	H	-9.0	-	5.6	-45.9	-62.6	54.6
4873.875	-51.118	-13.00	38.12	500.0	1000.0	313.0	H	-6.0	-	7.0	-45.9	-61.1	48.9
7311.500	-53.285	-13.00	40.29	500.0	1000.0	151.0	H	9.0	-96.9	9.0	-46.6	-59.3	43.6




Plot # 25 Radiated Emissions: 30 MHz – 1GHz

Channel: Mid

Final Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
702.186	-65.090	-13.00	52.09	500.0	100.0	117.0	H	32.0	-68.4	2.5	0.0	-70.9	3.3
711.521	-52.986	-13.00	39.99	500.0	100.0	141.0	V	356.0	-68.2	2.6	0.0	-70.8	15.2




Plot # 26 Radiated Emissions: 1 GHz - 3 GHz

Channel: Mid

Final Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
---	---	---	---	---	---	---	---	---	---	---	---	---	---




Preview Result 1-PK+ * Critical_Freqs PK+
 FCC Licensed -13dBm ◆ Final_Result RMS

Plot # 27 Radiated Emissions: 3 GHz – 9 GHz

Channel: Mid

Final_Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preampl (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
3249.286	-48.323	-13.00	35.32	500.0	1000.0	171.0	H	-9.0	-	5.6	-45.9	-62.6	54.6
4873.875	-51.118	-13.00	38.12	500.0	1000.0	313.0	H	-6.0	-	7.0	-45.9	-61.1	48.9
7311.500	-53.285	-13.00	40.29	500.0	1000.0	151.0	H	9.0	-96.9	9.0	-46.6	-59.3	43.6




Plot # 28 Radiated Emissions: 30 MHz – 1GHz

Channel: High

Final Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
708.128	-66.801	-13.00	53.80	500.0	100.0	153.0	V	343.0	-68.3	2.5	0.0	-70.8	1.5
717.545	-53.628	-13.00	40.63	500.0	100.0	136.0	V	32.0	-68.2	2.6	0.0	-70.7	14.6




— Preview Result 1-PK+ — FCC Licensed -13dBm ◆ Final_Result RMS

Plot # 29 Radiated Emissions: 1 GHz - 3 GHz

Channel: High

Final Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
1564.633	-53.234	-13.00	40.23	500.0	1000.0	158.0	V	5.0	-65.4	4.5	0.0	-69.9	12.1
1573.000	-55.325	-13.00	42.33	500.0	1000.0	150.0	V	335.0	-65.3	4.5	0.0	-69.8	10.0
2913.933	-50.838	-13.00	37.84	500.0	1000.0	107.0	V	45.0	-59.8	6.0	0.0	-65.8	9.0




— Preview Result 1-PK+ — FCC Licensed -13dBm ◆ Final_Result RMS

Plot # 30 Radiated Emissions: 3 GHz – 9 GHz

Channel: High

Final Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
3249.274	-49.359	-13.00	36.36	500.0	1000.0	186.0	H	1.0	-	5.6	-45.9	-62.6	53.5
4873.902	-51.548	-13.00	38.55	500.0	1000.0	107.0	H	349.0	-	7.0	-45.9	-61.1	48.4
7311.500	-53.641	-13.00	40.64	500.0	1000.0	160.0	H	8.0	-96.9	9.0	-46.6	-59.3	43.2



8.2.8 Measurement plots:


8.2.8.1 LTE Band 13

Plot # 31 Radiated Emissions: 30 MHz – 1GHz

Channel: Low

Final Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preampl (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
786.479	-66.683	-13.00	53.68	500.0	100.0	207.0	V	20.0	-67.0	2.6	0.0	-69.6	0.3
793.428	-71.666	-13.00	58.67	500.0	100.0	135.0	H	14.0	-66.9	2.6	0.0	-69.5	-4.8




— Preview Result 1-PK+ — FCC Licensed -13dBm ◆ Final_Result RMS

Plot # 32 Radiated Emissions: 1 GHz - 3 GHz

Channel: Low

Final_Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
1554.950	-48.312	-13.00	35.31	500.0	1000.0	168.0	V	305.0	-65.4	4.5	0.0	-69.9	17.1
1562.750	-56.458	-13.00	43.46	500.0	1000.0	107.0	V	20.0	-65.4	4.5	0.0	-69.9	8.9




— Preview Result 1-PK+ — FCC Licensed -13dBm ◆ Final_Result RMS

Plot # 33 Radiated Emissions: 3 GHz – 9 GHz

Channel: Low

Final_Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preampl (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
3249.204	-47.314	-13.00	34.31	500.0	1000.0	176.0	H	-7.0	-	5.6	-45.9	-62.6	55.6
3886.813	-68.854	-13.00	55.85	500.0	1000.0	238.0	V	344.0	-	6.2	-45.9	-62.1	32.9
4873.922	-51.503	-13.00	38.50	500.0	1000.0	107.0	H	348.0	-	7.0	-45.9	-61.1	48.5
7310.188	-52.220	-13.00	39.22	500.0	1000.0	152.0	H	8.0	-96.9	9.0	-46.6	-59.3	44.7




— Preview Result 1-PK+ — FCC Licensed -13dBm ◆ Final_Result RMS

Plot # 34 Radiated Emissions: 30 MHz – 1GHz

Channel: Mid

Final Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
786.116	-48.100	-13.00	35.10	500.0	100.0	215.0	V	13.0	-67.0	2.7	0.0	-69.6	18.9



— Preview Result 1-PK+

— FCC Licensed -13dBm


◆ Final_Result RMS

Plot # 35 Radiated Emissions: 1 GHz - 3 GHz

Channel: Mid

Final Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preampl (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
1559.304	-55.244	-13.00	42.24	500.0	1000.0	185.0	V	358.0	-65.4	4.5	0.0	-69.9	10.2




— Preview Result 1-PK+ — FCC Licensed -13dBm ◆ Final_Result RMS

Plot # 36 Radiated Emissions: 3 GHz – 9 GHz

Channel: Mid

Final_Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preampl (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
3249.269	-47.799	-13.00	34.80	500.0	1000.0	169.0	H	354.0	-	5.6	-45.9	-62.6	55.1
3899.256	-69.689	-13.00	56.69	500.0	1000.0	221.0	V	-9.0	-	6.1	-45.9	-62.0	32.1
4873.920	-50.375	-13.00	37.38	500.0	1000.0	138.0	H	351.0	-	7.0	-45.9	-61.1	49.6
7311.431	-53.067	-13.00	40.07	500.0	1000.0	134.0	H	6.0	-96.9	9.0	-46.6	-59.3	43.8




Plot # 37 Radiated Emissions: 30 MHz – 1GHz

Channel: High

Final_Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
783.909	-42.765	-13.00	29.77	500.0	100.0	243.0	H	27.0	-67.1	2.7	0.0	-69.8	24.3
788.321	-47.409	-13.00	34.41	500.0	100.0	223.0	V	26.0	-67.0	2.6	0.0	-69.6	19.6




— Preview Result 1-PK+ — FCC Licensed -13dBm ◆ Final_Result RMS

Plot # 38 Radiated Emissions: 1 GHz - 3 GHz

Channel: High

Final Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preamp (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
1564.633	-53.234	-13.00	40.23	500.0	1000.0	158.0	V	5.0	-65.4	4.5	0.0	-69.9	12.1
1573.000	-55.325	-13.00	42.33	500.0	1000.0	150.0	V	335.0	-65.3	4.5	0.0	-69.8	10.0
2913.933	-50.838	-13.00	37.84	500.0	1000.0	107.0	V	45.0	-59.8	6.0	0.0	-65.8	9.0




— Preview Result 1-PK+ — FCC Licensed -13dBm ◆ Final_Result RMS

Plot # 39 Radiated Emissions: 3 GHz – 9 GHz

Channel: High

Final Result

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Sig Path (dB)	Preampl (dB)	Trd Corr. (dB)	Raw Rec (dBμV)
3249.250	-47.749	-13.00	34.75	500.0	1000.0	229.0	H	49.0	-	5.6	-45.9	-62.6	55.1
4873.895	-51.444	-13.00	38.44	500.0	1000.0	135.0	H	348.0	-	7.0	-45.9	-61.1	48.5
7310.340	-53.234	-13.00	40.23	500.0	1000.0	143.0	H	7.0	-96.9	9.0	-46.6	-59.3	43.7



— Preview Result 1-PK+ — FCC Licensed -13dBm ◆ Final_Result RMS

9 Test setup photos

Setup photos are included in supporting file name: "EMC_AETHE_001_25001_FCC_22_24_27_Setup_photos.pdf"

10 Test Equipment And Ancillaries Used For Testin

Equipment Type	Manufacturer	Model	Serial #	Calibration Cycle	Last Calibration Date
Active Monopole	Com-Power Corp.	AM-741R	10200112	3 Years	11/09/2023
BILOG ANTENNA	A.H. SYSTEMS	BiLA2G	569	3 Years	10/30/2023
HORN ANTENNA	EMCO	3115	00035111	3 Years	10/26/2023
HORN ANTENNA	ETS LINDGREN	3117-PA	00167061	3 Years	9/25/2023
HORN ANTENNA	ETS LINDGREN	3116C-PA	00166821	3 Years	10/26/2023
ESW.EMI TEST RECEIVER	ROHDE & SCHWARZ	ESW44	101715	3 Years	10/24/2023
DIGITAL THERMOMETER	Control Company	4410,90080-03	230712972	3 Years	10/18/2023
Signal Analyzer	R&S	FSV40	101022	3 Years	09/25/2023
Multimeter	Fluke	115	56090717MV	3 Years	09/26/2023
Software	EMC32	Version 10.50.40	-	-	-
Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	1201.002K50-127068-mX	3 Years	10/2/2024

Note: Equipment used meets the measurement uncertainty requirements as required per applicable standards for 95% confidence levels. Calibration due dates, unless defined specifically, falls on the last day of the month. Items indicated "N/A" for cal status either do not specifically require calibration or is internally characterized before use.

11 Revision History

Date	Report Name	Changes to report	Prepared by
2025-09-08	EMC_AETHE_001_25001_FCC_24_27	Initial Version	Art Thammanavarat

<<< The End >>>
