

# TEST REPORT

Product Name : Wireless Earbuds

Model Number : BL6

FCC ID : 2AWEA-BL6

Prepared for : Scholastic Inc.  
Address : 557 Broadway New York, NY 10012 USA

Prepared by : EMTEK (SHENZHEN) CO., LTD.  
Address : Building 69, Majialong Industry Zone, Nanshan District,  
Shenzhen, Guangdong, China

Tel: (0755) 26954280  
Fax: (0755) 26954282

Report Number : ES200320033W  
Date(s) of Tests : March 20, 2019 to June 02, 2020  
Date of issue : June 02, 2020

## Table of Contents

1 TEST RESULT CERTIFICATION .....	3
2 EUT TECHNICAL DESCRIPTION .....	4
3 SUMMARY OF TEST RESULT .....	5
4 TEST METHODOLOGY .....	6
4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS .....	6
4.2 MEASUREMENT EQUIPMENT USED .....	6
4.3 DESCRIPTION OF TEST MODES .....	7
5 FACILITIES AND ACCREDITATIONS .....	8
5.1 FACILITIES .....	8
5.2 LABORATORY ACCREDITATIONS AND LISTINGS .....	8
6 TEST SYSTEM UNCERTAINTY .....	9
7 SETUP OF EQUIPMENT UNDER TEST .....	10
7.1 RADIO FREQUENCY TEST SETUP 1 .....	10
7.2 RADIO FREQUENCY TEST SETUP 2 .....	10
7.3 CONDUCTED EMISSION TEST SETUP .....	11
7.4 SUPPORT EQUIPMENT .....	12
8 FREQUENCY HOPPING SYSTEM REQUIREMENTS .....	13
8.1 STANDARD APPLICABLE .....	13
8.2 EUT PSEUDORANDOM FREQUENCY HOPPING SEQUENCE .....	13
8.3 EQUAL HOPPING FREQUENCY USE .....	14
8.4 FREQUENCY HOPPING SYSTEM .....	14
9 TEST REQUIREMENTS .....	15
9.1 20DB BANDWIDTH .....	15
9.2 CARRIER FREQUENCY SEPARATION .....	21
9.3 NUMBER OF HOPPING FREQUENCIES .....	27
9.4 AVERAGE TIME OF OCCUPANCY (DWELL TIME) .....	29
9.5 MAXIMUM PEAK CONDUCTED OUTPUT POWER .....	32
9.6 CONDUCTED SPURIOUS EMISSION .....	38
9.7 RADIATED SPURIOUS EMISSION .....	45
9.8 CONDUCTED EMISSION TEST .....	58
9.9 ANTENNA APPLICATION .....	59

## 1 TEST RESULT CERTIFICATION

Applicant:	Scholastic Inc. 557 Broadway New York, NY 10012 USA
Manufacture:	K&M INTERNATIONAL (HK) LIMITED Unit 919, No.1, East Street, Huijing Plaza, Huadu District, Guangzhou, China
Product Description:	Wireless Earbuds
Model Number:	BL6
Trade Mark:	N/A

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 2 2018, Subpart J	
FCC 47 CFR Part 15 2018, Subpart C	PASS

The above equipment was tested by EMTEK(SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.247.

The test results of this report relate only to the tested sample identified in this report.

Date of Test :

March 20, 2019 to June 02, 2020

Prepared by:

  
YihuXiong/Editor

Reviewer:

  
Joe Xia/Supervisor

Approve & Authorized Signer :

  
Lisa Wang/Manager

## 2 EUT TECHNICAL DESCRIPTION

Characteristics	Description
<b>Product Name</b>	Wireless Earbuds
<b>Model number</b>	BL6 (Note: EUT does not work while charging.)
<b>Device Type</b>	4.1 BT Signal mode
<b>Data Rate</b>	1Mbps for GFSK modulation 2Mbps for pi/4-DQPSK modulation 3Mbps for 8DPSK modulation
<b>Modulation</b>	GFSK modulation (1Mbps) pi/4-DQPSK modulation (2Mbps) 8DPSK modulation (3Mbps)
<b>Operating Frequency Range</b>	2402-2480MHz
<b>Number of Channels</b>	79 channels
<b>Max Transmit Power</b>	4.382 dBm
<b>Antenna Type</b>	PCB Antenna
<b>Gain</b>	2 dBi
<b>Power supply</b>	DC 3.7V Battery
<b>Temperature Range</b>	-20°C ~ +55°C

**Note:** for more details, please refer to the User's manual of the EUT.

### 3 SUMMARY OF TEST RESULT

FCC PartClause	Test Parameter	Verdict	Remark
15.247(a)(1)	20 dB Bandwidth	PASS	
15.247(a)(1)	Carrier Frequency Separation	PASS	
15.247(a)(1)	Number of Hopping Frequencies	PASS	
15.247(a)(1)	Average Time of Occupancy (Dwell Time)	PASS	
15.247(b)(1)	Maximum Peak Conducted Output Power	PASS	
15.247(c)	Conducted Spurious Emissions	PASS	
15.247(d)	Radiated Spurious Emissions	PASS	
15.209			
15.207	Conducted Emission	N/A	
15.203	Antenna Application	PASS	
NOTE1:N/A (Not Applicable)			

#### RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: 2AWEA-BL6 filing to comply with Section 15.247 of the FCC Part 15, Subpart C.

## 4 TEST METHODOLOGY

### 4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:  
 FCC 47 CFR Part 2, Subpart J  
 FCC 47 CFR Part 15, Subpart C  
 558074 D01 15.247 Meas Guidance V05r02

### 4.2 MEASUREMENT EQUIPMENT USED

#### 4.2.1 Radiated Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	DUE CAL.
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	May 18, 2020	May 17, 2021
Pre-Amplifier	HP	8447F	2944A07999	May 17, 2020	May 16, 2021
Bilog Antenna	Schwarzbeck	VULB9163	142	May 17, 2020	May 16, 2021
Loop Antenna	ARA	PLA-1030/B	1029	May 17, 2020	May 16, 2021
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	May 18, 2020	May 16, 2021
Horn Antenna	Schwarzbeck	BBHA 9120	D143	May 17, 2020	May 16, 2021
Cable	Schwarzbeck	AK9513	ACRX1	May 18, 2020	May 17, 2021
Cable	Rosenberger	N/A	FP2RX2	May 18, 2020	May 17, 2021
Cable	Schwarzbeck	AK9513	CRPX1	May 18, 2020	May 17, 2021
Cable	Schwarzbeck	AK9513	CRRX2	May 18, 2020	May 17, 2021

#### 4.2.2 Radio Frequency Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LASTCAL.	DUE CAL.
Spectrum Analyzer	Agilent	E4407B	88156318	May 18, 2020	May 17, 2021
Spectrum Analyzer	R & S	FSV30	103040	May 18, 2020	May 17, 2021

#### 4.2.3 Conducted Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	DUE CAL.
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	May 18, 2020	May 17, 2021
L.I.S.N.	Schwarzbeck	NNLK8129	8129-203	May 18, 2020	May 17, 2021
50Ω Coaxial Switch	Anritsu	MP59B	M20531	May 18, 2020	May 17, 2021

*Remark: Each piece of equipment is scheduled for calibration once a year.*

#### 4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps for Bluetooth GFSK modulation; 2Mbps for Bluetooth pi/4-DQPSK modulation, 3Mbps for Bluetooth 8DPSK modulation) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for Bluetooth V4.1 Signal mode

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	39	2441	...	...
1	2403	40	2442	76	2478
2	2404	41	2443	77	2479
...	...	...	...	78	2480

Note:  $fc = 2402\text{MHz} + (k-1) \times 1\text{MHz}$  k=1 to 79

Test Frequency and Channel for Bluetooth V4.1 Signal mode

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	39	2441	78	2480

## 5 FACILITIES AND ACCREDITATIONS

### 5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

Building 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

### 5.2 LABORATORY ACCREDITATIONS AND LISTINGS

#### Site Description

EMC Lab. : Accredited by CNAS, 2018.11.30

The certificate is valid until 2022.10.28

The Laboratory has been assessed and proved to be in compliance with  
CNAS-CL01:2018 (identical to ISO/IEC 17025:2017)

The Certificate Registration Number is L2291.

Accredited by FCC, August 06, 2018

The certificate is valid until August 07, 2020

Designation Number: CN1204

Test Firm Registration Number: 882943

Accredited by A2LA, August 08, 2018

The certificate is valid until August 31, 2020

The Certificate Number is 4321.01.

Name of Firm : EMTEK (SHENZHEN) CO., LTD.

Site Location : Building 69, Majialong Industry Zone, Nanshan District, Shenzhen,  
Guangdong, China

## 6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0 \text{dB}$
Conducted Emissions Test	$\pm 2.0 \text{dB}$
Radiated Emission Test	$\pm 2.0 \text{dB}$
Occupied Bandwidth Test	$\pm 1.0 \text{dB}$
Band Edge Test	$\pm 3 \text{dB}$
All emission, radiated	$\pm 3 \text{dB}$
Antenna Port Emission	$\pm 3 \text{dB}$
Temperature	$\pm 0.5 \text{ }^\circ\text{C}$
Humidity	$\pm 3\%$


Measurement Uncertainty for a level of Confidence of 95%



## 7 SETUP OF EQUIPMENT UNDER TEST

### 7.1 RADIO FREQUENCY TEST SETUP 1

The Bluetooth component's antenna port(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



### 7.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.


30MHz-1GHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


Above 1GHz:

The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


(a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




### 7.3 CONDUCTED EMISSION TEST SETUP

The mains cable of the EUT (Game fitness board) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



**7.4 SUPPORT EQUIPMENT****EUT Cable List and Details**

Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

**Auxiliary Cable List and Details**

Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

**Auxiliary Equipment List and Details**

Description	Manufacturer	Model	Serial Number
/	/	/	/

**Notes:**

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

## 8 FREQUENCY HOPPING SYSTEM REQUIREMENTS

### 8.1 Standard Applicable

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

- (g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.
- (h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

### 8.2 EUT Pseudorandom Frequency Hopping Sequence


The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels.

The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master; the phase in the hopping sequence is determined by the Bluetooth clock of the master. The channel is divided into time slots where each slot corresponds to an RF hop frequency. Consecutive hops correspond to different RF hop frequencies. The normal hop is 1 600 hops/s.


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage, and the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones. Number of shift register stages: 9

Length of pseudo-random sequence:  $2^9 - 1 = 524$  bits

Longest sequence of zeros: 8 (non-inverted signal)



*Linear Feedback Shift Register for Generation of the PRBS sequence*



Each frequency used equally on the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

### 8.3 Equal Hopping Frequency Use

All Bluetooth units participating in the piconet are time and hop-synchronized to the channel.

Example of a 79 hopping sequence in data mode:

35, 27, 6, 44, 14, 61, 74, 32, 1, 11, 23, 2, 55, 65, 29, 3, 9, 52, 78, 58, 40, 25, 0, 7, 18, 26, 76, 60, 47, 50, 2, 5, 16, 37, 70, 63, 66, 54, 20, 13, 4, 8, 15, 21, 26, 10, 73, 77, 67, 69, 43, 24, 57, 39, 46, 72, 48, 33, 17, 31, 75, 19, 41, 62, 68, 28, 51, 66, 30, 56, 34, 59, 71, 22, 49, 64, 38, 45, 36, 42, 53

Each Frequency used equally on the average by each transmitter

### 8.4 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH- enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

## 9 TEST REQUIREMENTS

### 9.1 20DB BANDWIDTH

#### 9.1.1 Applicable Standard

According to FCC Part 15.247(a)(1) and 558074 D01 15.247 Meas Guidance V05r02

#### 9.1.2 Conformance Limit

No limit requirement.

#### 9.1.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

#### 9.1.4 Test Procedure

The EUT was operating in Bluetooth V4.1 Signal mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 30 kHz.

Set the video bandwidth (VBW) =100kHz.

Set Span= approximately 2 to 3 times the 20 dB bandwidth

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the markerdeltafunction, and move the marker to the other side of the emission, until it is (asclose as possible to) even with the reference marker level. The marker-delta reading atthis point is the 20 dB bandwidth of the emission.


If this value varies with differentmodes of operation (e.g., data rate, modulation format, etc.), repeat this test for eachvariation.


Measure and record the results in the test report.


### Test Results


Temperature:	21°C	Test Date:	April 30, 2020
Humidity:	45%	Test By:	XW


Modulation Mode	Channel Number	Channel Frequency (MHz)	20dB Bandwidth (kHz)
GFSK	0	2402	1046
	39	2441	1045
	78	2480	1010
pi/4-DQPSK	0	2402	1379
	39	2441	1322
	78	2480	1326
8DPSK	0	2402	1364
	39	2441	1361
	78	2480	1383

Test Model	20dB Bandwidth		GFSK Modulation
	Channel 0: 2402MHz		
	<b>Agilent</b> 15:57:34 Apr 30, 2020 <b>Ch Freq</b> 2.402 GHz <b>Trig</b> Free Occupied Bandwidth <b>Center</b> 2.402000000 GHz  Ref 10 dBm Atten 20 dB Mkr1 2.4019550 GHz -0.995 dBm #Peak Log 10 dB/ Span 3 MHz Center 2.402 GHz #VBW 100 kHz Sweep 5 ms (401 pts) <b>Occupied Bandwidth</b> 906.0643 kHz <b>Occ BW % Pwr</b> 99.00 % <b>x dB</b> -20.00 dB <b>Transmit Freq Error</b> -29.537 kHz <b>x dB Bandwidth</b> 1.046 MHz	<b>Freq/Channel</b> <b>Center Freq</b> 2.402000000 GHz <b>Start Freq</b> 2.400500000 GHz <b>Stop Freq</b> 2.403500000 GHz <b>CF Step</b> 300.000000 kHz Auto Man <b>Freq Offset</b> 0.000000000 Hz <b>Signal Track</b> On Off <b>Scale Type</b> Log Lin	
	<b>Agilent</b> 16:01:12 Apr 30, 2020 <b>Ch Freq</b> 2.441 GHz <b>Trig</b> Free Occupied Bandwidth <b>Center</b> 2.441000000 GHz  Ref 10 dBm Atten 20 dB Mkr1 2.4409625 GHz -0.423 dBm #Peak Log 10 dB/ Span 3 MHz Center 2.441 GHz #VBW 100 kHz Sweep 5 ms (401 pts) <b>Occupied Bandwidth</b> 902.7106 kHz <b>Occ BW % Pwr</b> 99.00 % <b>x dB</b> -20.00 dB <b>Transmit Freq Error</b> -29.604 kHz <b>x dB Bandwidth</b> 1.045 MHz	<b>Freq/Channel</b> <b>Center Freq</b> 2.441000000 GHz <b>Start Freq</b> 2.439500000 GHz <b>Stop Freq</b> 2.442500000 GHz <b>CF Step</b> 300.000000 kHz Auto Man <b>Freq Offset</b> 0.000000000 Hz <b>Signal Track</b> On Off <b>Scale Type</b> Log Lin	









## 9.2 CARRIER FREQUENCY SEPARATION

### 9.2.1 Applicable Standard

According to FCC Part 15.247(a)(1) and 558074 D01 15.247 Meas Guidance V05r02

### 9.2.2 Conformance Limit

Frequency hopping systems operating in the 2400-2483.5MHz band shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

In case of an output power less than 125mW, the frequency hopping system may have channels separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

### 9.2.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

### 9.2.4 Test Procedure

■ According to FCC Part 15.247(a)(1)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:  
Set the RBW = 100kHz. Set VBW = 300kHz.

Set the span = wide enough to capture the peaks of two adjacent channels

Set Sweep time = auto couple.

Set Detector = peak. Set Trace mode = max hold.

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.


### Test Results


Temperature: 21°C  
Humidity: 45%



Test Date: April 30, 2020  
Test By: XW



Modulation Mode	Channel Number	Channel Frequency (MHz)	Measurement Bandwidth (kHz)	Limit (kHz)	Verdict
GFSK	0	2402	992.0	697.3	PASS
	39	2441	975.0	696.7	PASS
	78	2480	997.5	673.3	PASS
pi/4-DQPSK	0	2402	1000.0	919.3	PASS
	39	2441	1005.0	881.3	PASS
	78	2480	1005.0	884.0	PASS
8DPSK	0	2402	985.0	909.3	PASS
	39	2441	1012.5	907.3	PASS
	78	2480	1035.0	922.0	PASS


Note: Limit = 20dB bandwidth \* 2/3, if it is greater than 25kHz and the output power is less than 125mW (21dBm).





Test Model	Carrier Frequency Separation		pi/4-DQPSK Modulation	
	Channel 39: 2441MHz			
	 <p>Agilent 16:20:44 Apr 30, 2020</p> <p>Ref 10 dBm Atten 20 dB Mkr1 <math>\Delta</math> 1.0050 MHz 0.026 dB</p> <p>Peak Log 10 dB/ 1R 1</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.441500000 GHz</p> <p>Center 2.442 GHz #Res BW 100 kHz #VBW 300 kHz Span 3 MHz Sweep 5 ms (401 pts)</p>	<b>Freq/Channel</b> <b>Center Freq</b> 2.44150000 GHz <b>Start Freq</b> 2.44000000 GHz <b>Stop Freq</b> 2.44300000 GHz <b>CF Step</b> 300.000000 kHz Auto Man <b>Freq Offset</b> 0.00000000 Hz <b>Signal Track</b> On Off <b>Scale Type</b> Log Lin		
	 <p>Agilent 16:26:03 Apr 30, 2020</p> <p>Ref 10 dBm Atten 20 dB Mkr1 <math>\Delta</math> 1.0050 MHz -0.138 dB</p> <p>Peak Log 10 dB/ 1R 1</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.479500000 GHz</p> <p>Center 2.479 GHz #Res BW 100 kHz #VBW 300 kHz Span 3 MHz Sweep 5 ms (401 pts)</p>	<b>Freq/Channel</b> <b>Center Freq</b> 2.47950000 GHz <b>Start Freq</b> 2.47800000 GHz <b>Stop Freq</b> 2.48100000 GHz <b>CF Step</b> 300.000000 kHz Auto Man <b>Freq Offset</b> 0.00000000 Hz <b>Signal Track</b> On Off <b>Scale Type</b> Log Lin		

Test Model	Carrier Frequency Separation	
	Channel 0: 2402MHz	
	8DPSK Modulation	
	 <p>Agilent 16:15:47 Apr 30, 2020</p> <p>Ref 10 dBm Atten 20 dB Mkr1 <math>\Delta</math> 985 kHz 0.057 dB</p> <p>Peak Log 10 dB/ 1R 1</p> <p>M1 S2 S3 FC AA</p> <p>Marker <math>\Delta</math> 984.574 kHz 0.057 dB</p> <p>Center 2.402 GHz #Res BW 100 kHz Span 2.985 MHz</p> <p>#VBW 300 kHz Sweep 5 ms (401 pts)</p>	<p>Peak Search</p> <p>Meas Tools</p> <p>Next Peak</p> <p>Next Pk Right</p> <p>Next Pk Left</p> <p>Min Search</p> <p>Pk-Pk Search</p> <p>More 1 of 2</p>
	 <p>Agilent 16:22:23 Apr 30, 2020</p> <p>Ref 10 dBm Atten 20 dB Mkr1 <math>\Delta</math> 1.0125 MHz -0.099 dB</p> <p>Peak Log 10 dB/ 1R 1</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.441500000 GHz</p> <p>Center 2.442 GHz #Res BW 100 kHz Span 3 MHz</p> <p>#VBW 300 kHz Sweep 5 ms (401 pts)</p>	<p>Freq/Channel</p> <p>Center Freq 2.44150000 GHz</p> <p>Start Freq 2.440000000 GHz</p> <p>Stop Freq 2.443000000 GHz</p> <p>CF Step 300.0000000 kHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p>



### 9.3 NUMBER OF HOPPING FREQUENCIES

#### 9.3.1 Applicable Standard

According to FCC Part 15.247(a)(1) (iii) and 558074 D01 15.247 Meas Guidance V05r02

#### 9.3.2 Conformance Limit

Frequency hopping systems operating in the 2400-2483.5MHz band shall use at least 15 channels.

#### 9.3.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

#### 9.3.4 Test Procedure

- According to FCC Part 15.247(a)(1)(iii)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW = 100kHz

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies.

#### Test Results

Temperature:

21°C

Test Date:

April 30, 2020

Humidity:


45 %

Test By:

XW

Hopping Channel Frequency Range	Quantity of Hopping Channel	Quantity of Hopping Channel limit
2402-2480 (GFSK)	79	>15

Note: Both BR & EDR mode has same result .



## 9.4 AVERAGE TIME OF OCCUPANCY (DWELL TIME)

### 9.4.1 Applicable Standard

According to FCC Part 15.247(a)(1)(iii) and 558074 D01 15.247 Meas Guidance V05r02

### 9.4.2 Conformance Limit

For frequency hopping systems operating in the 2400-2483.5MHz band, the averagetime of occupancy on any channel shall not be greater than 0.4s within a period of 0.4smultiplied by the number of hopping channels employed.

### 9.4.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

### 9.4.4 Test Procedure

- According to FCC Part15.247(a)(1)(iii)

The EUT must have its hopping function enabled. Use the following spectrum analyzersettings:

Span = zero span, centered on a hopping channel

RBW = 1 MHz

VBW  $\geq$  RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

If possible, use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section.

### 9.4.5 Test Results

Temperature: 21°C  
Humidity: 45 %

Test Date: April 30, 2020  
Test By: XW

Modulation Mode	Channel Number	Packet type	Pluse width (ms)	DwellTime (ms)	Limit (ms)	Verdict
GFSK	0	DH1	0.430	137.600	<400	PASS
	0	DH3	1.660	265.600	<400	PASS
	0	DH5	3.000	320.000	<400	PASS

Note1: DwellTime(DH1)=PW\*(1600/2/79)\*31.6

DwellTime(DH3)=PW\*(1600/4/79)\*31.6

DwellTime(DH5)=PW\*(1600/6/79)\*31.6

Note2: Bluetooth (GFSK, pi/4-DQPSK, 8DPSK)mode have been tested, and the worst results has been recorded on the follow page.

