

# CINO Technology(shenzhe n)Ltd

## TEST REPORT

**SCOPE OF WORK**

EMC TESTING—CB1-0-01

**REPORT NUMBER**

200409026GZU-001

**ISSUE DATE**

[REVISED DATE]

15-June-2020

[-----]

**PAGES**

29

**DOCUMENT CONTROL NUMBER**

FCC Part 15.225-b

© 2017 INTERTEK



**TEST REPORT**

Block E, No.7-2 Guang Dong  
Software Science Park, Caipin Road,  
Guangzhou Science City, GETDD  
Guangzhou, China

Telephone: 86-20-8213 9688

Fax: 86-20-3205 7538

[www.intertek.com](http://www.intertek.com)

Applicant Name & : CINO Technology(shenzhen)Ltd  
Address : 3rd, 4th & 5th floor, G Building, Licheng Scientific and Technology  
Industrial P shenzhen, China  
Manufacturing Site : Same as applicant  
Intertek Report No: 200409026GZU-001  
FCC ID: 2AWEK -CB1-0-01

**Test standards**

**47 CFR PART 15 Subpart C: 2019 section 15.225**

**Sample Description**

Product : CUBO Single Serve Home Brewing System  
Model No. : CB1-0-01  
Electrical Rating : 120Vac, 60Hz  
Serial No. : Not Labeled  
Date Received : 09 April 2020  
Date Test Conducted : 09 April 2020-27 May 2020

Prepared and Checked By



Daniel He

Project Engineer

Intertek Guangzhou

Approved By:



Helen Ma

Team Leader

Intertek Guangzhou

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**TEST REPORT****CONTENT**

<b>TEST REPORT</b> .....	<b>1</b>
<b>CONTENT</b> .....	<b>3</b>
<b>1.0 TEST RESULT SUMMARY</b> .....	<b>4</b>
<b>2.0 GENERAL DESCRIPTION</b> .....	<b>5</b>
2.1 PRODUCT DESCRIPTION .....	5
2.2 RELATED SUBMITTAL(S) GRANTS .....	5
2.3 TEST METHODOLOGY .....	5
2.4 TEST FACILITY .....	5
<b>3.0 SYSTEM TEST CONFIGURATION</b> .....	<b>6</b>
3.1 JUSTIFICATION .....	6
3.2 EUT EXERCISING SOFTWARE .....	7
3.3 SPECIAL ACCESSORIES .....	7
3.4 MEASUREMENT UNCERTAINTY .....	7
3.5 EQUIPMENT MODIFICATION .....	8
3.6 SUPPORT EQUIPMENT LIST AND DESCRIPTION .....	8
<b>4.0 MEASUREMENT RESULTS</b> .....	<b>9</b>
4.1 ANTENNA REQUIREMENT .....	9
4.2 OCCUPIED BANDWIDTH .....	10
4.3 RADIATED EMISSION .....	12
4.4 FREQUENCY STABILITY .....	23
4.5 CONDUCTED EMISSION TEST .....	25
<b>5.0 TEST EQUIPMENT LIST</b> .....	<b>28</b>

**TEST REPORT****1.0 TEST RESULT SUMMARY**

Test Item	Test Requirement	Test Method	Result
Antenna Requirement	FCC PART 15 C Section 15.203	FCC PART 15 C Section 15.203	PASS
Occupied Bandwidth	FCC PART 15 C section 15.215(c)	ANSI C63.10: Clause 6.9	PASS
Radiated Emission	FCC PART 15 C section 15.225 (a), (b), (c), (d)	ANSI C63.10: Clause 6.4 & 6.5	PASS
Frequency Stability	FCC PART 15 C section 15.225 (e)	ANSI C63.10: Clause 6.8	PASS
Conducted Emissions at Mains Terminals	FCC PART 15 C section 15.207	ANSI C63.10: Clause 6.2	PASS
<b>Remark:</b> N/A: not applicable. Refer to the relative section for the details. EUT: In this whole report EUT means Equipment Under Test. Tx: In this whole report Tx (or tx) means Transmitter. Rx: In this whole report Rx (or rx) means Receiver. RF: In this whole report RF means Radio Frequency. ANSI C63.10: the detail version is ANSI C63.10:2013 in the whole report			

## TEST REPORT

### 2.0 General Description

#### 2.1 Product Description

Operating Frequency	13.56 MHz
Type of Modulation:	ASK
Number of Channels	1 Channel
Channel Separation:	N/A
Antenna Type	Cooper Wire printed circuit board
Antenna gain:	0 dBi
Power Supply:	120Vac, 60Hz
Power cord:	1.8m x 2 wires unscreened AC power cord

#### 2.2 Related Submittal(s) Grants

This is an application for certification of:  
DXX- Low Power Communications Device Transmitter

Remaining portions are subject to the following procedures:  
Receiver portion: exempt from technical requirement of this Part.

#### 2.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10. Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans and final tests were performed in the semi-anechoic chamber to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise.

#### 2.4 Test Facility

All tests were performed at:  
Room102/104, No 203, KeZhu Road, Science City, GETDD Guangzhou, China  
Except Conducted Emissions was performed at:  
Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD Guangzhou, China

A2LA Certificate Number 0078.10

## TEST REPORT

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch is accredited by A2LA and Listed in FCC website. FCC accredited test labs may perform both Certification testing under Parts 15 and 18 and Declaration of Conformity testing.

### 3.0 System Test Configuration

#### 3.1 Justification

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. It was powered by 120Vac supply.

When below 30MHz, the measurement antenna was positioned with its plane perpendicular to the ground at the specified distance. When perpendicular to the ground plane, the lowest height of the magnetic antenna was 1 m above the ground and was positioned at 3m distance from the EUT. During testing the loop antenna was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane. For each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable.

When above 30MHz, the antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. The spurious emissions more than 20 dB below the permissible value are not reported.

For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in the following table:

Frequency range of radiated emission measurements

Lowest frequency generated in the device	Upper frequency range of measurement
9 kHz to below 10 GHz	10th harmonic of highest fundamental frequency or to 40 GHz, whichever is lower
At or above 10 GHz to below 30 GHz	5th harmonic of highest fundamental frequency or to 100 GHz, whichever is lower
At or above 30 GHz	5th harmonic of highest fundamental frequency or to 200 GHz, whichever is lower, unless otherwise specified

## TEST REPORT

Number of fundamental frequencies to be tested in EUT transmit band

Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
1 MHz or less	1	Middle
1 MHz to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

### 3.2 EUT Exercising Software

N/A

### 3.3 Special Accessories

No special accessories used.

### 3.4 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	20 dB Bandwidth	2.3%
	6dB Bandwidth	
	99% Bandwidth	
	Frequency Stability	
2	Carrier Frequencies Separated	2.3%
3	Dwell Time	1.2%
4	Maximum Peak Conducted Output Power	1.5dB
5	Peak Power Spectral Density	1.5dB
6	Out of Band Conducted Emissions	1.5dB
7	Band edges measurement	1.5dB
8	Radiated Emissions	4.7 dB (25 MHz-1 GHz)
		4.8 dB (1 GHz-18 GHz)
		5.21dB (18GHz-26GHz)
9	Conducted Emissions at Mains Terminals	2.58dB
10	Temperature	0.5 °C
11	Humidity	0.4 %
12	Time	1.2%

## TEST REPORT

The measurement uncertainty describes the overall uncertainty of the given measured value during the operation of the EUT.

Measurement uncertainty is calculated in accordance with ETSI TR 100 028-2001.  
The measurement uncertainty is given with a confidence of 95%, k=2.

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

Uncertainty and Compliance – Unless the standard specifically states that measured values are to be extended by the measurement uncertainty in determining compliance, all compliance determinations are based on the actual measured value

### 3.5 Equipment Modification

Any modifications installed previous to testing by CINO Technology(shenzhen)Ltd.will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Guangzhou Branch.

### 3.6 Support Equipment List and Description

The client made a continuous transmit sample for test.

## TEST REPORT

### 4.0 Measurement Results

#### 4.1 Antenna Requirement


Standard requirement:

15.203 requirement:

For intentional device. According to 15.203 an intentional radiator shall be designed to Ensure that no antenna other than that furnished by the responsible party shall be used with the device.

EUT Antenna

The antenna is a Cooper Wire printed circuit board and integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0 dBi.




**TEST REPORT****4.2 Occupied Bandwidth**

Test Requirement: FCC PART 15 C section 15.215(c)  
(c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

Test Method: ANSI C63.10: Clause 6.9

Test Status: Pre-Scan has been conducted to determine the worst-case mode.

Test Configuration:

**Test Procedure:**

The transmitter was operated at its maximum carrier power measured under normal test conditions.

- a) The instrument center frequency was set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer was between 1.5 times and 5.0 times the OBW(20 dB Bandwidth).
- b) The nominal IF filter bandwidth (3 dB RBW) was in the range of 1% to 5% of the OBW, and VBW was approximately three times the RBW.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope was more than  $[10 \log (OBW/RBW)]$  below the reference level.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) The dynamic range of the instrument at the selected RBW was more than 10 dB below the target “-20 dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW was at least 30 dB below the reference value.

## TEST REPORT

- f) Peak detection and max hold mode (until the trace stabilizes) was used.
- g) Used the 20dB bandwidth function of the instrument and reported the measured bandwidth.
- h) The occupied bandwidth was reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division was clearly labeled. Tabular data was reported in addition to the plot(s).


### Used Test Equipment List

Spectrum Analyzer. Refer to Clause 5 Test Equipment List for details.

20 dB bandwidth:

Frequency (MHz)	20 dB bandwidth (kHz)	lower frequency (MHz)	upper frequency (MHz)	Assigned Band (MHz)	Result
13.560	2.75	13.558	13.561	13.110-14.010	Pass

Result plot as follows:



Test result: The unit does meet the FCC requirements.

## TEST REPORT

### 4.3 Radiated Emission

Test Requirement: FCC PART 15 C section 15.225 (a), (b), (c), (d)

The field strength of emissions from intentional radiators operated under this Section shall not exceed the following:

- 15.225(a): The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.i.e. 124.0dB $\mu$ V/m @ 3 m.
- 15.225(b): Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters. i.e. 90.5dB $\mu$ V/m @ 3 m.
- 15.225(c): Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters. i.e. 80.5dB $\mu$ V/m @ 3 m.
- 15.225(d) :The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in § 15.209.

#### § 15.209 Limit:

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

Field strength limits(below 30MHz) at 30 m and 300 m change to 3 m by formula:

$$\text{Limit3m(dB}\mu\text{V)} = \text{Limit30m(dB}\mu\text{V)} + 40 * \log(30\text{m}/3\text{m})$$

$$\text{Limit3m(dB}\mu\text{V)} = \text{Limit300m(dB}\mu\text{V)} + 40 * \log(300\text{m}/3\text{m})$$

Frequency (MHz)	Field Strength (dB $\mu$ V/m @ 3m)
0.009-0.490	128.5 to 93.8
0.490-1.705	68.9 to 62.9
1.705-30.0	69.5
30-88	40
88-216	43.5
216-960	46
Above 960	54

Test Method: ANSI C63.10: Clause 6.4 and 6.5.

Test Status: Pre-Scan has been conducted to determine the worst-case mode from all possible configuration.

Test site: Measurement Distance: 3m (Semi-Anechoic Chamber)

## TEST REPORT

Detector:

Quasi-Peak detector:  
RBW=200 Hz for 9 kHz to 150 kHz  
RBW=9 kHz for 150 kHz to 30 MHz  
RBW=120 kHz for 30 MHz to 1GHz  
Sweep = auto  
Trace = max hold

Field Strength Calculation:

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below:

FS = RA + AF + CF - AG + PD + AV

FS = RA + Correct Factor + AV

FS = Field Strength in dB $\mu$ V/m

Where:

RA = Receiver Amplitude (including preamplifier) in dB $\mu$ V

AF = Antenna Factor in dB

CF = Cable Attenuation Factor in dB

AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

AV = Average Factor in -dB

Correct Factor = AF + CF - AG + PD

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

FS = RA + AF + CF - AG + PD + AV

Assume a receiver reading of 62.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32 dB $\mu$ V/m.

RA = 62.0 dB $\mu$ V

AF = 7.4 dB

CF = 1.6 dB

AG = 29.0 dB

PD = 0 dB

AV = -10 dB

Correct Factor = 7.4 + 1.6 - 29.0 + 0 = -20 dB

FS = 62 + (-20) + (-10) = 32 dB $\mu$ V/m

**TEST REPORT**

## Section 15.205 Restricted bands of operation.


MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	
13.36 - 13.41	322 - 335.4		

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in 15.209.


## TEST REPORT

Test Configuration:

- 1) 9 kHz to 30 MHz emissions:



- 2) 30 MHz to 1 GHz emissions:



## TEST REPORT

### Test Procedure:

#### 1) 9 kHz to 30 MHz emissions:

For testing performed with the loop antenna. The centre of the loop was positioned 1 m above the ground and positioned with its plane vertical at the special distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane.

#### 2) 30 MHz to 1 GHz emissions:

For testing performed with the bi-log type antenna. The measurement is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurement for both the horizontal and vertical antenna polarizations.

#### 3) The receiver was scanned from 9 kHz to 1000 MHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. The worst case emissions were reported.


### Used Test Equipment List:

3m Semi-Anechoic Chamber, EMI Test Receiver (9 kHz~7 GHz), Signal and Spectrum Analyzer (10 Hz~40 GHz), Loop antenna (9 kHz-30 MHz). TRILOG Super Broadband test Antenna(30 MHz-3 GHz) (RX), Double-Ridged Waveguide Horn Antenna (800 MHz-18 GHz)(RX) and High Frequency Antenna & preamplifier(18 GHz~26.5 GHz) (RX). Refer to Clause 5 Test Equipment List for details.

## TEST REPORT

### Radiated Emissions (Below 30 MHz)


#### Horizontal:



Notes: All other emissions were greater than 20 dB below the limit.

## TEST REPORT


Radiated emission from 13.11MHz to 14.01MHz:



Frequency (MHz)	Receiver Reading Level (dB $\mu$ V)	Correction factors (dB/m)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
13.56	28.4	21.0	49.4	124.0


## TEST REPORT

### Vertical:



Notes: All other emissions were greater than 20 dB below the limit.

## TEST REPORT



Radiated emission from 13.11MHz to 14.01MHz:

Frequency (MHz)	Receiver Reading Level (dB $\mu$ V)	Correction factors (dB/m)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
13.56	29.3	21.0	50.3	124.0


The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

## Remark:

1. Corr. (dB) = Antenna Factor (dB) + Cable Loss (dB)
2. Level (dB $\mu$ V/m) = Corr. (dB) + Read Level (dB $\mu$ V)
3. Margin (dB) = Limit (dB $\mu$ V/m) – Level (dB $\mu$ V/m)
4. Only record the date closest to limit
5. The emission is worst case on Vertical
6. When Peak emission level was below AV or QP limit, the AV and QP emission level was not recorded.

**TEST REPORT**
**Horizontal:**

Quasi-peak measurement




Frequency (MHz)	Receiver Reading Level (dB $\mu$ V)	Correction factors (dB/m)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
162.68	19.7	10.4	30.1	43.5
189.84	18.2	12.0	30.2	43.5
244.04	19.3	14.2	33.5	46.0

**Remark:**

Final Test Level = Receiver Reading + Correction Factor

Correction Factor = Antenna Factor + Cable Loss.

**TEST REPORT**

 Vertical  
 Quasi-peak measurement


Frequency (MHz)	Receiver Reading Level (dB $\mu$ V)	Correction factors (dB/m)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)
135.56	14.3	9.8	24.1	43.5
162.68	20.8	10.4	31.2	43.5
189.84	14.2	12.0	26.2	43.5

Remark:

Final Test Level = Receiver Reading + Correction Factor

Correction Factor = Antenna Factor + Cable Loss.

## TEST REPORT

### 4.4 Frequency Stability

Test Requirement: FCC Part 15 C section 15.225 (e)  
(e) The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  of the operating frequency over a temperature variation of -20 degrees to + 50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

Test Method: ANSI C63.10: Clause 6.8

Test Procedure:

- (1) Supply the EUT with a new battery. Turn the EUT OFF and place it inside the environmental temperature chamber.
- (2) Set the temperature control on the chamber to +50 degrees C and allow the oscillator heater and the chamber temperature to stabilize.
- (3) While maintaining a constant temperature inside the environmental chamber, turn the EUT ON and record the operating frequency.
- (4) Switch OFF the EUT. Lower the chamber temperature by not more than 10 °C, and allow the temperature inside the chamber to stabilize. Repeat step 3) through step 4) down to the lowest specified temperature.
- (5) At a temperature of 20°C, record the frequency at 85% and 115% of the nominal supply voltage.

#### Used Test Equipment List:

Signal and Spectrum Analyzer, Programmable Temperature & Humidity Test Chamber, Regulated DC Power supply. Refer to Clause 5 Test Equipment List for details.

The main frequency is 13.56MHz, under unnormal conditions, it's should be within +/- 1.356 kHz (+/- 0.01% of the operating frequency).

**TEST REPORT**

Temperature (°C)	Measured Frequency (MHz)	Result
+40	13.5601	Pass
+30	13.5602	Pass
+20	13.5600	Pass
+10	13.5600	Pass
0	13.5601	Pass


Remark: the device will stop work outside of the operation temperature (0 degree to 40 degree).

Power Supply (Vac)	Measured Frequency (MHz)	Result
85%	13.5599	Pass
95%	13.5600	Pass
105%	13.5601	Pass
115%	13.5602	Pass

## TEST REPORT

### 4.5 Conducted Emission Test

Test Configuration:



#### Test Setup and Procedure:

Test was performed according to ANSI C63.10 Clause 6.2. The EUT was set to achieve the maximum emission level. The mains terminal disturbance voltage was measured with the EUT in a shielded room. The EUT was connected to AC power source through an Artificial Mains Network which provides a  $50\Omega$  linear impedance. Artificial hand is used if appropriate (for handheld apparatus). The load/control terminal disturbance voltage was measured with passive voltage probe if appropriate.

The table-top EUT was placed on a 0.8m high non-metallic table above earthed ground plane (Ground Reference Plane). And for floor standing EUT, was placed on a 0.1m high non-metallic supported on GRP. The EUT keeps a distance of at least 0.8m from any other of the metallic surface. The Artificial Mains Network is situated at a distance of 0.8m from the EUT.

During the test, mains lead of EUT excess 0.8m was folded back and forth parallel to the lead so as to form a horizontal bundle with a length between 0.3m and 0.4m

The bandwidth of test receiver was set at 9 kHz. The frequency range from 150 kHz to 30MHz was checked.


## TEST REPORT

### Test Data and Curve

At main terminal: Pass

Tested Wire: Live

Operation Mode: transmitting mode



EDIT PEAK LIST (Final Measurement Results)				
Trace1:	FCC15QP			
Trace2:	FCC15AV			
Trace3:	---			
TRACE	FREQUENCY	LEVEL dB $\mu$ V	L1	DELTA LIMIT dB
1 Quasi Peak	162 kHz	43.84	L1	-21.51
1 Quasi Peak	590 kHz	33.42	L1	-22.57
1 Quasi Peak	13.562 MHz	48.38	L1	-11.62
2 Average	13.562 MHz	48.63	L1	-1.36


### Remark:

1. Corr. (dB) = LISN Factor (dB) + Cable Loss (dB)
2. Level (dB $\mu$ V) = Corr. (dB) + Read Level (dB $\mu$ V)
3. Delta Limit (dB) = Level (dB $\mu$ V)-Limit (dB $\mu$ V)

**TEST REPORT**

Tested Wire: Neutral

Operation Mode: transmitting mode



EDIT PEAK LIST (Final Measurement Results)				
Trace1:	FCC15QP			
Trace2:	FCC15AV			
Trace3:	---			
TRACE	FREQUENCY	LEVEL dBµV	DELTA LIMIT dB	
1 Quasi Peak	162 kHz	43.92 L1	-21.43	
1 Quasi Peak	13.562 MHz	46.95 L1	-13.04	
2 Average	13.562 MHz	47.21 L1	-2.78	

Remark:

1. Corr. (dB) = LISN Factor (dB) + Cable Loss (dB)
2. Level (dBµV) = Corr. (dB) + Read Level (dBµV)
3. Delta Limit (dB) = Level (dBµV)-Limit (dBµV)

**TEST REPORT**
**5.0 Test Equipment List**
**Conducted Disturbance-Mains Terminal (1)**

Equipment No.	Equipment	Model	Manufacturer	Calibration Interval
EM080-05	EMI receiver	ESCI	R&S	1Y
EM006-05	LISN	ENV216	R&S	1Y
SA047-112	Digital Temperature-Humidity Recorder	RS210	YIJIE	1Y
EM004-04	EMC shield Room	8m×3m×3m	Zhongyu	1Y

**Radiated Disturbance (9 kHz-30 MHz)**

Equipment No.	Equipment	Model	Manufacturer	Calibration Interval
EM030-04	3m Semi-Anechoic Chamber	9×6×6 m3	ETS-LINDGREN	1Y
EM031-02	EMI Test Receiver (9 kHz~7 GHz)	R&S ESR7	R&S	1Y
EM011-04	Loop antenna (9 kHz-30 MHz)	HFH2-Z2	R&S	1Y
EM031-02-01	Coaxial cable	/	R&S	1Y
SA047-118	Digital Temperature-Humidity Recorder	RS210	YIJIE	1Y
EM045-01-01	EMC32 software (RE/RS)	V10.01.00	R&S	N/A

**Radiated Disturbance (30 MHz-1 GHz)**

Equipment No.	Equipment	Model	Manufacturer	Calibration Interval
EM030-04	3m Semi-Anechoic Chamber	9×6×6 m3	ETS-LINDGREN	1Y
EM031-02	EMI Test Receiver (9 kHz~7 GHz)	R&S ESR7	R&S	1Y
EM033-01	TRILOG Super Broadband test Antenna (30 MHz-3 GHz)	VULB 9163	SCHWARZBECK	1Y
EM031-02-01	Coaxial cable	/	R&S	1Y
EM036-01	Common-mode absorbing clamp	CMAD 20B	TESEQ	1Y
SA047-118	Digital Temperature-Humidity Recorder	RS210	YIJIE	1Y
EM045-01-01	EMC32 software (RE/RS)	V10.01.00	R&S	N/A

**Occupied Bandwidth:**

Equipment No.	Equipment	Model	Manufacturer	Calibration Interval
EM031-02	EMI Test Receiver (9 kHz~7 GHz)	R&S ESR7	R&S	1Y

## TEST REPORT

Equipment No.	Cal. Due date (DD-MM-YYYY)
<b>Conducted Disturbance-Mains Terminal (1)</b>	
EM080-05	17/07/2020
EM006-05	07/06/2021
SA047-112	08/11/2020
EM004-04	05/01/2021
<b>Conducted Disturbance-Mains Terminal (2)</b>	
EM080-04	10/11/2020
EM031-04	16/01/2021
EM006-06	08/09/2020
SA047-111	08/11/2020
EM004-03	05/01/2021
EM031-04-01	N/A
<b>Conducted Disturbance-Load and Control Terminal (1)</b>	
EM080-05	17/07/2020
EM080-05-01	08/09/2020
SA047-112	08/11/2020
EM004-04	05/01/2021
<b>Conducted Disturbance-Load and Control Terminal (2)</b>	
EM080-05	17/07/2020
EM005-06-01	09/09/2020
SA047-112	08/11/2020
EM004-04	05/01/2021
<b>Conducted Disturbance-Telecom Terminal</b>	
EM080-05	17/07/2020
EM011-05	12/04/2021
EM011-06	12/04/2021
EM006-06	08/09/2020
SA047-112	08/11/2020
EM004-04	05/01/2021
<b>Conducted Disturbance-Antenna Terminal</b>	
EM080-04	10/11/2020
EM031-04	16/01/2021
EM084-02	18/07/2020
EM041-01	07/01/2021
EM041-02	07/01/2021
SA047-111	08/11/2020
EM004-03	05/01/2021
<b>Click (1)</b>	
EM008-01	17/07/2020
EM006-06	08/09/2020
SA047-111	08/11/2020
EM004-03	05/01/2021
<b>Click (2)</b>	
EM008-02	10/11/2020
EM008-02-01	10/11/2020
EM006-04	09/09/2020
EM032-02	17/07/2020
SA047-111	08/11/2020
EM004-03	05/01/2021
<b>Disturbance Power</b>	
EM080-05	18/07/2020
EM081-04	11/03/2021
SA047-112	08/11/2020
EM004-04	05/01/2021

Equipment No.	Cal. Due date (DD-MM-YYYY)
<b>Radiated Disturbance (CDN Method)</b>	
EM080-05	17/07/2020
EM003-02	10/11/2020
EM003-03	10/11/2020
EM003-01-05	08/09/2020
SA047-112	08/11/2020
EM004-04	05/01/2021
<b>Radiated electromagnetic disturbances (9 kHz-30 MHz)</b>	
EM080-04	10/11/2020
EM031-04	16/01/2021
EM061-04	8/03/2021
SA047-111	08/11/2020
EM004-03	05/01/2021
<b>Radiated Disturbance (9 kHz-30 MHz)</b>	
EM030-04	10/04/2021
EM031-02	22/10/2020
EM011-04	24/06/2020
EM031-02-01	12/04/2021
SA047-118	16/7/2020
EM045-01-01	N/A
<b>Radiated Disturbance (30 MHz-1 GHz)</b>	
EM030-04	10/04/2021
EM031-02	22/10/2020
EM033-01	19/09/2020
EM031-02-01	12/04/2021
EM036-01	21/07/2020
SA047-118	16/07/2020
EM045-01-01	N/A
<b>Radiated Disturbance (1-18 GHz)</b>	
EM030-04	10/04/2021
EM031-02	22/10/2020
EM031-03	08/09/2020
EM033-02	22/06/2020
EM033-02-02	12/04/2021
EM022-03	10/05/2021
SA047-118	16/07/2020
EM045-01-01	N/A
<b>Harmonic Currents and Flicker (1)</b>	
EM001-02	10/11/2020
SA047-111	08/11/2020
<b>Harmonic Currents and Flicker (2)</b>	
EM001-03	09/09/2020
EM001-03-01	08/09/2020
SA047-140	01/01/2021
<b>EMF</b>	
EM007-03	23/02/2021
SA047-112	08/11/2020
<b>Induced Current Density (20 kHz-10 MHz)</b>	
EM080-04	10/11/2020
EM031-04	16/01/2021
EM007-02	07/01/2021
SA047-111	08/11/2020

Equipment No.	Cal. Due date (DD-MM-YYYY)
<b>Electrostatic Discharge (1)</b>	
EM077-04	15/04/2021
SA047-143	26/09/2020
<b>Electrostatic Discharge (2)</b>	
EM077-02	08/05/2021
SA047-143	26/09/2020
<b>Electrical Fast Transient/Burst (1)</b>	
EM005-12	12/04/2021
EM005-10-01	15/04/2021
SA047-140	01/01/2021
<b>Electrical Fast Transient/Burst (2)</b>	
EM005-10	05/05/2021
EM005-10-01	15/04/2021
SA047-140	01/01/2021
<b>Surge (2)</b>	
EM005-08	30/07/2020
SA047-140	01/01/2021
<b>Surge (3)</b>	
EM005-09	12/05/2020
SA047-140	01/01/2021
<b>Conducted Susceptibility (1)</b>	
EM046-04	19/12/2020
EM084-02	18/07/2020
EM003-01-04	08/09/2020
EM003-01-05	08/09/2020
EM019-01-01	08/09/2020
EM019-03	17/07/2020
SA047-140	01/01/2021
<b>Conducted Susceptibility (2)</b>	
EM019-01	12/04/2021
EM019-01-01	08/09/2020
EM019-01-02	08/09/2020
EM019-01-03	08/09/2020
EM019-03	17/07/2020
SA047-140	01/01/2021
<b>Voltage Dips and Interruptions (2)</b>	
EM005-09	12/05/2020
EM005-09-01	12/05/2020
SA047-140	01/01/2021
<b>Voltage Dips and Interruptions (3)</b>	
SZ063-01	06/01/2021
SZ063-01-01	06/01/2021
<b>Radiated Susceptibility</b>	
EM030-04	10/04/2021
EM031-01	18/07/2020
EM086-11	24/11/2020
EM086-11-01	24/11/2020
EM046-01	19/03/2021
EM046-03	08/09/2020
EM061-05	11/10/2021
EM061-07	11/10/2021
EM034-01	/
EM045-01-01	/
SA047-118	16/07/2020
<b>Power Frequency Magnetic Field</b>	
EM001-03	09/09/2020
EM001-03-02	09/09/2020
SA047-140	01/01/2021
<b>Ring Wave</b>	
EM005-11	12/04/2021
SA047-140	01/01/2021

\*\*\*\*End of the test report\*\*\*\*\*