

WAG-F-LBG0-00-052 Specification

1. Explanation of part number :

WAG F LBG0 00 052
(1) (2) (3) (4) (5)

(1) Product Type: Wireless Antenna

(2) Material: FPC

(3) Frequency : 1575.42/2400-2500/5150-5850MHz

(4) Coaxial Cable Type : 00

(5) Suffix : 052

2. Storage Condition:

Temperature -40 to +85°C
Humidity 20 to 65 %RH
Recommended storage condition:

Store in room condition as listed below: Temperature -20°C~+45°C, Humidity 80% Max.

3. Operating Condition:

Temperature -40 to +85°C
Humidity 10 to 85 %RH

4. Electrical Specification :

Those specifications were specially defined for WLAN model, and all characteristics were measured in the customer's machine.

4-1. Frequency Band:


Frequency Band	MHz
WBG Antenna	1575.42/2400-2500/5150-5850MHz

4- 2.Impedance

50 ohm nominal

UNLESS OTHER SPECIFIED TOLERANCES ON : X = ± X.X = ± X.XX = ± ANGLES = ± HOLEDIA = ±		Shenzhen HamyWe Technology Co., Ltd.	
SCALE :	UNIT : mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF Shenzhen HamyWe Technology Co., Ltd. AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION	
DRAWN BY: Eason	CHECKED BY: Jake		
DESIGNED BY: Eason	APPROVED BY : Jake		
TITLE: WAG-F-LBG0-00-052 Specification		DOCUMENT NO.	PAGE REV.
		ENS	P0

4-3. VSWR:

Frequency Band	1575.42	2400	2500	5150	5850
2-3-1. Typical Value:	≤ 4	≤ 5	≤ 3	≤ 4	≤ 3
2-3-2 Measuring Method	1. A 50Ωcoaxial cable is connected to the fpcb antenna. Then this cable is connected to a network analyzer to measure the VSWR. 2. Keeping this jig away from metal at least 20 cm.				
2-3-3 Picture					


4-4. Gain and Efficiency

4-4.1 Measure method

1. Using a low loss coaxial cable to link a standard handset jig
2. Fixed this handset jig on chamber's rotator plane
3. Linking jig into network analyzer port and using a probing horn antenna to collect data.
4. Using another standard gain horn antenna to calibrated those data

UNLESS OTHER SPECIFIED TOLERANCES ON :		Shenzhen HamyWe Technology Co., Ltd.		
X = ±	X.X = ±			
ANGLES = ±	HOLEDIA = ±			
SCALE :	UNIT : mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF Shenzhen HamyWe Technology Co., Ltd. AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION		
DRAWN BY: Eason	CHECKED BY: Jake			
DESIGNED BY: Eason	APPROVED BY : Jake			
TITLE: WAG-F-LBG0-00-052 Specification		DOCUMENT NO.	ENS	PAGE REV.
				P0

4-4.2 Chamber definition



1. An anechoic chamber (8mx4mx3.5m) which satisfied far-field condition was applied to avoid multi-path effect
2. The quiet room region is 40cmx40cmx40cm at the center of rotator
3. The distance between DUT and standard antenna is 4.38 m
4. Probing antenna (9120D horn antenna) and standard gain horn antenna (BBHA9120 LPF 700MHz ~6GHz)

2-4.3 Gain and Efficiency

Fre	Effi(db)	Gain(dBi)	Effi(%)	Fre	Effi(db)	Gain(dBi)	Effi(%)
1500	-1.81	2.08	65.91	5000	-3.33	1.05	46.44
1505	-1.64	2.16	68.56	5050	-3.13	2.12	48.64
1510	-1.99	1.71	63.27	5100	-2.93	3.05	50.88
1515	-1.77	1.9	66.56	5150	-2.99	3.49	50.22
1520	-2.1	1.56	61.72	5200	-2.96	3.75	50.55
1525	-1.94	1.67	64	5250	-2.61	4.31	54.88
1530	-2.3	1.25	58.91	5300	-2.86	4.01	51.81
1535	-1.88	1.61	64.84	5350	-2.83	4.04	52.16
1540	-2.27	1.1	59.24	5400	-3.02	3.86	49.94

UNLESS OTHER SPECIFIED TOLERANCES ON :

X = ± X.X = ± X.XX = ±

ANGLES = ± HOLEDIA = ±

SCALE : UNIT : mm

DRAWN BY: Eason CHECKED BY: Jake

DESIGNED BY: Eason APPROVED BY : Jake

TITLE: WAG-F-LBG0-00-052 Specification

Shenzhen HamyWe Technology Co., Ltd.

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF Shenzhen HamyWe Technology Co., Ltd. AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

DOCUMENT
NO.

ENS

PAGE REV.
P0

1545	-1.94	1.37	63.94	5450	-2.97	3.97	50.42
1550	-2.25	1.1	59.63	5500	-2.99	3.94	50.25
1555	-1.89	1.43	64.68	5550	-2.81	4.01	52.34
1560	-2.39	0.89	57.63	5600	-2.5	4.38	56.18
1565	-1.96	1.33	63.69	5650	-2.5	4.11	56.2
1570	-2.14	1.09	61.05	5700	-2.23	4.43	59.91
1575	-2.41	0.9	57.38	5750	-2.07	4.62	62.04
1580	-2.6	0.81	54.97	5800	-2.01	4.42	63.01
1585	-2.1	1.21	61.65	5850	-1.78	4.62	66.43
1590	-2.52	0.87	55.97	5900	-1.58	4.64	69.55
1595	-2.08	1.31	61.9	5950	-0.91	5.06	81.02
1600	-2.43	1.01	57.14	6000	-1.09	4.78	77.82
1605	-2.1	1.37	61.62				
1610	-2.41	1.14	57.46				
1615	-2.2	1.49	60.24				
1620	-2.42	1.29	57.29				
2300	-5.77	-1.28	26.46				
2320	-4.83	-0.55	32.85				
2340	-4.2	-0.2	38.02				
2360	-3.73	0.07	42.34				
2380	-3.57	0.16	43.97				
2400	-4.26	-0.54	37.51				
2420	-3.53	0.21	44.39				
2440	-2.94	0.76	50.77				
2460	-2.4	1.26	57.48				
2480	-2.15	1.47	60.97				
2500	-2.16	1.38	60.75				
2520	-0.93	3	80.76				
2540	-1.04	3.05	78.7				
2560	-1.18	2.93	76.13				
2580	-1.3	2.8	74.12				
2600	-1.51	2.75	70.7				

2-5.OTA And Data 3D


2-5.1 OTA And Boom

1、OTA


UNLESS OTHER SPECIFIED TOLERANCES ON :		Shenzhen HamyWe Technology Co., Ltd.		
X = ± X.X = ± X.XX = ±				
ANGLES = ± HOLEDIA = ±				
SCALE :	UNIT : mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF Shenzhen HamyWe Technology Co., Ltd. AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION		
DRAWN BY: Eason	CHECKED BY: Jake			
DESIGNED BY: Eason	APPROVED BY : Jake			
TITLE: WAG-F-LBG0-00-052 Specification		DOCUMENT NO.	ENS	PAGE REV.
				P0

GPS.WIFI-2.4G				
802.11b	6Mbps	TRP	1	16.03
			7	16.52
			13	16.33
	54Mbps	TIS	1	-83.54
			7	-84.22
			13	-82.46
GPS		CNO	TIS	
		42.05	-155.24	


2-5.2 Data 3D



1575MHz




2460MHz



5500MHz

5.Mechanical Specification:

UNLESS OTHER SPECIFIED TOLERANCES ON :			Shenzhen HamyWe Technology Co., Ltd.			
X = ± X.X = ± X.XX = ±						
ANGLES = ± HOLEDIA = ±						
SCALE :		UNIT : mm		THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF Shenzhen HamyWe Technology Co., Ltd. AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION		
DRAWN BY: Eason		CHECKED BY: Jake				
DESIGNED BY: Eason		APPROVED BY : Jake				
TITLE: WAG-F-LBG0-00-052 Specification			DOCUMENT NO.	ENS		PAGE REV.
						P0



UNLESS OTHER SPECIFIED TOLERANCES ON :

X = $\pm$ X.X = $\pm$ X.XX = $\pm$

ANGLES = $\pm$ HOLEDIA = $\pm$

SCALE : UNIT : mm

DRAWN BY: Eason CHECKED BY: Jake

DESIGNED BY: Eason APPROVED BY : Jake

TITLE: WAG-F-LBG0-00-052 Specification

Shenzhen HamyWe Technology Co., Ltd.

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF Shenzhen HamyWe Technology Co., Ltd. AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

DOCUMENT
NO.

ENS

PAGE REV.
P0

WAG-F-LTE12-00-237 Specification

1. Explanation of part number :

WAG F LTE12 00 237
(1) (2) (3) (4) (5)

(1) Product Type : Wireless Antenna

(2) Material: FPC

(3) Frequency : 617-960/1710-2690MHz

(4) Coaxial Cable Type : 00

(5) Suffix : 237

2. Storage Condition:

Temperature -40 to +85°C
Humidity 20 to 65 %RH
Recommended storage condition:

Store in room condition as listed below: Temperature -20°C~+45°C, Humidity 80% Max.

3. Operating Condition:

Temperature -40 to +85°C
Humidity 10 to 85 %RH

4. Electrical Specification :

Those specifications were specially defined for DIV model, and all characteristics were measured in the customer's machine.

4-1. Frequency Band:


Frequency Band	MHz
DIV	617-960/1710-2690MHz

4- 2.Impedance

50 ohm nominal

UNLESS OTHER SPECIFIED TOLERANCES ON : X = ± X.X = ± X.XX = ± ANGLES = ± HOLEDIA = ±		Shenzhen HamyWe Technology Co., Ltd.	
SCALE :	UNIT : mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF Shenzhen HamyWe Technology Co., Ltd. AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION	
DRAWN BY: Eason	CHECKED BY: Jake		
DESIGNED BY: Eason	APPROVED BY : Jake		
TITLE: WAG-F-LTE12-00-237 Specification		DOCUMENT NO.	PAGE REV.
		ENS	P0

4-3. VSWR:

Frequency Band	617	960	1710	2200	2690																														
2-3-1. Typical Value:	≤ 2.5	≤ 3.5	≤ 3.0	≤ 3.5	≤ 2.5																														
2-3-2 Measuring Method	1. A 50Ωcoaxial cable is connected to the fpcb antenna. Then this cable is connected to a network analyzer to measure the VSWR. 2. Keeping this jig away from metal at least 20 cm.																																		
2-3-3 Picture	▶ IT2 S22 SWR 1.000/ Ref 1.000 <table><tr><th>Point</th><th>Frequency</th><th>SWR</th></tr><tr><td>1</td><td>617.00000 MHz</td><td>6.5352</td></tr><tr><td>2</td><td>791.00000 MHz</td><td>4.9896</td></tr><tr><td>3</td><td>824.00000 MHz</td><td>3.8243</td></tr><tr><td>4</td><td>960.00000 MHz</td><td>6.0383</td></tr><tr><td>5</td><td>1.7100000 GHz</td><td>1.1349</td></tr><tr><td>6</td><td>2.1700000 GHz</td><td>1.9173</td></tr><tr><td>7</td><td>2.3000000 GHz</td><td>1.6942</td></tr><tr><td>8</td><td>2.4000000 GHz</td><td>1.1960</td></tr><tr><td>9</td><td>2.6900000 GHz</td><td>2.9048</td></tr></table>					Point	Frequency	SWR	1	617.00000 MHz	6.5352	2	791.00000 MHz	4.9896	3	824.00000 MHz	3.8243	4	960.00000 MHz	6.0383	5	1.7100000 GHz	1.1349	6	2.1700000 GHz	1.9173	7	2.3000000 GHz	1.6942	8	2.4000000 GHz	1.1960	9	2.6900000 GHz	2.9048
Point	Frequency	SWR																																	
1	617.00000 MHz	6.5352																																	
2	791.00000 MHz	4.9896																																	
3	824.00000 MHz	3.8243																																	
4	960.00000 MHz	6.0383																																	
5	1.7100000 GHz	1.1349																																	
6	2.1700000 GHz	1.9173																																	
7	2.3000000 GHz	1.6942																																	
8	2.4000000 GHz	1.1960																																	
9	2.6900000 GHz	2.9048																																	

4-4. Gain and Efficiency

4-4.1 Measure method

1. Using a low loss coaxial cable to link a standard handset jig
2. Fixed this handset jig on chamber's rotator plane
3. Linking jig into network analyzer port and using a probing horn antenna to collect data.
4. Using another standard gain horn antenna to calibrated those data

UNLESS OTHER SPECIFIED TOLERANCES ON :

X = $\pm$ X.X = $\pm$ X.XX = $\pm$

ANGLES = $\pm$ HOLEDIA = $\pm$

SCALE : UNIT : mm

DRAWN BY: Eason CHECKED BY: Jake

DESIGNED BY: Eason APPROVED BY : Jake

TITLE: WAG-F-LTE12-00-237 Specification

Shenzhen HamyWe Technology Co., Ltd.


THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF Shenzhen HamyWe Technology Co., Ltd.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

DOCUMENT
NO.

ENS

PAGE REV.
P0

4-4.2 Chamber definition



1. An anechoic chamber (8mx4mx3.5m) which satisfied far-field condition was applied to avoid multi-path effect
2. The quiet room region is 40cmx40cmx40cm at the center of rotator
3. The distance between DUT and standard antenna is 4.38 m
4. Probing antenna (9120D horn antenna) and standard gain horn antenna (BBHA9120 LPF 700MHz ~6GHz)

2-4.3 Gain and Efficiency

Fre	Effi(db)	Gain(dBi)	Effi(%)	Fre	Effi(db)	Gain(dBi)	Effi(%)
600	-7.17	-4.46	19.18	1710	-0.85	2.88	82.22
610	-6.54	-3.8	22.2	1740	-0.56	3.01	87.86
620	-6.08	-3.25	24.67	1770	-0.66	2.99	85.85
630	-5.65	-2.79	27.22	1800	-0.77	2.5	83.7
640	-5.06	-2.23	31.19	1830	-1	1.86	79.52
650	-4.65	-1.84	34.3	1860	-0.98	1.73	79.8
660	-4.19	-1.26	38.1	1890	-1.06	1.52	78.32
670	-3.91	-0.95	40.61	1920	-1.24	1.28	75.24
680	-3.45	-0.4	45.17	1950	-1.29	1.39	74.34
690	-2.94	0.1	50.78	1980	-1.77	0.81	66.56
700	-1.71	1.41	67.51	2010	-1.97	0.78	63.47

UNLESS OTHER SPECIFIED TOLERANCES ON :

X = ± X.X = ± X.XX = ±

ANGLES = ± HOLEDIA = ±

SCALE : UNIT : mm

DRAWN BY: Eason CHECKED BY: Jake

DESIGNED BY: Eason APPROVED BY : Jake

TITLE: WAG-F-LTE12-00-237 Specification

Shenzhen HamyWe Technology Co., Ltd.

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF Shenzhen HamyWe Technology Co., Ltd. AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

DOCUMENT
NO.



ENS

PAGE REV.
P0

710	-1.67	1.43	68	2040	-2.02	1.17	62.78
720	-1.11	2.17	77.39	2070	-2.18	0.95	60.53
730	-0.96	2.7	80.08	2100	-2.02	1.37	62.74
740	-1.14	2.74	76.97	2130	-2.18	1.09	60.58
750	-1.44	2.72	71.74	2160	-2.05	1.11	62.35
760	-2.39	2.02	57.71	2190	-1.82	1.32	65.79
770	-3.87	1.6	41.07	2220	-1.6	1.61	69.26
780	-5.08	1.25	31.03	2250	-2.4	0.87	57.56
790	-5.19	0.56	30.25	2280	-1.07	2.64	78.21
800	-4.54	0.09	35.16	2310	-0.95	2.85	80.27
810	-4.23	-0.51	37.79	2340	-0.8	3.22	83.17
820	-4.19	-1.06	38.11	2370	-0.8	3.43	83.12
830	-4.37	-1.55	36.59	2400	-2.07	2.04	62.09
840	-5.26	-2.17	29.78	2430	-1.88	2.1	64.94
850	-6.77	-3.05	21.05	2460	-1.58	2.19	69.43
860	-6.48	-3.27	22.47	2490	-1.77	1.96	66.59
870	-5.83	-2.82	26.15	2520	-0.9	2.81	81.24
880	-5.15	-1.83	30.55	2550	-1.12	2.22	77.24
890	-4.82	-1.39	32.99	2580	-1.52	1.74	70.52
900	-4.69	-1.25	34	2610	-1.7	1.37	67.58
910	-4.29	-0.71	37.28	2640	-2.16	0.79	60.85
920	-4.15	-0.49	38.43	2670	-2.47	0.95	56.59
930	-4.21	-0.37	37.92	2690	-3.28	0.7	46.98
940	-4.22	-0.24	37.88				
950	-4.13	0.11	38.64				
960	-4.28	0.06	37.31				

2-5.OTA And Data 3D

2-5.1 Data 3D



UNLESS OTHER SPECIFIED TOLERANCES ON :

X = ± X.X = ± X.XX = ±

ANGLES = ± HOLEDIA = ±

SCALE : UNIT : mm

DRAWN BY: Eason CHECKED BY: Jake

DESIGNED BY: Eason APPROVED BY : Jake

TITLE: WAG-F-LTE12-00-237 Specification

Shenzhen HamyWe Technology Co., Ltd.


THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF Shenzhen HamyWe Technology Co., Ltd. AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

DOCUMENT
NO.


ENS

PAGE REV.
P0


640 MHz




730 MHz




800 MHz




960 MHz



1740 MHz



1980 MHz



2100 MHz

2310 MHz

UNLESS OTHER SPECIFIED TOLERANCES ON :

X = $\pm$ X.X = $\pm$ X.XX = $\pm$

ANGLES = $\pm$ HOLEDIA = $\pm$

SCALE : UNIT : mm

DRAWN BY: Eason CHECKED BY: Jake

DESIGNED BY: Eason APPROVED BY : Jake

TITLE: WAG-F-LTE12-00-237 Specification


Shenzhen HamyWe Technology Co., Ltd.

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF Shenzhen HamyWe Technology Co., Ltd. AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

DOCUMENT
NO.

ENS

PAGE REV.
P0



2580 MHz

5.Mechanical Specification:

UNLESS OTHER SPECIFIED TOLERANCES ON :		Shenzhen HamyWe Technology Co., Ltd.	
X = ± X.X = ± X.XX = ±			
ANGLES = ±			

WAG-F-LTE12-00-236 Specification

1. Explanation of part number :

WAG F LTE12 00 236
(1) (2) (3) (4) (5)

- (1) Product Type : Wireless Antenna
- (2) Material: FPC
- (3) Frequency : 617-960/1710-2690MHz
- (4) Coaxial Cable Type : 00
- (5) Suffix : 236

2. Storage Condition:

Temperature -40 to +85°C
Humidity 20 to 65 %RH
Recommended storage condition:

Store in room condition as listed below: Temperature -20°C~+45°C, Humidity 80% Max.

3. Operating Condition:

Temperature -40 to +85°C
Humidity 10 to 85 %RH

4. Electrical Specification :

Those specifications were specially defined for Main model, and all characteristics were measured in the customer's machine.

4-1. Frequency Band:


Frequency Band	MHz
Main	617-960/1710-2690MHz

4- 2.Impedance

50 ohm nominal

UNLESS OTHER SPECIFIED TOLERANCES ON : X = ± X.X = ± X.XX = ± ANGLES = ± HOLEDIA = ±		Shenzhen HamyWe Technology Co., Ltd.	
SCALE :	UNIT : mm		
DRAWN BY: Eason	CHECKED BY: Jake	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF Shenzhen HamyWe Technology Co., Ltd. AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION	
DESIGNED BY: Eason	APPROVED BY : Jake		
TITLE: WAG-F-LTE12-00-236 Specification		DOCUMENT NO.	PAGE REV.
		ENS	P0

4-3. VSWR:

Frequency Band	617	960	1805	2200	2690
2-3-1. Typical Value:	≤ 8	≤ -7	≤ 4	≤ 5	≤ 4
2-3-2 Measuring Method	1. A 50Ωcoaxial cable is connected to the fpcb antenna. Then this cable is connected to a network analyzer to measure the VSWR. 2. Keeping this jig away from metal at least 20 cm.				
2-3-3 Picture					

4-4. Gain and Efficiency

4-4.1 Measure method

1. Using a low loss coaxial cable to link a standard handset jig
2. Fixed this handset jig on chamber's rotator plane
3. Linking jig into network analyzer port and using a probing horn antenna to collect data.
4. Using another standard gain horn antenna to calibrated those data

UNLESS OTHER SPECIFIED TOLERANCES ON :

X = $\pm$ X.X = $\pm$ X.XX = $\pm$

ANGLES = $\pm$ HOLEDIA = $\pm$

SCALE : UNIT : mm

DRAWN BY: Eason CHECKED BY: Jake

DESIGNED BY: Eason APPROVED BY : Jake

TITLE: WAG-F-LTE12-00-236 Specification

Shenzhen HamyWe Technology Co., Ltd.


THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF Shenzhen HamyWe Technology Co., Ltd. AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

DOCUMENT
NO.

ENS

PAGE REV.
P0

4-4.2 Chamber definition



1. An anechoic chamber (8mx4mx3.5m) which satisfied far-field condition was applied to avoid multi-path effect
2. The quiet room region is 40cmx40cmx40cm at the center of rotator
3. The distance between DUT and standard antenna is 4.38 m
4. Probing antenna (9120D horn antenna) and standard gain horn antenna (BBHA9120 LPF 700MHz ~6GHz)

2-4.3 Gain and Efficiency

Fre	Effi(db)	Gain(dBi)	Effi(%)	Fre	Effi(db)	Gain(dBi)	Effi(%)
600	-11.28	-8.94	7.45	1710	-3.33	0.36	46.43
610	-10.49	-8.07	8.93	1740	-2.05	2.31	62.43
620	-9.68	-7.06	10.77	1770	-1.55	3.12	69.95
630	-8.79	-6	13.22	1800	-1.27	3.12	74.68
640	-8.06	-5.08	15.63	1830	-1.01	3.13	79.2
650	-7.44	-4.32	18.03	1860	-0.65	3.7	86.17
660	-7.3	-3.91	18.63	1890	-0.78	3.69	83.55
670	-8.19	-4.45	15.16	1920	-0.99	3.25	79.6
680	-10.23	-5.75	9.49	1950	-1.07	3.07	78.13
690	-11.95	-7.34	6.39	1980	-1.69	2.46	67.78

UNLESS OTHER SPECIFIED TOLERANCES ON :

X = ± X.X = ± X.XX = ±

ANGLES = ± HOLEDIA = ±

SCALE : UNIT : mm

DRAWN BY: Eason CHECKED BY: Jake

DESIGNED BY: Eason APPROVED BY : Jake

TITLE: WAG-F-LTE12-00-236 Specification

Shenzhen HamyWe Technology Co., Ltd.

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF Shenzhen HamyWe Technology Co., Ltd. AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

DOCUMENT
NO.

ENS

PAGE REV.
P0

700	-9.97	-6.8	10.07	2010	-2.15	1.91	60.98
710	-7.75	-5.22	16.8	2040	-2.39	1.68	57.68
720	-4.87	-2.22	32.56	2070	-2.74	1.49	53.19
730	-3.18	-0.14	48.12	2100	-2.99	1.11	50.23
740	-2.16	0.47	60.75	2130	-3.35	0.5	46.22
750	-1.23	1.27	75.26	2160	-3.55	0.33	44.2
760	-0.7	1.66	85.04	2190	-3.41	0.53	45.65
770	-0.53	1.86	88.49	2220	-3.17	0.34	48.22
780	-0.68	1.78	85.58	2250	-3.95	-0.69	40.23
790	-0.94	1.62	80.62	2280	-2.67	0.51	54.06
800	-1.19	1.35	76.01	2310	-2.68	0.3	53.92
810	-1.75	0.89	66.8	2340	-2.35	0.21	58.18
820	-2.52	0.39	56.01	2370	-2.14	0.17	61.13
830	-3.63	-0.32	43.36	2400	-3.33	-0.89	46.46
840	-5.57	-3	27.71	2430	-2.82	-0.18	52.19
850	-5	-2.03	31.62	2460	-2.41	0.31	57.42
860	-4.67	-2.33	34.15	2490	-2.19	1.01	60.4
870	-4.98	-2.94	31.77	2520	-1.18	2.65	76.23
880	-4.97	-2.88	31.84	2550	-1.32	2.85	73.77
890	-5.15	-2.93	30.56	2580	-1.47	2.73	71.34
900	-5.39	-3.26	28.88	2610	-1.53	3.1	70.23
910	-5.29	-3.12	29.56	2640	-1.8	2.72	66.01
920	-5.35	-3.16	29.19	2670	-2.06	2.05	62.2
930	-5.5	-3.27	28.2	2690	-2.88	0.98	51.58
940	-5.6	-3.38	27.54				
950	-5.46	-3.16	28.44				
960	-5.54	-2.92	27.93				

2-5.OTA And Data 3D

2-5.1 OTA And Boom/Switch

1、OTA

Band	Channel Bandwidth (MHz)	Channel	FS		Band	Channel Bandwidth (MHz)	Channel	FS	
			TRP	TIS				TRP	TIS
Band 2	10M	18650	18.37	-96.27	Band 14	10M			
		18900	18.4	-96.76			23330	21.75	-96.96
		19150	18.15	-97.74					
Band4	10M	20000	18.15	-95.72	Band 25	5M	26065	17.89	-97.68
		20175	18.52	-96.99			26365	18.02	-97.63
		20350	19.14	-96.2			26665	17.71	-98.03

UNLESS OTHER SPECIFIED TOLERANCES ON :

X = ± X.X = ± X.XX = ±

ANGLES = ± HOLEDIA = ±

SCALE : UNIT : mm

DRAWN BY: Eason CHECKED BY: Jake

DESIGNED BY: Eason APPROVED BY : Jake

Shenzhen HamyWe Technology Co., Ltd.

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF Shenzhen HamyWe Technology Co., Ltd. AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE: WAG-F-LTE12-00-236 Specification


DOCUMENT NO.

ENS


PAGE REV.
P0

Band66	10M	132022	18.58	-95.66	Band 26	5M	26715	20.76	-97.66
		132322	19.56	-96.42			26865	19.75	-97.04
		132622	19.64	-96.43			27015	18.93	-97.57
Band5	10M	20450	19.7	-94.9	Band30	10M			
		20525	19.01	-95.34			27710	18.36	-98.1
		20600	18.2	-95.03					
Band 7	10M	20850	17.97	-97.74	Band71	10M	133172	18.99	-95.83
		21100	18.45	-97.56			133297	20.23	-96.25
		21350	18.48	-97.33			133422	20.58	-95.9
Band 12	5M	23035	21.02	-99.27	Band 41	20M	40340	18.36	-93.31
		23095	21.47	-99.15			40620	18.54	-92.67
		23155	21.25	-99.43			41140	18.37	-93.6
Band 13	10M								
		23230	21.41	-94.47					


2-5.2 Data 3D




640 MHz



730 MHz



800 MHz



960 MHz

UNLESS OTHER SPECIFIED TOLERANCES ON :

X = ± X.X = ± X.XX = ±

ANGLES = ± HOLEDIA = ±

SCALE : UNIT : mm

DRAWN BY: Eason CHECKED BY: Jake


DESIGNED BY: Eason APPROVED BY : Jake

TITLE: WAG-F-LTE12-00-236 Specification


Shenzhen HamyWe Technology Co., Ltd.

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF Shenzhen HamyWe Technology Co., Ltd. AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION


DOCUMENT NO.	ENS	PAGE REV.
		P0




1740 MHz




1980 MHz



2100 MHz



2310 MHz



2580 MHz

5.Mechanical Specification:

UNLESS OTHER SPECIFIED TOLERANCES ON :

X = $\pm$ X.X = $\pm$ X.XX = $\pm$

ANGLES = $\pm$ HOLEDIA = $\pm$

SCALE : UNIT : mm

DRAWN BY: Eason CHECKED BY: Jake

DESIGNED BY: Eason APPROVED BY : Jake

TITLE: WAG-F-LTE12-00-236 Specification


Shenzhen HamyWe Technology Co., Ltd.

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF Shenzhen HamyWe Technology Co., Ltd. AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

DOCUMENT
NO.

ENS

PAGE REV.
P0



UNLESS OTHER SPECIFIED TOLERANCES ON :		Shenzhen HamyWe Technology Co., Ltd.	
X = ±	X.X = ±		
ANGLES = ±		HOLEDIA = ±	
SCALE :	UNIT : mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF Shenzhen HamyWe Technology Co., Ltd. AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION	
DRAWN BY: Eason	CHECKED BY: Jake		
DESIGNED BY: Eason	APPROVED BY : Jake		
TITLE: WAG-F-LTE12-00-236 Specification		DOCUMENT NO.	PAGE REV.
		ENS	P0