



P	O	N	M	L	K	J	I	H	G	F	E	D	C	B	A
DEG.			✓												
DIV.	A	B	C	D	ANGLE										
0~5	±0.02	±0.05	±0.1	±0.2	0~30°	±0.1°									
5~10	±0.05	±0.1	±0.15	±0.5	31°~60°	±0.3°									
10~50	±0.1	±0.15	±0.2	±0.5	61°~90°	±0.5°									
50~500	±0.15	±0.2	±0.25	±0.5											
500~	±0.15%	±0.2%	±0.25%	±1.0											




REV

REV




Page 9

Page 10




Page 11

Page 12




Page 1

Page 2




Page 3

Page 4




Page 5

Page 6




Page 7

Page 8




Page 13

Page 14




Page 15

Page 16




Page 17

Page 18




Page 19

Page 20




Page 21

Page 22



Page 23

Page 24



Page 25

Page 26

未注公差：		制图	审核	批准	产品名称	ORVIBO OLOCK 说明书	材料	
≤10mm	±0.05mm	周宇婷			产品料号	3.06.010817	版次	V0.1
≤50mm	±0.1mm				<div> <div>           深圳市欧瑞博科技股份有限公司            SHENZHEN ORVIBO TECH CO.,LTD.         </div> </div>			
>50mm	±0.2mm							
单位	mm	日期	14-JAN-22		<div> <div>           深圳市欧瑞博科技股份有限公司            SHENZHEN ORVIBO TECH CO.,LTD.         </div> </div>			