

Test Report

Applicant : QINGDAO KINGFORCE INTELLIGENT TECHNOLOGY CO.,LTD
Address : 69, GUANGSHENG ROAD QINGDAO, CHINA
Product Name : Smart Lock
Brand Mark : Noqiz
Model : M19F
Series model : M19/ M15/ M22/ M12/ M31/ M12-HH/ M30/ M12-F/ M12-H/ M16
Report Number : BLA-EMC-202504-A8302
FCC ID : 2AWGO-M19F
Date of Receipt : Apr.22, 2025
Date of Test : Apr.24, 2025 to Apr.29, 2025
Test Standard : 47 CFR Part 15, Subpart C 15.247
Test Result : Pass

Compiled by: *charlie*

Review by: *Xavier*

Approved by: *Blue.Zheng*

Issued Date: May 06, 2025



BlueAsia of Technical Services(Shenzhen) Co.,Ltd.

Address: Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District,
Shenzhen, Guangdong Province, China



The test report is effective only with both signature and specialized stamp and The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full. The results described in this report do not represent the quality or characteristics of the sampled batch, nor do they represent any similar or identical products that are not explicitly stated.

Table of Contents

1 General information	5
1.1 General information	5
1.2 General description of EUT	5
2 Test summary	6
3 Test Configuration	7
3.1 Test mode	7
3.2 Operation Frequency each of channel	8
3.3 Test channel	8
3.4 Configuration diagram of EUT	9
3.5 Auxiliary equipment	9
3.6 Test environment	9
4 Laboratory information	10
4.1 Laboratory and accreditations	10
4.2 Measurement uncertainty	10
5 Test equipment	11
6 Test result	13
6.1 Antenna requirement	13
6.2 Conducted peak output Power	14
6.3 Minimum 6dB bandwidth	15
6.4 Power spectrum density	16
6.5 Conducted Band Edges Measurement	17
6.6 Conducted spurious emissions	19
6.7 Radiated spurious emissions	21
6.8 Radiated emissions which fall in the restricted bands	32
7 Appendix A	39
7.1 Maximum PK Conducted Output Power	39
7.2 -6dB Bandwidth	41
7.3 Occupied Channel Bandwidth	43
7.4 Maximum Power Spectral Density Level	45
7.5 Band Edge	47

7.6 Conducted RF Spurious Emission	50
Appendix B: photographs of test setup	54
Appendix C: photographs of EUT	55

BlueAsia

Revise Record

Version No.	Date	Description
01	May 06,2025	Original

BlueAsia

1 General information

1.1 General information

Applicant	QINGDAO KINGFORCE INTELLIGENT TECHNOLOGY CO.,LTD
Address	69, GUANGSHENG ROAD QINGDAO, CHINA
Manufacturer	QINGDAO KINGFORCE INTELLIGENT TECHNOLOGY CO.,LTD
Address	69, GUANGSHENG ROAD QINGDAO, CHINA
Factory	QINGDAO KINGFORCE INTELLIGENT TECHNOLOGY CO.,LTD
Address	69, GUANGSHENG ROAD QINGDAO, CHINA

1.2 General description of EUT

Product Name	Smart Lock
Model No.	M19F
Series model	M19/ M15/ M22/ M12/ M31/ M12-HH/ M30/ M12-F/ M12-H/ M16
Differences of Series model	The above models are identical in PCB layout,internal structure and components,only model No.and color is different.
Operation Frequency	2402MHz-2480MHz
Modulation Type	GFSK
Channel Spacing:	2MHz
Number of Channels	40
Antenna Type	PCB antenna
Antenna Gain	3.1dBi(Provided by customer)
Power supply or adapter information	DC6V(dry accumulator1.5V*4)
Hardware Version	M19FBZB
Software Version	V1.0
Engineer sample no	BLA-EMC-202504-A83

Note: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

2 Test summary

No.	Test item	FCC Part Section(s)	Test Method(Clause)	Result
1	Antenna Requirement	§15.203	N/A	Pass
2	Conducted Emissions at AC Power Line (150kHz-30MHz)	§15.207	ANSI C63.10-2013 Clause 6.2	N/A
3	Conducted Peak Output Power	§15.247(b)(3)	ANSI C63.10-2013 Clause 7.8.5	Pass
4	Minimum 6dB Bandwidth	§15.247a(2)	ANSI C63.10-2013 Clause 11.8.1	Pass
5	Power Spectrum Density	§15.247(d)	ANSI C63.10-2013 Clause 11.10.2	Pass
6	Conducted Band Edges Measurement	§15.247(d)	ANSI C63.10-2013 Clause 11.13	Pass
7	Conducted Spurious Emissions	§15.247(d)	ANSI C63.10-2013 Clause 11.11	Pass
8	Radiated Spurious Emissions	§15.209 §15.247(d)	ANSI C63.10-2013 Clause 6.4,6.5,6.6	Pass
9	Radiated Emissions which fall in the restricted bands	§15.209 §15.247(d)	ANSI C63.10-2013 Clause 11.12	Pass

N/A: Not Applicable

3 Test Configuration

3.1 Test mode


Test Mode <small>Note 1</small>	Description
TX	Keep the EUT in continuously transmitting with modulation mode.
RX	Keep the EUT in receiving mode
TX Low channel	Keep the EUT in continuously transmitting mode in low channel
TX middle channel	Keep the EUT in continuously transmitting mode in middle channel
TX high channel	Keep the EUT in continuously transmitting mode in high channel

Note 1: The EUT was configured to measure its highest possible emission and/or immunity level. The test modes were adapted according to the operation manual for use; the EUT was operated in the engineering mode Note 2 to fix the TX or Rx frequency that was for the purpose of the measurements.

Note 2: Special software is used. The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.

Power level setup in software			
Test Software Name	BK32xx RF Test - V1.8.2_en(Mar 14 2019)		
Mode	Channel	Frequency (MHz)	Soft Set
GFSK	CH0	2402	TX level : 2
	CH20	2442	
	CH39	2480	

Run Software



3.2 Operation Frequency each of channel


Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
...
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz

3.3 Test channel

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2442MHz
The Highest channel	2480MHz


3.4 Configuration diagram of EUT

Radiated emission:



Note: see test photographs attached in APPENDIX A for the actual connections between Product and support equipment.

RF Test:



Support equipment:

Name	Device type	Brand	Mode	Series No	Remark
(1)	PC	lenovo	E460C	N/A	N/A
(2)	Fixed frequency board	N/A	N/A	N/A	N/A

3.5 Auxiliary equipment

Device Type	Manufacturer	Model Name	Serial No.	Remark
PC	lenovo	E460C	N/A	From lab (No.BLA-ZC-BS-2022005)
Note: -- mean no any auxiliary device during testing.				

3.6 Test environment

Environment	Temperature	Voltage
Normal	25°C	DC 6V

4 Laboratory information

4.1 Laboratory and accreditations

The test facility is recognized, certified, or accredited by the following organizations:

Company name:	BlueAsia of Technical Services(Shenzhen) Co., Ltd.
Address:	Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
CNAS accredited No.:	L9788
A2LA Cert. No.:	5071.01
FCC Designation No.:	CN1252
ISED CAB identifier No.:	CN0028
Telephone:	+86-755-28682673
FAX:	+86-755-28682673

4.2 Measurement uncertainty

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

Parameter	Expanded Uncertainty
Radiated Emission(9kHz-30MHz)	±4.34dB
Radiated Emission(30Mz-1000MHz)	±4.24dB
Radiated Emission(1GHz-18GHz)	±4.68dB
AC Power Line Conducted Emission(150kHz-30MHz)	±3.45dB
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±1.5 dB
Power Spectral Density, conducted	±3.0 dB
Unwanted Emissions, conducted	±3.0 dB
Temperature	±3 °C
Supply voltages	±3 %
Time	±5 %

5 Test equipment

Radiated Spurious Emissions (Below 1GHz)

Equipment	Name	Model	Manufacture	S/N	Cal. Date	Due. Date
BLA-EMC-002-01	Anechoic chamber	9*6*6 chamber	SKET	N/A	2024/3/27	2027/3/26
BLA-EMC-002-02	Control room	966 control room	SKET	N/A	2024/3/27	2027/3/26
BLA-EMC-009	EMI receiver	ESR7	R&S	101199	2024/08/08	2025/08/07
BLA-EMC-043	Loop antenna	FMZB1519B	Schwarzbeck	00102	2024/06/29	2026/06/28
BLA-EMC-065	Broadband antenna	VULB9168	Schwarzbeck	01065P	2024/06/29	2026/06/27
BLA-XC-01	Coaxial Cable	N/A	BlueAsia	V01	N/A	N/A
BLA-XC-02	Coaxial Cable	N/A	BlueAsia	V02	N/A	N/A

Radiated Spurious Emissions (Above 1GHz)

Equipment	Name	Model	Manufacture	S/N	Cal. Date	Due. Date
BLA-EMC-001-01	Anechoic chamber	9*6*6 chamber	SKET	N/A	2023/11/16	2026/11/15
BLA-EMC-001-02	Control Room	966 control room	SKET	N/A	2023/11/16	2025/11/15
BLA-EMC-008	Spectrum	FSP40	R&S	100817	2024/08/08	2025/08/07
BLA-EMC-012	Broadband antenna	VULB9168	Schwarzbeck	00836 P:00227	2022/10/12	2025/10/11
BLA-EMC-013	Horn Antenna	BBHA9120D	Schwarzbeck	01892	2024/06/29	2026/06/28
BLA-EMC-014	Amplifier	PA_000318G-45	SKET	PA201804 3003	2024/08/08	2025/08/07
BLA-EMC-046	Filter bank	2.4G/5G Filter bank	SKET	N/A	2024/06/28	2025/06/27
BLA-EMC-061	Receiver	ESPI7	R&S	101477	2024/06/28	2025/06/27
BLA-EMC-066	Amplifier	LNPA_30M01 G-30	SKET	SK202106 0801	2024/06/28	2025/06/27
BLA-EMC-086	Amplifier	LNPA_18G40 G-50dB	SKET	SK202207 1301	2024/06/28	2025/06/27
BLA-EMC-087	Horn Antenna	BBHA 9170	Schwarzbeck	1106	2024/06/29	2026/06/28
BLA-XC-03	Coaxial Cable	N/A	BlueAsia	V03	N/A	N/A
BLA-XC-04	Coaxial Cable	N/A	BlueAsia	V04	N/A	N/A

RF conducted

Equipment	Name	Model	Manufacture	S/N	Cal. Date	Due. Date
BLA-EMC-003-003	Shield room	5*3*3	SKET	N/A	2023/11/16	2025/11/15
BLA-EMC-016	Signal Generator	N5182A	Agilent	MY52420567	2024/06/28	2025/06/27
BLA-EMC-038	Spectrum	N9020A	Agilent	MY49100060	2024/08/08	2025/08/07
BLA-EMC-042	Power sensor	RPR3006W	DARE	14I00889SN042	2024/08/08	2025/08/07
BLA-EMC-044	Radio communication tester	CMW500	R&S	132429	2024/08/08	2025/08/07
BLA-EMC-064	Signal Generator	N5182B	KEYSIGHT	MY58108892	2024/06/28	2025/06/27
BLA-EMC-079	Spectrum	N9020A	Agilent	MY54420161	2024/08/08	2025/08/07
BLA-EMC-088	Audio Analyzer	ATS-1	Audio Precision	ATS141094	2024/06/28	2025/06/27

Test Software Record

Software No.	Software Name	Manufacture	Software version	Test site
BLA-EMC-S001	EZ-EMC	EZ	EEMC-3A1+	RE
BLA-EMC-S002	EZ-EMC	EZ	EEMC-3A1+	RE
BLA-EMC-S010	MTS 8310	MW	2.0.0.0	RF

BlueAsia

6 Test result

6.1 Antenna requirement


Test Standard	47 CFR Part 15, Subpart C 15.203
Test Method	N/A

6.1.1 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of a so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT antenna:

The antenna is internal PCB Antenna The best case gain of the antenna is 3.1dBi




6.2 Conducted peak output Power

Test Standard	47 CFR Part 15, Subpart C 15.247(b)(3)
Test Method	ANSI C63.10-2013 Clause 7.8.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.2.1 Limit

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

6.2.2 Test setup



6.2.3 Test data

Note: PK power sensor is used to read PK Conducted power power directly

Pass: Please refer to appendix A for details

BlueAsia of Technical Services (Shenzhen) Co.,Ltd.

Tel: +86-755-23059481

Email: marketing@cblueasia.com www.cblueasia.com

Version:v1.3


6.3 Minimum 6dB bandwidth

Test Standard	47 CFR Part 15, Subpart C 15.247a(2)
Test Method	ANSI C63.10-2013 Clause 11.8.1
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.3.1 Limit

≥500 kHz

6.3.2 Test setup



6.3.3 Test data

Pass: Please refer to appendix A for details


6.4 Power spectrum density

Test Standard	47 CFR Part 15, Subpart C 15.247(d)
Test Method	ANSI C63.10-2013 Clause 11.10.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.4.1 Limit

≤8dBm in any 3 kHz band during any time interval of continuous transmission

6.4.2 Test setup



6.4.3 Test data

Pass: Please refer to appendix A for details

6.5 Conducted Band Edges Measurement

Test Standard	47 CFR Part 15, Subpart C 15.247(d)
Test Method	ANSI C63.10-2013 Clause 11.13
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.5.1 Limit


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20dB.

Attenuation below the general limits specified in §15.209(a) is not required.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

6.5.2 Test setup



6.5.3 Test data

Pass: Please refer to appendix A for details

BlueAsia

6.6 Conducted spurious emissions

Test Standard	47 CFR Part 15, Subpart C 15.247(d)
Test Method	ANSI C63.10-2013 Clause 11.11
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX

6.6.1 Limit


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20dB.

Attenuation below the general limits specified in §15.209(a) is not required.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

6.6.2 Test setup



6.6.3 Test data

Pass: Please refer to appendix A for details

BlueAsia

6.7 Radiated spurious emissions

Test Standard	47 CFR Part 15, Subpart C 15.247(d)
Test Method	ANSI C63.10-2013 Clause 6.4,6.5,6.6
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX


6.7.1 Limit

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

6.7.2 Test setup


Below 1GHz:



30MHz-1GHz:



Above 1GHz:



6.7.3 Procedure

- a) For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c) The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d) The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f) The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g) If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h) Test the EUT in the lowest channel, the middle channel, the highest channel.
- i) The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j) Repeat above procedures until all frequencies measured was complete.

Note 1: Scan from 9 kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. Fundamental frequency is blocked by filter, and only spurious emission is shown.

Note 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.


Note 3: The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

$$\text{Level (dBuV)} = \text{Reading (dBuV)} + \text{Factor (dB/m)}$$

6.7.4 Test data


Below 1GHz

[Test mode: TX]; [Polarity: Horizontal]



Test Result: Pass

[Test mode: TX]; [Polarity: Vertical]



Site
Limit: FCC Part15 Class B
EUT: Smart Lock
M/N: M19F
Mode: BLE TX Mode
Note:

Polarization: *Vertical*

Temperature: (C)

Power:

Humidity: %RH

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	38.4809	1.97	19.24	21.21	40.00	-18.79	QP	P	
2 *	62.2128	7.27	18.16	25.43	40.00	-14.57	QP	P	
3	162.0414	3.20	20.33	23.53	43.50	-19.97	QP	P	
4	196.5098	6.57	16.48	23.05	43.50	-20.45	QP	P	
5	444.8514	-0.08	24.33	24.25	46.00	-21.75	QP	P	
6	729.3583	1.65	29.00	30.65	46.00	-15.35	QP	P	

Test Result: Pass

BlueAsia of Technical Services (Shenzhen) Co.,Ltd.


Tel: +86-755-23059481

Email: marketing@cblueasia.com www.cblueasia.com

Version:v1.3

Above 1GHz:

[Test mode: TX low channel]; [Polarity: Horizontal]



Site: Polarization: **Horizontal** Temperature: (C)
Limit: FCC Part15 (PK) Power: Humidity: %RH
EUT: Smart Lock
M/N: M19F
Mode: BLE-TX-2402
Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4804.000	39.21	4.02	43.23	74.00	-30.77	peak	
2		6957.250	40.07	10.55	50.62	74.00	-23.38	peak	
3		8038.250	39.17	12.85	52.02	74.00	-21.98	peak	
4		9753.750	37.39	15.11	52.50	74.00	-21.50	peak	
5		10505.75	37.46	15.01	52.47	74.00	-21.53	peak	
6	*	11539.75	36.54	16.05	52.59	74.00	-21.41	peak	

Test Result: Pass


BlueAsia of Technical Services (Shenzhen) Co.,Ltd.

Tel: +86-755-23059481

Email: marketing@cblueasia.com www.cblueasia.com

Version:v1.3

[**Test mode: TX low channel**]; [**Polarity: Vertical**]

Radiated Emission Measurement


Site: Polarization: **Vertical** Temperature: (C)
 Limit: FCC Part15 (PK) Power: Humidity: %RH
 EUT: Smart Lock
 M/N: M19F
 Mode: BLE-TX-2402
 Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4804.000	39.07	4.02	43.09	74.00	-30.91	peak	
2		7439.000	39.84	11.96	51.80	74.00	-22.20	peak	
3		8461.250	39.18	12.93	52.11	74.00	-21.89	peak	
4		9377.750	38.56	14.32	52.88	74.00	-21.12	peak	
5		10635.00	38.22	14.55	52.77	74.00	-21.23	peak	
6 *		11939.25	37.73	15.39	53.12	74.00	-20.88	peak	

Test Result: Pass


[Test mode: TX middle channel]; [Polarity: Horizontal]

Radiated Emission Measurement

Project No.: RE

Data :#9

2025/4/29



Site: Limit: FCC Part15 (PK) EUT: Smart Lock M/N: M19F Mode: BLE-TX-2442 Note: Polarization: **Horizontal** Power: Temperature: (C) Humidity: %RH

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over		
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4884.000	40.26	4.44	44.70	74.00	-29.30	peak	
2		7321.500	40.95	11.04	51.99	74.00	-22.01	peak	
3	*	9319.000	38.26	14.52	52.78	74.00	-21.22	peak	
4		10447.00	37.02	14.90	51.92	74.00	-22.08	peak	
5		11340.00	37.62	14.73	52.35	74.00	-21.65	peak	
6		12033.25	36.67	15.66	52.33	74.00	-21.67	peak	

Test Result: Pass

BlueAsia of Technical Services (Shenzhen) Co.,Ltd.

Tel: +86-755-23059481

Email: marketing@cblueasia.com www.cblueasia.com

Version:v1.3

[Test mode: TX middle channel]; [Polarity: Vertical]

Radiated Emission Measurement

Project No.: RE

Data #10

2025/4/29



Site: Limit: FCC Part15 (PK) EUT: Smart Lock M/N: M19F Mode: BLE-TX-2442 Note: Polarization: **Vertical** Power: Temperature: (C) Humidity: %RH

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over		
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4884.000	40.64	4.44	45.08	74.00	-28.92	peak	
2	*	7321.500	41.30	11.04	52.34	74.00	-21.66	peak	
3		8484.750	38.86	12.87	51.73	74.00	-22.27	peak	
4		9354.250	37.60	14.65	52.25	74.00	-21.75	peak	
5		10247.25	37.40	14.59	51.99	74.00	-22.01	peak	
6		11363.50	37.31	15.00	52.31	74.00	-21.69	peak	

Test Result: Pass


BlueAsia of Technical Services (Shenzhen) Co.,Ltd.

Tel: +86-755-23059481

Email: marketing@cblueasia.com www.cblueasia.com

Version:v1.3

[Test mode: TX High channel]; [Polarity: Horizontal]



Site: Polarization: **Horizontal** Temperature: (C)
Limit: FCC Part15 (PK) Power: Humidity: %RH
EUT: Smart Lock
M/N: M19F
Mode: BLE-TX-2480
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over							
							MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4960.000	37.85	4.90	42.75	74.00	-31.25	peak						
2		7192.250	39.03	11.31	50.34	74.00	-23.66	peak						
3		8672.750	38.49	13.15	51.64	74.00	-22.36	peak						
4		10141.50	37.22	14.47	51.69	74.00	-22.31	peak						
5	*	11387.00	36.80	15.27	52.07	74.00	-21.93	peak						
6		11974.50	36.21	15.65	51.86	74.00	-22.14	peak						

Test Result: Pass

BlueAsia of Technical Services (Shenzhen) Co.,Ltd.

Tel: +86-755-23059481

Email: marketing@cblueasia.com www.cblueasia.com

Version:v1.3

[Test mode: TX High channel]; [Polarity: Vertical]

Radiated Emission Measurement

Project No.: RE

Data #12

2025/4/29



Site Polarization: **Vertical** Temperature: (C)

Limit: FCC Part15 (PK) Power: Humidity: %RH

EUT: Smart Lock

M/N: M19F

Mode: BLE-TX-2480

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over		
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4960.000	39.18	4.90	44.08	74.00	-29.92	peak	
2		7145.250	39.36	11.50	50.86	74.00	-23.14	peak	
3		8473.000	38.76	12.90	51.66	74.00	-22.34	peak	
4	*	9319.000	38.11	14.52	52.63	74.00	-21.37	peak	
5		10893.50	37.93	14.32	52.25	74.00	-21.75	peak	
6		11998.00	36.66	15.84	52.50	74.00	-21.50	peak	

Test Result: Pass

When scanning in the range of 1GHz~ 40GHz and the interference above 12.75GHz is very small, it is a low noise signal. The point shown in the figure above is the highest emission that can be found during the test, so only the above point is shown. The fundamental frequency is blocked by the filter. Only stray emission.

6.8 Radiated emissions which fall in the restricted bands

Test Standard	47 CFR Part 15, Subpart C 15.247(d)
Test Method	ANSI C63.10-2013 Clause 6.12
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX


6.8.1 Limit

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

6.8.2 Test setup


Below 1GHz:



30MHz-1GHz:



Above 1GHz:



6.8.3 Procedure


- a) For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c) The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d) The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f) The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g) If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h) Test the EUT in the lowest channel, the middle channel, the highest channel.
- i) The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j) Repeat above procedures until all frequencies measured was complete.

Note 1: Level (dBuV) = Reading (dBuV) + Factor (dB/m)

Note 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

6.8.4 Test data

[Test mode: TX low channel]; [Polarity: Horizontal]



Site	Polarization: Horizontal	Temperature: (C)
Limit: FCC Part15 (PK)	Power:	Humidity: %RH
EUT: Smart Lock		
M/N: M19F		
Mode: BLE-TX-2402		
Note:		

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment		Detector	Comment
1		2310.000	43.30	-2.87	40.43	74.00	-33.57	peak
2	*	2390.000	43.77	-2.44	41.33	74.00	-32.67	peak

Test Result: Pass

[**Test mode:TX low channel**]; [**Polarity: Vertical**]


Radiated Emission Measurement

Project No.: RE

Data #:4

2025/4/29

107.0 dBuV/m


Site Polarization: **Vertical** Temperature: (C)

Limit: FCC Part15 (PK) Power: Humidity: %RH

EUT: Smart Lock

M/N: M19F


Mode: BLE-TX-2402

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
			MHz	dBuV	dB	dBuV/m	dB		
1		2310.000	42.71	-2.87	39.84	74.00	-34.16	peak	
2	*	2390.000	43.26	-2.44	40.82	74.00	-33.18	peak	

Test Result: Pass

[Test mode: TX High channel]; [Polarity: Horizontal]




Site: Polarization: **Horizontal** Temperature: (C)
Limit: FCC Part15 (PK) Power: Humidity: %RH
EUT: Smart Lock
M/N: M19F
Mode: BLE-TX-2480
Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment		Detector	Comment
1	*	2483.500	44.87	-2.91	41.96	74.00	-32.04	peak
2		2500.000	43.40	-3.00	40.40	74.00	-33.60	peak

Test Result: Pass

[Test mode:TX High channel]; [Polarity: Vertical]



Site: Polarization: **Vertical** Temperature: (C)
Limit: FCC Part15 (PK) Power: Humidity: %RH
EUT: Smart Lock
M/N: M19F
Mode: BLE-TX-2480
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over							
							MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	2483.500	43.56	-2.91	40.65	74.00	-33.35	peak						
2		2500.000	42.84	-3.00	39.84	74.00	-34.16	peak						

Test Result: Pass

7 Appendix A


7.1 Maximum PK Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	-1.822	30	Pass
NVNT	BLE 1M	2442	Ant1	-2.427	30	Pass
NVNT	BLE 1M	2480	Ant1	-1.716	30	Pass


Power NVNT BLE 1M 2402MHz Ant1



Power NVNT BLE 1M 2442MHz Ant1




Power NVNT BLE 1M 2480MHz Ant1




7.2-6dB Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	Ant1	0.666	0.5	Pass
NVNT	BLE 1M	2442	Ant1	0.667	0.5	Pass
NVNT	BLE 1M	2480	Ant1	0.663	0.5	Pass


-6dB Bandwidth NVNT BLE 1M 2402MHz Ant1



-6dB Bandwidth NVNT BLE 1M 2442MHz Ant1




-6dB Bandwidth NVNT BLE 1M 2480MHz Ant1




7.3 Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	BLE 1M	2402	Ant1	1.033200019
NVNT	BLE 1M	2442	Ant1	1.031149665
NVNT	BLE 1M	2480	Ant1	1.035505125


OBW NVNT BLE 1M 2402MHz Ant1



OBW NVNT BLE 1M 2442MHz Ant1




OBW NVNT BLE 1M 2480MHz Ant1




7.4 Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	-16.247	8	Pass
NVNT	BLE 1M	2442	Ant1	-17.118	8	Pass
NVNT	BLE 1M	2480	Ant1	-16.35	8	Pass


PSD NVNT BLE 1M 2402MHz Ant1



PSD NVNT BLE 1M 2442MHz Ant1




PSD NVNT BLE 1M 2480MHz Ant1




7.5 Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-52.31	-20	Pass
NVNT	BLE 1M	2480	Ant1	-52.26	-20	Pass


Band Edge NVNT BLE 1M 2402MHz Ant1 Ref




Band Edge NVNT BLE 1M 2402MHz Ant1 Emission



Band Edge NVNT BLE 1M 2480MHz Ant1 Ref




Band Edge NVNT BLE 1M 2480MHz Ant1 Emission




7.6 Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-41.49	-20	Pass
NVNT	BLE 1M	2442	Ant1	-26.22	-20	Pass
NVNT	BLE 1M	2480	Ant1	-25.7	-20	Pass


Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Ref



Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Emission




Tx. Spurious NVNT BLE 1M 2442MHz Ant1 Ref




Tx. Spurious NVNT BLE 1M 2442MHz Ant1 Emission





Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Ref



Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Emission



Appendix B: photographs of test setup



Appendix C: photographs of EUT

Reference to the test report no. BLA-EMC-202504-A8301

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, the result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.

BlueAsia