



## FCC TEST REPORT

**FCC ID: 2AWIJ-RBO**

On Behalf of

Warwick GmbH&Co Music Equipment KG

RockBoard MOD 4 and U2 Transmitter Wireless System and

TRS & XLR Patchbay

Model No.: RBO B MOD 4 AND RBO B MOD 4 U2

Prepared for : Warwick GmbH&Co Music Equipment KG  
Address : Gewerbepark 46 08258 Markneukirchen Germany

Prepared By : Shenzhen Alpha Product Testing Co., Ltd.  
Address : Building i, No.2, Lixin Road, Fuyong Street, Bao'an District,  
518103, Shenzhen, Guangdong, China

Report Number : A2005039-C07-R02  
Date of Receipt : May 20, 2020  
Date of Test : May 20-July 15, 2020  
Date of Report : July 15, 2020  
Version Number : V0

## TABLE OF CONTENTS

<u>Description</u>	<u>Page</u>
<b>1. Summary of Standards And Results .....</b>	<b>6</b>
1.1. Description of Standards and Results .....	6
<b>2. General Information .....</b>	<b>7</b>
2.1. Description of Device (EUT) .....	7
2.2. Accessories of Device (EUT) .....	8
2.3. Tested Supporting System Details .....	8
2.4. Block Diagram of connection between EUT and simulators.....	8
2.5. Test Mode Description.....	8
2.6. Test Conditions .....	9
2.7. Test Facility .....	9
2.8. Measurement Uncertainty .....	9
2.9. Test Equipment List .....	10
<b>3. Power Line Conducted Emission Test.....</b>	<b>11</b>
3.1. Block Diagram of Test Setup.....	11
3.2. Test Limits .....	11
3.3. Configuration of EUT on Test .....	12
3.4. Operating Condition of EUT .....	12
3.5. Test Procedure .....	12
3.6. Test Results .....	12
<b>4. Radiated Emission Test.....</b>	<b>14</b>
4.1. Block Diagram of Test Setup.....	14
4.2. Test Limit.....	15
4.3. Configuration of EUT on Test .....	16
4.4. Operating Condition of EUT .....	16
4.5. Test Procedure .....	16
4.6. Test Results .....	17
<b>5. Band Edge Test .....</b>	<b>22</b>
5.1. Block Diagram of Test Setup.....	22
5.2. Test Limit .....	22
5.3. Configuration of EUT on Test .....	23
5.4. Operating Condition of EUT .....	23
5.5. Test Procedure .....	23
5.6. Test Results .....	25
<b>6. Occupied bandwidth Test .....</b>	<b>27</b>
6.1. Block Diagram of Test Setup.....	27
6.2. Test Limit .....	27
6.3. Test Procedure .....	27
6.4. Test Results .....	27
<b>7. Antenna Requirement .....</b>	<b>29</b>
7.1. Standard Requirement.....	29
7.2. Antenna Connected Construction .....	29

7.3. Results.....	29
<b>8. Photograph.....</b>	<b>30</b>
8.1. Photos of Radiated Emission Test .....	30
8.2. Power Line Conducted Emission Test .....	31
<b>9. Photos of The EUT .....</b>	<b>32</b>

## TEST REPORT DECLARATION

Applicant : Warwick GmbH&Co Music Equipment KG  
Address : Gewerbepark 46 08258 Markneukirchen Germany  
Manufacturer : SHENZHEN FZON TECHNOLOGY CO., LTD  
Address : 2<sup>nd</sup> Floor, No12 building, Xicheng Industrial Area, Baoan district, Shenzhen, Guangdong, China  
EUT Description : RockBoard MOD 4 and U2 Transmitter Wireless System and TRS & XLR : Patchbay  
(A) Model No. : RBO B MOD 4 AND RBO B MOD 4 U2  
(B) Trademark : Rockboard

Measurement Standard Used:

### FCC Rules and Regulations Part 15 Subpart C Section 15.249

### ANSI C63.10:2013

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed full responsibility for the accuracy and completeness of test. Also, this report shows that the EUT is technically compliant with the FCC Part 15 requirements.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....: Lucas Pang  
Project Engineer



Approved by (name + signature).....: Simple Guan  
Project Manager



Date of issue.....: July 15, 2020

**Revision History**

Revision	Issue Date	Revisions	Revised By
V0	July 15, 2020	Initial released Issue	Simple Guan

## 1. SUMMARY OF STANDARDS AND RESULTS

### 1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

EMISSION			
Description of Test Item	Test Requirement	Standard Paragraph	Results
Power Line Conducted Emission Test	FCC Part 15	Section 15.207	P
Spurious Emission Test	FCC Part 15	Section 15.249&15.209	P
Occupied bandwidth	FCC Part 15	Section 15. 249	P
Band edge Requirement	FCC Part 15	Section 15.249	P
Antenna Requirement	FCC Part 15	Section 15.203	P

Note: 1. P is an abbreviation for Pass.  
2. F is an abbreviation for Fail.  
3. N/A is an abbreviation for Not Applicable.

## 2. GENERAL INFORMATION

### 2.1. Description of Device (EUT)

EUT Name : RockBoard MOD 4 and U2 Transmitter Wireless System and TRS & XLR Patchbay

Trademark : Rockboard

Model No. : RBO B MOD 4 AND RBO B MOD 4 U2

DIFF. : N/A

Power supply : DC 3.7V by battery, DC 5V from USB

#### 2.4G Technology

Operation frequency : 2402MHz -2482MHz

Modulation : GFSK

Antenna Type : PCB Antenna, max gain 1.98dBi.

Sample Type : Prototype production

## 2.2. Accessories of Device (EUT)

Accessories1 : /  
 Manufacturer : /  
 Model : /  
 Power supply : /

## 2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification or SDOC
1.	DC power	JUNKE	JK12010S	20140927-6	N/A

## 2.4. Block Diagram of connection between EUT and simulators



## 2.5. Test Mode Description

Test mode:

Mode	Channel	Frequency (MHz)
GFSK	Low :CH1	2402
GFSK	Middle: CH5	2448
GFSK	High: CH12	2482

Note:

1. The test was used to control EUT work in Continuous TX mode, and select test channel, wireless mode
2. The EUT has been tested as an independent unit. And Continual Transmitting in maximum power.
3. New battery is used during all tests.
4. For the relevant Conducted Measurement, the temporary antenna connector is used during the measurement. Antenna Connector Impedance:  $50\Omega$  , Cable Loss: 1.0 dB

Channel list:

Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	5	2448MHz	9	2472MHz
2	2408MHz	6	2450MHz	10	2474MHz
3	2420MHz	7	2456MHz	11	2480MHz
4	2432MHz	8	2458MHz	12	2482MHz

## 2.6. Test Conditions

Temperature range	21-25°C
Humidity range	40-75%
Pressure range	86-106kPa

## 2.7. Test Facility

Shenzhen Alpha Product Testing Co., Ltd.  
 Building i, No.2, Lixin Road, Fuyong Street, Bao'an District,  
 518103, Shenzhen, Guangdong, China

June 21, 2018 File on Federal Communication Commission  
 Registration Number: 293961

July 15, 2019 Certificated by IC  
 Registration Number: CN0085

## 2.8. Measurement Uncertainty

(95% confidence levels, k=2)


Item	Uncertainty
Uncertainty for Power point Conducted Emissions Test	2.74dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	2.13 dB(Polarize: V)
	2.57dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.77 dB (Distance: 3m Polarize: V)
	3.80 dB (Distance: 3m Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	4.13 dB (Distance: 3m Polarize: V)
	4.16 dB (Distance: 3m Polarize: H)
Uncertainty for radio frequency	$5.8 \times 10^{-8}$
Uncertainty for conducted RF Power	0.37dB
Uncertainty for temperature	0.2°C
Uncertainty for humidity	1%
Uncertainty for DC and low frequency voltages	0.06%

## 2.9. Test Equipment List

Equipment	Manufacture	Model No.	Serial No.	Last cal.	Cal Interval
9*6*6 anechoic chamber	CHENYU	9*6*6	N/A	2019.09.06	3Year
Spectrum analyzer	ROHDE&SCHWARZ	FSV40-N	102137	2019.09.05	1Year
Spectrum analyzer	Agilent	N9020A	MY499100060	2019.09.05	1Year
Receiver	ROHDE&SCHWARZ	ESR	1316.3003K03-102 082-Wa	2019.09.06	1Year
Receiver	R&S	ESCI	101165	2019.09.05	1Year
Bilog Antenna	Schwarzbeck	VULB 9168	VULB9168-438	2019.09.06	2Year
Horn Antenna	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D(1201)	2020.04.12	2Year
Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00059	2019.09.07	2Year
Cable	Resenberger	N/A	No.1	2019.09.05	1Year
Cable	Resenberger	N/A	No.2	2019.09.05	1Year
Cable	Resenberger	N/A	No.3	2019.09.05	1Year
Pre-amplifier	HP	HP8347A	2834A00455	2019.09.05	1Year
Pre-amplifier	Agilent	8449B	3008A02664	2019.09.05	1Year
L.I.S.N.#1	Schwarzbeck	NSLK8126	8126466	2019.09.05	1Year
L.I.S.N.#2	ROHDE&SCHWARZ	ENV216	101043	2019.09.05	1 Year
20db Attenuator	ICPROBING	IATS1	82347	2019.08.26	1 Year
Horn Antenna	SCHWARZBECK	BBHA9170	00946	2019.09.07	2 Year
Preamplifier	SKET	LNPA_1840-50	SK2018101801	2019.09.06	1 Year
Power Meter	Agilent	E9300A	MY41496625	2019.09.06	1 Year
Temp. &Humid. Chamber	Weihuang	WHTH-1000-40 -880	100631	2019.09.06	1 Year
Switching Mode Power Supply	JUNKE	JK12010S	20140927-6	2019.09.05	1 Year

### 3. POWER LINE CONDUCTED EMISSION TEST

#### 3.1. Block Diagram of Test Setup



#### 3.2. Test Limits

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB( $\mu$ V)	Average Level dB( $\mu$ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. Emission level=Read level + LISN factor·Preamp factor + Cable loss

2. \* Decreasing linearly with logarithm of frequency.

3. The lower limit shall apply at the transition frequencies.

### 3.3. Configuration of EUT on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

### 3.4. Operating Condition of EUT

- (1) Setup the EUT as shown as Section 3.1.
- (2) Turn on the power of all equipment.
- (3) Let the EUT work in test mode taking the test.


### 3.5. Test Procedure

- (1) The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#). This provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N.#2). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013 on conducted Emission test.
- (2) The frequency range from 150kHz to 30MHz is checked, the bandwidth of test receiver is set at 9kHz.
- (3) The frequency range from 30MHz to 1000MHz was pre-scanned with a Peak detector and all final readings of measurement from Test Receiver are Quasi-Peak and Average values.
- (4) The test results are reported on Section 3.6.

### 3.6. Test Results


EUT	RockBoard MOD 4 and U2 Transmitter : Wireless System and TRS & XLR Patchbay	Test Date : 2020.06.08
M/N	: RBO B MOD 4 AND RBO B MOD 4 U2	Temperature : 24°C
Test Engineer	: Lucas Pang	Humidity : 56%
Test Mode	: TX 2402MHz	
Test Results	: <b>PASS</b>	
Note: 1. The test results are listed in next pages.		

## Polarity: L



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Detector	Comment
		MHz	dBuV	dB	dBuV	dB			
1		0.2519	14.51	9.97	24.48	61.69	-37.21	peak	
2		0.4980	9.13	9.96	19.09	56.03	-36.94	peak	
3		0.9720	7.56	9.93	17.49	56.00	-38.51	peak	
4		3.0240	7.11	9.95	17.06	56.00	-38.94	peak	
5		8.4480	7.79	10.16	17.95	60.00	-42.05	peak	
6	*	25.8779	24.99	10.48	35.47	60.00	-24.53	peak	

## Polarity: N




Note: This report only shall the worst case mode for TX 2402MHz.


## 4. RADIATED EMISSION TEST

### 4.1. Block Diagram of Test Setup


In Semi Anechoic Chamber (3m) Test Setup Diagram for 9KHz~30MHz



In Semi Anechoic Chamber (3m) Test Setup Diagram for 30MHz~1000MHz



## In Semi Anechoic Chamber (3m) Test Setup Diagram for Above 1GHz



## 4.2. Test Limit

Frequency MHz	Distance (Meters)	Field Strengths Limits	
		uV/m	dB uV/m
0.009 ~ 0.490	300	2400/F(kHz)	---
0.490 1.705	30	24000/F(kHz)	----
1.705 30	30	30	29.5
30 88	3	100(3nW)	40
88 216	3	150(6.8nW)	43.5
216 960	3	200(12nW)	46
Above 960	3	500(75nW)	54
Carrier frequency	3	50000(avg)	113.97(peak) 93.97(avg)

Notes:

1. Emission level = Read level + Antenna Factor - Preamp Factor + Cable Loss
2. The smaller limit shall apply at the cross point between two frequency bands.
3. Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.
4. For frequencies above 1000 MHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

#### 4.3. Configuration of EUT on Test

The following equipment are installed on Radiated Emission Test to meet the commission requirements and operating regulations in a manner that tends to maximize its emission characteristics in normal application.

#### 4.4. Operating Condition of EUT

- (1) Setup the EUT as shown as Section 4.1.
- (2) Turn on the power of all equipment.
- (3) Let the EUT work in test mode taking the test.

#### 4.5. Test Procedure

- (1) The EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1GHz and 150 cm above the ground plane inside a semi-anechoic chamber for above 1GHz. An antenna was located 3m from the EUT on an adjustable mast. A pre-scan was first performed in order to find prominent radiated emissions. For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10: 2013 on Radiated Emission test.
- (2) For the radiated emission test above 1GHz:  
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- (3) Test antenna was located 4m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.
  - (a) Change work frequency or channel of device if practicable.
  - (b) Change modulation type of device if practicable.
  - (c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions
- (4) For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP
- (5) The frequency range from 9KHz to 150KHz is checked, the bandwidth of test receiver is

set at 200Hz.

The frequency range from 150KHz to 30MHz is checked, the bandwidth of test receiver is set at 9KHz.

The frequency range from 30MHz to 1000MHz is checked, the bandwidth of test receiver is set at 120kHz.

The frequency range from above 1GHz is checked, the bandwidth of Signal Analyzer is set at 1MHz.


- (6) The frequency range from 30MHz to 1000MHz was pre-scanned with a peak detector and all final readings of measurement from Test Receiver are Quasi-Peak values, the frequency range from 1GHz to 6GHz was pre-scanned with a peak detector and all final readings of measurement from Spectrum Analyzer are peak and average values checked, all measurement distance is 3m in 3m semi anechoic chamber.
- (7) Test for all x, y, z axes is performed and only the worst case of X axes was recorded in the test report.
- (8) The test results are reported on Section 4.6.

#### 4.6. Test Results

<b>Frequency Range : 9KHz~30MHz</b>		
EUT	: RockBoard MOD 4 and U2 Transmitter Wireless System and TRS & XLR Patchbay	Test Date : 2020.06.08
M/N	: RBO B MOD 4 AND RBO B MOD 4 U2	Temperature : 24°C
Test Engineer	: Lucas Pang	Humidity : 56%
Test Mode	: TX 2402MHz	
Test Results	: <b>PASS</b>	
Note:	1. Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.	


<b>Frequency Range : 30MHz~1000MHz</b>		
Test Mode	: TX 2402MHz	
Test Results	: <b>PASS</b>	
Note: 1. The test results are listed in next pages. 2. This mode is worst case mode, and this report only reflected the worst mode. 3. If the limits for the measurement with the quasi-peak detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the quasi-peak detector need not be carried out.		

## Vertical:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin	Antenna Height	Table Degree	Comment
		MHz	dB <sub>uV</sub>	dB	dB <sub>uV/m</sub>	dB <sub>uV/m</sub>	dB	Detector	cm	degree
1		43.5515	9.11	14.23	23.34	40.00	-16.66	peak		
2		58.4894	9.05	13.33	22.38	40.00	-17.62	peak		
3		115.4824	13.17	12.49	25.66	43.50	-17.84	peak		
4		176.5160	9.97	13.17	23.14	43.50	-20.36	peak		
5		470.1934	10.62	17.75	28.37	46.00	-17.63	peak		
6	*	725.7864	11.32	22.09	33.41	46.00	-12.59	peak		

## Horizontal:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin	Antenna Height	Table Degree	Comment
		MHz	dB <sub>uV</sub>	dB	dB <sub>uV/m</sub>	dB <sub>uV/m</sub>	dB	Detector	cm	degree
1		35.2263	9.83	13.74	23.57	40.00	-16.43	peak		
2		53.8440	9.35	13.72	23.07	40.00	-16.93	peak		
3		144.9942	9.66	14.68	24.34	43.50	-19.16	peak		
4		343.7821	10.85	15.14	25.99	46.00	-20.01	peak		
5		497.6764	14.58	18.18	32.76	46.00	-13.24	peak		
6	*	794.5095	10.86	22.87	33.73	46.00	-12.27	peak		

Note: This report only shall the worst case mode for TX 2402MHz.








## 5. BAND EDGE TEST

### 5.1. Block Diagram of Test Setup



### 5.2. Test Limit

Please refer section 15.249 and section 15.205.

249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in section 15.209, whichever is the lesser attenuation.

249(e) As shown in section 15.35(b), for frequencies above 1000MHz, the above field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation under paragraph (b) of this section, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth.

### 5.3. Configuration of EUT on Test

The following equipment are installed on Radiated Emission Test to meet the commission requirements and operating regulations in a manner that tends to maximize its emission characteristics in normal application.

### 5.4. Operating Condition of EUT

- (1) Setup the EUT as shown as Section 5.1.
- (2) Turn on the power of all equipment.
- (3) Let the EUT work in test mode taking the test.

### 5.5. Test Procedure


- (1) The EUT was placed on a non-metallic table, 150 cm above the ground plane inside a semi-anechoic chamber. An antenna was located 3m from the EUT on an adjustable mast. A pre-scan was first performed in order to find prominent radiated emissions. For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10: 2013 on Radiated Emission test.
- (2) For the radiated emission test above 1GHz:  
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- (3) Test antenna was located 4m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.
  - (a) Change work frequency or channel of device if practicable.
  - (b) Change modulation type of device if practicable.
  - (c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions

- (5) The frequency range from above 1GHz is checked, the bandwidth of Signal Analyzer is set at 1MHz.
- (6) The frequency range from 1GHz to 6GHz was pre-scanned with a peak detector and all final readings of measurement from Spectrum Analyzer are peak and average values checked, all measurement distance is 3m in 3m semi anechoic chamber.
- (7) Test for all x, y, z axes is performed and only the worst case of X xes was recorded in the test report.
- (8) The test results are reported on Section 5.6.

## 5.6. Test Results

Polarization: Vertical


Test Mode: TX 2402MHz



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		2390.000	46.02	-3.40	42.62	74.00	-31.38	peak		
2	*	2402.680	62.09	-3.41	58.68	74.00	-15.32	peak		

Polarization: Horizontal


Test Mode: TX 2402MHz



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		2390.000	46.88	-3.40	43.48	74.00	-30.52	peak		
2	*	2401.980	66.98	-3.41	63.57	74.00	-10.43	peak		

Polarization: Vertical


Test Mode: TX 2482MHz



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin	Antenna Height	Table Degree		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2482.310	64.52	-3.38	61.14	74.00	-12.86	peak			
2		2483.500	58.74	-3.38	55.36	74.00	-18.64	peak			
3		2483.500	43.50	-3.38	40.12	54.00	-13.88	AVG			

Polarization: Horizontal

Test Mode: TX 2482MHz




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin	Antenna Height	Table Degree		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2481.580	76.37	-3.38	72.99	74.00	-1.01	peak			
2		2483.500	66.83	-3.38	63.45	74.00	-10.55	peak			
3		2483.500	53.01	-3.38	49.63	54.00	-4.37	AVG			

Note: 1. \*:Maximum data; x:Over limit; !:over margin.

2. Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

## 6. OCCUPIED BANDWIDTH TEST

### 6.1. Block Diagram of Test Setup



### 6.2. Test Limit

Please refer section 15.249 and section 15.205.

### 6.3. Test Procedure

- (1) The bandwidth is measured at an amplitude level reduced 20dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.
- (2) The test receiver RBW set 30KHz, VBW set 100KHz, Sweep time set auto.

### 6.4. Test Results


Mode		Frequency MHz	20dB Bandwidth (MHz)	99% Bandwidth (KHz)	Limit (kHz)
GFSK	ANT1	2402	2.337	2.2102	/
		2441	2.370	2.2034	/
		2480	2.195	2.1303	/

Note: 1. The test results are listed in next pages.


## Frequency: 2402MHz



## Frequency: 2448MHz



## Frequency: 2482MHz



## 7. ANTENNA REQUIREMENT

### 7.1. Standard Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### 7.2. Antenna Connected Construction


The directional gains of antenna used for transmitting is 3.23dBi, and the antenna is fixed antenna no consideration of replacement. Please see EUT photo for details.

### 7.3. Results

The EUT antenna is PCB Antenna. It complies with the standard requirement.

## 8. PHOTOGRAPH

### 8.1. Photos of Radiated Emission Test



## 8.2. Power Line Conducted Emission Test







## 9. PHOTOS OF THE EUT















-----THE END OF REPORT-----