FCC ID: 2AWLO-NIO1

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency	Electric Field	Magnetic	Power	Average			
Range(MHz)	Strength(V/m)	Field	Density(mW/cm ²)	Time			
		Strength(A/m)					
(A) Limits for Occupational/Control Exposures							
300-1500			F/300	6			
1500-100000			5	6			
(B) Limits for General Population/Uncontrol Exposures							
300-1500			F/1500	6			
1500-100000			1	30			

11.1 Friis transmission formula: Pd= (Pout*G)\ (4*pi*R²)

Where

Pd= Power density in mW/cm²

Pout=output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

Pi=3.1416

R= distance between observation point and center of the radiator in cm Pd the limit of MPE, 1mW/cm², If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

RF Exposure Information: The radiated output power of this device meets the limits of FCC/IC radio frequency exposure limits. This device should be operated with a minimum separation distance of 20cm (8 inches) between the equipment and a person's body.

11.2 Measurement Result

WIFI2.4G and WIFI5G cannot support MIMO.

BLE

Antenna gain: 2.4 dBi

modulation	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
GFSK	5.46	5 to 6	6	1.74	0.001377	1

2.4G WIFI

Antenna gain: 2.4 dBi

7 11 11 CT 11 1 CK 9 CK						
modulation	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
	(ubili)		(ubiii)	Numeric	(IIIVV/CITIZ)	(IIIVV/CITIZ)
802.11b	19.80	18 to 20	20	1.74	0.034590	1

5G Wifi

Antenna gain: 3.33 dBi

modulation	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
UNII-1	16.77	15 to18	18	2.15	0.027036	1
UNII-2A	15.96	15 to 18	18	2.15	0.027036	1
UNII-2C	16.43	15 to 18	18	2.15	0.027036	1
UNII-3	15.98	15 to 18	18	2.15	0.027036	1

----- END OF REPORT-----