



243 Jubug-Ri, Yangji-Myeon, Yongin-Si, Gyeonggi-Do, Korea 17159
 Tel: +82-31-323-6008 Fax: +82-31-323-6010
<http://www.ltalab.com>

Dates of Tests: Dec 01 2020 ~ Apr 22, 2021
 Test Report S/N: LR500112104M
 Test Site : LTA CO., LTD.

CERTIFICATION OF COMPLIANCE

FCC ID.

2AWMDA712

APPLICANT

Apulse Technology Co., Ltd.

Equipment Class	:	Digital Transmission System (DTS) _LE,802.11
Manufacturing Description	:	RFID Smart Reader
Manufacturer	:	Apulse Technology Co., Ltd.
Model name	:	a712
Test Device Serial No.:	:	Identical prototype
Rule Part(s)	:	FCC Part 15.247 Subpart C ; ANSI C63.10 - 2013
Frequency Range	:	BLE 2402 ~ 2480 MHz 802.11 b,g,n20 2412 ~ 2462 MHz
Max. Output Power	:	Max 8.29 dBm - Conducted
Data of issue	:	April 23, 2021

This test report is issued under the authority of:

The test was supervised by:

Ja-Beom Koo, Manager

Eun-Hwan Jung, Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



NVLAP LAB Code.: 200723-0

TABLE OF CONTENTS

1. GENERAL INFORMATION	-----	3
2. INFORMATION ABOUT TEST ITEM	-----	4
3. TEST REPORT	-----	5
3.1 SUMMARY OF TESTS	-----	5
3.2 TECHNICAL CHARACTERISTICS TEST	-----	6
3.2.1 6 dB BANDWIDTH	-----	6
3.2.2 PEAK OUTPUT POWER	-----	12
3.2.3 POWER SPECTRAL DENSITY	-----	18
3.2.4 BAND EDGE	-----	24
3.2.5 CONDUCTED SPURIOUS EMISSIONS	-----	29
3.2.6 RADIATED SPURIOUS EMISSIONS	-----	34
APPENDIX	-----	
APPENDIX TEST EQUIPMENT USED FOR TESTS	-----	50

1. General information

1-1 Test Performed

Company name : LTA Co., Ltd.
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 17159
 Web site : <http://www.ltalab.com>
 E-mail : chahn@ltalab.com
 Telephone : +82-31-323-6008
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2021-09-30	ECT accredited Lab.
RRA	KOREA	KR0049	-	EMC accredited Lab.
FCC	U.S.A	649054	2021-04-11	FCC CAB
VCCI	JAPAN	C-4948,	2023-09-10	VCCI registration
VCCI	JAPAN	T-2416,	2023-09-10	VCCI registration
VCCI	JAPAN	R-4483(10 m),	2023-08-15	VCCI registration
VCCI	JAPAN	G-847	2021-12-13	VCCI registration
IC	CANADA	5799A-1	2021-06-16	IC filing
KOLAS	KOREA	NO.551	2021-08-20	KOLAS accredited Lab.

2. Information about test item

2-1 Client & Manufacturer

Client Company name : Apulse Technology Co., Ltd.
 Address : A-1403, Gwangmyeongtechnopark, 60, Haan-ro, Gwangmyeong-si, Gyeonggi-do, Korea
 Tel / Fax : +82-10-5526-0605 / +82-70-4222-5686
 Manufacturer : Apulse Technology Co., Ltd.
 Address : A-1403, Gwangmyeongtechnopark, 60, Haan-ro, Gwangmyeong-si, Gyeonggi-do, Korea
 Tel / Fax : +82-10-5526-0605 / +82-70-4222-5686

2-2 Equipment Under Test (EUT)

Model name : a712
 Serial number : Identical prototype
 Date of receipt : Dec 01, 2020
 EUT condition : Pre-production, not damaged
 Antenna type : FPCB Antenna (Max Gain : 0.07 dBi)
 Frequency Range : BLE 2402 ~ 2480 MHz
 Frequency Range : 802.11 b,g,n20 2412 ~ 2462 MHz
 RF output power : Max 8.29 dBm – Conducted
 Type of Modulation : Pi/4 DQPSK, 8DPSK, OFDMA
 Power Source : DC 3.7 V

2-3 Tested frequency

	LOW	MID	HIGH
Frequency (MHz) 802.11 b,g,n20	2412	2442	2462
Frequency (MHz) BLE	2402	2442	2480

2-4 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
Notebook	-	MS-1736	MSI

3. Test Report

3.1 Summary of tests

FCC Part Section(s)	Parameter	Test Condition	Status (note 1)
15.247(a)	6 dB Bandwidth	Conducted	C
15.247(b)	Transmitter Peak Output Power		C
15.247(e)	Transmitter Power Spectral Density		C
15.247(d)	Band Edge & Conducted Spurious emission		C
15.209	Transmitter emission	Radiated	C
15.207	AC Conducted Emissions	Conducted	N/A
15.203	Antenna requirement	-	C

N/A : This product is battery-enabled and excludes the test.

The above equipment was tested by LTA Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.247. The test results of this report relate only to the tested sample identified in this report.

The tests were performed according to the method of measurements prescribed in KDB No.558074.

→ Antenna Requirement

Apulse Technology Co., Ltd. FCC ID: 2AWMDA712 unit complies with the requirement of §15.203.
The antenna type is PCB Antenna

3.2 Technical Characteristics Test

3.2.1 6 dB Bandwidth

Procedure:

The bandwidth at 6 dB below the highest in-band spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate frequencies.

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 6 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 6 dB bandwidth of the emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz

Span = 3 X RBW

VBW = 3 X RBW

Sweep = auto

Trace = max hold

Detector function = peak

Measurement Data : **Complies**

BLE Mode

Frequency (MHz)	Test Results	
	Measured Bandwidth (kHz)	Result
2402	729.400	Complies
2442	732.300	Complies
2480	738.100	Complies

(802.11 b)

Frequency (MHz)	Test Results	
	Measured Bandwidth (MHz)	Result
2412	10.507	Complies
2442	10.564	Complies
2462	10.507	Complies

(802.11 g)

Frequency (MHz)	Test Results	
	Measured Bandwidth (MHz)	Result
2412	16.903	Complies
2442	16.961	Complies
2462	16.729	Complies

(802.11 n20)

Frequency (MHz)	Test Results	
	Measured Bandwidth (MHz)	Result
2412	-15.53	Complies
2442	-16.79	Complies
2462	-16.18	Complies

- See next pages for actual measured spectrum plots.

Minimum Standard:

6 dB Bandwidth \geq 500 kHz

Measurement Setup






Figure 1: Measurement setup for the carrier frequency separation


BLE




802.11 b



802.11 g



802.11 n20



3.2.2 Peak Output Power Measurement

Procedure:

The following procedure can be used when the maximum available RBW of the instrument is less than the DTS bandwidth :

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

$$\text{RBW} \geq \text{DTS Bandwidth} \quad \text{Span} \geq 3 \times \text{RBW}$$

Detector function = peak

Measurement Data : Complies

BLE Mode

Frequency (MHz)	Test Results	
	Measured data (dBm)	Result
2402	5.76	Complies
2442	5.92	Complies
2480	5.15	Complies

802.11 b Mode

Frequency (MHz)	Test Results	
	Measured data (dBm)	Result
2412	7.69	Complies
2442	8.01	Complies
2462	8.29	Complies

802.11 g Mode

Frequency (MHz)	Test Results	
	Measured data (dBm)	Result
2412	4.35	Complies
2442	4.58	Complies
2462	4.42	Complies

802.11 n20 Mode

Frequency (MHz)	Test Results	
	Measured data (dBm)	Result
2412	1.97	Complies
2442	2.60	Complies
2462	2.63	Complies

- See next pages for actual measured spectrum plots.


Minimum Standard:

Peak output power	≤ 1 W(30 dBm)
-------------------	---------------


Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)


BLE




802.11 b



802.11 g



802.11 n20



3.2.3 Power Spectral Density

Procedure:

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance.

The spectrum analyzer is set to:

RBW = 3 kHz (3 kHz ≤ RBW ≤ 100 kHz)	Span ≥ 1.5 times the DTS bandwidth
VBW = 3 X RBW	Sweep = auto
Detector function = peak	Trace = max hold

Measurement Data : Complies

BLE Mode

Frequency (MHz)	Test Results	
	dBm / 3 kHz BW	Result
2402	-8.50	Complies
2442	-8.27	Complies
2480	-9.11	Complies

802.11 b Mode

Frequency (MHz)	Test Results	
	dBm / 3 kHz BW	Result
2412	-14.85	Complies
2442	-14.81	Complies
2462	-15.93	Complies

802.11 g Mode

Frequency (MHz)	Test Results	
	dBm / 3 kHz BW	Result
2412	-16.61	Complies
2442	-16.41	Complies
2462	-16.00	Complies

802.11 n20 Mode

Frequency (MHz)	Test Results	
	dBm / 3 kHz BW	Result
2412	-17.68	Complies
2442	-18.73	Complies
2462	-17.10	Complies

- See next pages for actual measured spectrum plots.


Minimum Standard:

Power Spectral Density	\leq 8 dBm @ 3 kHz BW
------------------------	-------------------------


Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)


BLE




802.11 b



802.11 g



802.11 n20



3.2.4 Band Edge

Procedure:

The Unwanted emission from the EUT were measured according to the dictates PKPSD measurement procedure in section 11.11 of ANSI C63.10-2013.

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits.

If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB..

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 1 MHz VBW > 3 X RBW


Detector function = peak Trace = max hold



Sweep = auto



Measurement Data: Complies



- All conducted emission in any 100 kHz bandwidth outside of the spread spectrum band was at least 20 dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.

Minimum Standard: $\leq 20 \text{ dBc}$

BLE

802.11 b

802.11 g

802.11 n20

3.2.5 Conducted Spurious Emissions

Procedure:

The test follows KDB558074. The conducted spurious emissions were measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels.

After the trace being stable, set the marker on the peak of any spurious emission recorded.

The spectrum analyzer is set to:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions

RBW = 100 kHz Sweep = auto

VBW = 100 kHz Detector function = peak

Trace = max hold


Measurement Data: **Complies**




- All conducted emission in any 100 kHz bandwidth outside of the spread spectrum band was at least 20 dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.


Minimum Standard:	≥ 20 dBc
--------------------------	---------------


Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Unwanted Emission – BLE (Low,Middle,High)

Unwanted Emission – 802.11 b (Low,Middle,High)

Unwanted Emission – 802.11 g (Low,Middle,High)

Unwanted Emission – 802.11 n20 (Low,Middle,High)

3.2.6 Radiated Spurious Emissions

Procedure:

Radiated emissions from 30 MHz to 25 GHz were measured according to the methods defined in ANSI C63.10-2013.

The EUT is placed on a turn table. For emissions testing at or below 1 GHz, the table height shall be 0.8 m above the reference ground plane. For emission measurements above 1 GHz, the table height shall be 1.5 m. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes and measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made “while keeping the antenna in the ‘cone of radiation’ from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.” is still within the 3dB illumination BW of the measurement antenna.

The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 9 kHz ~ 10th harmonic.

RBW = 120 kHz (30 MHz ~ 1 GHz)

$$\text{VBW} \geq \text{RBW}$$

= 1 MHz (1 GHz \sim 10th harmonic)


Detector function = peak



Sweep = auto

Duty cycle : 98.89 %

The EUT configured to transmit continuously ($D \geq 98\%$)/ Duty Factor = 0

below 30 MHz.




below 1 GHz (30 MHz to 1 GHz)**above 1 GHz****Measurement Data: Complies**

- See next pages for actual measured data.
- No other emissions were detected at a level greater than 20 dB below limit include from 9 kHz to 30MHz.
- The test results for the worst of the various operating modes are presented in accordance with 6.3.4 of ANSI C63.10.
- Checked with a red circle is the fundamental frequency.

Minimum Standard: FCC Part 15.209(a)


Frequency (MHz)	Limit (uV/m) @ 3 m
0.009 ~ 0.490	2400/F(kHz) (@ 300 m)
0.490 ~ 1.705	24000/F(kHz) (@ 30 m)
1.705 ~ 30	30(@ 30 m)
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

Radiated Emissions – BLE


No.	Freq MHz	Reading dB μ V	C.F dB	Result dB μ V/m	Limit dB μ V/m	Margin dB	Height cm	Angle deg	Polarity
1.	203.15	56.69	-19.52	37.17	43.50	6.33	100	67	horizontal
2.	383.81	45.80	-13.01	32.79	46.00	13.21	100	133	horizontal
3.	790.36	38.60	-4.13	34.47	46.00	11.53	100	147	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




No.	Freq MHz	Reading dB μ V	C.F dB	Result dB μ V/m	Limit dB μ V/m	Margin dB	Height cm	Angle deg	Polarity
1.	203.15	57.39	-19.52	37.87	43.50	5.63	100	258	vertical
2.	474.14	50.20	-10.67	39.53	46.00	6.47	100	8	vertical
3.	519.37	50.20	-9.51	40.69	46.00	5.31	100	87	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




No.	Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin	Height	Angle	Polarity
	MHz	PK	AV		PK	AV	PK	AV	PK	AV	cm	deg	
1.	1394.20	53.59	-----	-9.99	43.60	-----	74.00	-----	38.40	-----	125	130	horizontal
2.	4868.12	51.13	-----	4.47	55.66	-----	74.00	-----	18.48	-----	199	284	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




No.	Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin	Height	Angle	Polarity
	MHz	PK	AV		PK	AV	PK	AV	PK	AV	cm	deg	
1.	1985.51	47.73	-----	-6.19	41.54	-----	74.00	-----	32.46	-----	132	127	vertical
2.	4868.12	51.19	-----	4.47	55.66	-----	74.00	-----	18.34	-----	191	185	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




No.	Freq	RD	RD	C.F		Result		Result		Limit		Limit		Margin	Margin	Height	Angle	Polarity
				PK	AV	PK	AV	PK	AV	PK	AV	PK	AV					
	MHz	dB μ V	dB μ V	dB	dB μ V	dB	dB	cm	deg									
2.	35883.25	37.28	28.20	23.32	68.52	51.52	80.00	68.00	19.48	8.48	100	50	Horizontal					
4.	37629.50	36.53	27.53	23.66	68.19	51.19	80.00	68.00	19.81	8.81	100	7	horizontal					
6.	39447.25	36.40	28.40	23.88	68.28	52.28	80.00	68.00	19.72	7.72	100	96	horizontal					

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




No.	Freq	RD	RD	C.F		Result		Result		Limit		Limit		Margin	Margin	Height	Angle	Polarity
				PK	AV	PK	AV	PK	AV	PK	AV	PK	AV					
	MHz	dB μ V	dB μ V	dB	dB μ V	dB	dB	cm	deg									
2.	35083.00	38.48	28.48	22.30	68.78	50.78	80.00	68.00	19.22	9.22	100	124	vertical					
4.	37420.50	36.51	27.51	23.74	68.25	51.25	80.00	68.00	19.75	8.75	100	155	vertical					
6.	39837.75	37.13	27.13	24.34	61.47	51.47	80.00	60.00	18.53	8.53	100	285	vertical					

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emissions – 802.11 b


No.	Freq	Reading	C.F	Result QP	Limit	Margin	Height	Angle	Polarity
	MHz	dB μ V	dB	dB μ V/m	dB μ V/m	dB	cm	deg	
1.	203.15	50.59	-19.52	31.07	43.50	12.43	100	117	horizontal
2.	225.82	53.40	-18.37	35.03	46.00	10.97	100	117	horizontal
3.	383.81	47.20	-13.01	34.19	46.00	11.81	100	67	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




No.	Freq	Reading	C.F	Result QP	Limit	Margin	Height	Angle	Polarity
	MHz	dB μ V	dB	dB μ V/m	dB μ V/m	dB	cm	deg	
1.	203.15	55.69	-19.52	36.17	43.50	7.33	100	343	vertical
2.	519.37	48.70	-9.51	39.19	46.00	6.81	100	42	vertical
3.	600.00	40.10	-7.45	32.65	46.00	13.35	100	360	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




No.	Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin	Height	Angle	Polarity
		PK	AV	PK	AV	PK	AV	PK	AV	PK	AV	cm	deg
1.	4868.12	-----	48.81	4.47	-----	52.48	-----	54.00	-----	1.52	199	284	horizontal
2.	4868.12	67.81	48.81	4.47	71.48	52.48	74.00	54.00	2.52	1.52	199	284	horizontal
3.	7331.88	-----	48.50	8.08	-----	48.58	-----	54.00	-----	5.42	228	233	horizontal
4.	7331.88	53.01	48.50	8.08	61.09	48.58	74.00	54.00	12.91	5.42	228	233	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




No.	Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin	Height	Angle	Polarity
		PK	AV	PK	AV	PK	AV	PK	AV	PK	AV	cm	deg
1.	4868.12	-----	48.51	4.47	-----	52.98	-----	54.00	-----	1.02	217	211	vertical
2.	4868.12	67.51	48.51	4.47	71.98	52.98	74.00	54.00	2.02	1.02	217	211	vertical
3.	7331.88	-----	42.60	8.08	-----	50.68	-----	54.00	-----	3.32	186	179	vertical
4.	7331.88	54.61	42.60	8.08	62.69	50.68	74.00	54.00	11.31	3.32	186	179	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




No.	Freq	RD	RD	C.F	Result		Result		Limit		Limit		Margin	Margin	Height	Angle	Polarity
					PK	AV	PK	AV	PK	AV	PK	AV					
MHz	dB μ V	dB μ V	dB	dB μ V	dB μ V	dB	dB μ V	dB μ V	dB	dB μ V	dB	cm	deg				
2.	35083.25	37.20	28.20	23.32	60.52	51.52	60.00	60.00	19.48	8.48	100	50	horizontal				
4.	37629.50	36.53	27.53	23.66	60.18	51.19	60.00	60.00	19.81	8.81	100	7	horizontal				
6.	39447.25	36.40	28.40	23.88	60.28	52.28	60.00	60.00	19.72	7.72	100	96	horizontal				

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




No.	Freq	RD	RD	C.F	Result		Result		Limit		Limit		Margin	Margin	Height	Angle	Polarity
					PK	AV	PK	AV	PK	AV	PK	AV					
MHz	dB μ V	dB μ V	dB	dB μ V	dB μ V	dB	dB μ V	dB μ V	dB	dB μ V	dB	cm	deg				
2.	35083.00	38.48	28.48	22.30	60.78	50.78	60.00	60.00	19.22	9.22	100	124	vertical				
4.	37428.50	36.51	27.51	23.74	60.25	51.25	60.00	60.00	19.75	8.75	100	155	vertical				
6.	39837.75	37.13	27.13	24.34	61.47	51.47	60.00	60.00	18.53	8.53	100	285	vertical				

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emissions – 802.11 g


No.	Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
	MHz	dB μ V	dB	dB μ V/m	dB μ V/m	dB	cm	deg	
1.	600.11	40.70	-8.28	32.42	46.00	13.58	100	0	horizontal
2.	926.16	36.40	-3.37	33.03	46.00	12.97	100	295	horizontal
3.	1000.00	38.00	-2.60	35.40	54.00	18.60	100	198	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




No.	Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
	MHz	dB μ V	dB	dB μ V/m	dB μ V/m	dB	cm	deg	
1.	790.62	42.60	-5.01	37.59	46.00	8.41	100	146	vertical
2.	835.88	43.30	-4.39	38.91	46.00	7.09	100	146	vertical
3.	880.63	41.89	-3.86	38.03	46.00	7.97	100	146	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




No.	Freq	RD	RD	C.F	Result		Result		Limit		Margin		Height	Angle	Polarity
					PK	AV	PK	AV	PK	AV	PK	AV			
MHz	dB μ V	dB μ V	dB	dB μ V	dB μ V	dB	dB μ V	dB μ V	dB	dB	dB	dB	cm	deg	
2.	1792.63	54.19	47.40	-7.47	46.72	39.93	74.00	54.00	27.28	14.07	197	189	horizontal		
4.	4884.50	55.03	43.00	4.52	59.55	47.52	74.00	54.00	14.45	6.48	9	6	horizontal		

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




No.	Freq	RD	RD	C.F	Result		Result		Limit		Margin		Height	Angle	Polarity
					PK	AV	PK	AV	PK	AV	PK	AV			
MHz	dB μ V	dB μ V	dB	dB μ V	dB μ V	dB	dB μ V	dB μ V	dB	dB	dB	dB	cm	deg	
2.	1397.38	55.10	50.10	-9.97	45.13	48.13	74.00	54.00	28.87	13.87	360	360	vertical		
4.	4888.75	57.36	47.41	4.52	61.88	51.93	74.00	54.00	12.12	2.07	9	9	vertical		

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




No.	Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin	Height	Angle	Polarity
	MHz	PK	AV		PK	AV	PK	AV	PK	AV	cm	deg	
1.	38842.25	27.64	-----	21.53	49.17	-----	74.00	-----	24.83	-----	258	263	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




No.	Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin	Height	Angle	Polarity
	MHz	PK	AV		PK	AV	PK	AV	PK	AV	cm	deg	
1.	38853.25	28.06	-----	21.49	49.55	-----	74.00	-----	24.45	-----	84	77	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emissions – 802.11 n


No.	Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
	MHz	dB _u V	dB	dB _u V/m	dB _u V/m	dB	cm	deg	
1.	504.04	40.60	-10.78	29.82	46.00	16.18	100	128	horizontal
2.	597.75	43.70	-8.34	35.36	46.00	10.64	100	360	horizontal
3.	880.63	38.79	-3.86	34.93	46.00	11.07	100	294	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




No.	Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
	MHz	dB _u V	dB	dB _u V/m	dB _u V/m	dB	cm	deg	
1.	203.26	50.80	-20.06	30.74	43.50	12.76	100	246	vertical
2.	600.11	40.60	-8.28	32.32	46.00	13.68	100	0	vertical
3.	835.88	42.20	-4.39	37.81	46.00	8.19	100	146	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




No.	Freq	RD		RD		C.F	Result	Result	Limit		Margin		Height	Angle	Polarity
		PK	AV	PK	AV				PK	AV	PK	AV			
MHz	dB μ V	dB μ V	dB	dB μ V	dB	dB μ V	dB	dB μ V	dB	dB	dB	dB	cm	deg	
2.	1998.75	54.52	47.80	-6.11	48.41	41.69	74.00	54.00	25.59	12.31	322	315	horizontal		
4.	4880.25	54.08	44.70	-4.51	58.51	49.21	74.00	54.00	15.49	4.78	108	108	horizontal		

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



No.	Freq	RD		RD		C.F	Result	Result	Limit		Margin		Height	Angle	Polarity
		PK	AV	PK	AV				PK	AV	PK	AV			
MHz	dB μ V	dB μ V	dB	dB μ V	dB	dB μ V	dB	dB μ V	dB	dB	dB	dB	cm	deg	
2.	1998.25	49.81	44.60	-6.16	42.85	38.44	74.00	54.00	31.15	15.56	339	345	vertical		
4.	4884.50	54.08	44.50	-4.52	58.50	49.42	74.00	54.00	15.48	4.58	123	123	vertical		


Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



No.	Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin	Height	Angle	Polarity
	MHz	PK	AV		PK	AV	PK	AV	PK	AV	cm	deg	
		dB μ V	dB μ V		dB	dB μ V	dB μ V	dB μ V	dB	dB			

1.	38861.50	28.88	-----	21.48	58.36	-----	74.00	-----	23.64	-----	256	263	horizontal
----	----------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-----	-----	------------

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



No.	Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin	Height	Angle	Polarity
	MHz	PK	AV		PK	AV	PK	AV	PK	AV	cm	deg	
		dB μ V	dB μ V		dB	dB μ V	dB μ V	dB μ V	dB	dB			

1.	38842.25	27.32	-----	21.53	48.85	-----	74.00	-----	25.15	-----	368	368	vertical
----	----------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-----	-----	----------

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

3.2.7 AC Conducted Emissions

Procedure:

The conducted emissions are measured in the shielded room with a spectrum analyzer in peak hold. While the measurement, EUT had its hopping function disabled at the middle channels in line with Section 15.31(m). Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation and Exerciser operation. The highest emissions relative to the limit are listed.

Minimum Standard: FCC Part 15.207(a) / EN 55022

Measurement Data: N/A

Class B

Frequency Range	quasi-peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

* Decreases with the logarithm of the frequency

APPENDIX
TEST EQUIPMENT USED FOR TESTS

	Use	Description	Model No.	Serial No.	Manufacturer	Interval	Next Cal. Date
1	■	Signal Analyzer (9 kHz ~ 30 GHz)	FSV30	100757	R&S	1 year	2021-09-07
2	■	Signal Generator (~3.2 GHz)	8648C	3623A02597	HP	1 year	2022-03-16
3		SYNTHESIZED CW GENERATOR	83711B	US34490456	HP	1 year	2022-03-16
4		Attenuator (3 dB)	8491A	37822	HP	1 year	2021-09-07
5		Attenuator (10 dB)	8491A	63196	HP	1 year	2021-09-07
6	■	EMI Test Receiver (~7 GHz)	ESCI7	100722	R&S	1 year	2021-09-07
7		RF Amplifier (~1.3 GHz)	8447D OPT 010	2944A07684	HP	1 year	2021-09-07
8		RF Amplifier (1~26.5 GHz)	8449B	3008A02126	HP	1 year	2022-03-16
9	■	Horn Antenna (1~18 GHz)	3115	00114105	ETS	2 year	2022-09-10
10		DRG Horn (Small)	3116B	81109	ETS-Lindgren	2 year	2022-03-18
11		DRG Horn (Small)	3116B	133350	ETS-Lindgren	2 year	2022-03-18
12	■	TRILOG Antenna	VULB 9160	9160-3237	SCHWARZBECK	2 year	2023-03-20
13		Temp.Humidity Data Logger	SK-L200TH II A	00801	SATO	1 year	2022-03-16
14		Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	-	-
15	■	DC Power Supply	6674A	3637A01657	Agilent	-	-
17	■	Power Meter	EPM-441A	GB32481702	HP	1 year	2022-03-16
18	■	Power Sensor	8481A	3318A94972	HP	1 year	2021-09-07
19		Audio Analyzer	8903B	3729A18901	HP	1 year	2021-09-07
20		Modulation Analyzer	8901B	3749A05878	HP	1 year	2021-09-07
21		TEMP & HUMIDITY Chamber	YJ-500	LTAS06041	JinYoung Tech	1 year	2021-09-07
22		Stop Watch	HS-3	812Q08R	CASIO	2 year	2022-03-18
23		LISN	KNW-407	8-1430-1	Kyoritsu	1 year	2022-03-16
24		Two-Lime V-Network	ESH3-Z5	893045/017	R&S	1 year	2022-03-16
25		UNIVERSAL RADIO COMMUNICATION TESTER	CMU200	106243	R&S	1 year	2022-03-16
26		Highpass Filter	WHKX1.5/15G-10SS	74	Wainwright Instruments	1 year	2022-03-16
27		Highpass Filter	WHKX3.0/18G-10SS	118	Wainwright Instruments	1 year	2022-03-16
28		OSP120 BASE UNIT	OSP120	101230	R&S	1 year	2022-03-16
29		Signal Generator(100 kHz ~ 40 GHz)	SMB100A03	177621	R&S	1 year	2022-03-16
30		Signal Analyzer (10 Hz ~ 40 GHz)	FSV40	101367	R&S	1 year	2022-03-16
31	■	Active Loop Antenna	FMZB 1519	1519-031	SCHWARZBECK	2 year	2021-09-07