

RF Exposure Evaluation Report

Product : Smart LED Flood Light
Trade mark : MustWin
Model/Type reference : MWA09
Serial Number : N/A
Report Number : EED32M00214602
FCC ID : 2AWPYMWA09
Date of Issue : Aug. 14, 2020
Test Standards : 47 CFR Part 1.1307
47 CFR Part 2.1091
KDB447498D01v06
Test result : PASS

Prepared for:

Shenzhen Michuang Technology Ltd.
Rm.1012, A Bldg., No.142, Meilong St.,
Longhua District, Shenzhen, CHINA 518000

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Compiled by:

Smile Zhong

Smile Zhong

Reviewed by:

Jok Yang

Jok Yang

Approved by:

Sam Chuang

Sam Chuang

Date:

Aug. 14, 2020

Check No.: 2447696923



2 Version

Version No.	Date	Description
00	Aug. 14, 2020	Original

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS.....	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT.....	4
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	4
4.4 TEST LOCATION.....	5
4.5 DEVIATION FROM STANDARDS.....	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
5 RF EXPOSURE EVALUATION.....	6
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	6
5.2 MAXIMUM PERMISSIBLE EXPOSURE.....	7
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS.....	8

4 General Information

4.1 Client Information

Applicant:	Shenzhen Michuang Technology Ltd.
Address of Applicant:	Rm.1012, A Bldg., No.142, Meilong St., Longhua District, Shenzhen, CHINA 518000
Manufacturer:	Shenzhen Michuang Technology Ltd.
Address of Manufacturer:	Rm.1012, A Bldg., No.142, Meilong St., Longhua District, Shenzhen, CHINA 518000
Factory:	Shenzhen Michuang Technology Ltd.
Address of Factory:	Rm.1012, A Bldg., No.142, Meilong St., Longhua District, Shenzhen, CHINA 518000

4.2 General Description of EUT

Product Name:	Smart LED Flood Light
Model No.(EUT):	MWA09
Trade Mark:	MustWin
EUT Supports Radios application	BT 5.0 Single mode, 2402MHz to 2480MHz

4.3 Product Specification subjective to this standard

Frequency Range:	2402MHz to 2480MHz			
Modulation Type:	GFSK			
Test Power Grade:	Default			
Test Software of EUT:	EMI Test Tool			
Antenna Type:	Dipole Antenna			
Antenna Specification	Bluetooth :	Antenna Gain :	2.00 dBi	(Numeric gain: 1.58)
Maximum tune up power	Bluetooth:		4.000 dBm	(2.512 mW)
Power Supply:	DC 5V			
Sample Received Date:	Jul. 17, 2020			
Sample tested Date:	Jul. 17, 2020 to Aug. 12, 2020			
The tested sample(s) and the sample information are provided by the client.				

4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

5.2 Maximum Permissible Exposure

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

Bluetooth:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
39	2480	2.512	1.58	20	0.0008	1

PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No. EED32M00214601 for EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.