

# INTERTEK TESTING SERVICES

---

## RF Exposure

The equipment under test (EUT) is a Toy RC Pixie Cruiser operating at 2.4G Band. The EUT can be powered by DC 9.0V (1 x 9.0V 6F22 battery). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna

Modulation Type: GFSK

Antenna Gain: 0dBi

The nominal conducted output power specified: -12.0 dBm ( $\pm 3$ dB)

The nominal radiated output power (e.i.r.p) specified: -12.0 dBm ( $\pm 3$ dB)

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 82.5 dB $\mu$ V/m at 3m in the frequency 2475MHz

The EIRP =  $[(FS^*D)^2 / 30]$  mW = -12.73dBm  
which is within the production variation.

The Minimum peak radiated emission for the EUT is 82.3 dB $\mu$ V/m at 3m in the frequency 2440MHz

The EIRP =  $[(FS^*D)^2 / 30]$  mW = -12.93dBm  
which is within the production variation.

The maximum conducted output power specified is -9dBm= 0.126mW

The source- based time-averaging conducted output power  
=0.126\* Duty cycle mW <0.126 mW(Duty cycle <100%)

The SAR Exclusion Threshold Level:

$$P_{th}(\text{mW}) = \text{ERP}_{20\text{cm}} * (d/20\text{cm})^x \quad (X = -\log_{10} \left( \frac{60}{\text{ERP}_{20\text{cm}} \sqrt{f}} \right))$$
$$= 3060 * (0.5/20)^{1.9} \text{ mW}$$
$$= 2.72 \text{ mW}$$

Since max. power of the source-based time-averaging conducted output power and effective radiated power (ERP) is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 21.7826ms

Effective period of the cycle = 0.6087ms

DC = 0.6087ms / 21.7826ms = 0.0279 or 2.79%