

FCC ID: 2AWR5-KY004LN01

Maximum Permissible Exposure (MPE)

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

2.4G WIFI:

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz,

Power density limited: $1\text{mW}/\text{cm}^2$

Antenna Type: FPC antenna

Antenna gain: 2.33dBi;

R=20cm

$\text{mW}=10^{(\text{dBm}/10)}$

antenna gain Numeric= $10^{(\text{dBi}/10)}=10^{(2.33/10)}=1.71$

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density
		(dBm)		tune-up power		Gain		(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	(dBi)	Numeric		
2412	802.11b	14.19	14±1	15	31.623	2.33	1.71	0.0108	1
2437		14.17	14±1	15	31.623	2.33	1.71	0.0108	1
2462		14.35	14±1	15	31.623	2.33	1.71	0.0108	1
2412	802.11g	12.36	12.5±1	13.5	22.387	2.33	1.71	0.0076	1
2437		12.82	12.5±1	13.5	22.387	2.33	1.71	0.0076	1
2462		13.23	12.5±1	13.5	22.387	2.33	1.71	0.0076	1
2412	802.11n H20	12.06	12±1	13	19.953	2.33	1.71	0.0068	1
2437		12.45	12±1	13	19.953	2.33	1.71	0.0068	1
2462		12.94	12±1	13	19.953	2.33	1.71	0.0068	1

5G WIFI:

Operation Frequency: WIFI 802.11a/n(HT20):

5180-5240MHz;5260-5320MHz,5500-5700MHz,5745-5825MHz;

Power density limited: 1mW/cm

Antenna Type: FPC antenna

Antenna gain:4.33dBi;

R=20cm

$mW=10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)}=10^{(4.33/10)}=2.71$

5.2G

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density
		(dBm)		tune-up power		Gain		(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	(dBi)	Numeric		
5180	802.11a	10.07	10±1	11	12.589	4.33	2.71	0.0068	1
5200		10.85	10±1	11	12.589	4.33	2.71	0.0068	1
5240		10.67	10±1	11	12.589	4.33	2.71	0.0068	1
5180	802.11n H20	10.4	10±1	11	12.589	4.33	2.71	0.0068	1
5200		10.96	10±1	11	12.589	4.33	2.71	0.0068	1
5240		10.54	10±1	11	12.589	4.33	2.71	0.0068	1

5.3G

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density
		(dBm)		tune-up power		Gain		(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	(dBi)	Numeric		
5260	802.11a	10.58	10±1	11	12.589	4.33	2.71	0.0068	1
5280		10.3	10±1	11	12.589	4.33	2.71	0.0068	1
5320		10.5	10±1	11	12.589	4.33	2.71	0.0068	1
5260	802.11n H20	10.63	10±1	11	12.589	4.33	2.71	0.0068	1
5280		10.46	10±1	11	12.589	4.33	2.71	0.0068	1
5320		10.7	10±1	11	12.589	4.33	2.71	0.0068	1

5.6G

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density
		(dBm)		tune-up power		Gain			
				(dBm)	(dBm)	(mW)	(dBi)	Numeric	(mW/cm2)
5500	802.11a	8.59	8±1	9	7.943	4.33	2.71	0.0043	1
5600		8.57	8±1	9	7.943	4.33	2.71	0.0043	1
5700		8.15	8±1	9	7.943	4.33	2.71	0.0043	1
5500	802.11n(HT20)	8.75	8±1	9	7.943	4.33	2.71	0.0043	1
5600		8.55	8±1	9	7.943	4.33	2.71	0.0043	1
5700		8.2	8±1	9	7.943	4.33	2.71	0.0043	1

5.8G

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm2)	Power density (mW/cm2)
		(dBm)		tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric		
5745	802.11a	10.6	10±1	11	12.589	4.33	2.71	0.0068	1
5785		10.67	10±1	11	12.589	4.33	2.71	0.0068	1
5825		10.08	10±1	11	12.589	4.33	2.71	0.0068	1
5745	802.11n H20	10.68	10±1	11	12.589	4.33	2.71	0.0068	1
5785		10.86	10±1	11	12.589	4.33	2.71	0.0068	1
5825		10.14	10±1	11	12.589	4.33	2.71	0.0068	1

Signature:

Date: 2022-11-10



NAME AND TITLE (Please print or type): alex li/Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.