



FCC RADIO TEST REPORT

FCC ID : 2AWRO-8432
Equipment : Wireless Tablet
Model Name : P5N8EC
Applicant : Abyssal Plain LLC
CASTLE HILLS 1100 NW LOOP 410, SUITE 700, SAN ANTONIO, TEXAS, 78213
Standard : FCC Part 15 Subpart C §15.225

The product was received on Dec. 07, 2022 and testing was performed from Dec. 08, 2022 to Dec. 24, 2022. We, Sporton International Inc. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

Sportun International Inc. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1. General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	5
1.3 Modification of EUT	5
1.4 Testing Location	6
1.5 Applicable Standards.....	6
2. Test Configuration of Equipment Under Test.....	7
2.1 Descriptions of Test Mode.....	7
2.2 Connection Diagram of Test System.....	8
2.3 Table for Supporting Units.....	9
2.4 EUT Operation Test Setup	9
3. Test Results	10
3.1 AC Power Line Conducted Emissions Measurement	10
3.2 20dB and 99% OBW Spectrum Bandwidth Measurement.....	12
3.3 Frequency Stability Measurement	13
3.4 Field Strength of Fundamental Emissions and Mask Measurement.....	14
3.5 Radiated Emissions Measurement.....	16
3.6 Antenna Requirements.....	19
4. List of Measuring Equipment	20
5. Uncertainty of Evaluation	21

Appendix A. Test Results of Conducted Emission Test

Appendix B. Test Results of Near Field Test Items

- B1. Test Result of 20dB Spectrum Bandwidth
- B2. Test Result of Frequency Stability

Appendix C. Test Results of Radiated Test Items

- C1. Test Result of Field Strength of Fundamental Emissions
- C2. Results of Radiated Emissions (9 kHz~30MHz)
- C3. Results of Radiated Emissions (30MHz~1GHz)



History of this test report



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)
3.1	15.207	AC Power Line Conducted Emissions	Pass
3.2	15.215(c)	20dB Spectrum Bandwidth	Pass
	2.1049	99% OBW Spectrum Bandwidth	Reporting only
3.3	15.225(e)	Frequency Stability	Pass
3.4	15.225(a)(b)(c)	Field Strength of Fundamental Emissions	Pass
3.5	15.225(d) 15.209	Radiated Spurious Emissions	Pass
3.6	15.203	Antenna Requirements	Pass

Declaration of Conformity:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers. It's means measurement values may risk exceeding the limit of regulation standards, if measurement uncertainty is include in test results.
2. The measurement uncertainty please refer to report "Uncertainty of Evaluation".

Comments and Explanations:

The product specifications of the EUT presented in the report are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Alan Liu

Report Producer: Dewi Huang



1. General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Wireless Tablet
Model Name	P5N8EC
FCC ID	2AWRO-8432
EUT supports Radios application	NFC/GNSS/WPT Client WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE

1.2 Product Specification of Equipment Under Test

Product Specification is subject to this standard	
Tx/Rx Frequency	13.553 ~ 13.567MHz
Channel Number	1
Antenna Type	Loop Antenna
Type of Modulation	ASK

1.3 Modification of EUT

No modifications made to the EUT during the testing.



1.4 Testing Location

Test Site	Sportun International Inc. EMC & Wireless Communications Laboratory		
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	Sportun Site No.		
	TH03-HY	CO05-HY	03CH07-HY
Test Engineer	Louis Chung	Tom Lee and Calvin Wang	Stan Hsieh and Ken Wu
Temperature	21.2~24.6 °C	23~26 °C	16.5 ~18.8 °C
Relative Humidity	64.2~68.7 %	45~55 %	49.3~53.6 %

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190

1.5 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.225
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.



2. Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Investigation has been done on all the possible configurations.

The following table is a list of the test modes shown in this test report.

Test Items	
AC Power Line Conducted Emissions	Field Strength of Fundamental Emissions
20dB Spectrum Bandwidth	Frequency Stability
Radiated Emissions 9kHz~30MHz	Radiated Emissions 30MHz~1GHz

The EUT pre-scanned in reader mode with NFC tag (four NFC type A, B, F, V) and without reading tag.


Based on the highest field strength of fundamental and spurious emissions, the worst case type (type F) was recorded in this report.

The measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10exploratory test procedures and only the worst case emissions were reported in this report.


Test Cases	
AC Conducted Emission	Mode 1: WLAN (5GHz) Idle + Bluetooth Idle + NFC Read + MicroSD card + Earphone + USB Cable (Charging from Adapter)

2.2 Connection Diagram of Test System

<AC Conducted Emission Mode>



< NFC Tx Mode>





2.3 Table for Supporting Units

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	GPS Station	Pendulum	GSG-54	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
3.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A
4.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
5.	NFC Card	N/A	N/A	N/A	N/A	N/A
6.	Earphone	N/A	N/A	N/A	Unshielded, 1.15 m	N/A
7.	Adapter	Liteon	PS57CP	N/A	N/A	N/A

2.4 EUT Operation Test Setup

The EUT is programmed to be in continuously transmitting mode.

The ancillary equipment, NFC card, is used to make the EUT (NFC) continuously transmitting signal (Power Level: Default) at 13.56MHz and is placed around 0 cm gap to the EUT.



3. Test Results

3.1 AC Power Line Conducted Emissions Measurement

3.1.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

For terminal test result, the testing follows FCC KDB 174176.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.1.4 Test setup



3.1.5 Test Result of AC Conducted Emission

Please refer to Appendix A.

Note:

(1) with antenna

Remark: 13.560MHz is the NFC RF fundamental signal.

(2) with dummy load

Remark: Only the fundamental NFC signal needs to be retested per C63.4.

3.2 20dB and 99% OBW Spectrum Bandwidth Measurement

3.2.1 Limit

Intentional radiators must be designed to ensure that the 20 dB and 99% emission bandwidth in the specific band 13.553~13.567 MHz.


3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max Hold Mode.
2. The resolution bandwidth of 1 kHz and the video bandwidth of 3 kHz were used.
3. Measured the spectrum width with power higher than 20 dB below carrier.
4. Measured the 99% OBW.

3.2.4 Test Setup



3.2.5 Test Result of Near Field Test Items

Please refer to Appendix B.

3.3 Frequency Stability Measurement

3.3.1 Limit

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed by using a new battery.


3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT.
2. EUT has transmitted signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire emissions bandwidth.
4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
5. The fc is declaring of channel frequency. Then the frequency error formula is $(fc-f)/fc \times 10^6$ ppm and the limit is less than +/-100ppm.
6. Extreme temperature rule is -20°C~50°C.

3.3.4 Test Setup



3.3.5 Test Result of Near Field Test Items

Please refer to Appendix B.



3.4 Field Strength of Fundamental Emissions and Mask Measurement

3.4.1 Limit

Rules and specifications		FCC CFR 47 Part 15 section 15.225			
Description	Compliance with the spectrum mask is tested with RBW set to 9kHz.				
Freq. of Emission (MHz)	Field Strength (μ V/m) at 30m	Field Strength (dB μ V/m) at 30m	Field Strength (dB μ V/m) at 10m	Field Strength (dB μ V/m) at 3m	
1.705~13.110	30	29.5	48.58	69.5	
13.110~13.410	106	40.5	59.58	80.5	
13.410~13.553	334	50.5	69.58	90.5	
13.553~13.567	15848	84.0	103.08	124.0	
13.567~13.710	334	50.5	69.58	90.5	
13.710~14.010	106	40.5	59.58	80.5	
14.010~30.000	30	29.5	48.58	69.5	

Remark:

1. The field strength test result is in 3m test distance, follow test rules the test data use distance extrapolation factor and reported in this report at 30m test result.
2. Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB)

3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.


3.4.3 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT is placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower is placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable is rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the receiving antenna is fixed at one meter above ground to find the maximum emissions field strength.
4. For Fundamental emissions, use the receiver to measure QP reading.
5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
6. Compliance with the spectrum mask is tested with RBW set to 9 kHz.

Note: Emission level (dB μ V/m) = 20 log Emission level (μ V/m).

3.4.4 Test Setup

For radiated test below 30MHz



3.4.5 Test Result of Field Strength of Fundamental Emissions and Mask

Please refer to Appendix C.



3.5 Radiated Emissions Measurement

3.5.1 Limit

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed the general radiated emissions limits.

Frequencies (MHz)	Field Strength (μ V/m)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Measuring Instrument Setting

The following table is the setting of receiver:

Receiver Parameter	Setting
Attenuation	Auto
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak

Note: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz and 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.




3.5.4 Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT is placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower is placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable is rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna is varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower is scanned (from 1 M to 4 M) and then the turntable is rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
7. In case the emission is lower than 30 MHz, loop antenna has to be used for measurement and the recorded data shall be QP measured by receiver.
8. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.

3.5.5 Test Setup

For radiated test below 30MHz



For radiated test above 30MHz



3.5.6 Test Result of Radiated Emissions Measurement

Please refer to Appendix C.

Remark: There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.



3.6 Antenna Requirements

3.6.1 Standard Applicable

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.



4. List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N-06	35419 & 03	30MHz~1GHz	Apr. 24, 2022	Dec. 23, 2022~Dec. 24, 2022	Apr. 23, 2023	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz~1GHz	Oct. 03, 2022	Dec. 23, 2022~Dec. 24, 2022	Oct. 02, 2023	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY15682/4	30MHz to 18GHz	Feb. 23, 2022	Dec. 23, 2022~Dec. 24, 2022	Feb. 22, 2023	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24971/4	9kHz to 18GHz	Feb. 23, 2022	Dec. 23, 2022~Dec. 24, 2022	Feb. 22, 2023	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/4	9kHz to 18GHz	Feb. 23, 2022	Dec. 23, 2022~Dec. 24, 2022	Feb. 22, 2023	Radiation (03CH07-HY)
Controller	EMEC	EM1000	N/A	Control Ant Mast	N/A	Dec. 23, 2022~Dec. 24, 2022	N/A	Radiation (03CH07-HY)
Controller	MF	MF-7802	N/A	Control Turn table	N/A	Dec. 23, 2022~Dec. 24, 2022	N/A	Radiation (03CH07-HY)
Antenna Mast	EMEC	AM-BS-4500E	N/A	Boresight mast 1M~4M	N/A	Dec. 23, 2022~Dec. 24, 2022	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Dec. 23, 2022~Dec. 24, 2022	N/A	Radiation (03CH07-HY)
Software	Audix	E3	N/A	N/A	N/A	Dec. 23, 2022~Dec. 24, 2022	N/A	Radiation (03CH07-HY)
USB Data Logger	TECPEL	TR-32	HE17XB2495	N/A	Mar. 07, 2022	Dec. 23, 2022~Dec. 24, 2022	Mar. 06, 2023	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Sep. 20, 2022	Dec. 23, 2022~Dec. 24, 2022	Sep. 19, 2023	Radiation (03CH07-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY57290111	3Hz~26.5GHz	Dec. 15, 2022	Dec. 23, 2022~Dec. 24, 2022	Dec. 14, 2023	Radiation (03CH07-HY)
Hygrometer	TECPEL	DTM-303B	TP200735	N/A	Mar. 04, 2022	Dec. 08, 2022~Dec. 23, 2022	Mar. 03, 2023	Conducted (TH03-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP7	101131	9kHz~7GHz	Aug. 17, 2022	Dec. 08, 2022~Dec. 23, 2022	Aug. 16, 2023	Conducted (TH03-HY)
Temperature & Humidity Cabinet Chamber	ESPEC	SU-641	92013721	-30°C ~70°C	Oct. 17, 2022	Dec. 08, 2022~Dec. 23, 2022	Oct. 16, 2023	Conducted (TH03-HY)
Nearby field probe	LANGER EMV-TECHNIK	LF-U5	02-559	100 kHz up to 50 MHz	Apr. 04, 2022	Dec. 08, 2022~Dec. 23, 2022	Apr. 03, 2023	Conducted (TH03-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Dec. 16, 2022~Dec. 20, 2022	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Dec. 01, 2022	Dec. 16, 2022~Dec. 20, 2022	Nov. 30, 2023	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Nov. 17, 2022	Dec. 16, 2022~Dec. 20, 2022	Nov. 16, 2023	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 17, 2022	Dec. 16, 2022~Dec. 20, 2022	Nov. 16, 2023	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32	N/A	N/A	N/A	Dec. 16, 2022~Dec. 20, 2022	N/A	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	00691	N/A	Aug. 01, 2022	Dec. 16, 2022~Dec. 20, 2022	Jul. 31, 2023	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	260260	N/A	Dec. 30, 2021	Dec. 16, 2022~Dec. 20, 2022	Dec. 29, 2022	Conduction (CO05-HY)



5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	3.5 dB
---	--------

Uncertainty of Radiated Emission Measurement (9 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	3.8 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	6.50 dB
---	---------




Appendix A. Test Results of Conducted Emission Test

Test Engineer :	Tom Lee and Calvin Wang	Temperature :	23~26°C
		Relative Humidity :	45~55%

Original

Report NO : 2D0516
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Line

Full Spectrum




Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.161250	---	36.96	55.40	18.44	L1	OFF	19.8
0.161250	51.06	---	65.40	14.34	L1	OFF	19.8
0.170250	---	41.39	54.95	13.56	L1	OFF	19.8
0.170250	52.92	---	64.95	12.03	L1	OFF	19.8
0.197250	---	34.86	53.73	18.87	L1	OFF	19.8
0.197250	47.74	---	63.73	15.99	L1	OFF	19.8
0.231000	---	32.33	52.41	20.08	L1	OFF	19.8
0.231000	45.55	---	62.41	16.86	L1	OFF	19.8
0.267000	---	31.66	51.21	19.55	L1	OFF	19.8
0.267000	42.43	---	61.21	18.78	L1	OFF	19.8
0.296250	---	29.83	50.35	20.52	L1	OFF	19.8
0.296250	39.78	---	60.35	20.57	L1	OFF	19.8
0.330000	---	27.70	49.45	21.75	L1	OFF	19.8
0.330000	37.97	---	59.45	21.48	L1	OFF	19.8
0.478500	---	27.68	46.37	18.69	L1	OFF	19.8
0.478500	33.74	---	56.37	22.63	L1	OFF	19.8
10.977000	---	26.13	50.00	23.87	L1	OFF	20.2
10.977000	27.84	---	60.00	32.16	L1	OFF	20.2
13.560000	---	61.61	50.00	-11.61	L1	OFF	20.3
13.560000	63.22	---	60.00	-3.22	L1	OFF	20.3
27.120000	---	33.64	50.00	16.36	L1	OFF	20.7

27.120000	36.65	---	60.00	23.35	L1	OFF	20.7
-----------	-------	-----	-------	-------	----	-----	------

Report NO : 2D0516
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Neutral

Full Spectrum




Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.161250	---	32.41	55.40	22.99	N	OFF	19.8
0.161250	45.74	---	65.40	19.66	N	OFF	19.8
0.206250	---	31.91	53.36	21.45	N	OFF	19.8
0.206250	43.57	---	63.36	19.79	N	OFF	19.8
0.235500	---	30.96	52.25	21.29	N	OFF	19.8
0.235500	42.45	---	62.25	19.80	N	OFF	19.8
0.267000	---	29.42	51.21	21.79	N	OFF	19.8
0.267000	38.65	---	61.21	22.56	N	OFF	19.8
0.519000	---	29.85	46.00	16.15	N	OFF	19.8
0.519000	34.29	---	56.00	21.71	N	OFF	19.8
5.754750	---	26.10	50.00	23.90	N	OFF	20.0
5.754750	27.59	---	60.00	32.41	N	OFF	20.0
13.560000	---	61.55	50.00	-11.55	N	OFF	20.4
13.560000	63.17	---	60.00	-3.17	N	OFF	20.4
27.120000	---	33.66	50.00	16.34	N	OFF	20.8
27.120000	36.71	---	60.00	23.29	N	OFF	20.8

Terminal

Report NO : 2D0516
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Line


Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
13.560000	---	25.03	50.00	24.97	L1	OFF	20.3
13.560000	26.45	---	60.00	33.55	L1	OFF	20.3

Report NO : 2D0516
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Neutral





Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
13.560000	---	25.14	50.00	24.86	N	OFF	20.4
13.560000	26.35	---	60.00	33.65	N	OFF	20.4

Appendix B. Test Results of Near Field Test Items

B1. Test Result of 20dB Spectrum Bandwidth

Test mode	NFC Tx	Test Frequency (MHz)	13.56
 NFC Tx	 <p>Ref -10 dBm Att 30 dB SWT 20 ms 13.559860000 MHz</p> <p>Marker 1 [T1] -18.71 dBm RBW 1 kHz VBW 3 kHz Temp 1 [T1 noise]</p> <p>ndB [T1] 20.00 dB BW 2.640000000 kHz Temp 1 [T1 noise]</p> <p>-10 -20 -30 -40 -50 -60 -70 -80 -90 -100 -110</p> <p>13.558500000 MHz -38.66 dBm Temp 2 [T1 noise]</p> <p>-10 -20 -30 -40 -50 -60 -70 -80 -90 -100 -110</p> <p>13.561140000 MHz -38.75 dBm Temp 2 [T1 noise]</p> <p>3dB</p> <p>3dB</p> <p>Center 13.56 MHz 1 kHz/ Span 10 kHz</p>	 NFC Tx	 <p>Ref -10 dBm Att 30 dB SWT 20 ms 13.559860000 MHz</p> <p>Marker 1 [T1] -17.68 dBm RBW 1 kHz VBW 3 kHz Temp 1 [T1 OBW]</p> <p>OBW 2.240000000 kHz Temp 1 [T1 OBW] -32.31 dBm 13.558700000 MHz Temp 2 [T1 OBW] -32.18 dBm 13.560940000 MHz</p> <p>-10 -20 -30 -40 -50 -60 -70 -80 -90 -100 -110</p> <p>Center 13.56 MHz 1 kHz/ Span 10 kHz</p>
20dB Bandwidth (kHz)	2.640	99% OccupiedBW(kHz)	2.240
Frequency range (MHz)	$f_L > 13.558$	13.55850	Test Result
	$f_H < 13.561$	13.56114	Complies

Remark: Because the measured signal is CW adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.

**B2. Test Result of Frequency Stability**

Voltage vs. Frequency Stability		Temperature vs. Frequency Stability		
Voltage (Vdc)	Measurement Frequency (MHz)	Temperature (°C)	Time	Measurement Frequency (MHz)
3.4	13.559820	-11	0	13.559940
3.87	13.559820		2	13.559940
4.4	13.559860		5	13.559930
			10	13.559930
		0	0	13.559930
			2	13.559930
			5	13.559920
			10	13.559920
		10	0	13.559900
			2	13.559890
			5	13.559880
			10	13.559880
		20	0	13.559820
			2	13.559820
			5	13.559820
			10	13.559860
		30	0	13.559820
			2	13.559800
			5	13.559800
			10	13.559800
		40	0	13.559780
			2	13.559780
			5	13.559780
			10	13.559780




Voltage vs. Frequency Stability		Temperature vs. Frequency Stability		
Voltage (Vdc)	Measurement Frequency (MHz)	Temperature (°C)	Time	Measurement Frequency (MHz)
		50	0	13.559770
			2	13.559770
			5	13.559770
			10	13.559780
Max.Deviation (MHz)	-0.000180	Max.Deviation (MHz)		-0.000230
Max.Deviation (ppm)	-13.2743	Max.Deviation (ppm)		-16.9617
Limit	FS < ±100 ppm	Limit		FS < ±100 ppm
Test Result	PASS	Test Result		PASS


Note: *-12~-20°C will automatically shut down and there will be no NFC signal transmission, so there is no test for -12~-20°C.



Appendix C. Test Results of Radiated Test Items

C1. Test Result of Field Strength of Fundamental Emissions




**Note :**

1. Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB)
2. Level = Antenna Factor + Cable Loss + Read Level - Distance extrapolation factor.



C2. Results of Radiated Spurious Emissions (9 kHz~30MHz)


Test Mode :		NFC Tx		Polarization :		Horizontal								
									Date: 2022-12-24					
Site : 03CH07-HY Condition : 15.209 LIMIT LINE 3m LOOP_ANT(H)_100488 HORIZONTAL														
Frequency (MHz)	Level (dB μ V/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark				
0.05006	-20.01	80	-53.63	33.62	40.27	19.7	0.02	-	-	Average				
0.06012	-28.13	80	-60.15	32.02	32.15	19.7	0.02	-	-	Average				
0.09746	-44.86	80	-72.69	27.83	15.49	19.63	0.02	-	-	QP				
0.15	-37.39	80	-61.47	24.08	22.98	19.6	0.03	-	-	Average				
0.15034	-30.29	80	-54.35	24.06	30.08	19.6	0.03	-	-	Average				
0.55008	-3.06	40	-35.86	32.8	17.36	19.5	0.08	-	-	QP				
9.128	-3.97	40	-33.47	29.5	16.31	19.4	0.32	-	-	QP				
13.56	18.49	40	-11.01	29.5	38.7	19.4	0.39	-	-	QP				
17.359	-3.77	40	-33.27	29.5	16.26	19.5	0.47	-	-	QP				
27.27	-4.46	40	-33.96	29.5	14.57	20.2	0.77	-	-	QP				


**Note :**

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB)
3. Level = Antenna Factor + Cable Loss + Read Level - Distance extrapolation factor.
4. 13.56 MHz is fundamental signal which can be ignored



C3. Results of Radiated Spurious Emissions (30MHz~1GHz)

Test Mode :	NFC Tx	Polarization :	Horizontal																																																																													
			Date: 2022-12-24																																																																													
Site : 03CH07-HY Condition : QP 3m LF-ANT-35419(6) HORIZONTAL																																																																																
<table border="1"><thead><tr><th>Frequency (MHz)</th><th>Level (dBμV/m)</th><th>Over Limit (dB)</th><th>Limit Line (dBμV/m)</th><th>Read Level (dBμV)</th><th>Antenna Factor (dB)</th><th>Cable Loss (dB)</th><th>Preamp Factor (dB)</th><th>Ant Pos (cm)</th><th>Table Pos (deg)</th><th>Remark</th></tr></thead><tbody><tr><td>94.8</td><td>33</td><td>-10.5</td><td>43.5</td><td>46.32</td><td>15.15</td><td>1.55</td><td>30.02</td><td>-</td><td>-</td><td>Peak</td></tr><tr><td>192.27</td><td>26.65</td><td>-16.85</td><td>43.5</td><td>39.71</td><td>14.71</td><td>2.26</td><td>30.03</td><td>-</td><td>-</td><td>Peak</td></tr><tr><td>248.43</td><td>31.12</td><td>-14.88</td><td>46</td><td>40.37</td><td>18.1</td><td>2.56</td><td>29.91</td><td>-</td><td>-</td><td>Peak</td></tr><tr><td>496.7</td><td>34.34</td><td>-11.66</td><td>46</td><td>36.84</td><td>23.73</td><td>3.73</td><td>29.96</td><td>-</td><td>-</td><td>Peak</td></tr><tr><td>775.3</td><td>30.6</td><td>-15.4</td><td>46</td><td>27.76</td><td>27.83</td><td>4.67</td><td>29.66</td><td>-</td><td>-</td><td>Peak</td></tr><tr><td>937</td><td>33.2</td><td>-12.8</td><td>46</td><td>27.43</td><td>29.5</td><td>5.15</td><td>28.88</td><td>-</td><td>-</td><td>Peak</td></tr></tbody></table>				Frequency (MHz)	Level (dB μ V/m)	Over Limit (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark	94.8	33	-10.5	43.5	46.32	15.15	1.55	30.02	-	-	Peak	192.27	26.65	-16.85	43.5	39.71	14.71	2.26	30.03	-	-	Peak	248.43	31.12	-14.88	46	40.37	18.1	2.56	29.91	-	-	Peak	496.7	34.34	-11.66	46	36.84	23.73	3.73	29.96	-	-	Peak	775.3	30.6	-15.4	46	27.76	27.83	4.67	29.66	-	-	Peak	937	33.2	-12.8	46	27.43	29.5	5.15	28.88	-	-	Peak
Frequency (MHz)	Level (dB μ V/m)	Over Limit (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark																																																																						
94.8	33	-10.5	43.5	46.32	15.15	1.55	30.02	-	-	Peak																																																																						
192.27	26.65	-16.85	43.5	39.71	14.71	2.26	30.03	-	-	Peak																																																																						
248.43	31.12	-14.88	46	40.37	18.1	2.56	29.91	-	-	Peak																																																																						
496.7	34.34	-11.66	46	36.84	23.73	3.73	29.96	-	-	Peak																																																																						
775.3	30.6	-15.4	46	27.76	27.83	4.67	29.66	-	-	Peak																																																																						
937	33.2	-12.8	46	27.43	29.5	5.15	28.88	-	-	Peak																																																																						

**Note:**

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dB μ V/m) = 20 log Emission level (μ V/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level.
4. The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only.

—————THE END—————