

TEST REPORT

Applicant: Sealoc

Address of Applicant: 1720 Bray Central Dr Suite 100-X McKinney TX 75069 USA

Manufacturer/Factory : Shenzhen Sunnyslink Technology Co.,Ltd

Address of Manufacturer/Factory : 3F, Building A1, NO.2082, Jincheng Road, Haoer Community, Shajing Street, Baoan District, Shenzhen

Equipment Under Test (EUT)

Product Name: OUTDOOR SOUNDBAR

Model No.: SB621

Trade Mark: SEALOC

FCC ID: 2AWTH-SB621

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of sample receipt: July 05, 2020

Date of Test: July 05-July 20, 2020

Date of report issued: July 20, 2020

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

A circular blue ink seal for GTS Global United Technology Services Co., Ltd. is stamped over a handwritten signature in black ink. The signature appears to read 'Robinson Lo' and 'July 20, 2020'. The seal contains the text 'GTS', 'GLOBAL UNITED TECHNOLOGY SERVICES CO., LTD.', and 'LABORATORY TESTING'.

Robinson Lo

Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	July 20, 2020	Original

Prepared By:




Date:

July 20, 2020

Project Engineer

Check By:



Date:

July 20, 2020

Reviewer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	7
5.3 DESCRIPTION OF SUPPORT UNITS	7
5.4 DEVIATION FROM STANDARDS	7
5.5 ABNORMALITIES FROM STANDARD CONDITIONS	7
5.6 TEST FACILITY	7
5.7 TEST LOCATION	7
6 TEST INSTRUMENTS LIST	8
7 TEST RESULTS AND MEASUREMENT DATA	10
7.1 ANTENNA REQUIREMENT	10
7.2 CONDUCTED EMISSIONS	11
7.3 CONDUCTED PEAK OUTPUT POWER	14
7.4 20dB EMISSION BANDWIDTH	21
7.5 CARRIER FREQUENCIES SEPARATION	28
7.6 HOPPING CHANNEL NUMBER	35
7.7 DWELL TIME	38
7.8 PSEUDORANDOM FREQUENCY HOPPING SEQUENCE	46
7.9 BAND EDGE	47
7.9.1 Conducted Emission Method	47
7.9.2 Radiated Emission Method	51
7.10 SPURIOUS EMISSION	53
7.10.1 Conducted Emission Method	53
7.10.2 Radiated Emission Method	60
8 TEST SETUP PHOTO	68
9 EUT CONSTRUCTIONAL DETAILS	68

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna Requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(1)	Pass
20dB Occupied Bandwidth	15.247 (a)(1)	Pass
Carrier Frequencies Separation	15.247 (a)(1)	Pass
Hopping Channel Number	15.247 (a)(1)	Pass
Dwell Time	15.247 (a)(1)	Pass
Pseudorandom Frequency Hopping Sequence	15.247(b)(4)	Pass
Radiated Emission	15.205/15.209	Pass
Band Edge	15.247(d)	Pass

Remarks:

1. Pass: The EUT complies with the essential requirements in the standard.
2. Test according to ANSI C63.10:2013

Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	30MHz-200MHz	3.8039dB	(1)
Radiated Emission	200MHz-1GHz	3.9679dB	(1)
Radiated Emission	1GHz-18GHz	4.29dB	(1)
Radiated Emission	18GHz-40GHz	3.30dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	3.44dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product Name:	OUTDOOR SOUNDBAR
Model No.:	SB621
Test sample(s) ID:	GTS202007000030-1
Sample(s) Status:	Engineer sample
Serial No.:	N/A
Hardware Version:	H1.0
Software Version:	S1.0
Operation Frequency:	2402MHz~2480MHz
Channel numbers:	79
Channel separation:	1MHz
Modulation type:	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Antenna Type:	PCB Antenna
Antenna gain:	0dBi
Power supply:	DC 12V,6.5A Form Adapter AC 100-240V,50/60Hz

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
<i>Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

5.3 Description of Support Units

None.

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations: ● FCC —Registration No.: 381383 Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383. ● IC —Registration No.: 9079A The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A ● NVLAP (LAB CODE:600179-0) Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP). LAB CODE:600179-0

5.7 Test Location

All tests were performed at:
Global United Technology Services Co., Ltd. Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 02 2020	July. 01 2025
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 25 2020	June. 24 2021
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 25 2020	June. 24 2021
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 25 2020	June. 24 2021
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 25 2020	June. 24 2021
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 25 2020	June. 24 2021
9	Coaxial Cable	GTS	N/A	GTS211	June. 25 2020	June. 24 2021
10	Coaxial cable	GTS	N/A	GTS210	June. 25 2020	June. 24 2021
11	Coaxial Cable	GTS	N/A	GTS212	June. 25 2020	June. 24 2021
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 25 2020	June. 24 2021
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 25 2020	June. 24 2021
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 25 2020	June. 24 2021
15	Band filter	Amindeon	82346	GTS219	June. 25 2020	June. 24 2021
16	Power Meter	Anritsu	ML2495A	GTS540	June. 25 2020	June. 24 2021
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 25 2020	June. 24 2021
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 25 2020	June. 24 2021
19	Splitter	Agilent	11636B	GTS237	June. 25 2020	June. 24 2021
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 25 2020	June. 24 2021
21	Breitband hornantenne	SCHWARZBECK	BBHA 9170	GTS579	Oct. 19 2019	Oct. 18 2020
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 19 2019	Oct. 18 2020
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 19 2019	Oct. 18 2020
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June. 25 2020	June. 24 2021

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.15 2019	May.14 2022
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 25 2020	June. 24 2021
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June. 25 2020	June. 24 2021
4	ENV216 2-L-V-NETZNACHB.DE	ROHDE&SCHWARZ	ENV216	GTS226	June. 25 2020	June. 24 2021
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June. 25 2020	June. 24 2021
8	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	June. 25 2020	June. 24 2021
9	ISN	SCHWARZBECK	NTFM 8158	GTD565	June. 25 2020	June. 24 2021

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	June. 25 2020	June. 24 2021
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 25 2020	June. 24 2021
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June. 25 2020	June. 24 2021
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	June. 25 2020	June. 24 2021
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	June. 25 2020	June. 24 2021
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	June. 25 2020	June. 24 2021
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	June. 25 2020	June. 24 2021
8	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	June. 25 2020	June. 24 2021

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	June. 25 2020	June. 24 2021
2	Barometer	ChangChun	DYM3	GTS255	June. 25 2020	June. 24 2021

7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
E.U.T Antenna:	
<i>The antenna is PCB antenna, the best case gain of the is 0dBi, reference to the appendix II for details</i>	

7.2 Conducted Emissions


Test Requirement:	FCC Part15 C Section 15.207						
Test Method:	ANSI C63.10:2013						
Test Frequency Range:	150KHz to 30MHz						
Class / Severity:	Class B						
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto						
Limit:	Frequency range (MHz)		Limit (dBuV)				
			Quasi-peak		Average		
	0.15-0.5		66 to 56*		56 to 46*		
	0.5-5		56		46		
	5-30		60		50		
* Decreases with the logarithm of the frequency.							
Test setup:	Reference Plane Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m						
Test procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.						
Test Instruments:	Refer to section 6.0 for details						
Test mode:	Refer to section 5.2 for details						
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar	
Test voltage:	AC 120V, 60Hz						
Test results:	Pass						

Remark: Both high and low voltages have been tested to show only the worst low voltage test data.

Measurement data:

Line:


90.0 dBuV



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.3975	32.42	11.01	43.43	57.91	-14.48	QP	P	
2	0.3975	25.49	11.01	36.50	47.91	-11.41	AVG	P	
3	1.0500	11.40	10.43	21.83	56.00	-34.17	QP	P	
4	1.1040	-0.66	10.41	9.75	46.00	-36.25	AVG	P	
5	2.0040	11.08	10.19	21.27	56.00	-34.73	QP	P	
6	2.0040	2.11	10.19	12.30	46.00	-33.70	AVG	P	
7	6.0000	13.61	8.61	22.22	60.00	-37.78	QP	P	
8	6.3150	10.30	8.60	18.90	50.00	-31.10	AVG	P	
9	12.1155	15.64	8.76	24.40	60.00	-35.60	QP	P	
10	12.2910	4.87	8.78	13.65	50.00	-36.35	AVG	P	
11	18.8070	20.80	9.69	30.49	60.00	-29.51	QP	P	
12	18.8070	8.43	9.69	18.12	50.00	-31.88	AVG	P	

Neutral:

00.0 dBuV




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.3975	32.42	11.01	43.43	57.91	-14.48	QP	P	
2	0.3975	25.95	11.01	36.96	47.91	-10.95	AVG	P	
3	1.1805	12.45	10.39	22.84	56.00	-33.16	QP	P	
4	1.1849	5.29	10.39	15.68	46.00	-30.32	AVG	P	
5	3.2370	1.97	9.79	11.76	46.00	-34.24	AVG	P	
6	3.3585	11.40	9.71	21.11	56.00	-34.89	QP	P	
7	8.8260	17.60	8.51	26.11	60.00	-33.89	QP	P	
8	8.8260	10.44	8.51	18.95	50.00	-31.05	AVG	P	
9	13.2315	13.94	8.91	22.85	60.00	-37.15	QP	P	
10	13.2315	5.08	8.91	13.99	50.00	-36.01	AVG	P	
11	15.6660	17.83	9.25	27.08	60.00	-32.92	QP	P	
12	15.6660	5.97	9.25	15.22	50.00	-34.78	AVG	P	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss

7.3 Conducted Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	ANSI C63.10:2013
Limit:	30dBm(for GFSK),20.97dBm(for EDR)
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data

Mode	Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
GFSK	Lowest	-2.721	30.00	Pass
	Middle	-2.472		
	Highest	-2.419		
$\pi/4$ -DQPSK	Lowest	-3.839	20.97	Pass
	Middle	-3.554		
	Highest	-3.514		
8-DPSK	Lowest	-4.221	20.97	Pass
	Middle	-4.074		
	Highest	-3.949		


Test plot as follows:

Test mode:	GFSK mode
------------	-----------


Lowest channel



Middle channel




Highest channel




Test mode:	$\pi/4$ -DQPSK mode
------------	---------------------


Lowest channel



Middle channel




Highest channel




Test mode:

8-DPSK mode


Lowest channel




Middle channel



Highest channel



7.4 20dB Emission Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	ANSI C63.10:2013
Limit:	N/A
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Mode	Test channel	20dB Emission Bandwidth (MHz)	Result
GFSK	Lowest	1.036	Pass
	Middle	1.039	
	Highest	1.036	
$\pi/4$ -DQPSK	Lowest	1.318	Pass
	Middle	1.340	
	Highest	1.320	
8-DPSK	Lowest	1.309	Pass
	Middle	1.313	
	Highest	1.367	


Test plot as follows:

Test mode:	GFSK mode
------------	-----------

Lowest channel



Middle channel




Highest channel




Test mode:	$\pi/4$ -DQPSK mode
------------	---------------------


Lowest channel



Middle channel




Highest channel




Test mode:

8-DPSK mode


Lowest channel




Middle channel



Highest channel



7.5 Carrier Frequencies Separation

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100KHz, VBW=300KHz, detector=Peak
Limit:	GFSK: 20dB bandwidth $\pi/4$ -DQPSK & 8DSK: 0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Mode	Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
GFSK	Lowest	1083	691	Pass
	Middle	1008	693	Pass
	Highest	982	691	Pass
$\pi/4$ -DQPSK	Lowest	1005	879	Pass
	Middle	938	893	Pass
	Highest	902	880	Pass
8-DPSK	Lowest	895	873	Pass
	Middle	1005	875	Pass
	Highest	984	911	Pass

Test plot as follows:

Modulation mode:	GFSK
------------------	------

Lowest channel



Middle channel




Highest channel




Test mode:

$\pi/4$ -DQPSK


Lowest channel



Middle channel




Highest channel




Test mode:

8-DPSK


Lowest channel




Middle channel



Highest channel





7.6 Hopping Channel Number

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100kHz, VBW=300kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak
Limit:	15 channels
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data:

Mode	Hopping channel numbers	Limit	Result
GFSK	79	15	Pass
$\pi/4$ -DQPSK	79	15	Pass
8-DPSK	79	15	Pass


Test plot as follows:



Test mode:	8-DPSK
------------	--------



7.7 Dwell Time

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=1MHz, VBW=1MHz, Span=0Hz, Detector=Peak
Limit:	0.4 Second
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. The table is supported by two vertical legs. Below the table is a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data**GFSK mode:**

Frequency	Packet	Dwell time(ms)	Limit(ms)	Result
2441MHz	DH1	82.24	400	Pass
2441MHz	DH3	242.08	400	Pass
2441MHz	DH5	294.51	400	Pass

Remarks:

The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

Test channel: 2441MHz as blow

DH1 time slot = $0.257(\text{ms}) \times (1600 / (2 \times 79)) \times 31.6 = 82.24\text{ms}$

DH3 time slot = $1.513(\text{ms}) \times (1600 / (4 \times 79)) \times 31.6 = 242.08\text{ms}$

DH5 time slot = $2.761(\text{ms}) \times (1600 / (6 \times 79)) \times 31.6 = 294.51\text{ms}$

 $\pi/4$ -DQPSK mode:

Frequency	Packet	Dwell time(ms)	Limit(ms)	Result
2441MHz	2DH1	85.76	400	Pass
2441MHz	2DH3	243.20	400	Pass
2441MHz	2DH5	295.36	400	Pass

Remarks:

The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

Test channel: 2441MHz as blow

DH1 time slot = $0.268(\text{ms}) \times (1600 / (2 \times 79)) \times 31.6 = 85.76\text{ms}$

DH3 time slot = $1.520(\text{ms}) \times (1600 / (4 \times 79)) \times 31.6 = 243.20\text{ms}$

DH5 time slot = $2.769(\text{ms}) \times (1600 / (6 \times 79)) \times 31.6 = 295.36\text{ms}$

8-DPSK mode:

Frequency	Packet	Dwell time(ms)	Limit(ms)	Result
2441MHz	3DH1	86.40	400	Pass
2441MHz	3DH3	243.04	400	Pass
2441MHz	3DH5	295.36	400	Pass

Remarks:

The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

Test channel: 2441MHz as blow

DH1 time slot = $0.270(\text{ms}) \times (1600 / (2 \times 79)) \times 31.6 = 86.40\text{ms}$

DH3 time slot = $1.519(\text{ms}) \times (1600 / (4 \times 79)) \times 31.6 = 243.04\text{ms}$


DH5 time slot = $2.769(\text{ms}) \times (1600 / (6 \times 79)) \times 31.6 = 295.36\text{ms}$

Test plot as follows:


GFSK mode:

Test channel:	2441MHz
---------------	---------


DH1



DH3




DH5




$\pi/4$ -DQPSK mode:

Test channel:	2441MHz
---------------	---------


DH1



DH3




DH5




8-DPSK mode:

Test channel:	2441MHz
---------------	---------


DH1



DH3



DH5




7.8 Pseudorandom Frequency Hopping Sequence

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)/g/h requirement:
<i>a(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.</i> <i>Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.</i> <i>(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.</i> <i>(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.</i>	
EUT Pseudorandom Frequency Hopping Sequence	
The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones. • Number of shift register stages: 9 • Length of pseudo-random sequence: $2^9 - 1 = 511$ bits • Longest sequence of zeros: 8 (non-inverted signal) <i>Linear Feedback Shift Register for Generation of the PRBS sequence</i> An example of Pseudorandom Frequency Hopping Sequence as follow: <i>Each frequency used equally on the average by each transmitter.</i> <i>The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.</i> <i>it permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted.</i>	

7.9 Band Edge

7.9.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100kHz, VBW=300kHz, Detector=Peak
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by two vertical legs. Below the table is a Ground Reference Plane, represented by a thick grey bar.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Test plot as follows:

GFSK Mode:


Test channel:

Lowest channel

No-hopping mode




Hopping mode




Test channel:

Highest channel

No-hopping mode



Hopping mode




$\pi/4$ -DQPSK Mode:


Test channel:

Lowest channel

No-hopping mode




Hopping mode




Test channel:

Highest channel

No-hopping mode



Hopping mode




8-DPSK Mode:


Test channel:

Lowest channel

No-hopping mode




Hopping mode




Test channel:

Highest channel


No-hopping mode



Hopping mode



7.9.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	Above 1GHz		54.00		Average Value
			74.00		Peak Value
Test setup:					
Test Procedure:	1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.				
Test Instruments:	Refer to section 6.0 for details				
Test mode:	Refer to section 5.2 for details				
Test results:	Pass				

Measurement Data

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Preamplifier Factor (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	53.51	39.55	7.77	25.66	47.39	74.00	-26.61	Horizontal
2400.00	51.60	38.33	7.3	24.55	45.12	74.00	-28.88	Horizontal
2390.00	53.85	39.55	7.77	25.66	47.73	74.00	-26.27	Vertical
2400.00	52.49	38.33	7.3	23.55	45.01	74.00	-28.99	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	43.37	39.55	7.77	25.66	37.25	54.00	-16.75	Horizontal
2400.00	43.98	38.33	7.3	24.55	37.50	54.00	-16.50	Horizontal
2390.00	43.70	39.55	7.77	25.66	37.58	54.00	-16.42	Vertical
2400.00	43.75	38.33	7.3	23.22	35.94	54.00	-18.06	Vertical

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	51.53	38.75	7.38	25.45	45.61	74.00	-28.39	Horizontal
2485.50	54.74	38.65	7.15	24.78	48.02	74.00	-25.98	Horizontal
2483.50	52.32	38.75	7.38	25.45	46.40	74.00	-27.60	Vertical
2485.50	53.91	38.65	7.15	24.78	47.19	74.00	-26.81	Vertical

Average value:


Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	43.77	38.75	7.38	25.45	37.85	54.00	-16.15	Horizontal
2485.50	43.98	38.65	7.15	24.78	37.26	54.00	-16.74	Horizontal
2483.50	43.99	38.75	7.38	25.45	38.07	54.00	-15.93	Vertical
2485.50	43.85	38.65	7.15	24.78	37.13	54.00	-16.87	Vertical

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.
4. During the test, pre-scan the GFSK, $\pi/4$ -DQPSK, 8-DPSK modulation, and found the GFSK modulation which it is worse case.

7.10 Spurious Emission


7.10.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by two vertical legs and sits on a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

GFSK mode:

Test channel:


Lowest channel



30MHz~25GHz

Test channel:


Middle channel



30MHz~25GHz

Test channel:


Highest channel



30MHz~25GHz


$\pi/4$ -DQPSK mode:

Test channel:	Lowest channel
---------------	----------------




30MHz~25GHz

Test channel:	Middle channel
---------------	----------------



30MHz~25GHz

Test channel:	Highest channel
---------------	-----------------




30MHz~25GHz

8-DPSK mode:

Test channel:


Lowest channel



30MHz~25GHz

Test channel:


Middle channel



30MHz~25GHz


Test channel:



Highest channel



30MHz~25GHz

7.10.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Limit (uV/m)		Value	Measurement Distance
	0.009MHz-0.490MHz	2400/F(KHz)		QP	300m
	0.490MHz-1.705MHz	24000/F(KHz)		QP	30m
	1.705MHz-30MHz	30		QP	30m
	30MHz-88MHz	100		QP	3m
	88MHz-216MHz	150		QP	
	216MHz-960MHz	200		QP	
	960MHz-1GHz	500		QP	
	Above 1GHz	500		Average	
		5000		Peak	
Test setup:	For radiated emissions from 9kHz to 30MHz				
					

	For radiated emissions from 30MHz to 1GHz  For radiated emissions above 1GHz 
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details

Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Measurement data:*Remarks:*

1. During the test, pre-scan the GFSK, $\pi/4$ -DQPSK, 8-DPSK modulation, and found the GFSK modulation which it is worse case.
2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.


■ 9kHz~30MHz

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

■ Below 1GHz


Pre-scan all test modes, found worst case at GFSK 2480MHz, and so only show the test result of GFSK 2480MHz

Horizontal:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	59.9639	30.22	-14.24	15.98	40.00	-24.02	QP				
2	139.1172	39.23	-17.40	21.83	43.50	-21.67	QP				
3	160.0648	51.27	-16.80	34.47	43.50	-9.03	QP				
4	221.3921	47.41	-18.90	28.51	46.00	-17.49	QP				
5	261.5164	52.01	-17.08	34.93	46.00	-11.07	QP				
6	282.9852	49.57	-16.56	33.01	46.00	-12.99	QP				

Vertical:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	43.3534	40.89	-17.01	23.88	40.00	-16.12	QP				
2	53.0382	38.94	-17.60	21.34	40.00	-18.66	QP				
3	67.2022	37.42	-19.05	18.37	40.00	-21.63	QP				
4	161.4742	45.95	-20.78	25.17	43.50	-18.33	QP				
5	235.4033	41.95	-21.65	20.30	46.00	-25.70	QP				
6	280.5152	42.92	-20.73	22.19	46.00	-23.81	QP				

■ Above 1GHz

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Preamp Factor (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	52.22	39.55	7.77	25.66	46.10	74.00	-27.90	Vertical
7206.00	53.16	38.33	7.30	24.55	46.68	74.00	-27.32	Vertical
15450.00	53.25	35.23	6.60	26.59	51.21	74.00	-22.79	Vertical
4804.00	51.03	39.55	7.77	25.66	44.91	74.00	-29.09	Horizontal
7206.00	52.44	38.33	7.30	23.55	44.96	74.00	-29.04	Horizontal
15450.00	53.13	35.45	6.60	27.88	52.16	74.00	-21.84	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Preamp Factor (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	43.21	39.55	7.77	25.66	37.09	54.00	-16.91	Vertical
7206.00	42.16	38.33	7.30	24.55	35.68	54.00	-18.32	Vertical
15450.00	42.36	35.23	6.60	26.59	40.32	54.00	-13.68	Vertical
4804.00	43.10	39.55	7.77	25.66	36.98	54.00	-17.02	Horizontal
7206.00	42.33	38.33	7.30	23.55	34.85	54.00	-19.15	Horizontal
15450.00	43.06	35.45	6.60	27.88	42.09	54.00	-11.91	Horizontal

Test channel:	Middle channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Preamp Factor (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882.00	50.23	39.55	7.77	25.66	44.11	74.00	-29.89	Vertical
7323.00	51.36	38.33	7.30	24.55	44.88	74.00	-29.12	Vertical
15450.00	53.26	35.23	6.60	26.59	51.22	74.00	-22.78	Vertical
4882.00	53.11	39.55	7.77	25.66	46.99	74.00	-27.01	Horizontal
7323.00	52.65	38.33	7.30	23.55	45.17	74.00	-28.83	Horizontal
15450.00	51.36	35.45	6.60	27.88	50.39	74.00	-23.61	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Preamp Factor (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882.00	43.21	39.55	7.77	25.66	37.09	54.00	-16.91	Vertical
7323.00	42.36	38.33	7.30	24.55	35.88	54.00	-18.12	Vertical
15450.00	43.65	35.23	6.60	26.59	41.61	54.00	-12.39	Vertical
4882.00	43.16	39.55	7.77	25.66	37.04	54.00	-16.96	Horizontal
7323.00	42.05	38.33	7.30	23.55	34.57	54.00	-19.43	Horizontal
15450.00	41.33	35.45	6.60	27.88	40.36	54.00	-13.64	Horizontal

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Preamp Factor (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	51.32	39.55	7.77	25.66	45.20	74.00	-28.80	Vertical
7440.00	51.36	38.33	7.30	24.55	44.88	74.00	-29.12	Vertical
15450.00	53.25	35.23	6.60	26.59	51.21	74.00	-22.79	Vertical
4960.00	53.11	39.55	7.77	25.66	46.99	74.00	-27.01	Horizontal
7440.00	52.42	38.33	7.30	23.55	44.94	74.00	-29.06	Horizontal
15450.00	51.36	35.45	6.60	27.88	50.39	74.00	-23.61	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Preamp Factor (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	42.38	39.55	7.77	25.66	36.26	54.00	-17.74	Vertical
7440.00	43.27	38.33	7.30	24.55	36.79	54.00	-17.21	Vertical
15450.00	43.66	35.23	6.60	26.59	41.62	54.00	-12.38	Vertical
4960.00	44.23	39.55	7.77	25.66	38.11	54.00	-15.89	Horizontal
7440.00	43.29	38.33	7.30	23.55	35.81	54.00	-18.19	Horizontal
15450.00	42.34	35.45	6.60	27.88	41.37	54.00	-12.63	Horizontal

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamp Factor
2. “**”, means this data is too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. The test data shows only the worst case GFSK mode

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----