

# FCC Radio Test Report

## FCC ID: 2AWU4-CL-250W

### Original Grant

**Report No.** : TB-FCC174064

**Applicant** : Shenzhen Cloudecho Audio Co.,Ltd

#### Equipment Under Test (EUT)

**EUT Name** : Hi-Fi Wifi Stereo Audio Amplifier

**Model No.** : CL-250W

**Series Model No.** : N/A

**Brand Name** : Cloudyx

**Sample ID** : TBBJ-20200629-12-1#& TBBJ-20200629-12-2#

**Receipt Date** : 2020-07-07

**Test Date** : 2020-07-08 to 2020-07-27

**Issue Date** : 2020-07-28

**Standards** : FCC Part 15, Subpart C 15.247

**Test Method** : ANSI C63.10: 2013

**Conclusions** : **PASS**

In the configuration tested, the EUT complied with the standards specified above,

The EUT technically complies with the FCC and IC requirements

**Test/Witness Engineer** :



Jack Deng

**Engineer Supervisor** :




Ivan Su

**Engineer Manager** :



Ray Lai



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should

**TB-RF-074-1.0**

ensure that all products in series production are in conformity with the product sample detailed in the report.

## Contents

<b>CONTENTS.....</b>	<b>2</b>
<b>1. GENERAL INFORMATION ABOUT EUT.....</b>	<b>5</b>
1.1 Client Information.....	5
1.2 General Description of EUT (Equipment Under Test) .....	5
1.3 Block Diagram Showing the Configuration of System Tested .....	6
1.4 Description of Support Units .....	6
1.5 Description of Test Mode.....	7
1.6 Description of Test Software Setting .....	8
1.7 Measurement Uncertainty .....	8
1.8 Test Facility.....	9
<b>2. TEST SUMMARY.....</b>	<b>10</b>
<b>3. TEST SOFTWARE.....</b>	<b>10</b>
<b>4. TEST EQUIPMENT.....</b>	<b>11</b>
<b>5. CONDUCTED EMISSION TEST .....</b>	<b>12</b>
5.1 Test Standard and Limit.....	12
5.2 Test Setup.....	12
5.3 Test Procedure.....	13
5.4 Deviation From Test Standard.....	13
5.5 EUT Operating Mode .....	13
5.6 Test Data.....	13
<b>6. RADIATED EMISSION TEST .....</b>	<b>14</b>
6.1 Test Standard and Limit.....	14
6.2 Test Setup.....	15
6.3 Test Procedure.....	16
6.4 Deviation From Test Standard.....	17
6.5 EUT Operating Condition .....	17
6.6 Test Data.....	17
<b>7. RESTRICTED BANDS REQUIREMENT .....</b>	<b>18</b>
7.1 Test Standard and Limit.....	18
7.2 Test Setup.....	18
7.3 Test Procedure.....	19
7.4 Deviation From Test Standard.....	19
7.5 EUT Operating Condition .....	19
7.6 Test Data.....	19
<b>8. BANDWIDTH TEST.....</b>	<b>20</b>
8.1 Test Standard and Limit.....	20

---

8.2 Test Setup.....	20
8.3 Test Procedure.....	20
8.4 Deviation From Test Standard.....	20
8.5 EUT Operating Condition .....	20
8.6 Test Data.....	20
<b>9. PEAK OUTPUT POWER TEST.....</b>	<b>21</b>
9.1 Test Standard and Limit.....	21
9.2 Test Setup.....	21
9.3 Test Procedure.....	21
9.4 Deviation From Test Standard.....	21
9.5 EUT Operating Condition .....	21
9.6 Test Data.....	21
<b>10. POWER SPECTRAL DENSITY TEST .....</b>	<b>22</b>
10.1 Test Standard and Limit .....	22
10.2 Test Setup.....	22
10.3 Test Procedure.....	22
9.4 Deviation From Test Standard.....	22
9.5 EUT Operating Condition .....	22
9.6 Test Data.....	22
<b>11. ANTENNA REQUIREMENT.....</b>	<b>23</b>
11.1 Standard Requirement.....	23
11.2 Deviation From Test Standard.....	23
11.3 Antenna Connected Construction .....	23
<b>ATTACHMENT A-- CONDUCTED EMISSION TEST DATA .....</b>	<b>24</b>
<b>ATTACHMENT C-- RESTRICTED BANDS REQUIREMENT AND BAND-EDGE TEST DATA .....</b>	<b>37</b>
<b>ATTACHMENT D-- BANDWIDTH TEST DATA.....</b>	<b>52</b>
<b>ATTACHMENT E-- PEAK OUTPUT POWER TEST DATA.....</b>	<b>58</b>
<b>ATTACHMENT F-- POWER SPECTRAL DENSITY TEST DATA.....</b>	<b>62</b>

## Revision History

## 1. General Information about EUT

### 1.1 Client Information

<b>Applicant</b>	:	Shenzhen Cloudecho Audio Co.,Ltd
<b>Address</b>	:	Rm707, Biwan Building, Biwan Road, Baoan District, Shenzhen, P.R.China
<b>Manufacturer</b>	:	Shenzhen Cloudecho Audio Co.,Ltd
<b>Address</b>	:	Rm707, Biwan Building, Biwan Road, Baoan District, Shenzhen, P.R.China

### 1.2 General Description of EUT (Equipment Under Test)

<b>EUT Name</b>	:	Hi-Fi Wifi Stereo Audio Amplifier
<b>Models No.</b>	:	CL-250W
<b>Model Difference</b>	:	N/A
<b>Product Description</b>	Operation Frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz
	Number of Channel:	802.11b/g/n(HT20):11 channels see note(3)
	RF Output Power:	802.11b: 15.55 dBm 802.11g: 14.99 dBm 802.11n (HT20): 13.78 dBm
	Modulation Type:	802.11b: DSSS(CCK, DQPSK, DBPSK) 802.11g/n: OFDM(BPSK,QPSK,16QAM,64QAM)
	Antenna Gain:	2dBi External Antenna
<b>Power Supply</b>	:	Adapter(3205000) Input: AC 100~240V, 50/60Hz 2.2A MAX Output: DC 32V, 5A.
<b>Software Version</b>	:	V38
<b>Hardware Version</b>	:	V1.0
<b>Connecting I/O Port(S)</b>	:	Please refer to the User's Manual
<b>Remark</b>	:	The antenna gain and adapter provided by the applicant, the verified for the RF conduction test and adapter provided by TOBY test lab.

#### Note:

- (1) This Test Report is FCC Part 15.247 for 802.11b/g/n, the test procedure follows the FCC KDB 558074 D01 DTS Meas Guidance v05.
- (2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

## (3) Channel List:


Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	05	2432	09	2452
02	2417	06	2437	10	2457
03	2422	07	2442	11	2462
04	2427	08	2447		

Note: CH 01~CH 11 for 802.11b/g/n(HT20)


(4) The Antenna information about the equipment is provided by the applicant.

### 1.3 Block Diagram Showing the Configuration of System Tested

#### Charging Mode+TX mode



#### TX Mode



### 1.4 Description of Support Units

Equipment Information				
Name	Model	FCC ID/VOC	Manufacturer	Used "√"
----	-----	----	----	√
Cable Information				
Number	Shielded Type	Ferrite Core	Length	Note
Cable 1	Yes	NO	1.0M	Accessory

## 1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test	
Final Test Mode	Description
Mode 1	Charging + TX B Mode

For Radiated Test	
Final Test Mode	Description
Mode 2	TX Mode B Mode Channel 01/06/11
Mode 3	TX Mode G Mode Channel 01/06/11
Mode 4	TX Mode N(HT20) Mode Channel 01/06/11
Mode 5	TX Mode N(HT40) Mode Channel 03/06/09

### Note:

(1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate.

According to ANSI C63.10 standards, the measurements are performed at the highest, Middle, lowest available channels, and the worst case data rate as follows:

802.11b Mode: CCK (1 Mbps)  
802.11g Mode: OFDM (6 Mbps)  
802.11n (HT20) Mode: MCS 0 (6.5 Mbps)  
802.11n (HT40) Mode: MCS 0 (13 Mbps)

(2) During the testing procedure, the continuously transmitting with the maximum power mode was programmed by the customer.  
(3) The EUT is considered a Fixde unit; in normal use it was positioned on X-plane. The worst case was found positioned on X-plane. Therefore only the test data of this X-plane was used for radiated emission measurement test.

## 1.6 Description of Test Software Setting

During testing channel&Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of WLAN.

Test Software Version	LaunchEngmode		
Channel	CH 01	CH 06	CH 11
IEEE 802.11b DSSS	DEF	DEF	DEF
IEEE 802.11g OFDM	DEF	DEF	DEF
IEEE 802.11n (HT20)	DEF	DEF	DEF

## 1.7 Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty ( $U_{Lab}$ )
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	$\pm 3.50$ dB $\pm 3.10$ dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	$\pm 4.60$ dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	$\pm 4.50$ dB
Radiated Emission	Level Accuracy: Above 1000MHz	$\pm 4.20$ dB

## 1.8 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

### **CNAS (L5813)**

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

### **A2LA Certificate No.: 4750.01**

The laboratory has been accredited by American Association for Laboratory Accreditation(A2LA) to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the technical competence in the field of Electrical Testing. And the A2LA Certificate No.: 4750.01. FCC Accredited Test Site Number: 854351.

### **IC Registration No.: (11950A)**

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A.

## 2. Test Summary

FCC Part 15 Subpart C(15.247)/RSS 247 Issue 2					
Standard Section		Test Item	Test Sample(s)	Judgment	Remark
FCC	IC				
15.203		Antenna Requirement	TBBJ-20200629-12-2#	PASS	N/A
15.207(a)	RSS-GEN 7.2.4	Conducted Emission	TBBJ-20200629-12-1#	PASS	N/A
15.205&15.247(d)	RSS-GEN 7.2.2	Band-Edge & Unwanted Emissions into Restricted Frequency	TBBJ-20200629-12-2#	PASS	N/A
15.247(a)(2)	RSS 247 5.2 (1)	6dB Bandwidth	TBBJ-20200629-12-2#	PASS	N/A
15.247(b)(3)	RSS 247 5.4 (4)	Conducted Max Output Power	TBBJ-20200629-12-2#	PASS	N/A
15.247(e)	RSS 247 5.2 (2)	Power Spectral Density	TBBJ-20200629-12-2#	PASS	N/A
15.205, 15.209&15.247(d)	RSS 247 5.5	Transmitter Radiated Spurious &Unwanted Emissions into Restricted Frequency	TBBJ-20200629-12-1# TBBJ-20200629-12-2#	PASS	N/A

**Note:** N/A is an abbreviation for Not Applicable.

## 3. Test Software

Test Item	Test Software	Manufacturer	Version No.
Conducted Emission	EZ-EMC	EZ	CDI-03A2
Radiation Emission	EZ-EMC	EZ	FA-03A2RE

## 4. Test Equipment

Conducted Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Jul. 06, 2020	Jul. 05, 2021
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jul. 06, 2020	Jul. 05, 2021
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jul. 06, 2020	Jul. 05, 2021
LISN	Rohde & Schwarz	ENV216	101131	Jul. 06, 2020	Jul. 05, 2021
Radiation Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 06, 2020	Jul. 05, 2021
EMI Test Receiver	Rohde & Schwarz	ESPI	100010/007	Jul. 06, 2020	Jul. 05, 2021
Spectrum Analyzer	Rohde & Schwarz	FSV40-N	102197	Jul. 06, 2020	Jul. 05, 2021
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Mar.01, 2020	Feb. 28, 2021
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar.01, 2020	Feb. 28, 2022
Horn Antenna	ETS-LINDGREN	BBHA 9170	BBHA9170582	Mar.01, 2020	Feb. 28, 2022
Loop Antenna	SCHWARZBECK	FMZB 1519 B	1519B-059	Jul. 06, 2020	Jul. 05, 2021
Pre-amplifier	Sonoma	310N	185903	Mar.01, 2020	Feb. 28, 2021
Pre-amplifier	HP	8449B	3008A00849	Mar.01, 2020	Feb. 28, 2021
Pre-amplifier	SKET	LNPA_1840G-50	SK201904032	Jul. 27, 2020	Jul. 26, 2021
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar.01, 2020	Feb. 28, 2021
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A
Antenna Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 06, 2020	Jul. 05, 2021
Spectrum Analyzer	Rohde & Schwarz	ESCI	100010/007	Jul. 06, 2020	Jul. 05, 2021
MXA Signal Analyzer	Agilent	N9020A	MY49100060	Sep. 16, 2019	Sep. 15, 2020
Vector Signal Generator	Agilent	N5182A	MY50141294	Sep. 16, 2019	Sep. 15, 2020
Analog Signal Generator	Agilent	N5181A	MY50141953	Sep. 16, 2019	Sep. 15, 2020
RF Power Sensor	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO26	Sep. 16, 2019	Sep. 15, 2020
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO29	Sep. 16, 2019	Sep. 15, 2020
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO31	Sep. 16, 2019	Sep. 15, 2020
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO33	Sep. 16, 2019	Sep. 15, 2020

## 5. Conducted Emission Test

### 5.1 Test Standard and Limit

5.1.1 Test Standard  
FCC Part 15.207

5.1.2 Test Limit


#### Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dB $\mu$ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Notes:

- (1) \*Decreasing linearly with logarithm of the frequency.
- (2) The lower limit shall apply at the transition frequencies.
- (3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 5.2 Test Setup



### 5.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis.

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.

### 5.4 Deviation From Test Standard

No deviation

### 5.5 EUT Operating Mode

Please refer to the description of test mode.

### 5.6 Test Data

Please refer to the Attachment A.

## 6. Radiated Emission Test

### 6.1 Test Standard and Limit

6.1.1 Test Standard  
FCC Part 15.209

6.1.2 Test Limit

Radiated Emission Limits ( 9 kHz~1000 MHz)

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Radiated Emission Limit (Above 1000MHz)

Frequency (MHz)	Distance of 3m (dBuV/m)	
	Peak	Average
Above 1000	74	54


**Note:**

- (1) The tighter limit applies at the band edges.
- (2) Emission Level(dBuV/m)=20log Emission Level(uV/m)


## 6.2 Test Setup



Below 30MHz Test Setup



Below 1000MHz Test Setup



Above 1GHz Test Setup

### 6.3 Test Procedure

- (1) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency Below 1GHz. The EUT was placed on a rotating 0.8m high above the ground. The table was rotated 360 degrees to determine the position of the highest radiation.
- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Below 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

## 6.4 Deviation From Test Standard

No deviation

## 6.5 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

## 6.6 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

Please refer to the Attachment B.

## 7. Restricted Bands Requirement

### 7.1 Test Standard and Limit

#### 7.1.1 Test Standard

FCC Part 15.247(d)


FCC Part 15.209

FCC Part 15.205

#### 7.1.2 Test Limit

Restricted Frequency Band (MHz)	Distance of 3m (dBuV/m)	
	Peak	Average
2310 ~2390	74	54
2483.5 ~2500	74	54

### 7.2 Test Setup



### 7.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency below 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Below 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

### 7.4 Deviation From Test Standard

No deviation

### 7.5 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

### 7.6 Test Data

Please refer to the Attachment C.


## 8. Bandwidth Test

### 8.1 Test Standard and Limit

- 8.1.1 Test Standard  
FCC Part 15.247 (a)(2)
- 8.1.2 Test Limit

FCC Part 15 Subpart C(15.247)/RSS-210		
Test Item	Limit	Frequency Range(MHz)
Bandwidth	>=500 KHz (6dB bandwidth)	2400~2483.5

### 8.2 Test Setup



### 8.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) The bandwidth is measured at an amplitude level reduced 6dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst -case (i.e the widest) bandwidth.
- (3) Measure the channel separation the spectrum analyzer was set to Resolution Bandwidth:100 kHz, and Video Bandwidth:300 kHz, Detector: Peak, Sweep Time set auto.

### 8.4 Deviation From Test Standard

No deviation

### 8.5 EUT Operating Condition

The EUT was set to continuously transmitting in each mode and low, Middle and high channel for the test.

### 8.6 Test Data

Please refer to the Attachment D.


## 9. Peak Output Power Test

### 9.1 Test Standard and Limit

- 9.1.1 Test Standard  
FCC Part 15.247 (b)
- 9.1.2 Test Limit

FCC Part 15 Subpart C(15.247)/RSS-210		
Test Item	Limit	Frequency Range(MHz)
Peak Output Power	1 Watt or 30 dBm	2400~2483.5

### 9.2 Test Setup



### 9.3 Test Procedure

The measurement is according to section 9.1.2 of KDB 558074 D01 DTS Meas Guidance v05. The EUT was connected to RF power meter via a broadband power sensor as show the block above. The power sensor video bandwidth is greater than or equal to the DTS bandwidth of the equipment.

### 9.4 Deviation From Test Standard

No deviation

### 9.5 EUT Operating Condition

The EUT was set to continuously transmitting in the max power during the test.

### 9.6 Test Data

Please refer to the Attachment E.


## 10. Power Spectral Density Test

### 10.1 Test Standard and Limit

- 10.1.1 Test Standard  
FCC Part 15.247 (e)
- 10.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	Limit	Frequency Range(MHz)
Power Spectral Density	8dBm(in any 3 kHz)	2400~2483.5

### 10.2 Test Setup



### 10.3 Test Procedure

The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to section 10.2 of KDB 558074 D01 DTS Meas Guidance v05.

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Set analyser centre frequency to DTS channel centre frequency.
- (3) Set the span to 1.5 times the DTS bandwidth.
- (4) Set the RBW to: 3 kHz
- (5) Set the VBW to: 10 kHz
- (6) Detector: peak
- (7) Sweep time: auto
- (8) Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.

### 9.4 Deviation From Test Standard

No deviation

### 9.5 EUT Operating Condition

The EUT was set to continuously transmitting in each mode and low, Middle and high channel for the test.

### 9.6 Test Data

Please refer to the Attachment F.

## 11. Antenna Requirement

### 11.1 Standard Requirement

#### 11.1.1 Standard

FCC Part 15.203

#### 11.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### 11.2 Deviation From Test Standard

No deviation

### 11.3 Antenna Connected Construction

The gains of the antenna used for transmitting is 2dBi, and the antenna de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.


### Result

The EUT antenna is a External Antenna. It complies with the standard requirement.

Antenna Type
<input type="checkbox"/> Permanent attached antenna
<input checked="" type="checkbox"/> Unique connector antenna
<input type="checkbox"/> Professional installation antenna


## Attachment A-- Conducted Emission Test Data

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Terminal:	Line		
Test Mode:	Charging with TX B Mode		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector
			Level	Factor	ment			
1	*	0.1819	43.31	9.70	53.01	64.39	-11.38	QP
2		0.1819	30.34	9.70	40.04	54.39	-14.35	AVG
3		0.2140	38.23	9.70	47.93	63.04	-15.11	QP
4		0.2140	25.11	9.70	34.81	53.04	-18.23	AVG
5		0.2580	33.50	9.70	43.20	61.49	-18.29	QP
6		0.2580	23.21	9.70	32.91	51.49	-18.58	AVG
7		0.5140	30.72	9.70	40.42	56.00	-15.58	QP
8		0.5140	20.31	9.70	30.01	46.00	-15.99	AVG
9		1.1860	29.02	9.78	38.80	56.00	-17.20	QP
10		1.1860	20.47	9.78	30.25	46.00	-15.75	AVG
11		1.9700	28.74	9.70	38.44	56.00	-17.56	QP
12		1.9700	21.85	9.70	31.55	46.00	-14.45	AVG

Emission Level= Read Level+ Correct Factor


Temperature:	25 °C	Relative Humidity:	55%					
Test Voltage:	AC 120V/60 Hz							
Terminal:	Neutral							
Test Mode:	Charging with TX B Mode							
Remark:	Only worse case is reported							
								
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1	*	0.1740	45.05	9.80	54.85	64.76	-9.91	QP
2		0.1740	32.46	9.80	42.26	54.76	-12.50	AVG
3		0.2140	38.72	9.80	48.52	63.04	-14.52	QP
4		0.2140	25.69	9.80	35.49	53.04	-17.55	AVG
5		0.3060	31.93	9.80	41.73	60.08	-18.35	QP
6		0.3060	24.17	9.80	33.97	50.08	-16.11	AVG
7		0.4620	32.40	9.80	42.20	56.66	-14.46	QP
8		0.4620	20.83	9.80	30.63	46.66	-16.03	AVG
9		0.9220	30.03	9.80	39.83	56.00	-16.17	QP
10		0.9220	21.69	9.80	31.49	46.00	-14.51	AVG
11		1.9660	28.56	9.80	38.36	56.00	-17.64	QP
12		1.9660	20.25	9.80	30.05	46.00	-15.95	AVG

Emission Level= Read Level+ Correct Factor

**Attachment B-- Radiated Emission Test Data****9KHz~30MHz**

From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

**30MHz~1GHz**

\*:Maximum data x:Over limit !:over margin

**Emission Level= Read Level+ Correct Factor**

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2412MHz		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1		36.5092	50.60	-17.37	33.23	40.00	-6.77
2	!	64.8865	58.63	-23.82	34.81	40.00	-5.19
3	*	78.9652	57.69	-22.56	35.13	40.00	-4.87
4		96.7749	58.59	-21.92	36.67	43.50	-6.83
5		135.5062	53.92	-22.37	31.55	43.50	-11.95
6		254.7284	50.85	-17.12	33.73	46.00	-12.27

\*:Maximum data    x:Over limit    !:over margin

Emission Level= Read Level+ Correct Factor

**Above 1GHz**

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 32V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX B Mode 2412MHz		
<b>Remark:</b>	No report for the emission which more than 20 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dB	Detector	
1		4824.462	49.19	13.16	62.35	74.00	-11.65	peak
2	*	4824.563	34.18	13.16	47.34	54.00	-6.66	AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 32V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX B Mode 2412MHz		
<b>Remark:</b>	No report for the emission which more than 20 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dB	Detector	
1	*	4824.562	34.07	13.16	47.23	54.00	-6.77	AVG
2		4824.664	49.25	13.16	62.41	74.00	-11.59	peak

Emission Level= Read Level+ Correct Factor

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 32V		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2437MHz		
Remark:	No report for the emission which more than 20 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1		4874.466	49.13	13.53	62.66	74.00	-11.34 peak
2	*	4874.593	33.83	13.53	47.36	54.00	-6.64 AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 32V		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2437MHz		
Remark:	No report for the emission which more than 20 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1		4873.665	48.82	13.53	62.35	74.00	-11.65 peak
2	*	4874.646	34.09	13.53	47.62	54.00	-6.38 AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	25 °C		<b>Relative Humidity:</b>	55%																																				
<b>Test Voltage:</b>	DC 32V																																							
<b>Ant. Pol.</b>	Horizontal																																							
<b>Test Mode:</b>	TX B Mode 2462MHz																																							
<b>Remark:</b>	No report for the emission which more than 20 dB below the prescribed limit.																																							
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left; padding: 2px;">No.</th> <th style="text-align: left; padding: 2px;">Mk.</th> <th style="text-align: left; padding: 2px;">Freq.</th> <th style="text-align: left; padding: 2px;">Reading Level</th> <th style="text-align: left; padding: 2px;">Correct Factor</th> <th style="text-align: left; padding: 2px;">Measure-ment</th> <th style="text-align: left; padding: 2px;">Limit</th> <th style="text-align: left; padding: 2px;">Over</th> </tr> <tr> <th style="text-align: left; padding: 2px;"></th> <th style="text-align: left; padding: 2px;"></th> <th style="text-align: left; padding: 2px;">MHz</th> <th style="text-align: left; padding: 2px;">dBuV</th> <th style="text-align: left; padding: 2px;">dB/m</th> <th style="text-align: left; padding: 2px;">dBuV/m</th> <th style="text-align: left; padding: 2px;">dBuV/m</th> <th style="text-align: left; padding: 2px;">dB</th> <th style="text-align: left; padding: 2px;">Detector</th> </tr> </thead> <tbody> <tr> <td style="text-align: left; padding: 2px;">1</td> <td style="text-align: left; padding: 2px;">*</td> <td style="text-align: left; padding: 2px;">4924.366</td> <td style="text-align: left; padding: 2px;">34.07</td> <td style="text-align: left; padding: 2px;">13.16</td> <td style="text-align: left; padding: 2px;">47.23</td> <td style="text-align: left; padding: 2px;">54.00</td> <td style="text-align: left; padding: 2px;">-6.77</td> <td style="text-align: left; padding: 2px;">AVG</td> </tr> <tr> <td style="text-align: left; padding: 2px;">2</td> <td style="text-align: left; padding: 2px;"></td> <td style="text-align: left; padding: 2px;">4925.656</td> <td style="text-align: left; padding: 2px;">49.44</td> <td style="text-align: left; padding: 2px;">13.18</td> <td style="text-align: left; padding: 2px;">62.62</td> <td style="text-align: left; padding: 2px;">74.00</td> <td style="text-align: left; padding: 2px;">-11.38</td> <td style="text-align: left; padding: 2px;">peak</td> </tr> </tbody> </table>						No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	1	*	4924.366	34.07	13.16	47.23	54.00	-6.77	AVG	2		4925.656	49.44	13.18	62.62	74.00	-11.38	peak
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																																	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector																																
1	*	4924.366	34.07	13.16	47.23	54.00	-6.77	AVG																																
2		4925.656	49.44	13.18	62.62	74.00	-11.38	peak																																
<b>Emission Level= Read Level+ Correct Factor</b>																																								

<b>Temperature:</b>	25 °C		<b>Relative Humidity:</b>	55%																																				
<b>Test Voltage:</b>	DC 32V																																							
<b>Ant. Pol.</b>	Vertical																																							
<b>Test Mode:</b>	TX B Mode 2462MHz																																							
<b>Remark:</b>	No report for the emission which more than 20 dB below the prescribed limit.																																							
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left; padding: 2px;">No.</th> <th style="text-align: left; padding: 2px;">Mk.</th> <th style="text-align: left; padding: 2px;">Freq.</th> <th style="text-align: left; padding: 2px;">Reading Level</th> <th style="text-align: left; padding: 2px;">Correct Factor</th> <th style="text-align: left; padding: 2px;">Measure-ment</th> <th style="text-align: left; padding: 2px;">Limit</th> <th style="text-align: left; padding: 2px;">Over</th> </tr> <tr> <th style="text-align: left; padding: 2px;"></th> <th style="text-align: left; padding: 2px;"></th> <th style="text-align: left; padding: 2px;">MHz</th> <th style="text-align: left; padding: 2px;">dBuV</th> <th style="text-align: left; padding: 2px;">dB/m</th> <th style="text-align: left; padding: 2px;">dBuV/m</th> <th style="text-align: left; padding: 2px;">dBuV/m</th> <th style="text-align: left; padding: 2px;">dB</th> <th style="text-align: left; padding: 2px;">Detector</th> </tr> </thead> <tbody> <tr> <td style="text-align: left; padding: 2px;">1</td> <td style="text-align: left; padding: 2px;">*</td> <td style="text-align: left; padding: 2px;">4924.216</td> <td style="text-align: left; padding: 2px;">33.37</td> <td style="text-align: left; padding: 2px;">13.89</td> <td style="text-align: left; padding: 2px;">47.26</td> <td style="text-align: left; padding: 2px;">54.00</td> <td style="text-align: left; padding: 2px;">-6.74</td> <td style="text-align: left; padding: 2px;">AVG</td> </tr> <tr> <td style="text-align: left; padding: 2px;">2</td> <td style="text-align: left; padding: 2px;"></td> <td style="text-align: left; padding: 2px;">4924.263</td> <td style="text-align: left; padding: 2px;">48.76</td> <td style="text-align: left; padding: 2px;">13.89</td> <td style="text-align: left; padding: 2px;">62.65</td> <td style="text-align: left; padding: 2px;">74.00</td> <td style="text-align: left; padding: 2px;">-11.35</td> <td style="text-align: left; padding: 2px;">peak</td> </tr> </tbody> </table>						No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	1	*	4924.216	33.37	13.89	47.26	54.00	-6.74	AVG	2		4924.263	48.76	13.89	62.65	74.00	-11.35	peak
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																																	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector																																
1	*	4924.216	33.37	13.89	47.26	54.00	-6.74	AVG																																
2		4924.263	48.76	13.89	62.65	74.00	-11.35	peak																																
<b>Emission Level= Read Level+ Correct Factor</b>																																								

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%																																										
<b>Test Voltage:</b>	DC 32V																																												
<b>Ant. Pol.</b>	Horizontal																																												
<b>Test Mode:</b>	TX G Mode 2412MHz																																												
<b>Remark:</b>	No report for the emission which more than 20 dB below the prescribed limit.																																												
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">No.</th> <th style="text-align: center;">Mk.</th> <th style="text-align: center;">Freq.</th> <th style="text-align: center;">Reading Level</th> <th style="text-align: center;">Correct Factor</th> <th style="text-align: center;">Measure-ment</th> <th style="text-align: center;">Limit</th> <th style="text-align: center;">Over</th> </tr> <tr> <th></th> <th></th> <th style="text-align: center;">MHz</th> <th style="text-align: center;">dBuV</th> <th style="text-align: center;">dB/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dB</th> </tr> <tr> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1</td> <td></td> <td style="text-align: center;">4823.565</td> <td style="text-align: center;">49.00</td> <td style="text-align: center;">13.16</td> <td style="text-align: center;">62.16</td> <td style="text-align: center;">74.00</td> <td style="text-align: center;">-11.84</td> <td>peak</td> </tr> <tr> <td style="text-align: center;">2</td> <td>*</td> <td style="text-align: center;">4824.543</td> <td style="text-align: center;">34.40</td> <td style="text-align: center;">13.16</td> <td style="text-align: center;">47.56</td> <td style="text-align: center;">54.00</td> <td style="text-align: center;">-6.44</td> <td>AVG</td> </tr> </tbody> </table>				No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB								Detector	1		4823.565	49.00	13.16	62.16	74.00	-11.84	peak	2	*	4824.543	34.40	13.16	47.56	54.00	-6.44	AVG
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																																						
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB																																						
							Detector																																						
1		4823.565	49.00	13.16	62.16	74.00	-11.84	peak																																					
2	*	4824.543	34.40	13.16	47.56	54.00	-6.44	AVG																																					
<b>Emission Level= Read Level+ Correct Factor</b>																																													

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%																																										
<b>Test Voltage:</b>	DC 32V																																												
<b>Ant. Pol.</b>	Vertical																																												
<b>Test Mode:</b>	TX G Mode 2412MHz																																												
<b>Remark:</b>	No report for the emission which more than 20 dB below the prescribed limit.																																												
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">No.</th> <th style="text-align: center;">Mk.</th> <th style="text-align: center;">Freq.</th> <th style="text-align: center;">Reading Level</th> <th style="text-align: center;">Correct Factor</th> <th style="text-align: center;">Measure-ment</th> <th style="text-align: center;">Limit</th> <th style="text-align: center;">Over</th> </tr> <tr> <th></th> <th></th> <th style="text-align: center;">MHz</th> <th style="text-align: center;">dBuV</th> <th style="text-align: center;">dB/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dB</th> </tr> <tr> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1</td> <td></td> <td style="text-align: center;">4824.263</td> <td style="text-align: center;">49.46</td> <td style="text-align: center;">13.16</td> <td style="text-align: center;">62.62</td> <td style="text-align: center;">74.00</td> <td style="text-align: center;">-11.38</td> <td>peak</td> </tr> <tr> <td style="text-align: center;">2</td> <td>*</td> <td style="text-align: center;">4825.593</td> <td style="text-align: center;">34.17</td> <td style="text-align: center;">13.18</td> <td style="text-align: center;">47.35</td> <td style="text-align: center;">54.00</td> <td style="text-align: center;">-6.65</td> <td>AVG</td> </tr> </tbody> </table>				No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB								Detector	1		4824.263	49.46	13.16	62.62	74.00	-11.38	peak	2	*	4825.593	34.17	13.18	47.35	54.00	-6.65	AVG
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																																						
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB																																						
							Detector																																						
1		4824.263	49.46	13.16	62.62	74.00	-11.38	peak																																					
2	*	4825.593	34.17	13.18	47.35	54.00	-6.65	AVG																																					
<b>Emission Level= Read Level+ Correct Factor</b>																																													

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%																																										
<b>Test Voltage:</b>	DC 32V																																												
<b>Ant. Pol.</b>	Horizontal																																												
<b>Test Mode:</b>	TX G Mode 2437MHz																																												
<b>Remark:</b>	No report for the emission which more than 20 dB below the prescribed limit.																																												
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">No.</th> <th style="text-align: center;">Mk.</th> <th style="text-align: center;">Freq.</th> <th style="text-align: center;">Reading Level</th> <th style="text-align: center;">Correct Factor</th> <th style="text-align: center;">Measure-ment</th> <th style="text-align: center;">Limit</th> <th style="text-align: center;">Over</th> </tr> <tr> <th></th> <th></th> <th style="text-align: center;">MHz</th> <th style="text-align: center;">dBuV</th> <th style="text-align: center;">dB/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dB</th> </tr> <tr> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>*</td> <td style="text-align: center;">4874.546</td> <td style="text-align: center;">34.03</td> <td style="text-align: center;">13.53</td> <td style="text-align: center;">47.56</td> <td style="text-align: center;">54.00</td> <td style="text-align: center;">-6.44</td> <td>AVG</td> </tr> <tr> <td>2</td> <td></td> <td style="text-align: center;">4874.645</td> <td style="text-align: center;">48.12</td> <td style="text-align: center;">13.53</td> <td style="text-align: center;">61.65</td> <td style="text-align: center;">74.00</td> <td style="text-align: center;">-12.35</td> <td>peak</td> </tr> </tbody> </table>				No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB								Detector	1	*	4874.546	34.03	13.53	47.56	54.00	-6.44	AVG	2		4874.645	48.12	13.53	61.65	74.00	-12.35	peak
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																																						
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB																																						
							Detector																																						
1	*	4874.546	34.03	13.53	47.56	54.00	-6.44	AVG																																					
2		4874.645	48.12	13.53	61.65	74.00	-12.35	peak																																					
<b>Emission Level= Read Level+ Correct Factor</b>																																													

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%																																										
<b>Test Voltage:</b>	DC 32V																																												
<b>Ant. Pol.</b>	Vertical																																												
<b>Test Mode:</b>	TX G Mode 2437MHz																																												
<b>Remark:</b>	No report for the emission which more than 20 dB below the prescribed limit.																																												
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">No.</th> <th style="text-align: center;">Mk.</th> <th style="text-align: center;">Freq.</th> <th style="text-align: center;">Reading Level</th> <th style="text-align: center;">Correct Factor</th> <th style="text-align: center;">Measure-ment</th> <th style="text-align: center;">Limit</th> <th style="text-align: center;">Over</th> </tr> <tr> <th></th> <th></th> <th style="text-align: center;">MHz</th> <th style="text-align: center;">dBuV</th> <th style="text-align: center;">dB/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dB</th> </tr> <tr> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td></td> <td style="text-align: center;">4875.263</td> <td style="text-align: center;">49.09</td> <td style="text-align: center;">13.54</td> <td style="text-align: center;">62.63</td> <td style="text-align: center;">74.00</td> <td style="text-align: center;">-11.37</td> <td>peak</td> </tr> <tr> <td>2</td> <td>*</td> <td style="text-align: center;">4875.336</td> <td style="text-align: center;">34.02</td> <td style="text-align: center;">13.54</td> <td style="text-align: center;">47.56</td> <td style="text-align: center;">54.00</td> <td style="text-align: center;">-6.44</td> <td>AVG</td> </tr> </tbody> </table>				No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB								Detector	1		4875.263	49.09	13.54	62.63	74.00	-11.37	peak	2	*	4875.336	34.02	13.54	47.56	54.00	-6.44	AVG
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																																						
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB																																						
							Detector																																						
1		4875.263	49.09	13.54	62.63	74.00	-11.37	peak																																					
2	*	4875.336	34.02	13.54	47.56	54.00	-6.44	AVG																																					
<b>Emission Level= Read Level+ Correct Factor</b>																																													

<b>Temperature:</b>	25 °C		<b>Relative Humidity:</b>	55%																																			
<b>Test Voltage:</b>	DC 32V																																						
<b>Ant. Pol.</b>	Horizontal																																						
<b>Test Mode:</b>	TX G Mode 2462MHz																																						
<b>Remark:</b>	No report for the emission which more than 20 dB below the prescribed limit.																																						
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">No.</th> <th style="text-align: center;">Mk.</th> <th style="text-align: center;">Freq.</th> <th style="text-align: center;">Reading Level</th> <th style="text-align: center;">Correct Factor</th> <th style="text-align: center;">Measure-ment</th> <th style="text-align: center;">Limit</th> <th style="text-align: center;">Over</th> </tr> <tr> <th></th> <th></th> <th style="text-align: center;">MHz</th> <th style="text-align: center;">dBuV</th> <th style="text-align: center;">dB/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dB</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>*</td> <td style="text-align: center;">4923.652</td> <td style="text-align: center;">33.50</td> <td style="text-align: center;">13.89</td> <td style="text-align: center;">47.39</td> <td style="text-align: center;">54.00</td> <td style="text-align: center;">-6.61</td> <td>AVG</td> </tr> <tr> <td>2</td> <td></td> <td style="text-align: center;">4924.496</td> <td style="text-align: center;">48.52</td> <td style="text-align: center;">13.89</td> <td style="text-align: center;">62.41</td> <td style="text-align: center;">74.00</td> <td style="text-align: center;">-11.59</td> <td>peak</td> </tr> </tbody> </table>						No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dBuV	dB/m	dBuV/m	dB	Detector	1	*	4923.652	33.50	13.89	47.39	54.00	-6.61	AVG	2		4924.496	48.52	13.89	62.41	74.00	-11.59	peak
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																																
		MHz	dBuV	dB/m	dBuV/m	dB	Detector																																
1	*	4923.652	33.50	13.89	47.39	54.00	-6.61	AVG																															
2		4924.496	48.52	13.89	62.41	74.00	-11.59	peak																															
<b>Emission Level= Read Level+ Correct Factor</b>																																							

<b>Temperature:</b>	25 °C		<b>Relative Humidity:</b>	55%																																				
<b>Test Voltage:</b>	DC 32V																																							
<b>Ant. Pol.</b>	Vertical																																							
<b>Test Mode:</b>	TX G Mode 2462MHz																																							
<b>Remark:</b>	No report for the emission which more than 20 dB below the prescribed limit.																																							
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">No.</th> <th style="text-align: center;">Mk.</th> <th style="text-align: center;">Freq.</th> <th style="text-align: center;">Reading Level</th> <th style="text-align: center;">Correct Factor</th> <th style="text-align: center;">Measure-ment</th> <th style="text-align: center;">Limit</th> <th style="text-align: center;">Over</th> </tr> <tr> <th></th> <th></th> <th style="text-align: center;">MHz</th> <th style="text-align: center;">dBuV</th> <th style="text-align: center;">dB/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dB</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>*</td> <td style="text-align: center;">4924.362</td> <td style="text-align: center;">33.80</td> <td style="text-align: center;">13.89</td> <td style="text-align: center;">47.69</td> <td style="text-align: center;">54.00</td> <td style="text-align: center;">-6.31</td> <td>AVG</td> </tr> <tr> <td>2</td> <td></td> <td style="text-align: center;">4925.266</td> <td style="text-align: center;">47.43</td> <td style="text-align: center;">13.91</td> <td style="text-align: center;">61.34</td> <td style="text-align: center;">74.00</td> <td style="text-align: center;">-12.66</td> <td>peak</td> </tr> </tbody> </table>							No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dBuV	dB/m	dBuV/m	dB	Detector	1	*	4924.362	33.80	13.89	47.69	54.00	-6.31	AVG	2		4925.266	47.43	13.91	61.34	74.00	-12.66	peak
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																																	
		MHz	dBuV	dB/m	dBuV/m	dB	Detector																																	
1	*	4924.362	33.80	13.89	47.69	54.00	-6.31	AVG																																
2		4925.266	47.43	13.91	61.34	74.00	-12.66	peak																																
<b>Emission Level= Read Level+ Correct Factor</b>																																								

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%																																							
<b>Test Voltage:</b>	DC 32V																																									
<b>Ant. Pol.</b>	Horizontal																																									
<b>Test Mode:</b>	TX N(HT20) Mode 2412MHz																																									
<b>Remark:</b>	No report for the emission which more than 20 dB below the prescribed limit.																																									
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">No.</th> <th style="text-align: center;">Mk.</th> <th style="text-align: center;">Freq.</th> <th style="text-align: center;">Reading Level</th> <th style="text-align: center;">Correct Factor</th> <th style="text-align: center;">Measure-ment</th> <th style="text-align: center;">Limit</th> <th style="text-align: center;">Over</th> </tr> <tr> <th></th> <th></th> <th style="text-align: center;">MHz</th> <th style="text-align: center;">dBuV</th> <th style="text-align: center;">dB/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dB</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>*</td> <td style="text-align: center;">4824.416</td> <td style="text-align: center;">33.13</td> <td style="text-align: center;">13.16</td> <td style="text-align: center;">46.29</td> <td style="text-align: center;">54.00</td> <td style="text-align: center;">-7.71</td> <td>AVG</td> </tr> <tr> <td>2</td> <td></td> <td style="text-align: center;">4824.565</td> <td style="text-align: center;">48.09</td> <td style="text-align: center;">13.16</td> <td style="text-align: center;">61.25</td> <td style="text-align: center;">74.00</td> <td style="text-align: center;">-12.75</td> <td>peak</td> </tr> </tbody> </table>								No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	1	*	4824.416	33.13	13.16	46.29	54.00	-7.71	AVG	2		4824.565	48.09	13.16	61.25	74.00	-12.75	peak
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																																			
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector																																		
1	*	4824.416	33.13	13.16	46.29	54.00	-7.71	AVG																																		
2		4824.565	48.09	13.16	61.25	74.00	-12.75	peak																																		
<b>Emission Level= Read Level+ Correct Factor</b>																																										

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%																																							
<b>Test Voltage:</b>	DC 32V																																									
<b>Ant. Pol.</b>	Vertical																																									
<b>Test Mode:</b>	TX N(HT20) Mode 2412MHz																																									
<b>Remark:</b>	No report for the emission which more than 20 dB below the prescribed limit.																																									
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">No.</th> <th style="text-align: center;">Mk.</th> <th style="text-align: center;">Freq.</th> <th style="text-align: center;">Reading Level</th> <th style="text-align: center;">Correct Factor</th> <th style="text-align: center;">Measure-ment</th> <th style="text-align: center;">Limit</th> <th style="text-align: center;">Over</th> </tr> <tr> <th></th> <th></th> <th style="text-align: center;">MHz</th> <th style="text-align: center;">dBuV</th> <th style="text-align: center;">dB/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dB</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td></td> <td style="text-align: center;">4823.546</td> <td style="text-align: center;">48.10</td> <td style="text-align: center;">13.16</td> <td style="text-align: center;">61.26</td> <td style="text-align: center;">74.00</td> <td style="text-align: center;">-12.74</td> <td>peak</td> </tr> <tr> <td>2</td> <td>*</td> <td style="text-align: center;">4824.462</td> <td style="text-align: center;">32.87</td> <td style="text-align: center;">13.16</td> <td style="text-align: center;">46.03</td> <td style="text-align: center;">54.00</td> <td style="text-align: center;">-7.97</td> <td>AVG</td> </tr> </tbody> </table>								No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	1		4823.546	48.10	13.16	61.26	74.00	-12.74	peak	2	*	4824.462	32.87	13.16	46.03	54.00	-7.97	AVG
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																																			
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector																																		
1		4823.546	48.10	13.16	61.26	74.00	-12.74	peak																																		
2	*	4824.462	32.87	13.16	46.03	54.00	-7.97	AVG																																		
<b>Emission Level= Read Level+ Correct Factor</b>																																										

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%																																										
<b>Test Voltage:</b>	DC 32V																																												
<b>Ant. Pol.</b>	Horizontal																																												
<b>Test Mode:</b>	TX N(HT20) Mode 2437MHz																																												
<b>Remark:</b>	No report for the emission which more than 20 dB below the prescribed limit.																																												
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">No.</th> <th style="text-align: center;">Mk.</th> <th style="text-align: center;">Freq.</th> <th style="text-align: center;">Reading Level</th> <th style="text-align: center;">Correct Factor</th> <th style="text-align: center;">Measure-ment</th> <th style="text-align: center;">Limit</th> <th style="text-align: center;">Over</th> </tr> <tr> <th></th> <th></th> <th style="text-align: center;">MHz</th> <th style="text-align: center;">dBuV</th> <th style="text-align: center;">dB/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dB</th> </tr> <tr> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1</td> <td></td> <td style="text-align: center;">4873.364</td> <td style="text-align: center;">48.40</td> <td style="text-align: center;">13.16</td> <td style="text-align: center;">61.56</td> <td style="text-align: center;">74.00</td> <td style="text-align: center;">-12.44</td> <td>peak</td> </tr> <tr> <td style="text-align: center;">2</td> <td>*</td> <td style="text-align: center;">4873.562</td> <td style="text-align: center;">33.13</td> <td style="text-align: center;">13.16</td> <td style="text-align: center;">46.29</td> <td style="text-align: center;">54.00</td> <td style="text-align: center;">-7.71</td> <td>AVG</td> </tr> </tbody> </table>				No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB								Detector	1		4873.364	48.40	13.16	61.56	74.00	-12.44	peak	2	*	4873.562	33.13	13.16	46.29	54.00	-7.71	AVG
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																																						
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB																																						
							Detector																																						
1		4873.364	48.40	13.16	61.56	74.00	-12.44	peak																																					
2	*	4873.562	33.13	13.16	46.29	54.00	-7.71	AVG																																					
<b>Emission Level= Read Level+ Correct Factor</b>																																													


<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%																																										
<b>Test Voltage:</b>	DC 32V																																												
<b>Ant. Pol.</b>	Vertical																																												
<b>Test Mode:</b>	TX N(HT20) Mode 2437MHz																																												
<b>Remark:</b>	No report for the emission which more than 20 dB below the prescribed limit.																																												
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">No.</th> <th style="text-align: center;">Mk.</th> <th style="text-align: center;">Freq.</th> <th style="text-align: center;">Reading Level</th> <th style="text-align: center;">Correct Factor</th> <th style="text-align: center;">Measure-ment</th> <th style="text-align: center;">Limit</th> <th style="text-align: center;">Over</th> </tr> <tr> <th></th> <th></th> <th style="text-align: center;">MHz</th> <th style="text-align: center;">dBuV</th> <th style="text-align: center;">dB/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dB</th> </tr> <tr> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1</td> <td></td> <td style="text-align: center;">4874.462</td> <td style="text-align: center;">49.48</td> <td style="text-align: center;">13.16</td> <td style="text-align: center;">62.64</td> <td style="text-align: center;">74.00</td> <td style="text-align: center;">-11.36</td> <td>peak</td> </tr> <tr> <td style="text-align: center;">2</td> <td>*</td> <td style="text-align: center;">4875.652</td> <td style="text-align: center;">33.16</td> <td style="text-align: center;">13.18</td> <td style="text-align: center;">46.34</td> <td style="text-align: center;">54.00</td> <td style="text-align: center;">-7.66</td> <td>AVG</td> </tr> </tbody> </table>				No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB								Detector	1		4874.462	49.48	13.16	62.64	74.00	-11.36	peak	2	*	4875.652	33.16	13.18	46.34	54.00	-7.66	AVG
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																																						
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB																																						
							Detector																																						
1		4874.462	49.48	13.16	62.64	74.00	-11.36	peak																																					
2	*	4875.652	33.16	13.18	46.34	54.00	-7.66	AVG																																					
<b>Emission Level= Read Level+ Correct Factor</b>																																													

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%																																
<b>Test Voltage:</b>	DC 32V																																		
<b>Ant. Pol.</b>	Horizontal																																		
<b>Test Mode:</b>	TX N(HT20) Mode 2462MHz																																		
<b>Remark:</b>	No report for the emission which more than 20 dB below the prescribed limit.																																		
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">No.</th> <th style="text-align: center;">Mk.</th> <th style="text-align: center;">Freq.</th> <th style="text-align: center;">Reading Level</th> <th style="text-align: center;">Correct Factor</th> <th style="text-align: center;">Measure-ment</th> <th style="text-align: center;">Limit</th> <th style="text-align: center;">Over</th> </tr> <tr> <th></th> <th></th> <th style="text-align: center;">MHz</th> <th style="text-align: center;">dBuV</th> <th style="text-align: center;">dB/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dB</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">*</td> <td style="text-align: center;">4824.239</td> <td style="text-align: center;">33.87</td> <td style="text-align: center;">13.16</td> <td style="text-align: center;">47.03</td> <td style="text-align: center;">54.00</td> <td style="text-align: center;">-6.97</td> </tr> <tr> <td style="text-align: center;">2</td> <td></td> <td style="text-align: center;">4924.361</td> <td style="text-align: center;">47.40</td> <td style="text-align: center;">13.89</td> <td style="text-align: center;">61.29</td> <td style="text-align: center;">74.00</td> <td style="text-align: center;">-12.71</td> </tr> </tbody> </table>				No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	1	*	4824.239	33.87	13.16	47.03	54.00	-6.97	2		4924.361	47.40	13.89	61.29	74.00	-12.71
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																												
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB																												
1	*	4824.239	33.87	13.16	47.03	54.00	-6.97																												
2		4924.361	47.40	13.89	61.29	74.00	-12.71																												
<b>Emission Level= Read Level+ Correct Factor</b>																																			


<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%																																
<b>Test Voltage:</b>	DC 32V																																		
<b>Ant. Pol.</b>	Vertical																																		
<b>Test Mode:</b>	TX N(HT20) Mode 2462MHz																																		
<b>Remark:</b>	No report for the emission which more than 20 dB below the prescribed limit.																																		
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">No.</th> <th style="text-align: center;">Mk.</th> <th style="text-align: center;">Freq.</th> <th style="text-align: center;">Reading Level</th> <th style="text-align: center;">Correct Factor</th> <th style="text-align: center;">Measure-ment</th> <th style="text-align: center;">Limit</th> <th style="text-align: center;">Over</th> </tr> <tr> <th></th> <th></th> <th style="text-align: center;">MHz</th> <th style="text-align: center;">dBuV</th> <th style="text-align: center;">dB/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dB</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1</td> <td></td> <td style="text-align: center;">4923.294</td> <td style="text-align: center;">49.37</td> <td style="text-align: center;">13.89</td> <td style="text-align: center;">63.26</td> <td style="text-align: center;">74.00</td> <td style="text-align: center;">-10.74</td> </tr> <tr> <td style="text-align: center;">2</td> <td style="text-align: center;">*</td> <td style="text-align: center;">4924.261</td> <td style="text-align: center;">35.26</td> <td style="text-align: center;">13.89</td> <td style="text-align: center;">49.15</td> <td style="text-align: center;">54.00</td> <td style="text-align: center;">-4.85</td> </tr> </tbody> </table>				No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	1		4923.294	49.37	13.89	63.26	74.00	-10.74	2	*	4924.261	35.26	13.89	49.15	54.00	-4.85
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																												
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB																												
1		4923.294	49.37	13.89	63.26	74.00	-10.74																												
2	*	4924.261	35.26	13.89	49.15	54.00	-4.85																												
<b>Emission Level= Read Level+ Correct Factor</b>																																			

## Attachment C-- Restricted Bands Requirement and Band-edge Test Data

### (1) Radiation Test



Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 32V		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	44.36	1.28	45.64	74.00	-28.36	peak
2		2390.000	34.35	1.28	35.63	54.00	-18.37	AVG
3	X	2412.100	100.87	1.39	102.26	Fundamental Frequency		peak
4	*	2413.000	93.47	1.40	94.87	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor


Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 32V		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment			
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	X	2462.300	115.53	1.73	117.26	Fundamental Frequency		peak
2	*	2462.800	106.56	1.74	108.30	Fundamental Frequency		AVG
3		2483.500	57.47	1.88	59.35	74.00	-14.65	peak
4		2483.500	47.27	1.88	49.15	54.00	-4.85	AVG


Emission Level= Read Level+ Correct Factor


Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 32V		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2462MHz		
Remark:	N/A		





No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
1	X	2462.300	102.83	1.73	104.56	Fundamental Frequency	peak
2	*	2462.800	94.74	1.74	96.48	Fundamental Frequency	AVG
3		2483.500	46.41	1.88	48.29	74.00	-25.71 peak
4		2483.500	36.91	1.88	38.79	54.00	-15.21 AVG

Emission Level= Read Level+ Correct Factor











Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 32V		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1		2390.000	51.06	1.28	52.34	74.00	-21.66 peak
2		2390.000	40.75	1.28	42.03	54.00	-11.97 AVG
3	X	2413.300	107.05	1.41	108.46	Fundamental Frequency	peak
4	*	2414.600	96.84	1.41	98.25	Fundamental Frequency	AVG


Emission Level= Read Level+ Correct Factor


Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 32V		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
1		2390.000	45.85	1.28	47.13	74.00	-26.87 peak
2		2390.000	35.77	1.28	37.05	54.00	-16.95 AVG
3	X	2412.500	94.25	1.40	95.65	Fundamental Frequency	peak
4	*	2414.600	84.95	1.41	86.36	Fundamental Frequency	AVG


Emission Level= Read Level+ Correct Factor







## (2) Conducted Test


Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 32V		
Test Mode:	TX B Mode 2412MHz / TX B Mode 2462MHz		
Remark:	The EUT is programed in continuously transmitting mode		








## Attachment D-- Bandwidth Test Data


Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 32V		
Test Mode:	TX 802.11B Mode		
Channel frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
2412	8.233	12.871	>=0.5
2437	7.607	12.780	
2462	7.592	12.789	
<b>802.11B Mode</b>			
<b>2412 MHz</b>			
			



Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 32V		
Test Mode:	TX 802.11G Mode		
Channel frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
2412	17.37	17.812	
2437	17.18	17.821	>=0.5
2462	17.46	17.835	
<b>802.11G Mode</b>			
<b>2412 MHz</b>			
			


## 802.11G Mode


2437 MHz




## 802.11G Mode

2462 MHz



Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 32V		
Test Mode:	TX 802.11N(HT20) Mode		
Channel frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
2412	13.88	17.528	
2437	14.96	17.535	>=0.5
2462	17.30	17.785	
<b>802.11N(HT20) Mode</b>			
<b>2412 MHz</b>			
			
<b>Occupied Bandwidth</b> <b>17.528 MHz</b>			
Transmit Freq Error	11.767 kHz	% of OBW Power	99.00 %
x dB Bandwidth	13.88 MHz	x dB	-6.00 dB



## Attachment E-- Peak Output Power Test Data

<b>Test Conditions:</b>		Continuous Transmitting Mode	
Temperature:	25 °C	Relative Humidity:	55%
<b>Test Voltage:</b>		DC 32V	
Mode	Channel frequency (MHz)	Test Result (dBm)	Limit (dBm)
802.11b	2412	15.54	30
	2437	15.55	
	2462	15.22	
802.11g	2412	14.35	
	2437	14.99	
	2462	14.80	
802.11n (HT20)	2412	13.13	
	2437	13.78	
	2462	13.00	
<b>Result:</b> PASS			


Duty Cycle		
Mode	Channel frequency (MHz)	Test Result
802.11b	2412	
	2437	
	2462	
802.11g	2412	>98%
	2437	
	2462	
802.11n (HT20)	2412	
	2437	
	2462	


Please see below plots

## 802.11 B Mode 2437 MHz



## 802.11 G Mode 2437 MHz







## Attachment F-- Power Spectral Density Test Data


Temperature:	25 °C	Relative Humidity:	55%	
Test Voltage:	DC 32V			
Test Mode:	TX 802.11B Mode			
Channel Frequency (MHz)		Power Density (dBm/3 kHz)	Limit (dBm/3 kHz)	
2412		-5.068	8	
2437		-7.265		
2462		-6.611		
802.11B Mode				
2412 MHz				
				



<b>Temperature:</b>	25 °C	<b>Temperature:</b>	25 °C	
<b>Test Voltage:</b>	DC 32V			
<b>Test Mode:</b>	TX 802.11G Mode			
<b>Channel Frequency (MHz)</b>		<b>Power Density (dBm/3 kHz)</b>	<b>Limit (dBm/3 kHz)</b>	
2412		-10.347	8	
2437		-9.298		
2462		-9.820		
<b>802.11G Mode</b>				
<b>2412 MHz</b>				
				



<b>Temperature:</b>	25 °C	<b>Temperature:</b>	25 °C
<b>Test Voltage:</b>	DC 32V		
<b>Test Mode:</b>	TX 802.11N(HT20) Mode		
<b>Channel Frequency (MHz)</b>		<b>Power Density (dBm/3 kHz)</b>	<b>Limit (dBm/3 kHz)</b>
2412		-11.258	
2437		-12.238	8
2462		-10.761	
<b>802.11N(HT20) Mode</b>			
<b>2412 MHz</b>			
			



-----END OF REPORT-----