



FCC TEST REPORT

FCC ID: 2AWVE0IRISIANVERSAN

Product Name	:	VERSA N
Model Name	:	J80
Brand Name	:	IRISIAN
Report No.	:	PTC20051404901E-FC02
Prepared for		
Shanghai Irisian Optronics Technology Co.,Ltd		
Floor 8, No. 800, Second West Huanhu Road, Pudong New District, Shanghai		
Prepared by		
Precise Testing & Certification Corp., Ltd.		
Building 1, No.6 Tongxin Road, Dongcheng Street, Dongguan,China		



1TEST RESULT CERTIFICATION

Applicant's name : Shanghai Irisian Optronics Technology Co.,Ltd
Address : Floor 8, No. 800, Second West Huanhu Road, Pudong New District, Shanghai

Manufacture's name : Shanghai Irisian Optronics Technology Co.,Ltd
Address : Floor 8, No. 800, Second West Huanhu Road, Pudong New District, Shanghai

Product name : VERSA N
Model name : J80

Standards : FCC CFR47 Part 15 Section 15.247
Test procedure : ANSI C63.10:2013
Test Date : June 10, 2020 to June 28, 2020
Date of Issue : July 08, 2020
Test Result : Pass

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink that reads 'Leo Yang'.

Leo Yang / Engineer

Technical Manager:

A handwritten signature in black ink that appears to read 'Chris Du'.

Chris Du / Manager



TABLE OF CONTENTS

	Test report declares.....	4
1.	Summary of test results.....	6
2.	General test information.....	7
2.1.	Description of EUT.....	7
2.2.	Accessories of EUT.....	7
2.3.	Assistant equipment used for test.....	8
2.4.	Block diagram of EUT configuration for test.....	8
2.5.	Deviations of test standard.....	8
2.6.	Test environment conditions.....	8
2.7.	Test laboratory.....	9
2.8.	Measurement uncertainty.....	9
3.	Equipment used during test.....	10
4.	6dB Bandwidth.....	11
4.1.	Block diagram of test setup.....	11
4.2.	Limits.....	11
4.3.	Test Procedure.....	11
4.4.	Test Result.....	12
4.5.	original test data.....	13
5.	Conducted peak Output Power.....	23
5.1.	Block diagram of test setup.....	23
5.2.	Limits.....	23
5.3.	Test Procedure.....	23
5.4.	Test Result.....	24
5.5.	original test data.....	25
6.	Power Spectral Density.....	35
6.1.	Block diagram of test setup.....	35
6.2.	Limits.....	35
6.3.	Test Procedure.....	35
6.4.	Test Result.....	36
6.5.	original test data.....	37



7.	Band Edge and Spurious Emissions (Conducted).....	48
7.1.	Block diagram of test setup.....	48
7.2.	Limits.....	48
7.3.	Test Procedure.....	48
7.4.	Test Result.....	49
7.5.	original test data.....	49
8.	Radiated Spurious Emissions.....	88
8.1.	Block diagram of test setup.....	88
8.2.	Limit.....	89
8.3.	Test Procedure.....	90
8.4.	Test result.....	92
9.	Radiated Band Edge Compliance.....	96
9.1.	Block diagram of test setup.....	96
9.2.	Limit.....	96
9.3.	Test Procedure.....	96
9.4.	Test result.....	96
10.	Power Line Conducted Emission.....	113
10.1.	Block diagram of test setup.....	113
10.2.	Power Line Conducted Emission Limits(Class B).....	113
10.3.	Test Procedure.....	113
10.4.	Test Result.....	114
11.	Antenna Requirements.....	117
11.1.	Limit.....	117
11.2.	Result.....	117



1. Summary of test results

The EUT have been tested according to the applicable standards as referenced below.		
Description of Test Item	Standard	Results
6dB Bandwidth Bandwidth	FCC 15.247 (a) (2)	PASS
Conducted Output Power	FCC 15.247 (b) (3)	PASS
Power Spectral Density	FCC 15.247 (e)	PASS
Band-edge and Spurious Emissions (Conducted)	FCC 15.247 (d)	PASS
Radiated Spurious Emissions	FCC 15.247 (d) FCC 15.209 FCC 15.205	PASS
Radiated Band Edge Compliance	FCC 15.247 (d) FCC 15.209 FCC 15.205	PASS
Power Line Conducted Emission	FCC 15.207	PASS
Antenna requirement	FCC 15.203	PASS



2. TEST FACILITY

Dongguan Precise Testing & Certification Corp., Ltd.

Address: Building 1, No.6 Tongxin Road, Dongcheng Street, Dongguan, China

FCC Registration Number: 790290

A2LA Certificate No.: 4408.01

IC Registration Number: 12191A-1

3. General test information

3.1. Description of EUT

EUT* Name	: VERSA N
Model Number	: J80
EUT function description	: Please reference user manual of this device
Power supply	: DC 12V from external AC Adapter (Model : HKA03612030-7K)
Radio Technology	: IEEE 802.11b/g/n
Operation frequency	: IEEE 802.11b: 2412MHz—2462MHz IEEE 802.11g: 2412MHz—2462MHz IEEE 802.11n HT20: 2412MHz—2462MHz
Modulation	: IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Transmitter rate	: IEEE 802.11b: 1, 2, 5.5, 11 Mbps IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps IEEE 802.11n HT20: up to 150 Mbps
Antenna Type	: Integrated metal antenna 0: 2.4G band maximum PK gain 2dBi Integrated metal antenna 1: 2.4G band maximum PK gain 2dBi
Sample Type	: Single production

Note1: EUT is the ab. of equipment under test.

Antenna information			
	Ant0 gain	Ant1 gain	MIMO
IEEE 802.11b	2	/	/
IEEE 802.11g	2	2	/
IEEE 802.11n HT20	2	2	6.01

Channel information							
CH	Frequency	CH	Frequency	CH	Frequency	CH	Frequency
1	2412	5	2432	9	2452	/	/
2	2417	6	2437	10	2457	/	/
3	2422	7	2442	11	2462	/	/
4	2427	8	2447	/	/	/	/

Note: Directional gain calculation result is; 6.01 dBi. The limit will be reduce 0.01 dBm.



32 Accessories of EUT

Description of Accessories	Manufacturer	Model number	Serial No.	Other
AC Adapter	N/A	HKA03612030-7K	N/A	Input: AC 100-240V -50/60Hz, 1A; Output: DC 12V, 3A; Length: 1.60m

33 Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	EMC Compliance	SN
Notebook	DELL	Latitude D610	FCC DOC	00045-534-136-300
Network Cable	N/A	N/A	N/A	Length: 1.5m

34 Block diagram of EUT configuration for test



EUT was connected to control to provided by manufacturer which has a standard LAN PORT connector to connect to Notebook, and the Notebook will run “CMD telnet” to control EUT work in Continuous Tx mode, and select test channel, wireless mode and data rate.

Tested mode, channel, and data rate information				
Mode	Setting Tx Power	data rate (Mbps) (see Note)	Channel	Frequency (MHz)
IEEE 802.11b	/	11	LCH :CH1	2412
	/	11	MCH: CH6	2437
	/	11	HCH: CH11	2462
IEEE 802.11g	/	54	LCH :CH1	2412
	/	54	MCH: CH6	2437
	/	54	HCH: CH11	2462
IEEE 802.11n HT20	/	MCS 7	LCH :CH1	2412
	/	MCS 7	MCH: CH6	2437
	/	MCS 7	HCH: CH11	2462

Note: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.

35 Deviations of test standard

No Deviation

36 Test environment conditions

During the measurement the environmental conditions were within the listed ranges:



Report No.: PTC20051404901E-FC02

Temperature range:	21-25°C
Humidity range:	40-75%
Pressure range:	86-106kPa



3.7. Measurement uncertainty

Parameter	Uncertainty
RF output power, conducted	$\pm 1.0\text{dB}$
Power Spectral Density, conducted	$\pm 2.2\text{dB}$
Radio Frequency	$\pm 1 \times 10^{-6}$
Bandwidth	$\pm 1.5 \times 10^{-6}$
Time	$\pm 2\%$
Duty Cycle	$\pm 2\%$
Temperature	$\pm 1^{\circ}\text{C}$
Humidity	$\pm 5\%$
DC and low frequency voltages	$\pm 3\%$
Conducted Emissions (150kHz~30MHz)	$\pm 3.64\text{dB}$
Radiated Emission(30MHz~1GHz)	$\pm 5.03\text{dB}$
Radiated Emission(1GHz~25GHz)	$\pm 4.74\text{dB}$
Remark: The coverage Factor (k=2), and measurement Uncertainty for a level of Confidence of 95%	




4. Equipment used during test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
RF Connected Test (Tonscend RF Measurement System)					
Spectrum analyzer	R&S	FSU26	200071	Sep. 19, 2019	1 Year
Wideband Radio Communication tester	R&S	CMW500	117491	Sep. 19, 2019	1 Year
Vector Signal Generator	Agilent	E8267D	US49060192	Sep. 19, 2019	1 Year
Vector Signal Generator	Agilent	N5182A	MY48180737	Sep. 19, 2019	1 Year
Power Sensor	Agilent	U2021XA	MY55150010	Sep. 19, 2019	1 Year
Power Sensor	Agilent	U2021XA	MY55150011	Sep. 19, 2019	1 Year
DC Power Source	MATRIS	MPS-3005L-3	D813058W	Sep. 19, 2019	1 Year
Attenuator	Mini-Circuits	BW-S10W2	101109	Sep. 19, 2019	1 Year
RF Cable	Micable	C10-01-01-1	100309	Sep. 19, 2019	1 Year
Temp&Humi Programmable	ZHIXIANG	ZXGDS-150 L	ZX170110-A	Sep. 19, 2019	1 Year
Test Software	JS Tonscend	JS1120-3	Ver.2.7	N/A	N/A
Radiated Emission Test Chamber 1#					
EMI Test Receiver	R&S	ESU8	100316	Sep. 19, 2019	1 Year
Spectrum analyzer	Agilent	E4447A	MY50180031	Sep. 19, 2019	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB9163	9163-462	Sep. 19, 2019	1 Year
Active Loop antenna	Schwarzbeck	FMZB-1519	1519-038	Sep. 19, 2019	1 Year
Double Ridged Horn Antenna	R&S	HF907	100276	Sep. 19, 2019	1 Year
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	790	Sep. 19, 2019	1 Year
Pre-amplifier	A.H.	PAM-0118	360	Sep. 19, 2019	1 Year
Pre-amplifier	TERA-MW	TRLA-0040G 35	101303	Sep. 19, 2019	1 Year
RF Cable	HUBSER	CP-X2+ CP-X1	W11.03+ W12.02	Sep. 19, 2019	1 Year
RF Cable	N/A	SMAJ-SMAJ-1M+ 11M	17070133+17070131	Sep. 19, 2019	1 Year
MI Cable	HUBSER	C10-01-01-1 M	1091629	Sep. 19, 2019	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A
Power Line Conducted Emissions Test					
Test Receiver	R&S	ESU8	100316	Sep. 19, 2019	1 Year
LISN 1	R&S	ENV216	101109	Sep. 19, 2019	1 Year
LISN 2	R&S	ESH2-Z5	100309	Sep. 19, 2019	1 Year
Pulse Limiter	R&S	ESH3-Z2	101242	Sep. 19, 2019	1 Year
CE Cable 1	HUBSER	N/A	W10.01	Sep. 19, 2019	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A

5. 6dB Bandwidth

51. Block diagram of test setup



52. Limits

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500 kHz

53. Test Procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Set the spectrum analyzer as follows:


RBW:	100kHz
VBW:	300kHz
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold
- (3) Allow the trace to stabilize, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.




54 Test Result


Test Mode	Freq. [MHz]	Ant	6dB Bandwidth [MHz]	Limit	Verdict
11B	2412	Ant0	8.000	0.5	PASS
11B	2437	Ant0	7.640	0.5	PASS
11B	2462	Ant0	8.120	0.5	PASS
11G	2412	Ant0	15.760	0.5	PASS
11G	2412	Ant1	15.160	0.5	PASS
11G	2437	Ant0	15.160	0.5	PASS
11G	2437	Ant1	14.200	0.5	PASS
11G	2462	Ant0	15.440	0.5	PASS
11G	2462	Ant1	15.200	0.5	PASS
11N20	2412	Ant0	15.200	0.5	PASS
11N20	2412	Ant1	16.040	0.5	PASS
11N20	2437	Ant0	16.400	0.5	PASS
11N20	2437	Ant1	16.160	0.5	PASS
11N20	2462	Ant0	17.440	0.5	PASS
11N20	2462	Ant1	16.320	0.5	PASS

55 original test data







11G_Ant0_2412




11G_Ant1_2412




11G_Ant0_2437




11G_Ant1_2437




11G_Ant0_2462




11G_Ant1_2462




11N20MIMO_Ant0_2412




11N20MIMO_Ant1_2412






11N20MIMO_Ant0_2462



11N20MIMO_Ant1_2462





6. Conducted peak Output Power

6.1. Block diagram of test setup

Same as section 4.1

6.2 Limits

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

6.3 Test Procedure

Connect each EUT's antenna output to power sensor by RF cable and attenuator
Measure the PK output power of each antenna port by Spectrum Analyzer.





64 Test Result

Test Mode	Antenna	Freq. [MHz]	Power[dBm]	Limit[dBm]	Verdict
11B	Ant0	2412	24.76	30	PASS
11B	Ant0	2437	24.95	30	PASS
11B	Ant0	2462	24.57	30	PASS
11G	Ant0	2412	23.38	30	PASS
11G	Ant1	2412	22.87	30	PASS
11G	Ant0	2437	23.55	30	PASS
11G	Ant1	2437	23.22	30	PASS
11G	Ant0	2462	23.38	30	PASS
11G	Ant1	2462	22.89	30	PASS
11N20 MIMO	Ant0	2412	21.98	30	PASS
11N20 MIMO	Ant1	2412	21.99	30	PASS
11N20 MIMO	total	2412	25.01	30	PASS
11N20 MIMO	Ant0	2437	22.14	30	PASS
11N20 MIMO	Ant1	2437	22.16	30	PASS
11N20 MIMO	total	2437	25.16	30	PASS
11N20 MIMO	Ant0	2462	21.63	30	PASS
11N20 MIMO	Ant1	2462	21.60	30	PASS
11N20 MIMO	total	2462	24.61	30	PASS




65 original test data







11G_Ant0_2412




11G_Ant1_2412




11G_Ant0_2437




11G_Ant1_2437




11G_Ant0_2462




11G_Ant1_2462




11N20MIMO_Ant0_2412




11N20MIMO_Ant1_2412




11N20MIMO_Ant0_2437




11N20MIMO_Ant1_2437



11N20MIMO_Ant0_2462



11N20MIMO_Ant1_2462





7. Power Spectral Density

7.1. Block diagram of test setup

Same as section 4.1

7.2 Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

7.3 Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows:

Center frequency	DTS Channel center frequency
RBW:	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW:	$\geq 3\text{RBW}$
Span	1.5times the DTS bandwidth
Detector Mode:	RMS
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.

(4) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.





74 Test Result

Test Mode	Antenna	Freq. [MHz]	PSD[dBm]	Limit[dBm/kHz]	Verdict
11B	Ant0	2412	4.35	8.00	PASS
11B	Ant0	2437	5.02	8.00	PASS
11B	Ant0	2462	4.43	8.00	PASS
11G	Ant0	2412	-0.83	8.00	PASS
11G	Ant1	2412	-0.08	8.00	PASS
11G	Ant0	2437	0.18	8.00	PASS
11G	Ant1	2437	-1.13	8.00	PASS
11G	Ant0	2462	-1.66	8.00	PASS
11G	Ant1	2462	-1.72	8.00	PASS
11N20 MIMO	Ant0	2412	-0.93	8.00	PASS
11N20 MIMO	Ant1	2412	-1.12	8.00	PASS
11N20 MIMO	total	2412	1.99	8.00	PASS
11N20 MIMO	Ant0	2437	-1.19	8.00	PASS
11N20 MIMO	Ant1	2437	-1.13	8.00	PASS
11N20 MIMO	total	2437	1.85	8.00	PASS
11N20 MIMO	Ant0	2462	-1.10	8.00	PASS
11N20 MIMO	Ant1	2462	-1.95	8.00	PASS
11N20 MIMO	total	2462	1.51	8.00	PASS




7.5 original test data







11G_Ant0_2412




11G_Ant1_2412




11G_Ant0_2437




11G_Ant1_2437




11G_Ant0_2462




11G_Ant1_2462








11N20MIMO_Ant0_2437



11N20MIMO_Ant1_2437







8. Band Edge and Spurious Emissions (Conducted)

8.1. Block diagram of test setup

Same as section 4.1

8.2 Limits

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

8.3 Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	DTS Channel center frequency
RBW:	100kHz
VBW:	300kHz
Span	1.5times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:

RBW:	100kHz
VBW:	300kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{span}/\text{RBW}$
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band




84 Test Result


EUT Set Mode	CH or Frequency	Ant0 Result (dBm)	EUT Set Mode	CH or Frequency	Ant0 Result Result (dBm)
11b	CH1	PASS	11n HT 20	CH1	PASS
	CH6	PASS		CH6	PASS
	CH11	PASS		CH11	PASS

EUT Set Mode	CH or Frequency	Ant1 Result (dBm)	EUT Set Mode	CH or Frequency	Ant1 Result (dBm)
11b	CH1	/	11n HT 20	CH1	PASS
	CH6	/		CH6	PASS
	CH11	/		CH11	PASS


85 original test data

Band Edge







11G_Ant0_Low




11G_Ant1_Low




11G_Ant0_High




11G_Ant1_High




11N20MIMO_Ant0_Low




11N20MIMO_Ant1_Low



11N20MIMO_Ant0_High





11N20MIMO_Ant1_High




Spurious Emissions

11B_Ant0_2412_Ref







11B_Ant0_2412_1000~26500




11B_Ant0_2437_Ref







11B_Ant0_2437_30~1000




11B_Ant0_2437_1000~26500












11G_Ant1_2412_Ref




11G_Ant1_2412_30~1000




11G_Ant1_2412_1000~26500




11G_Ant0_2437_Ref





11G_Ant0_2437_30~1000





11G_Ant0_2437_1000~26500






















11N20MIMO_Ant1_2412_Ref





11N20MIMO_Ant1_2412_30~1000



















9. Radiated Spurious Emissions

9.1. Block diagram of test setup


In 3m Anechoic Chamber Test Setup Diagram for 9kHz-30MHz



In 3m Anechoic Chamber Test Setup Diagram for 30MHz-1GHz



In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

92 Limit

9.2.1 FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.G
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

9.2.2 FCC 15.209 Limit.

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V/m}$	$\text{dB}(\mu\text{V})/\text{m}$
0.009 ~ 0.490	300	$2400/F(\text{kHz})$	$67.6-20\log(F)$
0.490 ~ 1.705	30	$24000/F(\text{kHz})$	$87.6-20\log(F)$
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)	

Note: (1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3\text{m}}(\text{dB}\mu\text{V}/\text{m}) = \text{Limit}_{30\text{m}}(\text{dB}\mu\text{V}/\text{m}) + 40\log(30\text{m}/3\text{m})$$

9.2.3 Limit for this EUT

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

9.3 Test Procedure

(1) EUT height should be 0.8m for below 1GHz at a semi - anechoic chamber while EUT height should be 1.5m for above 1GHz at full chamber or semi - anechoic chamber ground with absorbers.

(2) The antenna used as below table.

Test frequency range	Test antenna used	Measuring distance
9kHz-30MHz	Active Loop antenna	3 m
30MHz-1GHz	Trilog Broadband Antenna	3 m
1GHz-18GHz	Double Ridged Horn Antenna(1GHz-18GHz)	3 m
18GHz-40GHz	Horn Antenna(18GHz-40GHz)	1 m

According ANSI C63.10:2013 clause 6.4.4.2 and 6.5.3, for measurements below 30 MHz, the loop antenna was positioned with its plane vertical from the EUT and rotated about its vertical



axis for maximum response at each azimuth position around the EUT. And the loop antenna also be positioned with its plane horizontal at the specified distance from the EUT. The center of the loop is 1 m above the ground. for measurement above 30MHz, the Trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9kHz to 25GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1m to 4m(Except loop antenna, it's fixed 1m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9kHz to 25GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18GHz to 25GHz, so below final test was performed with frequency range from 9kHz to 18GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 2013 on Radiated Emission test.

(5) The emissions from 9kHz to 1GHz were measured based on CISPR QP detector except for the frequency bands 9-90kHz, 110-490kHz, for emissions from 9kHz-90kHz,110kHz-490kHz and above 1GHz were measured based on average detector, for emissions above 1GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9kHz to 1GHz, QP or average values were measured with EMI receiver with below RBW

Frequency band	RBW
9kHz-150kHz	200Hz
150kHz-30MHz	9kHz
30MHz-1GHz	120kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum



Report No.: PTC20051404901E-FC02

Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RMS detector RBW 1MHz VBW 3MHz for Average measure(according ANSI C63.10:2013 clause 4.2.3.2.3 procedure for average measure).



94 Test result

PASS. (See below detailed test result)

All the emissions except fundamental emission from 9kHz to 25GHz were comply with 15.209 limit.


Note1: According exploratory test no any obvious emission were detected from 9kHz to 30MHz and 18GHz to 25GHz, so the final test was performed with frequency range from 30MHz to 18GHz and recorded in below.

Note2: For emissions below 1GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1GHz, the final test was only performed with EUT working in Ant0, 11b, Tx CH6 mode.

Note3: For emissions above 1GHz, Scan with 11b mode ANT 1, 11g mode ANT 1 and ANT 0, 11n HT20 mode ANT 1 and ANT0, the worst case is 11b ANT 1 mode

Radiated Emission test (below 1GHz)

HORIZONTAL




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	59.44	4.94	11.52	4.09	20.55	40.00	-19.45	QP	HORIZONTAL
2	155.36	9.94	8.34	4.80	23.08	43.50	-20.42	QP	HORIZONTAL
3	229.29	11.84	12.11	5.19	29.14	46.00	-16.86	QP	HORIZONTAL
4	403.25	3.59	15.28	5.93	24.80	46.00	-21.20	QP	HORIZONTAL
5	531.96	7.52	18.15	5.78	31.45	46.00	-14.55	QP	HORIZONTAL
6	787.85	5.32	21.12	7.28	33.72	46.00	-12.28	QP	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

VERTICAL



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBUV/m)	Limit Line (dBUV/m)	Over Limit (dB)	Detector	Polarization
1	37.29	10.76	12.06	3.85	26.67	40.00	-13.33	QP	VERTICAL
2	65.80	15.39	10.08	4.14	29.61	40.00	-10.39	QP	VERTICAL
3	156.46	18.00	8.40	4.80	31.20	43.50	-12.30	QP	VERTICAL
4	231.72	12.33	12.15	5.20	29.68	46.00	-16.32	QP	VERTICAL
5	462.35	4.65	16.69	5.54	26.88	46.00	-19.12	QP	VERTICAL
6	912.86	3.46	22.57	7.64	33.67	46.00	-12.33	QP	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.


Radiated Emission test (above 1GHz)

Freq (MHz)	Read level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector type	Polarization
11b CH1									
4825.00	43.03	34.72	43.91	7.40	41.24	74.00	-32.76	Peak	HORIZONTAL
6525.00	41.00	35.76	43.36	8.27	41.67	74.00	-32.33	Peak	HORIZONTAL
8939.00	40.83	37.48	44.08	10.30	44.53	74.00	-29.47	Peak	HORIZONTAL
11506.00	39.09	38.60	44.17	11.01	44.53	74.00	-29.47	Peak	HORIZONTAL
13121.00	41.03	39.42	44.38	11.47	47.54	74.00	-26.46	Peak	HORIZONTAL
14889.00	40.06	41.58	44.29	12.81	50.16	74.00	-23.84	Peak	HORIZONTAL
4774.00	41.82	34.64	43.94	7.35	39.87	74.00	-34.13	Peak	VERTICAL
6389.00	40.04	35.70	43.32	8.26	40.68	74.00	-33.32	Peak	VERTICAL
8599.00	39.14	37.34	43.98	9.91	42.41	74.00	-31.59	Peak	VERTICAL
10095.00	40.88	38.26	44.39	10.91	45.66	74.00	-28.34	Peak	VERTICAL
12050.00	39.57	38.89	44.11	10.99	45.34	74.00	-28.66	Peak	VERTICAL
14821.00	39.85	41.56	44.31	12.78	49.88	74.00	-24.12	Peak	VERTICAL
11b CH6									
4774.00	41.29	34.64	43.94	7.35	39.34	74.00	-34.66	Peak	HORIZONTAL
6525.00	40.20	35.76	43.36	8.27	40.87	74.00	-33.13	Peak	HORIZONTAL
9024.00	39.70	37.51	44.11	10.38	43.48	74.00	-30.52	Peak	HORIZONTAL
10979.00	40.37	38.79	44.25	11.06	45.97	74.00	-28.03	Peak	HORIZONTAL
13121.00	38.49	39.42	44.38	11.47	45.00	74.00	-29.00	Peak	HORIZONTAL
13954.00	39.77	39.98	44.59	12.31	47.47	74.00	-26.53	Peak	HORIZONTAL
4825.00	43.92	34.72	43.91	7.40	42.13	74.00	-31.87	Peak	VERTICAL
5981.00	39.68	35.69	43.21	8.20	40.36	74.00	-33.64	Peak	VERTICAL
8956.00	39.61	37.48	44.09	10.32	43.32	74.00	-30.68	Peak	VERTICAL
10894.00	40.59	38.74	44.27	11.04	46.10	74.00	-27.90	Peak	VERTICAL
14141.00	39.96	40.42	44.55	12.43	48.26	74.00	-25.74	Peak	VERTICAL
15569.00	39.67	42.63	44.05	13.23	51.48	74.00	-22.52	Peak	VERTICAL
11b CH11									
4740.00	41.99	34.58	43.96	7.32	39.93	74.00	-34.07	Peak	HORIZONTAL
5760.00	40.81	35.60	43.34	8.06	41.13	74.00	-32.87	Peak	HORIZONTAL
7630.00	39.79	37.05	43.69	8.90	42.05	74.00	-31.95	Peak	HORIZONTAL
9194.00	40.43	37.58	44.16	10.47	44.32	74.00	-29.68	Peak	HORIZONTAL
10945.00	39.21	38.77	44.26	11.05	44.77	74.00	-29.23	Peak	HORIZONTAL
13410.00	39.04	39.71	44.45	11.76	46.06	74.00	-27.94	Peak	HORIZONTAL
4825.00	43.81	34.72	43.91	7.40	42.02	74.00	-31.98	Peak	VERTICAL
6440.00	40.57	35.70	43.33	8.26	41.20	74.00	-32.80	Peak	VERTICAL
7936.00	40.24	37.17	43.78	9.17	42.80	74.00	-31.20	Peak	VERTICAL
9959.00	40.77	38.16	44.39	10.87	45.41	74.00	-28.59	Peak	VERTICAL
12050.00	39.69	38.89	44.11	10.99	45.46	74.00	-28.54	Peak	VERTICAL
15552.00	39.34	42.62	44.06	13.22	51.12	74.00	-22.88	Peak	VERTICAL



Report No.: PTC20051404901E-FC02


Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

3: For emissions above 1GHz. If peak results comply with AV limit, AV Result is deemed to comply with AV limit.

10. Radiated Band Edge Compliance

101. Block diagram of test setup



102. Limit

All restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with RSS-Gen Issue 3 clause 7.2.5 (Same as FCC 15.209) limits.

103. Test Procedure

Same with clause 8.3 except change investigated frequency range from 2310MHz to 2422MHz and 2450MHz to 2500MHz.

Remark: All restriction band have been tested, and only the worse case is shown in report.

104. Test result

PASS. (See below detailed test result)


Note: 11b Ant0, 11g ANT 0/1, n20 ANT 0/1 mode all have been tested, only ANT 1 mode is worse case and reported.



Memo : 11B 2412MHz HORIZONTAL

Report No.: PTC20051404901E-FC02

Data: 6




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/ m)	Over Limit (dB)	Detector	Polarization
1	2321.42	62.37	26.76	44.32	5.03	49.84	74.00	-24.16	Peak	HORIZONTAL
2	2389.97	56.63	27.00	44.32	5.11	44.42	74.00	-29.58	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.



Memo : 11B 2412MHz VERTICAL

Data: 5




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/ m)	Over Limit (dB)	Detector	Polarization
1	2362.64	48.04	26.91	44.32	5.08	35.71	74.00	-38.29	Peak	VERTICAL
2	2389.97	54.71	27.00	44.32	5.11	42.50	74.00	-31.50	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.



Memo : 11B 2462MHz HORIZONTAL

Data: 14




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/ m)	Over Limit (dB)	Detector	Polarization
1	2483.50	55.29	27.34	44.32	5.21	43.52	74.00	-30.48	Peak	HORIZONTAL
2	2487.50	52.50	27.35	44.32	5.22	40.75	74.00	-33.25	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.



Memo : 11B 2462MHz VERTICAL

Data: 13




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/ m)	Over Limit (dB)	Detector	Polarization
1	2483.50	52.99	27.34	44.32	5.21	41.22	74.00	-32.78	Peak	VERTICAL
2	2488.60	49.82	27.36	44.32	5.22	38.08	74.00	-35.92	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.



Memo : 11G 2412MHz HORIZONTAL

Data: 15




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2374.40	59.86	26.95	44.32	5.09	47.58	74.00	-26.42	Peak	HORIZONTAL
2	2389.97	64.97	27.00	44.32	5.11	52.76	74.00	-21.24	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.



Memo : 11G 2412MHz VERTICAL

Data: 16




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/ m)	Over Limit (dB)	Detector	Polarization
1	2379.10	59.96	26.96	44.32	5.10	47.70	74.00	-26.30	Peak	VERTICAL
2	2389.97	63.55	27.00	44.32	5.11	51.34	74.00	-22.66	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.



Memo : 11G 2462MHz HORIZONTAL

Data: 18




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	65.03	27.34	44.32	5.21	53.26	74.00	-20.74	Peak	HORIZONTAL
2	2483.65	69.08	27.34	44.32	5.21	57.31	74.00	-16.69	Peak	HORIZONTAL
3	2483.71	49.55	27.34	44.32	5.21	37.78	54.00	-16.22	Average	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Test setup: RBW: 1 MHz, VBW: 10 Hz, Sweep time: auto for average measure.



Memo : 11G 2462MHz VERTICAL

Data: 17




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/ m)	Over Limit (dB)	Detector	Polarization
1	2483.50	62.17	27.34	44.32	5.21	50.40	74.00	-23.60	Peak	VERTICAL
2	2488.90	60.61	27.36	44.32	5.22	48.87	74.00	-25.13	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.



Memo : 11N20 2412MHz HORIZONTAL

Data: 19




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/ m)	Over Limit (dB)	Detector	Polarization
1	2384.14	60.54	26.98	44.32	5.10	48.30	74.00	-25.70	Peak	HORIZONTAL
2	2390.00	63.46	27.00	44.32	5.11	51.25	74.00	-22.75	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.



Memo : 11N20 2412MHz VERTICAL

Data: 20




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/ m)	Over Limit (dB)	Detector	Polarization
1	2354.46	50.15	26.88	44.32	5.07	37.78	74.00	-36.22	Peak	VERTICAL
2	2390.00	62.57	27.00	44.32	5.11	50.36	74.00	-23.64	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.



Memo : 11N20 2462MHz HORIZONTAL

Data: 22



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/ m)	Over Limit (dB)	Detector	Polarization
1	2483.50	51.14	27.34	44.32	5.21	39.37	54.00	-14.63	Average	HORIZONTAL
2	2483.50	68.99	27.34	44.32	5.21	57.22	74.00	-16.78	Peak	HORIZONTAL
3	2485.10	49.32	27.35	44.32	5.21	37.56	54.00	-16.44	Average	HORIZONTAL
4	2485.10	67.67	27.35	44.32	5.21	55.91	74.00	-18.09	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

4. Test setup: RBW: 1 MHz, VBW: 10 Hz, Sweep time: auto for average measure.



Memo : 11N20 2462MHz VERTICAL

Data: 21




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	51.36	27.34	44.32	5.21	39.59	54.00	-14.41	Average	VERTICAL
2	2483.50	66.43	27.34	44.32	5.21	54.66	74.00	-19.34	Peak	VERTICAL
3	2484.90	49.14	27.35	44.32	5.21	37.38	54.00	-16.62	Average	VERTICAL
4	2484.90	66.32	27.35	44.32	5.21	54.56	74.00	-19.44	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Test setup: RBW: 1 MHz, VBW: 10 Hz, Sweep time: auto for average measure.

11. Power Line Conducted Emission

11.1. Block diagram of test setup



11.2 Power Line Conducted Emission Limits(Class B)

Frequency	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

11.3 Test Procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.



A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

114. Test Result

PASS. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.


Note2: "----" means peak detection; "-----" means average detection

Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded worst case (AC 120V/60Hz).



Memo : AC 120V/60Hz LINE

Data: 2



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.16	42.05	9.52	0.04	9.86	61.47	65.69	-4.22	QP	LINE
2	0.16	22.58	9.52	0.04	9.86	42.00	55.69	-13.69	Average	LINE
3	0.19	34.68	9.51	0.04	9.86	54.09	63.89	-9.80	QP	LINE
4	0.19	15.76	9.51	0.04	9.86	35.17	53.89	-18.72	Average	LINE
5	0.23	28.43	9.52	0.04	9.86	47.85	62.39	-14.54	QP	LINE
6	0.23	10.81	9.52	0.04	9.86	30.23	52.39	-22.16	Average	LINE
7	1.12	12.13	9.57	0.14	9.86	31.70	56.00	-24.30	QP	LINE
8	1.12	5.46	9.57	0.14	9.86	25.03	46.00	-20.97	Average	LINE
9	2.21	8.45	9.60	0.12	9.87	28.04	56.00	-27.96	QP	LINE
10	2.21	1.68	9.60	0.12	9.87	21.27	46.00	-24.73	Average	LINE
11	4.32	11.15	9.64	0.10	9.87	30.76	56.00	-25.24	QP	LINE
12	4.32	3.20	9.64	0.10	9.87	22.81	46.00	-23.19	Average	LINE

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.



Memo : AC 120V/60Hz NEUTRAL

Data: 4



Item (Mark)	Freq. (MHz)	Read Level (dBUV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBUV)	Limit Line (dBUV)	Over Limit (dB)	Detector	Phase
1	0.16	41.34	9.48	0.04	9.86	60.72	65.69	-4.97	QP	NEUTRAL
2	0.16	21.33	9.48	0.04	9.86	40.71	55.69	-14.98	Average	NEUTRAL
3	0.20	33.60	9.45	0.04	9.86	52.95	63.80	-10.85	QP	NEUTRAL
4	0.20	15.69	9.45	0.04	9.86	35.04	53.80	-18.76	Average	NEUTRAL
5	0.38	19.00	9.37	0.04	9.83	38.24	58.21	-19.97	QP	NEUTRAL
6	0.38	10.50	9.37	0.04	9.83	29.74	48.21	-18.47	Average	NEUTRAL
7	0.42	17.19	9.37	0.04	9.82	36.42	57.44	-21.02	QP	NEUTRAL
8	0.42	8.21	9.37	0.04	9.82	27.44	47.44	-20.00	Average	NEUTRAL
9	0.63	12.80	9.33	0.07	9.84	32.04	56.00	-23.96	QP	NEUTRAL
10	0.63	5.34	9.33	0.07	9.84	24.58	46.00	-21.42	Average	NEUTRAL
11	1.45	9.90	9.28	0.13	9.86	29.17	56.00	-26.83	QP	NEUTRAL
12	1.45	4.30	9.28	0.13	9.86	23.57	46.00	-22.43	Average	NEUTRAL

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.



12. Antenna Requirements

121. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

122. Result

The antennas used for this product are integrated antenna and other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is 2dBi.

END OF REPORT