

# TEST REPORT

**FCC ID: 2AWVG-RBWS-20015**

**Product: WIRELESS CHARGING ALARM**

**Model No.: RBWS-20015**

**Additional Model No.: JCP-6228**

**Trade Mark: Rosewill, JCPAL**

**Report No.: TCT201022E018**

**Issued Date: Oct. 26, 2020**

Issued for:

**Shanghai JCPAL Industry Co. Ltd**

**Building 9, Zengmei Industrial Park, No.45, Jiangchang 1st Road, Jing'an  
District, Shanghai 200040, China**

Issued By:

**Shenzhen Tongce Testing Lab.**

**1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District,  
Shenzhen, Guangdong, China**

**TEL: +86-755-27673339**

**FAX: +86-755-27673332**

**Note:** This report shall not be reproduced except in full, without the written approval of Shenzhen Tongce Testing Lab.

This document may be altered or revised by Shenzhen Tongce Testing Lab. personnel only, and shall be noted in  
the revision section of the document. The test results in the report only apply to the tested sample.

**TABLE OF CONTENTS**


<b>1. Test Certification .....</b>	<b>3</b>
<b>2. Test Result Summary .....</b>	<b>4</b>
<b>3. EUT Description.....</b>	<b>5</b>
<b>4. General Information.....</b>	<b>6</b>
4.1. Test environment and mode.....	6
4.2. Description of Support Units .....	6
<b>5. Facilities and Accreditations .....</b>	<b>7</b>
5.1. Facilities .....	7
5.2. Location .....	7
5.3. Measurement Uncertainty.....	7
<b>6. Test Results and Measurement Data .....</b>	<b>8</b>
6.1. Antenna requirement .....	8
6.2. Conducted Emission.....	9
6.3. Radiated Spurious Emission Measurement .....	13

**Appendix A: Photographs of Test Setup****Appendix B: Photographs of EUT**

## 1. Test Certification

<b>Product:</b>	WIRELESS CHARGING ALARM
<b>Model No.:</b>	RBWS-20015
<b>Additional Model No.:</b>	JCP-6228
<b>Trade Mark:</b>	Rosewill, JCPAL
<b>Applicant:</b>	Shanghai JCPAL Industry Co. Ltd
<b>Address:</b>	Building 9, Zengmei Industrial Park, No.45, Jiangchang 1st Road, Jing'an District, Shanghai 200040, China
<b>Manufacturer:</b>	Shenzhen TecMotion Technology Co., Ltd.
<b>Address:</b>	2nd Floor, Chuangsheng Building, YangGuang Industrial. Xili Town, Nanshan District, Shenzhen, Guangdong Province, China
<b>Date of Test:</b>	Oct. 23, 2020 – Oct. 26, 2020
<b>Applicable Standards:</b>	FCC CFR Title 47 Part 15 Subpart C

The above equipment has been tested by Shenzhen Tongce Testing Lab. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

**Tested By:****Date:****Reviewed By:****Date:****Approved By:****Date:**

## 2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203	PASS
AC Power Line Conducted Emission	§15.207	PASS
Spurious Emission	§15.209(a)(f)	PASS

**Note:**

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

### 3. EUT Description

<b>Product:</b>	WIRELESS CHARGING ALARM
<b>Model No.:</b>	RBWS-20015
<b>Additional Model No.:</b>	JCP-6228
<b>Trade Mark:</b>	Rosewill, JCPAL
<b>Operation Frequency:</b>	110-205KHz
<b>Modulation Technology:</b>	MSK
<b>Antenna Type:</b>	Inductive loop coil Antenna
<b>Power Supply:</b>	Rechargeable Li-ion Battery DC 7.4V
<b>AC adapter:</b>	Adapter Information: MODEL: AK36WG-0900450U INPUT: AC 100-240V, 50/60Hz, 1.0A OUTPUT: DC 9V, 4.5A
<b>Remark:</b>	All models above are identical in interior structure, electrical circuits and components, just model names are different for the marketing requirement.

## 4. General Information

### 4.1. Test environment and mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1010 mbar
Test Mode:	
Engineering mode:	Keep the EUT in continuous transmitting by select channel and modulations(The value of duty cycle is 98.46%) with Fully-charged battery.
The sample was placed (0.1m below 1GHz, 1.5m above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.	

### 4.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
Mobile Phone	MQ6M2CH/A	C7DV86Y3JC6F	/	IPHONE

**Note:**

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 6dB Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

## 5. Facilities and Accreditations

### 5.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

Shenzhen Tongce Testing Lab

The 3m Semi-anechoic chamber has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

The 3m Semi-anechoic chamber of Shenzhen TCT Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

### 5.2. Location

Shenzhen Tongce Testing Lab

Address: 1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China

TEL: +86-755-27673339

### 5.3. Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	$\pm 2.56\text{dB}$
2	RF power, conducted	$\pm 0.12\text{dB}$
3	Spurious emissions, conducted	$\pm 0.11\text{dB}$
4	All emissions, radiated(<1G)	$\pm 3.92\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.28\text{dB}$
6	Temperature	$\pm 0.1^\circ\text{C}$
7	Humidity	$\pm 1.0\%$

## 6. Test Results and Measurement Data

### 6.1. Antenna requirement

<b>Standard requirement:</b>	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
<b>E.U.T Antenna:</b>	
The antenna is inductive loop coil antenna which permanently attached.	

## 6.2. Conducted Emission

### 6.2.1. Test Specification

<b>Test Requirement:</b>	FCC Part15 C Section 15.207														
<b>Test Method:</b>	ANSI C63.10:2013														
<b>Frequency Range:</b>	150 kHz to 30 MHz														
<b>Receiver setup:</b>	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
<b>Limits:</b>	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
<b>Test Setup:</b>	<p>Reference Plane</p> <p>40cm      80cm</p> <p>E.U.T      Adapter</p> <p>Test table/Insulation plane</p> <p>LISN</p> <p>Filter</p> <p>AC power</p> <p>EMI Receiver</p> <p>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>														
<b>Test Mode:</b>	Charging + Transmitting Mode														
<b>Test Procedure:</b>	<ol style="list-style-type: none"> <li>1. The E.U.T is connected to an adapter through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</li> <li>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li> <li>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.</li> </ol>														
<b>Test Result:</b>	PASS														

**6.2.2. Test Instruments**


Conducted Emission Shielding Room Test Site (843)				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Test Receiver	R&S	ESCI3	100898	Jul. 27, 2021
LISN-2	Schwarzbeck	NSLK 8126	8126453	Sep. 11, 2021
Line-5	TCT	CE-05	N/A	Sep. 02, 2021
EMI Test Software	Shurples Technology	EZ-EMC	N/A	N/A

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

### 6.2.3. Test data

Please refer to following diagram for individual

#### Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



Site	Phase: <b>L1</b>	Temperature: 25
Limit: FCC Part 15C Conduction(QP)	Power: AC 120V/60Hz	Humidity: 55 %

No.	Mk.	Freq. MHz	Reading Level dB $\mu$ V	Correct Factor dB	Measure- ment dB $\mu$ V	Limit dB	Over Detector	Comment
1	0.3659	31.82	10.13	41.95	58.59	-16.64	peak	
2	0.4650	30.70	10.13	40.83	56.60	-15.77	peak	
3	1.0947	31.87	10.12	41.99	56.00	-14.01	peak	
4	1.8191	32.21	10.12	42.33	56.00	-13.67	peak	
5	6.8864	36.67	10.14	46.81	60.00	-13.19	peak	
6 *	12.0209	38.84	10.16	49.00	60.00	-11.00	peak	

#### Note:

Freq. = Emission frequency in MHz

Reading level (dB $\mu$ V) = Receiver reading

Corr. Factor (dB) = Liss factor + Cable loss

Measurement (dB $\mu$ V) = Reading level (dB $\mu$ V) + Corr. Factor (dB)

Limit (dB $\mu$ V) = Limit stated in standard

Margin (dB) = Measurement (dB $\mu$ V) – Limits (dB $\mu$ V)


Q.P. = Quasi-Peak

AVG = average

Any value more than 10dB below limit have not been specifically reported.

\* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



Site: Phase: **N** Temperature: 25  
Limit: FCC Part 15C Conduction(QP) Power: AC 120V/60Hz Humidity: 55 %

No.	Mk.	Freq. MHz	Reading Level dB $\mu$ V	Correct Factor dB	Measure- ment dB $\mu$ V	Limit dB $\mu$ V	Over dB	Over	
								Detector	Comment
1	0.3613	31.88	10.13	42.01	58.70	-16.69		peak	
2	0.4107	30.88	10.13	41.01	57.63	-16.62		peak	
3	1.0904	31.43	10.12	41.55	56.00	-14.45		peak	
4	1.8059	31.64	10.12	41.76	56.00	-14.24		peak	
5	3.9660	32.92	10.13	43.05	56.00	-12.95		peak	
6 *	10.4458	37.08	10.15	47.23	60.00	-12.77		peak	

**Note1:**

Freq. = Emission frequency in MHz

Reading level (dB $\mu$ V) = Receiver reading

Corr. Factor (dB) = Liss factor + Cable loss

Measurement (dB $\mu$ V) = Reading level (dB $\mu$ V) + Corr. Factor (dB)

Limit (dB $\mu$ V) = Limit stated in standard

Margin (dB) = Measurement (dB $\mu$ V) - Limits (dB $\mu$ V)


Q.P. = Quasi-Peak AVG = average


Any value more than 10dB below limit have not been specifically reported.

\* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.


### 6.3. Radiated Spurious Emission Measurement

#### 6.3.1. Test Specification

<b>Test Requirement:</b>	FCC Part15 C Section 15.209				
<b>Test Method:</b>	ANSI C63.10: 2013				
<b>Frequency Range:</b>	9 kHz to 25 GHz				
<b>Measurement Distance:</b>	3 m				
<b>Antenna Polarization:</b>	Horizontal & Vertical				
<b>Operation mode:</b>	Refer to item 4.1				
<b>Receiver Setup:</b>	Frequency	Detector	RBW	VBW	Remark
9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value	
	Quasi-peak	9kHz	30kHz	Quasi-peak Value	
150kHz- 30MHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value	
	Peak	1MHz	3MHz	Peak Value	
30MHz-1GHz	Peak	1MHz	10Hz	Average Value	
<b>Limit:</b>	Frequency	Field Strength (microvolts/meter)		Measurement Distance (meters)	
0.009-0.490	2400/F(KHz)	300		300	
	24000/F(KHz)	30		30	
1.705-30	30	30		30	
	100	3		3	
30-88	150	3		3	
	200	3		3	
88-216	500	3		3	
	5000	3		Peak	
<b>Test setup:</b>	For radiated emissions below 30MHz 				



Above 1GHz



1. For the radiated emission test below 1GHz:

The EUT was placed on a turntable with 0.8 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level.

For the radiated emission test above 1GHz:

Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final

**Test Procedure:**

	<p>measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.</p> <p>2. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level</p> <p>3. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.</p> <p>4. Use the following spectrum analyzer settings:</p> <ol style="list-style-type: none"> <li>(1) Span shall wide enough to fully capture the emission being measured;</li> <li>(2) Set RBW=120 kHz for <math>f &lt; 1</math> GHz; VBW <math>\geq</math> RBW; Sweep = auto; Detector function = peak; Trace = max hold;</li> <li>(3) Set RBW = 1 MHz, VBW= 3MHz for <math>f \geq 1</math> GHz for peak measurement.</li> </ol> <p>For average measurement: VBW = 10 Hz, when duty cycle is no less than 98 percent. VBW <math>\geq 1/T</math>, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.</p>
<b>Test mode:</b>	Refer to section 4.1 for details
<b>Test results:</b>	PASS

### 6.3.2. Test Instruments

Radiated Emission Test Site (966)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Test Receiver	ROHDE&SCHW ARZ	ESIB7	100197	Jul. 27, 2021
Spectrum Analyzer	ROHDE&SCHW ARZ	FSQ40	200061	Sep. 11, 2021
Pre-amplifier	EM Electronics Corporation CO.,LTD	EM30265	07032613	Sep. 02, 2021
Pre-amplifier	HP	8447D	2727A05017	Sep. 02, 2021
Loop antenna	ZHINAN	ZN30900A	12024	Oct. 27, 2020
Broadband Antenna	Schwarzbeck	VULB9163	340	Sep. 04, 2022
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Sep. 04, 2022
Horn Antenna	A-INFO	LB-180400-KF	J211020657	Sep. 04, 2022
Antenna Mast	Keleto	RE-AM	N/A	N/A
Line-4	RE-high-04	TCT	N/A	Sep. 02, 2021
Line-8	RE-01	TCT	N/A	Jul. 27, 2021
EMI Test Software	Shurples Technology	EZ-EMC	N/A	N/A


**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

### 6.3.3. Test Data

Please refer to following diagram for individual

9KHz-30MHz


9KHz-150KHz:



Site	Polarization: <b>Horizontal</b>	Temperature: 25
Limit: FCC Part15.209(9K-150K)	Power: AC 120V60Hz	Humidity: 55 %

No.	Mk.	Freq. MHz	Reading	Correct	Measure-	Limit	Over
			Level dBuV/m	Factor dB	ment dBuV/m		
1		0.0120	42.57	22.78	65.35	126.0	-60.67 peak
2		0.0154	44.05	20.98	65.03	123.8	-58.82 peak
3		0.0461	43.73	20.29	64.02	114.3	-50.32 peak
4		0.0844	43.58	22.90	66.48	109.0	-42.61 peak
5		0.1295	38.46	25.39	63.85	105.3	-41.53 peak
6	*	0.1355	48.64	25.68	74.32	104.9	-30.66 peak

150KHz-30MHz:




Site Polarization: **Horizontal** Temperature: 25  
Limit: FCC Part15.209(150K-30M) Power: AC 120V60Hz Humidity: 55 %

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment		dB	Detector
		MHz	dBuA	dB	dBuA/m	dB/m		
1		0.2245	35.47	25.93	61.40	100.5	-39.19	peak
2		0.2836	34.44	25.83	60.27	98.56	-38.29	peak
3		0.5421	29.59	25.44	55.03	72.92	-17.89	peak
4		0.9929	28.31	25.44	53.75	67.68	-13.93	peak
5		6.5720	28.67	25.48	54.15	69.50	-15.35	peak
6	*	24.5192	30.25	25.41	55.66	69.50	-13.84	peak


30MHz-1GHz

Horizontal:



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment			
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		61.4343	36.83	-13.04	23.79	40.00	-16.21	peak
2		100.4712	39.00	-8.50	30.50	43.50	-13.00	peak
3	*	143.7760	47.54	-16.52	31.02	43.50	-12.48	peak
4		189.1076	43.26	-14.78	28.48	43.50	-15.02	peak
5		324.8645	32.98	-10.38	22.60	46.00	-23.40	peak
6		550.2902	29.79	-6.70	23.09	46.00	-22.91	peak

Vertical:



Site	Polarization: <b>Vertical</b>	Temperature: 25
Limit: FCC Part 15C 3M Radiation	Power:	Humidity: 55 %

No.	Mk.	Freq.	Reading	Correct Factor	Measure-ment	Limit	Over	
			Level				dB	Detector
		MHz	dBuV	dB	dBuV/m	dB/m		
1		61.4343	43.49	-13.04	30.45	40.00	-9.55	peak
2	*	84.2839	46.56	-14.36	32.20	40.00	-7.80	peak
3		103.3353	42.48	-8.74	33.74	43.50	-9.76	peak
4		140.7767	50.92	-16.48	34.44	43.50	-9.06	peak
5		214.6063	46.01	-13.82	32.19	43.50	-11.31	peak
6		307.1051	34.09	-10.85	23.24	46.00	-22.76	peak

**Note:**



Emission Level=Peak Reading + Correction Factor; Correction Factor=Antenna Factor + Cable loss – Pre-amplifier

## Appendix A: Photographs of Test Setup


Product: WIRELESS CHARGING ALARM

Model: RBWS-20015

Radiated Emission



Conducted Emission



## Appendix B: Photographs of EUT

Refer to test report TCT201022E008

\*\*\*\*\***END OF REPORT**\*\*\*\*\*