



FCC REPORT

Report Reference No...... : **CHTEW21040142**

Project No...... : **SHT2104021603EW**

FCC ID..... : **2AWVP-MAROMX4G**

Applicant's name..... : **NVISOL Ltd**

Address..... : **Ha'Alon 6, Afula, Israel**

Test item description : **Camera**

Trade Mark : **-**

Model/Type reference..... : **MAROM X 4G US**

Listed Model(s) : **-**

Standard : **FCC CFR Title 47 Part 2**
FCC CFR Title 47 Part 22
FCC CFR Title 47 Part 24
FCC CFR Title 47 Part 27

Date of receipt of test sample..... : **Apr. 12, 2021**

Date of testing..... : **Apr. 13, 2021- Apr. 25, 2021**

Date of issue..... : **Apr. 26, 2021**

Result..... : **Pass**

Report Verification:



Compiled by
(position+printedname+signature)....: **File administrators Silvia Li**

Supervised by
(position+printedname+signature)....: **Project Engineer Aaron Fang**

Approved by
(position+printedname+signature)....: **Manager Hans Hu**

Silvia Li

Aaron Fang

Hans Hu

Testing Laboratory Name : **Shenzhen Huatongwei International Inspection Co., Ltd.**

Address..... : **1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China**

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

Contents

<u>1.</u>	<u>TEST STANDARDS AND REPORT VERSION</u>	<u>3</u>
1.1.	Applicable Standards	3
1.2.	Report version information	3
<u>2.</u>	<u>TEST DESCRIPTION</u>	<u>4</u>
<u>3.</u>	<u>SUMMARY</u>	<u>5</u>
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Operation state	7
3.4.	EUT operation mode	9
3.5.	EUT configuration	9
3.6.	Modifications	9
<u>4.</u>	<u>TEST ENVIRONMENT</u>	<u>9</u>
4.1.	Testing Laboratory Information	9
4.2.	Equipments Used during the Test	10
4.3.	Environmental conditions	11
4.4.	Statement of the measurement uncertainty	11
<u>5.</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>12</u>
5.1.	ERP and EIRP	12
5.2.	Radiated Spurious Emission	24
<u>6.</u>	<u>TEST SETUP PHOTOS OF THE EUT</u>	<u>42</u>
<u>7.</u>	<u>APPENDIX REPORT</u>	<u>42</u>

1. TEST STANDARDS AND REPORT VERSION

1.1. Applicable Standards

The tests were performed according to following standards:

[FCC Rules Part 2](#): FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS

[FCC Rules Part 22](#): PUBLIC MOBILE SERVICES

[FCC Rules Part 24](#): PERSONAL COMMUNICATIONS SERVICES

[FCC Rules Part 27](#): MISCELLANEOUS WIRELESS COMMUNICATIONS SERVICES

[ANSI C63.26: 2015](#): American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services

[KDB 971168 D01 Power Meas License Digital Systems v03](#): MEASUREMENT GUIDANCE FOR CERTIFICATION OF LICENSED DIGITAL TRANSMITTERS

1.2. Report version information

Revision No.	Date of issue	Description
N/A	2021-04-26	Original

2. Test Description

Test Item	Section in CFR 47	Result	Test Engineer
Conducted Output Power	Part 2.1046 Part 22.913(a) Part 24.232(c) Part 27.50	Pass*	N/A
Peak-to-Average Ratio	Part 24.232 Part 27.50	Pass*	N/A
99% Occupied Bandwidth & 26 dB Bandwidth	Part 2.1049 Part 22.917(b) Part 24.238(b) Part 27.53	Pass*	N/A
Band Edge	Part 2.1051 Part 22.917 Part 24.238 Part 27.53	Pass*	N/A
Conducted Spurious Emissions	Part 2.1051 Part 22.917 Part 24.238 Part 27.53	Pass*	N/A
Frequency stability VS Temperature	Part 2.1055(a)(1)(b) Part 22.355 Part 24.235 Part 27.54	Pass*	N/A
Frequency stability VS Voltage	Part 2.1055(d)(1)(2) Part 22.355 Part 24.235 Part 27.54	Pass*	N/A
ERP and EIRP	Part 22.913(a) Part 24.232(b) Part 27.50	Pass	Pan Xie
Radiated Spurious Emissions	Part 2.1053 Part 22.917 Part 24.238 Part 27.53	Pass	Pan Xie

Note:

1. The measurement uncertainty is not included in the test result.
2. * reference to module report , which FCC ID is XMR201909EC25AFX

3. SUMMARY

3.1. Client Information

Applicant:	NVISOL Ltd
Address:	Ha'Alon 6,Afula, Israel
Manufacturer:	NVISOL Ltd
Address:	Ha'Alon 6,Afula, Israel

3.2. Product Description

Name of EUT:	Camera		
Trade Mark:	-		
Model No.:	MAROM X 4G US		
Listed Model(s):	-		
Power supply:	DC 3.7V		
Hardware version:	t3_a35_v1.2_210316		
Software version:	V2		
4G			
Operation Band:	☒ FDD Band 2 ☒ FDD Band 12 ☒ FDD Band 71	☒ FDD Band 4 ☒ FDD Band 13	☒ FDD Band 5 ☒ FDD Band 66
Transmit frequency:	FDD Band 2: FDD Band 4: FDD Band 5: FDD Band 12: FDD Band 13: FDD Band 66: FDD Band 71:	1850.7 MHz – 1909.3 MHz 1710.7 MHz – 1754.3 MHz 824.7 MHz – 848.3 MHz 699.7 MHz – 715.3 MHz 779.5 MHz – 784.5 MHz 1710.7 MHz – 1779.3 MHz 665.5 MHz – 695.5 MHz	
Receive frequency:	FDD Band 2: FDD Band 4: FDD Band 5: FDD Band 12: FDD Band 13: FDD Band 66: FDD Band 71:	1930.7 MHz – 1989.3 MHz 2110.7 MHz – 2154.3 MHz 869.7 MHz – 893.3 MHz 729.7 MHz – 745.3 MHz 748.5 MHz – 753.5 MHz 2110.7 MHz – 2179.3 MHz 619.5 MHz – 649.5 MHz	

Channel bandwidth:	FDD Band 2: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz FDD Band 4: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz FDD Band 5: 1.4MHz, 3MHz, 5MHz, 10MHz FDD Band 12: 1.4MHz, 3MHz, 5MHz, 10MHz FDD Band 13: 5MHz, 10MHz FDD Band 66: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz FDD Band 71: 5MHz, 10MHz, 15MHz, 20MHz
Power Class:	Class 3
Modulation type:	QPSK, 16QAM
Antenna type	Loop Antenna
Antenna Gain	Band2:1.20dBi Band4:0.9dBi Band5:-0.82dBi Band12:-0.9dBi Band13:-0.9dBi Band66:-0.9dBi Band71:-0.9dBi

3.3. Operation state

➤ Test frequency list

FDD Band 2	Test Frequency ID	Bandwidth [MHz]	N _{UL}	Frequency of Uplink [MHz]	N _{DL}	Frequency of Downlink [MHz]
	Low Range	1.4	18607	1850.7	607	1930.7
		3	18615	1851.5	615	1931.5
		5	18625	1852.5	625	1932.5
		10	18650	1855	650	1935
		15 ^[1]	18675	1857.5	675	1937.5
		20 ^[1]	18700	1860	700	1940
	Mid Range	1.4/3/5/10/15 ^[1] /20 ^[1]	18900	1880	900	1960
	High Range	1.4	19193	1909.3	1193	1989.3
		3	19185	1908.5	1185	1988.5
		5	19175	1907.5	1175	1987.5
		10	19150	1905	1150	1985
		15 ^[1]	19125	1902.5	1125	1982.5
		20 ^[1]	19100	1900	1100	1980
	NOTE 1: Bandwidth for which a relaxation of the specified UE receiver sensitivity requirement (TS 36.101 [27] Clause 7.3) is allowed.					
FDD Band 4	Test Frequency ID	Bandwidth [MHz]	N _{UL}	Frequency of Uplink [MHz]	N _{DL}	Frequency of Downlink [MHz]
	Low Range	1.4	19957	1710.7	1957	2110.7
		3	19965	1711.5	1965	2111.5
		5	19975	1712.5	1975	2112.5
		10	20000	1715	2000	2115
		15	20025	1717.5	2025	2117.5
		20	20050	1720	2050	2120
	Mid Range	1.4/3/5/10/15/20	20175	1732.5	2175	2132.5
	High Range	1.4	20393	1754.3	2393	2154.3
		3	20385	1753.5	2385	2153.5
		5	20375	1752.5	2375	2152.5
		10	20350	1750	2350	2150
		15	20325	1747.5	2325	2147.5
		20	20300	1745	2300	2145
FDD Band 5	Test Frequency ID	Bandwidth [MHz]	N _{UL}	Frequency of Uplink [MHz]	N _{DL}	Frequency of Downlink [MHz]
	Low Range	1.4	20407	824.7	2407	869.7
		3	20415	825.5	2415	870.5
		5	20425	826.5	2425	871.5
		10 ^[1]	20450	829	2450	874
	Mid Range	1.4/3/5/10 ^[1]	20525	836.5	2525	881.5
	High Range	1.4	20643	848.3	2643	893.3
		3	20635	847.5	2635	892.5
		5	20625	846.5	2625	891.5
		10 ^[1]	20600	844	2600	889
	NOTE 1: Bandwidth for which a relaxation of the specified UE receiver sensitivity requirement (TS 36.101 [27] Clause 7.3) is allowed.					
FDD Band 12	Table 4.3.1.12-1: Test frequencies for E-UTRA channel bandwidth for operating band 12					
	Test Frequency ID	Bandwidth [MHz]	N _{UL}	Frequency of Uplink [MHz]	N _{DL}	Frequency of Downlink [MHz]
	Low Range	1.4	23017	699.7	5017	729.7
		3	23025	700.5	5025	730.5
		5 ^[1]	23035	701.5	5035	731.5
		10 ^[1]	23060	704	5060	734
	Mid Range	1.4/3/5 ^[1] /10 ^[1]	23095	707.5	5095	737.5
	High Range	1.4	23173	715.3	5173	745.3
		3	23165	714.5	5165	744.5
		5 ^[1]	23155	713.5	5155	743.5
		10 ^[1]	23130	711	5130	741
	NOTE 1: Bandwidth for which a relaxation of the specified UE receiver sensitivity requirement (TS 36.101 [27] Clause 7.3) is allowed.					
FDD Band 13	Test Frequency ID	Bandwidth [MHz]	N _{UL}	Frequency of Uplink [MHz]	N _{DL}	Frequency of Downlink [MHz]
	Low Range	5 ^[1]	23205	779.5	5205	748.5
		10 ^[1]	23230	782	5230	751
	Mid Range	5 ^[1] /10 ^[1]	23230	782	5230	751
	High Range	5 ^[1]	23255	784.5	5255	753.5
		10 ^[1]	23230	782	5230	751
	NOTE 1: Bandwidth for which a relaxation of the specified UE receiver sensitivity requirement (TS 36.101 [27] Clause 7.3) is allowed.					

FDD Band 66

Table 4.3.1.1.66-1: Test frequencies for E-UTRA channel bandwidth for operating band 66

Test Frequency ID	Bandwidth [MHz]	N _{UL}	Frequency of Uplink [MHz]	N _{DL}	Frequency of Downlink [MHz]
Low Range	1.4	131979	1710.7	66443	2110.7
	3	131987	1711.5	66451	2111.5
	5	131997	1712.5	66461	2112.5
	10	132022	1715	66486	2115
	15	132047	1717.5	66511	2117.5
	20	132072	1720	66536	2120
Mid Range Tx ¹	1.4/3/5/10/15/20	132322	1745	66786	2145
Mid Range	1.4/3/5/10/15/20	132422	1755	66886	2155
Paired High Range ²	1.4	132665	1779.3	67129	2179.3
	3	132657	1778.5	67121	2178.5
	5	132647	1777.5	67111	2177.5
	10	132622	1775	67086	2175
	15	132597	1772.5	67061	2172.5
	20	132572	1770	67036	2170
High Range ³	1.4	NA	NA	67329	2199.3
	3	NA	NA	67321	2198.5
	5	NA	NA	67311	2197.5
	10	NA	NA	67286	2195
	15	NA	NA	67261	2192.5
	20	NA	NA	67236	2190

FDD Band 71

Table 4.3.1.1.71-1: Test frequencies for E-UTRA channel bandwidth for operating band 71

Test Frequency ID	Bandwidth [MHz]	N _{UL}	Frequency of Uplink [MHz]	N _{DL}	Frequency of Downlink [MHz]
Low Range	5	133147	665.5	68611	619.5
	10	133172	668	68636	622
	15	133197	670.5	68661	624.5
	20	133222	673	68686	627
Mid Range	5/10/15	133297	680.5	68761	634.5
	20	133322	683	68786	637
High Range	5	133447	695.5	68911	649.5
	10	133422	693	68886	647
	15	133397	690.5	68861	644.5
	20	133372	688	68836	642

3.4. EUT operation mode

For RF test items

The EUT has been tested under typical operating condition. Testing was performed by configuring EUT to maximum output power status.

Test Items	Band	Bandwidth (MHz)						Modulation		RB #		
		1.4	3	5	10	15	20	QPSK	16QAM	1	Half	Full
ERP and EIRP	2	o	o	o	o	o	o	o	o	o	-	-
	4	o	o	o	o	o	o	o	o	o	-	-
	5	o	o	o	o	-	-	o	o	o	-	-
	12	o	o	o	o	-	-	o	o	o	-	-
	13	-	-	o	o	-	-	o	o	o	-	-
	66	o	o	o	o	o	o	o	o	o	-	-
	71	-	-	o	o	o	o	o	o	o	-	-
Radiated Spurious Emission	2	o	o	o	o	o	o	o	o	o	-	-
	4	o	o	o	o	o	o	o	o	o	-	-
	5	o	o	o	o	-	-	o	o	o	-	-
	12	o	o	o	o	-	-	o	o	o	-	-
	13	-	-	o	o	-	-	o	o	o	-	-
	66	o	o	o	o	o	o	o	o	o	-	-
	71	-	-	o	o	o	o	o	o	o	-	-
Remark	1. The mark "o" means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not test. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.											

3.5. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

○ /		Manufacturer:	/
		Model No.:	/
○ /		Manufacturer:	/
		Model No.:	/

3.6. Modifications

No modifications were implemented to meet testing criteria.

4. TEST ENVIRONMENT

4.1. Testing Laboratory Information

Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.	
Laboratory Location	1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China	
Connect information:	Tel: 86-755-26715499 E-mail: cs@szhtw.com.cn http://www.szhtw.com.cn	
Qualifications	Type	Accreditation Number
	FCC	762235

4.2. Equipments Used during the Test

● Radiated Spurious Emission							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0122	SAC-3m-01	N/A	2018/09/27	2021/09/26
●	Spectrum Analyzer	R&S	HTWE0098	FSP40	100597	2020/10/20	2021/10/19
●	Loop Antenna	R&S	HTWE0170	HFH2-Z2	100020	2021/04/06	2022/04/05
●	Broadband Horn Antenna	SCHWARZBECK	HTWE0103	BBHA9170	BBHA9170472	2018/10/12	2021/10/11
●	Ultra-Broadband Antenna	SCHWARZBECK	HTWE0123	VULB9163	538	2021/04/06	2022/04/05
●	Horn Antenna	SCHWARZBECK	HTWE0126	9120D	1011	2020/04/01	2023/03/31
●	Pre-amplifier	CD	HTWE0071	PAP-0102	12004	2020/11/12	2021/11/11
●	Broadband Preamplifier	SCHWARZBECK	HTWE0201	BBV 9718	9718-248	2020/05/10	2021/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-01	6m 18GHz S Serisa	N/A	2020/05/10	2021/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-02	6m 3GHz RG Serisa	N/A	2020/05/10	2021/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-03	6m 3GHz RG Serisa	N/A	2020/05/10	2021/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-04	6m 3GHz RG Serisa	N/A	2020/05/10	2021/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0121-01	6m 18GHz S Serisa	N/A	2020/05/10	2021/05/09
●	EMI Test Software	Audix	N/A	E3	N/A	N/A	N/A
●	Radio communication tester	R&S	HTWE0287	CMW500	137688-Lv	2020/10/19	2021/10/18

4.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Voltage	VN=Nominal Voltage	DC 3.70V
	VL=Lower Voltage	DC 3.60V
	VH=Higher Voltage	DC 4.20V
Temperature	TN=Normal Temperature	25 °C
	Extreme Temperature	From -30° to + 50° centigrade
Humidity	30~60 %	
Air Pressure	950-1050 hPa	

4.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.51 dB	(1)
Transmitter power Radiated	2.66dB for <1GHz 3.44dB for >1GHz	(1)
Conducted spurious emissions 9kHz~40GHz	0.51 dB	(1)
Radiated spurious emissions	2.66dB for <1GHz 3.44dB for >1GHz	(1)
Occupied Bandwidth	15Hz for <1GHz 70Hz for >1GHz	(1)
Frequency error	15Hz for <1GHz 70Hz for >1GHz	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

5. TEST CONDITIONS AND RESULTS

5.1. ERP and EIRP

LIMIT

LTE Band 2: 2W(33dBm) EIRP


LTE Band 4/66: 1W(30dBm) EIRP

LTE Band 5: 7W(38.50dBm) ERP

LTE Band 12/71: 3W(34.77dBm) ERP

LTE Band 13: 30W(44.77dBm) ERP

TEST CONFIGURATION



TEST PROCEDURE

1. Place the EUT in the center of the turntable.
 - a) For radiated emissions measurements performed at frequencies less than or equal to 1 GHz, the EUT shall be placed on a RF-transparent table at a nominal height of 80 cm above the reference ground plane
 - b) For radiated measurements performed at frequencies above 1 GHz, the EUT shall be placed on an RF transparent table at a nominal height of 1.5 m above the ground plane.
2. Unless the EUT uses an integral antenna, the EUT shall be terminated with a non-radiating transmitter load. In cases where the EUT uses an adjustable antenna, the antenna shall be adjusted through typical positions and lengths to maximize emissions levels.
3. The EUT shall be tested while operating on the frequency per manufacturer specification. Set the transmitter to operate in continuous transmit mode.
4. Receiver or Spectrum set as follow:

Below 1GHz, RBW=100kHz, VBW=300kHz, Detector=Peak, Sweep time=Auto

Above 1GHz, RBW=1MHz, VBW=3MHz, Detector=Peck, Sweep time=Auto
5. Each emission under consideration shall be evaluated:
 - a) Raise and lower the measurement antenna from 1 m to 4 m, as necessary to enable detection of the maximum emission amplitude relative to measurement antenna height.

- b) Rotate the EUT through 360° to determine the maximum emission level relative to the axial position.
 - c) Return the turntable to the azimuth where the highest emission amplitude level was observed.
 - d) Vary the measurement antenna height again through 1 m to 4 m again to find the height associated with the maximum emission amplitude.
 - e) Record the measured emission amplitude level and frequency
6. Repeat step 5 for each emission frequency with the measurement antenna oriented in both the horizontal and vertical polarizations to determine the orientation that gives the maximum emissions amplitude.
7. Set-up the substitution measurement with the reference point of the substitution antenna located as near as possible to where the center of the EUT radiating element was located during the initial EUT measurement.
8. Maintain the previous measurement instrument settings and test set-up, with the exception that the EUT is removed and replaced by the substitution antenna.
9. Connect a signal generator to the substitution antenna; locate the signal generator so as to minimize any potential influences on the measurement results. Set the signal generator to the frequency where emissions are detected, and set an output power level such that the radiated signal can be detected by the measurement instrument, with sufficient dynamic range relative to the noise floor.
10. For each emission that was detected and measured in the initial test
 - a) Vary the measurement antenna height between 1 m to 4 m to maximize the received (measured) signal amplitude.
 - b) Adjust the signal generator output power level until the amplitude detected by the measurement instrument equals the amplitude level of the emission previously measured directly in step 5 and step 6.
 - c) Record the output power level of the signal generator when equivalence is achieved in step b).
11. Repeat step 8 through step 10 with the measurement antenna oriented in the opposite polarization.
12. Calculate the emission power in dBm referenced to a half-wave dipole using the following equation:
$$P_e = P_s(\text{dBm}) - \text{cable loss (dB)} + \text{antenna gain (dBd)}$$
where
 P_e = equivalent emission power in dBm
 P_s = source (signal generator) power in dBm
NOTE—dBd refers to the measured antenna gain in decibels relative to a half-wave dipole.
13. Correct the antenna gain of the substitution antenna if necessary to reference the emission power to a half-wave dipole. When using measurement antennas with the gain specified in dBi, the equivalent dipole-referenced gain can be determined from:
$$\text{gain (dBd)} = \text{gain (dBi)} - 2.15 \text{ dB}.$$
If necessary, the antenna gain can be calculated from calibrated antenna factor information
14. Provide the complete measurement results as a part of the test report.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ Passed ☐ Not Applicable

LTE Band 2-1.4MHz					
Modulation	Channel	EIRP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	20.87	18.58	≤33.00	PASS
	Mid	21.32	18.55		
	High	20.91	18.53		
16QAM	Low	20.68	18.49		PASS
	Mid	21.19	18.76		
	High	20.75	18.35		

LTE Band 2-3MHz					
Modulation	Channel	EIRP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	20.72	18.50	≤33.00	PASS
	Mid	21.37	18.41		
	High	20.97	18.56		
16QAM	Low	20.51	18.29		PASS
	Mid	20.89	18.44		
	High	20.62	18.40		

LTE Band 2-5MHz					
Modulation	Channel	EIRP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	20.74	18.45	≤33.00	PASS
	Mid	21.08	18.51		
	High	20.80	18.70		
16QAM	Low	20.75	18.73		PASS
	Mid	20.97	18.33		
	High	20.51	18.38		

LTE Band 2-10MHz					
Modulation	Channel	EIRP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	20.93	18.35	≤33.00	PASS
	Mid	21.33	18.60		
	High	20.70	18.50		
16QAM	Low	21.10	18.84		PASS
	Mid	21.40	18.79		
	High	20.70	18.49		

LTE Band 2-15MHz					
Modulation	Channel	EIRP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	20.78	18.39	≤33.00	PASS
	Mid	21.23	18.58		
	High	20.98	18.45		
16QAM	Low	20.54	18.49		PASS
	Mid	20.98	18.37		
	High	20.66	18.21		

LTE Band 2-20MHz					
Modulation	Channel	EIRP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	20.69	18.37	≤33.00	PASS
	Mid	21.05	18.34		
	High	20.72	18.72		
16QAM	Low	20.40	18.50		PASS
	Mid	20.71	18.28		
	High	20.66	18.27		

LTE Band 4-1.4MHz					
Modulation	Channel	EIRP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	21.03	17.96	≤30.00	PASS
	Mid	21.33	18.55		
	High	20.47	18.03		
16QAM	Low	20.93	17.91		PASS
	Mid	21.24	18.63		
	High	20.36	17.92		

LTE Band 4-3MHz					
Modulation	Channel	EIRP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	20.96	17.92	≤30.00	PASS
	Mid	21.36	18.49		
	High	20.49	18.05		
16QAM	Low	20.84	17.81		PASS
	Mid	21.13	18.51		
	High	20.31	17.96		

LTE Band 4-5MHz					
Modulation	Channel	EIRP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	20.98	17.90	≤30.00	PASS
	Mid	21.23	18.55		
	High	20.38	18.09		
16QAM	Low	21.00	18.07		PASS
	Mid	21.15	18.44		
	High	20.24	17.92		

LTE Band 4-10MHz					
Modulation	Channel	EIRP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	21.05	17.83	≤30.00	PASS
	Mid	21.34	18.58		
	High	20.38	18.04		
16QAM	Low	21.12	18.07		PASS
	Mid	21.33	18.63		
	High	20.36	18.02		

LTE Band 4-15MHz					
Modulation	Channel	EIRP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	20.97	17.85	≤30.00	PASS
	Mid	21.33	18.61		
	High	20.50	17.99		
16QAM	Low	20.85	17.90		PASS
	Mid	21.22	18.51		
	High	20.32	17.86		

LTE Band 4-20MHz					
Modulation	Channel	EIRP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	20.93	17.84	≤30.00	PASS
	Mid	21.20	18.46		
	High	20.38	18.16		
16QAM	Low	20.79	17.94		PASS
	Mid	21.05	18.44		
	High	20.34	17.90		

LTE Band 5-1.4MHz					
Modulation	Channel	ERP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	21.64	18.29	≤38.50	PASS
	Mid	22.53	18.78		
	High	21.24	18.54		
16QAM	Low	21.51	18.21		PASS
	Mid	22.44	18.91		
	High	21.15	18.43		

LTE Band 5-3MHz					
Modulation	Channel	ERP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	21.59	18.27	≤38.50	PASS
	Mid	22.50	18.65		
	High	21.34	18.62		
16QAM	Low	21.43	18.11		PASS
	Mid	22.28	18.73		
	High	21.13	18.54		

LTE Band 5-5MHz					
Modulation	Channel	ERP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	21.57	18.21	≤38.50	PASS
	Mid	22.30	18.68		
	High	21.20	18.68		
16QAM	Low	21.62	18.45		PASS
	Mid	22.24	18.59		
	High	20.99	18.43		

LTE Band 5-10MHz					
Modulation	Channel	ERP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	21.66	18.13	≤38.50	PASS
	Mid	22.53	18.81		
	High	21.20	18.63		
16QAM	Low	21.72	18.39		PASS
	Mid	22.48	18.84		
	High	21.19	18.61		

LTE Band 12-1.4MHz					
Modulation	Channel	ERP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	21.57	19.54	≤34.77	PASS
	Mid	22.14	20.15		
	High	21.59	19.61		
16QAM	Low	21.40	19.43		PASS
	Mid	22.02	20.19		
	High	21.49	19.50		

LTE Band 12-3MHz					
Modulation	Channel	ERP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	21.50	19.50	≤34.77	PASS
	Mid	22.18	20.08		
	High	21.62	19.62		
16QAM	Low	21.33	19.34		PASS
	Mid	21.90	20.07		
	High	21.44	19.54		

LTE Band 12-5MHz					
Modulation	Channel	ERP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	21.47	19.44	≤34.77	PASS
	Mid	22.00	20.11		
	High	21.53	19.70		
16QAM	Low	21.54	19.68		PASS
	Mid	21.96	20.03		
	High	21.37	19.51		

LTE Band 12-10MHz					
Modulation	Channel	ERP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	21.55	19.36	≤34.77	PASS
	Mid	22.14	20.17		
	High	21.52	19.65		
16QAM	Low	21.58	19.57		PASS
	Mid	22.13	20.23		
	High	21.53	19.65		

LTE Band 13-5MHz					
Modulation	Channel	ERP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	20.78	18.00	<44.77	PASS
	Mid	21.62	18.58		
	High	20.93	17.71		
16QAM	Low	20.70	17.95		PASS
	Mid	21.55	18.67		
	High	20.85	17.62		

LTE Band 13-10MHz					
Modulation	Channel	ERP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Mid	21.68	18.55	<44.77	PASS
16QAM	Mid	21.44	18.53		PASS

LTE Band 66-1.4MHz					
Modulation	Channel	EIRP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	21.20	18.52	≤30.00	PASS
	Mid	22.02	18.95		
	High	20.89	18.41		
16QAM	Low	20.96	18.39		PASS
	Mid	21.82	19.12		
	High	20.69	18.18		

LTE Band 66-3MHz					
Modulation	Channel	EIRP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	21.10	18.49	≤30.00	PASS
	Mid	22.10	18.81		
	High	21.04	18.52		
16QAM	Low	20.85	18.24		PASS
	Mid	21.66	18.96		
	High	20.57	18.28		

LTE Band 66-5MHz					
Modulation	Channel	EIRP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	21.09	18.40	≤30.00	PASS
	Mid	21.79	18.95		
	High	20.91	18.79		
16QAM	Low	21.19	18.85		PASS
	Mid	21.67	18.74		
	High	20.46	18.27		

LTE Band 66-10MHz					
Modulation	Channel	EIRP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	21.18	18.22	≤30.00	PASS
	Mid	21.92	18.92		
	High	20.73	18.46		
16QAM	Low	21.33	18.70		PASS
	Mid	21.95	19.07		
	High	20.70	18.42		

LTE Band 66-15MHz					
Modulation	Channel	EIRP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	21.12	18.32	≤30.00	PASS
	Mid	21.86	18.94		
	High	21.09	18.41		
16QAM	Low	20.80	18.39		PASS
	Mid	21.65	18.76		
	High	20.63	18.07		

LTE Band 66-20MHz					
Modulation	Channel	EIRP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	20.87	18.19	≤30.00	PASS
	Mid	21.68	18.69		
	High	20.76	18.78		
16QAM	Low	20.58	18.27		PASS
	Mid	21.37	18.69		
	High	20.62	18.13		

LTE Band 71-5MHz					
Modulation	Channel	ERP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	21.00	18.27	≤34.77	PASS
	Mid	21.96	19.07		
	High	20.62	17.93		
16QAM	Low	20.92	18.23		PASS
	Mid	21.91	19.19		
	High	20.52	17.83		

LTE Band 71-10MHz					
Modulation	Channel	ERP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	20.91	18.21	≤34.77	PASS
	Mid	22.04	19.02		
	High	20.65	17.96		
16QAM	Low	20.80	18.10		PASS
	Mid	21.74	19.01		
	High	20.44	17.83		

LTE Band 71-15MHz					
Modulation	Channel	ERP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	20.94	18.20	≤34.77	PASS
	Mid	21.87	19.08		
	High	20.62	18.11		
16QAM	Low	20.99	18.42		PASS
	Mid	21.81	18.98		
	High	20.42	17.87		


LTE Band 71-20MHz					
Modulation	Channel	ERP (dBm)		Limit (dBm)	Result
		Vertical	Horizontal		
QPSK	Low	21.01	18.13	≤34.77	PASS
	Mid	21.92	19.05		
	High	20.55	17.97		
16QAM	Low	21.12	18.40		PASS
	Mid	21.93	19.12		
	High	20.54	17.96		

5.2. Radiated Spurious Emission

LIMIT

LTE Band 2/4/5/12/13/66/71: -13dBm;

TEST CONFIGURATION



TEST PROCEDURE

1. Place the EUT in the center of the turntable.
 - a) For radiated emissions measurements performed at frequencies less than or equal to 1 GHz, the EUT shall be placed on a RF-transparent table at a nominal height of 80 cm above the reference ground plane
 - b) For radiated measurements performed at frequencies above 1 GHz, the EUT shall be placed on an RF transparent table at a nominal height of 1.5 m above the ground plane.
2. Unless the EUT uses an integral antenna, the EUT shall be terminated with a non-radiating transmitter load. In cases where the EUT uses an adjustable antenna, the antenna shall be adjusted through typical positions and lengths to maximize emissions levels.
3. The EUT shall be tested while operating on the frequency per manufacturer specification. Set the transmitter to operate in continuous transmit mode.
4. Receiver or Spectrum set as follow:

Below 1GHz, RBW=100kHz, VBW=300kHz, Detector=Peak, Sweep time=Auto

Above 1GHz, RBW=1MHz, VBW=3MHz, Detector=Peck, Sweep time=Auto
5. Each emission under consideration shall be evaluated:
 - a) Raise and lower the measurement antenna from 1 m to 4 m, as necessary to enable detection of the maximum emission amplitude relative to measurement antenna height.
 - b) Rotate the EUT through 360° to determine the maximum emission level relative to the axial position.
 - c) Return the turntable to the azimuth where the highest emission amplitude level was observed.
 - d) Vary the measurement antenna height again through 1 m to 4 m again to find the height associated with the maximum emission amplitude.
 - e) Record the measured emission amplitude level and frequency
6. Repeat step 5 for each emission frequency with the measurement antenna oriented in both the horizontal

- and vertical polarizations to determine the orientation that gives the maximum emissions amplitude.
7. Set-up the substitution measurement with the reference point of the substitution antenna located as near as possible to where the center of the EUT radiating element was located during the initial EUT measurement.
 8. Maintain the previous measurement instrument settings and test set-up, with the exception that the EUT is removed and replaced by the substitution antenna.
 9. Connect a signal generator to the substitution antenna; locate the signal generator so as to minimize any potential influences on the measurement results. Set the signal generator to the frequency where emissions are detected, and set an output power level such that the radiated signal can be detected by the measurement instrument, with sufficient dynamic range relative to the noise floor.
 10. For each emission that was detected and measured in the initial test
 - a) Vary the measurement antenna height between 1 m to 4 m to maximize the received (measured) signal amplitude.
 - b) Adjust the signal generator output power level until the amplitude detected by the measurement instrument equals the amplitude level of the emission previously measured directly in step 5 and step 6.
 - c) Record the output power level of the signal generator when equivalence is achieved in step b).
 11. Repeat step 8 through step 10 with the measurement antenna oriented in the opposite polarization.
 12. Calculate the emission power in dBm referenced to a half-wave dipole using the following equation:
$$P_e = P_s(\text{dBm}) - \text{cable loss (dB)} + \text{antenna gain (dBd)}$$
where
$$P_e = \text{equivalent emission power in dBm}$$
$$P_s = \text{source (signal generator) power in dBm}$$
NOTE—dBd refers to the measured antenna gain in decibels relative to a half-wave dipole.
 13. Correct the antenna gain of the substitution antenna if necessary to reference the emission power to a half-wave dipole. When using measurement antennas with the gain specified in dBi, the equivalent dipole-referenced gain can be determined from:
$$\text{gain (dBd)} = \text{gain (dBi)} - 2.15 \text{ dB.}$$
If necessary, the antenna gain can be calculated from calibrated antenna factor information
 14. Provide the complete measurement results as a part of the test report.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ **Passed** ☐ **Not Applicable**

Note: only show the worse case for QPSK modulation.

LTE Band 2-1.4MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	3701.4	Vertical	-34.59	≤-13.00	Pass
	5552.1	V	-39.55		
	7402.8	V	-42.29		
	3701.4	Horizontal	-36.13	≤-13.00	Pass
	5552.1	H	-41.21		
	7402.8	H	-43.02		
Mid	3760	Vertical	-33.78	≤-13.00	Pass
	5640	V	-38.84		
	7520	V	-41.55		
	3760	Horizontal	-35.48	≤-13.00	Pass
	5640	H	-40.21		
	7520	H	-42.50		
High	3818.6	Vertical	-33.04	≤-13.00	Pass
	5727.9	V	-37.93		
	7637.2	V	-40.33		
	3818.6	Horizontal	-34.28	≤-13.00	Pass
	5727.9	H	-39.53		
	7637.2	H	-42.09		

LTE Band 2-3MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	3703	Vertical	-32.60	≤-13.00	Pass
	5554.5	V	-37.37		
	7406	V	-40.07		
	3703	Horizontal	-34.07	≤-13.00	Pass
	5554.5	H	-39.08		
	7406	H	-41.57		
Mid	3760	Vertical	-32.09	≤-13.00	Pass
	5640	V	-36.92		
	7520	V	-39.60		
	3760	Horizontal	-33.66	≤-13.00	Pass
	5640	H	-38.45		
	7520	H	-41.24		
High	3817	Vertical	-31.62	≤-13.00	Pass
	5725.5	V	-36.34		
	7634	V	-38.83		
	3817	Horizontal	-32.90	≤-13.00	Pass
	5725.5	H	-38.02		
	7634	H	-40.98		

LTE Band 2-5MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	3705	Vertical	-31.18	≤-13.00	Pass
	5557.5	V	-35.78		
	7410	V	-38.57		
	3705	Horizontal	-32.69	≤-13.00	Pass
	5557.5	H	-37.57		
	7410	H	-40.46		
Mid	3760	Vertical	-30.67	≤-13.00	Pass
	5640	V	-35.33		
	7520	V	-38.10		
	3760	Horizontal	-32.28	≤-13.00	Pass
	5640	H	-36.94		
	7520	H	-40.13		
High	3815	Vertical	-30.20	≤-13.00	Pass
	5722.5	V	-34.75		
	7630	V	-37.33		
	3815	Horizontal	-31.52	≤-13.00	Pass
	5722.5	H	-36.51		
	7630	H	-39.87		

LTE Band 2-10MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	3710	Vertical	-29.92	≤-13.00	Pass
	5565	V	-34.40		
	7420	V	-37.16		
	3710	Horizontal	-31.39	≤-13.00	Pass
	5565	H	-36.23		
	7420	H	-39.54		
Mid	3760	Vertical	-29.60	≤-13.00	Pass
	5640	V	-34.12		
	7520	V	-36.87		
	3760	Horizontal	-31.13	≤-13.00	Pass
	5640	H	-35.83		
	7520	H	-39.33		
High	3810	Vertical	-29.31	≤-13.00	Pass
	5715	V	-33.76		
	7620	V	-36.39		
	3810	Horizontal	-30.65	≤-13.00	Pass
	5715	H	-35.56		
	7620	H	-39.17		

LTE Band 2-15MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	3715	Vertical	-28.91	≤-13.00	Pass
	5572.5	V	-33.26		
	7430	V	-36.15		
	3715	Horizontal	-30.46	≤-13.00	Pass
	5572.5	H	-35.16		
	7430	H	-38.70		
Mid	3760	Vertical	-28.45	≤-13.00	Pass
	5640	V	-32.86		
	7520	V	-35.73		
	3760	Horizontal	-30.09	≤-13.00	Pass
	5640	H	-34.59		
	7520	H	-38.40		
High	3805	Vertical	-28.03	≤-13.00	Pass
	5707.5	V	-32.34		
	7610	V	-35.04		
	3805	Horizontal	-29.40	≤-13.00	Pass
	5707.5	H	-34.20		
	7610	H	-38.17		

LTE Band 2-20MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	3720	Vertical	-27.78	≤-13.00	Pass
	5580	V	-32.02		
	7440	V	-34.89		
	3720	Horizontal	-29.28	≤-13.00	Pass
	5580	H	-33.94		
	7440	H	-37.87		
Mid	3760	Vertical	-27.49	≤-13.00	Pass
	5640	V	-31.76		
	7520	V	-34.62		
	3760	Horizontal	-29.05	≤-13.00	Pass
	5640	H	-33.58		
	7520	H	-37.68		
High	3800	Vertical	-27.22	≤-13.00	Pass
	5700	V	-31.43		
	7600	V	-34.18		
	3800	Horizontal	-28.62	≤-13.00	Pass
	5700	H	-33.34		
	7600	H	-37.53		

Remark:

1. Remark"---" means that the emission level is too low to be measured
2. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

LTE Band 4-1.4MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	3421.4	Vertical	-33.84	≤-13.00	Pass
	5132.1	V	-43.01		
	6842.8	V	-44.83		
	3421.4	Horizontal	-34.76	≤-13.00	Pass
	5132.1	H	-42.40		
	6842.8	H	-44.40		
Mid	3465	Vertical	-33.04	≤-13.00	Pass
	5197.5	V	-42.35		
	6930	V	-44.14		
	3465	Horizontal	-34.15	≤-13.00	Pass
	5197.5	H	-41.47		
	6930	H	-43.91		
High	3508.6	Vertical	-32.35	≤-13.00	Pass
	5262.9	V	-41.50		
	7017.2	V	-43.01		
	3508.6	Horizontal	-33.03	≤-13.00	Pass
	5262.9	H	-40.84		
	7017.2	H	-43.53		

LTE Band 4-3MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	3423	Vertical	-31.94	≤-13.00	Pass
	5134.5	V	-40.98		
	6846	V	-42.76		
	3423	Horizontal	-32.83	≤-13.00	Pass
	5134.5	H	-40.42		
	6846	H	-43.05		
Mid	3465	Vertical	-31.46	≤-13.00	Pass
	5197.5	V	-40.56		
	6930	V	-42.33		
	3465	Horizontal	-32.45	≤-13.00	Pass
	5197.5	H	-39.83		
	6930	H	-42.74		
High	3507	Vertical	-31.03	≤-13.00	Pass
	5260.5	V	-40.02		
	7014	V	-41.62		
	3507	Horizontal	-31.74	≤-13.00	Pass
	5260.5	H	-39.43		
	7014	H	-42.50		

LTE Band 4-5MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	3425	Vertical	-30.55	≤-13.00	Pass
	5137.5	V	-39.22		
	6850	V	-41.35		
	3425	Horizontal	-31.31	≤-13.00	Pass
	5137.5	H	-38.95		
	6850	H	-41.89		
Mid	3465	Vertical	-29.89	≤-13.00	Pass
	5197.5	V	-38.64		
	6930	V	-40.75		
	3465	Horizontal	-30.78	≤-13.00	Pass
	5197.5	H	-38.14		
	6930	H	-41.47		
High	3505	Vertical	-29.29	≤-13.00	Pass
	5257.5	V	-37.90		
	7010	V	-39.76		
	3505	Horizontal	-29.81	≤-13.00	Pass
	5257.5	H	-37.59		
	7010	H	-41.14		

LTE Band 4-10MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	3430	Vertical	-28.93	≤-13.00	Pass
	5145	V	-37.45		
	6860	V	-39.55		
	3430	Horizontal	-29.64	≤-13.00	Pass
	5145	H	-37.23		
	6860	H	-40.72		
Mid	3465	Vertical	-28.52	≤-13.00	Pass
	5197.5	V	-37.09		
	6930	V	-39.17		
	3465	Horizontal	-29.31	≤-13.00	Pass
	5197.5	H	-36.72		
	6930	H	-40.45		
High	3500	Vertical	-28.14	≤-13.00	Pass
	5250	V	-36.62		
	7000	V	-38.55		
	3500	Horizontal	-28.70	≤-13.00	Pass
	5250	H	-36.37		
	7000	H	-40.24		

LTE Band 4-15MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	3435	Vertical	-27.87	≤-13.00	Pass
	5152.5	V	-36.10		
	6870	V	-38.37		
	3435	Horizontal	-28.26	≤-13.00	Pass
	5152.5	H	-36.05		
	6870	H	-39.82		
Mid	3465	Vertical	-27.44	≤-13.00	Pass
	5197.5	V	-35.72		
	6930	V	-37.98		
	3465	Horizontal	-27.91	≤-13.00	Pass
	5197.5	H	-35.52		
	6930	H	-39.54		
High	3495	Vertical	-27.05	≤-13.00	Pass
	5242.5	V	-35.24		
	6990	V	-37.33		
	3495	Horizontal	-27.55	≤-13.00	Pass
	5242.5	H	-34.77		
	6990	H	-39.32		

LTE Band 4-20MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	3440	Vertical	-26.82	≤-13.00	Pass
	5160	V	-34.94		
	6880	V	-37.19		
	3440	Horizontal	-27.31	≤-13.00	Pass
	5160	H	-34.53		
	6880	H	-39.04		
Mid	3465	Vertical	-26.55	≤-13.00	Pass
	5197.5	V	-34.70		
	6930	V	-36.94		
	3465	Horizontal	-27.09	≤-13.00	Pass
	5197.5	H	-34.20		
	6930	H	-38.87		
High	3490	Vertical	-26.30	≤-13.00	Pass
	5235	V	-34.39		
	6980	V	-36.53		
	3490	Horizontal	-26.69	≤-13.00	Pass
	5235	H	-33.97		
	6980	H	-38.73		

Remark:

1. Remark"---" means that the emission level is too low to be measured
2. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

LTE Band 5-1.4MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	1649.4	Vertical	-32.41	≤-13.00	Pass
	2474.1	V	-41.39		
	3298.8	V	-43.18		
	1649.4	Horizontal	-33.76	≤-13.00	Pass
	2474.1	H	-41.75		
	3298.8	H	-43.46		
Mid	1673	Vertical	-32.13	≤-13.00	Pass
	2509.5	V	-40.92		
	3346	V	-42.66		
	1673	Horizontal	-33.12	≤-13.00	Pass
	2509.5	H	-41.39		
	3346	H	-43.07		
High	1696.6	Vertical	-31.67	≤-13.00	Pass
	2544.9	V	-40.31		
	3393.2	V	-42.05		
	1696.6	Horizontal	-32.51	≤-13.00	Pass
	2544.9	H	-41.05		
	3393.2	H	-42.87		

LTE Band 5-3MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	1651	Vertical	-31.38	≤-13.00	Pass
	2476.5	V	-39.94		
	3302	V	-41.87		
	1651	Horizontal	-32.37	≤-13.00	Pass
	2476.5	H	-40.75		
	3302	H	-42.52		
Mid	1673	Vertical	-31.04	≤-13.00	Pass
	2509.5	V	-39.64		
	3346	V	-41.56		
	1673	Horizontal	-32.10	≤-13.00	Pass
	2509.5	H	-40.33		
	3346	H	-42.30		
High	1695	Vertical	-30.73	≤-13.00	Pass
	2542.5	V	-39.26		
	3390	V	-41.05		
	1695	Horizontal	-31.60	≤-13.00	Pass
	2542.5	H	-40.05		
	3390	H	-42.13		

LTE Band 5-5MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	1653	Vertical	-30.35	≤-13.00	Pass
	2479.5	V	-38.63		
	3306	V	-40.84		
	1653	Horizontal	-31.26	≤-13.00	Pass
	2479.5	H	-39.67		
	3306	H	-41.65		
Mid	1673	Vertical	-29.83	≤-13.00	Pass
	2509.5	V	-38.18		
	3346	V	-40.37		
	1673	Horizontal	-30.84	≤-13.00	Pass
	2509.5	H	-39.03		
	3346	H	-41.32		
High	1693	Vertical	-29.36	≤-13.00	Pass
	2539.5	V	-37.60		
	3386	V	-39.59		
	1693	Horizontal	-30.07	≤-13.00	Pass
	2539.5	H	-38.59		
	3386	H	-41.06		

LTE Band 5-10MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	1658	Vertical	-29.08	≤-13.00	Pass
	2487	V	-37.24		
	3316	V	-39.42		
	1658	Horizontal	-29.94	≤-13.00	Pass
	2487	H	-38.30		
	3316	H	-40.73		
Mid	1673	Vertical	-28.75	≤-13.00	Pass
	2509.5	V	-36.95		
	3346	V	-39.12		
	1673	Horizontal	-29.68	≤-13.00	Pass
	2509.5	H	-37.90		
	3346	H	-40.52		
High	1688	Vertical	-28.45	≤-13.00	Pass
	2532	V	-36.58		
	3376	V	-38.63		
	1688	Horizontal	-29.20	≤-13.00	Pass
	2532	H	-37.63		
	3376	H	-40.36		

Remark:

1. Remark"---" means that the emission level is too low to be measured
2. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

LTE Band 12-1.4MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	1399.4	Vertical	-31.31	≤-13.00	Pass
	2099.1	V	-41.64		
	2798.8	V	-41.99		
	1399.4	Horizontal	-32.60	≤-13.00	Pass
	2099.1	H	-41.91		
	2798.8	H	-42.24		
Mid	1415	Vertical	-30.62	≤-13.00	Pass
	2122.5	V	-40.80		
	2830	V	-41.46		
	1415	Horizontal	-31.66	≤-13.00	Pass
	2122.5	H	-41.15		
	2830	H	-41.69		
High	1430.6	Vertical	-29.89	≤-13.00	Pass
	2145.9	V	-40.03		
	2861.2	V	-40.64		
	1430.6	Horizontal	-31.02	≤-13.00	Pass
	2145.9	H	-40.66		
	2861.2	H	-41.10		

LTE Band 12-3MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	1401	Vertical	-29.52	≤-13.00	Pass
	2101.5	V	-39.56		
	2802	V	-40.42		
	1401	Horizontal	-30.84	≤-13.00	Pass
	2101.5	H	-40.28		
	2802	H	-40.66		
Mid	1415	Vertical	-29.09	≤-13.00	Pass
	2122.5	V	-39.18		
	2830	V	-40.03		
	1415	Horizontal	-30.49	≤-13.00	Pass
	2122.5	H	-39.75		
	2830	H	-40.38		
High	1429	Vertical	-28.70	≤-13.00	Pass
	2143.5	V	-38.70		
	2858	V	-39.38		
	1429	Horizontal	-29.85	≤-13.00	Pass
	2143.5	H	-39.39		
	2858	H	-40.16		

LTE Band 12-5MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	1403	Vertical	-28.34	≤-13.00	Pass
	2104.5	V	-38.11		
	2806	V	-39.18		
	1403	Horizontal	-29.53	≤-13.00	Pass
	2104.5	H	-39.03		
	2806	H	-39.71		
Mid	1415	Vertical	-27.85	≤-13.00	Pass
	2122.5	V	-37.68		
	2830	V	-38.74		
	1415	Horizontal	-29.14	≤-13.00	Pass
	2122.5	H	-38.43		
	2830	H	-39.40		
High	1427	Vertical	-27.41	≤-13.00	Pass
	2140.5	V	-37.13		
	2854	V	-38.01		
	1427	Horizontal	-28.42	≤-13.00	Pass
	2140.5	H	-38.02		
	2854	H	-39.16		

LTE Band 12-10MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	1408	Vertical	-27.15	≤-13.00	Pass
	2112	V	-36.80		
	2816	V	-37.85		
	1408	Horizontal	-28.29	≤-13.00	Pass
	2112	H	-37.75		
	2816	H	-38.85		
Mid	1415	Vertical	-26.84	≤-13.00	Pass
	2122.5	V	-36.53		
	2830	V	-37.57		
	1415	Horizontal	-28.04	≤-13.00	Pass
	2122.5	H	-37.37		
	2830	H	-38.65		
High	1422	Vertical	-26.56	≤-13.00	Pass
	2133	V	-36.18		
	2844	V	-37.11		
	1422	Horizontal	-27.59	≤-13.00	Pass
	2133	H	-37.11		
	2844	H	-38.50		

Remark:

1. Remark"---" means that the emission level is too low to be measured
2. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

LTE Band 13-5MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	1559	Vertical	-31.10	≤-13.00	Pass
	2338.5	V	-37.70		
	3118	V	-40.35		
	1559	Horizontal	-34.98	≤-13.00	Pass
	2338.5	H	-41.78		
	3118	H	-42.46		
Mid	1564	Vertical	-30.95	≤-13.00	Pass
	2346	V	-37.36		
	3128	V	-40.16		
	1564	Horizontal	-34.80	≤-13.00	Pass
	2346	H	-41.46		
	3128	H	-41.99		
High	1569	Vertical	-30.72	≤-13.00	Pass
	2353.5	V	-36.93		
	3138	V	-39.91		
	1569	Horizontal	-34.63	≤-13.00	Pass
	2353.5	H	-40.91		
	3138	H	-41.26		

LTE Band 13-10MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Mid	1564	Vertical	-30.48	<-13.00	Pass
	2346	V	-36.72		
	3128	V	-39.69		
	1564	Horizontal	-34.44	<-13.00	Pass
	2346	H	-40.61		
	3128	H	-41.11		

Remark:

1. Remark"---" means that the emission level is too low to be measured
2. The emission levels of below 1 GHz are very lower than the limit and not show in test report

LTE Band 66-1.4MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	3701.4	Vertical	-34.40	≤-13.00	Pass
	5552.1	V	-41.91		
	7402.8	V	-43.16		
	3701.4	Horizontal	-34.07	≤-13.00	Pass
	5552.1	H	-39.63		
	7402.8	H	-43.12		
Mid	3765	Vertical	-33.91	≤-13.00	Pass
	5647.5	V	-41.46		
	7530	V	-42.70		
	3765	Horizontal	-33.66	≤-13.00	Pass
	5647.5	H	-38.94		
	7530	H	-42.73		
High	3828.6	Vertical	-33.39	≤-13.00	Pass
	5742.9	V	-40.81		
	7657.2	V	-41.94		
	3828.6	Horizontal	-32.90	≤-13.00	Pass
	5742.9	H	-38.51		
	7657.2	H	-42.48		

LTE Band 66-3MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	3703	Vertical	-33.08	≤-13.00	Pass
	5554.5	V	-40.42		
	7406	V	-41.75		
	3703	Horizontal	-32.75	≤-13.00	Pass
	5554.5	H	-38.19		
	7406	H	-42.11		
Mid	3765	Vertical	-32.72	≤-13.00	Pass
	5647.5	V	-40.10		
	7530	V	-41.42		
	3765	Horizontal	-32.46	≤-13.00	Pass
	5647.5	H	-37.74		
	7530	H	-41.88		
High	3827	Vertical	-32.39	≤-13.00	Pass
	5740.5	V	-39.69		
	7654	V	-40.88		
	3827	Horizontal	-31.92	≤-13.00	Pass
	5740.5	H	-37.44		
	7654	H	-41.70		

LTE Band 66-5MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	3705	Vertical	-32.12	≤-13.00	Pass
	5557.5	V	-39.24		
	7410	V	-40.73		
	3705	Horizontal	-31.67	≤-13.00	Pass
	5557.5	H	-37.17		
	7410	H	-41.35		
Mid	3765	Vertical	-31.75	≤-13.00	Pass
	5647.5	V	-38.91		
	7530	V	-40.39		
	3765	Horizontal	-31.37	≤-13.00	Pass
	5647.5	H	-36.71		
	7530	H	-41.11		
High	3825	Vertical	-31.41	≤-13.00	Pass
	5737.5	V	-38.49		
	7650	V	-39.83		
	3825	Horizontal	-30.82	≤-13.00	Pass
	5737.5	H	-36.40		
	7650	H	-40.92		

LTE Band 66-10MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	3710	Vertical	-31.21	≤-13.00	Pass
	5565	V	-38.23		
	7420	V	-39.71		
	3710	Horizontal	-30.72	≤-13.00	Pass
	5565	H	-36.19		
	7420	H	-40.68		
Mid	3765	Vertical	-30.98	≤-13.00	Pass
	5647.5	V	-38.02		
	7530	V	-39.50		
	3765	Horizontal	-30.53	≤-13.00	Pass
	5647.5	H	-35.90		
	7530	H	-40.53		
High	3820	Vertical	-30.77	≤-13.00	Pass
	5730	V	-37.76		
	7640	V	-39.15		
	3820	Horizontal	-30.18	≤-13.00	Pass
	5730	H	-35.70		
	7640	H	-40.41		

LTE Band 66-15MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	3715	Vertical	-30.47	≤-13.00	Pass
	5572.5	V	-37.19		
	7430	V	-38.95		
	3715	Horizontal	-29.69	≤-13.00	Pass
	5572.5	H	-35.34		
	7430	H	-39.94		
Mid	3765	Vertical	-29.99	≤-13.00	Pass
	5647.5	V	-36.77		
	7530	V	-38.51		
	3765	Horizontal	-29.31	≤-13.00	Pass
	5647.5	H	-34.75		
	7530	H	-39.63		
High	3815	Vertical	-29.55	≤-13.00	Pass
	5722.5	V	-36.23		
	7630	V	-37.79		
	3815	Horizontal	-28.91	≤-13.00	Pass
	5722.5	H	-33.92		
	7630	H	-39.39		

LTE Band 66-20MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	3720	Vertical	-29.29	≤-13.00	Pass
	5580	V	-35.90		
	7440	V	-37.63		
	3720	Horizontal	-28.65	≤-13.00	Pass
	5580	H	-33.66		
	7440	H	-39.08		
Mid	3765	Vertical	-28.99	≤-13.00	Pass
	5647.5	V	-35.64		
	7530	V	-37.36		
	3765	Horizontal	-28.41	≤-13.00	Pass
	5647.5	H	-33.29		
	7530	H	-38.89		
High	3810	Vertical	-28.72	≤-13.00	Pass
	5715	V	-35.30		
	7620	V	-36.91		
	3810	Horizontal	-27.96	≤-13.00	Pass
	5715	H	-33.04		
	7620	H	-38.74		

Remark:

- Remark"---" means that the emission level is too low to be measured
- The emission levels of below 1 GHz are very lower than the limit and not show in test report.

LTE Band 71-5MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	1331	Vertical	-32.56	≤-13.00	Pass
	1996.5	V	-39.71		
	2662	V	-41.98		
	1331	Horizontal	-30.70	≤-13.00	Pass
	1996.5	H	-40.50		
	2662	H	-41.47		
Mid	1361	Vertical	-31.87	≤-13.00	Pass
	2041.5	V	-38.87		
	2722	V	-41.45		
	1361	Horizontal	-29.76	≤-13.00	Pass
	2041.5	H	-39.74		
	2722	H	-40.92		
High	1391	Vertical	-31.23	≤-13.00	Pass
	2086.5	V	-37.98		
	2782	V	-40.63		
	1391	Horizontal	-29.12	≤-13.00	Pass
	2086.5	H	-39.25		
	2782	H	-40.33		

LTE Band 71-10MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	1336	Vertical	-30.80	≤-13.00	Pass
	2004	V	-37.44		
	2672	V	-40.37		
	1336	Horizontal	-28.91	≤-13.00	Pass
	2004	H	-38.81		
	2672	H	-39.82		
Mid	1361	Vertical	-30.30	≤-13.00	Pass
	2041.5	V	-37.00		
	2722	V	-39.91		
	1361	Horizontal	-28.51	≤-13.00	Pass
	2041.5	H	-38.19		
	2722	H	-39.50		
High	1386	Vertical	-29.84	≤-13.00	Pass
	2079	V	-36.44		
	2772	V	-39.16		
	1386	Horizontal	-27.77	≤-13.00	Pass
	2079	H	-37.77		
	2772	H	-39.25		



LTE Band 71-15MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	1341	Vertical	-29.29	≤-13.00	Pass
	2011.5	V	-35.53		
	2682	V	-38.85		
	1341	Horizontal	-27.28	≤-13.00	Pass
	2011.5	H	-37.22		
	2682	H	-38.56		
Mid	1361	Vertical	-28.54	≤-13.00	Pass
	2041.5	V	-34.88		
	2722	V	-38.17		
	1361	Horizontal	-26.68	≤-13.00	Pass
	2041.5	H	-36.30		
	2722	H	-38.08		
High	1381	Vertical	-27.86	≤-13.00	Pass
	2071.5	V	-34.04		
	2762	V	-37.05		
	1381	Horizontal	-25.57	≤-13.00	Pass
	2071.5	H	-35.67		
	2762	H	-37.71		

LTE Band 71-20MHz					
Channel	Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
		Polarization	Level (dBm)		
Low	1346	Vertical	-27.46	≤-13.00	Pass
	2019	V	-33.53		
	2692	V	-36.81		
	1346	Horizontal	-25.38	≤-13.00	Pass
	2019	H	-35.26		
	2692	H	-37.23		
Mid	1366	Vertical	-26.99	≤-13.00	Pass
	2049	V	-33.12		
	2732	V	-36.38		
	1366	Horizontal	-25.00	≤-13.00	Pass
	2049	H	-34.68		
	2732	H	-36.93		
High	1376	Vertical	-26.56	≤-13.00	Pass
	2064	V	-32.59		
	2752	V	-35.67		
	1376	Horizontal	-24.30	≤-13.00	Pass
	2064	H	-34.29		
	2752	H	-36.69		

Remark:

5. Remark"---" means that the emission level is too low to be measured
6. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

6. TEST SETUP PHOTOS OF THE EUT



7. APPENDIX REPORT