

FCC 47 CFR MPE REPORT

KERCHAN TECHNOLOGY CO.,LIMITED

Advertisement machine

Model Number: DSD2150A

Additional Model: DSD2150AF, DSD2150A-Pro, DSD2150AF-Pro,
DSD2150AF-UVC, DSD2150D, DSD2150A-CW, DSD2150AF-CW,
DSD2150DF, DSD1160D, DSD1160A, DSD1160A-Pro, DSD1160A-CW

FCC ID: 2AWVRKCN202007

Prepared for:	KERCHAN TECHNOLOGY CO.,LIMITED
	7th Floor, Building F, Fusen Commercial Center, Hangcheng Road,
	Bao'an District, Shenzhen, Guangdong, China
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2007138
Date of Test:	Jul. 02~18, 2020
Date of Report:	Jul. 21, 2020



Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain	
					(dBi)	(Linear)
GFSK	2402	8.43	6.966	8±1	4.3	2.69
	2441	8.35	6.839	8±1	4.3	2.69
	2480	8.76	7.516	8±1	4.3	2.69
8-DPSK	2402	6.47	4.436	6±1	4.3	2.69
	2441	6.90	4.898	6±1	4.3	2.69
	2480	5.98	3.963	5±1	4.3	2.69
BLE	2402	6.30	4.266	6±1	4.3	2.69
	2440	6.59	4.560	6±1	4.3	2.69
	2480	5.64	3.664	5±1	4.3	2.69
IEEE 802.11b	2412	18.40	69.183	18±1	4.3	2.69
	2437	17.88	61.376	17±1	4.3	2.69
	2462	17.47	55.847	17±1	4.3	2.69
IEEE 802.11g	2412	20.84	121.339	20±1	4.3	2.69
	2437	20.25	105.925	20±1	4.3	2.69
	2462	20.08	101.859	20±1	4.3	2.69
IEEE 802.11n HT20	2412	19.92	98.175	19±1	4.3	2.69
	2437	19.55	90.157	19±1	4.3	2.69
	2462	19.40	87.096	19±1	4.3	2.69

3. Calculated Result and Limit

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW/cm ²)	Limited of Power Density (S) (mW/cm ²)	Test Result
		(dBi)	(Linear)			
GFSK	9	4.3	2.69	0.00425	1	Compiles
8-DPSK	7	4.3	2.69	0.00268	1	Compiles
BLE	7	4.3	2.69	0.00268	1	Compiles
IEEE 802.11b	19	4.3	2.69	0.04253	1	Compiles
IEEE 802.11g	21	4.3	2.69	0.06741	1	Compiles
IEEE 802.11n HT20	20	4.3	2.69	0.05355	1	Compiles

End of Test Report