

FCC Test Report

Report No.: AGC08777211201FE03

FCC ID : 2AWVU-HUNKSTER

APPLICATION PURPOSE : Original Equipment

PRODUCT DESIGNATION: Hunkster Speaker

BRAND NAME : Origaudio

MODEL NAME : X9607601007

APPLICANT : Fortyfour group LLC

DATE OF ISSUE : Dec. 21, 2021

STANDARD(S) : FCC Part 15.247

REPORT VERSION: V1.0

Attestation of Global Charles (Shenzhen) Co., Ltd





Page 2 of 69

REPORT REVISE RECORD

| Report Version | Revise Time | Issued Date | Valid Version | Notes |
|----------------|-------------|---------------|---------------|-----------------|
| V1.0 | / | Dec. 21, 2021 | Valid | Initial Release |






TABLE OF CONTENTS

| 1. VERIFICATION OF CONFORMITY | 5 |
|---|----|
| 2. GENERAL INFORMATION | 6 |
| 2.1. PRODUCT DESCRIPTION | 6 |
| 2.2. TABLE OF CARRIER FREQUENCYS | 6 |
| 2.3. RECEIVER INPUT BANDWIDTH | 7 |
| 2.4. EXAMPLE OF A HOPPING SEQUENCY IN DATA MODE | 7 |
| 2.5. EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR | 7 |
| 2.6. RELATED SUBMITTAL(S) / GRANT (S) | 8 |
| 2.7. TEST METHODOLOGY | 8 |
| 2.8. SPECIAL ACCESSORIES | 8 |
| 2.9. EQUIPMENT MODIFICATIONS | 8 |
| 2.10. ANTENNA REQUIREMENT | 8 |
| 3. MEASUREMENT UNCERTAINTY | g |
| 4. DESCRIPTION OF TEST MODES | 10 |
| 5. SYSTEM TEST CONFIGURATION | 11 |
| 5.1. CONFIGURATION OF EUT SYSTEM | 11 |
| 5.2. EQUIPMENT USED IN TESTED SYSTEM | 11 |
| 5.3. SUMMARY OF TEST RESULTS | |
| 6. TEST FACILITY | 12 |
| 7. PEAK OUTPUT POWER | 13 |
| 7.1. MEASUREMENT PROCEDURE | 13 |
| 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) | 13 |
| 7.3. LIMITS AND MEASUREMENT RESULT | 14 |
| 8. 20DB BANDWIDTH | 19 |
| 8.1. MEASUREMENT PROCEDURE | 19 |
| 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) | 19 |
| 8.3. LIMITS AND MEASUREMENT RESULTS | 20 |
| 9. CONDUCTED SPURIOUS EMISSION | 25 |
| 9.1. MEASUREMENT PROCEDURE | 25 |



| 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) | 25 |
|---|----|
| 9.3. MEASUREMENT EQUIPMENT USED | 25 |
| 9.4. LIMITS AND MEASUREMENT RESULT | 25 |
| 10. RADIATED EMISSION | 46 |
| 10.1. MEASUREMENT PROCEDURE | 46 |
| 10.2. TEST SETUP | 48 |
| 10.3. LIMITS AND MEASUREMENT RESULT | 49 |
| 10.4. TEST RESULT | 49 |
| 11. NUMBER OF HOPPING FREQUENCY | 59 |
| 11.1. MEASUREMENT PROCEDURE | 59 |
| 11.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION) | 59 |
| 11.3. MEASUREMENT EQUIPMENT USED | 59 |
| 11.4. LIMITS AND MEASUREMENT RESULT | 59 |
| 12. TIME OF OCCUPANCY (DWELL TIME) | 60 |
| 12.1. MEASUREMENT PROCEDURE | 60 |
| 12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION) | 60 |
| 12.3. MEASUREMENT EQUIPMENT USED | 60 |
| 12.4. LIMITS AND MEASUREMENT RESULT | 60 |
| 13. FREQUENCY SEPARATION | 64 |
| 13.1. MEASUREMENT PROCEDURE | 64 |
| 13.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION) | 64 |
| 13.3. MEASUREMENT EQUIPMENT USED | 64 |
| 13.4. LIMITS AND MEASUREMENT RESULT | 64 |
| 14. LINE CONDUCTED EMISSION TEST | 65 |
| 14.1. LIMITS OF LINE CONDUCTED EMISSION TEST | 65 |
| 14.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST | 65 |
| 14.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST | 66 |
| 14.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST | 66 |
| 14.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST | 67 |
| APPENDIX A: PHOTOGRAPHS OF TEST SETUP | 69 |
| APPENDIX B: PHOTOGRAPHS OF EUT | 69 |



Page 5 of 69

1. VERIFICATION OF CONFORMITY

| Applicant | Fortyfour group LLC |
|--------------------------|--|
| Address | 1770 S. 5350 W Ste 100 Salt Lake City UT 84104 USA |
| Manufacturer | Fortyfour group LLC |
| Address | 1770 S. 5350 W Ste 100 Salt Lake City UT 84104 USA |
| Factory | Shenzhen Myon Technology Co., Ltd |
| Address | 4/F, Building 7, Lijincheng Industrial Park, Gongye Road, Longhua District, Shenzhen, China Post: 518109 |
| Product Designation | Hunkster Speaker |
| Brand Name | Origaudio |
| Test Model | X9607601007 |
| Date of test | Dec. 14, 2021 to Dec. 21, 2021 |
| Deviation | No any deviation from the test method |
| Condition of Test Sample | Normal |
| Test Result | Pass |
| Report Template | AGCRT-US-BR/RF |

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC PART 15.247.

| Prepared By | kenyohong | |
|-------------|--------------------------------|---------------|
| | Kelly Cheng (Project Engineer) | Dec. 21, 2021 |
| Reviewed By | Calin Lin | |
| | Calvin Liu (Reviewer) | Dec. 21, 2021 |
| Approved By | Max Zhang | |
| | Max Zhang (Authorized Officer) | Dec. 21, 2021 |



Page 6 of 69

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

The EUT is designed as "Hunkster Speaker". It is designed by way of utilizing the GFSK, Pi/4 DQPSK and 8DPSK technology to achieve the system operation.

A major technical description of EUT is described as following

| , | • |
|---------------------|--|
| Operation Frequency | 2.402 GHz to 2.480 GHz |
| RF Output Power | 3.703dBm (Max) |
| Bluetooth Version | V5.0 |
| Modulation | BR ⊠GFSK, EDR ⊠π /4-DQPSK, ⊠8DPSK BLE □GFSK 1Mbps □GFSK 2Mbps |
| Number of channels | 79 |
| Hardware Version | 1.0 |
| Software Version | 1.0 |
| Antenna Designation | PCB Antenna (Comply with requirements of the FCC part 15.203) |
| Antenna Gain | 1.9dBi |
| Power Supply | DC 5V by adapter or DC 3.7V by battery |

2.2. TABLE OF CARRIER FREQUENCYS

| Frequency Band | Channel Number | Frequency |
|----------------|----------------|-----------|
| | 0 | 2402 MHz |
| | 1 | 2403 MHz |
| | : | : |
| | 38 | 2440 MHz |
| 2402~2480MHz | 39 | 2441 MHz |
| | 40 | 2442 MHz |
| | : | : |
| | 77 | 2479 MHz |
| | 78 | 2480 MHz |



Report No.: AGC08777211201FE03 Page 7 of 69

2.3. RECEIVER INPUT BANDWIDTH

The input bandwidth of the receiver is 1.3MHz, in every connection one Bluetooth device is the master and the other one is slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally, the type of connection (e.g. single of multi slot packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also, the slave of the connection will use these settings. Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

2.4. EXAMPLE OF A HOPPING SEQUENCY IN DATA MODE

Example of a hopping sequence in data mode:

40, 21, 44, 23, 04, 15, 66, 56, 19, 78, 07, 28, 69, 55,

36, 45, 05, 13, 43, 74, 57, 35, 67, 76, 02, 34, 54, 63,

42, 11, 30, 06, 64, 25, 75, 48, 17, 33, 58, 01, 29, 14,

51, 72, 03, 31, 50, 61, 77, 18, 10, 47, 12, 68, 08, 49,

20, 00, 73, 09, 16, 60, 71, 41, 24, 53, 38, 26, 46, 37,

65, 32, 70, 52, 27, 59, 22, 62, 39

2.5. EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR

The generation of the hopping sequence in connection mode depends essentially on two input values:

- 1. LAP/UAP of the master of the connection.
- 2. Internal master clock.

The LAP (lower address part) are the 24 LSB's of the 48 BD_ADDRESS. The BD_ADDRESS is an unambiguous number of every Bluetooth unit. The UAP (upper address part) are the 24MSB's of the 48BD_ADDRESS

The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and is never turned off. For behavior action with other units only offset is used. It has no relation to the time of the day. Its resolution is at least half the RX/TX slot length of 312.5us. The clock has a cycle of about one day(23h30). In most case it is implemented as 28 bits counter. For the deriving of the hopping sequence the entire. LAP (24 bits),4LSB's(4bits) (Input 1) and the 27MSB's of the clock (Input 2) are used. With this input values different mathematical procedures (permutations, additions, XOR-operations) are performed to generate the Sequence. This will be done at the beginning of every new transmission.

Regarding short transmissions the Bluetooth system has the following behavior:

The first connection between the two devices is established, a hopping sequence was generated. For Transmitting the wanted data the complete hopping sequence was not used. The connection ended.



Report No.: AGC08777211201FE03 Page 8 of 69

The second connection will be established. A new hopping sequence is generated. Due to the fact the Bluetooth clock has a different value, because the period between the two transmission is longer (and it Cannot be shorter) than the minimum resolution of the clock(312.5us). The hopping sequence will always differ from the first one.

2.6. RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID**: **2AWVU-HUNKSTER** filing to comply with the FCC PART 15.247 requirements.

2.7. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013). Radiated testing was performed at an antenna to EUT distance 3 meters.

2.8. SPECIAL ACCESSORIES

Refer to section 5.2.

2.9. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

2.10. ANTENNA REQUIREMENT

This intentional radiator is designed with a permanently attached antenna of an antenna to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

For more information of the antenna, please refer to the APPENDIX B: PHOTOGRAPHS OF EUT.



Page 9 of 69

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

| Item | Measurement Uncertainty |
|---|----------------------------|
| Uncertainty of Conducted Emission for AC Port | $U_c = \pm 3.1 \text{ dB}$ |
| Uncertainty of Radiated Emission below 1GHz | $U_c = \pm 4.0 \text{ dB}$ |
| Uncertainty of Radiated Emission above 1GHz | $U_c = \pm 4.8 \text{ dB}$ |
| Uncertainty of total RF power, conducted | $U_c = \pm 0.8 \text{ dB}$ |
| Uncertainty of RF power density, conducted | $U_c = \pm 2.6 \text{ dB}$ |
| Uncertainty of spurious emissions, conducted | U _c = ±2 % |
| Uncertainty of Occupied Channel Bandwidth | $U_c = \pm 2 \%$ |




4. DESCRIPTION OF TEST MODES

| NO. | TEST MODE DESCRIPTION |
|-----|--------------------------|
| 1 | Low channel GFSK |
| 2 | Middle channel GFSK |
| 3 | High channel GFSK |
| 4 | Low channel π/4-DQPSK |
| 5 | Middle channel π/4-DQPSK |
| 6 | High channel π/4-DQPSK |
| 7 | Low channel 8DPSK |
| 8 | Middle channel 8DPSK |
| 9 | High channel 8DPSK |
| 10 | Hopping mode GFSK |
| 11 | Hopping mode π/4-DQPSK |
| 12 | Hopping mode 8DPSK |

Note:

- 1. Only the result of the worst case was recorded in the report, if no other cases.
- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 3. For Conducted Test method, a temporary antenna connector is provided by the manufacture.

Software Setting





Page 11 of 69

5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF EUT SYSTEM

Radiated Emission Configure:



Conducted Emission Configure:

| EUT | AE |
|-----|----|
| | |

5.2. EQUIPMENT USED IN TESTED SYSTEM

| Item | Equipment | Model No. | ID or Specification | Remark |
|------|------------------|---------------------|---------------------|--------|
| 1 | Hunkster Speaker | X9607601007 | 2AWVU-HUNKSTER | EUT |
| 2 | Adapter | ZL-PCB0100020502000 | N/A | AE |

5.3. SUMMARY OF TEST RESULTS

| FCC RULES | DESCRIPTION OF TEST | RESULT |
|--------------------|-----------------------------|-----------|
| 15.247 (b)(1) | Peak Output Power | Compliant |
| 15.247 (a)(1) | 20 dB Bandwidth | Compliant |
| 15.247 (d) | Conducted Spurious Emission | Compliant |
| 15.209 | Radiated Emission | Compliant |
| 15.247 (a)(1)(iii) | Number of Hopping Frequency | Compliant |
| 15.247 (a)(1)(iii) | Time of Occupancy | Compliant |
| 15.247 (a)(1) | Frequency Separation | Compliant |
| 15.207 | Conducted Emission | Compliant |



Page 12 of 69

6. TEST FACILITY

| Test Site | Attestation of Global Compliance (Shenzhen) Co., Ltd | | |
|-----------------------------------|--|--|--|
| Location | 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China | | |
| Designation Number | CN1259 | | |
| FCC Test Firm Registration Number | 975832 | | |
| A2LA Cert. No. | 5054.02 | | |
| Description | Attestation of Global Compliance (Shenzhen) Co., Ltd is accredited by A2LA | | |

TEST EQUIPMENT OF CONDUCTED EMISSION TEST

| Equipment | Manufacturer | Model | S/N | Cal. Date | Cal. Due |
|---------------|--------------|------------------|--------|---------------|---------------|
| TEST RECEIVER | R&S | ESPI | 101206 | May 15, 2021 | May 14, 2022 |
| LISN | R&S | ESH2-Z5 | 100086 | Jun. 09, 2021 | Jun. 08, 2022 |
| Test software | R&S | ES-K1(Ver.V1.71) | N/A | N/A | N/A |

TEST EQUIPMENT OF RADIATED EMISSION TEST

| Equipment | Manufacturer | Model | S/N | Cal. Date | Cal. Due |
|--------------------------------------|----------------|----------------------|------------|---------------|---------------|
| TEST RECEIVER | R&S | ESCI | 10096 | May 15, 2021 | May 14, 2022 |
| EXA Signal Analyzer | Agilent | N9010A | MY53470504 | Nov. 17, 2021 | Nov. 16, 2022 |
| 2.4GHz Filter | EM Electronics | 2400-2500MHz | N/A | Mar. 23, 2020 | Mar. 22, 2022 |
| Attenuator | ZHINAN | E-002 | N/A | Sep. 03, 2020 | Sep. 02, 2022 |
| Horn antenna | SCHWARZBECK | BBHA 9170 | #768 | Sep.15, 2021 | Sep. 14, 2023 |
| Active loop antenna (9K-30MHz) | ZHINAN | ZN30900C | 18051 | May 22, 2020 | May 21, 2022 |
| Double-Ridged Waveguide Horn | ETS LINDGREN | 3117 | 00034609 | Apr. 23, 2021 | Apr. 22, 2022 |
| Broadband Preamplifier | ETS LINDGREN | 3117PA | 00225134 | Sep. 03, 2020 | Sep. 02, 2022 |
| ANTENNA | SCHWARZBECK | VULB9168 | 494 | Jan. 08, 2021 | Jan. 07, 2023 |
| Test software | Tonscend | JS32-RE (Ver.2.5) | N/A | N/A | N/A |



Page 13 of 69

7. PEAK OUTPUT POWER

7.1. MEASUREMENT PROCEDURE


For peak power test:


- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
- 3. RBW > 20 dB bandwidth of the emission being measured.
- 4. VBW ≥RBW.
- 5. Sweep: Auto.
- 6. Detector function: Peak.
- 7. Trace: Max hold.

Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

PEAK POWER TEST SETUP







7.3. LIMITS AND MEASUREMENT RESULT

| Test Data of Conducted Output Power | | | | |
|-------------------------------------|-----------------------|---------------------|-----------------|--------------|
| Test Mode | Test Channel (MHz) | Peak Power (dBm) | Limits (dBm) | Pass or Fail |
| | 2402 | 3.046 | \$21 | Pass |
| GFSK | 2441 | 2.872 | ⊴ 21 | Pass |
| | 2480 | 2.327 | \$21 | Pass |
| π /4-DQPSK | 2402 | 3.360 | \$21 | Pass |
| | 2441 | 3.196 | ⊴ 21 | Pass |
| | 2480 | 2.656 | ≨ 21 | Pass |
| 8DPSK | 2402 | 3.703 | \$21 | Pass |
| | 2441 | 3.526 | ⊴ 21 | Pass |
| | 2480 | 2.980 | ≨ 21 | Pass |

Test Graphs of Conducted Output Power





















CF Step 500.000 kHz


Freq Offset

Man

<u>Auto</u>

Span 5.000 MHz Sweep 1.066 ms (1000 pts)





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_EDR_ANT1_2480_3Mbps_Peak Power

#VBW 5.0 MHz

Center 2.480000 GHz #Res BW 1.5 MHz




Page 19 of 69


8. 20DB BANDWIDTH

8.1. MEASUREMENT PROCEDURE

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hoping channel
 The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video
 bandwidth (VBW) shall be approximately three times RBW; Sweep = auto; Detector function = peak
- 4. Set SPA Trace 1 Max hold, then View.

8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)









8.3. LIMITS AND MEASUREMENT RESULTS

| Test Data of Occupied Bandwidth and -20dB Bandwidth | | | | | |
|---|-----------------------|---------------------------------|--------------------------|--------|--------------|
| Test Mode | Test Channel (MHz) | 99% Occupied Bandwidth (MHz) | -20dB Bandwidth (MHz) | Limits | Pass or Fail |
| GFSK | 2402 | 0.929 | 0.970 | N/A | Pass |
| | 2441 | 0.937 | 0.971 | N/A | Pass |
| | 2480 | 0.950 | 1.011 | N/A | Pass |
| π /4-DQPSK | 2402 | 1.196 | 1.307 | N/A | Pass |
| | 2441 | 1.202 | 1.309 | N/A | Pass |
| | 2480 | 1.205 | 1.314 | N/A | Pass |
| 8DPSK | 2402 | 1.194 | 1.264 | N/A | Pass |
| | 2441 | 1.200 | 1.263 | N/A | Pass |
| | 2480 | 1.201 | 1.261 | N/A | Pass |

Test Graphs of Occupied Bandwidth and -20 Bandwidth







OBW Power

Test_Graph_BR_ANT1_2480_1Mbps_OBW

x dB

99.00 %

-20.00 dB

96.418 kHz


1.011 MHz

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

Transmit Freq Error

x dB Bandwidth





x dB

Test_Graph_EDR_ANT1_2441_2Mbps_OBW


-20.00 dB

1.309 MHz

x dB Bandwidth

Freq Offset





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

OBW Power

Test_Graph_EDR_ANT1_2402_3Mbps_OBW

x dB

99.00 %

-20.00 dB

1.1935 MHz

84.693 kHz


1.264 MHz

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

Transmit Freq Error

x dB Bandwidth





OBW Power

Test_Graph_EDR_ANT1_2480_3Mbps_OBW

x dB

99.00 %

-20.00 dB

82.408 kHz

1.261 MHz

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

Transmit Freq Error

x dB Bandwidth



Page 25 of 69

9. CONDUCTED SPURIOUS EMISSION

9.1. MEASUREMENT PROCEDURE

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the EUT Work on the top, the Middle and the bottom operation frequency individually.
- 3. Set the Span = wide enough to capture the peak level of the in-band emission and all spurious emissions from the lowest frequency generated in the EUT up through the 10th harmonic.
 - RBW = 100 kHz; VBW= 300 kHz; Sweep = auto; Detector function = peak.
- 4. Set SPA Trace 1 Max hold, then View.

9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)


The same as described in section 8.2

9.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6


9.4. LIMITS AND MEASUREMENT RESULT

| LIMITS AND MEASUREMENT RESULT | | | |
|---|--------------------------------|----------|--|
| Amuliachia Limita | Measurement Result | | |
| Applicable Limits | Test Data | Criteria | |
| In any 100 kHz Bandwidth Outside the | At least -20dBc than the limit | | |
| frequency band in which the spread spectrum | Specified on the BOTTOM | PASS | |
| intentional radiator is operating, the radio frequency | Channel | | |
| power that is produce by the intentional radiator shall | | | |
| be at least 20 dB below that in 100KHz bandwidth | | | |
| within the band that contains the highest level of the | | | |
| desired power. | At least -20dBc than the limit | PASS | |
| In addition, radiation emissions which fall in the | Specified on the TOP Channel | PASS | |
| restricted bands, as defined in §15.205(a), must also | | | |
| comply with the radiated emission limits specified | | | |
| in§15.209(a)) | | | |





Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.













0 Hz

Stop 2.400 GHz Sweep 228.0 ms (30000 pts)





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_BR_ANT1_2480_1Mbps_Lower Band Emissions

#VBW 300 kHz

Start 30 MHz #Res BW 100 kHz

Start Freq 2.400500000 GHz

2.403500000 GHz


<u>Auto</u>

Span 3.000 MHz Sweep 2.000 ms (30000 pts) CF Step 300.000 kHz

Freq Offset

Man





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_EDR_ANT1_2402_2Mbps_Reference Level

#VBW 300 kHz

Center 2.402000 GHz #Res BW 100 kHz












<u>Auto</u>

Span 3.000 MHz Sweep 2.000 ms (30000 pts) Man

Freq Offset






Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_EDR_ANT1_2480_2Mbps_Reference Level

#VBW 300 kHz

Center 2.480000 GHz #Res BW 100 kHz


























Mkr1 4.882 3 GHz -44.342 dBm 10 dB/div Ref 20.00 dBm Center Freq 13.741750000 GHz Start Fred 2.483500000 GHz 25.000000000 GHz **CF Step** 2.251650000 GHz <u>Auto</u> Mar Freq Offset 0 Hz Start 2.48 GHz #Res BW 100 kHz Stop 25.00 GHz Sweep 2.152 s (30000 pts) #VBW 300 kHz Test_Graph_EDR_ANT1_2441_3Mbps_Higher Band Emissions














Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_BR_ANT1_2480_1Mbps_Higher Band Edge Emissions


Web: http://www.agccert.com/






Test_Graph_BR_HOP_ANT1_NA_1Mbps_Higher Band Edge Emissions






Test_Graph_EDR_ANT1_2480_2Mbps_Higher Band Edge Emissions












Test_Graph_EDR_ANT1_2480_3Mbps_Higher Band Edge Emissions









Page 46 of 69

10. RADIATED EMISSION

10.1. MEASUREMENT PROCEDURE

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.



Page 47 of 69

The following table is the setting of spectrum analyzer and receiver.


| Spectrum Parameter | Setting |
|-----------------------|---|
| Start ~Stop Frequency | 9KHz~150KHz/RB 200Hz for QP |
| Start ~Stop Frequency | 150KHz~30MHz/RB 9KHz for QP |
| Start ~Stop Frequency | 30MHz~1000MHz/RB 120KHz for QP |
| Start Stan Fraguency | 1GHz~26.5GHz |
| Start ~Stop Frequency | 1MHz/3MHz for Peak, 1MHz/3MHz for Average |

| Receiver Parameter | Setting |
|-----------------------|--------------------------------|
| Start ~Stop Frequency | 9KHz~150KHz/RB 200Hz for QP |
| Start ~Stop Frequency | 150KHz~30MHz/RB 9KHz for QP |
| Start ~Stop Frequency | 30MHz~1000MHz/RB 120KHz for QP |




10.2. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz





Page 49 of 69

10.3. LIMITS AND MEASUREMENT RESULT

15.209 Limit in the below table has to be followed


| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|----------------------|-----------------------------------|-------------------------------|
| 0.009~0.490 | 2400/F(kHz) | 300 |
| 0.490~1.705 | 24000/F(kHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

10.4. TEST RESULT

Radiated emission below 30MHz


The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.






Radiated emission from 30MHz to 1000MHz

| EUT | Hunkster Speaker | Model Name | X9607601007 |
|-------------|------------------|-------------------|----------------|
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 7 | Antenna | Horizontal |




| NO. | Freq. [MHz] | Level [dBµV/m] | Factor [dB] | Limit [dBµV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity |
|-----|----------------|-------------------|----------------|-------------------|----------------|----------------|--------------|------------|
| 1 | 54.25 | 29.64 | 11.35 | 40.00 | 10.36 | 100 | 115 | Horizontal |
| 2 | 65.89 | 26.16 | 9.93 | 40.00 | 13.84 | 100 | 20 | Horizontal |
| 3 | 143.49 | 29.52 | 14.88 | 43.50 | 13.98 | 100 | 165 | Horizontal |
| 4 | 159.98 | 30.45 | 14.94 | 43.50 | 13.05 | 100 | 107 | Horizontal |
| 5 | 240.49 | 36.96 | 13.67 | 46.00 | 9.04 | 100 | 355 | Horizontal |
| 6 | 315.18 | 34.67 | 15.09 | 46.00 | 11.33 | 100 | 227 | Horizontal |

RESULT: PASS





| EUT | Hunkster Speaker | Model Name | X9607601007 |
|-------------|------------------|-------------------|----------------|
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 7 | Antenna | Vertical |



| NO. | Freq. [MHz] | Level [dBµV/m] | Factor [dB] | Limit [dBµV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity |
|-----|----------------|-------------------|----------------|-------------------|----------------|----------------|--------------|----------|
| 1 | 30.97 | 29.24 | 10.02 | 40.00 | 10.76 | 100 | 191 | Vertical |
| 2 | 56.19 | 28.73 | 11.20 | 40.00 | 11.27 | 100 | 359 | Vertical |
| 3 | 126.03 | 30.02 | 13.88 | 43.50 | 13.48 | 100 | 212 | Vertical |
| 4 | 159.98 | 31.46 | 14.94 | 43.50 | 12.04 | 100 | 259 | Vertical |
| 5 | 240.49 | 36.64 | 13.67 | 46.00 | 9.36 | 100 | 330 | Vertical |
| 6 | 315.18 | 31.17 | 15.09 | 46.00 | 14.83 | 100 | 327 | Vertical |

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. All test modes had been pre-tested. The mode 7 is the worst case and recorded in the report.



Page 52 of 69

Radiated emission above 1GHz

| EUT | Hunkster Speaker | Model Name | X9607601007 |
|-------------|------------------|-------------------|----------------|
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 7 | Antenna | Horizontal |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type |
|-----------|---------------|--------|----------------|----------|--------|------------|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | value Type |
| 4804.000 | 44.51 | 0.08 | 44.59 | 74 | -29.41 | peak |
| 4804.000 | 37.21 | 0.08 | 37.29 | 54 | -16.71 | AVG |
| 7206.000 | 40.89 | 2.21 | 43.1 | 74 | -30.9 | peak |
| 7206.000 | 32.99 | 2.21 | 35.2 | 54 | -18.8 | AVG |
| | | | | | | |
| | | | | | | |
| Remark: | | | | | | |

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

| EUT | Hunkster Speaker | Model Name | X9607601007 |
|-------------|------------------|-------------------|----------------|
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 7 | Antenna | Vertical |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type |
|-----------|---------------|--------|----------------|----------|--------|------------|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | value Type |
| 4804.000 | 43.98 | 0.08 | 44.06 | 74 | -29.94 | peak |
| 4804.000 | 36.74 | 0.08 | 36.82 | 54 | -17.18 | AVG |
| 7206.000 | 40.15 | 2.21 | 42.36 | 74 | -31.64 | peak |
| 7206.000 | 31.62 | 2.21 | 33.83 | 54 | -20.17 | AVG |
| | | | | | | |
| | | | | | | |

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.



Page 53 of 69

| EUT | Hunkster Speaker | Model Name | X9607601007 |
|-------------|------------------|-------------------|----------------|
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 8 | Antenna | Horizontal |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type |
|-----------|---------------|--------|----------------|----------|--------|--------------|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | - Value Type |
| 4882.000 | 45.89 | 0.14 | 46.03 | 74 | -27.97 | peak |
| 4882.000 | 38.29 | 0.14 | 38.43 | 54 | -15.57 | AVG |
| 7323.000 | 41.67 | 2.36 | 44.03 | 74 | -29.97 | peak |
| 7323.000 | 34.33 | 2.36 | 36.69 | 54 | -17.31 | AVG |
| | | | | | | |
| | | _ | | | | |

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

| EUT | Hunkster Speaker | Model Name | X9607601007 |
|-------------|------------------|-------------------|----------------|
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 8 | Antenna | Vertical |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type |
|-----------|---------------|--------|----------------|----------|--------|------------|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | value Type |
| 4882.000 | 45.39 | 0.14 | 45.53 | 74 | -28.47 | peak |
| 4882.000 | 37.51 | 0.14 | 37.65 | 54 | -16.35 | AVG |
| 7323.000 | 40.09 | 2.36 | 42.45 | 74 | -31.55 | peak |
| 7323.000 | 34.12 | 2.36 | 36.48 | 54 | -17.52 | AVG |
| | | | | | | |
| emark: | | | | | | |



Page 54 of 69

| EUT | Hunkster Speaker | Model Name | X9607601007 |
|-------------|------------------|-------------------|----------------|
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 9 | Antenna | Horizontal |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type |
|-----------|---------------|--------|----------------|----------|--------|------------|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | value Type |
| 4960.000 | 46.87 | 0.22 | 47.09 | 74 | -26.91 | peak |
| 4960.000 | 38.44 | 0.22 | 38.66 | 54 | -15.34 | AVG |
| 7440.000 | 41.31 | 2.64 | 43.95 | 74 | -30.05 | peak |
| 7440.000 | 32.89 | 2.64 | 35.53 | 54 | -18.47 | AVG |
| | | | | | | |
| | | | | | | |

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

| EUT | Hunkster Speaker | Model Name | X9607601007 |
|-------------|------------------|-------------------|----------------|
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 9 | Antenna | Vertical |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type |
|---------------|--------------------|---------------|----------------|----------|--------|------------|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | value Type |
| 4960.000 | 46.41 | 0.22 | 46.63 | 74 | -27.37 | peak |
| 4960.000 | 38.74 | 0.22 | 38.96 | 54 | -15.04 | AVG |
| 7440.000 | 40.81 | 2.64 | 43.45 | 74 | -30.55 | peak |
| 7440.000 | 32.01 | 2.64 | 34.65 | 54 | -19.35 | AVG |
| Remark: | | | | | | |
| | | | | | | |
| actor = Anter | nna Factor + Cable | e Loss - Pre- | amplifier. | | | |

RESULT: PASS

Note:

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.

Factor = Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.


All test modes had been tested. The Note: The 8DPSK modulation is the worst case and recorded in the report. modulation is the worst case and recorded in the report.




Test result for band edge emission at restricted bands

| EUT | Hunkster Speaker | Model Name | X9607601007 |
|-------------|------------------|-------------------|----------------|
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 7 | Antenna | Horizontal |

Test Graph for Peak Measurement



Test Graph for Average Measurement



RESULT: PASS




| EUT | Hunkster Speaker | Model Name | X9607601007 |
|-------------|------------------|-------------------|----------------|
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 7 | Antenna | Vertical |

Test Graph for Peak Measurement




Test Graph for Average Measurement






| EUT | Hunkster Speaker | Model Name | X9607601007 |
|-------------|------------------|-------------------|----------------|
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 9 | Antenna | Horizontal |

Test Graph for Peak Measurement




Test Graph for Average Measurement






| EUT | Hunkster Speaker | Model Name | X9607601007 |
|-------------|------------------|-------------------|----------------|
| Temperature | 25°C | Relative Humidity | 55.4% |
| Pressure | 960hPa | Test Voltage | Normal Voltage |
| Test Mode | Mode 9 | Antenna | Vertical |

Test Graph for Peak Measurement



Test Graph for Average Measurement



Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer. The 8DPSK modulation is the worst case and recorded in the report. modulation is the worst case and recorded in the report.