



中国认可
国际互认
检测
TESTING
CNAS L6791

TEST REPORT

Applicant: Arashi Vision Inc.
Address: 11th Floor, Building 2, Jinlitong Financial Center, Bao'an District, Shenzhen, Guangdong, China
Equipment Type: Insta360 Wave
Model Name: CINSABCA
Brand Name: Insta360
FCC ID: 2AWWH-CINSABCA
ISED Number: 26293-CINSABCA
Test Standard: 47 CFR Part 15 Subpart C
RSS-Gen Issue 5
RSS-247 Issue 3
(refer to section 3.1)
Sample Arrival Date: Apr. 11, 2025
Test Date: May 13, 2025 - Jun. 17, 2025
Date of Issue: Sep. 12, 2025

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Yang Wenxuan**Checked by:** Ye Hongji**Approved by:** Sunny Zou

(Technical Director)

Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Aug. 27, 2025</u>	<u>Initial Issue</u>
<u>Rev. 02</u>	<u>Sep. 12, 2025</u>	<u>Corrected the antenna type in Section 2.4.</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	4
1.1	Test Laboratory	4
1.2	Test Location.....	4
2	PRODUCT INFORMATION.....	5
2.1	Applicant Information.....	5
2.2	Manufacturer Information	5
2.3	General Description for Equipment under Test (EUT)	5
2.4	Technical Information	6
3	SUMMARY OF TEST RESULTS.....	7
3.1	Test Standards	7
3.2	Test Verdict	7
4	GENERAL TEST CONFIGURATIONS.....	8
4.1	Test Environments	8
4.2	Test Equipment List.....	8
4.3	Test Software List.....	9
4.4	Measurement Uncertainty	9
4.5	Description of Test Setup	10
4.6	Measurement Results Explanation Example.....	13
5	TEST ITEMS.....	14
5.1	Antenna Requirements.....	14
5.2	Output Power	15
5.3	Occupied Bandwidth	17
5.4	Conducted Spurious Emission	18

5.5	Band Edge (Authorized-band band-edge).....	20
5.6	Conducted Emission	22
5.7	Radiated Spurious Emission	23
5.8	Band Edge (Restricted-band band-edge).....	28
5.9	Power Spectral density (PSD).....	29
ANNEX A	TEST RESULT	30
A.1	Output Power, E.I.R.P	30
A.2	Occupied Bandwidth	33
A.3	Conducted Spurious Emissions	38
A.4	Band Edge (Authorized-band band-edge).....	43
A.5	Conducted Emissions.....	46
A.6	Radiated Spurious Emission	48
A.7	Band Edge (Restricted-band band-edge).....	56
A.8	Power Spectral Density (PSD)	57
ANNEX B	TEST SETUP PHOTOS	60
ANNEX C	EUT EXTERNAL PHOTOS	60
ANNEX D	EUT INTERNAL PHOTOS	60

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	<input checked="" type="checkbox"/> Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China <input type="checkbox"/> 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196. The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Arashi Vision Inc.
Address	11th Floor, Building 2, Jinlitong Financial Center, Bao'an District, Shenzhen, Guangdong, China

2.2 Manufacturer Information

Manufacturer	Arashi Vision Inc.
Address	11th Floor, Building 2, Jinlitong Financial Center, Bao'an District, Shenzhen, Guangdong, China

2.3 General Description for Equipment under Test (EUT)

EUT Name	Insta360 Wave
Model Name Under Test	CINSABCA
Series Model Name	N/A
Description of Model name differentiation	N/A
Serial Number	PSPLB2503DBTDK
Hardware Version	V05
Software Version	VPSP_0.0.18.5
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Technical Information

Network and Wireless connectivity	Bluetooth (BR+EDR+BLE) WIFI 802.11a, 802.11b, 802.11g and 802.11n 2.4G ISM Band
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	DTS
Modulation Type	GFSK
Product Type	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Transfer Rate	1 Mbps, 2 Mbps
Frequency Range	The frequency range used is 2400 MHz to 2483.5 MHz.
Number of Channel	16 (at intervals of 4 MHz)
Tested Channel	1 (2406 MHz), 8 (2442 MHz), 16 (2474 MHz)
Antenna Type	FPC Antenna
Antenna Gain	0.89 dBi
Antenna Impedance	50Ω
Antenna System (MIMO Smart Antenna)	N/A

All channel was listed on the following table:

Channel number	Freq. (MHz)	Channel number	Freq. (MHz)
1	2406	9	2446
2	2410	10	2450
3	2414	11	2454
4	2418	12	2458
5	2422	13	2462
6	2434	14	2466
7	2438	15	2470
8	2442	16	2474

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Intentional radiators of radio frequency equipment
2	RSS-Gen Issue 5	General Requirements for Compliance of Radio Apparatus
3	RSS-247 Issue 3	Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices
4	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
5 ☆	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules

3.2 Test Verdict

No.	Description	FCC Part No.	ISED Part No.	Channel	Test Result	Verdict
1	Antenna Requirement	15.203	RSS-247, 5.4 (f)	N/A	--	Pass ^{Note1}
2	Output Power	15.247(b)	RSS-247, 5.4 (d)	Low/Middle/ High	ANNEX A.1	Pass
3	Occupied Bandwidth	15.247(a)	RSS-GEN, 6.7; RSS-247, 5.2 (a)	Low/Middle/ High	ANNEX A.2	Pass
4	Conducted Spurious Emission	15.247(d)	RSS-247, 5.5	Low/Middle/ High	ANNEX A.3	Pass
5	Band Edge(Authorized-band band-edge)	15.247(d)	RSS-247, 5.5;	Low/High	ANNEX A.4	Pass
6	Conducted Emission	15.207	RSS-GEN, 8.8	Low/Middle/ High	ANNEX A.5	Pass
7	Radiated Spurious Emission	15.209 15.247(d)	RSS-247, 5.5	Low/Middle/ High	ANNEX A.6	Pass
8	Band Edge(Restricted-band band-edge)	15.209 15.247(d)	RSS-247, 5.5	Low/High	ANNEX A.7	Pass
9	Power spectral density (PSD)	15.247(e)	RSS-247, 5.2 (b)	Low/Middle/ High	ANNEX A.8	Pass
10	Receiver Spurious Emissions	--	RSS-Gen, 7.4	--	N/A	N/A ^{Note2}

Note ¹: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

Note ²: Only radio communication receivers operating in stand-alone mode within the band 30-960 MHz, as well as scanner receivers, are subject to Industry Canada requirements, so this test is not applicable.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	42% to 65%		
Atmospheric Pressure	100 kPa to 102 kPa		
Temperature	NT (Normal Temperature)		+21.0°C to +24.8°C
Working Voltage of the EUT	NV (Normal Voltage)		5 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	KEYSIGHT	N9020A	MY56060183	2024.08.01	2025.07.31
Spectrum Analyzer	KEYSIGHT	N9020A	MY46471071	2024.07.04	2025.07.03
Power Sensor	KEYSIGHT	U2063XA	MY58000247	2024.07.04	2025.07.03
Spectrum Analyzer	KEYSIGHT	N9020A	MY50531259	2024.08.01	2025.07.31
Signaling Unit	ROHDE&SCHWARZ	CMW500	171150	2024.05.22 2025.04.28	2025.05.21 2026.04.27
Test Antenna-Horn	SCHWARZBECK	BBHA 9120D	02460	2024.05.16	2027.05.15
Test Antenna-Horn	A-INFO	LB-180400KF	J211060273	2024.06.15	2027.06.14
Anechoic Chamber	RAINFORD	9m*6m*6m	140	2024.07.28	2027.07.27
Amplifier	COM-MV	LSCX_LNA1-12G-01	7210214	2024.08.01	2025.07.31
Amplifier	COM-MV	XKu_LNA7-18G-01	7210209	2024.08.01	2025.07.31
Amplifier	COM-MV	KA LNA18 40G-01	18050001	2024.12.05	2025.12.04
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2024.08.01	2025.07.31
Test Antenna-Bi-Log	SCHWARZBECK	VULB 9168	9168-01162	2023.08.04	2026.08.03
Test Antenna-Loop	SCHWARZBECK	FMZB 1519	1519-037	2024.01.23	2027.01.22
Amplifier	COM-MV	ZT30-1000M	B2018054558	2024.11.28	2025.11.27
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	130	2024.07.13	2027.07.12
EMI Receiver	KEYSIGHT	N9010B	MY57110309	2024.08.01	2025.07.31
LISN	SCHWARZBECK	NSLK 8127	8127-687	2024.05.09 2025.04.29	2025.05.08 2026.04.28
Shielded Enclosure	YiHeng Electronic Co., Ltd	3.5m*3.1m*2.8m	112	2022.02.19 2025.02.14	2025.02.18 2028.02.13

4.3 Test Software List

Description	Manufacturer	Software Version	Serial No.	Applicable test Setup
BL410R	BALUN	V2.1.1.488	N/A	The section 4.5.1
BL410E	BALUN	V22.930	N/A	The section 4.5.2&4.5.3&4.5.4&4.5.5

4.4 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.


Parameters	Uncertainty
Occupied Channel Bandwidth	2.8%
RF output power, conducted	1.28 dB
Power Spectral Density, conducted	1.30 dB
Unwanted Emissions, conducted	1.84 dB
All emissions, radiated	5.36 dB
Temperature	0.8°C
Humidity	4%

4.5 Description of Test Setup


4.5.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)


For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:
 Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm



4.5.2 For AC Power Supply Port Test




4.5.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.5.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.5.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.6 Measurement Results Explanation Example

4.6.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

4.6.2 For radiated band edges and spurious emission test:

$$E = EIRP - 20\log D + 104.8$$

where:

E = electric field strength in $\text{dB}\mu\text{V}/\text{m}$,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203 & 15.247(b); RSS-247, 5.4 (f)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Output Power

5.2.1 Test Limit

FCC § 15.247(b)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements.

RSS-247, 5.4 (d)

For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. Except as provided in Section 5.4(5), the e.i.r.p. shall not exceed 4 W.

5.2.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

a) Maximum peak conducted output power

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

Set the $RBW \geq DTS$ bandwidth.

Set $VBW \geq 3 \times RBW$.

Set span $\geq 3 \times RBW$

Sweep time = auto couple.

Detector = peak.

Trace mode = max hold.

Allow trace to fully stabilize.

Use peak marker function to determine the peak amplitude level.

EIRP= Maximum peak conducted output power +Antenna Gain.

b) Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set RBW \geq OBW if possible; otherwise, set RBW to the largest available value.

Set VBW \geq RBW. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

5.2.4 Test Result

Please refer to ANNEX A.1.

5.3 Occupied Bandwidth

5.3.1 Limit

FCC §15.247(a); RSS-247, 5.2 (a); RSS-GEN, 6.7

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.

5.3.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

Use the following spectrum analyzer settings:

Set RBW = 100 kHz.

Set the video bandwidth (VBW) ≥ 3 RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.4 Test Result

Please refer to ANNEX A.2.

5.4 Conducted Spurious Emission

5.4.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.4.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

- a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).
- b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).
- c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

The following procedures shall be used to demonstrate compliance to these limits. Note that these procedures can be used in either an antenna-port conducted or radiated test set-up. Radiated tests must conform to the test site requirements and utilize maximization procedures defined herein.

Reference level measurement:

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ≥ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Emission level measurement:

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

Set the RBW = 100 kHz.

Set the VBW \geq 3 x RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

5.4.4 Test Result

Please refer to ANNEX A.3.

5.5 Band Edge (Authorized-band band-edge)

5.5.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.5.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The following procedures may be used to determine the peak or average field strength or power of an unwanted emission that is within 2 MHz of the authorized band edge. If a peak detector is utilized, use the procedure described in 13.2.1. Use the procedure described in 13.2.2 when using an average detector and the EUT can be configured to transmit continuously (i.e., duty cycle $\geq 98\%$). Use the procedure described in 13.2.3 when using an average detector and the EUT cannot be configured to transmit continuously but the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent). Use the procedure described in 13.2.4 when using an average detector for those cases where the EUT cannot be configured to transmit continuously and the duty cycle is not constant (duty cycle variations equal or exceed 2 percent).

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.

Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).

Set span to 2 MHz

RBW = 100 kHz.

VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)

Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency (f_{emission}) ± 0.5 MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by $f_{\text{emission}} \pm 0.5$ MHz.

5.5.4 Test Result

Please refer to ANNEX A.4.

5.6 Conducted Emission

5.6.1 Limit

FCC §15.207; RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.6.2 Test Setup

See section 4.5.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.6.4 Test Result

Please refer to ANNEX A.5.

5.7 Radiated Spurious Emission

5.7.1 Limit

FCC §15.209&15.247(d); RSS-GEN, 8.9; RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μ V/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. Field Strength ($\text{dB}\mu\text{V/m}$) = $20 \times \log[\text{Field Strength } (\mu\text{V/m})]$.
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: 54dB μ V/m@3m (AV) and 74dB μ V/m@3m (PK).

5.7.2 Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

Since the emission limits are specified in terms of radiated field strength levels, measurements performed to demonstrate compliance have traditionally relied on a radiated test configuration. Radiated measurements remain the principal method for demonstrating compliance to the specified limits; however antenna-port conducted measurements are also now acceptable to demonstrate compliance (see below for details). When radiated measurements are utilized, test site requirements and procedures for maximizing and measuring radiated emissions that are described in ANSI C63.10 shall be followed.

Antenna-port conducted measurements may also be used as an alternative to radiated measurements

for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

General Procedure for conducted measurements in restricted bands:

- a) Measure the conducted output power (in dBm) using the detector specified (see guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
- b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see guidance on determining the applicable antenna gain)
- c) Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies \leq 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies $>$ 1000 MHz).
- d) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
- e) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$$E = EIRP - 20\log D + 104.8$$

where:

E = electric field strength in $\text{dB}\mu\text{V}/\text{m}$,

$EIRP$ = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

- f) Compare the resultant electric field strength level to the applicable limit.
- g) Perform radiated spurious emission test.

Quasi-Peak measurement procedure

The specifications for measurements using the CISPR quasi-peak detector can be found in Publication 16 of the International Special Committee on Radio Frequency Interference (CISPR) of the International Electrotechnical Commission.

As an alternative to CISPR quasi-peak measurement, compliance can be demonstrated to the applicable emission limits using a peak detector.

Peak power measurement procedure:

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 1.
- b) VBW \geq 3 x RBW.

- c) Detector = Peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be longer for low duty cycle applications).

Table 1—RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Trace averaging across on and off times of the EUT transmissions followed by duty cycle correction:

If continuous transmission of the EUT (i.e., duty cycle \geq 98 percent) cannot be achieved and the duty cycle is constant (i.e., duty cycle variations are less than \pm 2 percent), then the following procedure shall be used:

- a) The EUT shall be configured to operate at the maximum achievable duty cycle.
- b) Measure the duty cycle, x, of the transmitter output signal as described in section 6.0.
- c) RBW = 1 MHz (unless otherwise specified).
- d) VBW \geq 3 x RBW.
- e) Detector = RMS, if span/(# of points in sweep) \leq (RBW/2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- f) Averaging type = power (i.e., RMS).
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- g) Sweep time = auto.
- h) Perform a trace average of at least 100 traces.
- i) A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:

- 1) If power averaging (RMS) mode was used in step f), then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.
- 2) If linear voltage averaging mode was used in step f), then the applicable correction factor is $20 \log(1/x)$, where x is the duty cycle.
- 3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

NOTE: Reduction of the measured emission amplitude levels to account for operational duty factor is not permitted. Compliance is based on emission levels occurring during transmission - not on an average across on and off times of the transmitter.

Determining the applicable transmit antenna gain:

A conducted power measurement will determine the maximum output power associated with a restricted band emission; however, in order to determine the associated EIRP level, the gain of the transmitting antenna (in dBi) must be added to the measured output power (in dBm).

Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.

See KDB 662911 for guidance on calculating the additional array gain term when determining the effective antenna gain for a EUT with multiple outputs occupying the same or overlapping frequency ranges in the same band.

Radiated spurious emission test:

An additional consideration when performing conducted measurements of restricted band emissions is that unwanted emissions radiating from the EUT cabinet, control circuits, power leads, or intermediate circuit elements will likely go undetected in a conducted measurement configuration. To address this concern, a radiated test shall be performed to ensure that emissions emanating from the EUT cabinet (rather than the antenna port) also comply with the applicable limits.

For these cabinet radiated spurious emission measurements the EUT transmit antenna may be replaced with a termination matching the nominal impedance of the antenna. Procedures for performing radiated measurements are specified in ANSI C63.10. All detected emissions shall comply with the applicable limits.

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360° , and both horizontal and vertical polarizations of the

Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.7.4 Test Result

Please refer to ANNEX A.6.

5.8 Band Edge (Restricted-band band-edge)

5.8.1 Limit

FCC §15.209&15.247(d); RSS-GEN, 8.10; RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.8.2 Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

For transmitters operating above 1 GHz repeat the measurement with an average detector.

5.8.4 Test Result

Please refer to ANNEX A.7.

5.9 Power Spectral density (PSD)

5.9.1 Limit

FCC §15.247(e); RSS-247, 5.2 (b)

The same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of Section 5.4(4), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

5.9.2 Test Setup

See section 4.5.1 (Diagram 1) for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.

Set the VBW $\geq 3 \text{ RBW}$.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.9.4 Test Result

Please refer to ANNEX A.8.

ANNEX A TEST RESULT**A.1 Output Power, E.I.R.P**Peak Power Test Data

Channel	Measured Output Peak Power		Limit		Verdict	
	GFSK (1Mbps)		dBm	mW		
	dBm	mW				
Low Channel	6.81	4.80			Pass	
Middle Channel	7.58	5.73	30	1000	Pass	
High Channel	7.55	5.69			Pass	

Channel	Measured Output Peak Power		Limit		Verdict	
	GFSK (2Mbps)		dBm	mW		
	dBm	mW				
Low Channel	8.25	6.68			Pass	
Middle Channel	9.02	7.98	30	1000	Pass	
High Channel	9.01	7.96			Pass	

E.I.R.P Test Data (For ISED)

Channel	E.I.R.P		Limit		Verdict	
	GFSK (1Mbps)		dBm	mW		
	dBm	mW				
Low Channel	7.70	5.89			Pass	
Middle Channel	8.47	7.04	36	4000	Pass	
High Channel	8.44	6.98			Pass	

Channel	E.I.R.P		Limit		Verdict	
	GFSK (2Mbps)		dBm	mW		
	dBm	mW				
Low Channel	9.14	8.19			Pass	
Middle Channel	9.91	9.79	36	4000	Pass	
High Channel	9.90	9.77			Pass	

Test Plots

GFSK (1Mbps) LOW CHANNEL



GFSK (1Mbps) MIDDLE CHANNEL



GFSK (1Mbps) HIGH CHANNEL



GFSK (2Mbps) LOW CHANNEL



GFSK (2Mbps) MIDDLE CHANNEL



GFSK (2Mbps) HIGH CHANNEL



A.2 Occupied Bandwidth

Test Data

Test Mode	GFSK (1Mbps)		
Channel	6 dB Bandwidth (kHz)	99% Bandwidth (kHz)	6 dB Bandwidth Limits (kHz)
Low Channel	689.900	1040.400	≥500
Middle Channel	712.600	1041.000	≥500
High Channel	705.100	1041.600	≥500

Test Mode	GFSK (2Mbps)		
Channel	6 dB Bandwidth (kHz)	99% Bandwidth (kHz)	6 dB Bandwidth Limits (kHz)
Low Channel	1140.000	2071.300	≥500
Middle Channel	1170.000	2070.800	≥500
High Channel	1200.000	2066.900	≥500

Test Plots**6 dB Bandwidth****GFSK (1Mbps) LOW CHANNEL****GFSK (1Mbps) MIDDLE CHANNEL****GFSK (1Mbps) HIGH CHANNEL**

GFSK (2Mbps) LOW CHANNEL



GFSK (2Mbps) MIDDLE CHANNEL



GFSK (2Mbps) HIGH CHANNEL



99% Bandwidth**GFSK (1Mbps) LOW CHANNEL****GFSK (1Mbps) MIDDLE CHANNEL****GFSK (1Mbps) HIGH CHANNEL**

GFSK (2Mbps) LOW CHANNEL



GFSK (2Mbps) MIDDLE CHANNEL



GFSK (2Mbps) HIGH CHANNEL






A.3 Conducted Spurious Emissions


Test Data

GFSK (1Mbps)				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-35.89	6.01	-13.99	Pass
Middle Channel	-37.68	6.78	-13.22	Pass
High Channel	-35.01	6.66	-13.34	Pass


GFSK (2Mbps)				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-34.17	7.11	-12.89	Pass
Middle Channel	-34.25	7.92	-12.08	Pass
High Channel	-34.15	7.87	-12.14	Pass

Test Plots**GFSK (1Mbps) LOW CHANNEL,
CARRIER LEVEL****GFSK (1Mbps) LOW CHANNEL,
SPURIOUS 30 MHz ~ 3 GHz****GFSK (1Mbps) LOW CHANNEL,
SPURIOUS 2 GHz ~ 25 GHz****GFSK (1Mbps) MIDDLE CHANNEL, CARRIER
LEVEL**

GFSK (1Mbps) MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK (1Mbps) MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




GFSK (1Mbps) HIGH CHANNEL, CARRIER LEVEL



GFSK (1Mbps) HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK (1Mbps) HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




GFSK (2Mbps) LOW CHANNEL, CARRIER LEVEL



GFSK (2Mbps) LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK (2Mbps) LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




GFSK (2Mbps) MIDDLE CHANNEL, CARRIER LEVEL



GFSK (2Mbps) MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK (2Mbps) MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




GFSK (2Mbps) HIGH CHANNEL, CARRIER LEVEL



GFSK (2Mbps) HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



GFSK (2Mbps) HIGH CHANNEL,
SPURIOUS 2 GHz ~ 25 GHz



A.4 Band Edge (Authorized-band band-edge)

Note: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Test Data

GFSK (1Mbps)				
Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-47.98	6.01	-13.99	Pass
High Channel	-47.28	6.66	-13.34	Pass


GFSK (2Mbps)				
Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-45.46	7.11	-12.89	Pass
High Channel	-46.20	7.87	-12.14	Pass

Test Plots

GFSK (1Mbps) LOW CHANNEL, CARRIER LEVEL




GFSK (1Mbps) LOW CHANNEL, BAND EDGE




GFSK (1Mbps) HIGH CHANNEL, CARRIER LEVEL




GFSK (1Mbps) HIGH CHANNEL, BAND EDGE



GFSK (2Mbps) LOW CHANNEL, CARRIER LEVEL




GFSK (2Mbps) LOW CHANNEL, BAND EDGE



GFSK (2Mbps) HIGH CHANNEL, CARRIER LEVEL



GFSK (2Mbps) HIGH CHANNEL, BAND EDGE



A.5 Conducted Emissions


Note ¹: The EUT is working in the Normal link mode. All modes have been tested and normal link mode is worst.

Note ²: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

Note ³: Results (dBuV) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)


Test Data and Plots

PHASE L



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.158	45.59	9.86	65.57	19.98	Peak	L	Pass
1**	0.158	28.18	9.86	55.57	27.39	AV	L	Pass
2	0.166	45.16	9.85	65.16	20.00	Peak	L	Pass
2**	0.166	27.71	9.85	55.16	27.45	AV	L	Pass
3	0.224	40.21	9.84	62.67	22.46	Peak	L	Pass
3**	0.224	25.67	9.84	52.67	27.00	AV	L	Pass
4	0.722	37.39	10.50	56.00	18.61	Peak	L	Pass
4**	0.722	26.09	10.50	46.00	19.91	AV	L	Pass
5	10.180	38.48	10.57	60.00	21.52	Peak	L	Pass
5**	10.180	27.49	10.57	50.00	22.51	AV	L	Pass
6	28.562	37.81	11.00	60.00	22.19	Peak	L	Pass
6**	28.562	23.45	11.00	50.00	26.55	AV	L	Pass

PHASE N



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.162	45.97	9.85	65.36	19.39	Peak	N	Pass
1**	0.162	27.45	9.85	55.36	27.91	AV	N	Pass
2	0.222	40.34	9.84	62.74	22.40	Peak	N	Pass
2**	0.222	26.05	9.84	52.74	26.69	AV	N	Pass
3	0.404	37.78	10.57	57.77	19.99	Peak	N	Pass
3**	0.404	25.17	10.57	47.77	22.60	AV	N	Pass
4	0.806	37.21	10.60	56.00	18.79	Peak	N	Pass
4**	0.806	26.09	10.60	46.00	19.91	AV	N	Pass
5	10.302	37.88	10.56	60.00	22.12	Peak	N	Pass
5**	10.302	25.59	10.56	50.00	24.41	AV	N	Pass
6	13.844	37.30	10.59	60.00	22.70	Peak	N	Pass
6**	13.844	24.96	10.59	50.00	25.04	AV	N	Pass

A.6 Radiated Spurious Emission

Note ¹: The symbol of “--” in the table which means not application.

Note ²: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.


Note ³: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note ⁴: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and 2M-Middle channel mode is the worst.

Note ⁵: Results (dBuV/m) = Original reading level of Spectrum Analyzer (dBuV/m) + Factor (dB)

Test Data and Plots


30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	34.849	14.21	-26.96	29.5	15.29	Peak	360.00	200	Horizontal	Pass
2	54.729	15.95	-27.13	29.5	13.55	Peak	150.00	200	Horizontal	Pass
3	99.823	14.00	-29.96	33.0	19.00	Peak	345.00	100	Horizontal	Pass
4	166.251	14.25	-26.28	33.0	18.75	Peak	237.00	200	Horizontal	Pass
5	287.956	18.70	-25.91	35.5	16.80	Peak	96.00	200	Horizontal	Pass
6	825.929	27.42	-11.94	35.5	8.08	Peak	15.00	200	Horizontal	Pass

30 MHz to 1 GHz, ANT V

10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	30.485	20.97	-26.85	29.5	8.53	Peak	329.00	100	Vertical	Pass
2	45.031	18.01	-26.77	29.5	11.49	Peak	155.00	100	Vertical	Pass
3	57.153	18.07	-27.28	29.5	11.43	Peak	166.00	100	Vertical	Pass
4	129.885	18.19	-27.59	33.0	14.81	Peak	285.00	100	Vertical	Pass
5	150.007	19.07	-26.28	33.0	13.93	Peak	280.00	100	Vertical	Pass
6	163.342	19.85	-26.26	33.0	13.15	Peak	258.00	100	Vertical	Pass

Note ¹: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note ²: The spurious from 18GHz-25GHz is noise only, do not show on the report.

GFSK (1Mbps) LOW CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1335.527	44.81	74.0	29.19	Peak	300.00	400	Horizontal	Pass
1**	1335.527	27.53	54.0	26.47	AV	300.00	400	Horizontal	Pass
2	2971.797	51.27	74.0	22.73	Peak	160.00	200	Horizontal	Pass
2**	2971.797	38.35	54.0	15.65	AV	160.00	200	Horizontal	Pass
3	4910.433	53.65	74.0	20.35	Peak	254.00	200	Horizontal	Pass
3**	4910.433	43.52	54.0	10.48	AV	254.00	200	Horizontal	Pass
4	7628.158	52.56	74.0	21.44	Peak	119.00	100	Horizontal	Pass
4**	7628.158	43.12	54.0	10.88	AV	119.00	100	Horizontal	Pass
5	12476.246	54.36	74.0	19.64	Peak	288.00	200	Horizontal	Pass
5**	12476.246	44.71	54.0	9.29	AV	288.00	200	Horizontal	Pass
6	16854.455	57.73	74.0	16.27	Peak	311.00	200	Horizontal	Pass
6**	16854.455	43.33	54.0	10.67	AV	311.00	200	Horizontal	Pass

GFSK (1Mbps) LOW CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1470.014	41.73	74.0	32.27	Peak	105.00	100	Vertical	Pass
1**	1470.014	31.88	54.0	22.12	AV	105.00	100	Vertical	Pass
2	2992.852	52.99	74.0	21.01	Peak	77.00	100	Vertical	Pass
2**	2992.852	40.89	54.0	13.11	AV	77.00	100	Vertical	Pass
3	4823.345	54.18	74.0	19.82	Peak	223.00	200	Vertical	Pass
3**	4823.345	39.40	54.0	14.60	AV	223.00	200	Vertical	Pass
4	7963.538	53.64	74.0	20.36	Peak	136.00	400	Vertical	Pass
4**	7963.538	43.63	54.0	10.37	AV	136.00	400	Vertical	Pass
5	12446.682	48.28	74.0	25.72	Peak	29.00	200	Vertical	Pass
5**	12446.682	44.10	54.0	9.90	AV	29.00	200	Vertical	Pass
6	17454.323	57.49	74.0	16.51	Peak	260.00	400	Vertical	Pass
6**	17454.323	44.04	54.0	9.96	AV	260.00	400	Vertical	Pass

GFSK (1Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1336.629	44.27	74.0	29.73	Peak	162.00	200	Horizontal	Pass
1**	1336.629	29.61	54.0	24.39	AV	162.00	200	Horizontal	Pass
2	2974.719	50.41	74.0	23.59	Peak	277.00	100	Horizontal	Pass
2**	2974.719	42.81	54.0	11.19	AV	277.00	100	Horizontal	Pass
3	4916.342	49.98	74.0	24.02	Peak	48.00	200	Horizontal	Pass
3**	4916.342	42.19	54.0	11.81	AV	48.00	200	Horizontal	Pass
4	7627.782	53.68	74.0	20.32	Peak	82.00	200	Horizontal	Pass
4**	7627.782	41.60	54.0	12.40	AV	82.00	200	Horizontal	Pass
5	12471.383	49.85	74.0	24.15	Peak	71.00	200	Horizontal	Pass
5**	12471.383	41.55	54.0	12.45	AV	71.00	200	Horizontal	Pass
6	16853.129	54.09	74.0	19.91	Peak	241.00	200	Horizontal	Pass
6**	16853.129	43.43	54.0	10.57	AV	241.00	200	Horizontal	Pass

GFSK (1Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1467.894	42.10	74.0	31.90	Peak	274.00	100	Vertical	Pass
1**	1467.894	29.49	54.0	24.51	AV	274.00	100	Vertical	Pass
2	2989.666	51.55	74.0	22.45	Peak	263.00	400	Vertical	Pass
2**	2989.666	36.61	54.0	17.39	AV	263.00	400	Vertical	Pass
3	4825.736	50.36	74.0	23.64	Peak	115.00	200	Vertical	Pass
3**	4825.736	41.43	54.0	12.57	AV	115.00	200	Vertical	Pass
4	7966.919	53.71	74.0	20.29	Peak	278.00	200	Vertical	Pass
4**	7966.919	41.45	54.0	12.55	AV	278.00	200	Vertical	Pass
5	12445.680	49.86	74.0	24.14	Peak	105.00	300	Vertical	Pass
5**	12445.680	40.97	54.0	13.03	AV	105.00	300	Vertical	Pass
6	17459.567	53.73	74.0	20.27	Peak	183.00	400	Vertical	Pass
6**	17459.567	46.79	54.0	7.21	AV	183.00	400	Vertical	Pass

GFSK (1Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1338.320	44.54	74.0	29.46	Peak	178.00	100	Horizontal	Pass
1**	1338.320	29.80	54.0	24.20	AV	178.00	100	Horizontal	Pass
2	2976.760	53.41	74.0	20.59	Peak	282.00	100	Horizontal	Pass
2**	2976.760	37.69	54.0	16.31	AV	282.00	100	Horizontal	Pass
3	4913.407	49.95	74.0	24.05	Peak	219.00	200	Horizontal	Pass
3**	4913.407	42.13	54.0	11.87	AV	219.00	200	Horizontal	Pass
4	7622.940	55.50	74.0	18.50	Peak	288.00	100	Horizontal	Pass
4**	7622.940	43.09	54.0	10.91	AV	288.00	100	Horizontal	Pass
5	12476.651	54.22	74.0	19.78	Peak	296.00	300	Horizontal	Pass
5**	12476.651	46.49	54.0	7.51	AV	296.00	300	Horizontal	Pass
6	16854.004	56.55	74.0	17.45	Peak	247.00	400	Horizontal	Pass
6**	16854.004	42.11	54.0	11.89	AV	247.00	400	Horizontal	Pass

GFSK (1Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1467.062	45.10	74.0	28.90	Peak	338.00	100	Vertical	Pass
1**	1467.062	33.17	54.0	20.83	AV	338.00	100	Vertical	Pass
2	2988.633	50.22	74.0	23.78	Peak	346.00	100	Vertical	Pass
2**	2988.633	37.91	54.0	16.09	AV	346.00	100	Vertical	Pass
3	4823.076	49.12	74.0	24.88	Peak	330.00	200	Vertical	Pass
3**	4823.076	43.90	54.0	10.10	AV	330.00	200	Vertical	Pass
4	7964.628	55.28	74.0	18.72	Peak	106.00	200	Vertical	Pass
4**	7964.628	42.34	54.0	11.66	AV	106.00	200	Vertical	Pass
5	12444.472	51.32	74.0	22.68	Peak	259.00	300	Vertical	Pass
5**	12444.472	45.89	54.0	8.11	AV	259.00	300	Vertical	Pass
6	17454.793	56.77	74.0	17.23	Peak	91.00	300	Vertical	Pass
6**	17454.793	44.70	54.0	9.30	AV	91.00	300	Vertical	Pass

GFSK (2Mbps) LOW CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1334.211	44.47	74.0	29.53	Peak	344.00	100	Horizontal	Pass
1**	1334.211	27.04	54.0	26.96	AV	344.00	100	Horizontal	Pass
2	2972.046	53.13	74.0	20.87	Peak	136.00	300	Horizontal	Pass
2**	2972.046	39.75	54.0	14.25	AV	136.00	300	Horizontal	Pass
3	4910.569	51.85	74.0	22.15	Peak	212.00	200	Horizontal	Pass
3**	4910.569	41.51	54.0	12.49	AV	212.00	200	Horizontal	Pass
4	7626.191	54.86	74.0	19.14	Peak	268.00	400	Horizontal	Pass
4**	7626.191	40.29	54.0	13.71	AV	268.00	400	Horizontal	Pass
5	12472.789	49.87	74.0	24.13	Peak	137.00	100	Horizontal	Pass
5**	12472.789	45.22	54.0	8.78	AV	137.00	100	Horizontal	Pass
6	16853.702	57.73	74.0	16.27	Peak	222.00	300	Horizontal	Pass
6**	16853.702	45.45	54.0	8.55	AV	222.00	300	Horizontal	Pass

GFSK (2Mbps) LOW CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1465.610	44.12	74.0	29.88	Peak	71.00	200	Vertical	Pass
1**	1465.610	29.40	54.0	24.60	AV	71.00	200	Vertical	Pass
2	2989.199	52.51	74.0	21.49	Peak	79.00	200	Vertical	Pass
2**	2989.199	37.95	54.0	16.05	AV	79.00	200	Vertical	Pass
3	4823.917	52.69	74.0	21.31	Peak	265.00	200	Vertical	Pass
3**	4823.917	40.06	54.0	13.94	AV	265.00	200	Vertical	Pass
4	7965.444	54.55	74.0	19.45	Peak	17.00	100	Vertical	Pass
4**	7965.444	45.28	54.0	8.72	AV	17.00	100	Vertical	Pass
5	12442.588	49.31	74.0	24.69	Peak	344.00	300	Vertical	Pass
5**	12442.588	45.82	54.0	8.18	AV	344.00	300	Vertical	Pass
6	17457.740	57.32	74.0	16.68	Peak	123.00	100	Vertical	Pass
6**	17457.740	44.42	54.0	9.58	AV	123.00	100	Vertical	Pass

GFSK (2Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1338.512	44.93	74.0	29.07	Peak	84.00	200	Horizontal	Pass
1**	1338.512	30.73	54.0	23.27	AV	84.00	200	Horizontal	Pass
2	2976.763	52.62	74.0	21.38	Peak	249.00	400	Horizontal	Pass
2**	2976.763	38.85	54.0	15.15	AV	249.00	400	Horizontal	Pass
3	4916.903	50.96	74.0	23.04	Peak	46.00	200	Horizontal	Pass
3**	4916.903	45.21	54.0	8.79	AV	46.00	200	Horizontal	Pass
4	7624.704	52.65	74.0	21.35	Peak	290.00	400	Horizontal	Pass
4**	7624.704	38.05	54.0	15.95	AV	290.00	400	Horizontal	Pass
5	12473.646	55.29	74.0	18.71	Peak	18.00	200	Horizontal	Pass
5**	12473.646	42.33	54.0	11.67	AV	18.00	200	Horizontal	Pass
6	16857.681	52.67	74.0	21.33	Peak	99.00	300	Horizontal	Pass
6**	16857.681	42.82	54.0	11.18	AV	99.00	300	Horizontal	Pass

GFSK (2Mbps) MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1468.887	40.77	74.0	33.23	Peak	122.00	400	Vertical	Pass
1**	1468.887	30.09	54.0	23.91	AV	122.00	400	Vertical	Pass
2	2990.984	50.76	74.0	23.24	Peak	289.00	400	Vertical	Pass
2**	2990.984	39.62	54.0	14.38	AV	289.00	400	Vertical	Pass
3	4820.613	51.67	74.0	22.33	Peak	337.00	200	Vertical	Pass
3**	4820.613	43.53	54.0	10.47	AV	337.00	200	Vertical	Pass
4	7970.403	56.11	74.0	17.89	Peak	238.00	100	Vertical	Pass
4**	7970.403	45.22	54.0	8.78	AV	238.00	100	Vertical	Pass
5	12446.181	48.29	74.0	25.71	Peak	135.00	200	Vertical	Pass
5**	12446.181	41.25	54.0	12.75	AV	135.00	200	Vertical	Pass
6	17457.409	55.22	74.0	18.78	Peak	162.00	100	Vertical	Pass
6**	17457.409	43.15	54.0	10.85	AV	162.00	100	Vertical	Pass

GFSK (2Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1338.000	41.23	74.0	32.77	Peak	326.00	300	Horizontal	Pass
1**	1338.000	29.65	54.0	24.35	AV	326.00	300	Horizontal	Pass
2	2974.736	47.73	74.0	26.27	Peak	25.00	400	Horizontal	Pass
2**	2974.736	37.90	54.0	16.10	AV	25.00	400	Horizontal	Pass
3	4910.645	48.66	74.0	25.34	Peak	335.00	200	Horizontal	Pass
3**	4910.645	45.12	54.0	8.88	AV	335.00	200	Horizontal	Pass
4	7624.263	56.79	74.0	17.21	Peak	2.00	400	Horizontal	Pass
4**	7624.263	42.26	54.0	11.74	AV	2.00	400	Horizontal	Pass
5	12470.801	53.13	74.0	20.87	Peak	191.00	200	Horizontal	Pass
5**	12470.801	45.15	54.0	8.85	AV	191.00	200	Horizontal	Pass
6	16856.930	57.90	74.0	16.10	Peak	312.00	100	Horizontal	Pass
6**	16856.930	43.41	54.0	10.59	AV	312.00	100	Horizontal	Pass

GFSK (2Mbps) HIGH CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1462.364	43.82	74.0	30.18	Peak	283.00	300	Vertical	Pass
1**	1462.364	29.09	54.0	24.91	AV	283.00	300	Vertical	Pass
2	2990.342	48.84	74.0	25.16	Peak	220.00	400	Vertical	Pass
2**	2990.342	41.76	54.0	12.24	AV	220.00	400	Vertical	Pass
3	4824.314	53.43	74.0	20.57	Peak	88.00	200	Vertical	Pass
3**	4824.314	38.49	54.0	15.51	AV	88.00	200	Vertical	Pass
4	7967.545	55.19	74.0	18.81	Peak	316.00	300	Vertical	Pass
4**	7967.545	43.82	54.0	10.18	AV	316.00	300	Vertical	Pass
5	12446.606	52.96	74.0	21.04	Peak	228.00	100	Vertical	Pass
5**	12446.606	46.01	54.0	7.99	AV	228.00	100	Vertical	Pass
6	17460.215	56.29	74.0	17.71	Peak	176.00	300	Vertical	Pass
6**	17460.215	43.75	54.0	10.25	AV	176.00	300	Vertical	Pass

A.7 Band Edge (Restricted-band band-edge)

Note ¹: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Note ²: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.

Note ³: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note ⁴: The Level (dBuV/m) has been corrected by factor.

Test Data

GFSK (1Mbps) LOW CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2320.324	55.85	74.0	18.15	Peak	115.00	300	Horizontal	Pass
1**	2320.324	44.72	54.0	9.28	AV	115.00	300	Horizontal	Pass
2	2390.000	53.11	74.0	20.89	Peak	271.00	100	Horizontal	Pass
2**	2390.000	45.2	54.0	8.80	AV	271.00	100	Horizontal	Pass

GFSK (1Mbps) HIGH CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	53.91	74.0	20.09	Peak	265.00	300	Horizontal	Pass
1**	2483.500	42.99	54.0	11.01	AV	265.00	300	Horizontal	Pass
2	2493.566	58.34	74.0	15.66	Peak	127.00	200	Horizontal	Pass
2**	2493.566	42.76	54.0	11.24	AV	127.00	200	Horizontal	Pass

GFSK (2Mbps) LOW CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2321.359	57.06	74.0	16.94	Peak	119.00	100	Horizontal	Pass
1**	2321.359	44.74	54.0	9.26	AV	119.00	100	Horizontal	Pass
2	2390.000	53.39	74.0	20.61	Peak	81.00	200	Horizontal	Pass
2**	2390.000	46.53	54.0	7.47	AV	81.00	200	Horizontal	Pass

GFSK (2Mbps) HIGH CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	55.09	74.0	18.91	Peak	161.00	100	Horizontal	Pass
1**	2483.500	45.14	54.0	8.86	AV	161.00	100	Horizontal	Pass
2	2493.636	55.61	74.0	18.39	Peak	90.00	100	Horizontal	Pass
2**	2493.636	42.77	54.0	11.23	AV	90.00	100	Horizontal	Pass

A.8 Power Spectral Density (PSD)

Test Data

GFSK (1Mbps)			
Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Low Channel	-8.09	8	Pass
Middle Channel	-7.34	8	Pass
High Channel	-7.35	8	Pass


GFSK (2Mbps)			
Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Low Channel	-9.40	8	Pass
Middle Channel	-8.24	8	Pass
High Channel	-8.27	8	Pass

Test Plots**GFSK (1Mbps) LOW CHANNEL****GFSK (1Mbps) MIDDLE CHANNEL****GFSK (1Mbps) HIGH CHANNEL**

GFSK (2Mbps) LOW CHANNEL



GFSK (2Mbps) MIDDLE CHANNEL



GFSK (2Mbps) HIGH CHANNEL



ANNEX B TEST SETUP PHOTOS

Please refer the document "BL-SZ2540813-AR.PDF".

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document "BL-SZ2540813-AW.PDF".

ANNEX D EUT INTERNAL PHOTOS

Please refer the document "BL-SZ2540813-AI.PDF".

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--