

FCC RADIO TEST REPORT

FCC ID: 2AWY6-ELMT7668BUNT

Product: WiFi Module

Trade Mark: CDTECH

Model No.: EL.MT7668BUN-WFT

Family Model: N/A

Report No.: S22051301104004

Issue Date: Jun 25, 2022

Prepared for

EXPRESS LUCK INDUSTRIAL (SHENZHEN) LIMITED

Floor1,Workshop1, NO.88, SOUTH BAOTONG ROAD,XIKENG COMMUNITY,
YUANSAN STREET, LONGGANG DISTRICT, Shenzhen, China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park Sanwei, Xixiang, Bao'an District
Shenzhen, Guangdong, China

Tel:400-800-6106,0755-2320 0050 / 2320 0090

Website:<http://www.ntek.org.cn>

TEST RESULT CERTIFICATION

Applicant's name : EXPRESS LUCK INDUSTRIAL (SHENZHEN) LIMITED
Address : Floor1,Workshop1, NO.88, SOUTH BAOTONG ROAD,XIKENG COMMUNITY, YUANSAN STREET, LONGGANG DISTRICT, Shenzhen, China
Manufacturer's Name..... : EXPRESS LUCK INDUSTRIAL (SHENZHEN) LIMITED
Address : Floor1,Workshop1, NO.88, SOUTH BAOTONG ROAD,XIKENG COMMUNITY, YUANSAN STREET, LONGGANG DISTRICT, Shenzhen, China

Product description

Product name..... : WiFi Module
Model and/or type reference : EL.MT7668BUN-WFT
Family Model..... : N/A

Standards..... : FCC Part15.407

Test procedure ANSI C63.10-2013
 KDB 789033 D02 General UNII Test Procedures New Rules v02r01
 FCC KDB 662911 D01 Multiple Transmitter Output v02r01

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

Test Sample Number S220513011004


Date of Test

Date (s) of performance of tests May 13. 2022 ~ Jun 25. 2022

Date of Issue Jun 25. 2022

Test Result..... **Pass**

Testing Engineer :



 (Mukzi Lee)

Authorized Signatory :



 (Alex Li)

Table of Contents

	Page
1. SUMMARY OF TEST RESULTS	7
1.1 FACILITIES AND ACCREDITATIONS	8
1.2 MEASUREMENT UNCERTAINTY	8
2. GENERAL INFORMATION	9
2.1 GENERAL DESCRIPTION OF EUT	9
2.2 DESCRIPTION OF TEST MODES	11
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	13
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	14
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	15
3. EMC EMISSION TEST	17
3.1 CONDUCTED EMISSION MEASUREMENT	17
3.1.1 APPLICABLE STANDARD	17
3.1.2 CONFORMANCE LIMIT	17
3.1.3 TEST CONFIGURATION	17
3.1.4 TEST PROCEDURE	17
3.2 RADIATED EMISSION MEASUREMENT	19
3.2.1 APPLICABLE STANDARD	19
3.2.2 CONFORMANCE LIMIT	19
3.2.3 MEASURING INSTRUMENTS	19
3.2.4 TEST CONFIGURATION	20
3.2.5 TEST PROCEDURE	21
3.2.6 TEST RESULTS (9KHZ – 30 MHZ)	22
3.2.7 TEST RESULTS (30MHZ – 1GHZ)	23
3.2.8 TEST RESULTS (1GHZ-18GHZ)	27
3.2.10 TEST ESULTS (18GHZ-40GHZ)	29
4. POWER SPECTRAL DENSITY TEST	34
4.1 APPLIED PROCEDURES / LIMIT	34
4.2 TEST PROCEDURE	35
4.3 DEVIATION FROM STANDARD	35
4.4 TEST SETUP	35
4.5 EUT OPERATION CONDITIONS	35
4.6 TEST RESULTS	36
5. 26DB & 99% EMISSION BANDWIDTH	37
5.1 APPLIED PROCEDURES / LIMIT	37
5.2 TEST PROCEDURE	37
5.3 EUT OPERATION CONDITIONS	38
5.4 TEST RESULTS	38

Table of Contents

	Page
6. MINIMUM 6 DB BANDWIDTH	39
6.1 APPLIED PROCEDURES / LIMIT	39
6.2 TEST PROCEDURE	39
6.3 DEVIATION FROM STANDARD	39
6.4 TEST SETUP	39
6.5 EUT OPERATION CONDITIONS	39
6.6 TEST RESULTS	40
7. MAXIMUM CONDUCTED OUTPUT POWER	41
7.1 PPLIED PROCEDURES / LIMIT	41
7.5 TEST RESULTS	43
8. OUT OF BAND EMISSIONS	44
8.1 APPLICABLE STANDARD	44
8.2 TEST PROCEDURE	44
8.3 DEVIATION FROM STANDARD	44
8.4 TEST SETUP	44
8.5 EUT OPERATION CONDITIONS	44
8.6 TEST RESULTS	45
9. FREQUENCY STABILITY MEASUREMENT	46
9.1 LIMIT	46
9.2 TEST PROCEDURES	46
9.3 TEST SETUP LAYOUT	46
9.4 EUT OPERATION DURING TEST	46
9.5 TEST RESULTS	47
10. ANTENNA REQUIREMENT	53
10.1 STANDARD REQUIREMENT	53
10.2 EUT ANTENNA	53
11. TEST RESULT	54
WIFI 5.2G	54
11.1 DUTY CYCLE	54
11.2 MAXIMUM CONDUCTED OUTPUT POWER	69
11.3 OCCUPIED CHANNEL BANDWIDTH	70
11.4 MAXIMUM POWER SPECTRAL DENSITY LEVEL	99
11.5 BAND EDGE	114
11.6 CONDUCTED RF SPURIOUS EMISSION	127
WIFI 5.2G MIMO	142
11.7 MAXIMUM CONDUCTED OUTPUT POWER	142
11.8 MAXIMUM POWER SPECTRAL DENSITY LEVEL	143

Table of Contents

	Page
11.9 BAND EDGE	144
11.10 CONDUCTED RF SPURIOUS EMISSION	150
WIFI 5.8G	156
11.1 DUTY CYCLE	156
11.2 MAXIMUM CONDUCTED OUTPUT POWER	171
11.3 -6DB EMISSION BANDWIDTH	172
11.4 OCCUPIED CHANNEL BANDWIDTH	187
11.5 MAXIMUM POWER SPECTRAL DENSITY LEVEL	216
11.6 BAND EDGE	231
11.7 CONDUCTED RF SPURIOUS EMISSION	244
WIFI 5.8G MIMO	259
11.8 MAXIMUM CONDUCTED OUTPUT POWER	259
11.9 MAXIMUM POWER SPECTRAL DENSITY LEVEL	260
11.10 BAND EDGE	261
11.11 CONDUCTED RF SPURIOUS EMISSION	267

Revision History

[illegible]

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.407) , Subpart E			
Standard Section	Test Item	Judgment	Remark
15.207	AC Power Line Conducted Emissions	N/A	
15.209(a), 15.407 (b)(1) 15.407 (b)(4) 15.407 (b)(9) 15.407 (b)(10)	Spurious Radiated Emissions	PASS	
15.407 (a)(1) 15.407 (a)(3)	26 dB and 99% Emission Bandwidth	PASS	
15.407(e)	Minimum 6 dB bandwidth	PASS	
15.407 (a)(1) 15.407 (a)(3)	Maximum Conducted Output Power	PASS	
15.407(b)(1) 15.407(b)(4)	Band Edge	PASS	
15.407 (a)(1) 15.407 (a)(3)	Power Spectral Density	PASS	
15.407(b)	Spurious Emissions at Antenna Terminals	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

1.1 FACILITIES AND ACCREDITATIONS

FACILITIES

All measurement facilities used to collect the measurement data are located at
1/F, Building E, Fenda Science Park Sanwei, Xixiang, Bao'an District
Shenzhen, Guangdong, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

CNAS-Lab. : The Certificate Registration Number is L5516.

IC-Registration : The Certificate Registration Number is 9270A.
CAB identifier:CN0074

FCC- Accredited : Test Firm Registration Number: 463705.
Designation Number: CN1184

A2LA-Lab. : The Certificate Registration Number is 4298.01

Name of Firm : Shenzhen NTEK Testing Technology Co., Ltd.

Site Location : 1/F, Building E, Fenda Science Park Sanwei, Xixiang, Bao'an District
Shenzhen, Guangdong, China

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.80\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(9KHz~30MHz)	$\pm 6\text{dB}$
5	All emissions, radiated(30MHz~1GHz)	$\pm 2.64\text{dB}$
6	All emissions, radiated(1GHz~6GHz)	$\pm 2.40\text{dB}$
7	All emissions, radiated(> 6GHz)	$\pm 2.52\text{dB}$
8	Temperature	$\pm 0.5^{\circ}\text{C}$
9	Humidity	$\pm 2\%$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	WiFi Module	
Trade Mark	CDTECH	
Model Name	EL.MT7668BUN-WFT	
Family Model	N/A	
Model Difference	N/A	
FCC ID	2AWY6-ELMT7668BUNT	
Product Description	Mode Supported	☒ 802.11a ☒ 802.11n(HT20) ☒ 802.11n(HT40) ☒ 802.11ac(VHT20) ☒ 802.11ac(VHT40) ☒ 802.11ac(VHT80)
	Data Rate	802.11a: 6,9,12,18,24,36,48,54Mbps; 802.11n(HT20/HT40):MCS0-MCS15; 802.11ac(VHT20): NSS1, MCS0-MCS8 802.11ac(VHT40/VHT80):NSS1, MCS0-MCS9
	Modulation	OFDM with BPSK/QPSK/16QAM/64QAM/256QAM
	Operating Frequency Range	☒ U-NII-1: 5150 MHz ~5250MHz ☐ U-NII-2A: 5250MHz~5350MHz ☐ U-NII-2C: 5470MHz~5725MHz ☒ U-NII-3: 5725 MHz ~5850 MHz
	Function:	☐ Outdoor AP ☐ Indoor AP ☐ Fixed P2P ☒ Client
	Smart system	☒ SISO for 802.11a/n/ac ☒ MIMO for 802.11n/ac
	Antenna Type	PIFA Antenna
	Antenna Gain	Antenna 1: 3.25 dBi; Antenna 2: 3.55dBi
	Based on the application, features, or specification exhibited in User's Manual, More details of EUT technical specification, please refer to the User's Manual.	
Adapter	N/A	
Battery	N/A	
Power Rating	DC 3.3V	
Connecting I/O Port(s)	Please refer to the User's Manual	
Hardware Version	CDW-F97668U-01-V0	
Software Version	CDW-F97668U-01-MT7668U_Efuse_V0_20220425	

Note: Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
2. Frequency and Channel list for 802.11a/n/ac(20MHz) band I (5180-5240MHz):

802.11a/n/ac(20MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220	-	-	-	-
40	5200	48	5240	-	-	-	-

Frequency and Channel list for 802.11n/ac(40MHz) band I (5190-5230MHz):

802.11n/ac(40MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	-	-	-	-	-	-
46	5230	-	-	-	-	-	-

Frequency and Channel list for 802.11ac(80MHz) band I (5210MHz):

802.11ac(80MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
42	5210	-	-	-	-	-	-

Frequency and Channel list for 802.11a/n/ac(20 MHz) band IV (5745-5825MHz):

802.11a/n/ac(20 MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	153	5765	157	5785	161	5805
165	5825	-	-	-	-	-	-

Frequency and Channel list for 802.11n/ac(40MHz) band IV (5755-5795MHz):

802.11n/ac(40MHz) Carrier Frequency Channel					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
151	5755	159	5795	-	-

Frequency and Channel list for 802.11ac(80MHz) band IV (5775MHz):

802.11ac(80MHz) Carrier Frequency Channel					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
155	5775	-	-	-	-

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	Normal Link Mode
Mode 2	802.11a/n/ac20 CH36/CH40/CH48/CH149/CH157/CH165
Mode 3	802.11n40/ac40 CH38/CH46CH151/CH159
Mode 4	802.11ac80 CH42/CH155

For Radiated Emission	
Final Test Mode	Description
Mode 1	Normal Link Mode
Mode 2	802.11a/n/ac20 CH36/CH40/CH48/CH149/CH157/CH165
Mode 3	802.11n40/ac40 CH38/CH46CH151/CH159
Mode 4	802.11ac80 CH42/CH155

For AC Conducted Emission	
Final Test Mode	Description
N/A	N/A

For Conducted Test Cases	
Final Test Mode	Description
Mode 1	Normal Link Mode
Mode 2	802.11a/n/ac20 CH36/CH40/CH48/CH149/CH157/CH165
Mode 3	802.11n40/ac40 CH38/CH46CH151/CH159
Mode 4	802.11ac80 CH42/CH155

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported

This EUT has two antennas, and different modes support different transmit mode what describe as following form:

Mode	Tx / Rx
802.11a / n(20MHz,40MHz) / ac(20MHz,40MHz,80MHz)	1TX, 1RX
802.11n(20MHz,40MHz) / ac(20MHz,40MHz,80MHz)	2TX, 2RX

d) *Unequal antenna gains, with equal transmit powers.* For antenna gains given by $G_1, G_2, \dots, G_N$ dBi


(i) If transmit signals are *correlated*, then

Directional gain = $10 \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{\text{ANT}}]$ dBi [Note the “20”s in the denominator of each exponent and the square of the sum of terms; the object is to combine the signal levels coherently.]

Note: Directional gain = $10 \log[(10^{3.25/20} + 10^{3.55/20})^2 / 2] = 6.41$ dBi

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

For Radiated Test Cases



Note: 1. The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
E-1	WiFi Module	EL.MT7668BUN-WFT	N/A	EUT
E-2	Laptop	N/A	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	USB Cable	NO	NO	0.5m

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) During the battery power test, the battery is fully charged.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation& Conducted Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2022.04.01	2023.03.31	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2022.04.01	2023.03.31	1 year
3	Spectrum Analyzer	R&S	FSV40	101417	2022.04.01	2023.03.31	1 year
4	Test Receiver	R&S	ESPI7	101318	2022.04.01	2023.03.31	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2022.03.30	2023.03.29	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2020.05.11	2023.05.10	3 year
7	Horn Antenna	EM	EM-AH-10180	2011071402	2022.03.31	2023.03.30	1 year
8	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	803	2022.03.31	2023.03.30	1 year
9	Amplifier	EMC	EMC051835SE	980246	2021.07.01	2022.06.30	1 year
10	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	055	2021.11.07	2022.11.06	1 year
11	Power Meter	DARE	RPR3006W	15I00041SN084	2021.11.07	2022.11.06	1 year
12	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2019.08.06	2022.08.05	3 year
13	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2019.08.06	2022.08.05	3 year
14	High Test Cable(1G-40G Hz)	N/A	R-03	N/A	2019.06.28	2022.06.27	3 year
15	Filter	TRILTHIC	2400MHz	29	2021.11.07	2022.11.06	1 year
16	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

Note:

We will use the temporary antenna connector (soldered on the PCB board) When conducted test
And this temporary antenna connector is listed within the instrument list

AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2022.04.06	2023.04.05	1 year
2	LISN	R&S	ENV216	101313	2022.04.06	2023.04.05	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2022.04.06	2023.04.05	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2020.05.11	2023.05.10	3 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2020.05.11	2023.05.10	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2020.05.11	2023.05.10	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2020.05.11	2023.05.10	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Test Cable& Aux Equipment which is scheduled for calibration every 3 years.

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 APPLICABLE STANDARD


According to FCC Part 15.207(a)

3.1.2 CONFORMANCE LIMIT

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. *Decreases with the logarithm of the frequency
 2. The lower limit shall apply at the transition frequencies
 3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3.1.3 TEST CONFIGURATION



3.1.4 TEST PROCEDURE

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.

EUT :	WiFi Module	Model Name. :	EL.MT7668BUN-WFT
Temperature :	23.5 °C	Relative Humidity :	45%
Pressure :	1010hPa	Phase :	N/A
Test Voltage :	N/A	Test Mode :	N/A

Note: not applicable

3.2 RADIATED EMISSION MEASUREMENT

3.2.1 APPLICABLE STANDARD

According to FCC Part 15.407(b)(9) and 15.209

3.2.2 CONFORMANCE LIMIT

According to FCC Part 15.407(b) (9): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300
0.490~1.705	24000/F(KHz)	20 log (uV/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Remark :1. Emission level in dBuV/m=20 log (uV/m)

2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

3. For Frequency 9kHz~30MHz:

Distance extrapolation factor =40log(Specific distance/ test distance)(dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor.

For Frequency above 30MHz:

Distance extrapolation factor =20log(Specific distance/ test distance)(dB);


Limit line=Specific limits(dBuV) + distance extrapolation factor.

3.2.3 MEASURING INSTRUMENTS


The Measuring equipment is listed in the section 6.3 of this test report.

3.2.4 TEST CONFIGURATION


(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



3.2.5 TEST PROCEDURE

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.

Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW} [kHz])$. , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

3.2.6 TEST RESULTS (9KHZ – 30 MHZ)

EUT :	WiFi Module	Model Name :	EL.MT7668BUN-WFT
Temperature :	26 °C	Relative Humidity :	54%
Pressure:	1010 hPa	Test Voltage :	DC 3.3V
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	N/A
--	--	--	--	N/A

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


3.2.7 TEST RESULTS (30MHZ – 1GHZ)

EUT :	WiFi Module	Model Name :	EL.MT7668BUN-WFT
Temperature :	25.2	Relative Humidity :	55%
Pressure :	1010 hPa	Test Voltage :	DC 3.3V
Test Mode :	TX(5.2G)- 802.11n20 MIMO Mode(Low CH)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	91.8162	11.69	16.13	27.82	43.50	-15.68	QP
V	135.0319	9.49	18.40	27.89	43.50	-15.61	QP
V	351.7078	14.16	22.93	37.09	46.00	-8.91	QP
V	890.7278	8.55	32.22	40.77	46.00	-5.23	QP
V	47.8260	19.84	15.87	35.71	40.00	-4.29	QP
V	30.8535	5.83	24.36	30.19	40.00	-9.81	QP

Remark:


Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	30.6378	5.31	24.59	29.90	40.00	-10.10	QP
H	97.1148	6.75	16.40	23.15	43.50	-20.35	QP
H	138.3873	6.16	18.89	25.05	43.50	-18.45	QP
H	350.4768	15.71	22.95	38.66	46.00	-7.34	QP
H	229.2931	11.80	17.77	29.57	46.00	-16.43	QP
H	962.1622	7.15	33.17	40.32	54.00	-13.68	QP

Remark:

Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit




EUT :	WiFi Module	Model Name :	EL.MT7668BUN-WFT
Temperature :	25.2	Relative Humidity :	55%
Pressure :	1010 hPa	Test Voltage :	DC 3.3V
Test Mode :	TX(5.8G) - 802.11n20 MIMO Mode(Low CH)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	31.5094	6.95	23.65	30.60	40.00	-9.40	QP
V	47.8260	19.39	15.87	35.26	40.00	-4.74	QP
V	91.8162	12.13	16.13	28.26	43.50	-15.24	QP
V	135.0319	9.49	18.40	27.89	43.50	-15.61	QP
V	329.0389	13.11	22.09	35.20	46.00	-10.80	QP
V	965.5421	7.15	33.25	40.40	54.00	-13.60	QP

Remark:


Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	30.7454	5.44	24.47	29.91	40.00	-10.09	QP
H	47.8260	8.45	15.87	24.32	40.00	-15.68	QP
H	135.0319	7.61	18.40	26.01	43.50	-17.49	QP
H	345.5951	15.95	22.72	38.67	46.00	-7.33	QP
H	229.2931	12.36	17.77	30.13	46.00	-15.87	QP
H	900.1473	7.38	32.42	39.80	46.00	-6.20	QP

Remark:

Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit



Note: All modes have been tested, just the the worst mode has been recorded in the report.

3.2.8 TEST RESULTS (1GHz-18GHz)

EUT :	WiFi Module	Model Name. :	EL.MT7668BUN-WFT
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.3V
Test Mode :	TX(5.2G) - 802.11n20 MIMO mode		

Polar	Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	dB/m	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G									
Vertical	3694.51	61.88	5.94	35.40	44.00	59.22	74.00	-14.78	Pk
Vertical	3694.33	42.49	5.94	35.40	44.00	39.83	54.00	-14.17	AV
Vertical	10360.69	58.70	8.46	39.75	44.50	62.41	68.20	-5.79	Pk
Vertical	15540.46	61.30	10.12	38.80	44.10	66.12	74.00	-7.88	Pk
Vertical	15540.74	39.95	10.12	38.80	42.70	46.17	54.00	-7.83	AV
Horizontal	3713.37	63.74	5.94	35.18	44.00	60.86	74.00	-13.14	Pk
Horizontal	3713.23	44.10	5.94	35.18	44.00	41.22	54.00	-12.78	AV
Horizontal	10360.72	59.08	8.46	38.71	44.50	61.75	68.20	-6.45	Pk
Horizontal	15540.92	57.79	10.12	38.38	44.10	62.19	74.00	-11.81	Pk
Horizontal	15540.82	41.24	10.12	38.38	44.10	45.64	54.00	-8.36	AV
Middle Channel (5200 MHz)-Above 1G									
Vertical	3624.70	58.89	6.48	36.35	44.05	57.67	74.00	-16.33	Pk
Vertical	3624.52	43.36	6.48	36.35	44.05	42.14	54.00	-11.86	AV
Vertical	10400.36	60.13	8.47	37.88	44.51	61.97	68.20	-6.23	Pk
Vertical	15600.66	60.41	10.12	38.80	44.10	65.23	74.00	-8.77	Pk
Vertical	15600.64	40.00	10.12	38.80	42.70	46.22	54.00	-7.78	AV
Horizontal	4202.51	58.74	6.48	36.37	44.05	57.54	74.00	-16.46	Pk
Horizontal	4202.54	45.10	6.48	36.37	44.05	43.90	54.00	-10.10	AV
Horizontal	10400.64	61.67	8.47	38.64	44.50	64.28	68.20	-3.92	Pk
Horizontal	15601.08	60.23	10.12	38.38	44.10	64.63	74.00	-9.37	Pk
Horizontal	15600.94	41.69	10.12	38.38	44.10	46.09	54.00	-7.91	AV
High Channel (5240 MHz)-Above 1G									
Vertical	4597.98	64.09	7.10	37.24	43.50	64.93	74.00	-9.07	Pk
Vertical	4598.27	43.76	7.10	37.24	43.50	44.60	54.00	-9.40	AV
Vertical	10480.62	60.50	8.46	37.68	44.50	62.14	68.20	-6.06	Pk
Vertical	15720.41	61.95	10.12	38.80	44.10	66.77	74.00	-7.23	Pk
Vertical	15720.48	40.59	10.12	38.80	42.70	46.81	54.00	-7.19	AV
Horizontal	4589.74	61.68	7.10	37.24	43.50	62.52	74.00	-11.48	Pk
Horizontal	4589.50	41.70	7.10	37.24	43.50	42.54	54.00	-11.46	AV
Horizontal	10480.84	62.45	8.46	38.57	44.50	64.98	68.20	-3.22	Pk
Horizontal	15720.58	60.18	10.12	38.38	44.10	64.58	74.00	-9.42	Pk
Horizontal	15720.70	43.25	10.12	38.38	44.10	47.65	54.00	-6.35	AV

Note: "802.11n20 MIMO" mode is the worst mode. PK value is lower than the Average value limit, So average didn't record.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

EUT :	WiFi Module	Model Name. :	EL.MT7668BUN-WFT
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.3V
Test Mode :	TX (5.8G) -- 802.11n20 MIMO		

Polar	Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	dB/m	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G									
Vertical	5123.01	64.19	5.94	35.40	44.00	61.53	74.00	-12.47	Pk
Vertical	5122.91	45.82	5.94	35.40	44.00	43.16	54.00	-10.84	AV
Vertical	11490.86	60.31	8.46	39.75	44.50	64.02	74.00	-9.98	Pk
Vertical	11491.12	43.55	8.46	39.75	44.50	47.26	54.00	-6.74	AV
Vertical	17235.91	52.41	10.12	38.80	44.10	57.23	68.20	-10.97	Pk
Horizontal	5167.15	59.74	5.94	35.18	44.00	56.86	68.20	-11.34	Pk
Horizontal	11490.87	59.21	8.46	38.71	44.50	61.88	74.00	-12.12	Pk
Horizontal	11490.72	42.86	8.46	38.71	44.50	45.53	54.00	-8.47	AV
Horizontal	17235.92	51.60	10.12	38.38	44.10	56.00	68.20	-12.20	Pk
middle Channel (5785 MHz)-Above 1G									
Vertical	5433.71	62.85	6.48	36.35	44.05	61.63	74.00	-12.37	Pk
Vertical	5433.68	43.34	6.48	36.35	44.05	42.12	54.00	-11.88	AV
Vertical	11570.92	60.86	8.47	37.88	44.51	62.70	74.00	-11.30	Pk
Vertical	11570.94	43.25	8.47	37.88	44.51	45.09	54.00	-8.91	AV
Vertical	17356.19	56.20	10.12	38.80	44.10	61.02	68.20	-7.18	Pk
Horizontal	4866.94	60.19	6.48	36.37	44.05	58.99	74.00	-15.01	Pk
Horizontal	4866.90	43.22	6.48	36.37	44.05	42.02	54.00	-11.98	AV
Horizontal	11570.85	63.21	8.47	38.64	44.50	65.82	74.00	-8.18	Pk
Horizontal	11570.80	44.40	8.47	38.64	44.50	47.01	54.00	-6.99	AV
Horizontal	17355.92	56.86	10.12	38.38	44.10	61.26	68.20	-6.94	Pk
High Channel (5825 MHz)-Above 1G									
Vertical	5243.56	62.01	7.10	37.24	43.50	62.85	68.20	-5.35	Pk
Vertical	11651.65	61.71	8.46	37.68	44.50	63.35	74.00	-10.65	Pk
Vertical	11651.72	43.20	8.46	37.68	44.50	44.84	54.00	-9.16	AV
Vertical	17473.12	60.56	10.12	38.80	44.10	65.38	68.20	-2.82	Pk
Vertical	17472.85	60.75	10.12	38.80	44.10	65.57	68.20	-2.63	Pk
Horizontal	5284.50	60.29	7.10	37.24	43.50	61.13	68.20	-7.07	Pk
Horizontal	11651.81	60.40	8.46	38.57	44.50	62.93	74.00	-11.07	Pk
Horizontal	11652.01	41.91	8.46	38.57	44.50	44.44	54.00	-9.56	AV
Horizontal	17473.81	58.41	10.12	38.38	44.10	62.81	68.20	-5.39	Pk
Horizontal	17473.95	58.38	10.12	38.38	44.10	62.78	68.20	-5.42	Pk

Note:"802.11n20 MIMO" mode is the worst mode. PK value is lower than the Average value limit, So average didn't record.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value

has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


3.2.10 TEST RESULTS (18GHz-40GHz)

EUT :	WiFi Module	Model Name. :	EL.MT7668BUN-WFT
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.3V
Test Mode :	TX (5.2G)-802.11n20 MIMO 5180MHz~5240MHz; TX (5.8G)-802.11ac20 MIMO 5745MHz~5825MHz		

All the modulation modes have been tested, and the worst result was report as below:


Low Channel (5180 MHz)-Above 1G

Horizontal



Frequency	Meter Reading	Cable loss	Antenna Factor	Preamplifier	Emission Level	Limits	Margin	Remark
39768.9	39.01	20.09	44.07	43.48	59.69	68.2	8.51	Peak
39766.78	27.51	20.09	44.04	43.48	48.16	54	5.84	AVG


Vertical



Frequency	Meter Reading	Cable loss	Antenna Factor	Preamplifier	Emission Level	Limits	Margin	Remark
39769.416	36.14	20.09	44.07	43.48	56.82	68.2	11.38	Peak
39769.195	27.34	20.09	44.04	43.48	47.99	54	6.01	AVG


High Channel (5240 MHz)-Above 1G

Horizontal



Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Remark
35627.96	41.09	19.11	42.73	44.61	58.32	68.2	9.88	Peak
35596.716	31.36	19.11	42.73	44.61	48.59	54	5.41	AVG


Vertical



Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Remark
39769.236	37.25	20.09	44.07	43.48	57.93	68.2	10.27	Peak
39769.356	25.56	20.09	44.04	43.48	46.21	54	7.79	AVG


Low Channel (5745 MHz)-Above 1G

Horizontal



Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Remark
39669.634	38.43	20.09	44.16	43.48	59.2	68.2	9	Peak
39669.624	29.61	20.09	44.16	43.48	50.38	54	3.62	AVG


Vertical



Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Remark
39731.122	37.46	20.06	44.07	43.21	58.38	68.2	9.82	Peak
39731.092	28.61	20.06	44.07	43.21	49.53	54	4.47	AVG


High Channel (5825 MHz)-Above 1G

Horizontal



Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Remark
35628.154	39.67	19.11	42.63	43.48	57.93	68.2	10.27	Peak
35635.708	30.08	19.12	42.63	43.48	48.35	54	5.65	AVG

Vertical



Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Remark
39821.723	38.24	20.1	44.1	43.22	59.22	68.2	8.98	Peak
39821.713	29.45	20.1	44.1	43.22	50.43	54	3.57	AVG

3.2.11 Spurious Emission in Restricted Band 4.5GHz~5.150 GHz& 5.350GHz~5460GHz

EUT :	WiFi Module	Model Name. :	EL.MT7668BUN-WFT
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.3V
Test Mode :	TX (5.2G)-802.11n20 MIMO		

All the modulation modes have been tested, The report just record the worst data mode.

Frequency	Meter Reading	Cable Loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	dB/m	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
5.2G WIFI-802.11n20 MIMO Mode									
4500	56.35	5.2	35.6	44.2	52.95	74	-21.05	Pk	Horizontal
4500	47.21	5.2	35.6	44.2	43.81	54	-10.19	AV	Horizontal
4500	59.41	5.2	35.6	44.2	56.01	74	-17.99	Pk	Vertical
4500	46.40	5.2	35.6	44.2	43	54	-11	AV	Vertical
5150	70.42	5.36	35.66	44.22	67.22	74	-6.78	Pk	Horizontal
5150	79.89	5.36	35.66	44.22	76.69	54	22.69	AV	Horizontal
5150	56.99	5.36	35.66	44.22	53.79	74	-20.21	Pk	Vertical
5150	79.85	5.36	35.66	44.22	76.65	54	22.65	AV	Vertical
5350	65.72	5.68	35.68	44.22	62.86	74	-11.14	Pk	Vertical
5350	47.42	5.68	35.68	44.22	44.56	54	-9.44	AV	Vertical
5350	61.21	5.68	35.68	44.22	58.35	74	-15.65	Pk	Horizontal
5350	45.83	5.68	35.68	44.22	42.97	54	-11.03	AV	Horizontal

Note: (1) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamplifier Factor

(2) "802.11n20 MIMO" mode is the worst mode. When PK value is lower than the Average value limit, average don't record.

4. POWER SPECTRAL DENSITY TEST

4.1 APPLIED PROCEDURES / LIMIT

According to FCC §15.407(a)

For the band 5.15-5.25 GHz,

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz

(3) For the band 5.725-5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

,

4.2 TEST PROCEDURE

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:


- a) Set $RBW \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $VBW \geq 3 RBW$.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/RBW)$ to the measured result, whereas $RBW (< 500 \text{ KHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1\text{MHz}/RBW)$ to the measured result, whereas $RBW (< 1 \text{ MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 KHz for the sections 5.c) and 5.d) above, since $RBW=100 \text{ KHz}$ is available on nearly all spectrum analyzers.

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



4.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

4.6 TEST RESULTS

EUT :	WiFi Module	Model Name :	EL.MT7668BUN-WFT
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1015 hPa	Test Voltage :	DC 3.3V
Test Mode :	TX Frequency Band 1 (5150-5250MHz), Band 4 (5745-5825MHz)		

For 5.2G band, 802.11n/ac has MIMO mode. Directional gain=6.41 dBi
 6.41dBi>6.0 dBi, so MIMO power spectral density limit=10.59dBm / 1MHz;
 For 5.8G band, 802.11n/ac has MIMO mode. Directional gain=6.411 dBi
 6.41dBi>6.0 dBi, so MIMO power spectral density limit=29.59dBm / 500kHz;

Test data reference attachment.

5. 26DB & 99% EMISSION BANDWIDTH

5.1 APPLIED PROCEDURES / LIMIT


The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

5.2 TEST PROCEDURE

- a) Set RBW = approximately 1% of the emission bandwidth.
- b) Set the VBW > RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW $\geq 3 \cdot$ RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.



5.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.4 TEST RESULTS

EUT :	WiFi Module	Model Name :	EL.MT7668BUN-WFT
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1012 hPa	Test Voltage :	DC 3.3V
Test Mode :	TX Frequency Band 1 (5150-5250MHz), Band 4 (5745-5825MHz)		

Test data reference attachment.

6. MINIMUM 6 DB BANDWIDTH

6.1 APPLIED PROCEDURES / LIMIT

According to FCC §15.407(e)

(e) Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

6.2 TEST PROCEDURE


Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.6 TEST RESULTS

EUT :	WiFi Module	Model Name :	EL.MT7668BUN-WFT
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1012 hPa	Test Voltage :	DC 3.3V
Test Mode :	TX (5G) Mode Frequency Band 4 (5725-5850MHz)		

Test data reference attachment.

7. MAXIMUM CONDUCTED OUTPUT POWER

7.1 PPLIED PROCEDURES / LIMIT

According to FCC §15.407

The maximum conducted output power should not exceed:

Frequency Band(MHz)	Limit
5150~5250	0.25W
5725~5850	1W

7.2 TEST PROCEDURE


· Method PM is Measurement using an RF average power meter. The procedure for this method is as follows:

- a) Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the following conditions are satisfied:
 - 1) The EUT is configured to transmit continuously, or to transmit with a constant duty cycle.
 - 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
 - 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- b) If the transmitter does not transmit continuously, measure the duty cycle D of the transmitter output signal as described in 12.2.
- c) Measure the average power of the transmitter. This measurement is an average over both the ON and OFF periods of the transmitter.
- d) Adjust the measurement in dBm by adding $[10 \log (1 / D)]$, where D is the duty cycle {e.g., $[10 \log (1 / 0.25)]$, if the duty cycle is 25%}.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.5 TEST RESULTS

EUT :	WiFi Module	Model Name :	EL.MT7668BUN-WFT
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1012 hPa	Test Voltage :	DC 3.3V
Test Mode :	TX Frequency Band 1 (5150-5250MHz), Band 4 (5745-5825MHz)		

For 5.2G band. Directional gain=6.41dBi; 6.41dBi > 6dBi, so conducted power limit= 23.59dBm.

For 5.8G band. Directional gain=6.41dBi; 6.41dBi > 6dBi, so conducted power limit= 29.59dBm.

Test data reference attachment.

8. OUT OF BAND EMISSIONS

8.1 APPLICABLE STANDARD

According to FCC §15.407(b)

Undesirable emission limits. Except as shown in paragraph (b)(9) (10) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.725-5.85 GHz band: For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.


8.2 TEST PROCEDURE

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

8.6 TEST RESULTS

EUT :	WiFi Module	Model Name :	EL.MT7668BUN-WFT
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1012 hPa	Test Voltage :	DC 3.3V

Test data reference attachment.

9. Frequency Stability Measurement


9.1 LIMIT

Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

9.2 TEST PROCEDURES

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5. f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f)/f_c \times 10^6$ ppm and the limit is less than ± 20 ppm (IEEE 802.11 specification).
6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
7. Extreme temperature is $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$.

9.3 TEST SETUP LAYOUT



9.4 EUT OPERATION DURING TEST

1. The EUT was programmed to be in continuously un-modulation transmitting mode.
2. The has two antennas, and the worst data is Antenna 1, only shown Antenna 1 Plot.

9.5 TEST RESULTS

EUT :	WiFi Module	Model Name. :	EL.MT7668BUN-WFT
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 3.3V
Test Mode :	TX Frequency Band I (5150-5250MHz)		

1(2) Represent the value of antenna 1 and 2, the worst data is Antenna 1 802.11a mode, only shown Antenna 1 802.11a mode data.

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5180MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.63	5180.0255	5180	0.0255	-4.9228
		V max (V)	3.30	5180.0072	5180	0.0072	-1.3900
		V min (V)	2.97	5180.0128	5180	0.0128	-2.4710
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5180MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.3	T (°C)	-20	5180.0121	5180	0.0121	-2.3359
		T (°C)	-10	5180.0085	5180	0.0085	-1.6409
		T (°C)	0	5180.0303	5180	0.0303	-5.8494
		T (°C)	10	5180.0071	5180	0.0071	-1.3707
		T (°C)	20	5180.0328	5180	0.0328	-6.3320
		T (°C)	30	5180.0077	5180	0.0077	-1.4865
		T (°C)	40	5180.0278	5180	0.0278	-5.3668
		T (°C)	50	5180.0057	5180	0.0057	-1.1004
		T (°C)	60	5180.0035	5180	0.0035	-0.6757
		T (°C)	70	5180.0180	5180	0.0180	-3.4749
Limits				Within 5150-5250MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5200MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.63	5200.0075	5200	0.0075	-1.4423
		V max (V)	3.30	5200.0065	5200	0.0065	-1.2500
		V min (V)	2.97	5200.0274	5200	0.0274	-5.2692
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5200MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.3	T (°C)	-20	5200.0231	5200	0.0231	-4.4423
		T (°C)	-10	5200.0041	5200	0.0041	-0.7885
		T (°C)	0	5200.0250	5200	0.0250	-4.8077
		T (°C)	10	5200.0102	5200	0.0102	-1.9615
		T (°C)	20	5200.0024	5200	0.0024	-0.4615
		T (°C)	30	5200.0118	5200	0.0118	-2.2692
		T (°C)	40	5200.0330	5200	0.0330	-6.3462
		T (°C)	50	5200.0326	5200	0.0326	-6.2692
		T (°C)	60	5200.0031	5200	0.0031	-0.5962
		T (°C)	70	5200.0011	5200	0.0011	-0.2115
Limits				Within 5150-5250MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5240MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.63	5240.0252	5240	0.0252	-4.8092
		V max (V)	3.30	5240.0298	5240	0.0298	-5.6870
		V min (V)	2.97	5240.024	5240	0.0240	-4.5802
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5240MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.3	T (°C)	-20	5240.0200	5240	0.0200	-3.8168
		T (°C)	-10	5240.0013	5240	0.0013	-0.2481
		T (°C)	0	5240.0232	5240	0.0232	-4.4275
		T (°C)	10	5240.0040	5240	0.0040	-0.7634
		T (°C)	20	5240.0049	5240	0.0049	-0.9351
		T (°C)	30	5240.0200	5240	0.0200	-3.8168
		T (°C)	40	5240.0236	5240	0.0236	-4.5038
		T (°C)	50	5240.0143	5240	0.0143	-2.7290
		T (°C)	60	5240.0284	5240	0.0284	-5.4198
		T (°C)	70	5240.0297	5240	0.0297	-5.6679
Limits				Within 5150-5250MHz			
Result				Complies			

EUT :	WiFi Module	Model Name. :	EL.MT7668BUN-WFT
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 3.3V
Test Mode :	TX Frequency(5745-5850MHz)		

1(2) Represent the value of antenna 1 and 2, the worst data is Antenna 1 802.11a mode, only shown Antenna 1 802.11a mode data.

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.63	5745.0023	5745	0.00230	-0.4003
		V max (V)	3.30	5745.037	5745	0.03700	-6.4404
		V min (V)	2.97	5745.0277	5745	0.02770	-4.8216
Limits				Within 5745-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.3	T (°C)	-20	5745.0097	5745	0.00970	-1.6884
		T (°C)	-10	5745.0164	5745	0.01640	-2.8547
		T (°C)	0	5745.0179	5745	0.01790	-3.1158
		T (°C)	10	5745.0080	5745	0.00800	-1.3925
		T (°C)	20	5745.0114	5745	0.01140	-1.9843
		T (°C)	30	5745.0305	5745	0.03050	-5.3090
		T (°C)	40	5745.0170	5745	0.01700	-2.9591
		T (°C)	50	5745.0040	5745	0.00400	-0.6963
		T (°C)	60	5745.0300	5745	0.03000	-5.2219
		T (°C)	70	5745.0237	5745	0.02370	-4.1253
Limits				Within 5745-5850MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.63	5785.0010	5785	0.00100	-0.1729
		V max (V)	3.30	5785.0125	5785	0.01250	-2.1608
		V min (V)	2.97	5785.0308	5785	0.03080	-5.3241
Limits				Within 5745-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	12	T (°C)	-20	5785.0062	5785	0.00620	-1.0717
		T (°C)	-10	5785.0113	5785	0.01130	-1.9533
		T (°C)	0	5785.0239	5785	0.02390	-4.1314
		T (°C)	10	5785.0023	5785	0.00230	-0.3976
		T (°C)	20	5785.0175	5785	0.01750	-3.0251
		T (°C)	30	5785.0015	5785	0.00150	-0.2593
		T (°C)	40	5785.0212	5785	0.02120	-3.6646
		T (°C)	50	5785.0153	5785	0.01530	-2.6448
		T (°C)	60	5785.0002	5785	0.00020	-0.0346
		T (°C)	70	5785.0213	5785	0.02130	-3.6819
Limits				Within 5745-5850MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.63	5825.0013	5825	0.00130	-0.2232
		V max (V)	3.30	5825.0236	5825	0.02360	-4.0515
		V min (V)	2.97	5825.027	5825	0.02700	-4.6352
Limits				Within 5745-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.3	T (°C)	-20	5825.0267	5825	0.02670	-4.5837
		T (°C)	-10	5825.0132	5825	0.01320	-2.2661
		T (°C)	0	5825.0154	5825	0.01540	-2.6438
		T (°C)	10	5825.0254	5825	0.02540	-4.3605
		T (°C)	20	5825.0168	5825	0.01680	-2.8841
		T (°C)	30	5825.0085	5825	0.00850	-1.4592
		T (°C)	40	5825.0110	5825	0.01100	-1.8884
		T (°C)	50	5825.0199	5825	0.01990	-3.4163
		T (°C)	60	5825.0174	5825	0.01740	-2.9871
		T (°C)	70	5825.0275	5825	0.02750	-4.7210
Limits				Within 5745-5850MHz			
Result				Complies			

10. ANTENNA REQUIREMENT

10.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

10.2 EUT ANTENNA

The EUT antenna is permanent attached Antenna: PIFA Antenna (Antenna 1: 3.25 dBi; Antenna 2: 3.55dBi), It comply with the standard requirement.


11. TEST RESULT

WIFI 5.2G


11.1 DUTY CYCLE

Antenna	Condition	Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor (dB)
Ant 1	NVNT	802.11a	5180	97.76	0.1
Ant 1	NVNT	802.11a	5200	97.75	0.1
Ant 1	NVNT	802.11a	5240	97.76	0.1
Ant 2	NVNT	802.11a	5180	97.76	0.1
Ant 2	NVNT	802.11a	5200	97.76	0.1
Ant 2	NVNT	802.11a	5240	97.76	0.1
Ant 1	NVNT	802.11ac20	5180	95.51	0.2
Ant 1	NVNT	802.11ac20	5200	95.51	0.2
Ant 1	NVNT	802.11ac20	5240	95.52	0.2
Ant 2	NVNT	802.11ac20	5180	95.51	0.2
Ant 2	NVNT	802.11ac20	5200	95.51	0.2
Ant 2	NVNT	802.11ac20	5240	95.52	0.2
Ant 1	NVNT	802.11ac40	5190	91.74	0.37
Ant 1	NVNT	802.11ac40	5230	91.68	0.38
Ant 2	NVNT	802.11ac40	5190	91.83	0.37
Ant 2	NVNT	802.11ac40	5230	91.81	0.37
Ant 1	NVNT	802.11ac80	5210	61.23	2.13
Ant 2	NVNT	802.11ac80	5210	61.17	2.13
Ant 1	NVNT	802.11n(HT20)	5180	97.6	0.11
Ant 1	NVNT	802.11n(HT20)	5200	97.59	0.11
Ant 1	NVNT	802.11n(HT20)	5240	97.6	0.11
Ant 2	NVNT	802.11n(HT20)	5180	97.61	0.11
Ant 2	NVNT	802.11n(HT20)	5200	97.6	0.11
Ant 2	NVNT	802.11n(HT20)	5240	97.59	0.11
Ant 1	NVNT	802.11n(HT40)	5190	95.34	0.21
Ant 1	NVNT	802.11n(HT40)	5230	95.34	0.21
Ant 2	NVNT	802.11n(HT40)	5190	95.34	0.21
Ant 2	NVNT	802.11n(HT40)	5230	95.34	0.21


Duty Cycle NVNT 802.11a 5180MHz Ant 1




Duty Cycle NVNT 802.11a 5200MHz Ant 1




Duty Cycle NVNT 802.11a 5240MHz Ant 1




Duty Cycle NVNT 802.11a 5180MHz Ant 2




Duty Cycle NVNT 802.11a 5200MHz Ant 2




Duty Cycle NVNT 802.11a 5240MHz Ant 2




Duty Cycle NVNT 802.11ac20 5180MHz Ant 1




Duty Cycle NVNT 802.11ac20 5200MHz Ant 1




Duty Cycle NVNT 802.11ac20 5240MHz Ant 1




Duty Cycle NVNT 802.11ac20 5180MHz Ant 2




Duty Cycle NVNT 802.11ac20 5200MHz Ant 2




Duty Cycle NVNT 802.11ac20 5240MHz Ant 2




Duty Cycle NVNT 802.11ac40 5190MHz Ant 1




Duty Cycle NVNT 802.11ac40 5230MHz Ant 1




Duty Cycle NVNT 802.11ac40 5190MHz Ant 2




Duty Cycle NVNT 802.11ac40 5230MHz Ant 2




Duty Cycle NVNT 802.11ac80 5210MHz Ant 1




Duty Cycle NVNT 802.11ac80 5210MHz Ant 2




Duty Cycle NVNT 802.11n(HT20) 5180MHz Ant 1




Duty Cycle NVNT 802.11n(HT20) 5200MHz Ant 1




Duty Cycle NVNT 802.11n(HT20) 5240MHz Ant 1




Duty Cycle NVNT 802.11n(HT20) 5180MHz Ant 2




Duty Cycle NVNT 802.11n(HT20) 5200MHz Ant 2




Duty Cycle NVNT 802.11n(HT20) 5240MHz Ant 2




Duty Cycle NVNT 802.11n(HT40) 5190MHz Ant 1




Duty Cycle NVNT 802.11n(HT40) 5230MHz Ant 1



Duty Cycle NVNT 802.11n(HT40) 5190MHz Ant 2



Duty Cycle NVNT 802.11n(HT40) 5230MHz Ant 2




11.2 MAXIMUM CONDUCTED OUTPUT POWER

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Power (dBm)	Limit (dBm)	Verdict
NVNT	802.11a	5180	Ant 1	10.59	0.1	10.69	24	Pass
NVNT	802.11a	5200	Ant 1	10.27	0.1	10.37	24	Pass
NVNT	802.11a	5240	Ant 1	10.08	0.1	10.18	24	Pass
NVNT	802.11a	5180	Ant 2	10.59	0.1	10.69	24	Pass
NVNT	802.11a	5200	Ant 2	10.26	0.1	10.36	24	Pass
NVNT	802.11a	5240	Ant 2	10.11	0.1	10.21	24	Pass
NVNT	802.11ac20	5180	Ant 1	8.61	0.2	8.81	24	Pass
NVNT	802.11ac20	5200	Ant 1	8.43	0.2	8.63	24	Pass
NVNT	802.11ac20	5240	Ant 1	8.23	0.2	8.43	24	Pass
NVNT	802.11ac20	5180	Ant 2	8.66	0.2	8.86	24	Pass
NVNT	802.11ac20	5200	Ant 2	8.35	0.2	8.55	24	Pass
NVNT	802.11ac20	5240	Ant 2	8.33	0.2	8.53	24	Pass
NVNT	802.11ac40	5190	Ant 1	8.49	0.37	8.86	24	Pass
NVNT	802.11ac40	5230	Ant 1	8.37	0.38	8.75	24	Pass
NVNT	802.11ac40	5190	Ant 2	8.63	0.37	9	24	Pass
NVNT	802.11ac40	5230	Ant 2	8.51	0.37	8.88	24	Pass
NVNT	802.11ac80	5210	Ant 1	5.9	2.13	8.03	24	Pass
NVNT	802.11ac80	5210	Ant 2	6.83	2.13	8.96	24	Pass
NVNT	802.11n(HT20)	5180	Ant 1	8.82	0.11	8.93	24	Pass
NVNT	802.11n(HT20)	5200	Ant 1	8.64	0.11	8.75	24	Pass
NVNT	802.11n(HT20)	5240	Ant 1	8.39	0.11	8.5	24	Pass
NVNT	802.11n(HT20)	5180	Ant 2	9.01	0.11	9.12	24	Pass
NVNT	802.11n(HT20)	5200	Ant 2	8.38	0.11	8.49	24	Pass
NVNT	802.11n(HT20)	5240	Ant 2	8.4	0.11	8.51	24	Pass
NVNT	802.11n(HT40)	5190	Ant 1	8.39	0.21	8.6	24	Pass
NVNT	802.11n(HT40)	5230	Ant 1	8.44	0.21	8.65	24	Pass
NVNT	802.11n(HT40)	5190	Ant 2	8.42	0.21	8.63	24	Pass
NVNT	802.11n(HT40)	5230	Ant 2	8.19	0.21	8.4	24	Pass


11.3 OCCUPIED CHANNEL BANDWIDTH

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)	-26 dB Bandwidth (MHz)	Verdict
NVNT	802.11a	5180	Ant 1	16.4984	19.92	Pass
NVNT	802.11a	5200	Ant 1	16.4424	19.288	Pass
NVNT	802.11a	5240	Ant 1	16.4104	19.436	Pass
NVNT	802.11a	5180	Ant 2	16.5183	19.756	Pass
NVNT	802.11a	5200	Ant 2	16.3304	19.488	Pass
NVNT	802.11a	5240	Ant 2	16.3104	19.66	Pass
NVNT	802.11ac20	5180	Ant 1	17.5342	20.016	Pass
NVNT	802.11ac20	5200	Ant 1	17.5462	19.84	Pass
NVNT	802.11ac20	5240	Ant 1	17.5302	19.768	Pass
NVNT	802.11ac20	5180	Ant 2	17.5422	19.836	Pass
NVNT	802.11ac20	5200	Ant 2	17.5022	19.972	Pass
NVNT	802.11ac20	5240	Ant 2	17.5062	19.776	Pass
NVNT	802.11ac40	5190	Ant 1	36.0604	40.36	Pass
NVNT	802.11ac40	5230	Ant 1	36.0364	40.48	Pass
NVNT	802.11ac40	5190	Ant 2	36.1804	41.208	Pass
NVNT	802.11ac40	5230	Ant 2	36.1884	40.928	Pass
NVNT	802.11ac80	5210	Ant 1	75.3365	80.848	Pass
NVNT	802.11ac80	5210	Ant 2	75.4485	81.216	Pass
NVNT	802.11n(HT20)	5180	Ant 1	17.5702	19.956	Pass
NVNT	802.11n(HT20)	5200	Ant 1	17.5662	19.924	Pass
NVNT	802.11n(HT20)	5240	Ant 1	17.4983	20.068	Pass
NVNT	802.11n(HT20)	5180	Ant 2	17.5462	20.08	Pass
NVNT	802.11n(HT20)	5200	Ant 2	17.4983	20.192	Pass
NVNT	802.11n(HT20)	5240	Ant 2	17.5582	19.888	Pass
NVNT	802.11n(HT40)	5190	Ant 1	36.1964	40.896	Pass
NVNT	802.11n(HT40)	5230	Ant 1	36.2124	40.712	Pass
NVNT	802.11n(HT40)	5190	Ant 2	36.2124	40.864	Pass
NVNT	802.11n(HT40)	5230	Ant 2	36.2124	40.696	Pass


OBW NVNT 802.11a 5180MHz Ant 1




-26 dB BW NVNT 802.11a 5180MHz Ant 1




OBW NVNT 802.11a 5200MHz Ant 1




-26 dB BW NVNT 802.11a 5200MHz Ant 1




OBW NVNT 802.11a 5240MHz Ant 1




-26 dB BW NVNT 802.11a 5240MHz Ant 1




OBW NVNT 802.11a 5180MHz Ant 2




-26 dB BW NVNT 802.11a 5180MHz Ant 2




OBW NVNT 802.11a 5200MHz Ant 2




-26 dB BW NVNT 802.11a 5200MHz Ant 2




OBW NVNT 802.11a 5240MHz Ant 2




-26 dB BW NVNT 802.11a 5240MHz Ant 2




OBW NVNT 802.11ac20 5180MHz Ant 1




-26 dB BW NVNT 802.11ac20 5180MHz Ant 1




OBW NVNT 802.11ac20 5200MHz Ant 1




-26 dB BW NVNT 802.11ac20 5200MHz Ant 1




OBW NVNT 802.11ac20 5240MHz Ant 1




-26 dB BW NVNT 802.11ac20 5240MHz Ant 1




OBW NVNT 802.11ac20 5180MHz Ant 2




-26 dB BW NVNT 802.11ac20 5180MHz Ant 2




OBW NVNT 802.11ac20 5200MHz Ant 2




-26 dB BW NVNT 802.11ac20 5200MHz Ant 2




OBW NVNT 802.11ac20 5240MHz Ant 2




-26 dB BW NVNT 802.11ac20 5240MHz Ant 2




OBW NVNT 802.11ac40 5190MHz Ant 1




-26 dB BW NVNT 802.11ac40 5190MHz Ant 1




OBW NVNT 802.11ac40 5230MHz Ant 1




-26 dB BW NVNT 802.11ac40 5230MHz Ant 1




OBW NVNT 802.11ac40 5190MHz Ant 2




-26 dB BW NVNT 802.11ac40 5190MHz Ant 2




OBW NVNT 802.11ac40 5230MHz Ant 2




-26 dB BW NVNT 802.11ac40 5230MHz Ant 2




OBW NVNT 802.11ac80 5210MHz Ant 1




-26 dB BW NVNT 802.11ac80 5210MHz Ant 1




OBW NVNT 802.11ac80 5210MHz Ant 2




-26 dB BW NVNT 802.11ac80 5210MHz Ant 2




OBW NVNT 802.11n(HT20) 5180MHz Ant 1




-26 dB BW NVNT 802.11n(HT20) 5180MHz Ant 1




OBW NVNT 802.11n(HT20) 5200MHz Ant 1




-26 dB BW NVNT 802.11n(HT20) 5200MHz Ant 1



OBW NVNT 802.11n(HT20) 5240MHz Ant 1



-26 dB BW NVNT 802.11n(HT20) 5240MHz Ant 1



OBW NVNT 802.11n(HT20) 5180MHz Ant 2

