



经续检验

SLG-CPC Testlaboratory

TEST REPORT

Report Number. :	90596-25-72-25-PP003	
Date of issue..... :	2025-07-24	
Prepared by (+signature)..... :	Pale	
Reviewer (+signature)..... :	Duke	
Approved by (+signature) :	Jason	
Testing Laboratory name	SLG-CPC Testlaboratory Co., Ltd.	
Address..... :	No. 11, Wu Song Road, Dongcheng District Dongguan, Guangdong Province, 523117, People's Republic of China	
Applicant's name	Zhuhai Xprinter Electronics Technology Co., Ltd.	
Address..... :	5F,1st Building,613 Huawei Road,Qianshan Industrial Park,Xiangzhou District,Zhuhai City,Guangdong Province,China	
Manufacturer's name	Zhuhai Xprinter Electronics Technology Co., Ltd.	
Address..... :	5F,1st Building,613 Huawei Road,Qianshan Industrial Park,Xiangzhou District,Zhuhai City,Guangdong Province,China	
Factory's name	Zhuhai Xprinter Electronics Technology Co., Ltd.	
Address..... :	5F,1st Building,613 Huawei Road,Qianshan Industrial Park,Xiangzhou District,Zhuhai City,Guangdong Province,China	
Standard(s)	FCC part 2.1091	
Test item description	THERMAL RECEIPT PRINTER, THERMAL BARCODE PRINTER, BLUETOOTH THERMAL RECEIPT PRINTER, BLUETOOTH THERMAL BARCODE PRINTER, WIRELESS THERMAL RECEIPT PRINTER, THERMAL LABEL PRINTER, CLOUD THERMAL RECEIPT PRINTER, CLOUD THERMAL BARCODE PRINTER	
Trade Mark	Xprinter® 芯烨	
Model/Type reference	XP-Q80AS (See Page 4-5 for series model)	
FCC ID	2AWYKXP-Q80AS	
Date of receipt of test item..... :	2025-07-15	
Date (s) of performance of test:	2025-07-16 to 2025-07-23	
Summary of Test Results	Pass	
The Summary of Test Results based on a technical opinion belongs to the standard(s).		
General disclaimer: This report shall not be reproduced except in full, without the written approval of SLG-CPC Testlaboratory Co., Ltd. The test results in the report only apply to the tested sample.		

Table of Contents

1. EUT SPECIFICATION	4
2. TEST REQUIREMENT:.....	6
3. MEASUREMENT RESULT.....	7

Modified History

Report No.	Revision Date	Summary
90596-25-72-25-PP003	2025-07-24	Original Report

1. EUT Specification

Characteristics	Description
Product:	THERMAL RECEIPT PRINTER, THERMAL BARCODE PRINTER, BLUETOOTH THERMAL RECEIPT PRINTER, BLUETOOTH THERMAL BARCODE PRINTER, WIRELESS THERMAL RECEIPT PRINTER, THERMAL LABEL PRINTER, CLOUD THERMAL RECEIPT PRINTER, CLOUD THERMAL BARCODE PRINTER
Model Number:	XP-T80A,XP-T80B,XP-T80C,XP-T80D,XP-T80E,XP-T80F,XP-T80G, XP-T80H,XP-T80K,XP-T80L,XP-T80M,XP-T80N,XP-T80S,XP-T80X, XP-T80U,XP-Q80A,XP-Q80B,XP-Q80C,XP-Q80D,XP-Q80E,XP-Q80F, XP-Q80G,XP-Q80H,XP-Q80I,XP-Q80K,XP-Q80L,XP-Q80M,XP-Q80N, XP-Q80S,XP-Q80X,XP-Q80U,XP-80A,XP-80B,XP-80C,XP-80D, XP-80E,XP-80F,XP-80G,XP-80H,XP-80K,XP-80L,XP-80M,XP-80N, XP-80S,XP-80X,XP-80U,XP-80T,XP-T81A,XP-T81B,XP-T81C, XP-T81D,XP-T81E,XP-T81F,XP-T81G,XP-T81H,XP-T81K,XP-T81L, XP-T81M,XP-T81N,XP-T81Q,XP-T81S,XP-T81U,XP-T81X,XP-T82A, XP-T82B,XP-T82C,XP-T82D,XP-T82E,XP-T82F,XP-T82G,XP-T82H, XP-T82K,XP-T82L,XP-T82M,XP-T82N,XP-T82Q,XP-T82S,XP-T82U, XP-T82X,XP-T83A,XP-T83B,XP-T83C,XP-T83D,XP-T83E,XP-T83F, XP-T83G,XP-T83H,XP-T83K,XP-T83L,XP-T83M,XP-T83N,XP-T83Q, XP-T83S,XP-T83U,XP-T83X,XP-T85A,XP-T85B,XP-T85C,XP-T85D, XP-T85E,XP-T85F,XP-T85G,XP-T85H,XP-T85K,XP-T85L,XP-T85M, XP-T85N,XP-T85Q,XP-T85S,XP-T85U,XP-T85X,XP-T86A,XP-T86B, XP-T86C,XP-T86D,XP-T86E,XP-T86F,XP-T86G,XP-T86H,XP-T86K, XP-T86L,XP-T86M,XP-T86N,XP-T86Q,XP-T86S,XP-T86U,XP-T86X, XP-T87A,XP-T87B,XP-T87C,XP-T87D,XP-T87E,XP-T87F,XP-T87G, XP-T87H,XP-T87K,XP-T87L,XP-T87M,XP-T87N,XP-T87Q,XP-T87S, XP-T87U,XP-T87X,XP-T88A,XP-T88B,XP-T88C,XP-T88D,XP-T88E, XP-T88F,XP-T88G,XP-T88H,XP-T88K,XP-T88L,XP-T88M,XP-T8N, XP-T88Q,XP-T88S,XP-T88U,XP-T88X,XP-T89A,XP-T89B,XP-T89C, XP-T89D,XP-T89E,XP-T89F,XP-T89G,XP-T89H,XP-T89K,XP-T89L, XP-T89M,XP-T89N,XP-T89Q,XP-T89S,XP-T89U,XP-T89X,DKT-M80A, DKT-M80B,DKT-M80C,DKT-M80C,DKT-M80D,DKT-M80E,DKT-M80F, DKT-M80G,DKT-M80H,DKT-M80I,DKT-M80J,DKT-M80K,DKT-M80L, DKT-M80M,DKT-M80N,DKT-M80P,DKT-M80Q,DKT-M80R,DKT-M80S, DKT-M80T,DKT-M80U,DKT-M80V,DKT-M80X,DKT-M80Y,DKT-M80Z, DKT-M88A,DKT-M88B,DKT-M88C,DKT-M88C,DKT-M88D,DKT-M88E, DKT-M88F,DKT-M88G,DKT-M88H,DKT-M88I,DKT-M88J,DKT-M88K, DKT-M88L,DKT-M88M,DKT-M88N,DKT-M88P,DKT-M88Q,DKT-M88R, DKT-M88S,DKT-M88T,DKT-M88U,DKT-M88V,DKT-M88X,DKT-M88Y, DKT-M88Z,XP-300B,XP-30B,XP-31B,XP-32B,XP-33B,XP-34B,XP-35B, XP-36B,XP-37B,XP-38B,XP-39B,XP-30U,XP-31U,XP-32U,XP-33U, XP-34U,XP-35U,XP-36U,XP-37U,XP-38U,XP-39U,XP-30F,XP-31F, XP-32F,XP-33F,XP-34F,XP-35F,XP-36F,XP-37F,XP-38F,XP-39F, XP-30N,XP-31N,XP-32N,XP-33N,XP-34N,XP-35N,XP-36N,XP-37N, XP-38N,XP-39N,XP-30Q,XP-31Q,XP-32Q,XP-33Q,XP-34Q,XP-35Q, XP-36Q,XP-37Q,XP-38Q,XP-39Q,XP-300B,XP-310B,XP-320B, XP-330B,XP-340B,XP-350B,XP-360B,XP-370B,XP-380B,XP-390B, XP-300U,XP-310U,XP-320U,XP-330U,XP-340U,XP-350U,XP-360U, XP-370U,XP-380U,XP-390U,XP-300F,XP-310F,XP-320F,XP-330F, XP-340F,XP-350F,XP-360F,XP-370F,XP-380F,XP-390F,XP-300N, XP-310N,XP-320N,XP-330N,XP-340N,XP-350N,XP-360N,XP-370N, XP-380N,XP-390N,XP-300Q,XP-310Q,XP-320Q,XP-330Q,XP-340Q,

	XP-350Q,XP-360Q,XP-370Q,XP-380Q,XP-390Q,XP-303B,XP-305B,XP-310B,XP-310BM,XP-318B,XP-318BM,XP-320B,XP-323B,XP-325B,XP-330B,XP-330BM,XP-338B,XP-338BM,XP-350B,XP-350BM,XP-356B,XP-356BM,XP-358B,XP-358BM,XP-360B,XP-363B,XP-365B,XP-367B,XP-370B,XP-370BM,XP-378B,XP-378BM,XP-T301F,XP-T302F,XP-T303F,XP-T304F,XP-T305F,XP-Q301F,XP-Q302F,XP-Q303F,XP-Q304F,XP-Q305F,XP-T361U,XP-T362U,XP-T363U,XP-T364U,XP-T365U,XP-Q361U,XP-Q362U,XP-Q363U,XP-Q364U,XP-Q365U,XP-T80AS,XP-T80BS,XP-T80CS,XP-T80DS,XP-T80ES,XP-T80FS,XP-T80GS,XP-T80HS,XP-T80KS,XP-T80LS,XP-T80MS,XP-T80NS,XP-T80SS,XP-T80XS,XP-T80US,XP-Q80AS,XP-Q80BS,XP-Q80CS,XP-Q80DS,XP-Q80ES,XP-Q80FS,XP-Q80GS,XP-Q80HS,XP-Q80IS,XP-Q80KS,XP-Q80LS,XP-Q80MS,XP-Q80NS,XP-Q80SS,XP-Q80XS,XP-Q80US,XP-80AS,XP-80BS,XP-80CS,XP-80DS,XP-80ES,XP-80FS,XP-80GS,XP-80HS,XP-80KS,XP-80LS,XP-80MS,XP-80NS,XP-80SS,XP-80XS,XP-80US,XP-80TS (All models are identical to each other except for product name and model name. All tests are performed on model XP-Q80AS.)
Device Type:	Bluetooth V5.0
Data Rate:	DSS: 1Mbps for GFSK modulation 2Mbps for pi/4-DQPSK modulation DTS: 1Mbps for GFSK modulation
Modulation:	DSS: GFSK, pi/4-DQPSK DTS: GFSK(1M)
Operating Frequency Range(s) :	2402-2480MHz
Number of Channels:	DSS: 79 channels DTS: 40 channels
Transmit Power Max:	DSS: 0.95 dBm DTS: 1 dBm
Antenna Gain:	-5.35 dBi
Power supply:	Power Input: 24V $\overline{\text{---}}$ 1.25A
AC/DC ADAPTER Information	MODEL: YC36-2401250 INPUT: 100-240V~ 50/60Hz 1.0A OUTPUT: 24V $\overline{\text{---}}$ 1.25A Manufacturer: Zhongshan City Youchuang Electronics Technology Co.,Ltd
Evaluation applied:	☒ MPE Evaluation ☐ SAR Evaluation

2. Test Requirement:

RF EXPOSURE EVALUATION

According to 447498 D01 V06: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

3. Measurement Result

Bluetooth

Antenna gain: -5.53 dBi

modulation	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
BR: GFSK	2402	0.6	±1	1.60	0.29	0.000084	1
	2441	0	±1	1.00	0.29	0.000073	1
	2480	0.95	±1	1.95	0.29	0.000091	1
EDR: pi/4-DQPSK	2402	-0.3	±1	0.70	0.29	0.000068	1
	2441	-0.91	±1	0.09	0.29	0.000059	1
	2480	0.02	±1	1.02	0.29	0.000073	1
BLE: GFSK(1M)	2402	0.63	±1	1.63	0.29	0.000084	1
	2441	0.10	±1	1.10	0.29	0.000075	1
	2480	1.00	±1	2.00	0.29	0.000092	1

the worst-case situation is 0.000092, which is less than “1”,
 This confirmed that the device comply with FCC 1.1310 MPE limit.

*** End of Report ***

声 明 Statement

1. 本报告无授权批准人签字及盖章无效;

This report is invalid without the signature and seal of the authorized approver.

2. 未经许可本报告不得部分复制;

This report shall not be copied partly without authorization.

3. 本报告的检测结果仅对送测样品有效, 委托方对样品的代表性和资料的真实性负责;

The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the sample and authenticity of the material.

4. 本检测报告中检测项目标注有特殊符号则该项目不在资质认定范围内, 仅作为客户委托、科研、教学或内部质量控制等目的使用;

The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.

5. 本检测报告以实测值进行符合性判定, 未考虑不确定度所带来的风险, 本实验室不承担相关责任, 特别约定、标准或规范中有明确规定的除外;

The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards or regulations, SLG-CPC shall not assume any responsibility.

6. 对本检测报告若有异议, 请于收到报告之日起 20 日内提出;

Objections shall be raised within 20 days from the date receiving the report.