

TEST REPORT

Applicant: Tanoshi, Inc.

Address of Applicant: 505 14TH ST STE 900 OAKLAND, CA 94612-1902
OAKLAND CA

Manufacturer/Factory: Heyuan Vastking Electronic Co.,Ltd

Address of Manufacturer/Factory: No.13, Hupu Road, PuQian, YuanCheng District, Heyuan, Guangdong, China.

Equipment Under Test (EUT)

Product Name: Tablet PC

Model No.: TTBKB10, TTBKB10-A1V, TTBKB10-A1B

Trade Mark: Tanoshi

FCC ID: 2AWYT-TTBKB10

Applicable standards: FCC CFR Title 47 Part 15 Subpart E Section 15.407

Date of sample receipt: Aug. 21, 2020

Date of Test: Aug. 21, 2020~Sep. 17, 2020

Date of report issued: Sep. 18, 2020

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Lo

Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	Sep. 18, 2020	Original

Prepared By:



Date:

Sep. 18, 2020

Project Engineer

Check By:



Reviewer

Date:

Sep. 18, 2020

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
4.1 MEASUREMENT UNCERTAINTY	4
5 GENERAL INFORMATION	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	7
5.3 DESCRIPTION OF SUPPORT UNITS	7
5.4 DEVIATION FROM STANDARDS	7
5.5 ABNORMALITIES FROM STANDARD CONDITIONS	7
5.6 TEST FACILITY	8
5.7 TEST LOCATION	8
6 TEST INSTRUMENTS LIST	9
7 TEST RESULTS AND MEASUREMENT DATA	11
7.1 ANTENNA REQUIREMENT	11
7.2 CONDUCTED EMISSIONS	12
7.3 CONDUCTED PEAK OUTPUT POWER	15
7.4 CHANNEL BANDWIDTH AND 99% OCCUPIED BANDWIDTH	16
7.5 POWER SPECTRAL DENSITY	27
7.6 BAND EDGE	33
7.6.1 Radiated Emission Method	33
7.7 SPURIOUS EMISSION	37
7.7.1 Radiated Emission Method	37
7.8 FREQUENCY STABILITY	44
8 TEST SETUP PHOTO	48
9 EUT CONSTRUCTIONAL DETAILS	48

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.407(a)(3)	Pass
Channel Bandwidth	15.407(e)	Pass
Power Spectral Density	15.407(a)(3)	Pass
Band Edge	15.407(b)(4)	Pass
Spurious Emission	15.205/15.209/15.407(b)(4)	Pass
Frequency Stability	15.407(g)	Pass

Remarks:

1. Pass: The EUT complies with the essential requirements in the standard.
2. Test according to ANSI C63.10:2013.

4.1 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	30MHz-200MHz	3.8039dB	(1)
Radiated Emission	200MHz-1GHz	3.9679dB	(1)
Radiated Emission	1GHz-18GHz	4.29dB	(1)
Radiated Emission	18GHz-40GHz	3.30dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	3.44dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product Name:	Tablet PC
Model No.:	TTBKB10, TTBKB10-A1V, TTBKB10-A1B
Serial No.:	N/A
Hardware Version:	EM_T6758_V1.0 P4
Software Version:	Android 10
Test sample(s) ID:	GTS202009000070-01
Sample(s) Status:	Engineer sample
Operation Frequency:	802.11a/802.11n(HT20)/802.11ac(HT20): 5745MHz ~ 5825MHz 802.11n(HT40)/ 802.11ac(HT40): 5755MHz ~ 5795MHz 802.11ac(HT80): 5775MHz
Channel numbers:	802.11a/802.11n(HT20)/802.11ac(HT20): 5 802.11n(HT40)/ 802.11ac(HT40): 2 802.11ac(HT80): 1
Channel bandwidth:	802.11a/802.11n(HT20)/802.11ac(HT20) : 20MHz 802.11n(HT40)/802.11ac(HT40) : 40MHz 802.11ac(HT80): 80MHz
Modulation technology:	802.11a/802.11n(H20)/802.11n(H40)/802.11ac(HT20)/802.11ac(HT40) /802.11ac(HT80): Orthogonal Frequency Division Multiplexing (OFDM)
Antenna Type:	FPCB antenna
Antenna gain:	0dBi
Power supply:	JML-0500200NZ-LW INPUT: 100-240V~ 50/60Hz 0.5A OUTPUT: DC 5V 2.0A

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
149	5745MHz	151	5755MHz	153	5765MHz	155	5775MHz
157	5785MHz	159	5795MHz	161	5805MHz	163	5815MHz
165	5825MHz						

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)		
	802.11 a/n/ac(HT20)	802.11 n/ac(HT40)	802.11ac(HT80)
Lowest channel	5745	5755	
Middle channel	5785		5775
Highest channel	5825	5795	

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode
<i>Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	Data rate
802.11a	6Mbps
802.11n(HT20)	6.5Mbps
802.11n(HT40)	13Mbps
802.11ac(HT20)	6.5Mbps
802.11ac(HT40)	13.5Mbps
802.11ac(HT80)	29.3Mbps

5.3 Description of Support Units

None.

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 381383**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383.

- **IC —Registration No.: 9079A**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A

- **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP). LAB CODE:600179-0

5.7 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone,
Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Tel: 0755-27798480

Fax: 0755-27798960

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 02 2020	July. 01 2025
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 25 2020	June. 24 2021
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 25 2020	June. 24 2021
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 25 2020	June. 24 2021
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 25 2020	June. 24 2021
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 25 2020	June. 24 2021
9	Coaxial Cable	GTS	N/A	GTS211	June. 25 2020	June. 24 2021
10	Coaxial cable	GTS	N/A	GTS210	June. 25 2020	June. 24 2021
11	Coaxial Cable	GTS	N/A	GTS212	June. 25 2020	June. 24 2021
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 25 2020	June. 24 2021
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 25 2020	June. 24 2021
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 25 2020	June. 24 2021
15	Band filter	Amindeon	82346	GTS219	June. 25 2020	June. 24 2021
16	Power Meter	Anritsu	ML2495A	GTS540	June. 25 2020	June. 24 2021
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 25 2020	June. 24 2021
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 25 2020	June. 24 2021
19	Splitter	Agilent	11636B	GTS237	June. 25 2020	June. 24 2021
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 25 2020	June. 24 2021
21	Breitband hornantenne	SCHWARZBECK	BBHA 9170	GTS579	Oct. 19 2019	Oct. 18 2020
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 19 2019	Oct. 18 2020
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 19 2019	Oct. 18 2020
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June. 25 2020	June. 24 2021

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.15 2019	May.14 2022
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 25 2020	June. 24 2021
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June. 25 2020	June. 24 2021
4	ENV216 2-L-V-NETZNACHB.DE	ROHDE&SCHWARZ	ENV216	GTS226	June. 25 2020	June. 24 2021
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June. 25 2020	June. 24 2021
8	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	June. 25 2020	June. 24 2021
9	ISN	SCHWARZBECK	NTFM 8158	GTD565	June. 25 2020	June. 24 2021

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	June. 25 2020	June. 24 2021
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 25 2020	June. 24 2021
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June. 25 2020	June. 24 2021
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	June. 25 2020	June. 24 2021
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	June. 25 2020	June. 24 2021
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	June. 25 2020	June. 24 2021
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	June. 25 2020	June. 24 2021
8	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	June. 25 2020	June. 24 2021


General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	June. 25 2020	June. 24 2021
2	Barometer	ChangChun	DYM3	GTS255	June. 25 2020	June. 24 2021

7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203
<i>15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</i>	
E.U.T Antenna:	
<i>The antennas are integral antenna, the best case gain of the antennas are 0 dBi, reference to the appendix II for details</i>	

7.2 Conducted Emissions


Test Requirement:	FCC Part15 C Section 15.207																			
Test Method:	ANSI C63.10:2013																			
Test Frequency Range:	150KHz to 30MHz																			
Class / Severity:	Class B																			
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto																			
Limit:	<table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table> * Decreases with the logarithm of the frequency.						Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)																			
	Quasi-peak	Average																		
0.15-0.5	66 to 56*	56 to 46*																		
0.5-5	56	46																		
5-30	60	50																		
Test setup:	Reference Plane  Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m																			
Test procedure:	<																			

Remark: Both high and low voltages have been tested to show only the worst low voltage test data.

Measurement data


Line:

100.0 dBuV



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1	*	0.1500	49.42	4.03	53.45	65.99	-12.54	peak
2		0.1500	32.05	4.03	36.08	55.99	-19.91	AVG
3		0.6340	32.79	9.96	42.75	56.00	-13.25	peak
4		0.6580	23.33	9.95	33.28	46.00	-12.72	AVG
5		16.1700	35.38	1.35	36.73	60.00	-23.27	peak
6		16.1700	28.51	1.35	29.86	50.00	-20.14	AVG

Neutral:
100.0 dBuV




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1500	31.68	4.03	35.71	55.99	-20.28	AVG
2	*	0.1539	50.94	3.49	54.43	65.78	-11.35	peak
3		0.6419	31.59	9.95	41.54	56.00	-14.46	peak
4		0.6540	24.03	9.95	33.98	46.00	-12.02	AVG
5		16.1700	33.30	1.35	34.65	60.00	-25.35	peak
6		16.1700	23.45	1.35	24.80	50.00	-25.20	AVG

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

7.3 Conducted Peak Output Power


Test Requirement:	FCC Part15 E Section 15.407(a)(3)
Test Method:	ANSI C63.10:2013 and KDB 789033 D02 General U-NII Test Procedures New Rules v02r01
Limit:	30dBm
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Test CH	Output Power (dBm)						Limit(dBm)	Result
	802.11a	802.11n (HT20)	802.11ac (HT20)	802.11n (HT40)	802.11ac (HT40)	802.11ac (HT80)		
Lowest	-1.30	-1.36	-1.34	-1.02	-1.05	-1.40	30.00	Pass
Middle	-1.35	-1.14	-1.13	--	--	--		
Highest	-2.21	2.05	-2.00	-1.57	-1.11	--		

Remark: "---" is not applicable

7.4 Channel Bandwidth and 99% Occupied Bandwidth

Test Requirement:	FCC Part15 E Section 15.407(e)
Test Method:	ANSI C63.10:2013 and KDB 789033 D02 General U-NII Test Procedures New Rules v02r01
Limit:	>500KHz
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data

Test CH	Channel Bandwidth (MHz)						Limit (KHz)	Result
	802.11a	802.11n (HT20)	802.11ac (HT20)	802.11n (HT40)	802.11ac (HT40)	802.11ac (HT80)		
Lowest	15.1025	15.1175	15.1100	35.0775	35.0775	75.1050	>500	Pass
Middle	15.1163	15.1088	15.1100	--	--	--		
Highest	15.1125	15.1100	15.1088	35.0875	35.0775	--		


Test CH	99%Channel Bandwidth (MHz)						Limit (KHz)	Result
	802.11a	802.11n (HT20)	802.11ac (HT20)	802.11n (HT40)	802.11ac (HT40)	802.11ac (HT80)		
Lowest	15.1025	16.6250	17.6075	36.0350	36.2775	75.4350	>500	Pass
Middle	15.1163	16.6738	17.5450	--	--	--		
Highest	15.1125	16.7538	17.5850	35.9200	36.1950	--		

Remark: "---"is not applicable


Test plot as follows:
6dB Occupied Bandwidth
Test mode: 802.11a



Lowest channel




Middle channel




Highest channel


Test mode: 802.11n(HT20)



Lowest channel




Middle channel




Highest channel


Test mode: 802.11ac(HT20)



Lowest channel




Middle channel




Highest channel

Test mode: 802.11n(HT40)




Lowest channel




Highest channel

Test mode: 802.11ac(HT40)




Lowest channel




Highest channel


Test mode: 802.11ac(HT80)




99% Occupied Bandwid
Test mode: 802.11a



Lowest channel




Middle channel




Highest channel


Test mode: 802.11n(HT20)



Lowest channel




Middle channel




Highest channel


Test mode: 802.11ac(HT20)



Lowest channel




Middle channel




Highest channel

Test mode: 802.11n(HT40)




Lowest channel




Highest channel

Test mode: 802.11ac(HT40)




Lowest channel




Highest channel

Test mode: 802.11ac(HT80)



7.5 Power Spectral Density

Test Requirement:	FCC Part15 E Section 15.407(a)(3)
Test Method:	ANSI C63.10:2013 and KDB 789033 D02 General U-NII Test Procedures New Rules v02r01
Limit:	30dBm/500kHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data

Test CH	Power Spectral Density (dBm)						Limit (dBm/500k Hz)	Result
	802.11a	802.11n (HT20)	802.11ac (HT20)	802.11n (HT40)	802.11ac (HT40)	802.11ac (HT80)		
Lowest	-1.17	-1.50	-1.60	-5.17	-5.34	-13.77	30.00	Pass
Middle	-1.17	-1.15	-1.23	--	--	--		
Highest	-0.43	-0.73	-0.52	-4.69	-4.58	--		


Remark: “---”is not applicable

Test plot as follows:


Test mode: 802.11a



Lowest channel




Middle channel




Highest channel


Test mode: 802.11n(HT20)



Lowest channel




Middle channel




Highest channel


Test mode: 802.11ac(HT20)



Lowest channel




Middle channel




Highest channel

Test mode: 802.11n(HT40)




Lowest channel




Highest channel

Test mode: 802.11ac(HT40)




Lowest channel



Highest channel


Test mode: 802.11ac(HT80)



Middle channel

7.6 Band edge

7.6.1 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	9kHz to 40GHz, only worse case is reported				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above 1GHz	Peak	1MHz	3MHz	Peak
		RMS	1MHz	3MHz	RMS
Limit:	All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.				
Test setup:					
Test Procedure:	1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 7. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.				

Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Remarks:

1. Only the worst case Main Antenna test data..
2. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.
5. According to KDB 789033 D02v02r01 section G) 1) d),for measurements above 1000 MHz @3m distance, the limit of field strength is computed as follows:
 $E[\text{dBuV/m}] = \text{EIRP}[\text{dBm}] + 95.2;$
 $E[\text{dBuV/m}] = -27 + 95.2 = 68.2\text{dBuV/m}.$
 $E[\text{dBuV/m}] = 10 + 95.2 = 105.2\text{dBuV/m}.$
 $E[\text{dBuV/m}] = 15.6 + 95.2 = 110.8\text{dBuV/m}.$
 $E[\text{dBuV/m}] = 27 + 95.2 = 122.2\text{dBuV/m}$

Measurement data:

IEEE 802.11a

Freq. (MHz)	Ant.Pol. H/V	Reading (dBuv)	Ant/CF (dB)	Act (dBuv/m)	Limit (dBuv/m)	Note
5725.000	V	65.81	3.95	69.76	122.2	CH 149
5725.000	H	65.85	3.95	69.80	122.2	CH 149
5850.000	V	49.27	3.96	53.23	122.2	CH 165
5850.000	H	49.25	3.96	53.21	122.2	CH 165

IEEE 802.11n HT20

Freq. (MHz)	Ant.Pol. H/V	Reading (dBuv)	Ant/CF (dB)	Act (dBuv/m)	Limit (dBuv/m)	Note
5725.000	V	63.20	3.95	67.15	122.2	CH 149
5725.000	H	66.44	3.95	70.39	122.2	CH 149
5850.000	V	52.22	3.96	56.18	122.2	CH 165
5850.000	H	52.63	3.96	56.59	122.2	CH 165

IEEE 802.11ac HT20

Freq. (MHz)	Ant.Pol. H/V	Reading (dBuv)	Ant/CF (dB)	Act (dBuv/m)	Limit (dBuv/m)	Note
5725.000	V	64.32	3.95	68.27	122.2	CH 149
5725.000	H	66.30	3.95	70.25	122.2	CH 149
5850.000	V	51.12	3.96	55.08	122.2	CH 165
5850.000	H	50.75	3.96	54.71	122.2	CH 165

IEEE 802.11n HT40

Freq. (MHz)	Ant.Pol. H/V	Reading (dBuv)	Ant/CF (dB)	Act (dBuv/m)	Limit (dBuv/m)	Note
5725.000	V	64.64	3.95	68.59	122.2	CH 151
5725.000	H	67.73	3.95	71.68	122.2	CH 151
5850.000	V	47.83	3.96	51.79	122.2	CH 159
5850.000	H	46.82	3.96	50.78	122.2	CH 159

IEEE 802.11ac HT40


Freq. (MHz)	Ant.Pol. H/V	Reading (dBuv)	Ant/CF (dB)	Act (dBuv/m)	Limit (dBuv/m)	Note
5725.000	V	65.58	3.95	69.53	122.2	CH 151
5725.000	H	65.08	3.95	69.03	122.2	CH 151
5850.000	V	44.35	3.96	48.31	122.2	CH 159
5850.000	H	47.22	3.96	51.18	122.2	CH 159



IEEE 802.11ac HT80

Freq. (MHz)	Ant.Pol. H/V	Reading (dBuv)	Ant/CF (dB)	Act (dBuv/m)	Limit (dBuv/m)	Note
5725.000	V	61.89	3.95	65.84	122.2	CH 155
5850.000	V	54.74	3.96	58.70	122.2	CH 155
5725.000	H	62.60	3.95	66.55	122.2	CH 155
5850.000	H	52.63	3.96	56.59	122.2	CH 155

7.7 Spurious Emission

7.7.1 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209, Part 15E Section 15.407(b)(4)				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 40GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9kHz-150KHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value
	150kHz-30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		AV	1MHz	3MHz	Average Value
Limit:	Frequency		Limit (uV/m)	Value	Measurement Distance
	0.009MHz-0.490MHz		2400/F(KHz)	QP	300m
	0.490MHz-1.705MHz		24000/F(KHz)	QP	300m
	1.705MHz-30MHz		30	QP	30m
	30MHz-88MHz		100	QP	3m
	88MHz-216MHz		150	QP	
	216MHz-960MHz		200	QP	
	960MHz-1GHz		500	QP	
	Frequency		Limit (dBm/MHz)		Remark
Above 1GHz		-27.0		Peak Value	
Test setup:	For radiated emissions from 9kHz to 30MHz				
					
	For radiated emissions from 30MHz to1GHz				

	 For radiated emissions above 1GHz 
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 7. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test

	worst case mode is recorded in the report.					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Remarks:

1. Only the worst case Main Antenna test data.
2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.


Measurement Data:**9 kHz ~ 30 MHz**

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Below 1GHz

Pre-scan all test modes, found worst case at 802.11ac(HT80), and so only show the test result of 802.11ac(HT80)


Horizontal:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		44.4308	24.06	-2.20	21.86	40.00	-18.14	peak
2		159.7844	32.54	-6.54	26.00	43.50	-17.50	peak
3		187.7530	32.40	-6.85	25.55	43.50	-17.95	peak
4		375.9385	37.41	-5.07	32.34	46.00	-13.66	peak
5		416.1791	34.92	-1.79	33.13	46.00	-12.87	peak
6	*	563.0695	34.70	4.42	39.12	46.00	-6.88	QP

Vertical:

80.0 dBuV



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
		MHz	Level	Factor	ment			Detector
			dBuV	dB	dBuV	dBuV	dB	
1		35.6240	25.92	-4.73	21.19	40.00	-18.81	peak
2		48.5016	25.95	-5.59	20.36	40.00	-19.64	peak
3		110.5687	24.83	-7.72	17.11	43.50	-26.39	peak
4		159.7844	32.83	-8.61	24.22	43.50	-19.28	peak
5		187.7530	37.01	-8.67	28.34	43.50	-15.16	peak
6	*	793.3960	25.66	7.69	33.35	46.00	-12.65	peak

Above 1GHz:

802.11a,11n(HT20),11ac(HT20),11n(HT40),11ac(HT40),11ac(HT80) all have been tested,
Only the data of worst case at each channel plan (nominal bandwidth =20MHz, 40MHz, 80MHz) is reported.

Test mode:		802.11a		Test channel:		lowest	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dBuV/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
V	11490	32.62	16.82	49.44	74.00	-24.56	PK
V	17235	29.65	22.93	52.58	74.00	-21.42	PK
H	11490	30.75	16.82	47.57	74.00	-26.43	PK
H	17235	29.24	22.93	52.17	74.00	-21.83	PK

Test mode:		802.11a		Test channel:		Middle	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dBuV/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
V	11570	32.07	16.71	48.78	74.00	-25.22	PK
V	17355	27.65	24.37	52.02	74.00	-21.98	PK
H	11570	29.78	16.71	46.49	74.00	-27.51	PK
H	17355	28.02	24.37	52.39	74.00	-21.61	PK

Test mode:		802.11a		Test channel:		Highest	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dBuV/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
V	11650	33.63	16.61	50.24	74.00	-23.76	PK
V	17475	27.64	25.01	52.65	74.00	-21.35	PK
H	11650	33.01	16.61	49.62	74.00	-24.38	PK
H	17475	28.36	25.01	53.37	74.00	-20.63	PK

Test mode:		802.11ac(HT40)		Test channel:		Lowest	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dBuV/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
V	11510	31.94	16.78	48.72	74.00	-25.28	PK
V	17265	27.61	23.29	50.90	74.00	-23.10	PK
H	11510	33.90	16.78	50.68	74.00	-23.32	PK
H	17265	28.62	23.29	51.91	74.00	-22.09	PK


Test mode:		802.11ac(HT40)		Test channel:		Highest	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dBuV/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
V	11590	30.38	16.69	47.07	74.00	-26.93	PK
V	17385	27.22	24.73	51.95	74.00	-22.05	PK
H	11590	31.81	16.69	48.50	74.00	-25.50	PK
H	17385	27.71	24.73	52.44	74.00	-21.56	PK

Test mode:		802.11ac(HT80)		Test channel:		Middle	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dBuV/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
V	11550	32.24	16.73	48.97	74.00	-25.03	PK
V	17325	26.71	24.01	50.72	74.00	-23.28	PK
H	11550	29.27	16.73	46.00	74.00	-28.00	PK
H	17325	25.61	24.01	49.62	74.00	-24.38	PK

Notes:

1. Measure Level = Reading Level + Factor.
2. The test trace is same as the ambient noise (the test frequency range: 18GHz~40GHz), therefore no data appear in the report.
3. This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

7.8 Frequency stability

Test Requirement:	FCC Part15 C Section 15.407(g)
Test Method:	ANSI C63.10:2013, FCC Part 2.1055
Limit:	Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified
Test Procedure:	The EUT was setup to ANSI C63.4, 2003; tested to 2.1055 for compliance to FCC Part 15.407(g) requirements.
Test setup:	 Note : Measurement setup for testing on Antenna connector
Test Instruments:	Refer to section 5.10 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement data:

HT 20MHz					
Frequency stability versus Temp.					
Power Supply: AC 120V					
Temp. (°C)	Operating Frequency (MHz)	0 minute Measured Frequency (MHz)	2 minute Measured Frequency (MHz)	5 minute Measured Frequency (MHz)	10 minute Measured Frequency (MHz)
-30	5745	5744.9511	5745.0117	5745.0183	5745.1124
	5785	5785.0583	5784.9106	5785.0350	5785.0145
	5825	5825.1050	5825.1060	5824.9703	5824.9676
-20	5745	5744.9816	5745.0827	5744.9435	5745.0467
	5785	5785.0948	5785.0206	5784.9222	5785.0939
	5825	5825.0372	5824.9979	5824.9991	5825.0246
-10	5745	5745.0880	5745.0221	5745.0899	5744.9555
	5785	5785.0492	5785.0827	5785.0310	5785.0539
	5825	5825.0684	5824.9539	5825.0468	5825.0165
0	5745	5744.9190	5745.0718	5744.9176	5745.0473
	5785	5785.0320	5785.0218	5784.9586	5784.9735
	5825	5825.0152	5825.0427	5824.9339	5825.0357
10	5745	5745.0007	5745.0882	5744.9145	5745.0433
	5785	5784.8924	5785.0761	5784.9015	5785.0016
	5825	5824.9728	5824.9280	5824.9609	5824.9799
20	5745	5744.9083	5745.0739	5745.0036	5745.0701
	5785	5784.9657	5785.0225	5785.0456	5785.0614
	5825	5825.0186	5825.0487	5824.9318	5824.9958
30	5745	5745.0149	5744.9553	5745.0408	5744.9081
	5785	5784.9710	5784.9456	5785.0415	5784.9199
	5825	5824.9059	5824.9860	5824.9789	5825.0136
40	5745	5744.9511	5745.0117	5745.0183	5745.1124
	5785	5785.0583	5784.9106	5785.0350	5785.0145
	5825	5825.1050	5825.1060	5824.9703	5824.9676
50	5745	5745.0857	5745.0541	5744.9638	5744.9351
	5785	5785.0767	5785.0402	5785.0331	5784.9350
	5825	5825.0516	5824.9875	5824.9239	5825.0403

Frequency stability versus Voltage					
Temperature: 25°C					
Power Supply (VAC)	Operating Frequency (MHz)	0 minute Measured Frequency (MHz)	2 minute Measured Frequency (MHz)	5 minute Measured Frequency (MHz)	10 minute Measured Frequency (MHz)
108	5745	5744.9587	5744.9485	5745.0574	5745.0416
	5785	5785.0181	5784.9096	5784.9071	5785.0553
	5825	5825.0299	5825.1145	5824.9365	5824.9866
120	5745	5745.0517	5744.9982	5745.0366	5744.9324
	5785	5785.1119	5784.9733	5785.0012	5785.0095
	5825	5824.9057	5825.0435	5824.9878	5824.9312
132	5745	5745.0176	5745.0724	5745.0969	5744.9776
	5785	5784.9956	5785.0571	5785.0273	5785.0096
	5825	5824.9424	5824.9574	5825.0800	5825.0584

HT40 MHz					
Frequency stability versus Temp.					
Power Supply: AC 120V					
Temp. (°C)	Operating Frequency (MHz)	0 minute Measured Frequency (MHz)	2 minute Measured Frequency (MHz)	5 minute Measured Frequency (MHz)	10 minute Measured Frequency (MHz)
-30	5745	5745.0904	5745.0268	5745.0077	5744.9955
	5785	5785.0437	5785.0968	5785.0672	5784.9182
-20	5825	5824.9680	5825.1045	5825.1156	5824.9228
	5745	5744.9431	5745.0355	5744.9644	5744.9606
-10	5785	5784.9847	5785.0157	5785.0889	5785.0092
	5825	5825.0574	5824.9458	5824.9376	5824.9542
0	5745	5745.0506	5744.9817	5745.1039	5744.9485
	5785	5785.0192	5785.0808	5784.9244	5784.9508
10	5825	5824.9499	5824.9694	5825.0977	5825.0864
	5745	5745.0832	5744.9980	5745.0252	5744.9960
20	5785	5784.9880	5784.9458	5784.9098	5784.9153
	5825	5825.0600	5824.9893	5824.9897	5824.9810
30	5745	5744.9358	5745.0408	5744.9716	5744.9408
	5785	5785.0102	5785.0190	5785.0433	5784.9865
40	5825	5744.9370	5745.0052	5744.9763	5745.0277
	5745	5785.0922	5784.9945	5785.0021	5785.0242
50	5785	5825.0654	5825.0527	5825.0571	5825.0049
	5825	5744.9598	5744.9852	5745.0359	5745.0002

Frequency stability versus Voltage					
Temperature: 25°C					
Power Supply (VAC)	Operating Frequency (MHz)	0 minute Measured Frequency (MHz)	2 minute Measured Frequency (MHz)	5 minute Measured Frequency (MHz)	10 minute Measured Frequency (MHz)
108	5745	5745.0933	5745.0817	5745.0755	5745.0274
	5785	5784.9648	5784.9231	5784.9425	5785.0059
120	5825	5824.9949	5825.0793	5825.0519	5824.9203
	5745	5745.0294	5744.9636	5744.9905	5745.0331
132	5785	5785.0564	5785.1080	5785.0928	5785.0746
	5825	5825.0748	5824.9173	5825.0535	5824.9885

HT80 MHz					
Frequency stability versus Temp.					
Power Supply: AC 120V					
Temp. (°C)	Operating Frequency (MHz)	0 minute	2 minute	5 minute	10 minute
		Measured Frequency (MHz)	Measured Frequency (MHz)	Measured Frequency (MHz)	Measured Frequency (MHz)
-30	5745	5744.9330	5744.9765	5744.9782	5745.0380
-20	5785	5785.0886	5785.0153	5785.0804	5785.0156
-10	5825	5825.0808	5824.9271	5825.0889	5824.9513
0	5745	5745.0247	5744.9990	5745.0654	5744.9786
10	5785	5784.9430	5785.0144	5785.1056	5784.9950
20	5825	5825.0070	5824.9465	5824.9451	5824.9937
30	5745	5745.0490	5745.0422	5745.0805	5745.0013
40	5785	5785.0474	5784.9270	5784.9685	5784.9104
50	5825	5825.0508	5825.0427	5824.9739	5824.9546

Frequency stability versus Voltage					
Temperature: 25°C					
Power Supply (VAC)	Operating Frequency (MHz)	0 minute	2 minute	5 minute	10 minute
		Measured Frequency (MHz)	Measured Frequency (MHz)	Measured Frequency (MHz)	Measured Frequency (MHz)
108	5745	5745.0758	5744.9687	5745.0202	5745.0529
120	5785	5785.0031	5785.0419	5784.9949	5784.9285
132	5825	5824.9084	5824.9210	5825.0471	5825.0326

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

-----END-----