



RF EXPOSURE

Test Report

Report No.: MTi230302018-05E2

Date of issue: 2023-05-31

Applicant: Shenzhen JideTech Development Co., Limited

Product: IP Camera

Model(s): D1, D2, D3, D4, D5, P9, P16, P18, S5, S7

FCC ID: 2AWZ2-D1

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>



Instructions

1. The report shall not be partially reproduced without the written consent of the laboratory;
2. The test results of this report are only responsible for the samples submitted;
3. This report is invalid without the seal and signature of the laboratory;
4. This report is invalid if transferred, altered or tampered with in any form without authorization;
5. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.



Test Result Certification	
Applicant:	ShenZhen JideTech Development Co., Limited
Address:	A916 Niulanqian Building Minzhi Avenue Xinniu Community, Minzhi Street, Longhua District, Shenzhen, China.
Manufacturer:	ShenZhen JideTech Development Co., Ltd
Address:	4F, Building 1, Peace Industrial Park, Shitouling, LongHua Street, Longhua District, Shenzhen, China 518027
Product description	
Product name:	IP Camera
Trademark:	JideTech
Model name:	D1
Serial Model:	D2, D3, D4, D5, P9, P16, P18, S5, S7
Standards:	N/A
Test procedure:	KDB 447498 D01 v06
Date of Test	
Date of test:	2023-04-27 ~ 2023-05-25
Test result:	Pass

Test Engineer :

Yanice Xie

(Yanice Xie)

Reviewed By :

Leon Chen

(Leon Chen)

Approved By :

Tom Xue

(Tom Xue)



RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Friis transmission formula: $Pd = (Pout * G) / (4 * \pi * R^2)$

Where

Pd= Power density in mW/cm²

Pout=output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

$\pi=3.1415926$

R= distance between observation point and center of the radiator in cm(20cm)

Pd the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.



Measurement Result

2.4G WiFi:

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz,

Power density limited: 1mW/ cm²

Antenna Type: FPC Antenna;

WIFI antenna gain: 2.98dBi

R=20cm

mW=10^(dBm/10)

antenna gain Numeric=10^(dBi/10)= 10^(2.98/10)=1.99

2.4G WiFi:

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits (mW/cm ²)
		(dBm)	(dBm)	tune-up power	Gain			
		(dBm)	(mW)	Numeric				
2412	802.11b	16.40	17±1	18	63.096	1.99	0.02493	1
2437		16.8	17±1	18	63.096	1.99	0.02493	1
2462		17.47	17±1	18	63.096	1.99	0.02493	1
2412	802.11g	17.9	17±1	18	63.096	1.99	0.02493	1
2437		17.5	17±1	18	63.096	1.99	0.02493	1
2462		18.15	18±1	19	79.433	1.99	0.03139	1
2412	802.11n H20	17.94	17±1	18	63.096	1.99	0.02493	1
2437		17.62	17±1	18	63.096	1.99	0.02493	1
2462		18.02	18±1	19	79.433	1.99	0.03139	1

Conclusion:

For the max result: 0.03139≤ 1.0 SAR, No SAR is required.

----END OF REPORT----