



MPE REPORT

FCC ID:2AWZ2-P2

Date of issue: Aug. 17, 2020

Report number: MTi20070619-5E2

Sample description: PTZ Camera

Model(s): P2, P3, P4, P6, P7, P9, P10, P12, P14, P16

Applicant: Shenzhen JideTech Development Co., Limited

Address: A916 Niulanqian Building Minzhi Avenue Xinniu Community,
Minzhi Street, Longhua District, Shenzhen City

Date of test: July 20, 2020 to Aug. 17, 2020

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>

This test report is valid for the tested samples only. It cannot be reproduced except in full without prior written consent of Shenzhen Microtest Co., Ltd.

Tel:(86-755)88850135

Fax: (86-755) 88850136

Web: <http://www.mtitest.com>

E-mail: mti@51mti.com

Address: 101, No. 7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen,
Guangdong, China.



TEST RESULT CERTIFICATION	
Applicant's name:	Shenzhen JideTech Development Co., Limited
Address:	A916 Niulanqian Building Minzhi Avenue Xinniu Community, Minzhi Street, Longhua District, Shenzhen City
Manufacture's name:	Shenzhen YGH Electronic Equipment Co., Ltd
Address:	3 / F, Building D, Liangxiang Industrial Zone, No. 269 Fuqian Road, Fucheng Street, Guanlan, Shenzhen, China
Product name:	PTZ Camera
Trademark:	JideTech
Model and/or type reference:	P2
Serial model:	P3, P4, P6, P7, P9, P10, P12, P14, P16
RF exposure procedures:	KDB 447498 D01 v06

This device described above has been tested by Shenzhen Microtest Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Tested by:

Demi Mu

Aug. 17, 2020

Reviewed by:

Leo Su

Aug. 17, 2020

Approved by:

Tom Xue

Aug. 17, 2020



RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d= Power density in mW/cm²

P_{out}=output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

$\pi=3.1415926$

R= distance between observation point and center of the radiator in cm(20cm)

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.



Measurement Result

WIFI:

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz,

802.11n HT40: 2422-2452MHz,

Power density limited: 1mW/ cm²

Antenna Type: External Antenna;

WIFI antenna gain: 3dBi

R=20cm

mW=10^(dBm/10)

antenna gain Numeric=10^(dBi/10)= 10^(3/10)=2

Chann el Freq. (MHz)	modulatio n	conducte d power	Tune -up powe r	Max		Ante nna	Evaluation result at 20cm	Power density Limits (mW/cm 2)
				(dBm)	tune-up power (dBm)	Gain (dBm)	Num eric	
		Ant A	Ant A	Ant A	Ant A	Ant A	Ant A	
2412	802.11b	16.4	17±1	18	63.095734	2	0.02510	1
2437		17.08	17±1	18	63.095734	2	0.02510	1
2462		16.88	17±1	18	63.095734	2	0.02510	1
2412	802.11g	13.64	13±1	14	25.118864	2	0.00999	1
2437		13.91	13±1	14	25.118864	2	0.00999	1
2462		13.97	13±1	14	25.118864	2	0.00999	1
2412	802.11n H20	13.77	14±1	15	31.622777	2	0.01258	1
2437		14.04	14±1	15	31.622777	2	0.01258	1
2462		14.02	14±1	15	31.622777	2	0.01258	1
2422	802.11n H40	14.13	14±1	15	31.622777	2	0.01258	1
2437		14.09	14±1	15	31.622777	2	0.01258	1
2452		14.25	14±1	15	31.622777	2	0.01258	1

Conclusion:

For the max result: 0.02510≤ 1.0 for 1g SAR, No SAR is required.

----END OF REPORT----