



Test Report

No.: AJT250402021EA-4

Applicant Name: GUANGDONG HENGDI TECHNOLOGY CORP.,LTD.
Applicant Address: BUILDING C, JINHUI INDUSTRIAL BUILDING, SOUTH OF YUTING
ROAD, EAST OF TAIAN ROAD, CHENGHAI DISTRICT, SHANTOU
CITY, GUANGDONG PROVINCE, CHINA
Manufacturer: GUANGDONG HENGDI TECHNOLOGY CORP.,LTD.
Manufacturer Address: BUILDING C, JINHUI INDUSTRIAL BUILDING, SOUTH OF YUTING
ROAD, EAST OF TAIAN ROAD, CHENGHAI DISTRICT, SHANTOU
CITY, GUANGDONG PROVINCE, CHINA

The following samples were submitted and identified by/on behalf of the client as:

Sample Description: RC TOY
Model No.: 2411SE
Additional Model: Please refer to page 3
FCC ID: 2AWZK-2411SECAM
Sample Received Date: 02 April, 2025
Testing Completed Date: 21 June, 2025

Tests conducted: For compliance with application, refer to attached page(s) for details.

Assess standard used:	Conclusion
FCC Part 1.1307	PASS

NOTE: This report supersedes the original report of AJT250402021E-4, FCC ID were revised.

Tested by: Glory

Reviewed by: Fly Liang

Approved by: Gordano

Position: Technical Supervisor

Date: 2025-07-15



This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Disagreement against this test report, if any, should be filed with to our company in writing within 15 days of receiving the report. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission.

AJT TESTING SERVICES LIMITED

Add: 1-2/F., No.1, Wenhua South Road, Chenghua Industrial Zone, Chenghai District, Shantou, Guangdong, China
Tel: 86-754-85860999 Fax: 86-754-86984098 Website: www.ajtesting.com Email: info@ajtesting.com





Test Report

No.: AJT250402021EA-4

TABLE OF CONTENTS

1 Test Standards3
2 Summary3
2.1 General Remarks.....	.3
3 General Information3
3.1 General Description of E.U.T.....	.3
3.2 Details of E.U.T.....	.4
4 Test Summary4
5 RF Exposure5
5.1 Requirements5
5.2 The procedures / limit5
5.3 MPE Calculation Method6
5.4 Result: Compliance.....	.6

This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Disagreement against this test report, if any, should be filed with to our company in writing within 15 days of receiving the report. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission.

AJT TESTING SERVICES LIMITED

Add: 1-2/F., No.1, Wenhua South Road, Chenghua Industrial Zone, Chenghai District, Shantou, Guangdong, China
Tel: 86-754-85860999 Fax: 86-754-86984098 Website: www.ajttesting.com Email: info@ajttesting.com





Test Report

No.: AJT250402021EA-4

1 Test Standards

The tests were performed according to following standards:
FCC Part 1.1307: Actions that may have a significant environmental effect, for which Environmental Assessments (EAs) must be prepared.
FCC Part 2.1091 & KDB 447498 D01 General RF Exposure Guidance v06

2 Summary

2.1 General Remarks

Date of receipt of test sample	02 April, 2025
Testing commenced on	02 April, 2025 ---- 21 June, 2025
Testing concluded on	21 June, 2025

3 General Information

3.1 General Description of E.U.T.

Product:	RC TOY
Model(s):	2411SE
Additional Model:	2306SE, 2308SE, 2316SE, 2418SE, 2411, 2411W, 2411S, 2418, 2418W, 2301, 2303, 2305, 2306, 2308, 2310, 2313, 2314, 2316A, 2316D, 2316W, 2316DW, 2320, 2323, 2202, 2205, 2205D, 2209H, 2215, 2216, 2106, 2106S, 2003, 2013, 1336, 1340, 1303, 1343A, 1339A, 1818, H20, H24, H26, H36, H65, HQ051, HQ051S, HQ052, HQ052S, HQ053, HQ056, HQ057, HQ058, BD101, BD102, 2008A, 2101, 2405, 2104, 2201, 2420, 2008B, 2213, 2401, 2409-1, 2409-2, 2409-4, 1802, 1802-4, 1906S, 1906, 1902, 1903, 2416, 1915, 1905-1, 1905-2, DB1-1, DB2-1, DB3-1, DB1-2, DB2-3, DB2-4, DB2-5, 1801SE, 2501, 2502, 2414, 2503, 2504, 2505, 2506, 2507, 2508, 2509, 2510, 40037, 2103, ODY-7500, ODY-1026, ODY-01SI, ODY-02SI, ODY-03SI, ODY-1208HRN, ODY-1208WT, ODY-1012BR, ODY-1956
FCC ID:	2AWZK-2411SECAM
Wi-Fi Specification:	2.4G-802.11b/g/n HT20
Antenna Gain:	2.0dBi
NOTE:	<p>1. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual. The laboratory is not responsible for the accuracy of the information provided by manufacturer.</p> <p>2. Product models same are identical in the PCB layout, electrical circuit design and functions, The differences are appearance color, exterior structure, and model name for commercial purpose.</p>

This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Disagreement against this test report, if any, should be filed with to our company in writing within 15 days of receiving the report. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission.

AJT TESTING SERVICES LIMITED

Add: 1-2/F., No.1, Wenhua South Road, Chenghua Industrial Zone, Chenghai District, Shantou, Guangdong, China
Tel: 86-754-85860999 Fax: 86-754-86984098 Website: www.ajttesting.com Email: info@ajttesting.com





Test Report

No.: AJT250402021EA-4

3.2 Details of E.U.T.

Operation Frequency:	Wi-Fi: 802.11b/g/n HT20: 2412~2462MHz
Max. RF output power:	Wi-Fi (2.4G): 4.07dBm
Type of Modulation:	Wi-Fi: DSSS, OFDM
Antenna installation:	Wi-Fi: External antenna,
Antenna Gain:	Wi-Fi (2.4G): 2.0dBi
Voltage:	DC 3.7V (Battery*1)
NOTE: 1. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual. The laboratory is not responsible for the accuracy of the information provided by manufacturer.	

4 Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307	PASS

This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Disagreement against this test report, if any, should be filed with to our company in writing within 15 days of receiving the report. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission.

AJT TESTING SERVICES LIMITED

Add: 1-2/F., No.1, Wenhua South Road, Chenghua Industrial Zone, Chenghai District, Shantou, Guangdong, China
Tel: 86-754-85860999 Fax: 86-754-86984098 Website: www.ajttesting.com Email: info@ajttesting.com





Test Report

No.: AJT250402021EA-4

5 RF Exposure

Test Requirement:	FCC Part 1.1307
Evaluation Method:	FCC Part 2.1091 & KDB 447498 D01 General RF Exposure Guidance v06

5.1 Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

5.2 The procedures / limit

(A) Limits for Occupational / Controlled Exposure

Frequency Range(MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz; *Plane-wave equivalent power density

This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Disagreement against this test report, if any, should be filed with to our company in writing within 15 days of receiving the report. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission.

AJT TESTING SERVICES LIMITED

Add: 1-2/F., No.1, Wenhua South Road, Chenghua Industrial Zone, Chenghai District, Shantou, Guangdong, China
Tel: 86-754-85860999 Fax: 86-754-86984098 Website: www.ajttesting.com Email: info@ajttesting.com





Test Report

No.: AJT250402021EA-4

5.3 MPE Calculation Method

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = output power to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

From the peak EUT RF output power, the minimum mobile separation distance, R=20cm, as well as the gain of the used antenna, the RF power density can be obtained

Mode 1: alone transmission

Mode	Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Output Power (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
2.4G WIFI	2.0	1.585	4.07	2.553	0.0008	1

5.4 Result: Compliance

No SAR measurement is required.

END OF TEST REPORT

This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Disagreement against this test report, if any, should be filed with to our company in writing within 15 days of receiving the report. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission.

AJT TESTING SERVICES LIMITED

Add: 1-2/F., No.1, Wenhua South Road, Chenghua Industrial Zone, Chenghai District, Shantou, Guangdong, China
Tel: 86-754-85860999 Fax: 86-754-86984098 Website: www.ajttesting.com Email: info@ajttesting.com

