

## INTERTEK TESTING SERVICES

---

### RF Exposure

The equipment under test (EUT) is a Drone 5inch Flying Car operating at 2.4G Band. The EUT can be powered by DC 6.0V (4 x 1.5V AA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: -1.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -1.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498 V06:

The Maximum peak radiated emission for the EUT is 94.1dBμV/m at 3m in the frequency 2420MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = -1.13dBm  
which is within the production variation.

The Minimum peak radiated emission for the EUT is 93.7dBμV/m at 3m in the frequency 2470MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = -1.53dBm  
which is within the production variation.

The maximum conducted output power specified is 2dBm = 1.585mW

The source- based time-averaging conducted output power  
= 1.585mW

The SAR Exclusion Threshold Level:

=  $3.0 \cdot (\text{min. test separation distance, mm}) / \sqrt{\text{freq. in GHz}}$

=  $3.0 \cdot 5 / \sqrt{2.470}$  mW

= 9.54 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

---

FCC ID: 2AWZKHD24C24G