

# FCC Radio Test Report

## FCC ID: 2AX45-SAFETEC

### Original Grant

**Report No.** : TB-FCC175040

**Applicant** : Ladner Creek Enterprise Ltd.

#### Equipment Under Test (EUT)

**EUT Name** : THERMAL SECURITY SYSTEM

**Model No.** : SAFETEC V1

**Series Model No.** : SAFETEC V1-D, SAFETEC V1-K, SAFETEC V1-O, SAFETEC V1-W

**Brand Name** : MIXONTEC

**Sample ID** : TBBJ-20200723-10-1# & TBBJ-20200723-10-2#

**Receipt Date** : 2020-08-20

**Test Date** : 2020-08-21 to 2020-09-28

**Issue Date** : 2020-09-28

**Standards** : FCC Part 15, Subpart C 15.247

**Test Method** : ANSI C63.10: 2013

**Conclusions** : **PASS**

In the configuration tested, the EUT complied with the standards specified above,

The EUT technically complies with the FCC requirements

**Test/Witness Engineer** :



Jack Deng




**Engineer Supervisor** :



Ivan Su

**Engineer Manager** :



Ray Lai

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

## Contents

<b>1.</b>	<b>GENERAL INFORMATION ABOUT EUT .....</b>	<b>5</b>
1.1	Client Information .....	5
1.2	General Description of EUT (Equipment Under Test) .....	5
1.3	Block Diagram Showing the Configuration of System Tested .....	6
1.4	Description of Support Units .....	7
1.6	Description of Test Software Setting .....	8
1.7	Measurement Uncertainty .....	8
1.8	Test Facility .....	9
<b>2.</b>	<b>TEST SUMMARY .....</b>	<b>10</b>
<b>3.</b>	<b>TEST SOFTWARE .....</b>	<b>10</b>
<b>4.</b>	<b>TEST EQUIPMENT .....</b>	<b>11</b>
<b>5.</b>	<b>CONDUCTED EMISSION TEST .....</b>	<b>12</b>
5.1	Test Standard and Limit .....	12
5.2	Test Setup .....	12
5.3	Test Procedure .....	13
5.4	Deviation From Test Standard .....	13
5.5	EUT Operating Mode .....	13
5.6	Test Data .....	13
<b>6.</b>	<b>RADIATED EMISSION TEST .....</b>	<b>14</b>
6.1	Test Standard and Limit .....	14
6.2	Test Setup .....	15
6.3	Test Procedure .....	16
6.4	Deviation From Test Standard .....	17
6.5	EUT Operating Condition .....	17
6.6	Test Data .....	17
<b>7.</b>	<b>RESTRICTED BANDS REQUIREMENT .....</b>	<b>18</b>
7.1	Test Standard and Limit .....	18
7.2	Test Setup .....	18
7.3	Test Procedure .....	18
7.4	Deviation From Test Standard .....	19
7.5	EUT Operating Condition .....	19
7.6	Test Data .....	19
<b>8.</b>	<b>BANDWIDTH TEST .....</b>	<b>20</b>
8.1	Test Standard and Limit .....	20
8.2	Test Setup .....	20
8.3	Test Procedure .....	20
8.4	Deviation From Test Standard .....	20
8.5	EUT Operating Condition .....	20
8.6	Test Data .....	20
<b>9.</b>	<b>PEAK OUTPUT POWER TEST .....</b>	<b>21</b>

---

9.1 Test Standard and Limit.....	21
9.2 Test Setup.....	21
9.3 Test Procedure.....	21
9.4 Deviation From Test Standard.....	21
9.5 EUT Operating Condition .....	21
9.6 Test Data.....	21
<b>10. POWER SPECTRAL DENSITY TEST .....</b>	<b>22</b>
10.1 Test Standard and Limit .....	22
10.2 Test Setup.....	22
10.3 Test Procedure.....	22
10.4 Deviation From Test Standard.....	22
10.5 EUT Operating Condition .....	22
10.6 Test Data.....	22
<b>11. ANTENNA REQUIREMENT.....</b>	<b>23</b>
11.1 Standard Requirement.....	23
11.2 Deviation From Test Standard.....	23
11.3 Antenna Connected Construction .....	23
11.4 Result.....	23
<b>ATTACHMENT A-- CONDUCTED EMISSION TEST DATA .....</b>	<b>24</b>
<b>ATTACHMENT B-- RADIATED EMISSION TEST DATA .....</b>	<b>26</b>
<b>ATTACHMENT C-- RESTRICTED BANDS REQUIREMENT AND BAND EDGE TEST DATA .....</b>	<b>31</b>
<b>ATTACHMENT D-- BANDWIDTH TEST DATA.....</b>	<b>36</b>
<b>ATTACHMENT E-- PEAK OUTPUT POWER TEST DATA.....</b>	<b>38</b>
<b>ATTACHMENT F-- POWER SPECTRAL DENSITY TEST DATA.....</b>	<b>40</b>

## Revision History

Report No.	Version	Description	Issued Date
TB-FCC175040	Rev.01	Initial issue of report	2020-09-28

# 1. General Information about EUT

## 1.1 Client Information

<b>Applicant</b>	:	Ladner Creek Enterprise Ltd.
<b>Address</b>	:	Suite 103, 12300 Horseshoe Way, Richmond, BC, Canada V7A 4Z1
<b>Manufacturer</b>	:	BEIJING BLUESTONE TECHNOLOGY CORP.
<b>Address</b>	:	Commercial Building 387, 3rd Floor, Building 1, Zhongxi Garden, Haidian District, Beijing, China

## 1.2 General Description of EUT (Equipment Under Test)

<b>EUT Name</b>	:	THERMAL SECURITY SYSTEM	
<b>Models No.</b>	:	SAFETEC V1, SAFETEC V1-D, SAFETEC V1-K, SAFETEC V1-O, SAFETEC V1-W	
<b>Model Different</b>	:	All these models are identical in the same PCB, layout and electrical circuit, The only difference is way to install.	
<b>Product Description</b>	Operation Frequency:	Bluetooth 4.1(BLE): 2402MHz~2480MHz	
	Number of Channel:	Bluetooth 4.1(BLE): 40 channels	see note(3)
	RF Output Power:	BLE:0.211dBm (Max)	
	Antenna Gain:	2dBi Internal Antenna	
	Modulation Type:	GFSK	
	Bit Rate of Transmitter:	1Mbps(GFSK)	
<b>Power Rating</b>	:	Adapter(XED-UL120200CC) Input: AC 100~240V, 50/60Hz 0.6A Output: DC 12V, 2A.	
<b>Software Version</b>	:	2.0.8	
<b>Hardware Version</b>	:	N/A	
<b>Connecting I/O Port(S)</b>	:	Please refer to the User's Manual	
<b>Remark</b>	:	The antenna gain and adapter provided by the applicant, the verified for the RF conduction test provided by TOBY test lab.	

### Note:

This Test Report is FCC Part 15.247 for BLE, the test procedure follows the FCC KDB 558074 D01 DTS Means Guidance v05r02.

(1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.


(2) Antenna information provided by the applicant.

(3) Channel List:


Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	14	2430	28	2458
01	2404	15	2432	29	2460
02	2406	16	2434	30	2462
03	2408	17	2436	31	2464
04	2410	18	2438	32	2466
05	2412	19	2440	33	2468
06	2414	20	2442	34	2470
07	2416	21	2444	35	2472
08	2418	22	2446	36	2474
09	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454		
13	2428	27	2456		

### 1.3 Block Diagram Showing the Configuration of System Tested

#### Conducted Test



#### Radiated Test



## 1.4 Description of Support Units

Equipment Information				
Name	Model	FCC ID/VOC	Manufacturer	Used “√”
---	---	---	---	---
Cable Information				
Number	Shielded Type	Ferrite Core	Length	Note
Cable 1	Yes	NO	1.0M	Accessory

## 1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test	
Final Test Mode	Description
Mode 1	Charging+TX Mode

For Radiated Test	
Final Test Mode	Description
Mode 2	TX Mode(Channel 00)
Mode 3	TX 1Mbps Mode (Channel 00/20/39)
Mode 4	TX 2Mbps Mode (Channel 00/20/39)

### Note:

(1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate.

According to ANSI C63.10 standards, the measurements are performed at the highest, middle, lowest available channels, and the worst case data rate as follows:

BLE Mode: GFSK Modulation Transmitting mode.

- (2) During the testing procedure, the continuously transmitting with the maximum power mode was programmed by the customer.
- (3) The EUT is considered a Fixde unit; in normal use it was positioned on X-plane. The worst case was found positioned on X-plane. Therefore only the test data of this X-plane was used for radiated emission measurement test.

## 1.6 Description of Test Software Setting

During testing channel & Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of RF setting.

Test Software Version	com.example.comdemo-1.apk		
Frequency	2402 MHz	2442MHz	2480 MHz
BLE GFSK	DEF	DEF	DEF

## 1.7 Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty ( $U_{Lab}$ )
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	$\pm 3.50$ dB $\pm 3.10$ dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	$\pm 4.60$ dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	$\pm 4.50$ dB
Radiated Emission	Level Accuracy: Above 1000MHz	$\pm 4.20$ dB

## 1.8 Test Facility

The testing was performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at: 1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China.

At the time of testing, the following bodies accredited the Laboratory:

### **CNAS (L5813)**

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

### **A2LA Certificate No.: 4750.01**

The laboratory has been accredited by American Association for Laboratory Accreditation(A2LA) to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the technical competence in the field of Electrical Testing. And the A2LA Certificate No.: 4750.01. FCC Accredited Test Site Number: 854351.

### **IC Registration No.: (11950A)**

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A.

## 2. Test Summary

FCC Part 15 Subpart C(15.247)/RSS 247 Issue 2					
Standard Section		Test Item	Test Sample(s)	Judgment	Remark
FCC	IC				
15.203		Antenna Requirement	TBBJ-20200723-10-2#	PASS	N/A
15.207(a)	RSS-GEN 7.2.4	Conducted Emission	TBBJ-20200723-10-1#	PASS	N/A
15.205&15.247(d)	RSS-GEN 7.2.2	Band-Edge & Unwanted Emissions into Restricted Frequency	TBBJ-20200723-10-2#	PASS	N/A
15.247(a)(2)	RSS 247 5.2 (1)	6dB Bandwidth	TBBJ-20200723-10-2#	PASS	N/A
15.247(b)(3)	RSS 247 5.4 (4)	Conducted Max Output Power	TBBJ-20200723-10-2#	PASS	N/A
15.247(e)	RSS 247 5.2 (2)	Power Spectral Density	TBBJ-20200723-10-2#	PASS	N/A
15.205, 15.209&15.247(d)	RSS 247 5.5	Transmitter Radiated Spurious &Unwanted Emissions into Restricted Frequency	TBBJ-20200723-10-1# TBBJ-20200723-10-2#	PASS	N/A

**Note:** N/A is an abbreviation for Not Applicable.

## 3. Test Software

Test Item	Test Software	Manufacturer	Version No.
Conducted Emission	EZ-EMC	EZ	CDI-03A2
Radiation Emission	EZ-EMC	EZ	FA-03A2RE
RF Conducted Measurement	MTS-8310	MWRFtest	V2.0.0.0

## 4. Test Equipment

Conducted Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Jul. 06, 2020	Jul. 05, 2021
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jul. 06, 2020	Jul. 05, 2021
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jul. 06, 2020	Jul. 05, 2021
LISN	Rohde & Schwarz	ENV216	101131	Jul. 06, 2020	Jul. 05, 2021
Radiation Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 06, 2020	Jul. 05, 2021
EMI Test Receiver	Rohde & Schwarz	ESPI	100010/007	Jul. 06, 2020	Jul. 05, 2021
Spectrum Analyzer	Rohde & Schwarz	FSV40-N	102197	Jul. 06, 2020	Jul. 05, 2021
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Mar.01, 2020	Feb. 28, 2022
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar.01, 2020	Feb. 28, 2022
Horn Antenna	ETS-LINDGREN	BBHA 9170	BBHA9170582	Mar.01, 2020	Feb. 28, 2022
Loop Antenna	SCHWARZBECK	FMZB 1519 B	1519B-059	Jul. 07, 2020	Jul. 06, 2021
Pre-amplifier	Sonoma	310N	185903	Mar.01, 2020	Feb. 28, 2021
Pre-amplifier	HP	8449B	3008A00849	Mar.01, 2020	Feb. 28, 2021
Pre-amplifier	SKET	LNPA_1840G-50	SK201904032	Mar.01, 2020	Feb. 28, 2021
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar.01, 2020	Feb. 28, 2021
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A
Antenna Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 06, 2020	Jul. 05, 2021
Spectrum Analyzer	Rohde & Schwarz	ESPI	100010/007	Jul. 06, 2020	Jul. 05, 2021
MXA Signal Analyzer	Agilent	N9020A	MY49100060	Sep. 11, 2020	Sep. 10, 2021
Vector Signal Generator	Agilent	N5182A	MY50141294	Sep. 11, 2020	Sep. 10, 2021
Analog Signal Generator	Agilent	N5181A	MY50141953	Sep. 11, 2020	Sep. 10, 2021
RF Power Sensor	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO26	Sep. 11, 2020	Sep. 10, 2021
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO29	Sep. 11, 2020	Sep. 10, 2021
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO31	Sep. 11, 2020	Sep. 10, 2021
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO33	Sep. 11, 2020	Sep. 10, 2021

## 5. Conducted Emission Test

### 5.1 Test Standard and Limit

5.1.1 Test Standard  
FCC Part 15.207

5.1.2 Test Limit


Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dB $\mu$ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Notes:

- (1) \*Decreasing linearly with logarithm of the frequency.
- (2) The lower limit shall apply at the transition frequencies.
- (3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 5.2 Test Setup



### 5.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis.

The bandwidth of EMI test receiver is set at 9 kHz, and the test frequency band is from 0.15MHz to 30MHz.

### 5.4 Deviation From Test Standard

No deviation

### 5.5 EUT Operating Mode

Please refer to the description of test mode.

### 5.6 Test Data

Please refer to the Attachment A.

## 6. Radiated Emission Test

### 6.1 Test Standard and Limit

6.1.1 Test Standard  
FCC Part 15.247(d)

6.1.2 Test Limit

#### Radiated Emission Limits (9kHz~1000MHz)

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3



#### Radiated Emission Limit (Above 1000MHz)


Frequency (MHz)	Distance Meters(at 3m)	
	Peak (dBuV/m)	Average (dBuV/m)
Above 1000	74	54

**Note:**

- (1) The tighter limit applies at the band edges.
- (2) Emission Level (dBuV/m)=20log Emission Level (uV/m)

## 6.2 Test Setup





Above 1GHz Test Setup

### 6.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

## 6.4 Deviation From Test Standard

No deviation

## 6.5 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

## 6.6 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

Please refer to the Attachment B.

## 7. Restricted Bands Requirement

### 7.1 Test Standard and Limit


#### 7.1.1 Test Standard

FCC Part 15.247(d) FCC Part 15.205

#### 7.1.2 Test Limit

Restricted Frequency Band (MHz)	Distance Meters(at 3m)	
	Peak (dBuV/m)	Average (dBuV/m)
2310 ~2390	74	54
2483.5 ~2500	74	54

### 7.2 Test Setup



### 7.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector

mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.

- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Below 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use  $VBW=120$  kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use  $RBW=1$  MHz and  $VBW=3$  MHz with Peak Detector for Peak Values, and use  $RBW=1$  MHz and  $VBW=10$  Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

#### 7.4 Deviation From Test Standard

No deviation

#### 7.5 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

#### 7.6 Test Data

Remark: During testing above 1GHz the measuring instrument use  $RBW=1$  MHz and  $VBW=3$  MHz with Peak Detector for Peak Values, and use  $RBW=1$  MHz and  $VBW=10$  Hz with Peak Detector for Average Values.

Please refer to the Attachment C.

## 8. Bandwidth Test

### 8.1 Test Standard and Limit


#### 8.1.1 Test Standard

FCC Part 15.247 (a)(2)

#### 8.1.2 Test Limit

FCC Part 15 Subpart C(15.247)/RSS-247		
Test Item	Limit	Frequency Range(MHz)
Bandwidth	>=500 KHz (6dB bandwidth)	2400~2483.5

### 8.2 Test Setup



### 8.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) The bandwidth is measured at an amplitude level reduced 6dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst -case (i.e the widest) bandwidth.
- (3) Measure the channel separation the spectrum analyzer was set to Resolution Bandwidth:100 kHz, and Video Bandwidth:300 kHz, Detector: Peak, Sweep Time set auto.

### 8.4 Deviation From Test Standard

No deviation

### 8.5 EUT Operating Condition

The EUT was set to continuously transmitting in each mode and low, middle and high channel for the test.

### 8.6 Test Data

Please refer to the Attachment D.

## 9. Peak Output Power Test

### 9.1 Test Standard and Limit


#### 9.1.1 Test Standard

FCC Part 15.247 (b)(3)

#### 9.1.2 Test Limit

FCC Part 15 Subpart C(15.247)/RSS-247		
Test Item	Limit	Frequency Range(MHz)
Peak Output Power	1 Watt or 30 dBm	2400~2483.5

### 9.2 Test Setup



### 9.3 Test Procedure

The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement is according to section 9.1.1 of KDB 558074 D01 DTS Meas Guidance v05r02.

- (1) Set the  $RBW \geq DTS$  Bandwidth
- (2) Set  $VBW \geq 3 * RBW$
- (3) Set  $Span \geq 3 * RBW$
- (4) Sweep time=auto
- (5) Detector= peak
- (6) Trace mode= max hold.
- (7) Allow trace to fully stabilize, and then use peak marker function to determine the peak amplitude level.

### 9.4 Deviation From Test Standard

No deviation

### 9.5 EUT Operating Condition

The EUT was set to continuously transmitting in the max power during the test.

### 9.6 Test Data

Please refer to the Attachment E.

## 10. Power Spectral Density Test

### 10.1 Test Standard and Limit


#### 10.1.1 Test Standard

FCC Part 15.247 (e)

#### 10.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	Limit	Frequency Range(MHz)
Power Spectral Density	8dBm(in any 3 kHz)	2400~2483.5

### 10.2 Test Setup



### 10.3 Test Procedure

The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to section 10.2 of KDB 558074 D01 DTS Meas Guidance v05r02.

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Set analyser centre frequency to DTS channel centre frequency.
- (3) Set the span to 1.5 times the DTS bandwidth.
- (4) Set the RBW to: 3 kHz
- (5) Set the VBW to: 10 kHz
- (6) Detector: peak
- (7) Sweep time: auto
- (8) Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.

### 10.4 Deviation From Test Standard

No deviation

### 10.5 EUT Operating Condition

The EUT was set to continuously transmitting in each mode and low, Middle and high channel for the test.

### 10.6 Test Data

Please refer to the Attachment F.

## 11. Antenna Requirement

### 11.1 Standard Requirement

#### 11.1.1 Standard

FCC Part 15.203

#### 11.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### 11.2 Deviation From Test Standard

No deviation

### 11.3 Antenna Connected Construction

The gains of the antenna used for transmitting is 2 dBi, and the antenna de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.


### 11.4 Result

The EUT antenna is a Internal Antenna. It complies with the standard requirement.

Antenna Type
<input type="checkbox"/> Permanent attached antenna
<input checked="" type="checkbox"/> Unique connector antenna
<input type="checkbox"/> Professional installation antenna

## Attachment A-- Conducted Emission Test Data


Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V 60Hz		
Terminal:	Line		
Test Mode:	Mode 1		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB	dBuV	dBuV	dB
1	*	0.1539	41.66	9.70	51.36	65.78	-14.42
2		0.1539	27.37	9.70	37.07	55.78	-18.71
3		0.2179	32.66	9.70	42.36	62.89	-20.53
4		0.2179	16.56	9.70	26.26	52.89	-26.63
5		0.2660	30.56	9.70	40.26	61.24	-20.98
6		0.2660	20.44	9.70	30.14	51.24	-21.10
7		0.3180	29.98	9.70	39.68	59.76	-20.08
8		0.3180	19.42	9.70	29.12	49.76	-20.64
9		0.3738	28.99	9.70	38.69	58.41	-19.72
10		0.3738	15.99	9.70	25.69	48.41	-22.72
11		4.1418	19.77	9.90	29.67	56.00	-26.33
12		4.1418	9.75	9.90	19.65	46.00	-26.35

## Remark:

1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB)
2. Margin (dB) = QuasiPeak/Average (dBuV)-Limit (dBuV)

Temperature:	25°C	Relative Humidity:	55%					
Test Voltage:	AC 120V 60Hz							
Terminal:	Neutral							
Test Mode:	Mode 1							
Remark:	Only worse case is reported							
								
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1	*	0.1539	41.56	9.80	51.36	65.78	-14.42	QP
2		0.1539	24.70	9.80	34.50	55.78	-21.28	AVG
3		0.1900	34.88	9.80	44.68	64.03	-19.35	QP
4		0.1900	19.87	9.80	29.67	54.03	-24.36	AVG
5		0.2580	30.87	9.80	40.67	61.49	-20.82	QP
6		0.2580	20.70	9.80	30.50	51.49	-20.99	AVG
7		0.3459	28.85	9.80	38.65	59.06	-20.41	QP
8		0.3459	20.80	9.80	30.60	49.06	-18.46	AVG
9		0.3820	27.89	9.80	37.69	58.23	-20.54	QP
10		0.3820	14.94	9.80	24.74	48.23	-23.49	AVG
11		0.5779	20.47	9.80	30.27	56.00	-25.73	QP
12		0.5779	9.95	9.80	19.75	46.00	-26.25	AVG
Remark:				1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB) 2. Margin (dB) = QuasiPeak/Average (dBuV)-Limit (dBuV)				

## Attachment B-- Radiated Emission Test Data


### 9 KHz~30 MHz

From 9 KHz to 30 MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB  
Below the permissible value has no need to be reported.

### 30MHz~1GHz

Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V 60Hz		
Ant. Pol.	Horizontal		
Test Mode:	Mode 2 2402MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1	!	247.6819	58.32	-17.68	40.64	46.00	-5.36
2		263.8190	56.04	-17.30	38.74	46.00	-7.26
3	!	346.8091	55.65	-15.03	40.62	46.00	-5.38
4		404.6664	48.33	-12.44	35.89	46.00	-10.11
5	*	528.2458	50.37	-9.66	40.71	46.00	-5.29
6		595.1326	46.08	-8.43	37.65	46.00	-8.35

#### Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. QuasiPeak (dB $\mu$ V/m)= Corr. (dB/m)+ Read Level (dB $\mu$ V)
3. Margin (dB) = QuasiPeak (dB $\mu$ V/m)-Limit QPK(dB $\mu$ V/m)

Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V 60Hz		
Ant. Pol.	Vertical		
Test Mode:	Mode 2 2402MHz		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		120.2766	55.92	-22.34	33.58	43.50	-9.92	QP
2		227.6904	54.85	-18.76	36.09	46.00	-9.91	QP
3	*	247.6819	55.31	-17.68	37.63	46.00	-8.37	QP
4		263.8190	54.59	-17.30	37.29	46.00	-8.71	QP
5		346.8091	51.06	-15.03	36.03	46.00	-9.97	QP
6		455.9057	49.47	-11.88	37.59	46.00	-8.41	QP

## Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. QuasiPeak (dB $\mu$ V/m)= Corr. (dB/m)+ Read Level (dB $\mu$ V)
3. Margin (dB) = QuasiPeak (dB $\mu$ V/m)-Limit QPK(dB $\mu$ V/m)

## Above 1GHz

<b>Temperature:</b>	25°C		<b>Relative Humidity:</b>	55%					
<b>Test Voltage:</b>	DC 12V								
<b>Ant. Pol.</b>	Horizontal								
<b>Test Mode:</b>	BLE Mode TX 2402 MHz								
<b>Remark:</b>	No report for the emission which more than 20 dB below the prescribed limit.								
<b>Remark:</b>	1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB $\mu$ V/m)= Corr. (dB/m)+ Read Level (dB $\mu$ V) 3. Margin (dB) = Peak/AVG (dB $\mu$ V/m)-Limit PK/AVG(dB $\mu$ V/m)								

<b>Temperature:</b>	25°C		<b>Relative Humidity:</b>	55%					
<b>Test Voltage:</b>	DC 12V								
<b>Ant. Pol.</b>	Vertical								
<b>Test Mode:</b>	BLE Mode TX 2402 MHz								
<b>Remark:</b>	No report for the emission which more than 20 dB below the prescribed limit.								
<b>Remark:</b>	1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB $\mu$ V/m)= Corr. (dB/m)+ Read Level (dB $\mu$ V) 3. Margin (dB) = Peak/AVG (dB $\mu$ V/m)-Limit PK/AVG(dB $\mu$ V/m)								

Temperature:	25°C	Relative Humidity:	55%																																						
Test Voltage:	DC 12V																																								
Ant. Pol.	Horizontal																																								
Test Mode:	BLE Mode TX 2442 MHz																																								
Remark:	No report for the emission which more than 20 dB below the prescribed limit.																																								
<table border="1"> <thead> <tr> <th>No.</th> <th>Mk.</th> <th>Freq.</th> <th>Reading Level</th> <th>Correct Factor</th> <th>Measure-ment</th> <th>Limit</th> <th>Over</th> </tr> <tr> <th></th> <th></th> <th>MHz</th> <th>dBuV</th> <th>dB/m</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>*</td> <td>4883.015</td> <td>28.96</td> <td>13.59</td> <td>42.55</td> <td>54.00</td> <td>-11.45</td> <td>AVG</td> </tr> <tr> <td>2</td> <td></td> <td>4883.145</td> <td>41.58</td> <td>13.59</td> <td>55.17</td> <td>74.00</td> <td>-18.83</td> <td>peak</td> </tr> </tbody> </table>							No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	1	*	4883.015	28.96	13.59	42.55	54.00	-11.45	AVG	2		4883.145	41.58	13.59	55.17	74.00	-18.83	peak
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																																		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector																																	
1	*	4883.015	28.96	13.59	42.55	54.00	-11.45	AVG																																	
2		4883.145	41.58	13.59	55.17	74.00	-18.83	peak																																	
Remark:	1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB $\mu$ V/m)= Corr. (dB/m)+ Read Level (dB $\mu$ V) 3. Margin (dB) = Peak/AVG (dB $\mu$ V/m)-Limit PK/AVG(dB $\mu$ V/m)																																								


Temperature:	25°C	Relative Humidity:	55%																																						
Test Voltage:	DC 12V																																								
Ant. Pol.	Vertical																																								
Test Mode:	BLE Mode TX 2442 MHz																																								
Remark:	No report for the emission which more than 20 dB below the prescribed limit.																																								
<table border="1"> <thead> <tr> <th>No.</th> <th>Mk.</th> <th>Freq.</th> <th>Reading Level</th> <th>Correct Factor</th> <th>Measure-ment</th> <th>Limit</th> <th>Over</th> </tr> <tr> <th></th> <th></th> <th>MHz</th> <th>dBuV</th> <th>dB/m</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>*</td> <td>4883.121</td> <td>28.93</td> <td>13.59</td> <td>42.52</td> <td>54.00</td> <td>-11.48</td> <td>AVG</td> </tr> <tr> <td>2</td> <td></td> <td>4883.154</td> <td>41.52</td> <td>13.59</td> <td>55.11</td> <td>74.00</td> <td>-18.89</td> <td>peak</td> </tr> </tbody> </table>							No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	1	*	4883.121	28.93	13.59	42.52	54.00	-11.48	AVG	2		4883.154	41.52	13.59	55.11	74.00	-18.89	peak
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																																		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector																																	
1	*	4883.121	28.93	13.59	42.52	54.00	-11.48	AVG																																	
2		4883.154	41.52	13.59	55.11	74.00	-18.89	peak																																	
Remark:	1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB $\mu$ V/m)= Corr. (dB/m)+ Read Level (dB $\mu$ V) 3. Margin (dB) = Peak/AVG (dB $\mu$ V/m)-Limit PK/AVG(dB $\mu$ V/m)																																								

Temperature:	25°C		Relative Humidity:	55%																																		
Test Voltage:	DC 12V																																					
Ant. Pol.	Horizontal																																					
Test Mode:	BLE Mode TX 2480 MHz																																					
Remark:	No report for the emission which more than 20 dB below the prescribed limit.																																					
<table border="1"> <thead> <tr> <th>No.</th> <th>Mk.</th> <th>Freq.</th> <th>Reading Level</th> <th>Correct Factor</th> <th>Measure-ment</th> <th>Limit</th> <th>Over</th> </tr> <tr> <th></th> <th></th> <th>MHz</th> <th>dB<math>\mu</math>V</th> <th>dB/m</th> <th>dB<math>\mu</math>V/m</th> <th>dB<math>\mu</math>V/m</th> <th>dB</th> </tr> </thead> <tbody> <tr> <td>1</td> <td></td> <td>4960.111</td> <td>40.97</td> <td>14.15</td> <td>55.12</td> <td>74.00</td> <td>-18.88 peak</td> </tr> <tr> <td>2</td> <td>*</td> <td>4960.144</td> <td>28.97</td> <td>14.15</td> <td>43.12</td> <td>54.00</td> <td>-10.88 AVG</td> </tr> </tbody> </table>							No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dB $\mu$ V	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB	1		4960.111	40.97	14.15	55.12	74.00	-18.88 peak	2	*	4960.144	28.97	14.15	43.12	54.00	-10.88 AVG
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																															
		MHz	dB $\mu$ V	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB																															
1		4960.111	40.97	14.15	55.12	74.00	-18.88 peak																															
2	*	4960.144	28.97	14.15	43.12	54.00	-10.88 AVG																															
<b>Remark:</b> 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB $\mu$ V/m)= Corr. (dB/m)+ Read Level (dB $\mu$ V) 3. Margin (dB) = Peak/AVG (dB $\mu$ V/m)-Limit PK/AVG(dB $\mu$ V/m)																																						


Temperature:	25°C		Relative Humidity:	55%																																		
Test Voltage:	DC 12V																																					
Ant. Pol.	Vertical																																					
Test Mode:	BLE Mode TX 2480 MHz																																					
Remark:	No report for the emission which more than 20 dB below the prescribed limit.																																					
<table border="1"> <thead> <tr> <th>No.</th> <th>Mk.</th> <th>Freq.</th> <th>Reading Level</th> <th>Correct Factor</th> <th>Measure-ment</th> <th>Limit</th> <th>Over</th> </tr> <tr> <th></th> <th></th> <th>MHz</th> <th>dB<math>\mu</math>V</th> <th>dB/m</th> <th>dB<math>\mu</math>V/m</th> <th>dB<math>\mu</math>V/m</th> <th>dB</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>*</td> <td>4961.100</td> <td>29.06</td> <td>14.16</td> <td>43.22</td> <td>54.00</td> <td>-10.78 AVG</td> </tr> <tr> <td>2</td> <td></td> <td>4961.122</td> <td>41.99</td> <td>14.16</td> <td>56.15</td> <td>74.00</td> <td>-17.85 peak</td> </tr> </tbody> </table>							No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			MHz	dB $\mu$ V	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB	1	*	4961.100	29.06	14.16	43.22	54.00	-10.78 AVG	2		4961.122	41.99	14.16	56.15	74.00	-17.85 peak
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over																															
		MHz	dB $\mu$ V	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB																															
1	*	4961.100	29.06	14.16	43.22	54.00	-10.78 AVG																															
2		4961.122	41.99	14.16	56.15	74.00	-17.85 peak																															
<b>Remark:</b> 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB $\mu$ V/m)= Corr. (dB/m)+ Read Level (dB $\mu$ V) 3. Margin (dB) = Peak/AVG (dB $\mu$ V/m)-Limit PK/AVG(dB $\mu$ V/m)																																						

## Attachment C-- Restricted Bands Requirement and Band Edge Test Data

### (1) Radiation Test



Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 12V		
Ant. Pol.	Vertical		
Test Mode:	BLE Mode TX 2402 MHz		
Remark:	N/A		




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1		2390.000	40.84	1.28	42.12	74.00	-31.88 peak
2		2390.000	29.98	1.28	31.26	54.00	-22.74 AVG
3	X	2402.200	79.99	1.33	81.32	Fundamental Frequency	peak
4	*	2402.200	68.04	1.33	69.37	Fundamental Frequency	AVG

## Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB $\mu$ V/m)= Corr. (dB/m)+ Read Level (dB $\mu$ V)
3. Margin (dB) = Peak/AVG (dB $\mu$ V/m)-Limit PK/AVG(dB $\mu$ V/m)


Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 12V		
Ant. Pol.	Horizontal		
Test Mode:	BLE Mode TX 2480 MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1	X	2479.600	79.30	1.85	81.15	Fundamental Frequency	peak
2	*	2479.600	75.72	1.85	77.57	Fundamental Frequency	AVG
3		2483.500	53.64	1.88	55.52	74.00	-18.48
4		2483.500	37.13	1.88	39.01	54.00	-14.99
							Detector

## Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB $\mu$ V/m)= Corr. (dB/m)+ Read Level (dB $\mu$ V)
3. Margin (dB) = Peak/AVG (dB $\mu$ V/m)-Limit PK/AVG(dB $\mu$ V/m)


Temperature:	25°C	Relative Humidity:	55%				
Test Voltage:	DC 12V						
Ant. Pol.	Vertical						
Test Mode:	BLE Mode TX 2480 MHz						
Remark:	N/A						
							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1	X	2479.600	79.25	1.85	81.10	Fundamental Frequency	peak
2	*	2479.600	70.87	1.85	72.72	Fundamental Frequency	AVG
3		2483.500	41.97	1.88	43.85	74.00	-30.15
4		2483.500	30.84	1.88	32.72	54.00	-21.28

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB $\mu$ V/m)= Corr. (dB/m)+ Read Level (dB $\mu$ V)
3. Margin (dB) = Peak/AVG (dB $\mu$ V/m)-Limit PK/AVG(dB $\mu$ V/m)

## (2) Conducted Test

Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 12V		
Test Mode:	BLE Mode TX 2402MHz / BLE Mode TX 2480MHz		
Remark:	The EUT is programed in continuously transmitting mode		




## Attachment D-- Bandwidth Test Data

Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 12V		
Test Mode:	BLE TX Mode		
Channel frequency (MHz)	6dB Bandwidth (kHz)	99% Bandwidth (kHz)	Limit (kHz)  >=500
2402	682.6	1018.1	
2442	664.9	1025.5	
2480	671.6	1027.2	


### BLE Mode


#### 2402 MHz





## Attachment E-- Peak Output Power Test Data

Temperature:	25°C	Relative Humidity:	55%				
Test Voltage:	DC 12V						
Test Mode:	BLE TX Mode						
Channel frequency (MHz)	Test Result (dBm)		Limit (dBm)				
2402	0.211		30				
2442	0.094						
2480	-0.375						
BLE Mode							
2402 MHz							
							





## Attachment F-- Power Spectral Density Test Data

Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 12V		
Test Mode:	BLE TX Mode		
Channel Frequency (MHz)	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2402	-15.066	8	PASS
2442	-15.429		
2480	-15.762		

**BLE Mode**

**2402 MHz**





-----END OF REPORT-----