										1
				Peak	5875.000	-47.65	≤10.00			PASS
				Peak	5925.000	-48.43	≤-27.00			PASS
11AC40SI SO	Ant1	Low	5190	AV	4500.000	-55.74	≤-41.20	39.46	≤54	PASS
				AV	5149.043	-49.1	≤-41.20	46.10	≤54	PASS
				AV	5150.000	-48.68	≤-41.20	46.52	≤54	PASS
				Peak	4500.000	-37.12	≤-21.20	58.08	≤74	PASS
				Peak	5149.043	-29.71	≤-21.20	65.49	≤74	PASS
				Peak	5150.000	-24.97	≤-21.20	70.23	≤74	PASS
		High	5230	AV	5350.000	-54.13	≤-41.20	41.07	≤54	PASS
				AV	5448.319	-52.3	≤-41.20	42.90	≤54	PASS
				AV	5460.000	-53.37	≤-41.20	41.83	≤54	PASS
				Peak	5350.000	-44.75	≤-21.20	50.45	≤74	PASS
				Peak	5378.986	-41.5	≤-21.20	53.70	≤74	PASS
				Peak	5460.000	-44.03	≤-21.20	51.17	≤74	PASS
		Low	5755	Peak	5650.000	-49.17	≤-27.00			PASS
				Peak	5700.000	-34.22	≤10.00			PASS
				Peak	5720.000	-42.29	≤15.60			PASS
				Peak	5725.000	-42.11	≤27.00			PASS
		High	5795	Peak	5850.000	-45.33	≤27.00			PASS
				Peak	5855.000	-47.85	≤15.60			PASS
				Peak	5875.000	-44.04	≤10.00			PASS
				Peak	5925.000	-47.95	≤-27.00			PASS
11AC80SI SO	Ant1	High	5210	AV	5350.000	-51.48	≤-41.20	43.72	≤54	PASS
				AV	5449.043	-51.41	≤-41.20	43.79	≤54	PASS
				AV	5460.000	-52.91	≤-41.20	42.29	≤54	PASS
				Peak	5350.000	-41.5	≤-21.20	53.70	≤74	PASS
				Peak	5453.507	-40.59	≤-21.20	54.61	≤74	PASS
				Peak	5460.000	-43.47	≤-21.20	51.73	≤74	PASS
		Low	5775	Peak	5650.000	-39.95	≤-27.00			PASS
				Peak	5700.000	-36.8	≤10.00			PASS
				Peak	5720.000	-32.96	≤15.60			PASS
				Peak	5725.000	-35.66	≤27.00			PASS
		High	5775	Peak	5850.000	-37.12	≤27.00			PASS
				Peak	5855.000	-36.97	≤15.60			PASS
				Peak	5875.000	-40.63	≤10.00			PASS
				Peak	5925.000	-41.29	≤-27.00			PASS

Note:

- 1. The Antenna Gain is compensated in the graph.
- 2. For transmitters operating in 5150-5350 GHz band and 5470-5725 GHz band: The limit in dBm for average detector is conversion from 54dBuV/m, according to 15.209(a). The limit in dBm for peak detector is 20dB above the limit of average detector in dBm.

Test Graphs



























