

Product Name: Smart Phone	Report No: FCC022023-00288RF7
Product Model: V20Pro	Security Classification: Open
Version: V1.0	Total Page: 224

TIRT Testing Report

Prepared By:	Checked By:	Approved By:	
Stone Tang	Randy Lv	Daniel Chen	
Stone Tang	Randy Lv	Daniel chen	

RF TEST REPORT

FCC ID: 2AX4YV20PRO

According to

**FCC CFR Title 47 Part 2
FCC CFR Title 47 Part 22 Subpart H
FCC CFR Title 47 Part 24 Subpart E
FCC CFR Title 47 Part 27
ANSI C63.26:2015**

Equipment : Smart Phone
Model No. : V20Pro
Trademark : DOOGEE
Applicant : Shenzhen DOOGEE Hengtong Technology CO.,LTD
B, 2/F, Building A4, Silicon Valley Power Digital Industrial Park, No. 22,
Longhua New District, Shenzhen, China

- The test result referred exclusively to the presented test model /sample.
- Without written approval of TIRT Inc. the test report shall not reproduced except in full.
- Test date: 2023/02/01~2023/02/20

Lab: Beijing TIRT Technology Service Co.,Ltd Shenzhen
Add: 101, 3 # Factory Building, Gongjin Electronics Shatin Community, Kengzi Street,
Pingshan District, Shenzhen, China
TEL: +86-0755-27087573

TABLE OF CONTENTS

	Description	Page
1	TEST SUMMARY	5
2	GENERAL INFORMATION	6
2.1	GENERAL DESCRIPTION OF EUT	6
2.2	RELATED SUBMITTAL(S) / GRANT (S)	7
2.3	TEST FACILITY	7
2.4	ACCESSORIES OF DEVICE (EUT)	7
2.5	TESTED SUPPORTING SYSTEM DETAILS	7
2.6	TEST CONDITIONS	7
2.7	MEASUREMENT UNCERTAINTY	8
3	TEST INSTRUMENTS LIST	9
4	SYSTEM TEST CONFIGURATION	10
4.1	TEST MODE	10
4.2	CONFIGURATION OF TESTED SYSTEM	10
4.3	CONDUCTED OUTPUT POWER	11
4.4	PEAK-TO-AVERAGE RATIO	29
4.5	OCCUPY BANDWIDTH	34
4.6	MODULATION CHARACTERISTIC	54
4.7	OUT OF BAND EMISSION AT ANTENNA TERMINALS	54
4.8	ERP, EIRP MEASUREMENT	135
4.9	FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT	201
4.10	FREQUENCY STABILITY V.S. TEMPERATURE MEASUREMENT	217
4.11	FREQUENCY STABILITY V.S. VOLTAGE MEASUREMENT	221
4.12	TEST SETUP PHOTO	224

History of this test report

Original Report Issue Date: 2023.02.20

- No additional attachment
- Additional attachments were issued following record

Attachment No.	Issue Date	Description

1 Test Summary

Test Item	Section in CFR 47	Result
RF Exposure (SAR)	Part 1.1307 Part 2.1093	Pass*(Please refer to SAR Report)
RF Output Power	Part 2.1046 Part 22.913(a) (5) Part 24.232 (c) Part 27.50 (d)(4) Part 27.50 (h)	Pass
Peak-To-Average Ratio	Part 2.1046 Part 22.913(d) Part 24.232 (d) Part 27.50(d)	Pass
Modulation Characteristics	Part 2.1047	N/A
99% & -26 dB Occupied Bandwidth	Part 2.1049 Part 22.917 Part 24.238 Part 27.53(a)	Pass
Spurious Emissions at Antenna Terminal	Part 2.1051 Part 22.917 (a) Part 24.238 (a) Part 27.53 (h)/(m)	Pass
Field Strength of Spurious Radiation	Part 2.1053 Part 22.917 (a) Part 24.238 (a) Part 27.53 (h)/(m)	Pass
Out of band emission, Band Edge	Part 22.917 (a) Part 24.238 (a) Part 27.53(h)/(m)	Pass
Frequency stability vs. temperature	Part 2.1055(a)(1)(b)	Pass
Frequency stability vs. voltage	Part 2.1055(d)(1)(2)	Pass

Note: 1. Pass: The EUT complies with the essential requirements in the standard.

2. The conclusion of this test report is judged by actual test data without considering measurement uncertainty.

2 General Information

2.1 General Description of EUT

Description of Device (EUT)

EUT Name : Smart Phone
Model No. : V20Pro
DIFF. : N/A

Power supply : DC 11V from adapter, DC 3.7V from battery

Support Bands : LTE Band 2/4/5/7/12/17/66

Channel Bandwidth : LTE Band 2: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz
LTE Band 4: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz
LTE Band 5: 1.4MHz, 3MHz, 5MHz, 10MHz

LTE Band 7: 5MHz, 10MHz, 15MHz, 20MHz
LTE Band 12: 1.4MHz, 3MHz, 5MHz, 10MHz
LTE Band 17: 5MHz, 10MHz
LTE Band 66: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz

TX Frequency : LTE Band 2: 1850 ~ 1910 MHz
LTE Band 4: 1710 ~ 1755 MHz
LTE Band 5: 824 ~ 849 MHz
LTE Band 7: 2500 ~ 2570 MHz
LTE Band 12: 699MHz ~ 716MHz
LTE Band 17: 704 MHz ~ 716 MHz
LTE Band 66: 1710 MHz ~ 1780 MHz

Modulation type : QPSK, 16QAM

Antenna Type : Internal antenna,
LTE Band 2: Maximum Gain is 0.3dBi.
LTE Band 4: Maximum Gain is 0.5dBi.
LTE Band 5: Maximum Gain is -0.4dBi.
LTE Band 7: Maximum Gain is 0.8dBi.
LTE Band 12: Maximum Gain is -0.6dBi.
LTE Band 17: Maximum Gain is -0.6dBi.
LTE Band 66: Maximum Gain is 0.5dBi.
Antenna information is provided by applicant.
There is WWAN diversity antenna inside the product, which is only for receiving function.

Software version : DOOGEE-V20Pro-EEA-Android12.0-20221209

Hardware version : A201_01

Remark 1: The worst-case simultaneous transmission configuration was evaluated with no non-compliance found. Results in this report are only for 4G function, and there is no other transmitter involved.

2. The product contains two SIM card slots, both of which have been tested and only reflect the data of SIM card slot 1.

2.2 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is filing to comply with Section Part 22 subpart H and Part 24 subpart E of the FCC CFR 47 Rules.

2.3 Test Facility

Company:	Beijing TIRT Technology Service Co.,Ltd Shenzhen
Address:	101, 3 # Factory Building, Gongjin Electronics Shatin Community, Kengzi Street, Pingshan District, Shenzhen, China
CNAS Registration Number:	CNAS L14158
A2LA Registration Number:	6049.01
FCC Designation Number:	CN1309
Test Firm Registration Number:	825524
Telephone:	+86-0755-27087573

2.4 Accessories of Device (EUT)

Accessories : /
Manufacturer : /
Model : /
Ratings : /

2.5 Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification or SDoC
--	--	--	--	--	--

2.6 Test Conditions

Items	Required	Actual
Temperature range:	15-35°C	24°C
Humidity range:	25-75%	56%
Pressure range:	86-106kPa	98kPa


2.7 Measurement Uncertainty

Uncertainty	
Parameter	Uncertainty
Occupied Channel Bandwidth	± 142.12 KHz
RF power conducted	± 0.74 dB
RF power radiated	± 3.25 dB
Spurious emissions, conducted	± 1.78 dB
Spurious emissions, radiated (9KHz~30MHz)	± 2.56 dB
Spurious emissions, radiated (30MHz~1GHz)	± 4.6 dB
Spurious emissions, radiated (Above 1GHz)	± 4.9 dB
Conduction Emissions(150kHz~30MHz)	± 3.1 dB
Humidity	$\pm 4.6\%$
Temperature	$\pm 0.7^{\circ}\text{C}$
Time	$\pm 1.25\%$

3 Test Instruments list

No.	Equipment	Manufacturer	Type No.	Serial No.	Cal. date (yyyy/mm/dd)	Cal. Due date (yyyy/mm/dd)
1	EMI Receiver	Rohde&Schwarz	ESCI	100718	2022/11/09	2023/11/10
2	AMN	Rohde&Schwarz	ENV216	100075	2022/11/09	2023/11/10
3	AMN	Schwarzbeck	NSLK8127	#829	2022/11/09	2023/11/10
4	ECSI RF IN RF Cable	Rohde&Schwarz	RP-X1	\	2022/11/17	2023/11/16
5	ECSI RF IN RF Cable	Rohde&Schwarz	Sapre sm	\	2022/11/09	2023/11/10
6	EMI Receiver	Rohde&Schwarz	ESR7	102013	2022/11/09	2023/11/10
7	Spectrum analyzer	Rohde&Schwarz	FSV30	103741	2022/11/09	2023/11/10
8	Spectrum analyzer	KEYSIGHT	N9010A	MY51440158	2022/11/09	2023/11/10
9	Integral Antenna	Schwarzbeck	VULB 9163	9163-868	2022/12/25	2023/12/24
10	Integral Antenna	Schwarzbeck	BBHA 9120D	BBHA 9120D 1201	2022/11/09	2023/11/10
11	Integral Antenna	Schwarzbeck	BBHA 9170	9170#685	2022/11/06	2023/11/10
12	Preamplifier	CD Systems Inc	PAP-03036- 30	85060000	2022/11/09	2023/11/10
13	Preamplifier	Schwarzbeck	BBV9721	9721-019	2022/11/09	2023/11/10
14	Preamplifier	emci	EMC012645 SE	980417	2022/11/09	2023/11/10
15	ECSI RF IN RF Cable	Rohde&Schwarz	AP-X1	\	2022/11/09	2023/11/10
16	Spectrum Analyzer	Agilent	N9010A	MY52221119	2022/11/09	2023/11/10
17	Power Collection Unit	Tonscend	JS0806-2	188060134	2022/09/12	2023/09/11
18	Tonscend Test System	Tonscend	2.6.77.0518	NA	NA	NA
19	Power Sensor	Agilent	U2021XA	MY55410011	2022/09/12	2023/09/11
20	Power Sensor	Agilent	U2021XA	MY55410012	2022/09/12	2023/09/11
21	Power Sensor	Agilent	U2021XA	MY55410018	2022/09/12	2023/09/11
22	Power Sensor	Agilent	U2021XA	MY55410019	2022/09/12	2023/09/11
23	Temp&Humidity Recorder	Anymetre	JR900	NA	2022/11/03	2023/11/02
24	Temp&Humidity Chamber	ETOMA	NTH1100- 30A	16080628	2022/09/01	2023/08/30

4.3 Conducted Output Power

Test Requirement:	FCC part22.913(a) (5), FCC part24.232(b) and FCC Part 27.50 (d)(4)/(h)
Test Method:	ANSI C63.26:2015
Limit:	LTE Band 2: 2W LTE Band 4: 1W LTE Band 5: 7W LTE Band 7: 2W LTE Band 12: 3W LTE Band 17: 1W LTE Band 66: 1W
Test setup:	 <i>Note: Measurement setup for testing on Antenna connector</i>
Test Procedure:	1. The transmitter output port was connected to base station. 2. The RF output of EUT was connected to the power meter by RF cable and attenuator, the path loss was compensated to the results for each measurement. 3. Set EUT at maximum power through base station. 4. Select lowest, middle, and highest channels for each band and different modulation. 5. Measure the maximum burst average power.
Test Instruments:	Refer to section 3 for details
Test mode:	Refer to section 4.1 for details
Test results:	Pass

Measurement Data

LTE Band2

BW (MHz)	Frequency (MHz)	RB Configuration		Average Power [dBm]	
		Size	Offset	QPSK	16QAM
1.4	1850.7	1	0	24.06	22.64
		1	3	22.16	23.77
		1	5	23.84	22.51
		3	0	23.33	24.18
		3	2	22.69	22.96
		3	3	23.91	22.75
		6	0	22.29	22.98
	1880.0	1	0	24.13	22.76
		1	3	23.43	23.38
		1	5	22.95	22.81
		3	0	22.31	22.37
		3	2	22.26	22.16
		3	3	23.32	22.15
		6	0	23.13	23.27
	1909.3	1	0	23.04	22.44
		1	3	21.99	23.05
		1	5	22.85	22.93
		3	0	21.97	22.25
		3	2	23.46	23.20
		3	3	22.73	22.86
		6	0	23.06	22.59
3	1851.5	1	0	23.21	22.81
		1	7	22.12	23.04
		1	14	24.50	23.67
		8	0	22.53	22.46
		8	4	23.05	22.97
		8	7	23.04	23.02
		15	0	22.92	22.37
	1880.0	1	0	22.37	22.69
		1	7	22.77	22.83
		1	14	23.14	22.64
		8	0	22.50	22.32
		8	4	22.42	22.85
		8	7	22.57	23.10
		15	0	22.87	22.39
	1908.5	1	0	22.99	22.10
		1	7	23.02	22.67
		1	14	23.16	21.96
		8	0	22.52	22.64
		8	4	22.88	22.31
		8	7	22.77	22.11
		15	0	22.28	22.57
5	1852.5	1	0	22.40	22.74
		1	12	23.02	22.30
		1	24	22.92	22.23

		12	0	22.47	22.46
		12	6	22.69	22.49
		12	13	22.79	22.28
		25	0	22.45	22.37
	1880.0	1	0	23.89	24.27
		1	12	22.93	23.63
		1	24	22.63	22.16
		12	0	22.21	22.91
		12	6	22.50	22.38
		12	13	22.32	22.75
		25	0	22.53	21.92
	1907.5	1	0	23.03	22.37
		1	12	22.18	22.34
		1	24	22.34	22.28
		12	0	22.81	22.82
		12	6	22.23	22.65
		12	13	22.60	22.46
		25	0	22.80	23.09
10	1855.0	1	0	24.02	23.18
		1	24	22.83	23.04
		1	49	22.96	22.58
		25	0	23.15	22.15
		25	12	22.53	23.04
		25	25	23.43	22.80
		50	0	23.19	22.66
	1880.0	1	0	22.10	23.52
		1	24	24.13	24.00
		1	49	23.13	22.47
		25	0	22.98	23.10
		25	12	22.46	22.23
		25	25	22.72	22.35
		50	0	22.30	22.74
	1905.0	1	0	23.77	22.55
		1	24	22.72	22.94
		1	49	22.46	23.31
		25	0	22.69	22.43
		25	12	23.21	22.55
		25	25	22.72	22.57
		50	0	23.12	22.35
15	1857.5	1	0	23.23	22.75
		1	37	22.63	23.51
		1	74	22.43	23.00
		37	0	23.00	22.18
		37	18	23.00	22.42
		37	38	22.68	23.00
		75	0	23.89	22.40
	1880.0	1	0	22.35	23.73
		1	37	23.94	22.00
		1	74	23.06	22.71
		37	0	22.43	22.75

		37	18	22.13	22.76
		37	38	22.91	22.44
		75	0	22.31	23.00
	1902.5	1	0	22.13	22.64
		1	37	23.43	22.61
		1	74	22.68	22.85
		37	0	21.95	22.89
		37	18	22.71	22.94
		37	38	22.31	23.09
		75	0	22.40	22.63
20	1860.0	1	0	23.41	22.63
		1	49	23.37	23.79
		1	99	22.70	23.46
		50	0	22.15	22.92
		50	25	23.36	22.70
		50	50	22.82	22.49
		100	0	22.58	22.26
	1880.0	1	0	24.94	24.86
		1	49	23.73	22.14
		1	99	24.23	22.24
		50	0	24.22	24.04
		50	25	24.12	22.95
		50	50	23.51	22.85
		100	0	23.52	23.08
	1900.0	1	0	24.90	24.47
		1	49	22.52	22.64
		1	99	22.55	23.11
		50	0	23.17	22.88
		50	25	23.41	22.37
		50	50	24.49	24.44
		100	0	22.47	22.24

LTE Band4

BW (MHz)	Frequency (MHz)	RB Configuration		Average Power [dBm]	
		Size	Offset	QPSK	16QAM
1.4	1710.7	1	0	24.35	22.92
		1	3	23.21	23.85
		1	5	24.16	22.57
		3	0	23.56	23.44
		3	2	22.47	22.67
		3	3	22.86	22.50
		6	0	22.90	22.87
	1732.5	1	0	23.58	23.01
		1	3	23.75	23.30
		1	5	23.10	23.06
		3	0	22.74	23.02
		3	2	23.10	23.26
		3	3	23.39	22.23
		6	0	22.49	23.25
	1754.3	1	0	22.74	22.59
		1	3	22.37	23.35
		1	5	22.58	23.02
		3	0	22.99	22.54
		3	2	23.33	22.90
		3	3	23.18	22.42
		6	0	23.50	22.36
3	1711.5	1	0	23.88	22.88
		1	7	22.59	22.95
		1	14	24.24	23.33
		8	0	22.18	22.46
		8	4	22.26	22.82
		8	7	22.13	22.76
		15	0	22.60	22.63
	1732.5	1	0	22.17	22.35
		1	7	22.93	22.15
		1	14	23.28	22.24
		8	0	23.15	22.41
		8	4	22.78	22.19
		8	7	22.26	22.93
		15	0	22.95	22.61
	1753.5	1	0	22.83	22.51
		1	7	22.30	22.84
		1	14	22.32	22.38
		8	0	22.05	23.15
		8	4	22.65	23.11
		8	7	23.00	23.10
		15	0	22.82	22.88
5	1712.5	1	0	22.11	22.12
		1	12	23.50	22.51
		1	24	22.94	22.51
		12	0	22.46	22.60

		12	6	22.40	22.97
		12	13	22.83	22.74
		25	0	22.23	23.04
	1732.5	1	0	24.70	24.54
		1	12	23.16	23.71
		1	24	22.12	22.50
		12	0	22.55	22.84
		12	6	22.97	22.81
		12	13	22.43	22.52
		25	0	22.92	22.79
		25	0	22.92	22.79
	1752.5	1	0	23.27	23.15
		1	12	22.64	22.72
		1	24	22.52	22.35
		12	0	22.24	22.98
		12	6	22.48	22.68
		12	13	22.77	22.40
		25	0	22.38	22.99
		25	0	22.38	22.99
10	1715.0	1	0	24.41	22.98
		1	24	23.00	23.33
		1	49	22.34	22.32
		25	0	22.45	22.73
		25	12	22.71	22.37
		25	25	22.81	22.79
		50	0	23.25	23.20
		50	0	23.25	23.20
	1732.5	1	0	22.72	23.93
		1	24	23.91	23.76
		1	49	23.00	22.73
		25	0	22.36	22.54
		25	12	23.03	22.69
		25	25	22.41	22.50
		50	0	22.84	22.63
		50	0	22.84	22.63
	1750.0	1	0	23.64	22.86
		1	24	22.40	23.42
		1	49	22.95	22.82
		25	0	22.42	22.25
		25	12	22.15	23.17
		25	25	22.54	22.33
		50	0	22.95	22.77
		50	0	22.95	22.77
15	1717.5	1	0	23.08	22.71
		1	37	22.64	23.97
		1	74	22.67	22.23
		37	0	23.31	22.21
		37	18	22.41	22.35
		37	38	22.20	22.39
		75	0	23.60	23.15
		75	0	23.60	23.15
	1732.5	1	0	23.13	23.62
		1	37	24.15	22.51
		1	74	22.94	22.89
		37	0	22.57	22.41
		37	18	23.16	22.44
		37	18	23.16	22.44

		37	38	22.52	23.03
		75	0	22.16	22.41
	1747.5	1	0	22.37	22.06
		1	37	23.64	22.78
		1	74	22.09	22.66
		37	0	22.46	22.70
		37	18	22.66	22.24
		37	38	22.57	23.23
		75	0	22.07	22.18
		1	0	23.80	22.76
20	1722.0	1	49	22.44	23.94
		1	99	22.21	22.89
		50	0	22.30	22.10
		50	25	23.72	23.24
		50	50	22.88	22.15
		100	0	22.71	23.34
	1732.5	1	0	24.94	24.69
		1	49	24.80	22.20
		1	99	23.74	22.85
		50	0	24.53	23.70
		50	25	23.85	22.77
		50	50	24.40	24.38
		100	0	23.59	22.63
	1745.0	1	0	22.16	22.15
		1	49	21.91	22.80
		1	99	22.18	23.03
		50	0	22.73	22.69
		50	25	23.00	22.59
		50	50	22.60	22.32
		100	0	22.56	22.78

LTE Band5

BW (MHz)	Frequency (MHz)	RB Configuration		Average Power [dBm]	
		Size	Offset	QPSK	16QAM
1.4	824.7	1	0	24.27	22.92
		1	3	22.63	23.55
		1	5	24.23	23.17
		3	0	24.03	23.66
		3	2	22.12	22.25
		3	3	23.34	22.18
		6	0	22.31	22.90
	836.5	1	0	23.60	23.23
		1	3	23.67	23.25
		1	5	22.99	22.96
		3	0	22.25	22.73
		3	2	22.25	22.19
		3	3	23.66	22.78
		6	0	22.61	22.65
	848.3	1	0	23.29	22.75
		1	3	22.42	23.04
		1	5	22.14	22.55
		3	0	22.62	23.00
		3	2	22.55	22.84
		3	3	22.43	22.19
		6	0	23.43	22.18
3	824.5	1	0	23.43	22.95
		1	7	22.96	23.14
		1	14	24.35	23.36
		8	0	23.21	22.37
		8	4	22.84	22.32
		8	7	22.28	22.59
		15	0	22.64	22.17
	836.5	1	0	22.20	22.47
		1	7	22.27	22.27
		1	14	22.62	22.20
		8	0	22.70	22.79
		8	4	22.45	23.42
		8	7	22.61	22.46
		15	0	22.62	22.47
	847.5	1	0	23.22	22.28
		1	7	22.87	22.92
		1	14	22.39	22.29
		8	0	23.03	22.78
		8	4	22.03	22.20
		8	7	22.82	22.11
		15	0	22.46	23.29
5	824.5	1	0	22.41	22.95
		1	12	22.66	22.50
		1	24	22.37	22.35
		12	0	22.25	22.17

		12	6	22.90	22.40
		12	13	22.22	22.28
		25	0	22.50	22.35
	836.5	1	0	24.13	24.15
		1	12	23.08	24.29
		1	24	22.42	22.50
		12	0	22.82	22.78
		12	6	22.87	22.79
		12	13	22.37	22.62
		25	0	22.75	22.81
		25	0	22.75	22.81
	846.5	1	0	22.79	22.39
		1	12	22.55	22.46
		1	24	22.66	22.87
		12	0	22.31	23.21
		12	6	22.38	22.87
		12	13	22.48	22.83
		25	0	22.18	22.69
		25	0	22.18	22.69
10	829.0	1	0	24.22	23.64
		1	24	23.13	24.57
		1	49	22.27	22.64
		25	0	24.12	23.60
		25	12	23.03	22.86
		25	25	22.56	22.59
		50	0	23.02	22.82
	836.5	1	0	22.44	24.00
		1	24	24.01	23.77
		1	49	22.77	22.45
		25	0	22.26	23.03
		25	12	22.65	22.40
		25	25	22.64	22.15
		50	0	22.33	22.20
	844.0	1	0	24.80	24.78
		1	24	23.14	23.12
		1	49	22.94	22.55
		25	0	22.92	22.03
		25	12	22.24	23.36
		25	25	22.29	22.99
		50	0	22.65	22.62

LTE Band7

BW (MHz)	Frequency (MHz)	RB Configuration		Average Power [dBm]	
		Size	Offset	QPSK	16QAM
5	2502.5	1	0	24.12	23.67
		1	12	22.67	23.15
		1	24	23.22	23.20
		12	0	23.63	24.12
		12	6	22.23	23.05
		12	13	23.06	22.58
		25	0	22.40	22.96
	2535.0	1	0	24.20	22.93
		1	12	24.69	23.35
		1	24	22.85	22.98
		12	0	22.08	22.80
		12	6	22.81	22.81
		12	13	23.78	23.06
		25	0	23.07	23.07
	2567.5	1	0	22.39	22.20
		1	12	22.96	22.82
		1	24	22.56	22.64
		12	0	22.14	22.82
		12	6	23.12	22.94
		12	13	22.75	23.14
		25	0	22.63	22.81
10	2505.0	1	0	23.25	22.89
		1	24	22.88	22.98
		1	49	24.45	23.79
		25	0	23.49	22.59
		25	12	23.21	22.98
		25	25	22.75	22.95
		50	0	22.49	22.31
	2535.0	1	0	22.36	22.81
		1	24	22.69	22.77
		1	49	22.79	22.43
		25	0	22.69	22.50
		25	12	22.73	22.49
		25	25	22.77	23.14
		50	0	23.03	22.88
	2565.0	1	0	23.02	22.30
		1	24	22.43	22.63
		1	49	22.30	22.85
		25	0	22.72	23.10
		25	12	22.59	22.80
		25	25	22.41	22.61
		50	0	22.23	22.66
15	2507.5	1	0	22.05	22.23
		1	37	23.22	22.17
		1	74	23.16	22.30
		37	0	22.40	22.42

		37	18	22.69	22.96
		37	38	22.75	22.33
		75	0	22.99	22.06
	2535.0	1	0	24.49	24.00
		1	37	22.46	23.23
		1	74	22.98	22.69
		37	0	22.80	22.55
		37	18	22.12	22.49
		37	38	22.24	23.16
		75	0	22.53	22.83
	2562.5	1	0	23.05	22.25
		1	37	22.31	22.48
		1	74	22.70	22.65
		37	0	22.10	22.96
		37	18	22.95	22.66
		37	38	22.89	22.24
		75	0	22.34	22.09
20	2510.0	1	0	23.39	22.25
		1	49	23.33	23.68
		1	99	23.00	22.38
		50	0	23.29	22.28
		50	25	22.33	22.37
		50	50	23.33	22.80
		100	0	23.90	22.84
	2535.0	1	0	24.78	24.60
		1	49	24.43	23.89
		1	99	22.82	22.70
		50	0	24.75	24.34
		50	25	23.18	22.94
		50	50	23.07	22.21
		100	0	22.16	22.83
	2560	1	0	23.53	22.82
		1	49	23.09	22.63
		1	99	22.58	22.98
		50	0	22.98	22.45
		50	25	23.11	23.06
		50	50	22.54	22.76
		100	0	22.36	22.82

LTE Band12

BW (MHz)	Frequency (MHz)	RB Configuration		Average Power [dBm]	
		Size	Offset	QPSK	16QAM
1.4	699.7	1	0		24.51
		1	3	22.55	22.41
		1	5	23.26	23.48
		3	0	22.95	23.28
		3	2	22.94	22.79
		3	3	23.29	23.29
		6	0	22.94	23.13
	707.5	1	0	23.76	23.65
		1	3	24.24	24.51
		1	5	22.94	22.69
		3	0	22.49	22.36
		3	2	22.32	22.38
		3	3	22.83	23.33
		6	0	22.74	22.46
	715.3	1	0	23.16	22.94
		1	3	22.56	22.07
		1	5	22.49	22.41
		3	0	22.92	23.14
		3	2	23.24	23.01
		3	3	22.85	22.79
		6	0	22.85	22.79
3	700.5	1	0	23.24	23.39
		1	7	22.95	23.48
		1	14	23.94	24.30
		8	0	22.92	23.15
		8	4	22.74	22.50
		8	7	22.75	22.97
		15	0	22.34	22.53
	707.5	1	0	22.54	22.68
		1	7	22.45	22.51
		1	14	22.85	22.81
		8	0	22.44	22.21
		8	4	22.94	22.84
		8	7	22.04	22.91
		15	0	22.75	22.37
	714.5	1	0	23.06	23.17
		1	7	22.46	22.43
		1	14	22.10	22.27
		8	0	23.01	23.20
		8	4	22.34	22.07
		8	7	22.90	22.67
		15	0	22.82	22.89
5	701.5	1	0	22.43	22.70
		1	12	23.50	23.63
		1	24	22.58	22.94
		12	0	22.67	22.56

		12	6	22.75	22.67
		12	13	21.99	22.94
		25	0	22.01	22.38
	707.5	1	0	23.76	24.11
		1	12	22.55	22.51
		1	24	22.71	22.86
		12	0	22.77	22.79
		12	6	22.96	22.77
		12	13	22.40	22.52
		25	0	22.51	22.65
		25	0	22.51	22.65
	713.5	1	0	22.92	22.82
		1	12	22.86	22.96
		1	24	22.34	22.65
		12	0	22.57	22.69
		12	6	22.25	22.21
		12	13	22.43	22.38
		25	0	22.65	22.41
		25	0	22.65	22.41
10	704	1	0	24.90	24.76
		1	24	22.80	22.92
		1	49	22.51	22.66
		25	0	23.11	23.11
		25	12	22.13	22.25
		25	25	22.66	22.66
		50	0	23.78	23.72
	707.5	1	0	24.47	24.49
		1	24	24.20	23.95
		1	49	22.98	22.82
		25	0	24.27	23.81
		25	12	22.69	22.51
		25	25	22.73	22.65
		50	0	22.94	23.06
	711.0	1	0	24.85	24.66
		1	24	22.53	24.60
		1	49	22.94	22.98
		25	0	24.38	24.07
		25	12	22.16	22.91
		25	25	22.70	22.81
		50	0	22.37	22.14

LTE Band17

BW (MHz)	Frequency (MHz)	RB Configuration		Average Power [dBm]	
		Size	Offset	QPSK	16QAM
5	706.5	1	0	24.46	23.01
		1	12	22.91	22.90
		1	24	23.94	23.30
		12	0	23.87	23.28
		12	6	22.32	22.61
		12	13	23.63	22.38
		25	0	22.72	23.00
	710.0	1	0	23.75	23.19
		1	12	24.14	22.72
		1	24	22.88	23.09
		12	0	23.02	22.72
		12	6	22.96	22.96
		12	13	23.09	22.29
		25	0	22.65	23.19
	713.5	1	0	22.92	22.14
		1	12	23.19	22.85
		1	24	23.05	22.21
		12	0	22.42	23.02
		12	6	22.55	22.69
		12	13	22.65	22.74
		25	0	23.00	22.91
10	709.0	1	0	23.66	22.80
		1	24	22.19	23.25
		1	49	24.35	23.15
		25	0	22.88	22.06
		25	12	22.58	22.68
		25	25	22.63	22.64
		50	0	23.05	22.78
	710.0	1	0	22.16	22.30
		1	24	22.51	22.14
		1	49	22.69	22.54
		25	0	22.04	22.87
		25	12	22.62	23.23
		25	25	22.16	22.30
		50	0	22.82	22.34
	711.0	1	0	24.85	24.72
		1	24	22.89	24.43
		1	49	22.81	22.35
		25	0	24.54	24.22
		25	12	22.69	22.40
		25	25	22.94	22.98
		50	0	22.75	22.80

LTE Band66


BW (MHz)	Frequency (MHz)	RB Configuration		Average Power [dBm]	
		Size	Offset	QPSK	16QAM
1.4	1710.7	1	0	24.29	23.15
		1	3	23.13	23.91
		1	5	24.16	22.35
		3	0	23.43	23.51
		3	2	22.58	22.57
		3	3	22.85	22.65
		6	0	22.89	23.03
	1745.0	1	0	23.67	22.81
		1	3	23.80	23.34
		1	5	23.19	22.99
		3	0	22.65	23.27
		3	2	22.89	23.23
		3	3	23.34	22.07
		6	0	22.43	23.25
	1779.3	1	0	22.80	22.55
		1	3	22.25	23.19
		1	5	22.41	23.09
		3	0	22.10	22.59
		3	2	23.34	23.02
		3	3	23.20	22.43
		6	0	23.41	22.44
3	1711.5	1	0	23.86	22.93
		1	7	22.55	22.60
		1	14	24.25	23.43
		8	0	22.37	22.46
		8	4	22.32	22.92
		8	7	22.13	22.84
		15	0	22.76	22.80
	1745.0	1	0	22.15	22.43
		1	7	22.86	22.09
		1	14	23.17	22.10
		8	0	23.07	22.25
		8	4	22.97	22.13
		8	7	22.51	22.99
		15	0	22.88	22.74

	1778.5	1	0	22.67	22.66
		1	7	22.36	22.75
		1	14	22.41	22.36
		8	0	22.44	22.89
		8	4	22.61	22.96
		8	7	22.86	22.99
		15	0	22.98	23.11
5	1712.5	1	0	22.03	22.16
		1	12	23.23	22.49
		1	24	22.92	22.53
		12	0	22.36	22.46
		12	6	22.35	22.97
		12	13	23.02	22.70
		25	0	22.22	22.89
	1745.0	1	0	24.53	24.54
		1	12	23.13	23.66
		1	24	22.41	22.84
		12	0	22.67	22.72
		12	6	22.81	22.85
		12	13	22.51	22.43
		25	0	22.68	22.07
	1777.5	1	0	23.17	22.94
		1	12	22.46	22.69
		1	24	22.54	22.45
		12	0	22.22	22.96
		12	6	22.47	22.43
		12	13	22.41	22.44
		25	0	22.29	22.86
10	1715.0	1	0	24.39	22.97
		1	24	22.97	23.21
		1	49	22.45	22.48
		25	0	22.29	22.76
		25	12	22.52	22.31
		25	25	23.03	22.67
		50	0	23.51	23.30
	1745.0	1	0	22.64	23.85
		1	24	23.95	23.46
		1	49	22.80	22.75
		25	0	22.26	22.42

		25	12	22.77	22.71
		25	25	22.34	22.68
		50	0	22.94	22.71
	1775.0	1	0	23.52	22.63
		1	24	22.35	23.27
		1	49	22.66	22.93
		25	0	22.37	22.38
		25	12	22.46	23.26
		25	25	22.62	22.27
		50	0	22.89	22.56
15	1717.5	1	0	23.03	22.89
		1	37	22.64	23.99
		1	74	22.61	21.95
		37	0	23.14	22.24
		37	18	22.41	22.23
		37	38	22.19	22.53
		75	0	23.65	23.10
	1745.0	1	0	23.10	23.60
		1	37	24.05	22.57
		1	74	23.00	22.79
		37	0	22.39	22.44
		37	18	23.10	22.56
		37	38	22.38	23.17
		75	0	22.27	22.49
	1772.5	1	0	22.29	22.09
		1	37	23.57	22.78
		1	74	22.98	22.38
		37	0	22.31	22.62
		37	18	22.79	22.32
		37	38	22.79	23.16
		75	0	22.22	22.11
20	1720.0	1	0	23.49	22.53
		1	49	22.68	23.91
		1	99	22.26	23.00
		50	0	22.38	22.13
		50	25	23.53	22.99
		50	50	23.03	22.08
		100	0	22.62	23.11
	1745.0	1	0	22.22	22.58

		1	49	24.87	22.15
		1	99	24.07	22.86
		50	0	24.67	23.46
		50	25	23.98	22.69
		50	50	24.37	24.35
		100	0	23.77	22.78
	1770.0	1	0	24.87	24.61
		1	49	22.07	22.77
		1	99	22.28	23.03
		50	0	22.71	22.71
		50	25	22.85	22.40
		50	50	22.62	22.35
		100	0	22.86	22.78


4.4 Peak-to-Average Ratio

Test Requirement:	Part 22.913(d), FCC part24.232(d) and FCC part27.50(d)(5)
Test Method:	ANSI C63.26:2015
Test Limit:	Used complementary cumulative distribution function (CCDF) of analyzer to determine that PAPR will not exceed 13 dB for more than 0.1 percent of the time
Test setup:	 <i>Note: Measurement setup for testing on Antenna connector</i>
Test Procedure:	1. The testing follows FCC KDB 971168 D01 v03r01 Section 5.7 2. The EUT was connected to spectrum and system simulator via a power divider 3. Using the CCDF measurement of spectrum analyzer; 4. Set $RBW \geq OBW$ or specified reference bandwidth; 5. Set the number of counts to a value that stabilizes the measured CCDF curve; 6. Set the measurement interval as 1ms 7. Record the maximum PAPR level associated with a probability of 0.1%.
Test Instruments:	Refer to section 3 for details
Test mode:	Refer to section 4.1 for details
Test results:	Pass


Test plots are listed as below:

Test mode	Peak to Average Ratio (dB)	Limit (dB)	Result
LTE Band 2 Middle channel/20MHz/QPSK	8.46	13	Pass
LTE Band 2 Middle channel/20MHz/16-QAM	8.43	13	Pass
LTE Band 4 Middle channel/20MHz/QPSK	7.12	13	Pass
LTE Band 4 Middle channel/20MHz/16-QAM	8.37	13	Pass
LTE Band 5 Middle channel/10MHz/QPSK	4.97	13	Pass
LTE Band 5 Middle channel/10MHz/16-QAM	6.15	13	Pass
LTE Band 7 Middle channel/20MHz/QPSK	6.47	13	Pass
LTE Band 7 Middle channel/20MHz/16-QAM	8.33	13	Pass
LTE Band 12 Middle channel/10MHz/QPSK	3.78	13	Pass
LTE Band 12 Middle channel/10MHz/16-QAM	5.22	13	Pass
LTE Band 17 Middle channel/10MHz/QPSK	4.33	13	Pass
LTE Band 17 Middle channel/10MHz/16-QAM	6.09	13	Pass
LTE Band 66 Middle channel/20MHz/QPSK	8.43	13	Pass
LTE Band 66 Middle channel/20MHz/16-QAM	8.46	13	Pass


Test Mode: LTE Band 2 Middle channel/20MHz/QPSK




Test Mode: LTE Band 2 Middle channel/20MHz/16-QAM




Test Mode: LTE Band 4 Middle channel/20MHz/QPSK




Test Mode: LTE Band 4 Middle channel/20MHz/16-QAM




Test Mode: LTE Band 5 Middle channel/10MHz/QPSK




Test Mode: LTE Band 5 Middle channel/10MHz/16-QAM




Test Mode: LTE Band 7 Middle channel/20MHz/QPSK




Test Mode: LTE Band 7 Middle channel/20MHz/16-QAM




Test Mode: LTE Band 12 Middle channel/10MHz/QPSK




Test Mode: LTE Band 12 Middle channel/10MHz/16-QAM




Test Mode: LTE Band 17 Middle channel/20MHz/QPSK



Test Mode: LTE Band 17 Middle channel/20MHz/16-QAM




Test Mode: LTE Band 66
Middle channel/20MHz/QPSK



Trace 1
Mean -23.20 dBm
Peak -11.61 dBm
Crest 11.58 dB

10 %	3.65 dB
1 %	6.67 dB
.1 %	8.43 dB
.01 %	9.74 dB

Test Mode: LTE Band 66
Middle channel/20MHz/16-QAM




Trace 1
Mean -23.28 dBm
Peak -11.97 dBm
Crest 11.31 dB

10 %	3.65 dB
1 %	6.70 dB
.1 %	8.46 dB
.01 %	9.74 dB

Note: All bandwidth and modulation are tested, only the worst results are reported.

4.5 Occupy Bandwidth

Test Requirement:	FCC part22.913(a), FCC part24.232(b) and FCC part27.53(a), FCC part 90.209
Test Method:	ANSI C63.26:2015
Test setup:	 <i>Note: Measurement setup for testing on Antenna connector</i>
Test Procedure:	1. The EUT's output RF connector was connected with a short cable to the spectrum analyzer, set center frequency to channel center frequency. 2. RBW was set to about 1%-5% of emission OBW, VBW$\geq$ 3 X RBW. 3. Set spectrum analyzer detection mode to peak, and the trace mode to max hold. 4. Use the 99% OBW function, The 99% power OBW can be found on the plot, determine the "-26dB amplitude" as equal to reference value -26dB.
Test Instruments:	Refer to section 3 for details
Test mode:	Refer to section 4.1 for details
Test results:	Pass

Measurement Data

EUT Mode	Channel Bandwidth	Mode	RB Configure		99% Occupy bandwidth (MHz)	-26dB bandwidth (MHz)
			RB Size	RB Offset		
LTE Band 2	1.4MHz	QPSK	6	0	1.09	1.23
		16-QAM	6	0	1.09	1.22
	3MHz	QPSK	15	0	2.69	2.86
		16-QAM	15	0	2.70	2.84
	5MHz	QPSK	25	0	4.51	4.78
		16-QAM	25	0	4.50	4.78
	10MHz	QPSK	50	0	9.00	9.70
		16-QAM	50	0	9.00	9.67
	15MHz	QPSK	75	0	13.55	14.55
		16-QAM	75	0	13.55	14.50
	20MHz	QPSK	100	0	18.067	19.67
		16-QAM	100	0	18.133	19.67

EUT Mode	Channel Bandwidth	Mode	RB Configure		99% Occupy bandwidth (MHz)	-26dB bandwidth (MHz)
			RB Size	RB Offset		
LTE Band 4	1.4MHz	QPSK	6	0	1.095	1.22
		16-QAM	6	0	1.095	1.22
	3MHz	QPSK	15	0	2.70	2.85
		16-QAM	15	0	2.70	2.86
	5MHz	QPSK	25	0	4.50	4.78
		16-QAM	25	0	4.51	4.78
	10MHz	QPSK	50	0	9.00	9.70
		16-QAM	50	0	8.967	9.67
	15MHz	QPSK	75	0	13.50	14.50
		16-QAM	75	0	13.50	14.55
	20MHz	QPSK	100	0	18.067	19.67
		16-QAM	100	0	18.067	19.67

EUT Mode	Channel Bandwidth	Mode	RB Configure		99% Occupy bandwidth (MHz)	-26dB bandwidth (MHz)
			RB Size	RB Offset		
LTE Band 5	1.4MHz	QPSK	6	0	1.09	1.22
		16-QAM	6	0	1.09	1.24
	3MHz	QPSK	15	0	2.69	2.85
		16-QAM	15	0	2.70	2.84
	5MHz	QPSK	25	0	4.50	4.78
		16-QAM	25	0	4.50	4.78
	10MHz	QPSK	50	0	9.00	9.70
		16-QAM	50	0	9.00	9.70

EUT Mode	Channel Bandwidth	Mode	RB Configure		99% Occupy bandwidth (MHz)	-26dB bandwidth (MHz)
			RB Size	RB Offset		
LTE Band 7	5MHz	QPSK	25	0	4.51	4.79
		16-QAM	25	0	4.51	4.77
	10MHz	QPSK	50	0	9.00	9.67
		16-QAM	50	0	9.00	9.67
	15MHz	QPSK	75	0	13.5	14.50
		16-QAM	75	0	13.5	14.55
	20MHz	QPSK	100	0	18.00	19.60
		16-QAM	100	0	18.00	19.60


EUT Mode	Channel Bandwidth	Mode	RB Configure		99% Occupy bandwidth (MHz)	-26dB bandwidth (MHz)
			RB Size	RB Offset		
LTE Band 12	1.4MHz	QPSK	25	0	1.10	1.26
		16-QAM	25	0	1.095	1.25
	3MHz	QPSK	50	0	2.71	2.86
		16-QAM	50	0	2.70	2.85
	5MHz	QPSK	25	0	4.50	4.78
		16-QAM	25	0	4.51	4.79
	10MHz	QPSK	50	0	9.00	9.70
		16-QAM	50	0	9.00	9.70

EUT Mode	Channel Bandwidth	Mode	RB Configure		99% Occupy bandwidth (MHz)	-26dB bandwidth (MHz)
			RB Size	RB Offset		
LTE Band 17	5MHz	QPSK	25	0	4.51	4.78
		16-QAM	25	0	4.50	4.79
	10MHz	QPSK	50	0	9.00	9.70
		16-QAM	50	0	9.00	9.67


EUT Mode	Channel Bandwidth	Mode	RB Configure		99% Occupy bandwidth (MHz)	-26dB bandwidth (MHz)
			RB Size	RB Offset		
LTE Band 66	1.4MHz	QPSK	6	0	1.095	1.21
		16-QAM	6	0	1.09	1.22
	3MHz	QPSK	15	0	2.69	2.84
		16-QAM	15	0	2.69	2.85
	5MHz	QPSK	25	0	4.50	4.77
		16-QAM	25	0	4.52	4.78
	10MHz	QPSK	50	0	9.00	9.67
		16-QAM	50	0	9.00	9.63
	15MHz	QPSK	75	0	13.50	14.55
		16-QAM	75	0	13.50	14.55
	20MHz	QPSK	100	0	18.067	19.67
		16-QAM	100	0	18.067	19.67

Test plot as follows:


Test Mode: LTE Band 2
Channel Bandwidth: 1.4MHz



Test Mode: LTE Band 2
Channel Bandwidth: 3MHz




QPSK




16-QAM

QPSK




16-QAM


Test Mode: LTE Band 2
Channel Bandwidth: 5MHz



Test Mode: LTE Band 2
Channel Bandwidth: 10MHz




QPSK




16-QAM

QPSK




16-QAM


Test Mode: LTE Band 2
Channel Bandwidth: 15MHz




Test Mode: LTE Band 2
Channel Bandwidth: 20MHz



QPSK




QPSK




16-QAM

16-QAM


Test Mode: LTE Band 4
Channel Bandwidth: 1.4MHz



Test Mode: LTE Band 4
Channel Bandwidth: 3MHz




QPSK




16-QAM

QPSK




16-QAM


Test Mode: LTE Band 4
Channel Bandwidth: 5MHz




Test Mode: LTE Band 4
Channel Bandwidth: 10MHz



QPSK




QPSK




16-QAM

16-QAM


Test Mode: LTE Band 4
Channel Bandwidth: 15MHz




Test Mode: LTE Band 4
Channel Bandwidth: 20MHz



QPSK




QPSK




16-QAM

16-QAM


Test Mode: LTE Band 5
Channel Bandwidth: 1.4MHz




Test Mode: LTE Band 5
Channel Bandwidth: 3MHz



QPSK




QPSK




16-QAM

16-QAM


Test Mode: LTE Band 5
Channel Bandwidth: 5MHz




Test Mode: LTE Band 5
Channel Bandwidth: 10MHz



QPSK




QPSK




16-QAM

16-QAM


Test Mode: LTE Band 7
Channel Bandwidth: 5MHz




Test Mode: LTE Band 7
Channel Bandwidth: 10MHz



QPSK




QPSK




16-QAM

16-QAM


Test Mode: LTE Band 7
Channel Bandwidth: 15MHz




Test Mode: LTE Band 7
Channel Bandwidth: 20MHz



QPSK




QPSK




16-QAM

16-QAM


Test Mode: LTE Band 12
Channel Bandwidth: 1.4MHz



Test Mode: LTE Band 12
Channel Bandwidth: 3MHz




QPSK




16-QAM

QPSK




16-QAM


Test Mode: LTE Band 12
Channel Bandwidth: 5MHz




Test Mode: LTE Band 12
Channel Bandwidth: 10MHz



QPSK




QPSK




16-QAM

16-QAM


Test Mode: LTE Band 17
Channel Bandwidth: 5MHz



Test Mode: LTE Band 17
Channel Bandwidth: 10MHz




QPSK




16-QAM

QPSK




16-QAM


Test Mode: LTE Band 66
Channel Bandwidth: 1.4MHz



Test Mode: LTE Band 66
Channel Bandwidth: 3MHz




QPSK




16-QAM

QPSK




16-QAM


Test Mode: LTE Band 66
Channel Bandwidth: 5MHz




Test Mode: LTE Band 66
Channel Bandwidth: 10MHz



QPSK




QPSK




16-QAM

16-QAM


Test Mode: LTE Band 66
Channel Bandwidth: 15MHz




Test Mode: LTE Band 66
Channel Bandwidth: 20MHz



QPSK



QPSK



16-QAM


16-QAM

Note: All bandwidth and modulation are tested, only the worst results are reported.

4.6 MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 24E & Part 27 there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

4.7 Out of band emission at antenna terminals



Test Requirement:	FCC part22.913(a), FCC part24.238(a), FCC part27.53(h) and FCC part27.53(m), FCC part90.691
Test Method:	ANSI C63.26:2015
Limit:	-13dBm Band 7/41: -25dBm
Test setup:	 <i>Note: Measurement setup for testing on Antenna connector</i>
Test Procedure:	1 The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation. 2 The resolution bandwidth of the spectrum analyzer was set at 1MHz, sufficient scans were taken to show the out of band Emissions if any up to 10th harmonic. 3 For the out of band: Set the RBW=1MHz, VBW = 3MHz, Start=30MHz, Stop= 10th harmonic. 4 Band Edge Requirements: In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions.
Test Instruments:	Refer to section 3 for details
Test mode:	Refer to section 4.1 for details
Test results:	Pass

Test plot as follows:



Conducted Spurious Emission:

Test Mode: LTE Band 2 / 1.4MHz /1RB



Test Mode: LTE Band 2 / 1.4MHz /6RB



Lowest channel




Middle channel




Highest channel



Test Mode: LTE Band 2 / 3MHz /1RB





Test Mode: LTE Band 2 / 3MHz /15RB



Lowest channel




Middle channel




Highest channel



Test Mode: LTE Band 2 / 5MHz /1RB





Test Mode: LTE Band 2 / 5MHz /25RB



Lowest channel



Middle channel



Highest channel