

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

Measurement Result

SRD

Operation Frequency: GFSK: 905 MHz~926.5MHz

Antenna Type:

Antenna 1: Planar Inverted F- Antenna(ocw=120k)

Antenna 2: Planar Inverted F- Antenna(ocw=120k)

Antenna 3: Planar Inverted F- Antenna(ocw=140k)

Antenna 4: Planar Inverted F- Antenna(ocw=140k)

Antenna 1 : -6dBi

Antenna 2 : -5dBi

Antenna 3 : -5dBi

Antenna 4 : -5dBi

R=20cm

Module 1:ant1

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric	(mW/cm2)	(mW/cm2)
905.00	GFSK-120K	15.36	15±1	16	39.811	-6.00	0.25	0.0020	0.60
915.85		15.26	15±1	16	39.811	-6.00	0.25	0.0020	0.61
926.50		15.17	15±1	16	39.811	-6.00	0.25	0.0020	0.62

ant2

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric	(mW/cm2)	(mW/cm2)
905.00	GFSK-120K	16.54	16±1	17	50.119	-5.00	0.32	0.0032	0.60
915.85		16.45	16±1	17	50.119	-5.00	0.32	0.0032	0.61
926.50		16.36	16±1	17	50.119	-5.00	0.32	0.0032	0.62

Module 2: ant3

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric	(mW/cm2)	(mW/cm2)
905.00	GFSK-140K	15.09	15±1	16	39.811	-5.00	0.32	0.0025	0.60
915.85		15.47	15±1	16	39.811	-5.00	0.32	0.0025	0.61
926.50		14.82	15±1	16	39.811	-5.00	0.32	0.0025	0.62

ant4

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric	(mW/cm2)	(mW/cm2)
905.00	GFSK-140K	15.3	15±1	16	39.811	-5.00	0.32	0.0025	0.60
915.85		15.26	15±1	16	39.811	-5.00	0.32	0.0025	0.61
926.50		15.15	15±1	16	39.811	-5.00	0.32	0.0025	0.62

SIMULTANEOUS TRANSMISSIONS

When a number of sources at different frequencies, and/or broadband sources, contribute to the total exposure, it becomes necessary to weigh each contribution relative to the MPE. To comply with the MPE, the fraction of the MPE in terms of E^2 , H^2 (or power density) incurred within each frequency interval should be determined and the sum of all such fractions should not exceed unity. In order to ensure compliance with the MPE for a controlled environment, the sum of the ratios of the power density to the corresponding MPE should not exceed unity. That is

$$\sum_{i=1}^n \frac{S_i}{MPE_i} \leq 1$$

Max. SIMULTANEOUS TRANSMISSIONS MODE

Antenna Gain: GSM/WCDMA/LTE: -1.5dBi

Band						MIMO		Verdict
	Max Conducted	Antenna	Separation distance (cm)	Evaluation result	Power density	Evaluation result	Power density Limits	
	(dBm)	Gain		(mW/cm2)	(mW/cm2)			
		(dBi)						
SRD 905 ANT1 +SRD 905 ANT2+LTE B 5	15.36	-6	20	0.006835	0.6	0.140722	1	PASS
	16.54	-5	20	0.008969	0.6			
	25	-1.5	20	0.06291	0.55			
SRD 905 ANT3 +SRD 905 ANT4+LTE B 5	15.09	-5	20	0.006423	0.6	0.136322	1	PASS
	15.3	-5	20	0.006741	0.6			
	25	-1.5	20	0.06291	0.55			

Note:

1. NO simultaneous transmissions are possible for this device of SRD ANT1+ANT2+ANT3+ANT4



Signature:

Date: 2025/08/05

NAME AND TITLE (Please print or type): Alex Li/Manager

COMPANY (Please print or type): No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China