

## TEST REPORT

**Application No.:** SZEM2102002030CR  
**Applicant:** AJAX SYSTEMS CYPRUS HOLDINGS LTD  
**Address of Applicant:** Ifigeneias, 17, Strovolos, 2007, Nicosia, Cyprus  
**Manufacturer:** AJAX SYSTEMS MANUFACTURING LIMITED LIABILITY COMPANY  
**Address of Manufacturer:** Sklyarenka, 5, Kyiv, 04073, Ukraine  
**Factory:** AJAX SYSTEMS MANUFACTURING LIMITED LIABILITY COMPANY  
**Address of Factory:** Sklyarenka, 5, Kyiv, 04073, Ukraine  
**Equipment Under Test (EUT):**  
**EUT Name:** Security control panel  
**Model No.:** Ajax Hub 2 Plus (9NA/AFA)  
**Trade Mark:** AJAX  
**FCC ID:** 2AX5VHUB2PL  
**Standard(s) :** 47 CFR Part 15, Subpart C 15.247  
**Date of Receipt:** 2021-03-23  
**Date of Test:** 2021-02-24 to 2021-03-25  
**Date of Issue:** 2021-03-29

|                     |              |
|---------------------|--------------|
| <b>Test Result:</b> | <b>Pass*</b> |
|---------------------|--------------|

\* In the configuration tested, the EUT complied with the standards specified above.

*Keny Xu*

Keny Xu  
EMC Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
**Attention:** To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

| Revision Record |         |            |          |          |
|-----------------|---------|------------|----------|----------|
| Version         | Chapter | Date       | Modifier | Remark   |
| 01              |         | 2021-03-29 |          | Original |
|                 |         |            |          |          |
|                 |         |            |          |          |

|                          |  |                            |  |  |
|--------------------------|--|----------------------------|--|--|
| Authorized for issue by: |  |                            |  |  |
|                          |  | Edison Li                  |  |  |
|                          |  | Edison Li/Project Engineer |  |  |
|                          |  | Eric Fu                    |  |  |
|                          |  | Eric Fu/Reviewer           |  |  |

## 2 Test Summary

| Radio Spectrum Technical Requirement                                                     |                                  |        |                                                 |        |
|------------------------------------------------------------------------------------------|----------------------------------|--------|-------------------------------------------------|--------|
| Item                                                                                     | Standard                         | Method | Requirement                                     | Result |
| Antenna Requirement                                                                      | 47 CFR Part 15, Subpart C 15.247 | N/A    | 47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4) | Pass   |
| Other requirements<br>Frequency Hopping<br>Spread Spectrum<br>System Hopping<br>Sequence |                                  | N/A    | 47 CFR Part 15, Subpart C 15.247(a)(1),(g),(h)  | Pass   |

| Radio Spectrum Matter Part       |                                  |                                        |                                           |        |
|----------------------------------|----------------------------------|----------------------------------------|-------------------------------------------|--------|
| Item                             | Standard                         | Method                                 | Requirement                               | Result |
| Conducted Peak Output Power      | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 7.8.5       | 47 CFR Part 15, Subpart C 15.247(b)(2)    | Pass   |
| 20dB Bandwidth                   |                                  | ANSI C63.10 (2013) Section 7.8.7       | 47 CFR Part 15, Subpart C 15.247(a)(1)    | Pass   |
| Carrier Frequencies Separation   |                                  | ANSI C63.10 (2013) Section 7.8.2       | 47 CFR Part 15, Subpart C 15.247a(1)      | Pass   |
| Hopping Channel Number           |                                  | ANSI C63.10 (2013) Section 7.8.3       | 47 CFR Part 15, Subpart C 15.247a(1)(i)   | Pass   |
| Dwell Time                       |                                  | ANSI C63.10 (2013) Section 7.8.4       | 47 CFR Part 15, Subpart C 15.247a(1)(i)   | Pass   |
| Conducted Band Edges Measurement |                                  | ANSI C63.10 (2013) Section 7.8.6       | 47 CFR Part 15, Subpart C 15.247(d)       | Pass   |
| Conducted Spurious Emissions     |                                  | ANSI C63.10 (2013) Section 7.8.8       | 47 CFR Part 15, Subpart C 15.247(d)       | Pass   |
| Radiated Spurious Emissions      |                                  | ANSI C63.10 (2013) Section 6.4,6.5,6.6 | 47 CFR Part 15, Subpart C 15.205 & 15.209 | Pass   |

Note: Both antennas have the same Tx port, RF conducted is tested under this Tx port;

| Emission Part                                       |                                   |                                |                                           |        |
|-----------------------------------------------------|-----------------------------------|--------------------------------|-------------------------------------------|--------|
| Item                                                | Standard                          | Method                         | Requirement                               | Result |
| Conducted Emissions at AC Power Line (150kHz-30MHz) | 47 CFR Part 15, Subpart C 15.247; | ANSI C63.10 (2013) Section 6.2 | 47 CFR Part 15, Subpart C 15.207 & 15.247 | Pass   |



### 3 Contents

|                                                                                        | Page |
|----------------------------------------------------------------------------------------|------|
| 1 COVER PAGE .....                                                                     | 1    |
| 2 TEST SUMMARY .....                                                                   | 3    |
| 3 CONTENTS .....                                                                       | 4    |
| 4 GENERAL INFORMATION .....                                                            | 6    |
| 4.1 DETAILS OF E.U.T. ....                                                             | 6    |
| 4.2 DESCRIPTION OF SUPPORT UNITS .....                                                 | 7    |
| 4.3 MEASUREMENT UNCERTAINTY .....                                                      | 7    |
| 4.4 TEST LOCATION .....                                                                | 8    |
| 4.5 TEST FACILITY .....                                                                | 8    |
| 4.6 DEVIATION FROM STANDARDS .....                                                     | 8    |
| 4.7 ABNORMALITIES FROM STANDARD CONDITIONS .....                                       | 8    |
| 5 EQUIPMENT LIST .....                                                                 | 9    |
| 6 RADIO SPECTRUM TECHNICAL REQUIREMENT .....                                           | 12   |
| 6.1 ANTENNA REQUIREMENT .....                                                          | 12   |
| 6.1.1 Test Requirement: .....                                                          | 12   |
| 6.2 OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM HOPPING SEQUENCE ..... | 13   |
| 6.2.1 Test Requirement: .....                                                          | 13   |
| 7 RADIO SPECTRUM MATTER TEST RESULTS .....                                             | 15   |
| 7.1 CONDUCTED PEAK OUTPUT POWER .....                                                  | 15   |
| 7.1.1 E.U.T. Operation .....                                                           | 15   |
| 7.1.2 Test Mode Description .....                                                      | 15   |
| 7.1.3 Test Setup Diagram .....                                                         | 16   |
| 7.1.4 Measurement Procedure and Data .....                                             | 16   |
| 7.2 20dB BANDWIDTH .....                                                               | 17   |
| 7.2.1 E.U.T. Operation .....                                                           | 17   |
| 7.2.2 Test Mode Description .....                                                      | 17   |
| 7.2.3 Test Setup Diagram .....                                                         | 17   |
| 7.2.4 Measurement Procedure and Data .....                                             | 17   |
| 7.3 CARRIER FREQUENCIES SEPARATION .....                                               | 18   |
| 7.3.1 E.U.T. Operation .....                                                           | 18   |
| 7.3.2 Test Mode Description .....                                                      | 18   |
| 7.3.3 Test Setup Diagram .....                                                         | 18   |
| 7.3.4 Measurement Procedure and Data .....                                             | 18   |
| 7.4 HOPPING CHANNEL NUMBER .....                                                       | 19   |
| 7.4.1 E.U.T. Operation .....                                                           | 19   |
| 7.4.2 Test Mode Description .....                                                      | 19   |
| 7.4.3 Test Setup Diagram .....                                                         | 19   |
| 7.4.4 Measurement Procedure and Data .....                                             | 19   |
| 7.5 DWELL TIME .....                                                                   | 20   |
| 7.5.1 E.U.T. Operation .....                                                           | 20   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch, China SGS-CSTC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgsgroup.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

|       |                                                           |       |
|-------|-----------------------------------------------------------|-------|
| 7.5.2 | Test Mode Description .....                               | 20    |
| 7.5.3 | Test Setup Diagram .....                                  | 20    |
| 7.5.4 | Measurement Procedure and Data .....                      | 20    |
| 7.6   | CONDUCTED BAND EDGES MEASUREMENT .....                    | 21    |
| 7.6.1 | E.U.T. Operation .....                                    | 21    |
| 7.6.2 | Test Mode Description .....                               | 21    |
| 7.6.3 | Test Setup Diagram .....                                  | 22    |
| 7.6.4 | Measurement Procedure and Data .....                      | 22    |
| 7.7   | CONDUCTED SPURIOUS EMISSIONS .....                        | 23    |
| 7.7.1 | E.U.T. Operation .....                                    | 23    |
| 7.7.2 | Test Mode Description .....                               | 23    |
| 7.7.3 | Test Setup Diagram .....                                  | 24    |
| 7.7.4 | Measurement Procedure and Data .....                      | 24    |
| 7.8   | RADIATED SPURIOUS EMISSIONS .....                         | 25    |
| 7.8.1 | E.U.T. Operation .....                                    | 25    |
| 7.8.2 | Test Mode Description .....                               | 25    |
| 7.8.3 | Test Setup Diagram .....                                  | 26    |
| 7.8.4 | Measurement Procedure and Data .....                      | 27    |
| 8     | EMISSION TEST RESULTS .....                               | 37    |
| 8.1   | CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ) ..... | 37    |
| 8.1.1 | E.U.T. Operation .....                                    | 37    |
| 8.1.2 | Test Mode Description .....                               | 37    |
| 8.1.3 | Test Setup Diagram .....                                  | 37    |
| 8.1.4 | Measurement Procedure and Data .....                      | 38    |
| 9     | TEST SETUP PHOTO .....                                    | 41    |
| 10    | EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS) .....             | 41    |
| 11    | APPENDIX FOR 15.247 .....                                 | 42-56 |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch, China, SGS EMC Laboratory.

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

## 4 General Information

### 4.1 Details of E.U.T.

|                             |                                                                                                                                                                                    |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:               | AC 110~240V, 50/60Hz, 0.1A<br>Backup Battery: 3.7V, Rechargeable Li-ion, 3000mAh                                                                                                   |
| Cable(s):                   | AC cable:142cm unshielded<br>network cable:94cm unshielded                                                                                                                         |
| Internal Source:            | More than 108MHz                                                                                                                                                                   |
| Operation Frequency:        | 905MHz to 926.5MHz                                                                                                                                                                 |
| Spectrum Spread Technology: | Frequency Hopping Spread Spectrum(FHSS)                                                                                                                                            |
| Modulation Type:            | GFSK                                                                                                                                                                               |
| Number of Channels:         | The number of available frequency hopping channels of this device is 103, only 101 channels are used in normal operation and constantly involved, 2 is reserve in case of jamming. |
| Antenna Type:               | PCB                                                                                                                                                                                |
| Antenna Gain:               | Antenna1: -5dBi, Antenna2: -6dBi<br>Note: The two antennas can't simultaneous transmission because it's forbidden in firmware.                                                     |

### Channel Lists:

| Ch. | Freq. (MHz) | Ch. | Freq. (MHz) | Ch. | Freq. (MHz) | Ch. | Freq. (MHz) | Ch. | Freq. (MHz) |
|-----|-------------|-----|-------------|-----|-------------|-----|-------------|-----|-------------|
| 1   | 916.05      | 26  | 921.05      | 51  | 915.65      | 76  | 910.65      | 101 | 915.85      |
| 2   | 916.25      | 27  | 921.25      | 52  | 915.45      | 77  | 910.45      | 102 | 905         |
| 3   | 916.45      | 28  | 921.45      | 53  | 915.25      | 78  | 910.25      | 103 | 926.5       |
| 4   | 916.65      | 29  | 921.65      | 54  | 915.05      | 79  | 910.05      |     |             |
| 5   | 916.85      | 30  | 921.85      | 55  | 914.85      | 80  | 909.85      |     |             |
| 6   | 917.05      | 31  | 922.05      | 56  | 914.65      | 81  | 909.65      |     |             |
| 7   | 917.25      | 32  | 922.25      | 57  | 914.45      | 82  | 909.45      |     |             |
| 8   | 917.45      | 33  | 922.45      | 58  | 914.25      | 83  | 909.25      |     |             |
| 9   | 917.65      | 34  | 922.65      | 59  | 914.05      | 84  | 909.05      |     |             |
| 10  | 917.85      | 35  | 922.85      | 60  | 913.85      | 85  | 908.85      |     |             |
| 11  | 918.05      | 36  | 923.05      | 61  | 913.65      | 86  | 908.65      |     |             |
| 12  | 918.25      | 37  | 923.25      | 62  | 913.45      | 87  | 908.45      |     |             |
| 13  | 918.45      | 38  | 923.45      | 63  | 913.25      | 88  | 908.25      |     |             |
| 14  | 918.65      | 39  | 923.65      | 64  | 913.05      | 89  | 908.05      |     |             |
| 15  | 918.85      | 40  | 923.85      | 65  | 912.85      | 90  | 907.85      |     |             |
| 16  | 919.05      | 41  | 924.05      | 66  | 912.65      | 91  | 907.65      |     |             |
| 17  | 919.25      | 42  | 924.25      | 67  | 912.45      | 92  | 907.45      |     |             |
| 18  | 919.45      | 43  | 924.45      | 68  | 912.25      | 93  | 907.25      |     |             |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch, China, SGS-CSTC Laboratory.

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

|    |        |    |        |    |        |     |        |  |  |
|----|--------|----|--------|----|--------|-----|--------|--|--|
| 19 | 919.65 | 44 | 924.65 | 69 | 912.05 | 94  | 907.05 |  |  |
| 20 | 919.85 | 45 | 924.85 | 70 | 911.85 | 95  | 906.85 |  |  |
| 21 | 920.05 | 46 | 925.05 | 71 | 911.65 | 96  | 906.65 |  |  |
| 22 | 920.25 | 47 | 925.25 | 72 | 911.45 | 97  | 906.45 |  |  |
| 23 | 920.45 | 48 | 925.45 | 73 | 911.25 | 98  | 906.25 |  |  |
| 24 | 920.65 | 49 | 925.65 | 74 | 911.05 | 99  | 906.05 |  |  |
| 25 | 920.85 | 50 | 925.85 | 75 | 910.85 | 100 | 905.85 |  |  |

## 4.2 Description of Support Units

| Description                                     | Manufacturer | Model No. | Serial No. |
|-------------------------------------------------|--------------|-----------|------------|
| --                                              | --           | --        | --         |
| The EUT has been tested as an independent unit. |              |           |            |

## 4.3 Measurement Uncertainty

| Test Item                                             | Measurement Uncertainty                    |
|-------------------------------------------------------|--------------------------------------------|
| Conducted Emissions at AC Power Line (150kHz-30MHz)   | ± 3.0dB (150kHz to 30MHz)                  |
| Conducted Peak Output Power                           | ± 0.75dB                                   |
| 20dB Bandwidth                                        | ± 3%                                       |
| Carrier Frequencies Separation                        | ± 7.25 x 10 <sup>-8</sup>                  |
| Hopping Channel Number                                | ± 7.25 x 10 <sup>-8</sup>                  |
| Dwell Time                                            | ± 0.37%                                    |
| Conducted Band Edges Measurement                      | ± 0.75dB                                   |
| Conducted Spurious Emissions                          | ± 0.75dB                                   |
| Radiated Emissions which fall in the restricted bands | ± 4.5dB (Below 1GHz); ± 4.8dB (Above 1GHz) |
| Radiated Spurious Emissions                           | ± 4.5dB (Below 1GHz); ± 4.8dB (Above 1GHz) |

#### 4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.  
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

#### 4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

#### 4.6 Deviation from Standards

None

#### 4.7 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
**Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com**

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

## 5 Equipment List

| Conducted Emissions at AC Power Line (150kHz-30MHz) |                  |                 |              |            |              |
|-----------------------------------------------------|------------------|-----------------|--------------|------------|--------------|
| Equipment                                           | Manufacturer     | Model No        | Inventory No | Cal Date   | Cal Due Date |
| Shielding Room                                      | ZhongYu Electron | GB-88           | SEM001-06    | 2019-06-13 | 2022-06-12   |
| EMI Test Receiver                                   | Rohde&Schwarz    | ESCI            | SEM004-02    | 2021-03-24 | 2022-03-23   |
| Measurement Software                                | AUDIX            | e3 V8.2014-6-27 | N/A          | N/A        | N/A          |
| Coaxial Cable                                       | SGS              | N/A             | SEM024-01    | 2020-07-10 | 2021-07-09   |
| LISN                                                | Rohde&Schwarz    | ENV216          | SEM007-01    | 2020-09-23 | 2021-09-22   |
| LISN                                                | ETS-LINDGREN     | 3816/2          | SEM007-02    | 2021-03-24 | 2022-03-25   |

| RF Conducted Test    |                 |                 |              |            |              |
|----------------------|-----------------|-----------------|--------------|------------|--------------|
| Equipment            | Manufacturer    | Model No        | Inventory No | Cal Date   | Cal Due Date |
| Shielding Room       | SAEMC           | MSR733          | SEM001-09    | 2019-06-13 | 2022-06-12   |
| DC Power Supply      | Rohde & Schwarz | NGSM 32/10      | SEM011-04    | 2021-03-23 | 2022-03-22   |
| Spectrum Analyzer    | Rohde & Schwarz | FSU43           | SEM004-08    | 2021-03-24 | 2022-03-23   |
| Signal Generator     | KEYSIGHT        | N5173B          | SEM006-05    | 2020-09-23 | 2021-09-22   |
| Measurement Software | TST             | TST PASS V1.0.5 | N/A          | N/A        | N/A          |
| Coaxial Cable        | SGS             | N/A             | SEM031-02    | 2020-07-10 | 2021-07-09   |
| Attenuator           | Huber+Suhner    | 6620_SMA-50-1   | SEM021-09    | 2020-05-21 | 2021-05-20   |

| Radiated Emissions       |                      |                 |              |            |              |
|--------------------------|----------------------|-----------------|--------------|------------|--------------|
| Equipment                | Manufacturer         | Model No        | Inventory No | Cal Date   | Cal Due Date |
| 3m Semi-Anechoic Chamber | ETS-LINDGREN         | N/A             | SEM001-01    | 2020-07-19 | 2023-07-18   |
| MXE EMI Receiver         | Agilent Technologies | N9038A          | SEM004-15    | 2020-11-02 | 2021-11-01   |
| BiConiLog Antenna        | ETS-LINDGREN         | 3142C           | SEM003-02    | 2019-05-24 | 2022-05-23   |
| Pre-Amplifier            | Agilent Technologies | 8447D           | SEM005-01    | 2020-04-01 | 2021-03-31   |
| Measurement Software     | AUDIX                | e3 V8.2014-6-27 | N/A          | N/A        | N/A          |
| Coaxial Cable            | SGS                  | N/A             | SEM025-01    | 2020-07-10 | 2021-07-09   |

| Radiated Emissions which fall in the restricted bands |                                    |                 |              |            |              |
|-------------------------------------------------------|------------------------------------|-----------------|--------------|------------|--------------|
| Equipment                                             | Manufacturer                       | Model No        | Inventory No | Cal Date   | Cal Due Date |
| 3m Semi-Anechoic Chamber                              | AUDIX                              | N/A             | SEM001-02    | 2018-03-31 | 2021-03-30   |
| EXA Signal Analyzer                                   | Agilent Technologies Inc           | N9010A          | SEM004-12    | 2020-04-09 | 2021-04-08   |
| Horn Antenna                                          | Rohde&Schwarz                      | HF907           | SEM003-07    | 2018-04-13 | 2021-04-12   |
| Pre-Amplifier                                         | Compliance Directions Systems Inc. | PAP-0126        | SEM004-11    | 2020-09-23 | 2021-09-22   |
| Measurement Software                                  | AUDIX                              | e3 V8.2014-6-27 | N/A          | N/A        | N/A          |
| Coaxial Cable                                         | SGS                                | N/A             | SEM026-01    | 2020-07-10 | 2021-07-09   |
| Horn Antenna                                          | Schwarzbeck                        | BBHA 9170       | SEM003-15    | 2020-11-14 | 2023-11-13   |
| Pre-Amplifier                                         | Compliance Directions Systems Inc. | PAP-2640-50     | SEM005-08    | 2021-03-24 | 2022-03-23   |

| Radiated Spurious Emissions |                                    |                 |              |            |              |
|-----------------------------|------------------------------------|-----------------|--------------|------------|--------------|
| Equipment                   | Manufacturer                       | Model No        | Inventory No | Cal Date   | Cal Due Date |
| 3m Semi-Anechoic Chamber    | AUDIX                              | N/A             | SEM001-02    | 2018-03-31 | 2021-03-30   |
| EXA Signal Analyzer         | Agilent Technologies Inc           | N9010A          | SEM004-12    | 2020-04-09 | 2021-04-08   |
| Horn Antenna                | Rohde&Schwarz                      | HF907           | SEM003-07    | 2018-04-13 | 2021-04-12   |
| Pre-Amplifier               | Compliance Directions Systems Inc. | PAP-0126        | SEM004-11    | 2020-09-23 | 2021-09-22   |
| Measurement Software        | AUDIX                              | e3 V8.2014-6-27 | N/A          | N/A        | N/A          |
| Coaxial Cable               | SGS                                | N/A             | SEM026-01    | 2020-07-10 | 2021-07-09   |
| Horn Antenna                | Schwarzbeck                        | BBHA 9170       | SEM003-15    | 2020-11-14 | 2023-11-13   |
| Pre-Amplifier               | Compliance Directions Systems Inc. | PAP-2640-50     | SEM005-08    | 2021-03-24 | 2022-03-23   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch, EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

| General used equipment          |                                           |          |              |            |              |
|---------------------------------|-------------------------------------------|----------|--------------|------------|--------------|
| Equipment                       | Manufacturer                              | Model No | Inventory No | Cal Date   | Cal Due Date |
| Humidity/ Temperature Indicator | Shanghai Meteorological Industry Factory  | ZJ1-2B   | SEM002-04    | 2020-09-15 | 2021-09-14   |
| Humidity/ Temperature Indicator | Mingle                                    | N/A      | SEM002-08    | 2020-09-15 | 2021-09-14   |
| Barometer                       | Changchun Meteorological Industry Factory | DYM3     | SEM002-01    | 2020-04-07 | 2021-04-06   |



## 6 Radio Spectrum Technical Requirement

### 6.1 Antenna Requirement

#### 6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

Limit:

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the Antenna1 is -5dBi, Antenna2 is -6dBi.

Antenna location: Refer to Internal photos.



## 6.2 Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence

### 6.2.1 Test Requirement:

47 CFR Part 15, Subpart C 15.247(a)(1),(g),(h)

Limit:

Standard Requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.


Compliance for section 15.247(a)(1):

According to Technical Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.

- > Number of shift register stages: 9
- > Length of pseudo-random sequence:  $2^9 - 1 = 511$  bits
- > Longest sequence of zeros: 8 (non-inverted signal)


Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



*Linear Feedback Shift Register for Generation of the PRBS sequence*

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

According to Technical Specification, the receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any transmitters and shift frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g):

According to Technical Specification, the system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h):

According to Technical specification, the system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

The system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.



## 7 Radio Spectrum Matter Test Results

### 7.1 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(2)  
Test Method: ANSI C63.10 (2013) Section 7.8.5  
Limit:

| Frequency range(MHz) | Output power of the intentional radiator(watt)         |
|----------------------|--------------------------------------------------------|
| 902-928              | 1 for $\geq 50$ hopping channels                       |
|                      | 0.25 for $25 \leq$ hopping channels $< 50$             |
|                      | 1 for digital modulation                               |
| 2400-2483.5          | 1 for $\geq 75$ non-overlapping hopping channels       |
|                      | 0.125 for all other frequency hopping systems          |
|                      | 1 for digital modulation                               |
| 5725-5850            | 1 for frequency hopping systems and digital modulation |

#### 7.1.1 E.U.T. Operation


Operating Environment:  
Temperature: 25 °C Humidity: 54 % RH Atmospheric Pressure: 1010 mbar

#### 7.1.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description                                                                                                |
|-----------------------|-----------|------------------------------------------------------------------------------------------------------------|
| Pre-scan              | 07        | TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation.                       |
| Final test            | 08        | Charge + TX_non-Hop mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation. |



### 7.1.3 Test Setup Diagram



### 7.1.4 Measurement Procedure and Data

Please Refer To Appendix For Details



### 7.2 20dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247(a)(1)  
Test Method: ANSI C63.10 (2013) Section 7.8.7  
Limit:

| 20 dB bandwidth | hopping frequencies |
|-----------------|---------------------|
| <250KHz         | ≥50                 |
| ≥250KHz         | ≥25                 |

#### 7.2.1 E.U.T. Operation


Operating Environment:

Temperature: 25 °C Humidity: 54 % RH Atmospheric Pressure: 1010 mbar

#### 7.2.2 Test Mode Description

| Pre-scan /<br>Final test | Mode<br>Code | Description                                                                                                |
|--------------------------|--------------|------------------------------------------------------------------------------------------------------------|
| Pre-scan                 | 07           | TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation.                       |
| Final test               | 08           | Charge + TX_non-Hop mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation. |

#### 7.2.3 Test Setup Diagram



#### 7.2.4 Measurement Procedure and Data

Please Refer To Appendix For Details

### 7.3 Carrier Frequencies Separation

Test Requirement 47 CFR Part 15, Subpart C 15.247a(1)  
 Test Method: ANSI C63.10 (2013) Section 7.8.2  
 Limit: Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.


#### 7.3.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25 °C Humidity: 54 % RH Atmospheric Pressure: 1010 mbar

#### 7.3.2 Test Mode Description

| Pre-scan /<br>Final test | Mode<br>Code | Description                                                              |
|--------------------------|--------------|--------------------------------------------------------------------------|
| Final test               | 09           | TX_Hop mode_Keep the EUT in frequency hopping mode with GFSK modulation. |

#### 7.3.3 Test Setup Diagram



#### 7.3.4 Measurement Procedure and Data

Please Refer To Appendix For Details

### 7.4 Hopping Channel Number

Test Requirement 47 CFR Part 15, Subpart C 15.247a(1)(i)  
Test Method: ANSI C63.10 (2013) Section 7.8.3  
Limit:

| Frequency range(MHz) | Number of hopping channels (minimum) |
|----------------------|--------------------------------------|
| 902-928              | 50 for 20dB bandwidth <250kHz        |
|                      | 25 for 20dB bandwidth ≥250kHz        |
| 2400-2483.5          | 15                                   |
| 5725-5850            | 75                                   |

#### 7.4.1 E.U.T. Operation


Operating Environment:

Temperature: 25 °C Humidity: 54 % RH Atmospheric Pressure: 1010 mbar

#### 7.4.2 Test Mode Description

| Pre-scan /<br>Final test | Mode<br>Code | Description                                                              |
|--------------------------|--------------|--------------------------------------------------------------------------|
| Final test               | 09           | TX_Hop mode_Keep the EUT in frequency hopping mode with GFSK modulation. |

#### 7.4.3 Test Setup Diagram



#### 7.4.4 Measurement Procedure and Data

Please Refer To Appendix For Details

### 7.5 Dwell Time

Test Requirement 47 CFR Part 15, Subpart C 15.247a(1)(i)  
Test Method: ANSI C63.10 (2013) Section 7.8.4  
Limit:

| Frequency(MHz) | Limit                                                                     |
|----------------|---------------------------------------------------------------------------|
| 902-928        | 0.4S within a 20S period(20dB bandwidth<250kHz)                           |
|                | 0.4S within a 10S period(20dB bandwidth≥250kHz)                           |
| 2400-2483.5    | 0.4S within a period of 0.4S multiplied by the number of hopping channels |
| 5725-5850      | 0.4S within a 30S period                                                  |


#### 7.5.1 E.U.T. Operation

Operating Environment:  
Temperature: 25 °C Humidity: 54 % RH Atmospheric Pressure: 1010 mbar

#### 7.5.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description                                                              |
|-----------------------|-----------|--------------------------------------------------------------------------|
| Final test            | 09        | TX_Hop mode_Keep the EUT in frequency hopping mode with GFSK modulation. |

#### 7.5.3 Test Setup Diagram



#### 7.5.4 Measurement Procedure and Data

Please Refer To Appendix For Details

## 7.6 Conducted Band Edges Measurement

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement | 47 CFR Part 15, Subpart C 15.247(d)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Test Method:     | ANSI C63.10 (2013) Section 7.8.6                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Limit:           | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)). |

### 7.6.1 E.U.T. Operation


|                        |    |    |           |         |                       |      |      |
|------------------------|----|----|-----------|---------|-----------------------|------|------|
| Operating Environment: |    |    |           |         |                       |      |      |
| Temperature:           | 25 | °C | Humidity: | 54 % RH | Atmospheric Pressure: | 1010 | mbar |

### 7.6.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description                                                                                                |
|-----------------------|-----------|------------------------------------------------------------------------------------------------------------|
| Pre-scan              | 07        | TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation.                       |
| Final test            | 08        | Charge + TX_non-Hop mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation. |
| Final test            | 09        | TX_Hop mode_Keep the EUT in frequency hopping mode with GFSK modulation.                                   |



### 7.6.3 Test Setup Diagram



### 7.6.4 Measurement Procedure and Data

Please Refer To Appendix For Details



## 7.7 Conducted Spurious Emissions

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement | 47 CFR Part 15, Subpart C 15.247(d)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Test Method:     | ANSI C63.10 (2013) Section 7.8.8                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Limit:           | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)). |

### 7.7.1 E.U.T. Operation


|                        |    |    |           |         |                       |      |      |
|------------------------|----|----|-----------|---------|-----------------------|------|------|
| Operating Environment: |    |    |           |         |                       |      |      |
| Temperature:           | 25 | °C | Humidity: | 54 % RH | Atmospheric Pressure: | 1010 | mbar |

### 7.7.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description                                                                                                |
|-----------------------|-----------|------------------------------------------------------------------------------------------------------------|
| Pre-scan              | 07        | TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation.                       |
| Final test            | 08        | Charge + TX_non-Hop mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation. |



### 7.7.3 Test Setup Diagram



### 7.7.4 Measurement Procedure and Data

Please Refer To Appendix For Details



## 7.8 Radiated Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209  
Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6  
Measurement Distance: 3m  
Limit:

| Frequency(MHz) | Field strength(microvolts/meter) | Measurement distance(meters) |
|----------------|----------------------------------|------------------------------|
| 0.009-0.490    | 2400/F(kHz)                      | 300                          |
| 0.490-1.705    | 24000/F(kHz)                     | 30                           |
| 1.705-30.0     | 30                               | 30                           |
| 30-88          | 100                              | 3                            |
| 88-216         | 150                              | 3                            |
| 216-960        | 200                              | 3                            |
| Above 960      | 500                              | 3                            |

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.


### 7.8.1 E.U.T. Operation

Operating Environment:  
Temperature: 25 °C Humidity: 54 % RH Atmospheric Pressure: 1010 mbar

### 7.8.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description                                                                                                |
|-----------------------|-----------|------------------------------------------------------------------------------------------------------------|
| Pre-scan              | 07        | TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation.                       |
| Final test            | 08        | Charge + TX_non-Hop mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation. |

### 7.8.3 Test Setup Diagram



#### 7.8.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


#### Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
4. Pretest the EUT at Jeweller antenna1 and Jeweller antenna2, found the Jeweller antenna1 which is worst case for FHSS mode, So, Only the worst test data is recorded in the report.



### Duty Cycle:

| On time(ms) | T(ms) | Duty Cycle(%) | Duty Factor |
|-------------|-------|---------------|-------------|
| 10.25641    | 100   | 0.1025641     | -19.78      |



### Note:


Average Level=Peak Level + Duty Factor

Duty Factor=20\*log(Duty Cycle)

Duty Cycle=On Time/T



Test Mode: 08; Polarity: Horizontal; Modulation: GFSK; Channel: Low



Condition: 3m HORIZONTAL


Job No. : 02030CR

Test Mode: 08

|      | Freq   | Cable | Ant    | Preamp | Read  | Limit  | Over   |              |
|------|--------|-------|--------|--------|-------|--------|--------|--------------|
|      | MHz    | Loss  | Factor | Factor | Level | Level  | Line   | Limit Remark |
|      | MHz    | dB    | dB/m   | dB     | dBuV  | dBuV/m | dBuV/m | dB           |
| 1    | 30.00  | 0.60  | 23.00  | 27.74  | 26.77 | 22.63  | 40.00  | -17.37 QP    |
| 2    | 63.31  | 0.80  | 12.80  | 27.66  | 27.22 | 13.16  | 40.00  | -26.84 QP    |
| 3    | 108.65 | 1.11  | 13.74  | 27.55  | 26.70 | 14.00  | 43.50  | -29.50 QP    |
| 4    | 179.39 | 1.18  | 15.41  | 27.22  | 27.80 | 17.17  | 43.50  | -26.33 QP    |
| 5    | 426.52 | 2.36  | 22.13  | 27.51  | 28.54 | 25.52  | 46.00  | -20.48 QP    |
| 6 pp | 785.09 | 3.24  | 28.00  | 27.76  | 26.97 | 30.45  | 46.00  | -15.55 QP    |



Test Mode: 08; Polarity: Vertical; Modulation: GFSK; Channel: Low



Condition: 3m VERTICAL


Job No. : 02030CR

Test Mode: 08

|      | Freq   | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level  | Limit  | Over   | Remark |
|------|--------|------------|------------|---------------|------------|--------|--------|--------|--------|
|      | MHz    | dB         | dB/m       | dB            | dBuV       | dBuV/m | dBuV/m | dB     |        |
| 1    | 34.40  | 0.65       | 20.66      | 27.72         | 24.68      | 18.27  | 40.00  | -21.73 | QP     |
| 2    | 62.21  | 0.80       | 12.97      | 27.66         | 26.57      | 12.68  | 40.00  | -27.32 | QP     |
| 3    | 102.00 | 1.10       | 13.94      | 27.60         | 27.61      | 15.05  | 43.50  | -28.45 | QP     |
| 4    | 142.32 | 1.15       | 13.71      | 27.37         | 27.39      | 14.88  | 43.50  | -28.62 | QP     |
| 5    | 319.94 | 2.07       | 19.80      | 26.99         | 27.82      | 22.70  | 46.00  | -23.30 | QP     |
| 6 pp | 771.45 | 3.19       | 28.02      | 27.78         | 27.52      | 30.95  | 46.00  | -15.05 | QP     |



Test Mode: 08; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 02030CR/02031CR  
Mode : 905MHz TX SE  
Note :

|   | Freq     | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level | Limit Line | Over Limit | Remark  |
|---|----------|------------|------------|---------------|------------|-------|------------|------------|---------|
|   | MHz      | dB         |            | dB/m          | dB         | dBuV  | dBuV/m     | dBuV/m     | dB      |
| 1 | 1808.551 | 3.51       | 27.10      | 40.11         | 50.81      | 41.31 | 74.00      | -32.69     | Peak    |
| 2 | 2715.000 | 4.68       | 29.71      | 40.58         | 55.81      | 49.62 | 74.00      | -24.38     | Peak    |
| 3 | 3620.000 | 5.71       | 31.95      | 41.16         | 49.26      | 45.76 | 74.00      | -28.24     | Peak    |
| 4 | 4525.000 | 6.78       | 33.63      | 41.89         | 42.66      | 41.18 | 54.00      | -12.82     | Average |
| 5 | 4525.000 | 6.78       | 33.63      | 41.89         | 62.44      | 60.96 | 74.00      | -13.04     | Peak    |
| 6 | 5430.000 | 8.05       | 34.54      | 42.34         | 49.66      | 49.91 | 74.00      | -24.09     | Peak    |
| 7 | 8145.000 | 9.63       | 36.79      | 40.49         | 29.55      | 35.48 | 54.00      | -18.52     | Average |
| 8 | 8145.000 | 9.63       | 36.79      | 40.49         | 49.33      | 55.26 | 74.00      | -18.74     | Peak    |



Test Mode: 08; Polarity: Vertical; Modulation:GFSK; Channel:Low




Site : chamber  
Condition: 3m VERTICAL  
Job No : 02030CR/02031CR  
Mode : 905MHz TX SE  
Note :

|   | Freq     | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level | Limit Line | Over Limit | Remark  |
|---|----------|------------|------------|---------------|------------|-------|------------|------------|---------|
|   | MHz      | dB         |            | dB/m          | dB         | dBuV  | dBuV/m     | dBuV/m     | dB      |
| 1 | 1810.000 | 3.51       | 27.10      | 40.11         | 47.71      | 38.21 | 74.00      | -35.79     | Peak    |
| 2 | 2715.000 | 4.68       | 29.71      | 40.58         | 52.73      | 46.54 | 74.00      | -27.46     | Peak    |
| 3 | 3620.000 | 5.71       | 31.95      | 41.16         | 48.30      | 44.80 | 74.00      | -29.20     | Peak    |
| 4 | 4525.000 | 6.78       | 33.63      | 41.89         | 37.01      | 35.53 | 54.00      | -18.47     | Average |
| 5 | 4525.000 | 6.78       | 33.63      | 41.89         | 56.79      | 55.31 | 74.00      | -18.69     | Peak    |
| 6 | 5430.000 | 8.05       | 34.54      | 42.34         | 48.68      | 48.93 | 74.00      | -25.07     | Peak    |
| 7 | 8145.000 | 9.63       | 36.79      | 40.49         | 31.84      | 37.77 | 54.00      | -16.23     | Average |
| 8 | 8145.000 | 9.63       | 36.79      | 40.49         | 51.62      | 57.55 | 74.00      | -16.45     | Peak    |



Test Mode: 08; Polarity: Horizontal; Modulation: GFSK; Channel: Middle




Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 02030CR/02031CR  
Mode : 915.85MHz TX SE  
Note :

|   | Freq     | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level | Limit Line | Over Limit | Remark  |
|---|----------|------------|------------|---------------|------------|-------|------------|------------|---------|
|   | MHz      | dB         |            | dB/m          | dB         | dBuV  | dBuV/m     | dBuV/m     | dB      |
| 1 | 1831.700 | 3.53       | 27.18      | 40.12         | 50.00      | 40.59 | 74.00      | -33.41     | Peak    |
| 2 | 2747.550 | 4.70       | 29.85      | 40.59         | 52.31      | 46.27 | 74.00      | -27.73     | Peak    |
| 3 | 3663.400 | 5.78       | 32.04      | 41.18         | 47.68      | 44.32 | 74.00      | -29.68     | Peak    |
| 4 | 4579.250 | 6.84       | 33.69      | 41.94         | 40.84      | 39.43 | 54.00      | -14.57     | Average |
| 5 | 4579.250 | 6.84       | 33.69      | 41.94         | 60.62      | 59.21 | 74.00      | -14.79     | Peak    |
| 6 | 7326.800 | 8.85       | 36.16      | 41.39         | 48.08      | 51.70 | 74.00      | -22.30     | Peak    |
| 7 | 8242.650 | 9.76       | 36.85      | 40.29         | 47.02      | 53.34 | 74.00      | -20.66     | Peak    |



Test Mode: 08; Polarity: Vertical; Modulation: GFSK; Channel: Middle




Site : chamber  
Condition: 3m VERTICAL  
Job No : 02030CR/02031CR  
Mode : 915.85MHz TX SE  
Note :

|   | Freq     | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level | Limit Line | Over Limit | Remark  |
|---|----------|------------|------------|---------------|------------|-------|------------|------------|---------|
|   | MHz      | dB         |            | dB/m          | dB         | dBuV  | dBuV/m     | dBuV/m     | dB      |
| 1 | 1831.700 | 3.53       | 27.18      | 40.12         | 46.50      | 37.09 | 74.00      | -36.91     | Peak    |
| 2 | 2747.550 | 4.70       | 29.85      | 40.59         | 52.05      | 46.01 | 74.00      | -27.99     | Peak    |
| 3 | 3663.400 | 5.78       | 32.04      | 41.18         | 46.64      | 43.28 | 74.00      | -30.72     | Peak    |
| 4 | 4579.250 | 6.84       | 33.69      | 41.94         | 55.08      | 53.67 | 74.00      | -20.33     | Peak    |
| 5 | 7326.800 | 8.85       | 36.16      | 41.39         | 47.87      | 51.49 | 74.00      | -22.51     | Peak    |
| 6 | 8242.650 | 9.76       | 36.85      | 40.29         | 29.87      | 36.19 | 54.00      | -17.81     | Average |
| 7 | 8242.650 | 9.76       | 36.85      | 40.29         | 49.65      | 55.97 | 74.00      | -18.03     | Peak    |



Test Mode: 08; Polarity: Horizontal; Modulation:GFSK; Channel:High




Site : chamber  
Condition: 3m HORIZONTAL  
Job No : 02030CR/02031CR  
Mode : 926.5MHz TX SE  
Note :

|   | Freq     | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level  | Limit Line | Over Limit | Remark  |
|---|----------|------------|------------|---------------|------------|--------|------------|------------|---------|
|   | MHz      | dB         | dB/m       | dB            | dBuV       | dBuV/m | dBuV/m     | dB         |         |
| 1 | 1853.000 | 3.54       | 27.26      | 40.13         | 49.21      | 39.88  | 74.00      | -34.12     | Peak    |
| 2 | 2779.500 | 4.72       | 29.99      | 40.61         | 54.13      | 48.23  | 74.00      | -25.77     | Peak    |
| 3 | 3706.000 | 5.84       | 32.12      | 41.21         | 47.44      | 44.19  | 74.00      | -29.81     | Peak    |
| 4 | 4632.500 | 6.90       | 33.76      | 41.99         | 39.99      | 38.66  | 54.00      | -15.34     | Average |
| 5 | 4632.500 | 6.90       | 33.76      | 41.99         | 59.77      | 58.44  | 74.00      | -15.56     | Peak    |
| 6 | 7412.000 | 8.93       | 36.23      | 41.32         | 48.13      | 51.97  | 74.00      | -22.03     | Peak    |
| 7 | 8338.500 | 9.89       | 36.91      | 40.10         | 46.12      | 52.82  | 74.00      | -21.18     | Peak    |



Test Mode: 08; Polarity: Vertical; Modulation:GFSK; Channel: High



Site : chamber  
Condition: 3m VERTICAL  
Job No : 02030CR/02031CR  
Mode : 926.5MHz TX SE  
Note :

|   | Freq     | Cable Loss | Ant Factor | Preamp Factor | Read Level | Level  | Limit Line | Over Limit | Remark  |
|---|----------|------------|------------|---------------|------------|--------|------------|------------|---------|
|   | MHz      | dB         | dB/m       | dB            | dBuV       | dBuV/m | dBuV/m     | dB         |         |
| 1 | 1853.000 | 3.54       | 27.26      | 40.13         | 47.45      | 38.12  | 74.00      | -35.88     | Peak    |
| 2 | 2782.060 | 4.72       | 29.99      | 40.61         | 53.81      | 47.91  | 74.00      | -26.09     | Peak    |
| 3 | 3706.000 | 5.84       | 32.12      | 41.21         | 47.69      | 44.44  | 74.00      | -29.56     | Peak    |
| 4 | 4626.946 | 6.90       | 33.76      | 41.99         | 54.40      | 53.07  | 74.00      | -20.93     | Peak    |
| 5 | 7412.000 | 8.93       | 36.23      | 41.32         | 48.48      | 52.32  | 74.00      | -21.68     | Peak    |
| 6 | 8338.500 | 9.89       | 36.91      | 40.10         | 28.94      | 35.64  | 54.00      | -18.36     | Average |
| 7 | 8338.500 | 9.89       | 36.91      | 40.10         | 48.72      | 55.42  | 74.00      | -18.58     | Peak    |



## 8 Emission Test Results

### 8.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement: 47 CFR Part 15, Subpart C 15.247 & 15.207

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

| Frequency of emission(MHz) | Conducted limit(dBμV) |           |
|----------------------------|-----------------------|-----------|
|                            | Quasi-peak            | Average   |
| 0.15-0.5                   | 66 to 56*             | 56 to 46* |
| 0.5-5                      | 56                    | 46        |
| 5-30                       | 60                    | 50        |

\*Decreases with the logarithm of the frequency.

Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz

#### 8.1.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C


Humidity: 54 % RH

Atmospheric Pressure: 1010 mbar

#### 8.1.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description                                                                                                |
|-----------------------|-----------|------------------------------------------------------------------------------------------------------------|
| Final test            | 08        | Charge + TX_non-Hop mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation. |

#### 8.1.3 Test Setup Diagram




#### 8.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor



Test Mode: 08; Line: Live Line




Site : Shielding Room  
Condition: Line  
Job No. : 02030CR  
Test mode: 08

|    | Freq    | Cable Loss | LISN Factor | Read Level | Level | Limit Line | Over Limit | Remark  |
|----|---------|------------|-------------|------------|-------|------------|------------|---------|
|    | MHz     | dB         | dB          | dBuV       | dBuV  | dBuV       | dB         |         |
| 1  | 0.1650  | 0.03       | 9.63        | 27.07      | 36.73 | 55.21      | -18.48     | Average |
| 2  | 0.1650  | 0.03       | 9.63        | 41.18      | 50.84 | 65.21      | -14.37     | QP      |
| 3  | 0.1976  | 0.04       | 9.64        | 21.37      | 31.05 | 53.71      | -22.66     | Average |
| 4  | 0.1976  | 0.04       | 9.64        | 35.49      | 45.17 | 63.71      | -18.54     | QP      |
| 5  | 0.2244  | 0.04       | 9.65        | 15.13      | 24.82 | 52.66      | -27.84     | Average |
| 6  | 0.2244  | 0.04       | 9.65        | 32.07      | 41.76 | 62.66      | -20.90     | QP      |
| 7  | 0.8045  | 0.09       | 9.68        | 7.52       | 17.29 | 46.00      | -28.71     | Average |
| 8  | 0.8045  | 0.09       | 9.68        | 16.73      | 26.50 | 56.00      | -29.50     | QP      |
| 9  | 5.6234  | 0.16       | 9.79        | 17.47      | 27.42 | 50.00      | -22.58     | Average |
| 10 | 5.6234  | 0.16       | 9.79        | 22.50      | 32.45 | 60.00      | -27.55     | QP      |
| 11 | 29.2387 | 0.21       | 10.01       | 25.03      | 35.25 | 50.00      | -14.75     | Average |
| 12 | 29.2387 | 0.21       | 10.01       | 28.50      | 38.72 | 60.00      | -21.28     | QP      |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Test Mode: 08; Line: Neutral Line



Site : Shielding Room  
Condition: Neutral  
Job No. : 02030CR  
Test mode: 08

|    | Freq    | Cable Loss | LISN Factor | Read Level | Level | Limit Line | Over Limit | Remark  |
|----|---------|------------|-------------|------------|-------|------------|------------|---------|
|    | MHz     | dB         | dB          | dBuV       | dBuV  | dBuV       | dB         |         |
| 1  | 0.1722  | 0.03       | 9.63        | 20.05      | 29.71 | 54.86      | -25.15     | Average |
| 2  | 0.1722  | 0.03       | 9.63        | 36.29      | 45.95 | 64.86      | -18.91     | QP      |
| 3  | 0.1965  | 0.04       | 9.63        | 21.09      | 30.76 | 53.76      | -23.00     | Average |
| 4  | 0.1965  | 0.04       | 9.63        | 34.83      | 44.50 | 63.76      | -19.26     | QP      |
| 5  | 0.2304  | 0.04       | 9.64        | 17.20      | 26.88 | 52.44      | -25.56     | Average |
| 6  | 0.2304  | 0.04       | 9.64        | 31.40      | 41.08 | 62.44      | -21.36     | QP      |
| 7  | 0.8217  | 0.09       | 9.67        | -0.99      | 8.77  | 46.00      | -37.23     | Average |
| 8  | 0.8217  | 0.09       | 9.67        | 8.40       | 18.16 | 56.00      | -37.84     | QP      |
| 9  | 5.6532  | 0.16       | 9.79        | 18.88      | 28.83 | 50.00      | -21.17     | Average |
| 10 | 5.6532  | 0.16       | 9.79        | 23.71      | 33.66 | 60.00      | -26.34     | QP      |
| 11 | 29.2387 | 0.21       | 10.10       | 24.41      | 34.72 | 50.00      | -15.28     | Average |
| 12 | 29.2387 | 0.21       | 10.10       | 27.64      | 37.95 | 60.00      | -22.05     | QP      |



## 9 Test Setup Photo

Refer to Setup Photos

## 10 EUT Constructional Details (EUT Photos)

Refer to external and internal photos for SZEM2102002030CR



## 11 Appendix for 15.247

### 1. Bandwidth

#### 1.1 Test Result

| Test Mode | Frequency (MHz) | TX Type | ANT No. | 20dB Bandwidth    | Limit (KHz) | Verdict |
|-----------|-----------------|---------|---------|-------------------|-------------|---------|
|           |                 |         |         | Test Result (MHz) |             |         |
| TX        | 905             | SISO    | 1       | 0.107             | ≤250        | PASS    |
|           | 915.85          | SISO    | 1       | 0.106             | ≤250        | PASS    |
|           | 926.5           | SISO    | 1       | 0.116             | ≤250        | PASS    |

| Test Mode | Frequency (MHz) | TX Type | ANT No. | 99% Occupied Bandwidth |                     |
|-----------|-----------------|---------|---------|------------------------|---------------------|
|           |                 |         |         | Test Result (MHz)      |                     |
| TX        | 905             | SISO    | 1       | 0.098                  | Only for Report Use |
|           | 915.85          | SISO    | 1       | 0.096                  | Only for Report Use |
|           | 926.5           | SISO    | 1       | 0.103                  | Only for Report Use |





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch, China, 518057


No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



### 1.2 Test Graph - 20dB Bandwidth





### 1.3 Test Graph - 99% Occupied Bandwidth








### 2. Maximum Conducted Output Power

#### 2.1 Test Result

| Test Mode | Frequency (MHz) | Tx Type | Measured Peak Output Power (dBm) | Limits (dBm) | Verdict |
|-----------|-----------------|---------|----------------------------------|--------------|---------|
|           |                 |         | Ant 1                            |              |         |
| TX        | 905             | SISO    | 13.09                            | 30           | PASS    |
|           | 915.85          | SISO    | 12.84                            | 30           | PASS    |
|           | 926.5           | SISO    | 13.23                            | 30           | PASS    |

#### 2.2 Test Graph






### 3. Carrier frequency separation

#### 3.1 Test Result

| Test Mode | TX Type | ANT No. | Channel Separation (MHz) | Limits (MHz) | Verdict |
|-----------|---------|---------|--------------------------|--------------|---------|
| TX        | SISO    | 1       | 0.200                    | ≥0.106       | PASS    |

#### 3.2 Test Graph




### 4. Number of hopping frequencies

#### 4.1 Test Result

| Test Mode | TX Type | ANT No. | Num of Hopping Frequencies | Limits | Verdict |
|-----------|---------|---------|----------------------------|--------|---------|
| TX        | SISO    | 1       | 102                        | ≥50    | PASS    |

#### 4.2 Test Graph



Note: The number of available frequency hopping channels of this device is 103, only 101 channels are used in normal operation and constantly involved, 2 is reserve in case of jamming.

## 5. Time of Occupancy (Dwell Time)


### 5.1 Test Result

| Test Mode | Packet Type | TX Type | ANT No. | Duration of Single Pulse (ms) | Observation Period (s) | Num of Pulse in Observation Period | Dwell Time (ms) | Limits (ms) | Verdict |
|-----------|-------------|---------|---------|-------------------------------|------------------------|------------------------------------|-----------------|-------------|---------|
| TX        | NoPT        | SISO    | 1       | 11.851                        | 20                     | 12                                 | 142.212         | ≤400        | PASS    |

Dwell Time (ms)= Duration of Single Pulse (ms)\* Num of Pulse in Observation Period



### 5.2 Test Graph





## 6. Unwanted Emissions in Non-restricted Frequency Bands



### 6.1 Test Result



| Test Mode | Frequency (MHz) | TX Type | ANT No. | Spurious Conducted Emission (dBm) | Limits (dBm) | Verdict |
|-----------|-----------------|---------|---------|-----------------------------------|--------------|---------|
| TX        | 905             | SISO    | 1       | Refer to test graph               | -6.80        | PASS    |
|           | 915.85          | SISO    | 1       | Refer to test graph               | -6.80        | PASS    |
|           | 926.5           | SISO    | 1       | Refer to test graph               | -6.80        | PASS    |
|           | Hopping         | SISO    | 1       | Refer to test graph               | -6.80        | PASS    |





### 6.2 Test Graph









- End of the Report -

