

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: 2AX97-A43

### EUT Specification

| EUT                               | Wifi Digital Photo Frame                                                                                                                                                                                                          |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Frequency band (Operating)</b> | <input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz<br><input type="checkbox"/> WLAN: 5.18GHz ~ 5.24GHz<br><input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz<br><input type="checkbox"/> Others: BDR+EDR: 2402-2480MHz |
| <b>Device category</b>            | <input type="checkbox"/> Portable (<20cm separation)<br><input checked="" type="checkbox"/> Mobile (>20cm separation)<br><input type="checkbox"/> Others _____                                                                    |
| <b>Exposure classification</b>    | <input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm <sup>2</sup> )<br><input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm <sup>2</sup> )                                     |
| <b>Antenna diversity</b>          | <input checked="" type="checkbox"/> Single antenna<br><input type="checkbox"/> Multiple antennas<br><input type="checkbox"/> Tx diversity<br><input type="checkbox"/> Rx diversity<br><input type="checkbox"/> Tx/Rx diversity    |
| <b>Antenna gain (Max)</b>         | 2dBi                                                                                                                                                                                                                              |
| <b>Directional Gain (Max)</b>     | /                                                                                                                                                                                                                                 |
| <b>Evaluation applied</b>         | <input checked="" type="checkbox"/> MPE Evaluation<br><input type="checkbox"/> SAR Evaluation                                                                                                                                     |

Limits for Maximum Permissible Exposure(MPE)

| Frequency Range(MHz)                                         | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density(mW/cm <sup>2</sup> ) | Average Time |
|--------------------------------------------------------------|------------------------------|------------------------------|------------------------------------|--------------|
| <b>(A) Limits for Occupational/Control Exposures</b>         |                              |                              |                                    |              |
| <b>300-1500</b>                                              | --                           | --                           | <b>F/300</b>                       | <b>6</b>     |
| <b>1500-100000</b>                                           | --                           | --                           | <b>5</b>                           | <b>6</b>     |
| <b>(B) Limits for General Population/Uncontrol Exposures</b> |                              |                              |                                    |              |
| <b>300-1500</b>                                              | --                           | --                           | <b>F/1500</b>                      | <b>6</b>     |
| <b>1500-100000</b>                                           | --                           | --                           | <b>1</b>                           | <b>30</b>    |

### **Friis transmission formula: $P_d = \frac{P_{out} \cdot G}{4 \cdot \pi \cdot R^2}$**

Where

$P_d$  = Power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in Mw

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

### **Max Measurement Result**

| Operating Mode | Measured Power | Tune up tolerance | Max. Tune up Power | Antenna Gain | Power density at 20cm  | Power density Limits (mW/cm <sup>2</sup> ) |
|----------------|----------------|-------------------|--------------------|--------------|------------------------|--------------------------------------------|
|                | (dBm)          | (dBm)             | (dBm)              | (dBi)        | (mW/ cm <sup>2</sup> ) |                                            |
| 2.4G WIFI      | 13.32          | 13.32 ±1          | 14.32              | 2            | 0.0085                 | 1                                          |