

TEST REPORT

Product : Otoadd F1
Trade mark : Otoadd
Model/Type reference : HEB-003, PEB-003
Serial Number : N/A
Report Number : EED32R81030202
FCC ID : 2AX9Z-HEB-003
Date of Issue : Jul. 17, 2025
Test Standards : 47 CFR Part 15 Subpart C
Test result : PASS

Prepared for:

RelaJet Tech (Taiwan) Co., Ltd.
8 F., No. 150, Sec. 4, Nanjing E. Rd., Songshan Dist., Taipei City 105036,
Taiwan (R.O.C.)

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Park, Zone 70, Bao'an District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Compiled by:

Wei shi fang

Keven Tan

Reviewed by:

Tom Chen

Frazer Li

Approved by:

Aaron Ma

Aaron Ma

Date:

Jul. 17, 2025



Check No.:6604230625

1 Contents

	Page
1 CONTENTS	2
2 TEST SUMMARY	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 TEST CONFIGURATION	6
3.4 TEST ENVIRONMENT	7
3.5 DESCRIPTION OF SUPPORT UNITS	7
4 TEST RESULTS AND MEASUREMENT DATA	12
4.1 ANTENNA REQUIREMENT	12
4.2 AC POWER LINE CONDUCTED EMISSIONS	13
4.3 MAXIMUM CONDUCTED OUTPUT POWER	19
4.4 20dB EMISSION BANDWIDTH	20
4.5 CARRIER FREQUENCY SEPARATION	21
4.6 NUMBER OF HOPPING CHANNEL	22
4.7 TIME OF OCCUPANCY	23
4.8 BAND EDGE MEASUREMENTS	24
4.9 CONDUCTED SPURIOUS EMISSIONS	25
4.10 PSEUDORANDOM FREQUENCY HOPPING SEQUENCE	26
4.11 RADIATED SPURIOUS EMISSION & RESTRICTED BANDS	28
5 APPENDIX A	62
6 PHOTOGRAPHS OF TEST SETUP	63
7 PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	65

2 Test Summary

Test Item	Test Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	PASS
Maximum Conducted Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(1)	PASS
20dB Emission Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	PASS
Carrier Frequency Separation	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	PASS
Number of Hopping Channels	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	PASS
Time of Occupancy	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	PASS
Pseudorandom Frequency Hopping Sequence	47 CFR Part 15, Subpart C Section 15.247(b)(4)	PASS
Band Edge Measurements	47 CFR Part 15, Subpart C Section 15.247(d)	PASS
Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	PASS
Radiated Spurious emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	PASS
Restricted bands around fundamental frequency	47 CFR Part 15, Subpart C Section 15.205/15.209	PASS

Remark:

Both left and right headphones have been tested. The report only contains the worst data (left headphones).

3 General Information

3.1 Client Information

Applicant:	RelaJet Tech (Taiwan) Co., Ltd.
Address of Applicant:	8 F., No. 150, Sec. 4, Nanjing E. Rd., Songshan Dist., Taipei City 105036, Taiwan (R.O.C.)
Manufacturer 1:	RelaJet Tech (Taiwan) Co., Ltd.
Address of Manufacturer 1:	9F.-1, No. 37, Guangfu N. Rd., Songshan Dist., Taipei City 105033, Taiwan (R.O.C.)
Manufacturer 2:	DONGGUAN SHUNHEFENG ELECTRICITY CO LTD
Address of Manufacturer 2:	NO.36, SHUNXING 6 ROAD,DAJINGTOU VILLAGE, DALANG TOWN,DONGGUAN CITY,GUANG DONG. CHINA
Factory Name 1:	RelaJet Tech (Taiwan) Co., Ltd.
Factory Address 1:	9F.-1, No. 37, Guangfu N. Rd., Songshan Dist., Taipei City 105033, Taiwan (R.O.C.)
Factory Name 2:	DONGGUAN SHUNHEFENG ELECTRICITY CO LTD
Factory Address 2:	NO.36, SHUNXING 6 ROAD,DAJINGTOU VILLAGE, DALANG TOWN,DONGGUAN CITY,GUANG DONG. CHINA

3.2 General Description of EUT

Product Name:	Otoadd F1		
Model No.:	HEB-003, PEB-003		
Test Model No.:	HEB-003		
Trade Mark:	Otoadd		
Product Type:	☐ Mobile ☒ Portable ☐ Fixed Location		
Operation Frequency:	2402MHz-2480MHz		
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)		
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK		
Number of Channel:	79		
Hopping Channel Type:	Adaptive Frequency Hopping systems		
Antenna Type:	Chip Antenna		
Antenna Gain:	L: 1.8 dBi R: 1.8 dBi		
Power Supply:	Battery:	DC 3.7V 0.259Wh	
Test Voltage:	DC 3.7V		
Sample Received Date:	Jun. 25, 2025		
Sample tested Date:	Jun. 25, 2025 to Jul. 05, 2025		
Remark: Model No.: HEB-003, PEB-003 Only the model HEB-003 was tested, Both models share the same electrical, PCB and layout, PEB-003 has some functions disabled via firmware / software configuration.			

Operation Frequency each of channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency(MHz)
The lowest channel (CH0)	2402
The middle channel (CH39)	2441
The highest channel (CH78)	2480

3.3 Test Configuration

EUT Test Software Settings:		
Test Software:	BlueTest3	
EUT Power Grade:	Default (Power level is built-in set parameters and cannot be changed and selected)	
Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.		
Mode	Channel	Frequency(MHz)
DH1/DH3/DH5	CH0	2402
	CH39	2441
	CH78	2480
2DH1/2DH3/2DH5	CH0	2402
	CH39	2441
	CH78	2480
3DH1/3DH3/3DH5	CH0	2402
	CH39	2441
	CH78	2480

3.4 Test Environment

Operating Environment:	
Radiated Spurious Emissions:	
Temperature:	22~25.0 °C
Humidity:	50~55 % RH
Atmospheric Pressure:	1010mbar
Conducted Emissions:	
Temperature:	22~25.0 °C
Humidity:	50~55 % RH
Atmospheric Pressure:	1010mbar
RF Conducted:	
Temperature:	22~25.0 °C
Humidity:	50~55 % RH
Atmospheric Pressure:	1010mbar

3.5 Description of Support Units

The EUT has been tested with associated equipment below.

1) Support equipment

Description	Manufacturer	Model No.	Certification	Supplied by
Netbook	Dell	P77F	FCC&CE	CTI

3.6 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Hongwei Industrial Park, Zone 70, Bao'an District, Shenzhen, Guangdong, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

3.7 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.9×10^{-8}
2	RF power, conducted	0.46dB (30MHz-1GHz)
		0.55dB (1GHz-40GHz)
3	Radiated Spurious emission test	3.3dB (9kHz-30MHz)
		4.3dB (30MHz-1GHz)
		4.5dB (1GHz-18GHz)
		3.4dB (18GHz-40GHz)
4	Conduction emission	3.5dB (9kHz-150kHz)
		3.1dB (150kHz-30MHz)
5	Temperature test	0.64°C
6	Humidity test	3.8%
7	DC power voltages	0.026%

3.8 Equipment List

RF test system					
Equipment	Manufacturer	Model No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Communication test set	R&S	CMW500	107929	06-16-2025	06-15-2026
Signal Generator	R&S	SMBV100A	1407.6004K02-262149-CV	09-02-2024	09-01-2025
Spectrum Analyzer	R&S	FSV40	101200	07-18-2024	07-17-2025
RF control unit(power unit)	MWRF-test	MW100-RFCB	MW220620CTI-42	06-16-2025	06-15-2026
High-low temperature test chamber	Dong Guang Qin Zhuo	LK-80GA	QZ20150611879	11-30-2024	11-29-2025
Temperature/ Humidity Indicator	biaozhi	HM10	1804186	05-26-2025	05-25-2026
BT&WI-FI Automatic test software	MWRF-test	MTS 8310	V2.0.0.0	---	---
Spectrum Analyzer	R&S	FSV3044	101509	02-14-2025	02-13-2026

Conducted disturbance Test					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
				(mm-dd-yyyy)	(mm-dd-yyyy)
Receiver	R&S	ESCI	100435	04-08-2025	04-07-2026
Temperature/ Humidity Indicator	Defu	TH128	/	03-31-2025	03-30-2026
LISN	R&S	ENV216	100098	09-19-2024	09-18-2025
Barometer	changchun	DYM3	1188	---	---
Test software	Fara	EZ-EMC	EMC-CON 3A1.1	---	---
Capacitive voltage probe	Schwarzbeck	CVP 9222C	00124	06-07-2025	06-06-2026
ISN	TESEQ	ISN T800	30297	12-05-2024	12-04-2025

3M Semi-anechoic Chamber (2)- Radiated disturbance Test					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
				(mm-dd-yyyy)	(mm-dd-yyyy)
3M Chamber & Accessory Equipment	TDK	SAC-3	---	01/13/2024	01/12/2027
Receiver	R&S	ESC17	100938-003	09/07/2024	09/06/2025
Spectrum Analyzer	R&S	FSV40	101200	07/18/2024	07/17/2025
TRILOG Broadband Antenna	schwarzbeck	VULB 9163	9163-618	05/14/2025	05/13/2026
Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-076	04/07/2025	04/06/2026
Microwave Preamplifier	Tonscend	EMC051845SE	980380	12/05/2024	12/04/2025
Horn Antenna	A.H.SYSTEMS	SAS-574	374	07/02/2023	07/01/2026
Horn Antenna	ETS-LINGREN	BBHA 9120D	9120D-1869	04/07/2025	04/06/2026
Preamplifier	Agilent	11909A	12-1	03/03/2025	03/02/2026
Preamplifier	CD	PAP-1840-60	6041.6042	05/26/2025	05/25/2026
Test software	Fara	EZ-EMC	EMEC-3A1-Pre	---	---
Cable line	Fulai(7M)	SF106	5219/6A	---	---
Cable line	Fulai(6M)	SF106	5220/6A	---	---
Cable line	Fulai(3M)	SF106	5216/6A	---	---
Cable line	Fulai(3M)	SF106	5217/6A	---	---

3M full-anechoic Chamber					
Equipment	Manufacturer	Model No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Fully Anechoic Chamber	TDK	FAC-3	---	01-09-2024	01-08-2027
Receiver	Keysight	N9038A	MY57290136	01-04-2025	01-03-2026
Spectrum Analyzer	Keysight	N9020B	MY57111112	01-14-2025	01-13-2026
Spectrum Analyzer	Keysight	N9030B	MY57140871	01-14-2025	01-13-2026
TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	9163-1148	04-12-2025	04-11-2026
Horn Antenna	Schwarzbeck	BBHA 9170	9170-832	04-12-2025	04-11-2026
Horn Antenna	ETS-LINDGREN	3117	57407	07-03-2024 06-29-2025	07-02-2025 06-28-2026
Preamplifier	EMCI	EMC001330	980563	03-03-2025	03-02-2026
Preamplifier	Tonscend	TAP-011858	AP21B806112	07-18-2024	07-17-2025
Preamplifier	Tonscend	EMC051845SE	980380	12-05-2024	12-04-2025
Communication test set	R&S	CMW500	102898	01-04-2025	01-03-2026
Temperature/ Humidity Indicator	biaozhi	GM1360	EE1186631	03-31-2025	03-30-2026
RSE Automatic test software	JS Tonscend	JS36-RSE	V4.0.0.0	---	---
Cable line	Times	SFT205-NMSM-2.50M	394812-0001		---
Cable line	Times	SFT205-NMSM-2.50M	394812-0002	---	---
Cable line	Times	SFT205-NMSM-2.50M	394812-0003	---	---
Cable line	Times	SFT205-NMSM-2.50M	393495-0001	---	---
Cable line	Times	EMC104-NMNM-1000	SN160710	---	---
Cable line	Times	SFT205-NMSM-3.00M	394813-0001	---	---
Cable line	Times	SFT205-NMNM-1.50M	381964-0001	---	---
Cable line	Times	SFT205-NMSM-7.00M	394815-0001	---	---
Cable line	Times	HF160-KMKM-3.00M	393493-0001	---	---

4 Test results and Measurement Data

4.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
EUT Antenna:	Please see Internal photos
The antenna is Chip antenna. The best case gain of the antenna is: L: 1.8 dBi R: 1.8 dBi	


Hotline:400-6788-333 www.cti-cert.com E-mail:info@cti-cert.com Complaint call:0755-33681700 Complaint E-mail:complaint@cti-cert.com

	5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type at the lowest, middle, high channel.
Final Test Mode:	Through Pre-scan, find the DH5 of data type and GFSK modulation at the lowest channel is the worst case. Only the worst case is recorded in the report.
Test Results:	Pass

Measurement Data

Ear L:

Live line:




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1500	45.20	10.28	55.48	66.00	-10.52	QP	
2		0.1500	31.97	10.28	42.25	56.00	-13.75	AVG	
3		0.2265	39.59	10.19	49.78	62.58	-12.80	QP	
4		0.2310	35.21	10.19	45.40	52.41	-7.01	AVG	
5		0.2760	31.06	10.15	41.21	50.94	-9.73	AVG	
6		0.3660	23.51	10.10	33.61	48.59	-14.98	AVG	
7		0.4245	37.20	10.09	47.29	57.36	-10.07	QP	
8		0.4695	22.54	10.08	32.62	46.52	-13.90	AVG	
9		0.4785	37.54	10.08	47.62	56.37	-8.75	QP	
10		0.5190	37.54	10.08	47.62	56.00	-8.38	QP	
11	*	0.6360	38.89	10.11	49.00	56.00	-7.00	QP	
12		0.6360	25.56	10.11	35.67	46.00	-10.33	AVG	

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1545	32.72	10.28	43.00	55.75	-12.75	AVG	
2		0.1598	42.81	10.27	53.08	65.47	-12.39	QP	
3		0.2085	28.42	10.20	38.62	53.26	-14.64	AVG	
4		0.2130	39.14	10.20	49.34	63.09	-13.75	QP	
5		0.2535	31.73	10.17	41.90	51.64	-9.74	AVG	
6		0.2625	38.19	10.16	48.35	61.35	-13.00	QP	
7		0.2714	31.10	10.15	41.25	51.07	-9.82	AVG	
8		0.3615	24.29	10.11	34.40	48.69	-14.29	AVG	
9		0.4245	37.69	10.09	47.78	57.36	-9.58	QP	
10		0.5235	36.23	10.08	46.31	56.00	-9.69	QP	
11	*	0.6270	37.32	10.11	47.43	56.00	-8.57	QP	
12		0.6406	23.17	10.11	33.28	46.00	-12.72	AVG	


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Ear R:

Live line:

80.0 dBuV




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1545	43.54	10.28	53.82	65.75	-11.93	QP	
2		0.1590	30.85	10.27	41.12	55.52	-14.40	AVG	
3		0.2220	39.70	10.19	49.89	62.74	-12.85	QP	
4		0.2310	30.21	10.19	40.40	52.41	-12.01	AVG	
5		0.2535	38.64	10.17	48.81	61.64	-12.83	QP	
6		0.2670	29.95	10.16	40.11	51.21	-11.10	AVG	
7		0.2985	27.09	10.13	37.22	50.28	-13.06	AVG	
8		0.4695	36.96	10.08	47.04	56.52	-9.48	QP	
9		0.4695	21.28	10.08	31.36	46.52	-15.16	AVG	
10		0.5190	37.07	10.08	47.15	56.00	-8.85	QP	
11	*	0.5685	37.52	10.09	47.61	56.00	-8.39	QP	
12		0.6405	22.87	10.11	32.98	46.00	-13.02	AVG	

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1500	44.82	10.28	55.10	66.00	-10.90	QP	
2		0.1545	33.04	10.28	43.32	55.75	-12.43	AVG	
3		0.2400	31.57	10.18	41.75	52.10	-10.35	AVG	
4		0.2625	38.34	10.16	48.50	61.35	-12.85	QP	
5		0.2670	31.34	10.16	41.50	51.21	-9.71	AVG	
6		0.3660	23.50	10.10	33.60	48.59	-14.99	AVG	
7		0.4155	33.93	10.09	44.02	57.54	-13.52	QP	
8		0.5144	37.01	10.08	47.09	56.00	-8.91	QP	
9		0.5775	36.53	10.10	46.63	56.00	-9.37	QP	
10	*	0.6315	38.06	10.11	48.17	56.00	-7.83	QP	
11		0.6360	25.64	10.11	35.75	46.00	-10.25	AVG	
12		0.8745	18.84	10.17	29.01	46.00	-16.99	AVG	


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.


4.3 Maximum Conducted Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	Use the following spectrum analyzer settings: Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel RBW > the 20 dB bandwidth of the emission being measured VBW ≥ RBW Sweep = auto Detector function = peak Trace = max hold Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission.
Limit:	21dBm
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type.
Test Results:	Refer to Appendix A


4.4 20dB Emission Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Use the following spectrum analyzer settings for 20dB Bandwidth measurement. Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel; $1\% \leq RBW \leq 5\%$ of the 20 dB bandwidth; $VBW \geq 3RBW$; Sweep = auto; Detector function = peak; Trace = max hold. 4. Measure and record the results in the test report.
Limit:	NA
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type.
Test Results:	Refer to Appendix A


4.5 Carrier Frequency Separation

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Enable the EUT hopping function. 4. Use the following spectrum analyzer settings: Span = wide enough to capture the peaks of two adjacent channels; RBW is set to approximately 30% of the channel spacing, adjust as necessary to best identify the center of each individual channel; VBW$\geq$RBW; Sweep = auto; Detector function = peak; Trace = max hold. 5. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Record the value in report.
Limit:	Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.
Exploratory Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type.
Test Results:	Refer to Appendix A


4.6 Number of Hopping Channel

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Enable the EUT hopping function. 4. Use the following spectrum analyzer settings: Span = the frequency band of operation; set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller; VBW≥RBW; Sweep= auto; Detector function = peak; Trace = max hold. 5. The number of hopping frequency used is defined as the number of total channel. 6. Record the measurement data in report.
Limit:	Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.
Test Mode:	Hopping transmitting with all kind of modulation
Test Results:	Refer to Appendix A


4.7 Time of Occupancy

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Enable the EUT hopping function. 4. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW shall be $\leq$ channel spacing and where possible RBW should be set $\gg 1/T$, where T is the expected dwell time per channel; VBW $\geq$ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold. 5. Measure and record the results in the test report.
Limit:	The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.
Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type.
Test Results:	Refer to Appendix A



4.8 Band edge Measurements

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	1. Set to the maximum power setting and enable the EUT transmit continuously. 2. Set RBW = 100 kHz, VBW = 300 kHz ($\geq$RBW). Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used. 3. Enable hopping function of the EUT and then repeat step 2 and 3. 4. Measure and record the results in the test report.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Hopping and Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type.
Test Results:	Refer to Appendix A

4.9 Conducted Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. 4. Measure and record the results in the test report. 5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type.
Test Results:	Refer to Appendix A

4.10 Pseudorandom Frequency Hopping Sequence

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1), (h) requirement:
	The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals. Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section. The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.
Compliance for section 15.247(a)(1)	
	According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones. • Number of shift register stages: 9 • Length of pseudo-random sequence: $2^9 - 1 = 511$ bits • Longest sequence of zeros: 8 (non-inverted signal)  <i>Linear Feedback Shift Register for Generation of the PRBS sequence</i> An example of Pseudorandom Frequency Hopping Sequence as follow:  Each frequency used equally on the average by each transmitter. According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.
Compliance for section 15.247(g)	
	According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom

hopping frequency system.
Compliance for section 15.247(h)
According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels. According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.

4.11 Radiated Spurious Emission & Restricted bands

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Peak	100 kHz	300kHz	Peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10kHz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.					

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:

- a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- Note: For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the


	measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel (2402MHz),the middle channel (2441MHz),the Highest channel (2480MHz) h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type and GFSK modulation is the worst case. Pretest the EUT at Transmitting mode, For below 1GHz part, through pre-scan, the worst case is the lowest channel. Only the worst case is recorded in the report.
Test Results:	Pass

Radiated Spurious Emission below 1GHz:

During the test, the Radiates Emission from 30MHz to 1GHz was performed in all modes, only the worst case lowest channel of DH5 for GFSK of Ear L was recorded in the report.

Horizontal:


Test Graph



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		54.8636	0.12	13.97	14.09	40.00	-25.91	QP	200	7
2		99.1275	2.20	13.06	15.26	43.50	-28.24	QP	200	18
3		147.4811	6.53	10.37	16.90	43.50	-26.60	QP	200	81
4		278.1643	9.14	15.75	24.89	46.00	-21.11	QP	100	352
5		438.0405	5.98	20.06	26.04	46.00	-19.96	QP	200	122
6	*	600.0571	4.76	23.35	28.11	46.00	-17.89	QP	100	100

Vertical:

Test Graph



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		30.3279	9.00	12.37	21.37	40.00	-18.63	QP	100	17
2		50.4443	0.02	14.52	14.54	40.00	-25.46	QP	100	49
3		147.6623	9.54	10.37	19.91	43.50	-23.59	QP	100	188
4		222.7549	11.30	13.64	24.94	46.00	-21.06	QP	200	143
5		345.3529	12.37	17.94	30.31	46.00	-15.69	QP	100	7
6	*	438.1942	13.34	20.06	33.40	46.00	-12.60	QP	100	177

Radiated Spurious Emission above 1GHz:

Mode:			GFSK Transmitting			Channel:		2402 MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1204.1469	11.65	37.00	48.65	74.00	25.35	Pass	H	PK
2	1640.8427	14.05	36.92	50.97	74.00	23.03	Pass	H	PK
3	3996.5164	-11.70	51.29	39.59	74.00	34.41	Pass	H	PK
4	4992.3828	-8.13	49.55	41.42	74.00	32.58	Pass	H	PK
5	7772.6182	-1.73	46.71	44.98	74.00	29.02	Pass	H	PK
6	11291.3028	2.43	44.17	46.60	74.00	27.40	Pass	H	PK
7	1109.874	11.28	38.74	50.02	74.00	23.98	Pass	V	PK
8	1460.164	13.01	36.90	49.91	74.00	24.09	Pass	V	PK
9	3566.1877	-13.60	52.97	39.37	74.00	34.63	Pass	V	PK
10	5846.5398	-5.44	47.31	41.87	74.00	32.13	Pass	V	PK
11	8563.7209	-0.47	45.62	45.15	74.00	28.85	Pass	V	PK
12	11261.4008	2.41	43.90	46.31	74.00	27.69	Pass	V	PK

Mode:			GFSK Transmitting			Channel:		2441 MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1245.6164	11.61	36.58	48.19	74.00	25.81	Pass	H	PK
2	1525.235	13.38	36.82	50.20	74.00	23.80	Pass	H	PK
3	3442.6795	-13.88	54.91	41.03	74.00	32.97	Pass	H	PK
4	4851.9735	-8.46	50.00	41.54	74.00	32.46	Pass	H	PK
5	6651.2934	-3.95	46.98	43.03	74.00	30.97	Pass	H	PK
6	11277.0018	2.43	45.47	47.90	74.00	26.10	Pass	H	PK
7	1188.2792	11.51	36.75	48.26	74.00	25.74	Pass	V	PK
8	1601.5068	13.73	35.80	49.53	74.00	24.47	Pass	V	PK
9	3188.5126	-14.49	56.48	41.99	74.00	32.01	Pass	V	PK
10	4766.1677	-8.63	50.09	41.46	74.00	32.54	Pass	V	PK
11	7752.4668	-1.47	46.49	45.02	74.00	28.98	Pass	V	PK
12	11158.0439	2.05	43.79	45.84	74.00	28.16	Pass	V	PK

Mode:			GFSK Transmitting			Channel:		2480 MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1162.1441	11.48	36.51	47.99	74.00	26.01	Pass	H	PK
2	1528.7019	13.43	36.22	49.65	74.00	24.35	Pass	H	PK
3	3354.2736	-14.01	54.06	40.05	74.00	33.95	Pass	H	PK
4	4911.1274	-8.23	50.92	42.69	74.00	31.31	Pass	H	PK
5	7157.0271	-3.19	46.81	43.62	74.00	30.38	Pass	H	PK
6	10263.5842	1.96	44.62	46.58	74.00	27.42	Pass	H	PK
7	1149.3433	11.50	37.26	48.76	74.00	25.24	Pass	V	PK
8	1602.1735	13.74	35.86	49.60	74.00	24.40	Pass	V	PK
9	3528.4852	-13.83	53.19	39.36	74.00	34.64	Pass	V	PK
10	4929.3286	-8.13	49.22	41.09	74.00	32.91	Pass	V	PK
11	6713.6976	-3.33	46.93	43.60	74.00	30.40	Pass	V	PK
12	9722.7482	1.28	44.05	45.33	74.00	28.67	Pass	V	PK

Mode:			$\pi/4$ DQPSK Transmitting			Channel:		2402 MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1147.6098	11.49	37.15	48.64	74.00	25.36	Pass	H	PK
2	1539.7693	13.49	36.74	50.23	74.00	23.77	Pass	H	PK
3	3377.0251	-13.99	54.45	40.46	74.00	33.54	Pass	H	PK
4	5130.8421	-7.45	49.62	42.17	74.00	31.83	Pass	H	PK
5	7188.2292	-3.35	46.12	42.77	74.00	31.23	Pass	H	PK
6	10275.9351	1.93	44.68	46.61	74.00	27.39	Pass	H	PK
7	1213.2142	11.59	37.03	48.62	74.00	25.38	Pass	V	PK
8	1730.0487	14.18	36.80	50.98	74.00	23.02	Pass	V	PK
9	3879.5086	-12.02	52.14	40.12	74.00	33.88	Pass	V	PK
10	4960.5307	-8.05	49.27	41.22	74.00	32.78	Pass	V	PK
11	6867.1078	-3.53	46.51	42.98	74.00	31.02	Pass	V	PK
12	9617.4412	1.34	44.39	45.73	74.00	28.27	Pass	V	PK

Mode:			$\pi/4$ DQPSK Transmitting			Channel:		2441 MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dB μ V]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Result	Polarity	Remark
1	1159.344	11.48	36.75	48.23	74.00	25.77	Pass	H	PK
2	1904.727	14.70	36.26	50.96	74.00	23.04	Pass	H	PK
3	3596.0897	-13.29	52.59	39.30	74.00	34.70	Pass	H	PK
4	5126.2918	-7.47	49.29	41.82	74.00	32.18	Pass	H	PK
5	7576.9551	-2.18	46.91	44.73	74.00	29.27	Pass	H	PK
6	10229.1319	1.79	44.67	46.46	74.00	27.54	Pass	H	PK
7	1268.6846	11.91	36.20	48.11	74.00	25.89	Pass	V	PK
8	1860.324	14.50	36.57	51.07	74.00	22.93	Pass	V	PK
9	3546.0364	-13.79	52.97	39.18	74.00	34.82	Pass	V	PK
10	5002.7835	-8.11	48.99	40.88	74.00	33.12	Pass	V	PK
11	6344.473	-4.41	47.21	42.80	74.00	31.20	Pass	V	PK
12	9127.3085	0.11	45.66	45.77	74.00	28.23	Pass	V	PK

Mode:			$\pi/4$ DQPSK Transmitting			Channel:		2480 MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dB μ V]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Result	Polarity	Remark
1	1158.5439	11.49	36.55	48.04	74.00	25.96	Pass	H	PK
2	1540.3027	13.49	36.19	49.68	74.00	24.32	Pass	H	PK
3	3729.9987	-12.82	53.54	40.72	74.00	33.28	Pass	H	PK
4	5043.0862	-8.08	50.41	42.33	74.00	31.67	Pass	H	PK
5	7706.3138	-1.65	46.15	44.50	74.00	29.50	Pass	H	PK
6	11122.9415	2.10	43.61	45.71	74.00	28.29	Pass	H	PK
7	1151.8768	11.50	37.84	49.34	74.00	24.66	Pass	V	PK
8	1436.0291	13.08	34.93	48.01	74.00	25.99	Pass	V	PK
9	3825.555	-12.25	53.30	41.05	74.00	32.95	Pass	V	PK
10	4567.2545	-9.53	49.66	40.13	74.00	33.87	Pass	V	PK
11	7188.2292	-3.35	49.12	45.77	74.00	28.23	Pass	V	PK
12	11674.1783	2.53	45.12	47.65	74.00	26.35	Pass	V	PK

Mode:			8DPSK Transmitting			Channel:		2402 MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1265.8844	11.91	36.65	48.56	74.00	25.44	Pass	H	PK
2	1584.1723	13.60	36.40	50.00	74.00	24.00	Pass	H	PK
3	3469.9813	-13.88	53.48	39.60	74.00	34.40	Pass	H	PK
4	5098.3399	-7.58	48.96	41.38	74.00	32.62	Pass	H	PK
5	6782.6022	-3.49	47.20	43.71	74.00	30.29	Pass	H	PK
6	9659.0439	1.22	44.54	45.76	74.00	28.24	Pass	H	PK
7	1155.077	11.49	38.02	49.51	74.00	24.49	Pass	V	PK
8	1530.302	13.46	36.05	49.51	74.00	24.49	Pass	V	PK
9	3835.3057	-12.18	52.10	39.92	74.00	34.08	Pass	V	PK
10	5006.0337	-8.09	50.13	42.04	74.00	31.96	Pass	V	PK
11	6649.9933	-3.97	46.84	42.87	74.00	31.13	Pass	V	PK
12	9735.099	1.30	44.23	45.53	74.00	28.47	Pass	V	PK

Mode:			8DPSK Transmitting			Channel:		2441 MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1165.211	11.46	36.58	48.04	74.00	25.96	Pass	H	PK
2	1700.0467	14.08	35.99	50.07	74.00	23.93	Pass	H	PK
3	3736.4991	-12.84	51.69	38.85	74.00	35.15	Pass	H	PK
4	5100.29	-7.57	49.41	41.84	74.00	32.16	Pass	H	PK
5	7054.9703	-3.30	47.50	44.20	74.00	29.80	Pass	H	PK
6	10272.6848	1.94	43.67	45.61	74.00	28.39	Pass	H	PK
7	1247.7498	11.61	36.85	48.46	74.00	25.54	Pass	V	PK
8	1751.1167	14.09	36.44	50.53	74.00	23.47	Pass	V	PK
9	3795.003	-12.48	51.98	39.50	74.00	34.50	Pass	V	PK
10	4844.1729	-8.49	49.73	41.24	74.00	32.76	Pass	V	PK
11	7101.1234	-3.21	46.07	42.86	74.00	31.14	Pass	V	PK
12	10227.8319	1.78	43.74	45.52	74.00	28.48	Pass	V	PK

Mode:			8DPSK Transmitting			Channel:		2480 MHz	
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1148.9433	11.49	36.74	48.23	74.00	25.77	Pass	H	PK
2	1491.7661	13.34	36.34	49.68	74.00	24.32	Pass	H	PK
3	3826.2051	-12.25	52.09	39.84	74.00	34.16	Pass	H	PK
4	5078.8386	-7.79	49.01	41.22	74.00	32.78	Pass	H	PK
5	7650.41	-2.27	46.93	44.66	74.00	29.34	Pass	H	PK
6	10248.6332	1.97	43.87	45.84	74.00	28.16	Pass	H	PK
7	1210.9474	11.61	37.62	49.23	74.00	24.77	Pass	V	PK
8	1586.3058	13.63	36.18	49.81	74.00	24.19	Pass	V	PK
9	3411.4774	-13.95	53.41	39.46	74.00	34.54	Pass	V	PK
10	4564.0043	-9.56	49.64	40.08	74.00	33.92	Pass	V	PK
11	6783.2522	-3.49	46.29	42.80	74.00	31.20	Pass	V	PK
12	10234.3323	1.84	43.26	45.10	74.00	28.90	Pass	V	PK

Remark:


- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, the disturbance above 10GHz and below 30MHz was very low. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

Restricted bands:

Test plot as follows:

EUT_Name		Test_Model	
Test_Mode	GFSK Transmitting	Test_Frequency	2402MHz
Tset_Engineer	chenjun	Test_Date	2025/07/01
Remark	Ear L		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390	15.96	34.64	50.60	74.00	23.40	PASS	Horizontal	PK
2	2390	15.96	17.66	33.62	54.00	20.38	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	GFSK Transmitting	Test_Frequency	2402MHz
Tset_Engineer	chenjun	Test_Date	2025/07/01
Remark	Ear L		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	2390	15.96	34.20	50.16	74.00	23.84	PASS	Vertical	PK
2	2390	15.96	17.78	33.74	54.00	20.26	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	GFSK Transmitting	Test_Frequency	2480MHz
Tset_Engineer	chenjun	Test_Date	2025/07/01
Remark	Ear L		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2483.5	16.29	36.66	52.95	74.00	21.05	PASS	Horizontal	PK
2	2483.5	16.29	26.63	42.92	54.00	11.08	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	GFSK Transmitting	Test_Frequency	2480MHz
Tset_Engineer	chenjun	Test_Date	2025/07/01
Remark	Ear L		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2483.5	16.29	35.13	51.42	74.00	22.58	PASS	Vertical	PK
2	2483.5	16.29	25.89	42.18	54.00	11.82	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	π /4DQPSK Transmitting	Test_Frequency	2402MHz
Tset_Engineer	chenjun	Test_Date	2025/07/01
Remark	Ear L		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390	15.96	34.58	50.54	74.00	23.46	PASS	Horizontal	PK
2	2390	15.96	18.13	34.09	54.00	19.91	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	π /4DQPSK Transmitting	Test_Frequency	2402MHz
Tset_Engineer	chenjun	Test_Date	2025/07/01
Remark	Ear L		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390	15.96	35.18	51.14	74.00	22.86	PASS	Vertical	PK
2	2390	15.96	17.88	33.84	54.00	20.16	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	π /4DQPSK Transmitting	Test_Frequency	2480MHz
Tset_Engineer	chenjun	Test_Date	2025/07/01
Remark	Ear L		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2483.5	16.29	35.38	51.67	74.00	22.33	PASS	Horizontal	PK
2	2483.5	16.29	26.47	42.76	54.00	11.24	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	π /4DQPSK Transmitting	Test_Frequency	2480MHz
Tset_Engineer	chenjun	Test_Date	2025/07/01
Remark	Ear L		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2483.5	16.29	36.28	52.57	74.00	21.43	PASS	Vertical	PK
2	2483.5	16.29	26.17	42.46	54.00	11.54	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	8DPSK Transmitting	Test_Frequency	2402MHz
Tset_Engineer	chenjun	Test_Date	2025/07/01
Remark	Ear L		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	2390	15.96	34.59	50.55	74.00	23.45	PASS	Horizontal	PK
2	2390	15.96	17.66	33.62	54.00	20.38	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	8DPSK Transmitting	Test_Frequency	2402MHz
Tset_Engineer	chenjun	Test_Date	2025/07/01
Remark	Ear L		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390	15.96	33.65	49.61	74.00	24.39	PASS	Vertical	PK
2	2390	15.96	17.89	33.85	54.00	20.15	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	8DPSK Transmitting	Test_Frequency	2480MHz
Tset_Engineer	chenjun	Test_Date	2025/07/01
Remark	Ear L		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2483.5	16.29	36.02	52.31	74.00	21.69	PASS	Horizontal	PK
2	2483.5	16.29	26.32	42.61	54.00	11.39	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	8DPSK Transmitting	Test_Frequency	2480MHz
Tset_Engineer	chenjun	Test_Date	2025/07/01
Remark	Ear L		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2483.5	16.29	36.39	52.68	74.00	21.32	PASS	Vertical	PK
2	2483.5	16.29	26.00	42.29	54.00	11.71	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	GFSK Transmitting	Test_Frequency	2402Mhz
Tset_Engineer	chenjun	Test_Date	2025/06/30
Remark	Ear R		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390	15.96	37.99	53.95	74.00	20.05	PASS	Horizontal	PK
2	2390	15.96	27.03	42.99	54.00	11.01	PASS	Horizontal	AV

EUT_Name		Test_Model	
Test_Mode	GFSK Transmitting	Test_Frequency	2402Mhz
Tset_Engineer	chenjun	Test_Date	2025/06/30
Remark	Ear R		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390	15.96	37.96	53.92	74.00	20.08	PASS	Vertical	PK
2	2390	15.96	27.43	43.39	54.00	10.61	PASS	Vertical	AV

EUT_Name		Test_Model	
Test_Mode	GFSK Transmitting	Test_Frequency	2480Mhz
Tset_Engineer	chenjun	Test_Date	2025/06/30
Remark	Ear R		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2483.5	16.29	38.15	54.44	74.00	19.56	PASS	Horizontal	PK
2	2483.5	16.29	30.28	46.57	54.00	7.43	PASS	Horizontal	AV