

## FCC RF Exposure Evaluation

### 1. Product Information

FCC ID	2AXBRCZ-ROBOTDF-DZ
Product name	Chuangze brand autonomous mobile intelligent disinfection robot (CZ-RobotDf-DZ type)
Model number	CZ-RobotDf-DZ
Power supply	Input: AC 100-240V, 50/60Hz, 180W max Output: DC 29V, 6A DC 25.9V by Battery, 60Ah
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V4.2(DSS) GFSK for Bluetooth V4.2(DTS) IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK); IEEE 802.11g/n: OFDM(64QAM, 16QAM, QPSK, BPSK)
Antenna Type	External Antenna
Antenna Gain	0dBi(Max.)
Hardware version	/
Software version	/
FCC Operation frequency	2402MHz ~ 2480MHz 2412MHz-2462MHz
Exposure category	General population/uncontrolled environment
EUT Type	Production Unit
Device Type	Mobile Devices

### 2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is  $\leq 1.0$ . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

### 3. Limit

#### 3. 1 Refer Evaluation Method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices

### 3. 2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure				
Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6
Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure				
Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

\*=Plane-wave equivalent power density

### 4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

### 5. Antenna Information

Artemis Antenna can only use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna type and antenna number	Operate frequency band	Maximum antenna gain	Note
Antenna	External Antenna	2402MHz ~ 2480MHz 2412MHz-2462MHz	0dBi	BT WIFI Antenna

## 6. Conducted Power

### < BT Max Conducted Power >

Mode	Channel	Frequency(MHz)	Max Conducted Power (dBm)
GFSK	0	2402	1.059
	39	2441	2.267
	78	2480	1.128
$\pi/4$ DQPSK	0	2402	0.266
	39	2441	1.429
	78	2480	0.343
8DPSK	0	2402	0.351
	39	2441	1.578
	78	2480	0.451

### < BT LE Max Conducted Power >

Mode	Channel	Frequency(MHz)	Max Conducted Power (dBm)
GFSK	0	2402	0.938
	19	2440	2.138
	39	2480	1.016

### <2.4G WLAN Max Conducted Power >

Mode	Channel	Frequency(MHz)	Max Conducted Power (dBm)
IEEE 802.11b	1	2412	13.72
	6	2437	13.48
	11	2462	13.71
IEEE 802.11g	1	2412	14.69
	6	2437	14.4
	11	2462	14.28
IEEE 802.11n HT20	1	2412	14.06
	6	2437	14.33
	11	2462	14.4
IEEE 802.11n HT40	3	2422	14.19
	6	2437	14.23
	9	2452	14.05

## 7. Manufacturing Tolerance

### <BT>

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	1.0	2.0	1.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
$\pi/4$ DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	0	1.0	0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
8DPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	0	1.0	0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

### <BT LE>

GFSK (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	0	2.0	1.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

### <2.4G WIFI>

11B (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11G (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20SISO (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40SISO (Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

## 8. Measurement Results

### 8.1 Standalone MPE

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance,  $r = 20\text{cm}$ , as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

[Antenna ]

<BT>

Band/Mode	RF output power		Antenna Gain (dBi)	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW			
GFSK	3.0	1.9953	0	0.0004	1.0000
$\pi/4$ DQPSK	2.0	1.5849	0	0.0003	1.0000
8DPSK	2.0	1.5849	0	0.0003	1.0000

<BT LE>

Band/Mode	RF output power		Antenna Gain (dBi)	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW			
GFSK	3.0	1.9953	0	0.0004	1.0000

<2.4G WIFI>

Band/Mode	RF output power		Antenna Gain (dBi)	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW			
IEEE 802.11b	14.0	25.1189	0	0.0050	1.0000
IEEE 802.11g	15.0	31.6228	0	0.0063	1.0000
IEEE 802.11n HT20	15.0	31.6228	0	0.0063	1.0000
IEEE 802.11n HT40	15.0	31.6228	0	0.0063	1.0000

*Remark:*

1. Output power including tune-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer;

### 8.2 Simultaneous Transmission MPE

### 9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

.....THE END OF REPORT.....