

FCC REPORT

(WIFI)

Applicant: SUZHOU INDUSTRIAL PARK DUBU ELECTRONIC CO. Ltd

Address of Applicant: Room10-04, Building 3, Suzhou Haobainian International Commercial Plaza, Gusu District, Suzhou City

Equipment Under Test (EUT)

Product Name: JUNCO NBOOK

Model No.: NB-YWS-I501

FCC ID: 2AXC9N253

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of sample receipt: 03 Jul., 2020

Date of Test: 04 Jul., to 28 Jul., 2020

Date of report issued: 25 Aug., 2020

Test Result: PASS*

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	31 Jul., 2020	Original
01	25 Aug., 2020	Update FCC ID.

Tested by:

Mike OU
Test Engineer

Date:

25 Aug., 2020

Reviewed by:

Winner Zhang
Project Engineer

Date:

25 Aug., 2020

3 Contents

Page

1	COVER PAGE	1
2	VERSION	2
3	CONTENTS	3
4	TEST SUMMARY	4
5	GENERAL INFORMATION	5
5.1	CLIENT INFORMATION	5
5.2	GENERAL DESCRIPTION OF E.U.T	5
5.3	TEST ENVIRONMENT AND MODE, AND TEST SAMPLES PLANS	6
5.4	DESCRIPTION OF SUPPORT UNITS	6
5.5	MEASUREMENT UNCERTAINTY	6
5.6	ADDITIONS TO, DEVIATIONS, OR EXCLUSIONS FROM THE METHOD	6
5.7	LABORATORY FACILITY	6
5.8	LABORATORY LOCATION	6
5.9	TEST INSTRUMENTS LIST	7
6	TEST RESULTS AND MEASUREMENT DATA	8
6.1	ANTENNA REQUIREMENT	8
6.2	CONDUCTED EMISSION	9
6.3	CONDUCTED OUTPUT POWER	12
6.4	OCCUPY BANDWIDTH	17
6.5	POWER SPECTRAL DENSITY	26
6.6	BAND EDGE	31
6.6.1	Conducted Emission Method	31
6.6.2	Radiated Emission Method	36
6.7	SPURIOUS EMISSION	69
6.7.1	Conducted Emission Method	69
6.7.2	Radiated Emission Method	74
7	TEST SETUP PHOTO	86
8	EUT CONSTRUCTIONAL DETAILS	87

4 Test Summary

Test Items	Section in CFR 47	Result
Antenna requirement	15.203 & 15.247 (b)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(3)	Pass
6dB Emission Bandwidth 99% Occupied Bandwidth	15.247 (a)(2)	Pass
Power Spectral Density	15.247 (e)	Pass
Band Edge	15.247 (d)	Pass
Spurious Emission	15.205 & 15.209	Pass
Remark: 1. Pass: The EUT complies with the essential requirements in the standard. 2. N/A: Not Applicable. 3. The cable insertion loss used by "RF Output Power" and other conduction measurement items is 0.5dB (provided by the customer).		
Test Method:	ANSI C63.4-2014 ANSI C63.10-2013 KDB 558074 D01 15.247 Meas Guidance v05r02	

5 General Information

5.1 Client Information

Applicant:	SUZHOU INDUSTRIAL PARK DUBU ELECTRONIC CO. Ltd
Address:	Room10-04, Building 3, Suzhou Haobainian International Commercial Plaza, Gusu District, Suzhou City

5.2 General Description of E.U.T.

Product Name:	JUNCO NBOOK
Model No.:	NB-YWS-I501
Operation Frequency:	2412MHz~2462MHz (802.11b/802.11g/802.11n(HT20)) 2422MHz~2452MHz (802.11n(HT40))
Channel numbers:	11 for 802.11b/802.11g/802.11(HT20) 7 for 802.11n(HT40)
Channel separation:	5MHz
Modulation technology: (IEEE 802.11b)	Direct Sequence Spread Spectrum (DSSS)
Modulation technology: (IEEE 802.11g/802.11n)	Orthogonal Frequency Division Multiplexing(OFDM)
Data speed (IEEE 802.11b):	1Mbps, 2Mbps, 5.5Mbps, 11Mbps
Data speed (IEEE 802.11g):	6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps
Data speed (IEEE 802.11n):	Up to 150Mbps
Antenna Type:	Internal Antenna
Antenna gain:	3.0dBi
Power supply:	Rechargeable Li-ion Battery DC11.55V-4800mAh
AC adapter:	Model: ADS-65HI-19A-3 19065E Input: AC100-240V, 50/60Hz, 1.5A Output: DC 19.0V, 3.42A
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

Operation Frequency each of channel for 802.11b/g/n(HT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		
Note: 1. For 802.11n-HT40 mode, the channel number is from 3 to 9; 2. Channel 1, 6 & 11 selected for 802.11b/g/n-HT20 as Lowest, Middle and Highest channel. Channel 3, 6 & 9 selected for 802.11n-HT40 as Lowest, Middle and Highest Channel.							

5.3 Test environment and mode, and test samples plans

Operating Environment:	
Temperature:	24.0 °C
Humidity:	54 % RH
Atmospheric Pressure:	1010 mbar
Test mode:	
Transmitting mode	Keep the EUT in continuous transmitting with modulation
Radiated Emission: The sample was placed 0.8m (below 1GHz)/1.5m (above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:	
Per-scan all kind of data rate, the follow list were the worst case.	
Mode	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(HT20)	6.5Mbps
802.11n(HT40)	13.5Mbps

5.4 Description of Support Units

The EUT has been tested as an independent unit.

5.5 Measurement Uncertainty

Parameters	Expanded Uncertainty
Conducted Emission (9kHz ~ 30MHz)	±1.60 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	±3.12 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	±4.32 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	±5.16 dB (k=2)
Radiated Emission (18GHz ~ 40GHz)	±3.20 dB (k=2)

5.6 Additions to, deviations, or exclusions from the method

No

5.7 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Designation No.: CN1211**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

5.8 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.
 Address: No.110~116, Building B, Jinyuan Business Building, Xixiang Road,
 Bao'an District, Shenzhen, Guangdong, China
 Tel: +86-755-23118282, Fax: +86-755-23116366
 Email: info@ccis-cb.com, Website: <http://www.ccis-cb.com>


5.9 Test Instruments list

Radiated Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	SAEMC	9m*6m*6m	966	07-22-2017	07-21-2020
				07-22-2020	07-21-2021
Loop Antenna	SCHWARZBECK	FMZB1519B	044	03-07-2020	03-06-2021
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	03-07-2020	03-06-2021
Horn Antenna	SCHWARZBECK	BBHA9120D	916	03-07-2020	03-06-2021
Horn Antenna	SCHWARZBECK	BBHA9120D	1805	06-22-2017	06-21-2020
				06-22-2020	06-21-2021
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170582	11-18-2019	11-17-2020
EMI Test Software	AUDIX	E3	Version: 6.110919b		
Pre-amplifier	HP	8447D	2944A09358	03-07-2020	03-06-2021
Pre-amplifier	CD	PAP-1G18	11804	03-07-2020	03-06-2021
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-05-2020	03-04-2021
Spectrum analyzer	Rohde & Schwarz	FSP40	100363	11-18-2019	11-17-2020
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-05-2020	03-04-2021
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-07-2020	03-06-2021
Cable	MICRO-COAX	MFR64639	K10742-5	03-07-2020	03-06-2021
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-07-2020	03-06-2021
RF Switch Unit	MWRFTTEST	MW200	N/A	N/A	N/A
Test Software	MWRFTTEST	MTS8200	Version: 2.0.0.0		

Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESCI	101189	03-05-2020	03-04-2021
Pulse Limiter	SCHWARZBECK	OSRAM 2306	9731	03-05-2020	03-04-2021
LISN	CHASE	MN2050D	1447	03-05-2020	03-04-2021
LISN	Rohde & Schwarz	ESH3-Z5	8438621/010	07-21-2017	07-20-2020
				07-21-2020	07-20-2021
Cable	HP	10503A	N/A	03-05-2020	03-04-2021
EMI Test Software	AUDIX	E3	Version: 6.110919b		

6 Test results and Measurement Data

6.1 Antenna requirement


Standard requirement:	FCC Part 15 C Section 15.203 /247(b)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
E.U.T Antenna:	
The Wi-Fi antenna is an Internal antenna which cannot replace by end-user, the best case gain of the antenna is 3.0 dBi.	
	

6.2 Conducted Emission

Test Requirement:	FCC Part 15 C Section 15.207		
Test Frequency Range:	150 kHz to 30 MHz		
Class / Severity:	Class B		
Receiver setup:	RBW=9 kHz, VBW=30 kHz		
Limit:	Frequency range (MHz)	Limit (dBUV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
	* Decreases with the logarithm of the frequency.		
Test procedure	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.), which provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10(latest version) on conducted measurement.		
Test setup:	 Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m		
Test Instruments:	Refer to section 5.9 for details		
Test mode:	Refer to section 5.3 for details		
Test results:	Passed		

Measurement Data:

Product name:	JUNCO NBOOK	Product model:	NB-YWS-I501
Test by:	Mike	Test mode:	Wi-Fi Tx mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Humi: 55%




	Freq	Read Level	LISN Factor	Cable Loss	Aux Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.150	39.44	-0.57	10.78	-0.05	49.60	66.00	-16.40	QP
2	0.150	23.73	-0.57	10.78	-0.05	33.89	56.00	-22.11	Average
3	0.158	23.05	-0.57	10.77	-0.07	33.18	55.56	-22.38	Average
4	0.162	38.53	-0.58	10.77	-0.08	48.64	65.34	-16.70	QP
5	0.174	36.53	-0.58	10.77	-0.11	46.61	64.77	-18.16	QP
6	0.182	35.45	-0.58	10.77	-0.12	45.52	64.42	-18.90	QP
7	0.194	35.36	-0.59	10.76	-0.15	45.38	63.84	-18.46	QP
8	0.343	20.56	-0.52	10.73	0.06	30.83	49.13	-18.30	Average
9	0.369	23.83	-0.50	10.73	0.23	34.29	48.52	-14.23	Average
10	0.385	28.71	-0.49	10.72	0.33	39.27	58.17	-18.90	QP
11	0.393	22.67	-0.48	10.72	0.38	33.29	47.99	-14.70	Average
12	0.417	17.22	-0.47	10.73	0.28	27.76	47.51	-19.75	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Aux Factor + Cable Loss.

Product name:	JUNCO NBOOK	Product model:	NB-YWS-I501
Test by:	Mike	Test mode:	Wi-Fi Tx mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Humi: 55%




	Freq	Read Level	LISN Factor	Cable Loss	Aux Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.150	44.32	-0.69	10.78	0.01	54.42	66.00	-11.58	QP
2	0.150	29.17	-0.69	10.78	0.01	39.27	56.00	-16.73	Average
3	0.159	42.49	-0.69	10.77	0.01	52.58	65.52	-12.94	QP
4	0.182	41.96	-0.68	10.77	0.00	52.05	64.42	-12.37	QP
5	0.182	25.97	-0.68	10.77	0.00	36.06	54.42	-18.36	Average
6	0.214	37.80	-0.67	10.76	0.00	47.89	63.05	-15.16	QP
7	0.234	35.71	-0.67	10.75	0.00	45.79	62.30	-16.51	QP
8	0.369	25.86	-0.64	10.73	-0.04	35.91	48.52	-12.61	Average
9	0.385	30.45	-0.64	10.72	-0.05	40.48	58.17	-17.69	QP
10	0.393	25.50	-0.63	10.72	-0.06	35.53	47.99	-12.46	Average
11	0.683	15.26	-0.64	10.77	0.04	25.43	46.00	-20.57	Average
12	1.094	14.94	-0.68	10.88	0.09	25.23	46.00	-20.77	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Aux Factor + Cable Loss.

6.3 Conducted Output Power

Test Requirement:	FCC Part 15 C Section 15.247 (b)(3)
Limit:	30dBm
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:

ANT1


Test CH	Maximum Conducted Output Power (dBm)				Limit(dBm)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	15.75	14.49	13.60	12.37	30.00	Pass
Middle	15.79	14.68	13.29	12.26		
Highest	16.43	15.44	13.84	12.82		

ANT2


Test CH	Maximum Conducted Output Power (dBm)				Limit(dBm)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	15.48	14.57	13.67	12.30	30.00	Pass
Middle	15.36	14.36	13.34	12.38		
Highest	15.41	14.43	13.36	12.36		

Test plot as follows:

ANT1




802.11n(HT20)




Date: 14.JUL.2020 13:51:46

802.11n(HT40)




Date: 14.JUL.2020 13:53:27

Lowest channel




Date: 14.JUL.2020 13:51:57

Lowest channel




Date: 14.JUL.2020 13:53:39

Middle channel



Date: 14.JUL.2020 13:52:13

Middle channel




Date: 14.JUL.2020 13:53:54

Highest channel

Highest channel


ANT2

802.11b




Date: 14.JUL.2020 18:38:18

802.11g




Date: 14.JUL.2020 18:39:35

Lowest channel




Date: 14.JUL.2020 18:38:45

Lowest channel




Date: 14.JUL.2020 18:39:23

Middle channel



Date: 14.JUL.2020 18:38:59

Middle channel




Date: 14.JUL.2020 18:39:12

Highest channel


Highest channel

802.11n(HT20)




Date: 14.JUL.2020 18:39:47

802.11n(HT40)




Date: 14.JUL.2020 18:40:39

Lowest channel




Date: 14.JUL.2020 18:39:58

Lowest channel




Date: 14.JUL.2020 18:40:52

Middle channel



Date: 14.JUL.2020 18:40:09

Middle channel




Date: 14.JUL.2020 18:41:03

Highest channel

Highest channel

6.4 Occupy Bandwidth

Test Requirement:	FCC Part 15 C Section 15.247 (a)(2)
Limit:	>500kHz
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:

ANT1:


Test CH	6dB Emission Bandwidth (MHz)				Limit(kHz)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	9.36	15.36	15.36	35.52	>500	Pass
Middle	9.36	15.28	15.28	35.52		
Highest	9.28	15.28	15.28	35.52		
Test CH	99% Occupy Bandwidth (MHz)				Limit(kHz)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	12.56	16.80	17.84	36.32	N/A	N/A
Middle	12.40	16.80	17.84	36.32		
Highest	12.48	16.72	17.84	36.32		

ANT2:

Test CH	6dB Emission Bandwidth (MHz)				Limit(kHz)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	9.36	15.36	15.36	35.52	>500	Pass
Middle	9.28	15.28	15.28	35.52		
Highest	9.28	15.52	15.36	35.52		
Test CH	99% Occupy Bandwidth (MHz)				Limit(kHz)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	13.12	16.96	18.00	36.32	N/A	N/A
Middle	12.88	16.80	17.92	36.32		
Highest	12.72	16.72	17.92	36.32		


ANT1:

Test plot as follows:




802.11g

6dB EBW




Date: 14.JUL.2020 14:01:47

99% OBW




Date: 14.JUL.2020 13:55:44

Lowest channel




Date: 14.JUL.2020 14:02:31

Lowest channel




Date: 14.JUL.2020 13:55:34

Middle channel



Date: 14.JUL.2020 14:03:06

Middle channel




Date: 14.JUL.2020 13:55:23

Highest channel

Highest channel


802.11n(HT20)

6dB EBW




Date: 14.JUL.2020 14:05:31

99% OBW




Date: 14.JUL.2020 13:54:50

Lowest channel




Date: 14.JUL.2020 14:04:52

Lowest channel




Date: 14.JUL.2020 13:55:00

Middle channel



Date: 14.JUL.2020 14:03:52

Middle channel




Date: 14.JUL.2020 13:55:11

Highest channel

Highest channel


802.11n(HT40)

6dB EBW




Date: 14.JUL.2020 14:06:19

99% OBW




Date: 14.JUL.2020 13:54:29

Lowest channel




Date: 14.JUL.2020 14:07:07

Lowest channel




Date: 14.JUL.2020 13:54:19

Middle channel



Date: 14.JUL.2020 14:07:54

Middle channel




Date: 14.JUL.2020 13:54:08

Highest channel

Highest channel


ANT2:

Test plot as follows:




802.11g

6dB EBW




Date: 14.JUL.2020 18:55:51

99% OBW




Date: 14.JUL.2020 18:42:57

Lowest channel




Date: 14.JUL.2020 18:56:57

Lowest channel




Date: 14.JUL.2020 18:42:49

Middle channel



Date: 14.JUL.2020 19:00:37

Middle channel




Date: 14.JUL.2020 18:42:33

Highest channel


Highest channel

802.11n(HT20)


6dB EBW




99% OBW




Lowest channel




Lowest channel



Middle channel



Middle channel




Highest channel

Highest channel


802.11n(HT40)

6dB EBW




Date: 14.JUL.2020 19:07:12

99% OBW




Date: 14.JUL.2020 18:41:43

Lowest channel




Date: 14.JUL.2020 19:08:06

Lowest channel




Date: 14.JUL.2020 18:41:31

Middle channel



Date: 14.JUL.2020 19:09:01

Middle channel




Date: 14.JUL.2020 18:41:16

Highest channel

Highest channel

6.5 Power Spectral Density

Test Requirement:	FCC Part 15 C Section 15.247 (e)
Limit:	8dBm/3kHz
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:

ANT1:


Test CH	Power Spectral Density (dBm/3kHz)				Limit (dBm/3kHz)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	-9.67	-13.19	-13.49	-17.44	8.00	Pass
Middle	-9.35	-13.01	-13.70	-17.00		
Highest	-7.93	-11.37	-12.28	-16.90		

ANT2:


Test CH	Power Spectral Density (dBm/3kHz)				Limit (dBm/3kHz)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	-10.14	-11.99	-13.42	-18.06	8.00	Pass
Middle	-9.24	-12.81	-12.92	-17.56		
Highest	-9.31	-12.11	-13.61	-15.81		

Test plot as follows:

ANT1:




Test mode: 802.11n(HT20)




Date: 14.JUL.2020 14:09:17

Test mode: 802.11n(HT40)




Date: 14.JUL.2020 14:09:00

Lowest channel




Date: 14.JUL.2020 14:09:31

Lowest channel




Date: 14.JUL.2020 14:08:44

Middle channel



Date: 14.JUL.2020 14:09:54

Middle channel




Date: 14.JUL.2020 14:08:25

Highest channel

Highest channel


ANT2:

Test mode: 802.11b




Date: 14.JUL.2020 20:06:41

Lowest channel



Date: 14.JUL.2020 20:06:56


Middle channel



Date: 14.JUL.2020 20:07:10


Highest channel

Test mode: 802.11g




Date: 14.JUL.2020 20:07:54

Lowest channel




Date: 14.JUL.2020 20:07:41

Middle channel




Date: 14.JUL.2020 20:07:25

Highest channel




Date: 14.JUL.2020 20:08:18




Date: 14.JUL.2020 20:09:17

Lowest channel




Date: 14.JUL.2020 20:08:32

Lowest channel




Date: 14.JUL.2020 20:09:33

Middle channel



Date: 14.JUL.2020 20:08:57

Middle channel




Date: 14.JUL.2020 20:09:58

Highest channel

Highest channel


6.6 Band Edge

6.6.1 Conducted Emission Method


Test Requirement:	FCC Part 15 C Section 15.247 (d)
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. The table is supported by two vertical legs and sits on a Ground Reference Plane.
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Test plot as follows:

ANT1:




802.11n(HT20)



Date: 14.JUL.2020 16:08:24


Lowest channel



Date: 14.JUL.2020 16:04:22


Highest channel

802.11n(HT40)



Date: 14.JUL.2020 16:06:58

Lowest channel




Date: 14.JUL.2020 16:06:10

Highest channel


ANT2:

802.11b



Date: 14.JUL.2020 20:06:18


Lowest channel



Date: 14.JUL.2020 19:53:34


Highest channel

802.11g



Date: 14.JUL.2020 20:05:40


Lowest channel



Date: 14.JUL.2020 19:54:18


Highest channel

802.11n(HT20)



Date: 14.JUL.2020 20:04:31


Lowest channel



Date: 14.JUL.2020 19:55:13


Highest channel

802.11n(HT40)



Date: 14.JUL.2020 19:58:58


Lowest channel



Date: 14.JUL.2020 19:56:28

Highest channel


6.6.2 Radiated Emission Method

Test Requirement:	FCC Part 15 C Section 15.209 and 15.205				
Test Frequency Range:	2310 MHz to 2390 MHz and 2483.5 MHz to 2500 MHz				
Test Distance:	3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		RMS	1MHz	3MHz	Average Value
Limit:	Frequency	Limit (dBuV/m @3m)		Remark	
	Above 1GHz	54.00		Average Value	
		74.00		Peak Value	
Test Procedure:	1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.				
Test setup:					
Test Instruments:	Refer to section 5.9 for details				
Test mode:	Refer to section 5.3 for details				
Test results:	Passed				

ANT1:

802.11b mode:

Product Name:	JUNCO NBOOK	Product Model:	NB-YWS-I501
Test By:	Mike	Test mode:	802.11b Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




	Freq	ReadAntenna Level Factor	Cable Loss Factor	Aux Preamp Factor Factor	Level	Limit	Over	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	23.88	27.03	4.28	1.68	0.00	56.87	74.00 -17.13 Peak
2	2390.000	15.74	27.03	4.28	1.68	0.00	48.73	54.00 -5.27 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	JUNCO NBOOK	Product Model:	NB-YWS-I501
Test By:	Mike	Test mode:	802.11b Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	21.28	27.03	4.28	1.68	0.00	54.27	74.00	-19.73	Peak
2	2390.000	13.17	27.03	4.28	1.68	0.00	46.16	54.00	-7.84	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	JUNCO NBOOK	Product Model:	NB-YWS-I501
Test By:	Mike	Test mode:	802.11b Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	20.09	27.27	4.38	1.70	0.00	53.44	74.00	-20.56	Peak
2	2483.500	12.86	27.27	4.38	1.70	0.00	46.21	54.00	-7.79	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.